

Q- Assign ports FastEthernet0/1 and FastEthernet0/2 to VLAN 10, and ports FastEthernet0/3 and FastEthernet0/4 to VLAN 20 on your switch.

```

Switch#
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#int rang fast
Switch(config)#int rang fastEthernet 0/1-2
Switch(config-if-range)#switchport mode access
Switch(config-if-range)#switchport access vlan10
Switch(config-if-range)#switchport access vlan10
Switch(config-if-range)#switchport access vlan 10
Switch(config-if-range)#exit
Switch(config)#int rang
Switch(config)#int rang fa
Switch(config)#int rang fastEthernet 0/3-4
Switch(config-if-range)#switchport mode access
Switch(config-if-range)#switchport access vlan 20
Switch(config-if-range)#exit
Switch(config)#do wr
Building configuration...
[OK]
Switch(config)#exit
Switch#
%SYS-5-CONFIG_I: Configured from console by console

Switch#show vlan brief

VLAN Name                Status    Ports
-----
1    default                active    Fa0/5, Fa0/6, Fa0/7, Fa0/8
                                           Fa0/9, Fa0/10, Fa0/11, Fa0/12
                                           Fa0/13, Fa0/14, Fa0/15, Fa0/16
                                           Fa0/17, Fa0/18, Fa0/19, Fa0/20
                                           Fa0/21, Fa0/22, Fa0/23, Fa0/24
                                           Gig0/1, Gig0/2
10   Engineering             active    Fa0/1, Fa0/2
20   Marketing               active    Fa0/3, Fa0/4
1002 fddi-default            active
1003 token-ring-default    active
1004 fddinet-default        active
1005 trnet-default         active
Switch#

```