



Cisco Packet Tracer

File Edit Options View Tools Extensions Window

Logical Physical x: 323, y: 140

Root 07:59:00

PC2

Physical Config Desktop Programming Attributes

IP Configuration

Interface FastEthernet0

IP Configuration

☐ DHCP ☒ Static

IPv4 Address 192.23.4.1

Subnet Mask 255.255.255.0

Default Gateway 192.23.4.3

DNS Server 0.0.0.0

IPv6 Configuration

☐ Automatic ☒ Static

IPv6 Address

Link Local Address FE80::201:97FF:FEE0:D1D

Default Gateway

DNS Server

802.1X

☐ Use 802.1X Security

Authentication MD5

Username

Password

☐ Top

Time: 00:16:05

Realtime Simulation

Automatically Choose Connection Type

Cisco Packet Tracer

File Edit Options View Tools Extensions Window

Logical Physical x 321, y: 311

Time: 00:11:35

PC-PT PC0

PC0

Physical Config Desktop Programming Attributes

Command Prompt

```
Cisco Packet Tracer PC Command Line 1.0
C:\>ping
Cisco Packet Tracer PC Ping

Usage: ping [-n count | -v TOS | -t ] target

C:\>ping 10.100.1.3

Pinging 10.100.1.3 with 32 bytes of data:

Request timed out.
Request timed out.
Request timed out.
Request timed out.

Ping statistics for 10.100.1.3:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\>ping 10.100.10.3

Pinging 10.100.10.3 with 32 bytes of data:

Reply from 10.100.10.3: bytes=32 time<1ms TTL=255
Reply from 10.100.10.3: bytes=32 time<1ms TTL=255
Reply from 10.100.10.3: bytes=32 time<1ms TTL=255
Reply from 10.100.10.3: bytes=32 time<1ms TTL=255

Ping statistics for 10.100.10.3:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\>10.100.10.1
Invalid Command.

C:\>
```

Top

Automatically Choose Connection Type

Root

05:42:30

Realtime Simulation