REALTY KANPUR

Apla	RCC Coeff	RCC /	Shutt Coeff	Shuttering	Steel Coeff	Steel
sqm		cum / /		sqm .		kg
4. 2 - T	<u> </u>	55	l .			1 .
60085,00	0.066	3984.54	0.26	1032.45	85 .	338685.80
		· <u>·</u>	·			
13965.00	0.070	977,55	1.00	97,7.55	80	78204.00
<u> </u>				·		
60085.00	0.238	14285.03	4	60931.68	175	2499861.06
·						
13965.DO	0.075	1047.38	800	8379 00	190	19900 1 25
24455 55	10.170		0.00			
60085.DO	0.126	7575.45	0.89	53706.25	80	606036.00
13965.00	0.440	1070.05	0.05	11070 05		450044.00
13903.00	0.142	1978.05	0.85	11870.25	80	158244.DO
60085.00	0.073	4382.43	8	34492.36	200	876485.00
	0.015	4002.40		34432.30	230	010403.00
13965.00	0.147	2047.80	7	13404.60	210	430038.00
10000.00	B. 147	2047.00	 	1 10-10-1-00	210	1
74050.00	0.004	294.08	6	1713.60	125	36760.50
			ľ	1	1.20	
74050.00	0.020	1461.00	7	10367.00	140	207340.00
]			
60085.00	0.015	918.00	1		45	41310.00
	. i			· · · · · · · · · · · · · · · · · · ·	·	
60085:D0	0.002	100.00	8	900.00	125	12500.00
	1					l .
60085.00	0.036	2180.25	<u> 16</u> -	34145.63	45	98111.32
				<u> </u>		1
74050.00	1	41251.56	· -	231820.37	· · · ·	5582596.92
					<u> </u>	
				ļ.,		
QTY	COEFF	ŲNIT				<u> </u>
E 340 529550	NA 28 27 11	aiu ai da air				1
56/65	Mr/op (c)	cum/sgm			·	
291820:37	3.13		 	 	 	
Zġ 10ZU.01	3.13	sqm/sqm				ļ.
EEGSEDE OS	75:39	kalaam		-		
5582596.92	110.00	kg/sqm.	.l	I	1	1

AREA CONSIDERED						
·		Tower	Noi			
basement 2	6015	1425				
basement 1	6150	1425				
ground floor	6075	1425				
court	370	370				
business centre	565	565				
club	1365	1365	Г			
1st floor .	1565	1565				
2nd floor	1500	1500				
for 29 floors	43500	43500	I			
refuse floor	1500	150D				
33rd floor lower penthouse	1585	1585				
34th floor upper penthouse	1245	1245				
terrace .	1500	1500				
upper terrace	1015	_ 1015				
Murnty/oht	10D	: 100				
	74050	60085				

₩ 050.0 ₩ .	7(1)	kg/sft*				-
 				<u> </u>	· -	-
173653.81	kg.					- -
mpers is taken	in consider	ration while	e salcullațin	g the steel.		

.

.

.

.

.

•

.

.

.

•

.

· .

.

.

· · · ·

.

.