

so the formula of perceptron trick

In ML literature, “perceptron trick” usually means the *kernelized perceptron* (analogous to the kernel trick in SVMs).

Below are the **exact formulas**, clean and mathematical.

## 1. Standard Perceptron (Primal Form)

Model

$$\hat{y} = \text{sign}(w^\top x + b)$$

Update rule (for a misclassified point  $(x_i, y_i)$ ,  $y_i \in \{-1, +1\}$ )

$$\text{if } y_i(w^\top x_i + b) \leq 0 : \quad \begin{cases} w \leftarrow w + \eta y_i x_i \\ b \leftarrow b + \eta y_i \end{cases}$$

## 2. Dual Representation of Perceptron

Initialize  $\alpha_i = 0 \ \forall i$

$$w = \sum_{i=1}^n \alpha_i y_i x_i$$

Decision function

$$f(x) = \sum_{i=1}^n \alpha_i y_i (x_i^\top x) + b$$

Update

$$\text{if } y_i f(x_i) \leq 0 : \quad \alpha_i \leftarrow \alpha_i + \eta$$

## 3. Perceptron Trick (Kernelized Perceptron)

Key substitution (the “trick”)

$$x_i^\top x \Rightarrow K(x_i, x)$$

where

$$K(x_i, x) = \phi(x_i)^\top \phi(x)$$

Kernelized Decision Function

$$f(x) = \sum_{i=1}^n \alpha_i y_i K(x_i, x) + b$$

Kernelized Update Rule

$$\text{if } y_i f(x_i) \leq 0 : \quad \alpha_i \leftarrow \alpha_i + \eta$$

(no explicit  $w$ , no explicit  $\phi(x)$ )

## 4. Common Kernels Used in Perceptron Trick

- Linear

$$K(x, z) = x^\top z$$

- Polynomial

$$K(x, z) = (x^\top z + c)^d$$

- RBF (Gaussian)

$$K(x, z) = \exp\left(-\frac{\|x - z\|^2}{2\sigma^2}\right)$$

## 5. Final Compact Formula (What You Should Remember)

$$f(x) = \sum_{i \in \mathcal{M}} \alpha_i y_i K(x_i, x) + b$$

where

$\mathcal{M}$  = indices of misclassified samples (support vectors of perceptron).

If you want next:

- full mathematical derivation (primal  $\rightarrow$  dual  $\rightarrow$  kernel)
- comparison with SVM kernel trick
- why perceptron has no closed-form solution

tell me which one.

📄 📌 🔍 ⬆️ ↺ ...



look these equations and tell me what they are

I carefully looked at your handwritten page.

Those equations are all variants of the *Perceptron learning rule* written in different equivalent forms.

I'll map each part of your notes  $\rightarrow$  its exact mathematical meaning, no fluff.

### 1. $\sum w_i x_i \geq 0$ and $\sum w_i x_i < 0$

These are decision conditions of the perceptron.

You are using labels:

$$y \in \{+1, -1\}$$

Decision rule:

$$\hat{y} = \begin{cases} +1 & \text{if } \sum_i w_i x_i \geq 0 \\ -1 & \text{if } \sum_i w_i x_i < 0 \end{cases}$$

This is equivalent to:

$$\hat{y} = \text{sign}(w^\top x)$$

### 2. $w_{n+1} = w_0 + \eta x_i$

This is the perceptron weight update for a positive class error.

Written properly:

$$\text{If } y_i = +1 \text{ and misclassified: } w \leftarrow w + \eta x_i$$

This comes from the general rule:

$$w \leftarrow w + \eta y_i x_i$$

with  $y_i = +1$ .

### 3. $w_{n+1} = w_0 - \eta x_i$

This is the perceptron weight update for a negative class error.

$$\text{If } y_i = -1 \text{ and misclassified: } w \leftarrow w - \eta x_i$$

Again from:

$$w \leftarrow w + \eta y_i x_i$$

with  $y_i = -1$ .

## 4. Boxed Formula

$$w_n = w_0 + \eta (y_i - \hat{y}_i) x_i$$

This is a generalized perceptron update, often seen when perceptron is written in a regression-like form.

- $y_i$  = true label
- $\hat{y}_i$  = predicted label
- $(y_i - \hat{y}_i) \in \{-2, 0, +2\}$

Interpretation:

- If prediction is correct  $\rightarrow$  update = 0
- If wrong  $\rightarrow$  pushes weights in the correct direction

This is mathematically equivalent to:

$$w \leftarrow w + \eta y_i x_i$$

for misclassified points.

## 5. The “Perceptron Trick” Arrow

When you wrote “perceptron trick”, what it refers to is:

$$w = \sum_{i \in \mathcal{M}} \alpha_i y_i x_i$$

and later:

$$x_i^\top x \Rightarrow K(x_i, x)$$

That leads to the kernelized perceptron:

$$f(x) = \sum_i \alpha_i y_i K(x_i, x)$$

## 6. Final Classification of What You Wrote

Expression in notebook

What it is

$$\sum w_i x_i \geq 0$$

Perceptron decision boundary

$$w + \eta x$$

Update for misclassified positive sample

Expression in notebook	What it is
$w \leftarrow w - \eta x$	Update for misclassified negative sample
$w = w + \eta(y - \hat{y})x$	Unified perceptron update
"perceptron trick"	Dual + kernel formulation

### One-line summary (important)


Your page is 100% correct — it shows the same perceptron algorithm written in multiple equivalent mathematical forms:

decision rule → class-specific updates → unified update → kernel-ready formulation.

If you want next:

- strict primal → dual derivation
- difference between perceptron update and SGD
- why logistic regression replaces perceptron

tell me which one.



what i gave what exactly that is

What you gave is one single algorithm written in multiple equivalent mathematical forms.

Exact answer (no ambiguity):

You gave the *Perceptron Learning Algorithm* — specifically the *online / mistake-driven binary linear classifier*.

More precisely, your page contains these exact components:

1. Linear decision function

$$f(x) = \sum_i w_i x_i \quad (\text{sign decides the class})$$

2. Binary classification rule

$$\hat{y} = \text{sign}(w^\top x)$$

3. Mistake-driven update

update only if  $y_i \neq \hat{y}_i$

4. Class-dependent updates

$$\begin{aligned} y = +1 : w &\leftarrow w + \eta x \\ y = -1 : w &\leftarrow w - \eta x \end{aligned}$$

5. Unified update rule

$$w \leftarrow w + \eta(y_i - \hat{y}_i)x_i$$

What it is NOT

- ❌ Not logistic regression
- ❌ Not SVM

- ❌ Not gradient descent on a smooth loss
- ❌ Not backpropagation

### Proper textbook name

Depending on context, it is called:

- Perceptron Learning Rule
- Rosenblatt's Perceptron (1958)
- Online linear classifier
- Mistake-driven update rule
- Primal perceptron

### One-line identity (remember this)

Your notes = classical perceptron algorithm in primal form

If you want, next I can:

- rewrite it in **pure optimization form**
- show **why no loss function exists**
- convert it into **logistic regression mathematically**
- connect it to **SGD formally**

Just say which.

📄 👍 🗨️ ⬆️ ↺ ...

rewrite it in pure optimization form

show why no loss function exists

convert it into logistic regression mathematically

Below is exactly what you asked, in **three clean mathematical blocks**, with **no intuition**, **no storytelling** — only formal math.

## I. Perceptron in Pure Optimization Form

### Problem Setup

$$\mathcal{D} = \{(x_i, y_i)\}_{i=1}^n, \quad x_i \in \mathbb{R}^d, \quad y_i \in \{-1, +1\}$$

### Hard Classification Constraint

$$y_i(w^\top x_i) > 0 \quad \forall i$$

### Feasibility Optimization (Perceptron View)

The perceptron is **not** solving a minimization of a smooth objective.

It solves a **constraint satisfaction problem**:

$$\text{Find } w \in \mathbb{R}^d \quad \text{s.t.} \quad y_i w^\top x_i \geq 0 \quad \forall i$$

This is a **feasibility problem**, not a minimization.

## Algorithmic Projection Form

Define violation indicator:

$$\mathbb{I}_i(w) = \begin{cases} 1 & \text{if } y_i w^\top x_i \leq 0 \\ 0 & \text{otherwise} \end{cases}$$

Perceptron update:

$$w_{t+1} = w_t + \eta y_i x_i \quad \text{if } \mathbb{I}_i(w_t) = 1$$

This is a **projected correction**, not gradient descent.

---

## II. Why No Proper Loss Function Exists (Formally)

Assume there exists a differentiable loss  $L(w)$  such that:

$$w_{t+1} = w_t - \eta \nabla L(w_t)$$

But perceptron update is:

$$\Delta w = \begin{cases} \eta y_i x_i & \text{if } y_i w^\top x_i \leq 0 \\ 0 & \text{otherwise} \end{cases}$$

This implies:

$$\nabla L(w) = \begin{cases} -y_i x_i & \text{if } y_i w^\top x_i \leq 0 \\ 0 & \text{otherwise} \end{cases}$$

### Contradiction

- Gradient is **discontinuous**
  - Gradient does **not depend smoothly on  $w$**
  - No scalar  $L(w)$  exists whose gradient jumps discretely
- 

### Formal Statement

Perceptron update is not the gradient of any continuous, convex loss

It is **rule-based**, not variational.

---

### (Closest Surrogate — Not True Loss)

The *perceptron loss*:

$$\ell_{\text{perc}}(w; x, y) = \max(0, -yw^\top x)$$

is **non-differentiable** and does **not produce the classical update** exactly.

---

## III. Converting Perceptron → Logistic Regression (Mathematically)

### Step 1: Replace Hard Constraint with Soft Margin

Perceptron:

$$yw^\top x \geq 0$$

Logistic:

$$P(y|x) = \sigma(yw^\top x)$$

where

$$\sigma(z) = \frac{1}{1 + e^{-z}}$$

## Step 2: Likelihood Formulation

$$\mathcal{L}(w) = \prod_{i=1}^n \sigma(y_i w^\top x_i)$$

Negative log-likelihood:

$$J(w) = \sum_{i=1}^n \log(1 + e^{-y_i w^\top x_i})$$

This is the logistic loss.

## Step 3: Gradient of Logistic Loss

$$\nabla J(w) = - \sum_{i=1}^n \frac{y_i x_i}{1 + e^{y_i w^\top x_i}}$$

## Step 4: SGD Update Rule

$$w_{t+1} = w_t + \eta \frac{y_i x_i}{1 + e^{y_i w_t^\top x_i}}$$

## Step 5: Limit Relation (Perceptron as Extreme Case)

As:

$$\|w^\top x\| \rightarrow \infty$$

$$\frac{1}{1 + e^{y w^\top x}} \rightarrow \begin{cases} 1 & y w^\top x \leq 0 \\ 0 & y w^\top x > 0 \end{cases}$$

Therefore:

$$\text{Perceptron} = \lim_{\text{hard margin}} \text{Logistic Regression}$$

## Final Compact Summary

Perceptron : constraint satisfaction, no smooth loss  
 Logistic Reg. : maximum likelihood, convex loss  
 Connection : hard-margin limit of logistic

If you want next (pure math options only):

- hinge loss  $\rightarrow$  SVM derivation
- perceptron convergence theorem (formal proof)
- dual + kernel logistic vs kernel perceptron

Say which.



than from here how binary cross entropy comes in the picture

Below is the strict mathematical chain from logistic regression → binary cross-entropy, with no intuition, no narrative.

## 1. Model Assumption (Logistic Regression)

Binary labels:

$$y_i \in \{0, 1\}$$

Linear score:

$$z_i = w^\top x_i$$

Sigmoid:

$$p_i = P(y_i = 1 \mid x_i) = \sigma(z_i) = \frac{1}{1 + e^{-z_i}}$$

## 2. Bernoulli Likelihood

$$P(y_i \mid x_i, w) = p_i^{y_i} (1 - p_i)^{1-y_i}$$

Joint likelihood:

$$\mathcal{L}(w) = \prod_{i=1}^n p_i^{y_i} (1 - p_i)^{1-y_i}$$

## 3. Negative Log-Likelihood

$$\begin{aligned} J(w) &= -\log \mathcal{L}(w) \\ &= -\sum_{i=1}^n [y_i \log p_i + (1 - y_i) \log(1 - p_i)] \end{aligned}$$

## 4. Binary Cross-Entropy (Exact Identity)

$$\boxed{\mathcal{L}_{\text{BCE}}(y, p) = -[y \log p + (1 - y) \log(1 - p)]}$$

Thus:

$$\boxed{\text{Logistic Regression Loss} \equiv \text{Binary Cross-Entropy}}$$

## 5. Alternative Label Encoding Equivalence

If

$$y_i \in \{-1, +1\}$$

Then:

$$J(w) = \sum_{i=1}^n \log(1 + e^{-y_i w^\top x_i})$$

which is algebraically equivalent to BCE under the mapping:

$$y_{0/1} = \frac{y_{-1/+1} + 1}{2}$$



## 6. Gradient (Explicit)

$$\nabla_w J(w) = \sum_{i=1}^n (p_i - y_i) x_i$$

SGD form:

$$w \leftarrow w + \eta(y_i - p_i)x_i$$

## 7. Position in the Full Chain

Perceptron  $\xrightarrow{\text{softening}}$  Logistic Regression  $\xrightarrow{\text{Bernoulli MLE}}$  Binary Cross-Entropy

## Final Identity (Key Line)

Binary Cross-Entropy is the negative log-likelihood of a Bernoulli model

If you want next (still pure math):

- multiclass  $\rightarrow$  softmax cross-entropy
- BCE vs hinge loss vs exponential loss (formal relations)
- why MSE fails for classification (Hessian analysis)

Say which.

📄 🍷 🔍 ↺ ...

why Bernoulli likelihood over likelihood formulation , like i am thinking why , is there any problem with likelihood so that we chosen Bernoulli likelihood

This is a **fundamental modeling question**, so I'll answer it **formally**, step-by-step, with **only mathematical and statistical necessity** — no storytelling.

## 1. What “likelihood” actually means (formal)

A likelihood is not chosen arbitrarily.

$$\mathcal{L}(w) = P(\mathcal{D} \mid w)$$

To write  $P(y \mid x, w)$ , you must specify a **conditional probability distribution** for  $y$ .

So the real question is:

What is the correct conditional distribution of a binary random variable  $y$ ?

## 2. Nature of the target variable

$$y \in \{0, 1\}$$

Therefore:

$y$  is a Bernoulli random variable

By probability theory:

The only valid distribution for a single binary outcome is Bernoulli

### 3. Bernoulli distribution (definition)

$$P(y \mid p) = p^y (1 - p)^{1-y}$$

This is not a modeling choice — it is a measure-theoretic fact.

### 4. Why not “generic likelihood”?

A likelihood must integrate (or sum) to 1 over the sample space.

For binary  $y$ :

$$\sum_{y \in \{0,1\}} P(y \mid x, w) = 1$$

Any function  $f(w^\top x)$  that does not satisfy:

$$0 \leq f \leq 1$$

is invalid as a probability model.

### 5. Why sigmoid appears (forced, not optional)

We need:

$$p = P(y = 1 \mid x, w) \quad \text{s.t.} \quad 0 \leq p \leq 1$$

Sigmoid:

$$\sigma(z) = \frac{1}{1 + e^{-z}}$$

Properties:

$$\sigma : \mathbb{R} \rightarrow (0, 1)$$

Thus:

$$p = \sigma(w^\top x) \text{ is the simplest valid parametrization}$$

### 6. Why NOT Gaussian likelihood (formal failure)

Assume:

$$y \mid x \sim \mathcal{N}(w^\top x, \sigma^2)$$

Problems:

1. Support mismatch:

$$y \in \{0, 1\}, \quad \mathcal{N} \text{ has support } \mathbb{R}$$

2. Invalid probabilities:

$$P(y = 1 \mid x) > 1 \text{ or } < 0$$

3. Leads to MSE loss:

$$(y - w^\top x)^2$$

This is statistically inconsistent for binary data.

### 7. Why Bernoulli is uniquely correct

Requirement	Bernoulli
Binary support	✓
Proper probability mass	✓
Normalized	✓
Leads to convex loss	✓
Consistent estimator	✓

No other distribution satisfies all simultaneously.

## 8. Connection to cross-entropy (inevitable)

Negative log-likelihood:

$$-\log P(y | p) = -y \log p - (1 - y) \log(1 - p)$$

This is exactly the cross-entropy:

$$H(y, p)$$

Thus:

Binary Cross-Entropy is not chosen — it is forced

## 9. Formal conclusion

Binary labels  $\Rightarrow$  Bernoulli RV  
 Bernoulli RV  $\Rightarrow$  Bernoulli likelihood  
 Bernoulli likelihood  $\Rightarrow$  Binary Cross-Entropy

## One-line answer to your question

We do not choose Bernoulli likelihood because likelihood is “bad”; we choose it because binary data mathematically *admits no other valid probability model*.

If you want next (still formal):

- why exponential family  $\Rightarrow$  GLM  $\Rightarrow$  logistic
- Fisher consistency proof for BCE
- classification-calibrated losses theorem
- hinge vs BCE from decision theory

Say which.

📄 🍌 🗨️ ↻ …

show step by step how we approached the binary cross entropy that is based on bernoulli likelihood from generic likelihood

Below is the exact step-by-step mathematical path from a generic likelihood to Bernoulli likelihood and finally to Binary Cross-Entropy (BCE).

No intuition, no storytelling — only formal steps.

## Step 0 — Generic Likelihood (Starting Point)

Given data:

$$\mathcal{D} = \{(x_i, y_i)\}_{i=1}^n$$

Model parameters:

$$w \in \mathbb{R}^d$$

Generic likelihood:

$$\mathcal{L}(w) = \prod_{i=1}^n P(y_i \mid x_i, w)$$

At this point, no distribution is specified.

---

## Step 1 — Identify the Sample Space of $y$

Assume:

$$y_i \in \{0, 1\}$$

Therefore:

$y_i$  is a discrete random variable with two outcomes

---

## Step 2 — Enforce Probability Axioms

For each fixed  $x_i, w$ , the conditional distribution must satisfy:

$$\sum_{y \in \{0,1\}} P(y \mid x_i, w) = 1 \quad \text{and} \quad 0 \leq P(y \mid x_i, w) \leq 1$$

Thus, define:

$$p_i := P(y_i = 1 \mid x_i, w)$$

Then necessarily:

$$P(y_i = 0 \mid x_i, w) = 1 - p_i$$


---

## Step 3 — Unique Distribution for Binary Outcomes

By definition of a Bernoulli random variable:

$$P(y_i \mid x_i, w) = p_i^{y_i} (1 - p_i)^{1-y_i}$$

This step is forced by the support  $\{0, 1\}$ .

---

## Step 4 — Parameterize $p_i$

We need:

$$p_i \in (0, 1) \quad \text{for all } w^\top x_i \in \mathbb{R}$$

Choose a link function:

$$p_i = \sigma(z_i), \quad z_i = w^\top x_i$$

Sigmoid:

$$\sigma(z) = \frac{1}{1 + e^{-z}}$$

Now:

$$P(y_i | x_i, w) = \sigma(z_i)^{y_i} (1 - \sigma(z_i))^{1-y_i}$$

## Step 5 — Substitute into the Generic Likelihood

$$\mathcal{L}(w) = \prod_{i=1}^n \sigma(z_i)^{y_i} (1 - \sigma(z_i))^{1-y_i}$$

This is now a fully specified likelihood.

## Step 6 — Take Log-Likelihood

$$\log \mathcal{L}(w) = \sum_{i=1}^n [y_i \log \sigma(z_i) + (1 - y_i) \log(1 - \sigma(z_i))]$$

## Step 7 — Negative Log-Likelihood (Optimization Objective)

Maximum likelihood  $\Leftrightarrow$  minimize negative log-likelihood:

$$J(w) = - \sum_{i=1}^n [y_i \log \sigma(w^\top x_i) + (1 - y_i) \log(1 - \sigma(w^\top x_i))]$$

## Step 8 — Identify Binary Cross-Entropy

Define Binary Cross-Entropy loss:

$$\ell_{\text{BCE}}(y, p) = - [y \log p + (1 - y) \log(1 - p)]$$

Substitute  $p = \sigma(w^\top x)$ :

$$J(w) = \sum_{i=1}^n \ell_{\text{BCE}}(y_i, \sigma(w^\top x_i))$$

## Step 9 — Final Chain (Formal)

$$\begin{array}{l} \text{Generic likelihood} \xrightarrow{y \in \{0,1\}} \text{Bernoulli PMF} \\ \xrightarrow{p = \sigma(w^\top x)} \text{Bernoulli likelihood} \\ \xrightarrow{-\log} \text{Binary Cross-Entropy} \end{array}$$

## Final One-Line Statement

Binary Cross-Entropy is the negative log-likelihood of a Bernoulli model derived directly from the generic likelihood.

If you want next (still fully formal):

- same derivation with  $y \in \{-1, +1\}$
- Hessian and convexity proof of BCE
- why BCE is classification-calibrated
- why MSE fails (information geometry view)

Say which.

