MELLOX AI

06

Rebuild Plan & Data Reference

A dependency-ordered implementation manual, acceptance gates, complete typed schema and migration index.

REBUILD BLUEPRINT SERIES / VOLUME 06 OF 06

Source snapshot: 21 October 2026 | Branch: master

Commit: 055c90977c2c | Internal working reference

Code-derived implementation. Production activation requires separate evidence.

01 How to use this volume

This is volume 06 of six documents describing Mellox AI as represented in the local source snapshot on 21 October 2026. The owner confirmed that this repository is current, Railway is the hosting platform, codebase pricing should be used, and mellox.ai is the public website.

Evidence labels: Implemented means source exists and is mapped here; it does not prove that a production migration, credential, permission or feature switch is enabled. Owner-confirmed identifies facts supplied by the owner. External-verified identifies official web information checked on the snapshot date. Recommended identifies a rebuild or operating procedure. Unverified identifies missing deployment or commercial evidence.

Runtime code, migrations and current configuration outrank older guides. Model and price tables describe defaults unless explicitly stated otherwise. They are a dated reference, not a promise that vendors will retain them. No credentials or customer records are included.

Volume	Read it for
01 Product & workflows	Feature behavior, journeys, approvals and module ownership
02 Architecture & engineering	Frontend, backend, integrations, APIs and implementation patterns
03 AI models & generation	Every task-model route, images, video, context and evaluations
04 Pricing & billing	Plans, feature gates, all action prices, wallets and economics
05 Railway & operations	Deployment, configuration, jobs, security, recovery and diagnostics
06 Rebuild & data reference	Build order, acceptance criteria, full typed schema and migration index

Contents

01 How to use this volume 2

02 How to rebuild from scratch 4

03 Phase 1 - repository and deployable skeleton 4

04 Phase 2 - auth, workspaces, roles and account ownership 4

05 Phase 3 - billing, AI gateway and durable accounting 5

06 Phase 4 - Brain, memory and assistant 5

07 Phase 5 - Studio, assets and editorial workflow 5

08 Phase 6 - social, website publishing and measurement 6

09 Phase 7 - video and composition 6

10 Phase 8 - visibility, fixes and controlled experiments 7

11 Phase 9 - learning, Autopilot, agencies and assistants 7

12 End-to-end acceptance matrix 8

13 Concrete request contracts and continuation behavior 8

14 Current-state corrections and decision backlog 9

15 Data dictionary conventions 10

16 Latest SQL addition not yet in generated types 33

17 Database function contract index 34

18 Migration chronology 42

19 Separate Python API inventory 48

20 Maintaining the blueprint 48

21 Source ledger and verification limits 49

02 How to rebuild from scratch

Rebuild Mellox around its invariants before copying its screens. Identity must be explicit, workspace data must stay isolated, paid work must be metered exactly once, generated work must remain reviewable, and long-lived side effects must survive process restarts. The order below is a recommended dependency plan inferred from current implementation, not a committed delivery schedule or team estimate.

Keep the six volumes and the source snapshot together. Volume 01 defines behavior, volume 02 maps architecture/contracts, volume 03 defines AI execution, volume 04 defines billing, volume 05 defines operations, and this volume provides implementation order plus the exact checked-in table/column and migration indexes.

PDFs cannot encode private vendor accounts, production environment values, invoices or future product decisions that were not supplied. A clean rebuild also needs a source repository and the owning provider accounts. Recreate the public contracts and invariants; do not assume an older audit, deprecated adapter or proposed feature is required merely because a historical file remains.

Implementation sources: docs/documentation-maintenance.md; src/server/route.ts; src/lib/billing/catalog.ts; supabase/migrations

03 Phase 1 - repository and deployable skeleton

Deliver the Next.js/React/TypeScript skeleton, current styling primitives, app/public route split, server-only boundary, Supabase clients, environment validation and a Railway-compatible container. Use the checked-in lockfile versions as the reproducibility baseline. Read the installed Next.js documentation before changing framework configuration or routing.

Create development, isolated test and production environments with separate data and credentials. Establish a migration mechanism, release manifest and health identity before paid features. Install native tools for the selected runtime: Chromium, FFmpeg and the image-metadata dependencies when those capabilities are enabled. Optional Redis is valuable for shared cache/rate behavior across replicas, but durable truth stays in PostgreSQL.

Acceptance: fresh build starts with the intended port; missing required production variables fail clearly; /health is live; safe health/readiness paths report the release identity and unavailable capabilities honestly; a browser bundle contains no server credentials.

Implementation sources: package.json; package-lock.json; Dockerfile; src/server/env.ts; src/instrumentation.ts; next.config.ts

04 Phase 2 - auth, workspaces, roles and account ownership

Implement signup/login, confirmation, password recovery, logout and workspace creation/listing. Wire canonical workspace routes, provider context and query-key isolation. Implement membership, invitation and role transitions with owner protection and operation-specific checks. Introduce the owner's billing account relationship before users create multiple brands.

Persist profiles, workspaces, members, invites, sources and connections through the canonical schema. Enable RLS, prohibit unsafe workspace reassignment, and reserve service-role queries for explicit server paths. A supplied workspace or item ID must be authorized every time; a remembered browser selection is only UI state.

Acceptance: outsider reads/writes fail even with real UUIDs; an editor cannot act as owner; a viewer cannot spend; a delayed response cannot replace another workspace's content; password-recovery replay and sign-out failure do not present false success; owner/account mapping remains stable across workspace changes.

Implementation sources: src/server/workspaces; src/server/fns/workspaces.ts; src/lib/workspace; src/integrations/supabase; supabase/migrations

05 Phase 3 - billing, AI gateway and durable accounting

Build the pure commercial catalog and entitlement resolver, then account allowances, restricted grants, holds, capture/release, replay keys, expiry and monthly windows. Keep general credits, video units and message counters separate. Add availability gates for later features. Integrate Stripe through server-created prices/checkouts and verified replay-safe events; do not let the browser set money amounts.

Add the AI task registry, provider gateway, spend controls, usage events, normalized errors, cache and rate limiting. Route call sites by task label, not arbitrary model names. Add provider-reported cost handling and safe estimate fallback. Model overrides must remain deliberate and auditable.

Acceptance: identical idempotency keys cannot charge twice; streaming cancellation releases only safely releasable funds; ambiguous capture is replayed safely; provider outages are visible; missing billing schema does not make production unlimited; fallback records the model actually used; an unknown test task fails registry coverage.

Implementation sources: src/lib/billing/catalog.ts; src/server/billing; src/server/ai; src/lib/ai-gateway.server.ts; src/server/platform

06 Phase 4 - Brain, memory and assistant

Build Brand DNA extraction/editing and current Brand Look, then competitor/market source stores, audience groups and strategy confirmation. Implement memory rules, provenance, removal markers, temporary expiry and the workspace use-memory switch. Retrieval of stored knowledge is the persistent-context mechanism; no custom foundation-model training is required by this architecture.

Add chat streaming, research and read tools. Store offered write actions server-side with explicit role recheck and single-run transition. Persist reply metadata for reload. Memory changes use the dedicated decision rules; retrieved untrusted data cannot authorize arbitrary writes.

Acceptance: an unconfirmed strategy never reaches a generator; a hallucinated competitor/source is rejected; changed memory invalidates context caches; removed memories stay removed; a read tool cannot mutate; duplicate action-button clicks run once; messages and tool data remain workspace-scoped.

Implementation sources: src/server/brain; src/server/strategy; src/server/memory; src/server/chat; src/lib/memory; src/lib/strategy

07 Phase 5 - Studio, assets and editorial workflow

Build content_items and asset persistence before individual generators. Implement durable studio_jobs with leases and recovery, then social text, scripts, ads, articles, carousels, Stories and image generation. Reuse shared context and brand rules, deterministic renderers, review stages and metadata.

Add the library, calendar, versioned edits, approval statuses, conflict detection and cancel-before-edit behavior for in-flight delivery. Persist media in private R2 through canonical workspace keys, while supporting existing legacy storage identities. Canva round trips produce new versioned assets, never overwrite originals. Notion is optional manual planning exchange with preview and conflict handling.

Acceptance: successful text/image work becomes a saved draft; a partial job settles its own billing; restart recovery does not lose accepted provider tasks; asset URLs cannot cross tenants; changing kind invalidates approval; stale saves return 409; pending local edits block approval until saved; scheduled work cannot be rewritten behind the provider's back.

Implementation sources: src/server/studio; src/server/assets; src/server/fns/content.ts; src/server/connectors/canva; src/server/connectors/notion; supabase/migrations/20261018090000_content_kind_approval.sql

08 Phase 6 - social, website publishing and measurement

Choose Post for Me or deliberately provision the separate SDR path. Implement account connection, current network metadata, media validation, schedule/publish/cancel, signature-verified callbacks, frame-level Story results, idempotent delivery and polling/reconciliation. Do not build the retired SocialAPI provider as a new default.

Implement website connection, source ownership and article publishing as distinct flows. GitHub changes produce reviewed PRs; CMS actions respect actual connector capabilities. Then connect GA4/GSC and social feed metrics with durable sync runs, attribution metadata and failure states.

Acceptance: unapproved content is refused; a duplicate webhook cannot regress a terminal publication; partial Story retry sends only unresolved frames with unchanged source identity; missing network metrics stay unavailable; website-source failure marks an incomplete queue; a social post does not deduct general AI credits.

Implementation sources: src/lib/postforme; src/lib/feature-flags.ts; src/server/social; src/server/articles; src/server/analytics; src/server/fns/publish.ts

09 Phase 7 - video and composition

Add product extraction, concepts, notes and plan-aware model routing. Share the capability registry with validation and UI; native duration, aspect ratio, resolution, audio and references depend on the selected provider. Quote and reserve video allowance using routed cost, not a hard-coded generic price.

Persist accepted provider/model/task identity before polling. Use provider fallback only after definite compatible refusal. Add the composition table, revision leases, segmented prompts, clip safety checks and FFmpeg assembly for longer outputs. Store and settle the final asset once. Keep cancellation behavior consistent with provider acceptance and financial state.

Acceptance: long output survives an application restart; uncertain submit cannot double-spend on another provider; a plan-locked model is not selected; preview and held quote agree; accepted clips are not recreated after polling; unsupported references fail explicitly; partial/unsafe output does not become a publishable asset.

Implementation sources: src/lib/ugc; src/server/ugc; src/server/billing/ugc-async.server.ts; src/server/ugc/providers/composition.server.ts; supabase/migrations/20261021090000_video_compositions.sql

10 Phase 8 - visibility, fixes and controlled experiments

Implement the public-URL-safe crawler, structured evidence, stable deterministic GEO rules, weighted scoring, finding fingerprints, monitors and verification. Add optional rendering and AI probes behind explicit gates. Keep tracked prompt observation history separate from deterministic technical site scores.

Add source ownership, proposal grounding, exact reviewed patches, PR creation and post-change checks before allowing an engineer to modify a site. Build Proof Engine only after source writes and Google page-level data are reliable. Current eligibility includes at least thirty pages, fifty-six complete pre-period days, concentration and power checks, balanced assignment, and final checkpoints from day twenty-one through forty-two. These source constants should not be weakened to obtain an attractive result.

Acceptance: all-pass applicable site reaches the expected score; N/A never deducts; score versions are not compared as ordinary deltas; blocked training crawlers alone do not count as blocked search access; provider failure is not a visibility gap; approval cannot resolve a finding; missing/incomplete experiment data remains inconclusive.

Implementation sources: src/lib/geo; src/server/geo; src/lib/experiments/constants.ts; src/lib/experiments/evaluate.ts; src/server/experiments

11 Phase 9 - learning, Autopilot, agencies and assistants

Add audience outcome calibration and controlled reuse of measured content. Current calibration requires at least one hundred views, eight comparator posts, eight prediction/outcome pairs and bounded shrinkage before corrections. Pure scoring numbers remain separate from model-generated rationale.

Build Autopilot on the same Studio, content, publication and billing services. Plan slots around existing calendar work, ground picks to stored sources, obey weekly spend limits and approval mode, expire missed pieces, then measure and learn. The agency view aggregates allowed workspaces without weakening tenant boundaries.

Expose the existing operations through MCP with OAuth, per-workspace access and change gates, rate limits, cleaned outputs and append-only call history. Add staff controls with explicit permissions, MFA and audited overrides. A commercial SSO/API product remains separate future work until implemented.

Acceptance: automatic-mode policy never broadens itself; new opportunities wait for review; existing posts prevent duplicate slots; article delivery still requires approval; stopping a program blocks future work; assistant tools cannot invoke excluded administration or unapproved publication; staff support access is narrow and audited.

Implementation sources: src/lib/audience/calibration.ts; src/server/autopilot; src/lib/autopilot; src/server/mcp; src/server/admin

12 End-to-end acceptance matrix

Scenario	Required observable result	Owning layer
Brand A user requests Brand B row	Denied before privileged provider or data operation	Route/RPC + RLS
Same Generate click submitted twice	One durable job and one financial settlement	Job + meter replay keys
Process dies after provider accepted render	Stored task can resume; no blind second submit	Provider + composition store
Caption save races approval	Revision conflict or serialized correct approval	Content service + database
Post type changes after approval	Approval invalidated	Database trigger
Publish callback arrives out of order	Newer terminal truth survives	Webhook/reconciler
Story frame fails after other frames succeeded	Only unresolved unchanged frames retried	Post for Me adapter
Expired media URL opened	Authorized route can issue fresh short-lived URL	Asset storage
GEO fix approved but not visible live	Finding remains unresolved/inconclusive	Verification engine
Audience content changed	Old prediction no longer shown as matching	Exact fingerprint cache
Experiment lacks sufficient complete days	No final positive verdict manufactured	Pure experiment evaluation
Plan falls to Free	Preserved content, constrained excess brands/spend	Entitlements and account lifecycle
Admin without required permission/MFA	Denied and refusal audited	Admin route kernel
MCP workspace changes disabled	Read works only where enabled; write/spend denied	MCP gate + app services

Implementation sources: tests; src/server; supabase/migrations

13 Concrete request contracts and continuation behavior

Start an AI Visibility scan

```
POST /api/geo/scans
Authorization: Bearer <member access token>
Content-Type: application/json

{"workspaceId":"<UUID>","url":"https://example.com",
"mode":"full","trigger":"manual",
"probes":false,"idempotencyKey":"<8-100 characters>"}
```

Editor required. URL text is 1-2000 characters and safe-fetch validates the real destination. Mode defaults full; trigger defaults manual and allows manual/chat/rescan. Probes and idempotencyKey are optional. Full non-rescan work checks monthly scan limits. Success is 201 {scan}; an active-scan conflict is 409 with activeScanId. Full work continues in a durable scan and is polled through its ID; quick work gets a bounded inline drive.

Studio and UGC contract ownership

POST /api/studio/jobs uses CreateJobSchema in src/lib/studio/jobs.ts, editor role and media-dependent rate limits. It returns {job}, with X-Billing-Balance when available. GET on the same route reads recent jobs for a workspace so UI can resume after reload. UGC POST /api/ugc/renders uses StartRenderBody in src/lib/ugc/schemas.ts; choices and a per-click replay key are client inputs, but price, allowance, model capability and activation remain server decisions. These richer schemas should be reused directly instead of approximating them from a static example.

Implementation sources: src/app/api/geo/scans/route.ts; src/app/api/studio/jobs/route.ts; src/lib/studio/jobs.ts; src/app/api/ugc/renders/route.ts; src/lib/ugc/schemas.ts

14 Current-state corrections and decision backlog

Older / ambiguous claim	Current blueprint treatment
SocialAPI as active social provider	Retired by provider selector; Post for Me configured first, optional SDR.
Social publication uses general credits	No general-credit charge; current monthly fair-use controls apply.
Brand Styles as parallel style library	Current Brain/Brand Look replaces that earlier design.
Video is always an eight-second single task	Current output defaults ten seconds; supports composition up to sixty.
Variation falls back to OpenRouter Grok	Current fallback is six-second Veo Lite.
Every feature waits for every post approval	Current explicit fully automatic mode can send qualifying plain/image content.
Scale SSO/API is implemented because of tagline	Catalog explicitly marks commercial SSO/API later.
Python adapter names define the main app models	Separate runtime; main task registry owns main-app defaults.
Amplify/Lightsail/tunnel docs prove current host	Owner confirms Railway; exact service details remain unverified.
Old forecasts are actual margins	Use current catalog estimates and measured invoices separately.
Model default is necessarily production model	Environment/admin overrides and actual returned model may differ.
A file or catalog entry proves production ready	Requires applied migration, credentials, flags, permissions and validation.

Implementation sources: src/lib/feature-flags.ts; src/lib/billing/catalog.ts; src/lib/ugc/models.ts; src/lib/ugc/duration.ts; src/server/ai/task-models.ts

Recommended backlog: fill production inventory and restore policy first; verify provider readiness and remaining schema deployment; align stale canonical guides with current code; validate quote/capability boundaries; maintain generated contract/schema references in CI; only then schedule catalog later features. These are recommendations, not owner-approved launch commitments.

15 Data dictionary conventions

The following is the complete 179-table Row-type dictionary extracted from the checked-in Supabase TypeScript schema. It includes field names, TypeScript scalar/union types and declared relationships. string can represent SQL text, UUID or timestamp; number can represent several SQL numeric types. Json is a schema-less TypeScript JSON value, whose business shape must be read from feature contracts and migrations. Nullability appears as | null. SQL defaults, check constraints, indexes, triggers, grants and exact RLS policies are not encoded by this Row dictionary.

Treat this as a navigation and reconstruction reference with the migration history, not runnable replacement DDL. It may include compatibility objects still represented in generated types. No table contents, customer rows or secret credential values are included. Service-only credential tables are named so their separation can be rebuilt, but must never become browser-readable just because they appear here.

Implementation sources: src/integrations/supabase/types.ts; supabase/migrations

account_notifications

account_id: string; created_at: string; id: string; kind: string; payload: Json; read_at: string | null; user_id: string; window_key: string | null

FK account_notifications_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

admin_audit_log

action: string; actor_role: string | null; actor_user_id: string | null; after_state: Json | null; before_state: Json | null; created_at: string; error: string | null; id: string; impersonating: string | null; ip: string | null; reason: string | null; request_id: string | null; success: boolean; target_id: string | null; target_type: string | null; user_agent: string | null; workspace_id: string | null

admin_user_notes

author_id: string; body: string; created_at: string; id: string; user_id: string

admin_users

created_at: string; created_by: string | null; denied_permissions: string[]; disabled_at: string | null; extra_permissions: string[]; last_seen_at: string | null; note: string | null; role: string; status: string; updated_at: string; user_id: string

admin_view_sessions

admin_user_id: string; ended_at: string | null; expires_at: string; id: string; reason: string; started_at: string; workspace_id: string

FK admin_view_sessions_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

agent_action_requests

affected_records: Json; args: Json; created_at: string; decided_at: string | null; decided_by: string | null; decision_reason: string | null; error: string | null; executed_at: string | null; expires_at: string; id: string; idempotency_key: string; preview: Json; requested_by: string | null; result: Json | null; run_id: string | null; source: string; status: string; title: string; tool: string; updated_at: string; workspace_id: string

FK agent_action_requests_run_id_fkey: (run_id) -> agent_runs (id); one-to-one false

FK agent_action_requests_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

agent_findings

affected: Json; confidence: number; created_at: string; evidence: Json; fingerprint: string; hypotheses: Json; id: string; last_seen_at: string; occurrences: number; recommended_action: string; requires_human_approval: boolean; resolved_at: string | null; resolved_by: string | null; run_id: string | null; severity: string; status: string; summary: string; title: string; updated_at: string; worker: string; workspace_id: string

FK agent_findings_run_id_fkey: (run_id) -> agent_runs (id); one-to-one false

FK agent_findings_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

agent_run_steps

cost_usd: number; created_at: string; id: string; kind: string; latency_ms: number | null; policy_decision: string | null; redacted_args: Json; result_summary: Json; run_id: string; seq: number; status: string; tool: string | null; tool_call_id: string | null; workspace_id: string

FK agent_run_steps_run_id_fkey: (run_id) -> agent_runs (id); one-to-one false

FK agent_run_steps_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

agent_runs

agent: string; budget: Json; content_item_id: string | null; cost_usd: number; created_at: string; created_by: string | null; duration_ms: number | null; error: string | null; finished_at: string | null; id: string; input_tokens: number; model: string | null; output: Json | null; output_tokens: number; parent_run_id: string | null; prompt: string; started_at: string | null; status: string; summary: string | null; trigger: string; updated_at: string; worker: string | null; workspace_id: string

FK agent_runs_content_item_id_fkey: (content_item_id) -> content_items (id); one-to-one false

FK agent_runs_parent_run_id_fkey: (parent_run_id) -> agent_runs (id); one-to-one false

FK agent_runs_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

ai_usage_daily

cached_calls: number; calls: number; cost_usd: number; day: string; error_calls: number; images: number; input_tokens: number; output_tokens: number; saved_usd: number; scope_key: string; truncated_calls: number; updated_at: string; user_id: string | null; videos: number; workspace_id: string | null

FK ai_usage_daily_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

ai_usage_events

billing_account_id: string | null; cached: boolean; charge_id: string | null; created_at: string; est_cost_usd: number; id: number; input_tokens: number; kind: string; latency_ms: number | null; model: string; output_tokens: number; provider: string; request_id: string | null; route: string; run_id: string | null; saved_usd: number; status: string; truncated: boolean; units: number; user_id: string | null; workspace_id: string | null

FK ai_usage_events_billing_account_id_fkey: (billing_account_id) -> billing_accounts (id); one-to-one false

FK ai_usage_events_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

ai_usage_reservations

captured_at: string | null; captured_cost_usd: number | null; created_at: string; est_cost_usd: number; expires_at: string; id: string; kind: string; model: string; provider: string; release_reason: string | null; released_at: string | null; route: string; scope_key: string; source: string; source_id: string; state: string; units: number; user_id: string | null; workspace_id: string | null

FK ai_usage_reservations_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

allowance_usage

account_id: string; extra_pages_scanned: number; scans_used: number; window_start: string

FK allowance_usage_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

analytics_ga4_daily

bounced_sessions: number; date: string; engaged_sessions: number; key_events: number; new_users: number; screen_page_views: number; session_duration_seconds: number; sessions: number; source_id: string; synced_at: string; total_users: number; workspace_id: string

FK analytics_ga4_daily_source_id_fkey: (source_id) -> analytics_sources (id); one-to-one false

FK analytics_ga4_daily_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

analytics_ga4_dimension_daily

date: string; dimension: string; key_events: number; screen_page_views: number; sessions: number; source_id: string; synced_at: string; total_users: number; value: string; workspace_id: string

FK analytics_ga4_dimension_daily_source_id_fkey: (source_id) -> analytics_sources (id); one-to-one false

FK analytics_ga4_dimension_daily_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

analytics_ga4_period_totals

date_from: string; date_to: string; fetched_at: string; source_id: string; total_users: number; workspace_id: string

FK analytics_ga4_period_totals_source_id_fkey: (source_id) -> analytics_sources (id); one-to-one false

FK analytics_ga4_period_totals_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

analytics_gsc_daily

clicks: number; date: string; impressions: number; position_weighted: number; source_id: string; synced_at: string; workspace_id: string

FK analytics_gsc_daily_source_id_fkey: (source_id) -> analytics_sources (id); one-to-one false

FK analytics_gsc_daily_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

analytics_gsc_dimension_daily

clicks: number; date: string; dimension: string; impressions: number; position_weighted: number; source_id: string; synced_at: string; value: string; workspace_id: string

FK analytics_gsc_dimension_daily_source_id_fkey: (source_id) -> analytics_sources (id); one-to-one false

FK analytics_gsc_dimension_daily_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

analytics_insights

created_at: string; fingerprint: string; id: string; insights: Json; model: string | null; range_key: string; signals: Json; workspace_id: string

FK analytics_insights_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

analytics_sources

account_name: string | null; backfill_completed_at: string | null; connection_id: string; created_at: string; currency: string | null; display_name: string; external_id: string; id: string; kind: string; last_error: string | null; last_synced_at: string | null; last_synced_date: string | null; selected_by: string | null; site_host: string | null; status: string; time_zone: string | null; updated_at: string; workspace_id: string

FK analytics_sources_connection_id_fkey: (connection_id) -> workspace_connections (id); one-to-one false

FK analytics_sources_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

analytics_sync_runs

attempts: number; completed_at: string | null; created_at: string; cursor_date: string; cursor_step: number; error_code: string | null; error_message: string | null; failures: number; id: string; lease_until: string | null; locked_by: string | null; max_attempts: number; next_attempt_at: string; range_end: string; range_start: string; requested_by: string | null; rows_written: number; source_id: string; started_at: string | null; status: string; trigger: string; updated_at: string; workspace_id: string

FK analytics_sync_runs_source_id_fkey: (source_id) -> analytics_sources (id); one-to-one false

FK analytics_sync_runs_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

api_rate_limits

bucket_key: string; request_count: number; updated_at: string; window_start: string

approvals

action: string; content_item_id: string | null; created_at: string; decided_at: string | null; id: string; payload: Json; status: string; workspace_id: string

FK approvals_content_item_id_fkey: (content_item_id) -> content_items (id); one-to-one false

FK approvals_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

assets

asset_type: string; attempt: number; brand_dna_version: string | null; content_item_id: string | null; created_at: string; creative_brief_version: string | null; deleted_at: string | null; filename: string; generation_id: string; height: number | null; id: string; idempotency_key: string; metadata: Json; mime_type: string; model: string | null; model_route: string | null; parent_asset_id: string | null; platform: string | null; prompt_version: string | null; provider: string | null; public_url: string | null; qa_score: number | null; seed: string | null; status: string; storage_path: string | null; thumbnail_path: string | null; updated_at: string; width: number | null; workspace_id: string

FK assets_content_item_id_fkey: (content_item_id) -> content_items (id); one-to-one false

FK assets_parent_asset_id_fkey: (parent_asset_id) -> assets (id); one-to-one false

FK assets_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

audience_calibration

bias: number; content_type: string; learned: Json; mae: number; n: number; platform: string; updated_at: string; workspace_id: string

FK audience_calibration_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

audience_outcomes

actual: number | null; content_item_id: string | null; content_type: string; delivered_at: string | null; engagement: number; horizon: string; id: string; measured_at: string; metrics: Json; platform: string; predicted: number; prediction_id: string; title: string; workspace_id: string

FK audience_outcomes_content_item_id_fkey: (content_item_id) -> content_items (id); one-to-one false

FK audience_outcomes_prediction_id_fkey: (prediction_id) -> audience_predictions (id); one-to-one false

FK audience_outcomes_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

audience_predictions

calibrated: boolean; content_item_id: string | null; content_type: string; created_at: string; created_by: string | null; depth: string; dimensions: Json; id: string; overall: number; platform: string; result: Json; run_id: string | null; score_version: number; subject: Json; subject_hash: string; twins_fingerprint: string; variant_index: number | null; workspace_id: string

FK audience_predictions_content_item_id_fkey: (content_item_id) -> content_items (id); one-to-one false

FK audience_predictions_run_id_fkey: (run_id) -> audience_runs (id); one-to-one false

FK audience_predictions_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

audience_run_events

created_at: string; data: Json; id: string; kind: string; run_id: string; summary: string; workspace_id: string

FK audience_run_events_run_id_fkey: (run_id) -> audience_runs (id); one-to-one false

FK audience_run_events_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

audience_runs

attempts: number; cancel_requested: boolean; content_item_id: string | null; created_at: string; created_by: string | null; finished_at: string | null; id: string; idempotency_key: string; input: Json; kind: string; last_error: string | null; lease_until: string | null; locked_by: string | null; next_attempt_at: string; output: Json; progress: Json; stage: string; state: Json; status: string; updated_at: string; workspace_id: string

FK audience_runs_content_item_id_fkey: (content_item_id) -> content_items (id); one-to-one false

FK audience_runs_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

audience_twins

created_at: string; created_by: string | null; id: string; kind: string; name: string; origin: string; origin_ref: string | null; profile: Json; segment: string; slug: string; status: string; summary: string; updated_at: string; updated_by: string | null; version: number; weight: number; workspace_id: string

FK audience_twins_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

audit_logs

action: string; created_at: string; entity: string | null; id: string; payload: Json; user_id: string | null; workspace_id: string

FK audit_logs_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

autopilot_actions

approved_by: string | null; approved_via: string | null; attempts: number; brief: string; content_item_ids: string[]; content_type: string | null; created_at: string; credits_charged: number; cycle: number; dedupe_key: string; finished_at: string | null; generation_attempt: number; goal: string | null; id: string; kind: string; last_error: string | null; lease_until: string | null; locked_by: string | null; next_attempt_at: string; opportunity_id: string | null; planned_for: string | null; platform: string | null; program_id: string | null; reason: string; requested_by: string | null; result: Json; slot: number | null; status: string; studio_job_id: string | null; title: string; updated_at: string; workspace_id: string

FK autopilot_actions_opportunity_id_fkey: (opportunity_id) -> marketing_opportunities (id); one-to-one false

FK autopilot_actions_program_id_fkey: (program_id) -> autopilot_programs (id); one-to-one false

FK autopilot_actions_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

autopilot_events

action_id: string | null; actor: string; actor_id: string | null; created_at: string; data: Json; id: string; kind: string; opportunity_id: string | null; program_id: string | null; summary: string; workspace_id: string

FK autopilot_events_action_id_fkey: (action_id) -> autopilot_actions (id); one-to-one false

FK autopilot_events_opportunity_id_fkey: (opportunity_id) -> marketing_opportunities (id); one-to-one false

FK autopilot_events_program_id_fkey: (program_id) -> autopilot_programs (id); one-to-one false

FK autopilot_events_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

autopilot_programs

act_on_opportunities: boolean; acting_user_id: string | null; automations: string[]; content_types: string[]; created_at: string; created_by: string | null; credit_cap_per_week: number; cycle: number; ends_on: string; finished_at: string | null; goal: string; goal_note: string; id: string; last_notified_at: string | null; mode: string; pause_reason: string | null; platforms: string[]; posts_per_week: number; starts_on: string; status: string; stories: Json; strategy: Json; timezone: string; updated_at: string; video_cap_per_week: number; weekdays: number[]; workspace_id: string

FK autopilot_programs_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

backlink_campaigns

created_at: string; created_by: string | null; goal: string; id: string; name: string; site_host: string | null; status: string; target_count: number; updated_at: string; workspace_id: string

FK backlink_campaigns_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

backlink_discovery_runs

cache_key: string; campaign_id: string | null; competitors: string[]; completed_at: string | null; cost_usd: number; created_at: string; created_by: string | null; error: string | null; expires_at: string; found: number; id: string; provider: Json; site_host: string; status: string; workspace_id: string

FK backlink_discovery_runs_campaign_id_fkey: (campaign_id) -> backlink_campaigns (id); one-to-one false

FK backlink_discovery_runs_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

backlink_events

actor: string | null; at: string; detail: Json; id: string; opportunity_id: string; type: string; workspace_id: string

FK backlink_events_opportunity_id_fkey: (opportunity_id) -> backlink_opportunities (id); one-to-one false

FK backlink_events_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

backlink_opportunities

ai: Json | null; anchor_found: string | null; campaign_id: string; competitor_hits: number; created_at: string; created_by: string | null; discovery_run_id: string | null; evidence: Json; first_live_at: string | null; id: string; is_nofollow: boolean | null; kind: string; live_url: string | null; method: string | null; outreach: Json | null; rank: number | null; score: number; source_domain: string; source_title: string | null; source_url: string | null; spam_score: number | null; status: string; suggested_anchor: string | null; target_url: string | null; updated_at: string; verification: string; verified_at: string | null; workspace_id: string

FK backlink_opportunities_campaign_id_fkey: (campaign_id) -> backlink_campaigns (id); one-to-one false

FK backlink_opportunities_discovery_run_id_fkey: (discovery_run_id) -> backlink_discovery_runs (id); one-to-one false

FK backlink_opportunities_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

backlink_verifications

anchor_found: string | null; checked_at: string; checked_by: string | null; checked_url: string; error: string | null; expected_target: string; http_status: number | null; id: string; is_nofollow: boolean | null; link_found: boolean | null; opportunity_id: string; result: string; workspace_id: string

FK backlink_verifications_opportunity_id_fkey: (opportunity_id) -> backlink_opportunities (id); one-to-one false

FK backlink_verifications_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

billing_accounts

billing_interval: string | null; cancel_at: string | null; capacity_reconciled_at: string | null; comped_plan_id: string | null; comped_until: string | null; created_at: string; current_period_end: string | null; current_period_start: string | null; downgrade_at: string | null; downgrade_to: string | null; enforcement_override: string | null; entitled_plan_id: string | null; founding: boolean; grace_until: string | null; grant_anchor: string | null; id: string; last_paid_invoice_id: string | null; next_grant_at: string | null; owner_user_id: string; pause_started_at: string | null; plan_id: string; pro_overage_mode: string; provider: string; provider_customer_id: string | null; provider_subscription_id: string | null; referral_code: string | null; referred_by_account_id: string | null; resume_plan_id: string | null; status: string; trial_ends_at: string | null; trial_used: boolean; updated_at: string

FK billing_accounts_referred_by_account_id_fkey: (referred_by_account_id) -> billing_accounts (id); one-to-one false

billing_admin_adjustments

account_id: string; actor_user_id: string; amount: number; created_at: string; grant_id: string | null; id: string; meter: string; operation: string; reason: string

FK billing_admin_adjustments_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

FK billing_admin_adjustments_grant_id_fkey: (grant_id) -> meter_grants (id); one-to-one false

billing_async_links

account_id: string; action: string; amount: number; captured: number | null; charge_id: string | null; charge_key: string; created_at: string; hold_id: string | null; kind: string; mode: string; ref_id: string; settled_at: string | null; shadow_decision: string | null; workspace_id: string | null

FK billing_async_links_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

FK billing_async_links_hold_id_fkey: (hold_id) -> meter_holds (id); one-to-one true

billing_charges

account_id: string; action: string; amount: number; created_at: string; id: string; meter: string; route: string | null; user_id: string | null; workspace_id: string | null

FK billing_charges_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

billing_customers

created_at: string; stripe_customer_id: string; workspace_id: string

FK billing_customers_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one true

billing_enforcement_actions

account_id: string; actor_user_id: string; created_at: string; id: string; next_mode: string | null; previous_mode: string | null; reason: string

FK billing_enforcement_actions_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

billing_events

account_id: string | null; error: string | null; id: string; occurred_at: string | null; payload: Json; processed_at: string | null; received_at: string; type: string

FK billing_events_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

billing_manual_activations

account_id: string; active_until: string | null; actor_user_id: string; billing_interval: string | null; catalog_key: string; created_at: string; id: string; kind: string; months: number | null; reason: string; reference: string | null; request_id: string | null

FK billing_manual_activations_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

FK billing_manual_activations_request_id_fkey: (request_id) -> billing_purchase_requests (id); one-to-one false

billing_payment_records

account_id: string; amount_cents: number; catalog_key: string; checkout_intent_id: string | null; created_at: string; grant_ids: Json; kind: string; provider_invoice_id: string | null; provider_payment_id: string; refunded_cents: number

FK billing_payment_records_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

FK billing_payment_records_checkout_intent_id_fkey: (checkout_intent_id) -> checkout_intents (id); one-to-one false

billing_price_map

active: boolean; amount_cents: number; catalog_key: string; environment: string; interval: string; provider_price_id: string; provider_product_id: string

billing_provider_health

credential_fingerprint: string | null; environment: string; last_event_id: string | null; updated_at: string; webhook_verified_at: string | null

billing_purchase_requests

account_id: string; admin_note: string | null; billing_interval: string | null; catalog_key: string; contact: string | null; created_at: string; handled_at: string | null; handled_by: string | null; id: string; kind: string; note: string | null; quantity: number; requested_by: string; status: string; updated_at: string

FK billing_purchase_requests_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

billing_shadow_events

account_id: string; action: string; amount: number | null; created_at: string; decision: string; id: number; idempotency_key: string | null; meter: string | null; reason: string | null; workspace_id: string | null

FK billing_shadow_events_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

billing_social_profile_slots

account_id: string; expires_at: string | null; state: string; updated_at: string; workspace_id: string

FK billing_social_profile_slots_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

FK billing_social_profile_slots_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one true

billing_studio_jobs

account_id: string; action: string; amount: number; charge_id: string | null; charge_key: string; created_at: string; hold_id: string | null; job_id: string; meter: string; mode: string; route: string; settled_at: string | null; shadow_decision: string; workspace_id: string

FK billing_studio_jobs_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

FK billing_studio_jobs_hold_id_fkey: (hold_id) -> meter_holds (id); one-to-one true

FK billing_studio_jobs_job_id_fkey: (job_id) -> studio_jobs (id); one-to-one true

FK billing_studio_jobs_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

billing_subscription_items

account_id: string; catalog_key: string; created_at: string; id: string; provider_item_id: string | null; provider_price_id: string | null; quantity: number; status: string; updated_at: string

FK billing_subscription_items_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

billing_suspended_members

account_id: string; original_created_at: string; original_role: Database["public"]["Enums"]["app_role"]; suspended_at: string; user_id: string; workspace_id: string

FK billing_suspended_members_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

FK billing_suspended_members_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

billing_ugc_renders

account_id: string; action: string; charge_id: string | null; charge_key: string; created_at: string; hold_id: string | null; mode: string; render_id: string; settled_at: string | null; shadow_decision: string; units: number; workspace_id: string

FK billing_ugc_renders_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

FK billing_ugc_renders_hold_id_fkey: (hold_id) -> meter_holds (id); one-to-one true

FK billing_ugc_renders_render_id_fkey: (render_id) -> ugc_renders (id); one-to-one true

FK billing_ugc_renders_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

brand_scan_allowances

account_id: string; kind: string; normalized_domain: string; used_at: string

FK brand_scan_allowances_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

brand_visual_capture_jobs

attempts: number; created_at: string; created_by: string | null; error: string | null; id: string; idempotency_key: string; lease_token: string | null; lease_until: string | null; max_pages: number; mode: string; next_page: number; pages: Json; stage: string; status: string; updated_at: string; url: string; warnings: Json; workspace_id: string

FK brand_visual_capture_jobs_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

brand_visual_feedback

created_at: string; created_by: string | null; id: string; job_id: string | null; note: string; profile_id: string | null; reason: string; source_ids: string[]; workspace_id: string

FK brand_visual_feedback_job_id_fkey: (job_id) -> studio_jobs (id); one-to-one false

FK brand_visual_feedback_profile_id_fkey: (profile_id) -> brand_visual_profiles (id); one-to-one false

FK brand_visual_feedback_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

brand_visual_profiles

capture_job_id: string | null; created_at: string; created_by: string | null; id: string; profile: Json; status: string; workspace_id: string

FK brand_visual_profiles_capture_job_id_fkey: (capture_job_id) -> brand_visual_capture_jobs (id); one-to-one true

FK brand_visual_profiles_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

brand_visual_settings

active_profile_id: string | null; updated_at: string; workspace_id: string

FK brand_visual_settings_active_profile_id_fkey: (active_profile_id) -> brand_visual_profiles (id); one-to-one false

FK brand_visual_settings_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one true

brand_visual_sources

asset_id: string; campaign: string | null; capture_job_id: string | null; created_at: string; formats: string[]; id: string; kind: string; label: string; notes: string; purpose: string; region: Json; source_url: string | null; status: string; workspace_id: string

FK brand_visual_sources_asset_id_fkey: (asset_id) -> assets (id); one-to-one false

FK brand_visual_sources_capture_job_id_fkey: (capture_job_id) -> brand_visual_capture_jobs (id); one-to-one false

FK brand_visual_sources_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

canva_design_mappings

asset_id: string | null; canva_asset_ids: string[]; canva_design_id: string; content_item_id: string | null; created_at: string; created_by: string | null; id: string; last_imported_at: string | null; last_opened_at: string; mode: string; source_key: string; title: string | null; workspace_id: string

FK canva_design_mappings_asset_id_fkey: (asset_id) -> assets (id); one-to-one false

FK canva_design_mappings_content_item_id_fkey: (content_item_id) -> content_items (id); one-to-one false

FK canva_design_mappings_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

canva_design_source_pages

canva_asset_id: string | null; mapping_id: string; page_number: number; source_asset_id: string | null; workspace_id: string

FK canva_design_source_pages_mapping_id_fkey: (mapping_id) -> canva_design_mappings (id); one-to-one false

FK canva_design_source_pages_source_asset_id_fkey: (source_asset_id) -> assets (id); one-to-one false

FK canva_design_source_pages_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

canva_fallback_slide_designs

canva_design_id: string; mapping_id: string; page_number: number; workspace_id: string

FK canva_fallback_slide_designs_mapping_id_fkey: (mapping_id) -> canva_design_mappings (id); one-to-one false

FK canva_fallback_slide_designs_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

canva_import_pages

asset_id: string; page_number: number; version_id: string; workspace_id: string

FK canva_import_pages_asset_id_fkey: (asset_id) -> assets (id); one-to-one false

FK canva_import_pages_version_id_fkey: (version_id) -> canva_import_versions (id); one-to-one false

FK canva_import_pages_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

canva_import_versions

id: string; imported_at: string; imported_by: string | null; mapping_id: string; selected_at: string | null; version_number: number; workspace_id: string

FK canva_import_versions_mapping_id_fkey: (mapping_id) -> canva_design_mappings (id); one-to-one false

FK canva_import_versions_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

canva_oauth_credentials

access_token_enc: string; access_token_expires_at: string; connection_id: string; created_at: string; refresh_token_enc: string; scopes: string[]; updated_at: string; workspace_id: string

FK canva_oauth_credentials_connection_id_fkey: (connection_id) -> workspace_connections (id); one-to-one true

FK canva_oauth_credentials_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

chat_actions

args: Json; conversation_id: string | null; created_at: string; destructive: boolean; detail: string; error: string | null; id: string; offered_to: string | null; result: Json | null; run_at: string | null; run_by: string | null; status: string; title: string; tool: string; updated_at: string; workspace_id: string

FK chat_actions_conversation_id_fkey: (conversation_id) -> conversations (id); one-to-one false

FK chat_actions_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

chat_messages

content: string; conversation_id: string | null; created_at: string; id: string; kind: string; metadata: Json; payload: Json; role: string; status: string; user_id: string | null; workspace_id: string

FK chat_messages_conversation_id_fkey: (conversation_id) -> conversations (id); one-to-one false

FK chat_messages_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

checkout_intents

account_id: string; catalog_key: string; consumed_at: string | null; created_at: string; created_by: string; expires_at: string; id: string; interval: string | null; kind: string; provider_price_id: string | null; provider_session_id: string | null; quantity: number

FK checkout_intents_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

client_events

actor_email: string | null; actor_name: string | null; actor_type: string; body: string | null; client_read_at: string | null; created_at: string; id: string; item_id: string | null; kind: string; marketer_decided_at: string | null; marketer_decided_by: string | null; marketer_decision: string; marketer_read_at: string | null; meta: Json; share_id: string

FK client_events_item_id_fkey: (item_id) -> client_share_items (id); one-to-one false

FK client_events_share_id_fkey: (share_id) -> client_shares (id); one-to-one false

client_share_items

created_at: string; description: string | null; id: string; kind: string; position: number; ref_id: string | null; share_id: string; snapshot: Json; title: string | null; visible: boolean

FK client_share_items_share_id_fkey: (share_id) -> client_shares (id); one-to-one false

client_shares

allow_approvals: boolean; allow_comments: boolean; allow_download: boolean; branding: Json; client_email: string | null; client_name: string | null; created_at: string; expires_at: string | null; id: string; last_viewed_at: string | null; owner_id: string; password_hash: string | null; slug: string; status: string; title: string; token_ciphertext: string | null; token_hash: string; updated_at: string; view_count: number; workspace_id: string

FK client_shares_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

competitor_alerts

after_value: string | null; before_value: string | null; detail: string | null; detected_at: string; id: string; kind: string; read_at: string | null; severity: string; source_url: string | null; title: string; watch_id: string; workspace_id: string

FK competitor_alerts_watch_id_fkey: (watch_id) -> competitor_watches (id); one-to-one false

FK competitor_alerts_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

competitor_intelligence_runs

competitor_id: string | null; competitor_url: string; completed_at: string | null; created_at: string; created_by: string | null; error: string | null; id: string; pages_crawled: Json; result: Json | null; status: string; updated_at: string; workspace_id: string

FK competitor_intelligence_runs_competitor_id_fkey: (competitor_id) -> workspace_competitors (id); one-to-one false

FK competitor_intelligence_runs_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

competitor_updates

competitor_id: string; detected_at: string; fingerprint: string; id: string; kind: string; published_at: string | null; read_at: string | null; significance: string; source_title: string | null; source_url: string | null; summary: string | null; title: string; workspace_id: string

FK competitor_updates_competitor_id_fkey: (competitor_id) -> workspace_competitors (id); one-to-one false

FK competitor_updates_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

competitor_watches

competitor_id: string | null; created_at: string; created_by: string | null; enabled: boolean; id: string; last_checked_at: string | null; last_error: string | null; last_snapshot: Json | null; name: string | null; updated_at: string; url: string; workspace_id: string

FK competitor_watches_competitor_id_fkey: (competitor_id) -> workspace_competitors (id); one-to-one false

FK competitor_watches_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

connector_install_states

consumed_at: string | null; created_at: string; expires_at: string; id: string; pkce_verifier_enc: string | null; provider: string; return_origin: string | null; return_path: string | null; state_hash: string; user_id: string; workspace_id: string

FK connector_install_states_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

content_items

agent: string; body: string | null; channel: string | null; created_at: string; created_by: string | null; hashtags: string[] | null; id: string; kind: string; media_url: string | null; meta: Json | null; metrics: Json | null; scheduled_at: string | null; status: string; title: string | null; updated_at: string; workspace_id: string

FK content_items_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

content_publications

account_id: string; attempt: number; content_item_id: string; created_at: string; delivered_at: string | null; error_category: string | null; error_code: string | null; frames: Json | null; id: string; last_error: string | null; metrics: Json | null; metrics_synced_at: string | null; placement: string; platform: string; platform_post_id: string | null; platform_post_url: string | null; provider: string; sdr_post_id: string; sdr_target_id: string; status: string; updated_at: string; workspace_id: string

FK content_publications_content_item_id_fkey: (content_item_id) -> content_items (id); one-to-one false

FK content_publications_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

conversations

archived_at: string | null; created_at: string; created_by: string | null; id: string; is_pinned: boolean; metadata: Json; preview: string | null; summary: string; title: string; updated_at: string; workspace_id: string

FK conversations_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

cron_heartbeats

expected_interval_seconds: number; failure_count: number; job: string; last_duration_ms: number | null; last_error: string | null; last_failed_at: string | null; last_result: Json | null; last_started_at: string | null; last_succeeded_at: string | null; run_count: number; updated_at: string

entitlement_overrides

account_id: string; allowed: boolean | null; created_at: string; created_by: string; expires_at: string | null; id: string; key: string; kind: string; limit_value: number | null; reason: string; revoke_reason: string | null; revoked_at: string | null; revoked_by: string | null; starts_at: string; workspace_id: string | null

FK entitlement_overrides_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

FK entitlement_overrides_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

experiment_assignments

active: boolean; arm: string; baseline: Json; created_at: string; excluded_at: string | null; excluded_reason: string | null; experiment_id: string; id: string; page_url: string; path: string; site_host: string; stratum: number; workspace_id: string

FK experiment_assignments_experiment_id_fkey: (experiment_id) -> experiments (id); one-to-one false

FK experiment_assignments_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

experiment_changes

after: string; before: string | null; created_at: string; experiment_id: string; field: string; grounding: Json; id: string; path: string; workspace_id: string

FK experiment_changes_experiment_id_fkey: (experiment_id) -> experiments (id); one-to-one false

FK experiment_changes_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

experiment_deliveries

agent_run_id: string | null; approved_at: string | null; approved_by: string | null; base_branch: string | null; base_sha: string | null; commit_sha: string | null; content_hash: string | null; created_at: string; created_by: string | null; error: string | null; experiment_id: string | null; fields: string[]; files: Json; head_branch: string | null; id: string; kind: string; live_at: string | null; merged_at: string | null; pr_number: number | null; pr_state: string | null; pr_url: string | null; source_id: string | null; status: string; template_files: string[]; updated_at: string; validation: Json; workspace_id: string

FK experiment_deliveries_experiment_id_fkey: (experiment_id) -> experiments (id); one-to-one false

FK experiment_deliveries_source_id_fkey: (source_id) -> workspace_sources (id); one-to-one false

FK experiment_deliveries_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

experiment_events

actor_id: string | null; created_at: string; data: Json; experiment_id: string; id: string; kind: string; summary: string; workspace_id: string

FK experiment_events_experiment_id_fkey: (experiment_id) -> experiments (id); one-to-one false

FK experiment_events_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

experiment_jobs

attempts: number; created_at: string; experiment_id: string; finished_at: string | null; id: string; kind: string; last_error: string | null; lease_until: string | null; locked_by: string | null; max_attempts: number; next_attempt_at: string; payload: Json; status: string; updated_at: string; workspace_id: string

FK experiment_jobs_experiment_id_fkey: (experiment_id) -> experiments (id); one-to-one false

FK experiment_jobs_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

experiment_metric_days

complete: boolean; date: string; experiment_id: string; pulled_at: string; source: string; workspace_id: string

FK experiment_metric_days_experiment_id_fkey: (experiment_id) -> experiments (id); one-to-one false

FK experiment_metric_days_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

experiment_metrics_daily

ai_referral_sessions: number; arm: string; clicks: number; date: string; experiment_id: string; impressions: number; key_events: number; path: string; position_weighted: number; revenue: number; sessions: number; updated_at: string; workspace_id: string

FK experiment_metrics_daily_experiment_id_fkey: (experiment_id) -> experiments (id); one-to-one false

FK experiment_metrics_daily_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

experiment_page_groups

created_at: string; detected_at: string; eligibility: Json; id: string; label: string; monthly_clicks: number; page_count: number; paths: string[]; pattern: string; rule: Json; source_id: string; template_file: string | null; updated_at: string; workspace_id: string

FK experiment_page_groups_source_id_fkey: (source_id) -> workspace_sources (id); one-to-one false

FK experiment_page_groups_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

experiments

approved_at: string | null; approved_by: string | null; approved_patch_hash: string | null; assignment_attempts: number | null; assignment_seed: number | null; cancelled_at: string | null; change_type: string; closed_at: string | null; closed_via: string | null; concluded_at: string | null; created_at: string; created_by: string | null; estimated_monthly_units: number | null; estimated_monthly_value: number | null; ga4_source_id: string | null; gsc_source_id: string | null; hypothesis: string; id: string; invalid_reason: string | null; invalidated_at: string | null; last_checkpoint_day: number | null; lift: number | null; lift_high: number | null; lift_low: number | null; live_confirmed_at: string | null; mde_estimate: number | null; name: string; page_group_id: string | null; planned_max_days: number; planned_min_days: number; pre_period_end: string | null; pre_period_start: string | null; primary_metric: string; result: Json; revenue_basis: Json; secondary_metrics: string[]; shipped_at: string | null; site_host: string; source_id: string | null; status: string; updated_at: string; value_currency: string | null; verdict: string | null; workspace_id: string

FK experiments_ga4_source_id_fkey: (ga4_source_id) -> analytics_sources (id); one-to-one false

FK experiments_gsc_source_id_fkey: (gsc_source_id) -> analytics_sources (id); one-to-one false

FK experiments_page_group_id_fkey: (page_group_id) -> experiment_page_groups (id); one-to-one false

FK experiments_source_id_fkey: (source_id) -> workspace_sources (id); one-to-one false

FK experiments_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

geo_agent_events

actor: string; at: string; detail: Json; id: number; kind: string; run_id: string; stage: string | null; summary: string; user_id: string | null; workspace_id: string

FK geo_agent_events_run_id_fkey: (run_id) -> geo_agent_runs (id); one-to-one false

FK geo_agent_events_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

geo_agent_runs

attempts: number; base_branch: string | null; base_sha: string | null; batch_id: string | null; cancel_requested_at: string | null; checkpoint: Json | null; completed_at: string | null; connection_id: string | null; correction_rounds: number; created_at: string; created_by: string | null; error: string | null; error_code: string | null; failed_at_step: string | null; feedback: string | null; files_inspected: Json; finding_id: string | null; fingerprint: string; framework: string | null; id: string; inputs: Json; kind: string; lease_until: string | null; locked_by: string | null; max_attempts: number; model: string | null; next_attempt_at: string; page_url: string | null; parent_run_id: string | null; patch: Json | null; plan: Json | null; plan_approved_at: string | null; plan_approved_by: string | null; plan_hash: string | null; plan_ready_at: string | null; plan_revision: number; proposal_id: string | null; provider: string; repo_external_id: string | null; repo_full_name: string | null; result: Json | null; review: Json | null; rule_id: string; scan_id: string | null; site_host: string; site_origin: string; site_ref: Json | null; source_id: string | null; status: string; status_detail: string | null; updated_at: string; usage: Json; validation: Json | null; verification_id: string | null; workspace_id: string

FK geo_agent_runs_batch_id_fkey: (batch_id) -> geo_fix_batches (id); one-to-one false

FK geo_agent_runs_connection_id_fkey: (connection_id) -> workspace_connections (id); one-to-one false

FK geo_agent_runs_finding_id_fkey: (finding_id) -> geo_findings (id); one-to-one false

FK geo_agent_runs_parent_run_id_fkey: (parent_run_id) -> geo_agent_runs (id); one-to-one false

FK geo_agent_runs_proposal_id_fkey: (proposal_id) -> geo_fix_proposals (id); one-to-one false

FK geo_agent_runs_scan_id_fkey: (scan_id) -> geo_scans (id); one-to-one false

FK geo_agent_runs_source_id_fkey: (source_id) -> workspace_sources (id); one-to-one false

FK geo_agent_runs_verification_id_fkey: (verification_id) -> geo_verifications (id); one-to-one false

FK geo_agent_runs_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

geo_audit_runs

created_at: string; created_by: string | null; id: string; meta: Json; score: number; subscores: Json; url: string | null; workspace_id: string

FK geo_audit_runs_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

geo_finding_states

dismiss_reason: string | null; fingerprint: string; note: string | null; reopened_at: string | null; resolved_via: string | null; reviewed_at: string | null; reviewed_by: string | null; state: string; updated_at: string; updated_by: string | null; verification_id: string | null; verified_at: string | null; workspace_id: string

FK geo_finding_states_verification_id_fkey: (verification_id) -> geo_verifications (id); one-to-one false

FK geo_finding_states_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

geo_findings

category: string; created_at: string; detail: string; effort: string; evidence: Json; fingerprint: string; fix_id: string | null; id: string; page_id: string | null; page_url: string | null; point_impact: number; priority: string; priority_score: number; rule_id: string; safety: string; scan_id: string; severity: string; status: string; title: string; workspace_id: string

FK geo_findings_page_id_fkey: (page_id) -> geo_scan_pages (id); one-to-one false

FK geo_findings_scan_id_fkey: (scan_id) -> geo_scans (id); one-to-one false

FK geo_findings_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

geo_fix_batches

approved_at: string | null; approved_by: string | null; base_branch: string | null; base_sha: string | null; checks: Json | null; cms_changes: Json | null; cms_snapshot: Json | null; commit_sha: string | null; connection_id: string | null; content_hash: string | null; created_at: string; created_by: string | null; error: string | null; explanation: string | null; files: Json; files_purged_at: string | null; framework: string | null; head_branch: string | null; host: string; id: string; items: Json; last_synced_at: string | null; pr_merged_at: string | null; pr_number: number | null; pr_state: string | null; pr_url: string | null; progress: Json; provider: string; repo_external_id: string | null; repo_full_name: string | null; scan_id: string | null; site_origin: string; source_id: string | null; status: string; updated_at: string; validation: Json; workspace_id: string

FK geo_fix_batches_connection_id_fkey: (connection_id) -> workspace_connections (id); one-to-one false

FK geo_fix_batches_scan_id_fkey: (scan_id) -> geo_scans (id); one-to-one false

FK geo_fix_batches_source_id_fkey: (source_id) -> workspace_sources (id); one-to-one false

FK geo_fix_batches_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

geo_fix_proposals

agent_run_id: string | null; applied_at: string | null; approved_at: string | null; approved_by: string | null; base_branch: string | null; base_sha: string | null; batch_id: string | null; checks: Json | null; cms_changes: Json | null; cms_snapshot: Json | null; commit_sha: string | null; connection_id: string | null; content_hash: string | null; created_at: string; created_by: string | null; error: string | null; explanation: string | null; files: Json; files_purged_at: string | null; finding_id: string | null; fingerprint: string; fix_id: string; framework: string | null; head_branch: string | null; id: string; last_synced_at: string | null; model: string | null; page_url: string | null; pr_merged_at: string | null; pr_number: number | null; pr_state: string | null; pr_url: string | null; preview: Json | null; provider: string; repo_external_id: string | null; repo_full_name: string | null; rolled_back_at: string | null; rolled_back_by: string | null; rule_id: string; scan_id: string | null; site_origin: string; site_ref: Json | null; source_id: string | null; status: string; strategy: string | null; updated_at: string; validation: Json; workspace_id: string

FK geo_fix_proposals_agent_run_id_fkey: (agent_run_id) -> geo_agent_runs (id); one-to-one false

FK geo_fix_proposals_batch_id_fkey: (batch_id) -> geo_fix_batches (id); one-to-one false

FK geo_fix_proposals_connection_id_fkey: (connection_id) -> workspace_connections (id); one-to-one false

FK geo_fix_proposals_finding_id_fkey: (finding_id) -> geo_findings (id); one-to-one false

FK geo_fix_proposals_scan_id_fkey: (scan_id) -> geo_scans (id); one-to-one false

FK geo_fix_proposals_source_id_fkey: (source_id) -> workspace_sources (id); one-to-one false

FK geo_fix_proposals_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

geo_prompt_checks

answer_excerpt: string | null; checked_at: string; cited: boolean; cited_urls: Json; competitors_mentioned: Json; engine: string; error: string | null; id: number; mentioned: boolean; model: string; position: number | null; prompt_id: string; web_search: boolean; workspace_id: string

FK geo_prompt_checks_prompt_id_fkey: (prompt_id) -> geo_tracked_prompts (id); one-to-one false

FK geo_prompt_checks_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

geo_scan_pages

analysis: Json | null; category_scores: Json; content_type: string | null; created_at: string; depth: number; fetch_ms: number | null; fetched_at: string | null; final_url: string | null; id: string; issues: number; scan_id: string; score: number | null; skip_reason: string | null; state: string; status_code: number | null; url: string; workspace_id: string; x_robots_tag: string | null

FK geo_scan_pages_scan_id_fkey: (scan_id) -> geo_scans (id); one-to-one false

FK geo_scan_pages_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

geo_scans

attempt_count: number; cancel_requested: boolean; category_scores: Json; completed_at: string | null; config: Json; created_at: string; created_by: string | null; error: string | null; host: string; id: string; idempotency_key: string | null; lease_until: string | null; locked_by: string | null; mode: string; origin: string; overall_score: number | null; previous_scan_id: string | null; probes: Json | null; progress: Json; report: Json | null; scheduled_job_id: string | null; site: Json; stage: string; started_at: string | null; status: string; trigger: string; updated_at: string; url: string; workspace_id: string

FK geo_scans_previous_scan_id_fkey: (previous_scan_id) -> geo_scans (id); one-to-one false

FK geo_scans_scheduled_job_id_fkey: (scheduled_job_id) -> scheduled_jobs (id); one-to-one false

FK geo_scans_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

geo_tracked_prompts

created_at: string; created_by: string | null; id: string; last_checked_at: string | null; lease_until: string | null; next_check_at: string; paused_at: string | null; text: string; workspace_id: string

FK geo_tracked_prompts_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

geo_verifications

after: Json; attempts: number; baseline_scan_id: string | null; batch_id: string | null; before: Json; completed_at: string | null; created_at: string; created_by: string | null; fingerprints: string[]; id: string; lease_until: string | null; locked_by: string | null; max_attempts: number; next_attempt_at: string; origin: string; outcome_detail: string | null; proposal_id: string | null; rule_ids: string[]; scan_id: string | null; status: string; updated_at: string; urls: string[]; workspace_id: string

FK geo_verifications_baseline_scan_id_fkey: (baseline_scan_id) -> geo_scans (id); one-to-one false

FK geo_verifications_batch_id_fkey: (batch_id) -> geo_fix_batches (id); one-to-one false

FK geo_verifications_proposal_id_fkey: (proposal_id) -> geo_fix_proposals (id); one-to-one false

FK geo_verifications_scan_id_fkey: (scan_id) -> geo_scans (id); one-to-one false

FK geo_verifications_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

google_oauth_credentials

access_token_enc: string | null; access_token_expires_at: string | null; connection_id: string; created_at: string; email: string | null; google_sub: string | null; refresh_token_enc: string; scopes: string[]; updated_at: string; workspace_id: string

FK google_oauth_credentials_connection_id_fkey: (connection_id) -> workspace_connections (id); one-to-one true

FK google_oauth_credentials_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

guardrail_events

created_at: string; detail: Json; id: number; kind: string; request_id: string | null; route: string; run_id: string | null; severity: string; user_id: string | null; workspace_id: string | null

FK guardrail_events_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

link_order_events

actor: string | null; at: string; detail: Json; id: string; line_id: string | null; order_id: string; type: string; workspace_id: string

FK link_order_events_line_id_fkey: (line_id) -> link_order_lines (id); one-to-one false

FK link_order_events_order_id_fkey: (order_id) -> link_orders (id); one-to-one false

FK link_order_events_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

link_order_lines

attribution: string; attribution_detail: Json; consecutive_missing: number; created_at: string; credits_price: number; donor_domain: string; donor_id: number; first_live_at: string | null; give_up_at: string | null; id: string; lost_at: string | null; next_check_at: string | null; opportunity_id: string | null; order_id: string; provider_basket_id: number | null; provider_cost_usd: number | null; provider_link_id: number | null; provider_order_content_id: number | null; published_at: string | null; published_url: string | null; settled: string; status: string; unit_price_usd: number; updated_at: string; verification: string; verified_at: string | null; workspace_id: string

FK link_order_lines_donor_id_fkey: (donor_id) -> rixot_donors (id); one-to-one false

FK link_order_lines_opportunity_id_fkey: (opportunity_id) -> backlink_opportunities (id); one-to-one false

FK link_order_lines_order_id_fkey: (order_id) -> link_orders (id); one-to-one false

FK link_order_lines_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

link_orders

attempt_count: number; balance_before_usd: number | null; campaign_id: string | null; charged_is_estimated: boolean; checkout_at: string | null; content_mode: string; created_at: string; created_by: string | null; credit_rate: number; credits_captured: number; credits_held: number; credits_refunded: number; failure_code: string | null; id: string; idempotency_key: string; in_flight_since: string | null; keyword: string; language: string; last_error: string | null; lease_until: string | null; line_count: number; lock_token: string | null; locked_by: string | null; needs_operator: boolean; next_attempt_at: string | null; operator_note: string | null; order_post_attempts: number; ordered_at: string | null; own_content: string | null; own_title: string | null; paid_at: string | null; pay_post_attempts: number; provider_basket_ids: number[]; provider_charged_usd: number | null; provider_order_content_ids: number[]; provider_total_usd: number | null; quoted_usd: number; recommendations: string | null; request_fingerprint: string | null; settled_at: string | null; status: string; substate: string | null; target_url: string; updated_at: string; workspace_id: string

FK link_orders_campaign_id_fkey: (campaign_id) -> backlink_campaigns (id); one-to-one false

FK link_orders_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

market_intelligence_cache

analysis_key: string; analysis_type: string; collection_id: string; context_fingerprint: string; created_at: string; id: string; result: Json; updated_at: string; workspace_id: string

FK market_intelligence_cache_collection_id_fkey: (collection_id) -> market_trend_collections (id); one-to-one false

FK market_intelligence_cache_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

market_trend_collections

completed_at: string | null; id: string; keywords: string[]; location: string | null; normalized_result: Json | null; provider: string; provider_error: Json | null; request_key: string; requested_at: string; status: string; updated_at: string; workspace_id: string

FK market_trend_collections_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

marketing_opportunities

created_at: string; decided_at: string | null; decided_by: string | null; evidence: Json; expires_at: string; fingerprint: string; id: string; kind: string; score: number; score_parts: Json; source_id: string | null; source_kind: string; status: string; suggested_action: string; suggested_platforms: string[]; suggested_type: string; summary: string; title: string; updated_at: string; why_relevant: string; workspace_id: string

FK marketing_opportunities_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

mcp_tool_calls

client_id: string | null; created_at: string; duration_ms: number; error_code: string | null; id: string; is_write: boolean; ok: boolean; summary: Json; tool: string; user_id: string | null; workspace_id: string | null

FK mcp_tool_calls_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

mcp_workspace_settings

allow_writes: boolean; enabled: boolean; updated_at: string; updated_by: string | null; workspace_id: string

FK mcp_workspace_settings_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one true

memory_insights

body: string; created_at: string; created_by: string | null; id: string; kind: string; meta: Json; source_label: string | null; updated_at: string; workspace_id: string

FK memory_insights_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

meter_balances

account_id: string; available: number; available_any: number; debt: number; held: number; meter: string; updated_at: string

FK meter_balances_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

meter_grants

account_id: string; amount: number; clawed_back: number; created_at: string; expires_at: string | null; id: string; idempotency_key: string; meter: string; period_start: string | null; provider_ref: string | null; remaining: number; restriction: string; source: string; workspace_id: string | null

FK meter_grants_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

meter_holds

account_id: string; action: string; allocations: Json; amount: number; captured_amount: number; created_at: string; expires_at: string; finalized_at: string | null; id: string; idempotency_key: string; meter: string; state: string; user_id: string | null; workspace_id: string | null

FK meter_holds_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

meter_ledger

account_id: string; action: string | null; actor: string | null; available_after: number; charge_id: string | null; created_at: string; delta_available: number; delta_held: number; grant_id: string | null; held_after: number; hold_id: string | null; id: number; idempotency_key: string; kind: string; meter: string; reason: string | null; user_id: string | null; workspace_id: string | null

FK meter_ledger_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

model_route_overrides

effort: string | null; models: string[] | null; reason: string | null; route_key: string; updated_at: string; updated_by: string | null

notion_content_mappings

content_item_id: string; created_at: string; id: string; last_mellox_hash: string | null; last_mellox_updated_at: string | null; last_notion_edited_at: string | null; last_notion_hash: string | null; last_sync_direction: string | null; last_sync_hash: string | null; notion_data_source_id: string; notion_page_id: string; updated_at: string; workspace_id: string

FK notion_content_mappings_content_item_id_fkey: (content_item_id) -> content_items (id); one-to-one false

FK notion_content_mappings_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

notion_oauth_credentials

access_token_enc: string; bot_id: string | null; connection_id: string; created_at: string; last_sync_at: string | null; selected_data_source_id: string | null; selected_database_id: string | null; selected_destination_name: string | null; selected_destination_url: string | null; selected_parent_page_id: string | null; sync_lock_owner: string | null; sync_lock_until: string | null; updated_at: string; workspace_id: string

FK notion_oauth_credentials_connection_id_fkey: (connection_id) -> workspace_connections (id); one-to-one true

FK notion_oauth_credentials_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

platform_announcements

active: boolean; body: string; created_at: string; created_by: string | null; dismissible: boolean; ends_at: string | null; id: string; link_url: string | null; starts_at: string; title: string; tone: string; updated_at: string

platform_flags

created_at: string; description: string; enabled: boolean; expires_at: string | null; key: string; rollout_percent: number; updated_at: string; updated_by: string | null; workspace_ids: string[]

platform_switches

changed_at: string; changed_by: string | null; engaged: boolean; key: string; reason: string | null

profiles

app_tour_seen_at: string | null; avatar_url: string | null; created_at: string; id: string; name: string | null; persona: string | null; persona_set_at: string | null

provider_basket_lock

acquired_at: string | null; holder: string | null; lease_until: string | null; order_id: string | null; phase: string | null; provider: string; quarantine_reason: string | null; quarantined: boolean; quarantined_at: string | null; released_at: string | null; renewed_at: string | null; takeover_count: number; token: string | null

FK provider_basket_lock_order_id_fkey: (order_id) -> link_orders (id); one-to-one false

referrals

created_at: string; id: string; referred_account_id: string; referrer_account_id: string; rewarded_at: string | null; status: string

FK referrals_referred_account_id_fkey: (referred_account_id) -> billing_accounts (id); one-to-one true

FK referrals_referrer_account_id_fkey: (referrer_account_id) -> billing_accounts (id); one-to-one false

rixot_donors

backlinks: number | null; cat: string | null; delisted_at: string | null; dfs_rank: number | null; domain: string; domain_hidden: boolean; dr: number | null; ext: string | null; first_seen_at: string; id: number; last_seen_at: string; page: string | null; price_usd: number; referring_domains: number | null; top100: number | null; topic: Json | null; topic_checked_at: string | null

rixot_link_sightings

claim_method: string | null; claimed_at: string | null; claimed_by: string | null; cost_usd: number | null; first_seen_at: string; keyword: string | null; last_seen_at: string; link_id: number; published_host: string | null; published_url: string | null; raw: Json; status: string | null; target_url: string | null; unclaimed_reason: string | null

FK rixot_link_sightings_claimed_by_fkey: (claimed_by) -> link_order_lines (id); one-to-one false

scheduled_jobs

active: boolean; agent: string; cadence: string; channel: string | null; created_at: string; created_by: string | null; id: string; last_content_item_id: string | null; last_run_at: string | null; last_run_error: string | null; last_run_status: string | null; locked_at: string | null; locked_by: string | null; meta: Json; next_run_at: string; prompt: string | null; run_count: number; task_type: string; timezone: string; title: string; updated_at: string; workspace_id: string

FK scheduled_jobs_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

sdr_webhook_events

account_id: string | null; delivery_id: string | null; event: string | null; id: number; outcome: string; provider: string; reason: string; received_at: string; sdr_post_id: string | null; sdr_target_id: string | null; workspace_id: string | null

FK sdr_webhook_events_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

site_blog_settings

blog_url: string | null; content_dir: string | null; created_at: string; detected_at: string | null; frontmatter: Json | null; host: string; id: string; post_format: string | null; provider: string; route_prefix: string | null; setup: Json | null; setup_run_id: string | null; source_id: string | null; status: string; status_detail: string | null; updated_at: string; webflow_collection_id: string | null; webflow_field_map: Json | null; workspace_id: string; wp_category_id: number | null; wp_posts_page_id: number | null

FK site_blog_settings_setup_run_id_fkey: (setup_run_id) -> geo_agent_runs (id); one-to-one false

FK site_blog_settings_source_id_fkey: (source_id) -> workspace_sources (id); one-to-one false

FK site_blog_settings_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

site_publications

approved_by: string | null; attempts: number; content_item_id: string; created_at: string; external_id: string | null; head_branch: string | null; host: string; id: string; last_error: string | null; lease_until: string | null; locked_by: string | null; max_attempts: number; next_attempt_at: string; payload_hash: string | null; pr_number: number | null; pr_url: string | null; provider: string; published_at: string | null; scheduled_for: string | null; slug: string; status: string; status_detail: string | null; title: string; updated_at: string; url: string | null; verification: Json | null; verified_at: string | null; workspace_id: string

FK site_publications_content_item_id_fkey: (content_item_id) -> content_items (id); one-to-one false

FK site_publications_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

slack_action_refs

action: string; consumed_at: string | null; content_item_id: string | null; context: Json; created_at: string; expires_at: string; id: string; installation_id: string; workspace_id: string

FK slack_action_refs_content_item_id_fkey: (content_item_id) -> content_items (id); one-to-one false

FK slack_action_refs_installation_id_workspace_id_fkey: (installation_id, workspace_id) -> slack_installations (id, workspace_id); one-to-one false

FK slack_action_refs_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

slack_channel_mappings

channel_id: string; channel_name: string; created_at: string; id: string; installation_id: string; purpose: string; team_id: string; workspace_id: string

FK slack_channel_mappings_installation_id_team_id_fkey: (installation_id, team_id) -> slack_installations (id, team_id); one-to-one false

FK slack_channel_mappings_installation_id_workspace_id_fkey: (installation_id, workspace_id) -> slack_installations (id, workspace_id); one-to-one false

slack_inbox

attempts: number; completed_at: string | null; created_at: string; delivery_key: string; id: string; installation_id: string; kind: string; last_error: string | null; lease_until: string | null; next_attempt_at: string; payload: Json; status: string; workspace_id: string

FK slack_inbox_installation_id_workspace_id_fkey: (installation_id, workspace_id) -> slack_installations (id, workspace_id); one-to-one false

slack_installations

bot_token_enc: string; bot_user_id: string; connected_by: string | null; created_at: string; id: string; last_error: string | null; last_event_at: string | null; last_outbound_at: string | null; status: string; team_id: string; team_name: string; updated_at: string; workspace_id: string

FK slack_installations_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

slack_link_codes

code_hash: string; consumed_at: string | null; expires_at: string; id: string; installation_id: string; mellox_user_id: string; workspace_id: string

FK slack_link_codes_installation_id_workspace_id_fkey: (installation_id, workspace_id) -> slack_installations (id, workspace_id); one-to-one false

slack_outbound

attempts: number; channel_id: string; created_at: string; dedupe_key: string; id: string; installation_id: string; last_error: string | null; lease_until: string | null; next_attempt_at: string; payload: Json; sent_at: string | null; slack_ts: string | null; status: string; workspace_id: string

FK slack_outbound_installation_id_workspace_id_fkey: (installation_id, workspace_id) -> slack_installations (id, workspace_id); one-to-one false

slack_preferences

approvals: boolean; brief_hour: number; brief_timezone: string; competitor_alerts: boolean; daily_brief: boolean; geo_alerts: boolean; market_alerts: boolean; performance_alerts: boolean; publishing_failures: boolean; updated_at: string; workspace_id: string

FK slack_preferences_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one true

slack_threads

channel_id: string; installation_id: string; messages: Json; thread_ts: string; updated_at: string; workspace_id: string

FK slack_threads_installation_id_workspace_id_fkey: (installation_id, workspace_id) -> slack_installations (id, workspace_id); one-to-one false

slack_user_links

id: string; installation_id: string; linked_at: string; mellox_user_id: string; slack_user_id: string; workspace_id: string

FK slack_user_links_installation_id_workspace_id_fkey: (installation_id, workspace_id) -> slack_installations (id, workspace_id); one-to-one false

social_accounts

avatar_url: string | null; brand_id: string | null; connected_at: string; connected_by: string | null; created_at: string; disconnected_at: string | null; display_name: string | null; id: string; last_synced_at: string; platform: string; provider: string; provider_account_id: string; reconnect_reason: string | null; status: string; updated_at: string; username: string | null; workspace_id: string

FK social_accounts_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

social_oauth_states

connection_id: string | null; consumed_at: string | null; created_at: string; expires_at: string; id: string; platform: string; provider: string; state_hash: string; user_id: string; workspace_id: string

FK social_oauth_states_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

social_trend_snapshots

claimed_at: string | null; collected_at: string | null; error: string | null; scope: string; sources: Json; status: string; trends: Json; updated_at: string

social_usage_events

content_item_id: string | null; created_at: string; id: number; operation: string; provider: string; provider_post_id: string | null; targets: number; user_id: string | null; workspace_id: string

FK social_usage_events_content_item_id_fkey: (content_item_id) -> content_items (id); one-to-one false

FK social_usage_events_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

spend_caps

daily_usd: number | null; id: string; monthly_usd: number | null; reason: string | null; scope: string; updated_at: string; updated_by: string | null; workspace_id: string | null

FK spend_caps_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

stripe_events

error: string | null; id: string; payload: Json; processed_at: string | null; received_at: string; type: string; workspace_id: string | null

FK stripe_events_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

studio_jobs

asset_ids: string[]; attempt: number; completed_at: string | null; content_item_ids: string[]; created_at: string; created_by: string | null; error: Json | null; group_id: string; id: string; idempotency_key: string; input: Json; lease_until: string | null; output: Json; parent_job_id: string | null; provider_tasks: Json; stage: string; stage_at: string; status: string; title: string | null; type: string; updated_at: string; workspace_id: string

FK studio_jobs_parent_job_id_fkey: (parent_job_id) -> studio_jobs (id); one-to-one false

FK studio_jobs_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

ugc_projects

brand_snapshot: Json; brief: Json; concepts: Json; created_at: string; created_by: string | null; id: string; product: Json; product_url: string | null; reference_asset_ids: string[]; script: Json | null; selected_concept_id: string | null; status: string; title: string; updated_at: string; workspace_id: string

FK ugc_projects_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

ugc_renders

actual_cost_usd: number | null; aspect_ratio: string; asset_id: string | null; attempts: number; audio: boolean; billing_ready: boolean; completed_at: string | null; created_at: string; created_by: string | null; duration_sec: number; error_code: string | null; error_message: string | null; est_cost_usd: number; generation_type: string; id: string; idempotency_key: string; lease_until: string | null; locked_by: string | null; max_attempts: number; model_key: string; next_attempt_at: string; project_id: string; prompt: string; provider: string; provider_meta: Json; provider_model: string; provider_state: string | null; provider_task_id: string | null; provider_variant: string | null; reference_asset_ids: string[]; reservation_id: string | null; resolution: string; script: Json; settings: Json; status: string; submit_attempts: number; submitted_at: string | null; updated_at: string; workspace_id: string

FK ugc_renders_asset_id_fkey: (asset_id) -> assets (id); one-to-one false

FK ugc_renders_project_id_fkey: (project_id) -> ugc_projects (id); one-to-one false

FK ugc_renders_reservation_id_fkey: (reservation_id) -> ai_usage_reservations (id); one-to-one false

FK ugc_renders_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

upgrade_requests

account_id: string; created_at: string; feature: string; id: string; message: string | null; requested_by: string; required_plan: string | null; status: string; updated_at: string; workspace_id: string

FK upgrade_requests_account_id_fkey: (account_id) -> billing_accounts (id); one-to-one false

webflow_oauth_credentials

access_token_enc: string; access_token_expires_at: string | null; connection_id: string; created_at: string; refresh_token_enc: string | null; scopes: string[]; updated_at: string; webflow_user_email: string | null; webflow_user_id: string | null; workspace_id: string

FK webflow_oauth_credentials_connection_id_fkey: (connection_id) -> workspace_connections (id); one-to-one true

FK webflow_oauth_credentials_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

webflow_sites

connection_id: string; created_at: string; domain: string | null; domains: string[]; id: string; last_error: string | null; last_synced_at: string | null; preview_url: string | null; selected: boolean; short_name: string | null; site_id: string; site_name: string; status: string; updated_at: string; workspace_id: string

FK webflow_sites_connection_id_fkey: (connection_id) -> workspace_connections (id); one-to-one false

FK webflow_sites_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

wordpress_credentials

api_namespaces: string[]; application_password_enc: string; connection_id: string; created_at: string; site_description: string | null; site_home: string | null; site_name: string | null; site_url: string; updated_at: string; username: string; workspace_id: string

FK wordpress_credentials_connection_id_fkey: (connection_id) -> workspace_connections (id); one-to-one true

FK wordpress_credentials_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

wordpress_oauth_credentials

access_token_enc: string; access_token_expires_at: string | null; connection_id: string; created_at: string; refresh_token_enc: string | null; scopes: string[]; updated_at: string; wordpress_user_id: string | null; wordpress_user_login: string | null; workspace_id: string

FK wordpress_oauth_credentials_connection_id_fkey: (connection_id) -> workspace_connections (id); one-to-one true

FK wordpress_oauth_credentials_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

wordpress_sites

api_namespaces: string[]; connection_id: string; created_at: string; id: string; last_error: string | null; last_synced_at: string | null; plugin_checked_at: string | null; selected: boolean; site_name: string; site_url: string; status: string; updated_at: string; wordpress_site_id: string | null; workspace_id: string

FK wordpress_sites_connection_id_fkey: (connection_id) -> workspace_connections (id); one-to-one false

FK wordpress_sites_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

workspace_access_state

changed_at: string; changed_by: string | null; mode: string; reason: string | null; workspace_id: string

FK workspace_access_state_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one true

workspace_agent_settings

agents_paused: boolean; disabled_workers: string[]; updated_at: string; updated_by: string | null; workspace_id: string

FK workspace_agent_settings_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one true

workspace_brand_dna

created_at: string; dna: Json; updated_at: string; updated_by: string | null; version: number; workspace_id: string

FK workspace_brand_dna_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one true

workspace_competitors

attempt_count: number; confidence: number; created_at: string; created_by: string | null; discovery_sources: Json; domain: string; id: string; lease_until: string | null; locked_by: string | null; name: string; next_check_at: string | null; profile: Json | null; profile_error: string | null; profile_status: string; profile_updated_at: string | null; rationale: string | null; relationship: string; source: string; status: string; updated_at: string; updates_checked_at: string | null; url: string | null; workspace_id: string

FK workspace_competitors_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

workspace_connections

account_avatar_url: string | null; account_login: string; account_type: string | null; connected_by: string | null; created_at: string; external_account_id: string; id: string; last_error: string | null; last_verified_at: string | null; manage_url: string | null; metadata: Json; permissions: Json; provider: string; repository_selection: string | null; revoked_at: string | null; revoked_reason: string | null; status: string; updated_at: string; verification: string; workspace_id: string

FK workspace_connections_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

workspace_create_requests

created_at: string; idempotency_key: string; user_id: string; workspace_id: string | null

FK workspace_create_requests_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

workspace_credit_balances

available: number; held: number; lifetime_spent: number; lifetime_topped_up: number; updated_at: string; workspace_id: string

FK workspace_credit_balances_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one true

workspace_credit_ledger

actor: string | null; balance_after: number; created_at: string; delta_available: number; delta_held: number; held_after: number; id: number; idempotency_key: string; kind: string; line_id: string | null; order_id: string | null; reason: string | null; workspace_id: string

FK workspace_credit_ledger_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

workspace_deletions

created_at: string; deleted_by: string | null; domain: string | null; id: string; owner_id: string | null; storage_objects_removed: number; workspace_id: string; workspace_name: string | null

workspace_invites

accepted_at: string | null; created_at: string; email: string; id: string; invited_by: string; role: string; token: string; workspace_id: string

FK workspace_invites_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

workspace_marketing_strategy

built_from: Json; confirmed_at: string | null; confirmed_by: string | null; created_at: string; generated_at: string | null; generations: number; source_fingerprint: string | null; status: string; strategy: Json; updated_at: string; updated_by: string | null; version: number; workspace_id: string

FK workspace_marketing_strategy_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one true

workspace_members

created_at: string; id: string; role: Database["public"]["Enums"]["app_role"]; user_id: string; workspace_id: string

FK workspace_members_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

workspace_memories

body: string; conversation_id: string | null; created_at: string; created_by: string | null; expires_at: string | null; fingerprint: string; id: string; kind: string; source: string; status: string; topic: string; updated_at: string; updated_by: string | null; workspace_id: string

FK workspace_memories_conversation_id_fkey: (conversation_id) -> conversations (id); one-to-one false

FK workspace_memories_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

workspace_memory_settings

created_at: string; enabled: boolean; updated_at: string; updated_by: string | null; workspace_id: string

FK workspace_memory_settings_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one true

workspace_report_branding

created_at: string; display_name: string | null; logo_path: string | null; updated_at: string; updated_by: string | null; workspace_id: string

FK workspace_report_branding_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one true

workspace_sdr

created_at: string; encrypted_api_key: string; id: string; last_provisioned_at: string | null; sdr_base_url: string; sdr_workspace_id: string; status: string; updated_at: string; webhook_secret: string | null; workspace_id: string

FK workspace_sdr_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one true

workspace_socialapi

brand_id: string | null; created_at: string; id: string; last_error: string | null; status: string; updated_at: string; workspace_id: string

FK workspace_socialapi_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one true

workspace_sources

agent_consent_at: string | null; agent_consent_by: string | null; branch: string | null; connection_id: string; created_at: string; default_branch: string | null; external_id: string; full_name: string; html_url: string | null; id: string; inspection: Json | null; kind: string; last_error: string | null; last_synced_at: string | null; name: string; owner_login: string | null; ownership_checked_at: string | null; ownership_checked_by: string | null; ownership_commit_sha: string | null; ownership_confidence: number | null; ownership_evidence: Json; ownership_hints: Json; ownership_site_host: string | null; ownership_status: string; private: boolean; provider: string; selected_by: string | null; site_host: string | null; site_url: string | null; status: string; updated_at: string; workspace_id: string

FK workspace_sources_connection_id_fkey: (connection_id) -> workspace_connections (id); one-to-one false

FK workspace_sources_workspace_id_fkey: (workspace_id) -> workspaces (id); one-to-one false

workspaces

audience: string | null; billing_account_id: string; brand_voice: Json; client_status: Database["public"]["Enums"]["client_status"]; connected_provider: string | null; created_at: string; domain: string | null; duplicate_of: string | null; first_prompt: string | null; frozen_at: string | null; frozen_reason: string | null; goals: string | null; id: string; industry: string | null; monthly_credit_cap: number | null; name: string; onboarded_at: string | null; owner_id: string; plan: string; website_url: string | null

FK workspaces_billing_account_id_fkey: (billing_account_id) -> billing_accounts (id); one-to-one false

FK workspaces_duplicate_of_fkey: (duplicate_of) -> workspaces (id); one-to-one false

16 Latest SQL addition not yet in generated types

The source audit found one table created by the current migration sequence that is not represented in the checked-in generated Row dictionary: video_compositions. Keep this SQL-only addition alongside the 179 typed tables. Regenerate types after applying the migration in the intended environment; do not omit the table when rebuilding longer-video support.

Column	Exact SQL declaration
id	uuid PRIMARY KEY
revision	integer NOT NULL DEFAULT 0
lease_until	timestamptz; nullable
state	jsonb NOT NULL
created_at	timestamptz NOT NULL DEFAULT now()

RLS is enabled. All privileges are revoked from anon and authenticated; service_role receives access. State contains the render request, clip target and render lengths, accepted provider task IDs, provider identity, available video URLs/cost and submission progress. The worker uses revision comparison and lease_until to coordinate writes. Sensitive state must remain server-only.

Implementation sources: supabase/migrations/20261021090000_video_compositions.sql; src/server/ugc/providers/composition.server.ts

17 Database function contract index

These are the 107 generated public-schema function signatures. They may be protected by SQL grants or intended for service role only. The presence of a function here is not permission for an authenticated browser to invoke it. Private-schema functions and functions absent from generated types require the SQL source.

accept_billed_workspace_invite

{ Args: { p_token: string; p_user: string; p_email: string; p_seat_limit?: number }; Returns: string; }

accept_workspace_invite

{ Args: { _token: string }; Returns: string }

account_billable_seat_count

{ Args: { p_account: string }; Returns: number }

account_has_billable_member

{ Args: { p_account: string; p_user: string }; Returns: boolean; }

account_wallet

{ Args: { p_account: string }; Returns: { meter: string; available: number; held: number; available_any: number; debt: number; }[]; }

acquire_provider_lock

{ Args: { p_provider: string; p_holder: string; p_order_id?: string; p_lease_seconds?: number; }; Returns: Json; }

activate_billing_social_profile_slot

{ Args: { p_workspace: string }; Returns: undefined }

activate_brand_visual_profile

{ Args: { p_workspace: string; p_profile: string; p_expected: string }; Returns: undefined; }

admin_abuse_signals

{ Args: never; Returns: Json }

admin_analytics

{ Args: { p_days: number }; Returns: Json }

admin_announcement_save

{ Args: { p_actor: string; p_actor_role: string; p_id: string; p_title: string; p_body: string; p_tone: string; p_link_url: string; p_dismissible: boolean; p_active: boolean; p_starts_at: string; p_ends_at: string; p_reason: string; p_request_id: string; p_ip: string; p_user_agent: string; }; Returns: Json; }

admin_emails_for

{ Args: { p_ids: string[] }; Returns: { id: string; email: string }[] }

admin_flag_save

{ Args: { p_actor: string; p_actor_role: string; p_key: string; p_description: string; p_enabled: boolean; p_rollout: number; p_workspaces: string[]; p_expires_at: string; p_reason: string; p_request_id: string; p_ip: string; p_user_agent: string; }; Returns: Json; }

admin_health

{ Args: never; Returns: Json }

admin_integrations

{ Args: never; Returns: Json }

admin_jobs

{ Args: { p_source: string; p_state: string; p_limit: number; p_offset: number }; Returns: Json; }

admin_lookup

{ Args: { p_query: string; p_match_email: boolean }; Returns: Json }

admin_override_create

{ Args: { p_actor: string; p_actor_role: string; p_account: string; p_workspace: string; p_kind: string; p_key: string; p_allowed: boolean; p_limit_value: number; p_starts_at: string; p_expires_at: string; p_reason: string; p_request_id: string; p_ip: string; p_user_agent: string; }; Returns: Json; }

admin_override_revoke

{ Args: { p_actor: string; p_actor_role: string; p_id: string; p_reason: string; p_request_id: string; p_ip: string; p_user_agent: string; }; Returns: Json; }

admin_overview

{ Args: never; Returns: Json }

admin_route_override_set

{ Args: { p_actor: string; p_actor_role: string; p_route: string; p_models: string[]; p_effort: string; p_reason: string; p_request_id: string; p_ip: string; p_user_agent: string; }; Returns: Json; }

admin_spend_cap_set

{ Args: { p_actor: string; p_actor_role: string; p_scope: string; p_workspace: string; p_daily: number; p_monthly: number; p_reason: string; p_request_id: string; p_ip: string; p_user_agent: string; }; Returns: Json; }

admin_switch_set

{ Args: { p_actor: string; p_actor_role: string; p_key: string; p_engaged: boolean; p_reason: string; p_request_id: string; p_ip: string; p_user_agent: string; }; Returns: Json; }

admin_team_save

{ Args: { p_actor: string; p_actor_role: string; p_user: string; p_role: string; p_status: string; p_extra: string[]; p_denied: string[]; p_note: string; p_reason: string; p_request_id: string; p_ip: string; p_user_agent: string; }; Returns: Json; }

admin_usage

{ Args: { p_days: number }; Returns: Json }

admin_user_add_note

{ Args: { p_actor: string; p_actor_role: string; p_user: string; p_body: string; p_request_id: string; p_ip: string; p_user_agent: string; }; Returns: Json; }

admin_user_directory

{ Args: { p_search: string; p_filter: string; p_sort: string; p_limit: number; p_offset: number; }; Returns: Json; }

admin_user_revoke_sessions

{ Args: { p_actor: string; p_actor_role: string; p_user: string; p_reason: string; p_request_id: string; p_ip: string; p_user_agent: string; }; Returns: Json; }

admin_user_set_suspended

{ Args: { p_actor: string; p_actor_role: string; p_user: string; p_suspend: boolean; p_reason: string; p_request_id: string; p_ip: string; p_user_agent: string; }; Returns: Json; }

admin_user_stats

{ Args: { p_user: string }; Returns: Json }

admin_view_end

{ Args: { p_actor: string; p_actor_role: string; p_session: string; p_request_id: string; p_ip: string; p_user_agent: string; }; Returns: Json; }

admin_view_read

{ Args: { p_actor: string; p_actor_role: string; p_session: string; p_section: string; p_request_id: string; p_ip: string; p_user_agent: string; }; Returns: Json; }

admin_view_start

{ Args: { p_actor: string; p_actor_role: string; p_workspace: string; p_reason: string; p_request_id: string; p_ip: string; p_user_agent: string; }; Returns: Json; }

admin_workspace_directory

{ Args: { p_search: string; p_filter: string; p_limit: number; p_offset: number }; Returns: Json; }

admin_workspace_members

{ Args: { p_workspace: string }; Returns: Json }

admin_workspace_set_access

{ Args: { p_actor: string; p_actor_role: string; p_workspace: string; p_mode: string; p_reason: string; p_request_id: string; p_ip: string; p_user_agent: string; }; Returns: Json; }

ai_usage_summary

{ Args: { p_scope_key: string }; Returns: { today_cost_usd: number; month_cost_usd: number; month_images: number; month_videos: number; month_calls: number; month_cached_calls: number; month_saved_usd: number; }[]; }

analytics_ga4_dimension_totals

{ Args: { p_source_id: string; p_dimension: string; p_from: string; p_to: string; p_limit?: number; }; Returns: { value: string; sessions: number; screen_page_views: number; key_events: number; }[]; }

analytics_gsc_dimension_totals

{ Args: { p_source_id: string; p_dimension: string; p_from: string; p_to: string; p_limit?: number; }; Returns: { value: string; clicks: number; impressions: number; position_weighted: number; }[]; }

apply_credit_entry

{ Args: { p: Json }; Returns: Json }

auth_user_id_for_email

{ Args: { p_email: string }; Returns: string }

autopilot_overview

{ Args: never; Returns: { workspace_id: string; program_id: string; status: string; pause_reason: string; mode: string; ends_on: string; needs_approval: number; plan_waiting: number; new_opportunities: number; failures: number; missed: number; performance_warnings: number; next_action_at: string; next_action_title: string; }[]; }

backlink_spent_credits

{ Args: { p_workspace: string }; Returns: number }

billing_margin_report

{ Args: never; Returns: Json }

billing_rollout_report

{ Args: never; Returns: Json }

call_app_hook

{ Args: { p_path: string }; Returns: number }

capture_ai_usage_reservation

{ Args: { p_id: string; p_actual_cost_usd?: number; p_latency_ms?: number }; Returns: boolean; }

change_billed_workspace_member_role

{ Args: { p_workspace: string; p_user: string; p_role: Database["public"]["Enums"]["app_role"]; p_seat_limit?: number; }; Returns: undefined; }

claim_analytics_sync_runs

{ Args: { p_worker: string; p_max?: number; p_lease_seconds?: number; p_id?: string }; Returns: Database["public"]["Tables"]["analytics_sync_runs"]["Row"][]; }

claim_audience_runs

{ Args: { p_worker: string; p_max?: number; p_lease_seconds?: number; p_id?: string }; Returns: Database["public"]["Tables"]["audience_runs"]["Row"][]; }

claim_autopilot_actions

{ Args: { p_worker: string; p_max?: number; p_lease_seconds?: number; p_id?: string }; Returns: Database["public"]["Tables"]["autopilot_actions"]["Row"][]; }

claim_competitor_jobs

{ Args: { p_worker: string; p_max?: number; p_lease_seconds?: number; p_competitor_id?: string; }; Returns: Database["public"]["Tables"]["workspace_competitors"]["Row"][]; }

claim_due_scheduled_jobs

{ Args: { p_max?: number; p_lease_seconds?: number; p_market_brain?: boolean; p_job_id?: string; }; Returns: Database["public"]["Tables"]["scheduled_jobs"]["Row"][]; }

claim_experiment_jobs

{ Args: { p_worker: string; p_max?: number; p_lease_seconds?: number; p_id?: string }; Returns: Database["public"]["Tables"]["experiment_jobs"]["Row"][]; }

claim_geo_agent_runs

{ Args: { p_worker: string; p_max?: number; p_lease_seconds?: number; p_id?: string }; Returns: Database["public"]["Tables"]["geo_agent_runs"]["Row"][]; }

claim_geo_scans

{ Args: { p_worker: string; p_max?: number; p_lease_seconds?: number; p_scan_id?: string }; Returns: Database["public"]["Tables"]["geo_scans"]["Row"][]; }

claim_geo_verifications

{ Args: { p_worker: string; p_max?: number; p_lease_seconds?: number; p_id?: string }; Returns: Database["public"]["Tables"]["geo_verifications"]["Row"][]; }

claim_link_orders

{ Args: { p_worker: string; p_max?: number; p_lease_seconds?: number; p_order_id?: string }; Returns: Database["public"]["Tables"]["link_orders"]["Row"][]; }

claim_site_publications

{ Args: { p_worker: string; p_max?: number; p_lease_seconds?: number; p_id?: string }; Returns: Database["public"]["Tables"]["site_publications"]["Row"][]; }

claim_slack_inbox

{ Args: { p_limit: number }; Returns: Database["public"]["Tables"]["slack_inbox"]["Row"][]; }

claim_slack_outbound

{ Args: { p_limit: number }; Returns: Database["public"]["Tables"]["slack_outbound"]["Row"][]; }

claim_tracked_prompts

{ Args: { p_limit: number; p_lease_seconds: number }; Returns: Database["public"]["Tables"]["geo_tracked_prompts"]["Row"][]; }

claim_ugc_renders

{ Args: { p_worker: string; p_max?: number; p_lease_seconds?: number; p_id?: string }; Returns: Database["public"]["Tables"]["ugc_renders"]["Row"][]; }

complete_visual_analysis

{ Args: { p_job: string; p_token: string; p_profile: Json }; Returns: undefined; }

consume_rate_limit

{ Args: { p_bucket_key: string; p_window_seconds: number; p_limit: number; p_cost?: number }; Returns: { allowed: boolean; current_count: number; reset_at: string }[]; }

create_billed_workspace_for_user

{ Args: { p_user_id: string; p_name: string; p_website_url: string; p_idempotency_key: string; p_brand_limit: number; }; Returns: { workspace_id: string; created: boolean }[]; }

create_workspace_for_user

{ Args: { p_user_id: string; p_name: string; p_website_url: string; p_idempotency_key: string; }; Returns: { workspace_id: string; created: boolean }[]; }

ensure_billing_account

{ Args: { p_user: string }; Returns: string }

experiment_overview

{ Args: never; Returns: { workspace_id: string; proven_monthly_value: number; proven_value_currency: string; won_experiments: number; running_experiments: number; }[]; }

is_workspace_member

{ Args: { _workspace_id: string; _user_id: string }; Returns: boolean }

log_audit

{ Args: { _workspace_id: string; _action: string; _entity?: string; _payload?: Json }; Returns: string; }

meter_capture

{ Args: { p: Json }; Returns: Json }

meter_clawback

{ Args: { p: Json }; Returns: Json }

meter_expire_due

{ Args: never; Returns: number }

meter_grant

{ Args: { p: Json }; Returns: Json }

meter_hold

{ Args: { p: Json }; Returns: Json }

meter_release

{ Args: { p: Json }; Returns: Json }

meter_release_expired_holds

{ Args: never; Returns: number }

meter_rollover

{ Args: { p: Json }; Returns: Json }

my_workspace_role

{ Args: { _workspace_id: string }; Returns: string }

platform_spend_since

{ Args: { p_since: string }; Returns: number }

prune_geo_agent_runs

{ Args: never; Returns: Json }

prune_operational_logs

{ Args: never; Returns: Json }

quarantine_provider_lock

{ Args: { p_provider: string; p_reason: string }; Returns: boolean; }

reconcile_billing_capacity

{ Args: { p_account: string; p_brand_limit: number; p_seat_limit: number; p_preferred_workspace?: string; }; Returns: Json; }

record_ai_usage

{ Args: { p_event: Json }; Returns: number }

refresh_canva_authorization

{ Args: { p_workspace_id: string; p_connection_id: string; p_previous_refresh_token_enc: string; p_access_token_enc: string; p_refresh_token_enc: string; p_expires_at: string; }; Returns: boolean; }

release_ai_usage_reservation

{ Args: { p_id: string; p_reason?: string }; Returns: boolean }

release_billing_social_profile_slot_if_empty

{ Args: { p_workspace: string }; Returns: boolean; }

release_expired_ai_usage_reservations

{ Args: never; Returns: number }

release_provider_lock

{ Args: { p_provider: string; p_token: string }; Returns: boolean }

renew_provider_lock

{ Args: { p_provider: string; p_token: string; p_phase?: string; p_lease_seconds?: number }; Returns: boolean; }

replace_visual_artwork

{ Args: { p_workspace: string; p_job: string; p_expected: Json; p_output: Json; p_asset: string; p_headline: string; }; Returns: undefined; }

reserve_ai_usage

{ Args: { p_request: Json }; Returns: Json }

reserve_billing_social_profile_slot

{ Args: { p_workspace: string; p_limit: number }; Returns: undefined; }

resolve_media_storage_paths

{ Args: { paths: string[] }; Returns: { source_path: string; target_path: string; status: string }[]; }

save_canva_authorization

{ Args: { p_workspace_id: string; p_user_id: string; p_state_id: string; p_access_token_enc: string; p_refresh_token_enc: string; p_expires_at: string; p_scopes: string[]; p_canva_user_id: string; p_canva_team_id: string; }; Returns: string; }

set_billing_enforcement_override

{ Args: { p_action: string; p_account: string; p_actor: string; p_mode: string; p_reason: string; }; Returns: Json; }

set_persona_once

{ Args: { _persona: string }; Returns: { persona: string; persona_set_at: string }[]; }

sweep_rixot_donors

{ Args: { p_before: string }; Returns: number }

tombstone_migrated_media

{ Args: { paths: string[] }; Returns: undefined }

upsert_rixot_donors

{ Args: { p_rows: Json }; Returns: number }

use_manual_visual_look

{ Args: { p_workspace: string; p_expected: string }; Returns: undefined; }

withdraw_canva_authorization

{ Args: { p_workspace_id: string }; Returns: { refresh_token_enc: string }[]; }

workspace_member_profiles

{ Args: { _workspace_id: string }; Returns: { user_id: string; role: string; name: string; avatar_url: string; joined_at: string; }[]; }

workspace_members_page

{ Args: { p_workspace: string; p_offset: number; p_limit: number }; Returns: Json; }

workspace_overview

{ Args: never; Returns: { id: string; name: string; website_url: string; domain: string; industry: string; client_status: string; plan: string; role: string; owner_id: string; duplicate_of: string; onboarded_at: string; created_at: string; logo_url: string; pending_approvals: number; draft_count: number; scheduled_count: number; published_count: number; failed_count: number; connected_social_accounts: number; geo_score: number; geo_scanned_at: string; last_activity_at: string; }[]; }

Implementation sources: src/integrations/supabase/types.ts

18 Migration chronology

All 175 SQL migrations in the extracted snapshot, ordered by filename. A timestamp establishes repository ordering, not proof it has been applied to production. Preserve migration history and review clean-install and upgrade behavior separately. The newest composition and approval migrations are necessary for their matching source behavior.

Migration file
supabase/migrations/20260515092856_f89390f2-6325-42a0-851e-f98e1eefea7f.sql
supabase/migrations/20260515092920_fe0a7e57-7fa8-4c00-ae75-cb64c147f1ff.sql
supabase/migrations/20260515135802_88eca8f8-cada-47c2-b1fc-eb69c8d7e954.sql
supabase/migrations/20260515171352_5adc29a4-a1c9-4078-a003-94c1f7674c44.sql
supabase/migrations/20260515182818_78eaf3f8-a75a-41ef-aa34-554d096ce288.sql
supabase/migrations/20260515183134_7b9834fc-9f54-4bfe-9482-f613bf39008e.sql
supabase/migrations/20260524095344_35bcd6b9-e019-492a-aabe-aad725fdd103.sql
supabase/migrations/20260601102030_84ed669b-c522-4dc5-a8c0-00f97d775439.sql
supabase/migrations/20260603041939_5ea73fac-cd96-4cbf-921d-30287135f0d6.sql
supabase/migrations/20260612120630_f30875d5-827c-42b1-8420-d36ac035f9fa.sql
supabase/migrations/20260612121844_ff58033e-2d55-475e-bc39-2029a81e161a.sql
supabase/migrations/20260613164523_3dc39956-68a4-4711-866d-63de937cfa8a.sql
supabase/migrations/20260620095236_c414764d-9c96-4fff-86ae-80f3e3dc7b73.sql
supabase/migrations/20260620095952_dd03daa6-3753-4f4e-a537-78d0baf9b849.sql
supabase/migrations/20260620100449_4da6100a-eef2-4d78-8cba-7070b7c8b802.sql
supabase/migrations/20260620101957_e39091c5-a1b9-43fc-92c7-1fd0c84a59aa.sql
supabase/migrations/20260620102147_283e6290-faa9-4151-aacc-295cf267db1f.sql
supabase/migrations/20260620102427_1adcf2e5-0ed0-4aa2-bbaf-6c5e5b161d29.sql
supabase/migrations/20260625122548_53ddd990-24cb-4ee9-8963-1a45cf3b48ac.sql
supabase/migrations/20260628091455_a06cae50-764c-4ff8-b1d9-3432e8e0bd23.sql
supabase/migrations/20260628091518_2db13045-fba3-4774-964e-fad75972b77d.sql
supabase/migrations/20260628092047_201bf8bb-842b-44c9-8332-7f18c4946b0f.sql
supabase/migrations/20260628153819_120670af-a4b9-4078-a8cd-751772916ee3.sql
supabase/migrations/20260629103118_1a4cdde3-a8ed-455e-826a-0bc5e6c5ba5f.sql
supabase/migrations/20260629103222_0f0ff6b4-3ec3-4c16-a0ba-b96c91074098.sql

Migration file
supabase/migrations/20260629103938_23e6571f-8b4a-4979-a8ce-a4aea34b096e.sql
supabase/migrations/20260630182537_4e453f97-ab49-4ca6-9014-999752576722.sql
supabase/migrations/20260630184724_e380d055-2b47-44dc-a4da-9de7c1fd7171.sql
supabase/migrations/20260630200258_1ce1cb32-45d3-42f3-becc-ac052001e396.sql
supabase/migrations/20260707193010_fea60858-a686-48a2-8fb6-e63f6e340f53.sql
supabase/migrations/20260707193116_954a033c-abb0-4dda-aa87-317f91ae5d66.sql
supabase/migrations/20260707193303_93348393-698b-4f35-ae22-644af74d8942.sql
supabase/migrations/20260707193445_46dd0707-2e4d-4ee8-b7d1-e2cea84ec364.sql
supabase/migrations/20260709194343_9ba1d523-b946-4e78-a69d-e6bdaf5ba26e.sql
supabase/migrations/20260709194553_bb8d43fe-2f5e-48cb-9c77-8042cb96e8be.sql
supabase/migrations/20260709212343_4feb1702-87f2-45f0-9b83-6b92ce93a1e9.sql
supabase/migrations/20260709213859_80e26c94-28cf-45c1-9383-304df23d4ba5.sql
supabase/migrations/20260710100535_45a3451d-82a0-4499-bc1d-7e2e6260ca0c.sql
supabase/migrations/20260712203224_2d6ac297-789e-40b6-9228-e05bdb9dfb39.sql
supabase/migrations/20260712220251_2a14b1a0-8e29-4a9a-bad7-e71064c4ce68.sql
supabase/migrations/20260718184546_e27386a1-4495-4b68-b399-0a94f1d7702d.sql
supabase/migrations/20260718184836_4ff53c1f-ade2-4fe4-88c2-518841d56158.sql
supabase/migrations/20260720095116_ad729590-6b24-416b-8a9f-bf7cd05b7214.sql
supabase/migrations/20260809000001_add_workspace_sdr.sql
supabase/migrations/20260809000002_add_content_publications.sql
supabase/migrations/20260809000003_publishing_status_doc.sql
supabase/migrations/20260810000001_add_publications_perf_indexes.sql
supabase/migrations/20260903000000_disable_legacy_competitor_watch_cron.sql
supabase/migrations/20260907120000_create_conversations.sql
supabase/migrations/20260907150000_enforce_content_lifecycle.sql
supabase/migrations/20260910010000_create_persistent_assets.sql
supabase/migrations/20260910020000_harden_generated_asset_storage.sql
supabase/migrations/20260910030000_harden_client_share_secrets.sql
supabase/migrations/20260910040000_protect_workspace_owner_membership.sql
supabase/migrations/20260910050000_add_schedule_claim_leases.sql

Migration file
supabase/migrations/20260910060000_lock_workspace_resource_ownership.sql
supabase/migrations/20260910070000_add_market_trend_collections.sql
supabase/migrations/20260910080000_add_market_intelligence_cache.sql
supabase/migrations/20260911000000_add_api_rate_limits.sql
supabase/migrations/20260911000100_add_app_hook_caller.sql
supabase/migrations/20260911090000_add_market_brain_production_schema.sql
supabase/migrations/20260911120000_add_sdr_webhook_events.sql
supabase/migrations/20260911120100_add_ai_usage_metering.sql
supabase/migrations/20260911120200_add_guardrail_events.sql
supabase/migrations/20260911120300_add_agent_control_plane.sql
supabase/migrations/20260911120400_add_cron_heartbeats_and_job_claims.sql
supabase/migrations/20260911120500_revoke_private_schema_from_anon.sql
supabase/migrations/20260911120600_schedule_app_cron_jobs.sql
supabase/migrations/20260913080000_content_lifecycle_distribution_meta.sql
supabase/migrations/20260913090000_studio_jobs.sql
supabase/migrations/20260913100000_add_socialapi_distribution.sql
supabase/migrations/20260914120000_add_geo_intelligence.sql
supabase/migrations/20260915090000_add_workspace_connectors.sql
supabase/migrations/20260916090000_add_geo_fix_workflow.sql
supabase/migrations/20260916100000_add_geo_fix_batches.sql
supabase/migrations/20260917090000_add_source_ownership.sql
supabase/migrations/20260917090100_add_geo_agent_runs.sql
supabase/migrations/20260918090000_connector_install_return_origin.sql
supabase/migrations/20260919090000_connector_install_return_path.sql
supabase/migrations/20260920090000_canonical_workspaces.sql
supabase/migrations/20260920090100_workspace_brand_dna.sql
supabase/migrations/20260920090200_workspace_overview.sql
supabase/migrations/20260920090300_stop_signup_placeholder_workspace.sql
supabase/migrations/20260920090400_client_portal_messages.sql
supabase/migrations/20260920090500_harden_client_portal_grants.sql

Migration file
supabase/migrations/20260921090000_add_ai_usage_reservations.sql
supabase/migrations/20260921090100_add_ugc_video_ads.sql
supabase/migrations/20260921110000_add_competitor_intelligence.sql
supabase/migrations/20260922090000_add_google_analytics_connector.sql
supabase/migrations/20260922090100_schedule_analytics_sync.sql
supabase/migrations/20260922090200_add_analytics_aggregates.sql
supabase/migrations/20260922090300_add_webflow_connector.sql
supabase/migrations/20260923090000_add_backlink_intelligence.sql
supabase/migrations/20260923090100_schedule_backlink_runs.sql
supabase/migrations/20260923090200_add_backlink_upsert_rpcs.sql
supabase/migrations/20260923100000_backlink_builder.sql
supabase/migrations/20260923110000_backlink_sites.sql
supabase/migrations/20260923120000_add_wordpress_connector.sql
supabase/migrations/20260923130000_add_wordpress_com_oauth.sql
supabase/migrations/20260924090000_backlink_acquisition.sql
supabase/migrations/20260925090000_link_marketplace.sql
supabase/migrations/20260925090100_link_marketplace_rpcs.sql
supabase/migrations/20260925090200_schedule_link_orders.sql
supabase/migrations/20260925090300_provider_lock_optional_order.sql
supabase/migrations/20260926090000_add_competitor_intelligence_graph.sql
supabase/migrations/20260926100000_replace_dataforseo_with_tavily_market_signals.sql
supabase/migrations/20260927090000_client_share_stable_links.sql
supabase/migrations/20260928090000_add_proof_engine.sql
supabase/migrations/20260928090100_fix_experiment_lock_children.sql
supabase/migrations/20260929090000_geo_site_connectors.sql
supabase/migrations/20260930090000_schedule_experiments_hook.sql
supabase/migrations/20261001090000_brand_kit_styles.sql
supabase/migrations/20261002090000_billing_account_schema.sql
supabase/migrations/20261002090100_billing_meter_rpcs.sql
supabase/migrations/20261002090200_billing_usage_attribution.sql

Migration file
supabase/migrations/20261002090300_billing_schedule.sql
supabase/migrations/20261002090400_billing_brand_limit.sql
supabase/migrations/20261002090500_billing_studio_async.sql
supabase/migrations/20261002090600_billing_ugc_async.sql
supabase/migrations/20261002090700_billing_seat_limit.sql
supabase/migrations/20261002090800_billing_social_profile_slots.sql
supabase/migrations/20261002090900_billing_provider_stripe.sql
supabase/migrations/20261002091000_billing_stripe_account.sql
supabase/migrations/20261002091100_billing_capacity_reconcile.sql
supabase/migrations/20261002091200_billing_invoice_clawback.sql
supabase/migrations/20261002091300_billing_operations.sql
supabase/migrations/20261002091400_billing_backlink_history.sql
supabase/migrations/20261002091500_billing_checkout_reservation.sql
supabase/migrations/20261002091600_billing_capacity_cursor.sql
supabase/migrations/20261002091700_billing_margin_report.sql
supabase/migrations/20261002091800_billing_provider_health.sql
supabase/migrations/20261002091900_billing_enforcement_override.sql
supabase/migrations/20261002092000_billing_frozen_brand_boundary.sql
supabase/migrations/20261002092100_postforme_social_profile_slots.sql
supabase/migrations/20261002092200_billing_purchase_requests.sql
supabase/migrations/20261002092300_billing_async_links.sql
supabase/migrations/20261002092400_billing_launch_grace.sql
supabase/migrations/20261002092500_billing_idempotency_terms.sql
supabase/migrations/20261002092501_geo_tracked_prompts.sql
supabase/migrations/20261002092600_billing_legacy_workspace_plan_sync.sql
supabase/migrations/20261002092700_content_lifecycle_calendar_plan.sql
supabase/migrations/20261003090000_autopilot.sql
supabase/migrations/20261003090100_autopilot_rpcs.sql
supabase/migrations/20261003090200_autopilot_strategy.sql
supabase/migrations/20261003090300_autopilot_tasks.sql

Migration file
supabase/migrations/20261004090000_social_trend_snapshots.sql
supabase/migrations/20261005090000_mcp.sql
supabase/migrations/20261005090100_billing_idempotency_terms_repair.sql
supabase/migrations/20261006090000_stories.sql
supabase/migrations/20261007090000_canva_connector.sql
supabase/migrations/20261008090000_canva_edit_versions.sql
supabase/migrations/20261008100000_workspace_invite_lookup.sql
supabase/migrations/20261009090000_notion_calendar.sql
supabase/migrations/20261010090000_audience_intelligence.sql
supabase/migrations/20261011090000_brand_look_from_default_style.sql
supabase/migrations/20261011090100_workspace_marketing_strategy.sql
supabase/migrations/20261012090000_canva_atomic_authorization.sql
supabase/migrations/20261012090000_drop_brand_styles.sql
supabase/migrations/20261012190000_r2_storage_migration.sql
supabase/migrations/20261013090000_slack_integration.sql
supabase/migrations/20261014090000_workspace_memory.sql
supabase/migrations/20261015090000_brand_visual_taste.sql
supabase/migrations/20261015090000_site_blog_setup.sql
supabase/migrations/20261016090000_repair_slack_claims_and_experiments_schedule.sql
supabase/migrations/20261017090000_app_tour.sql
supabase/migrations/20261018090000_admin_foundation.sql
supabase/migrations/20261018090000_content_kind_approval.sql
supabase/migrations/20261018100000_entitlement_overrides.sql
supabase/migrations/20261018120000_admin_operations.sql
supabase/migrations/20261018130000_admin_flags_announcements.sql
supabase/migrations/20261018140000_admin_insight.sql
supabase/migrations/20261018150000_admin_ai_controls.sql
supabase/migrations/20261018160000_admin_workspace_access.sql
supabase/migrations/20261018170000_admin_jobs_abuse.sql
supabase/migrations/20261021090000_video_compositions.sql

Implementation sources: supabase/migrations

19 Separate Python API inventory

These paths are statically extracted from direct @router/@app decorators in backend. Router prefixes can add a path segment at registration; this table is not a full OpenAPI export. Production deployment, auth policy and model availability for this separate service were not independently confirmed.

Decorator path	Method	Source
/health	GET	backend/app/main.py

Implementation sources: backend

20 Maintaining the blueprint

• Regenerate API/page/model/catalog/schema inventories whenever their source changes; store snapshot date, commit and file hashes.

• Update narrative when behavior changes, especially approval modes, billing, provider retirement, media capabilities or source ownership.

• Review official model availability and rate cards at each provider change; retain invoices as actual-spend evidence.

• Track production facts in a private operational supplement: services, migrations, flags, approved OAuth apps, backups and contacts.

• Keep future feature decisions separate from current-state documentation. Move a later catalog item to launch only with an implemented path and verified acceptance evidence.

• Retain the editable Markdown companions and machine-readable inventory so a future maintainer can update the series without reconstructing it from PDFs.

21 Source ledger and verification limits

Repository-relative paths below identify the owning implementation. The companion source folder includes an extracted inventory and SHA-256 hashes for source files and migrations. The inventory is a static extraction, not a database dump or a successful production test. Generated database types describe their checked-in state; migrations define actual SQL constraints, defaults and policies.

The Mellox connector failed with an internal error. The public site could not be fetched by the web tool or local network, and browser initialization was unavailable. Consequently public-site rendering, deployed commit, enabled credentials, vendor approvals, production schema, invoices, real usage and exact Railway service topology were not independently inspected. The local marketing implementation was used as a secondary source. No live provider generation or publication was triggered.

Source	SHA-256 prefix
docs/documentation-maintenance.md	8117afd85c931614
src/server/route.ts	391e0eb6fa6c43a7
src/lib/billing/catalog.ts	eb845ac041f58b84
supabase/migrations	directory reference
package.json	c6995b00a40c90b8
package-lock.json	3128315607b265d7
Dockerfile	430225c9b5bc79c7
src/server/env.ts	a814c54a60a11cb0
src/instrumentation.ts	5e3caad36277cc50
next.config.ts	bc5ebc3b26f710f9
src/server/workspaces	directory reference
src/server/fns/workspaces.ts	974d72a2d9da1509
src/lib/workspace	directory reference
src/integrations/supabase	directory reference
src/server/billing	directory reference
src/server/ai	directory reference
src/lib/ai-gateway.server.ts	45c14a06dd6557bf
src/server/platform	directory reference
src/server/brain	directory reference
src/server/strategy	directory reference
src/server/memory	directory reference
src/server/chat	directory reference

Source	SHA-256 prefix
src/lib/memory	directory reference
src/lib/strategy	directory reference
src/server/studio	directory reference
src/server/assets	directory reference
src/server/fns/content.ts	cbd7e21890647951
src/server/connectors/canva	directory reference
src/server/connectors/notion	directory reference
supabase/migrations/20261018090000_content_kind_approval.sql	df81942beba55d0e
src/lib/postforme	directory reference
src/lib/feature-flags.ts	e56ac35e17629593
src/server/social	directory reference
src/server/articles	directory reference
src/server/analytics	directory reference
src/server/fns/publish.ts	ba13a497e8368272
src/lib/ugc	directory reference
src/server/ugc	directory reference
src/server/billing/ugc-async.server.ts	687ecbb7c2909d94
src/server/ugc/providers/composition.server.ts	4b92cd5607c286fb
supabase/migrations/20261021090000_video_compositions.sql	d2c16d0b4eea8af7
src/lib/geo	directory reference
src/server/geo	directory reference
src/lib/experiments/constants.ts	c6a71a1733c65aa5
src/lib/experiments/evaluate.ts	d0203f55074861cd
src/server/experiments	directory reference
src/lib/audience/calibration.ts	0dd94c44e6bc5838
src/server/autopilot	directory reference
src/lib/autopilot	directory reference
src/server/mcp	directory reference
src/server/admin	directory reference
tests	directory reference

Source	SHA-256 prefix
src/server	directory reference
src/app/api/geo/scans/route.ts	a529199b35c27467
src/app/api/studio/jobs/route.ts	8a10299506026906
src/lib/studio/jobs.ts	edb9510909c0a97f
src/app/api/ugc/renders/route.ts	31d547eaf590ac88
src/lib/ugc/schemas.ts	63049c08f6641501
src/lib/ugc/models.ts	6d1c68c9c5d44b38
src/lib/ugc/duration.ts	6ad312021cd6c5d5
src/server/ai/task-models.ts	e905dc027bcc6d2b
src/integrations/supabase/types.ts	2c6c5e758669115b
backend	directory reference