

ASSIGNMENT-8.5

Name: T.Ravali

Hall No:2303A52408

Batch:36

Task Description #1 (Username Validator – Apply AI in Authentication Context)

- Task: Use AI to generate at least 3 assert test cases for a function `is_valid_username(username)` and then implement the function using Test-Driven Development principles.

- Requirements:

- o Username length must be between 5 and 15 characters.

- o Must contain only alphabets and digits.

- o Must not start with a digit.

- o No spaces allowed.

Example Assert Test Cases:

```
assert is_valid_username("User123") == True
```


```
assert is_valid_username("12User") == False
```

```
assert is_valid_username("Us er") == False
```

Expected Output #1:

- Username validation logic successfully passing all AI-generated test cases.

Output:



Task Description #2 (Even–Odd & Type Classification – Apply AI for Robust Input Handling)

- Task: Use AI to generate at least 3 assert test cases for a function `classify_value(x)` and implement it using conditional logic and loops.

- Requirements:

- o If input is an integer, classify as "Even" or "Odd".

- o If input is 0, return "Zero".

- o If input is non-numeric, return "Invalid Input".

Example Assert Test Cases:

`assert classify_value(8) == "Even"`


`assert classify_value(7) == "Odd"`

`assert classify_value("abc") == "Invalid Input"`

Expected Output #2:

- Function correctly classifying values and passing all test cases.

Output:



Task Description #3 (Palindrome Checker – Apply AI for String Normalization)

- Task: Use AI to generate at least 3 assert test cases for a function `is_palindrome(text)` and implement the function.
- Requirements:
 - o Ignore case, spaces, and punctuation.
 - o Handle edge cases such as empty strings and single characters.

Example Assert Test Cases:

```
assert is_palindrome("Madam") == True
```

```
assert is_palindrome("A man a plan a canal Panama") == True
```


```
assert is_palindrome("Python") == False
```

Expected Output #3:

- Function correctly identifying palindromes and passing all

AI-generated tests.

Output:



Task Description #4 (BankAccount Class – Apply AI for Object-Oriented Test-Driven Development)

- Task: Ask AI to generate at least 3 assert-based test cases for

a BankAccount class and then implement the class.

- Methods:

- o deposit(amount)

- o withdraw(amount)

- o get_balance()

Example Assert Test Cases:

```
acc = BankAccount(1000)
```

```
acc.deposit(500)
```

```
assert acc.get_balance() == 1500
```

```
acc.withdraw(300)
```

```
assert acc.get_balance() == 1200
```

Expected Output #4:

- Fully functional class that passes all AI-generated assertions.

Output:

The screenshot shows a code editor with a file named 'Task-04'. The code defines a `BankAccount` class with methods `__init__`, `deposit`, and `withdraw`. The `__init__` method checks if the initial balance is a non-negative number (int or float). The `deposit` method adds an amount to the balance, and the `withdraw` method subtracts an amount. A test suite is shown below the class, with tests for negative initial balance, float initial balance, deposit, and withdraw. The tests are all failing, with error messages indicating the expected vs. actual values. The output at the bottom shows 'All BankAccount tests passed!'.

```
# Function: BankAccount Class
class BankAccount:
    def __init__(self, initial_balance=0):
        if not isinstance(initial_balance, (int, float)) or initial_balance < 0:
            raise ValueError
        self.balance = initial_balance

    def deposit(self, amount):
        if not isinstance(amount, (int, float)) or amount < 0:
            raise ValueError
        self.balance += amount
        return self.balance

    def withdraw(self, amount):
        if not isinstance(amount, (int, float)) or amount < 0:
            raise ValueError
        if amount > self.balance:
            raise ValueError
        self.balance -= amount
        return self.balance

try:
    account10 = BankAccount(-50)
    assert False, "Test 10 Failed: Expected ValueError for negative initial balance"
except ValueError as e:
    assert str(e) == "Initial balance must be a non-negative number.", f"Test 10 Failed: Wrong error message: {e}"

# Test 11: Initial balance as float
account11 = BankAccount(100.50)
assert account11.get_balance() == 100.50, f"Test 11 Failed: Expected 100.50, got {account11.get_balance()}"

# Test 12: Deposit float amount
account12 = BankAccount(50)
account12.deposit(25.75)
assert account12.get_balance() == 75.75, f"Test 12 Failed: Expected 75.75, got {account12.get_balance()}"

# Test 13: Withdraw float amount
account13 = BankAccount(100.25)
account13.withdraw(10.15)
assert account13.get_balance() == 90.10, f"Test 13 Failed: Expected 90.10, got {account13.get_balance()}"

print("All BankAccount tests passed!")
```

Task Description #5 (Email ID Validation – Apply AI for Data Validation)

- Task: Use AI to generate at least 3 assert test cases for a function `validate_email(email)` and implement the function.
- Requirements:

- o Must contain @ and .
- o Must not start or end with special characters.
- o Should handle invalid formats gracefully.

Example Assert Test Cases:

```
assert validate_email("user@example.com") == True
```

```
assert validate_email("userexample.com") == False
```

```
assert validate_email("@gmail.com") == False
```

Expected Output #5:

- Email validation function passing all AI-generated test cases and handling edge cases correctly.

Output:

