

RAVE *generation*

OTTX

Multiband Dynamics Processor

User Manual

Overview

OTTX is a multiband dynamics processor combining aggressive upward and downward compression with per-band waveshaping. Features include oversampling for cleaner harmonics, linear phase crossover option, lookahead, and a mix knob for parallel compression.

Signal Flow

Input → In Gain → 3-Band Split (Low/Mid/High) → Per-Band Compression → Per-Band Inflator → Sum → Out Gain → Mix with Dry

The crossover splits your signal at two frequencies (Low/Mid and Mid/High). Each band gets independent upward and downward compression, then optional waveshaping via the Curve controls.

Main Controls



Depth	Master amount of compression effect (0-100%). At 0%, compression is bypassed. Higher values increase both upward and downward compression intensity.
Attack	Scales attack time for all bands (0-200%). 100% = default timing. Lower = faster attack, higher = slower.
Release	Scales release time for all bands (0-200%). 100% = default timing.
In Gain	Input gain before processing (-24 to +24 dB). Use to drive the compressor harder or softer.
Out Gain	Output gain after processing (-24 to +24 dB). Compensate for level changes.
Upward	Amount of upward compression (0-200%). Brings up quiet parts. 100% = default.
Downward	Amount of downward compression (0-200%). Pushes down loud parts. 100% = default.

Per-Band Controls

Gain & Threshold

Low/Mid/High Gain	Makeup gain per band (-40 to +6 dB). Adjust the balance between bands after compression.
Low/Mid/High Thresh	Threshold offset per band (0-200%). 100% = default. Lower values make compression kick in earlier.

Inflator & Ratio

Low/Mid/High Curve	Inflator waveshaping amount per band (0-100%). Adds harmonic density and loudness without traditional clipping. Subtle at low values, more aggressive higher up.
Low/Mid/High Ratio	Downward compression ratio per band (0-200%). 100% = default ratio. Higher = more aggressive limiting of peaks.

Crossover

Low/Mid Freq	Crossover between low and mid bands (28-148 Hz). Default 88 Hz works well for most material.
Mid/High Freq	Crossover between mid and high bands (2000-3000 Hz). Default 2500 Hz.

The crossovers use 24dB/octave Linkwitz-Riley filters in Minimum phase mode, or linear phase FIR filters in Linear mode.

Utilities

Oversample	Off / 2x / 4x. Higher oversampling reduces aliasing from the waveshaping, at the cost of more CPU.
Phase Mode	Minimum = lower latency, slight phase shift at crossovers. Linear = higher latency, no phase distortion. Linear is cleaner but adds delay.
Lookahead	20ms lookahead. Lets the compressor "see ahead" to catch transients more transparently. Adds latency.
Mix	Wet/dry blend (0-100%). At 100% you hear only processed signal. Lower values blend in dry signal for parallel compression.

Meters

The Low GR, Mid GR, and High GR meters show gain reduction per band in dB. Positive values indicate the signal is being pushed down (downward compression), negative values indicate it's being brought up (upward compression).

Quick Start

Classic sound: Set Depth to 50-70%, leave everything else at defaults.

Parallel compression: Depth at 100%, Mix at 30-50%. Blend to taste.

Cleaner processing: Enable 2x or 4x oversampling and Linear phase mode.

Tame harsh highs: Reduce High Gain or High Ratio.

Add weight: Increase Low Gain, maybe add some Low Curve for saturation.

More punch: Enable Lookahead for smoother transient handling.

Latency

OTTX has a fixed latency of approximately 43.8ms to ensure reliable DAW delay compensation. Your DAW will automatically compensate for this delay. This fixed latency allows you to freely switch between modes (oversampling, linear phase, lookahead) without causing sync issues.

Support

For technical support, updates, and additional information:

Website: ravegeneration.io

Email: support@ravegeneration.io

© 2025 Rave Generation. All rights reserved
