

Your code has one main problem:

```
ApplicationContext context = new ClassPathXmlApplicationContext();
```

You created the Spring container **without telling it where your XML configuration file is**. Therefore, Spring doesn't know about the "alien" bean.

1. Create spring.xml

Put it inside:

```
src/main/resources/spring.xml
```

Content:

```
<?xml version="1.0" encoding="UTF-8"?>
<beans xmlns="http://www.springframework.org/schema/beans"
       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
       xsi:schemaLocation="
         http://www.springframework.org/schema/beans
         https://www.springframework.org/schema/beans/spring-beans.xsd">
  <bean id="alien" class="org.example.Alien"/>
</beans>
```

2. Change your App.java

```
package org.example;

import org.springframework.context.ApplicationContext;
import org.springframework.context.support.ClassPathXmlApplicationContext;

public class App {

    public static void main(String[] args) {

        ApplicationContext context =
            new ClassPathXmlApplicationContext("spring.xml");

        Alien obj = (Alien) context.getBean("alien");
```

```
        obj.code();
    }
}
```

3. Your Alien.java

This is already correct:

```
package org.example;

public class Alien {
    public void code() {
        System.out.println("Coding..");
    }
}
```

Folder structure

Make sure your project looks like:

src

```
├── main
|   ├── java
|   |   ├── org
|   |   |   ├── example
|   |   |   |   ├── App.java
|   |   |   |   └── Alien.java
|   |
|   └── resources
|       └── spring.xml
```

What happens internally?

ApplicationContext context =

```
new ClassPathXmlApplicationContext("spring.xml");
```

Spring reads:

```
<bean id="alien" class="org.example.Alien"/>
```

So Spring creates an Alien object.

Then:

```
Alien obj = (Alien) context.getBean("alien");
```

gets that object from the Spring container.

Finally:

```
obj.code();
```

prints:

Coding..

Important: If you use:

```
new ClassPathXmlApplicationContext();
```

instead, Spring has no XML file loaded, so `getBean("alien")` will not work.

Would you like the same example rewritten using Java-based configuration instead of XML?