# SIMATS ENGINEERING

## MCQ Test

**COURSE NAME: Software Testing** **COURSE CODE: CSA37**

**COURSE OUTCOME COVERED**

**CO1:** *Apply software testing principles to enhance the effectiveness of software quality assurance and improve defect detection strategies.*
Assessment Tool Weightage: 20%

| Sl. No | MCQ Questions | Bloom's Level |
|---|---|---|
| 1 | A team applies systematic test design techniques during development. This reflects: a) Debugging b) Testing as an engineering activity c) Maintenance d) Deployment | 3 |
| 2 | If a project skips defined testing processes, what is the likely outcome? a) Faster delivery with high quality b) Increased defects in production c) Reduced testing cost only d) Improved documentation | 3 |
| 3 | Selecting test cases based on requirements demonstrates: a) Random testing b) Process-driven testing c) Ad hoc testing d) Maintenance testing | 3 |
| 4 | Applying equivalence partitioning is an example of: a) Debugging b) Test design technique c) Coding standard d) Deployment activity | 3 |
| 5 | A tester identifies missing requirements during testing. This shows: a) Coding error b) Process gap c) User error d) Hardware issue | 3 |
| 6 | Following a structured testing lifecycle ensures: a) Random defect detection b) Improved software quality c) Less documentation d) No defects | 3 |
| 7 | Which activity best represents testing as a process? a) Writing code b) Executing test cases systematically c) Deploying software d) User training | 3 |
| 8 | A tester reuses test cases from a repository. This supports: a) Efficiency in testing b) Increased coding errors c) Reduced coverage d) Random testing | 3 |
| 9 | If defects are tracked and analyzed, it improves: a) Coding speed b) Software quality process c) Deployment time d) User interface | 3 |
| 10 | Applying boundary value analysis helps to: a) Increase documentation b) Detect edge-case defects c) Reduce execution time d) Avoid testing | 3 |
| 11 | A tester validates system behavior against requirements. This is: a) Verification b) Validation c) Debugging d) Coding | 3 |

| | | |
|---|---|---|
| 12 | Detecting defects before release reduces: a) Development effort b) Maintenance cost c) Coding standards d) Testing scope | 3 |
| 13 | Applying testing principles ensures: a) Zero defects guarantee b) Early defect detection c) No testing needed d) Faster coding | 3 |
| 14 | Which principle suggests testing all inputs is impossible? a) Exhaustive testing b) Exhaustive testing is impossible c) Early testing d) Defect clustering | 3 |
| 15 | A tester focuses on frequently failing modules. This uses: a) Random testing b) Defect clustering principle c) Regression testing d) Smoke testing | 3 |
| 16 | If testing starts early in SDLC, it helps: a) Reduce defects cost b) Increase coding errors c) Delay project d) Skip documentation | 3 |
| 17 | A tester designs test cases independently from developers. This ensures: a) Bias b) Objectivity c) Delay d) Redundancy | 3 |
| 18 | A tester reviews requirements for errors. Role performed is: a) Developer b) Tester c) Manager d) User | 3 |
| 19 | Reporting defects clearly is part of: a) Coding b) Tester's responsibility c) Deployment d) Maintenance | 3 |
| 20 | A tester collaborates with developers to fix bugs. This shows: a) Isolation b) Teamwork c) Delay d) Redundancy | 3 |
| 21 | A requirement ambiguity causes defects. Origin is: a) Coding b) Requirements phase c) Testing phase d) Deployment | 3 |
| 22 | Incorrect algorithm implementation leads to: a) Requirement defect b) Design defect c) Coding defect d) Testing defect | 3 |
| 23 | Missing validation checks are example of: a) Design defects b) Coding defects c) Requirement defects d) Deployment defects | 3 |
| 24 | Poor UI design causing confusion is: a) Coding defect b) Design defect c) Requirement defect d) Hardware defect | 3 |
| 25 | A system crash due to memory leak is: a) Requirement defect b) Coding defect c) Design defect d) Documentation defect | 3 |
| 26 | Classifying defects based on severity helps: a) Ignore defects b) Prioritize fixing c) Delay release d) Increase cost | 3 |
| 27 | A critical defect impacts: a) Minor feature b) Core functionality c) UI color d) Documentation | 3 |
| 28 | A minor defect example is: a) System crash b) Login failure c) Typo error d) Data loss | 3 |
| 29 | Defect classification helps testers to: a) Ignore bugs b) Organize defects c) Skip testing d) Increase errors | 3 |

| | | |
|---|---|---|
| 30 | A defect repository is used to: a) Store code b) Store test cases c) Store defect details d) Store UI designs | 3 |
| 31 | Reusing defect data helps in: a) Predicting issues b) Increasing bugs c) Reducing tests d) Skipping phases | 3 |
| 32 | A defect repository improves: a) Code complexity b) Testing efficiency c) User interface d) Deployment speed | 3 |
| 33 | Logging defects with details ensures: a) Confusion b) Traceability c) Delay d) Redundancy | 3 |
| 34 | A tester uses past defect data to design tests. This is: a) Random testing b) Experience-based testing c) Debugging d) Deployment | 3 |
| 35 | Incorrect login validation is an example of: a) Functional defect b) Performance defect c) Security defect d) UI defect | 3 |
| 36 | Slow response time is a: a) Functional defect b) Performance defect c) UI defect d) Coding standard | 3 |
| 37 | Unauthorized data access indicates: a) UI defect b) Security defect c) Functional defect d) Design defect | 3 |
| 38 | Missing button functionality is: a) Functional defect b) Security defect c) Performance defect d) Hardware defect | 3 |
| 39 | Poor alignment in UI is: a) Functional defect b) UI defect c) Security defect d) Design defect | 3 |
| 40 | Applying testing principles avoids: a) Coding b) Redundant tests c) Deployment d) Maintenance | 3 |
| 41 | A tester validates outputs using expected results. This is: a) Debugging b) Test execution c) Coding d) Maintenance | 3 |
| 42 | If defects are not tracked, it leads to: a) Better quality b) Poor traceability c) Faster delivery d) No impact | 3 |
| 43 | Applying test process ensures: a) Random results b) Structured testing c) No defects d) No planning | 3 |
| 44 | Test case design based on requirements ensures: a) Low coverage b) High coverage c) No defects d) Less effort | 3 |
| 45 | Early testing reduces: a) Defect cost b) Code size c) UI design d) Deployment time | 3 |
| 46 | A tester identifies repeated defects. This indicates: a) Good design b) Poor process c) No issue d) Perfect testing | 3 |
| 47 | Reviewing test results helps: a) Ignore defects b) Improve quality c) Skip testing d) Reduce effort | 3 |
| 48 | A tester applies regression testing to: a) Add features b) Ensure fixes work c) Deploy software d) Design UI | 3 |
| 49 | Identifying root cause of defects helps: a) Increase bugs b) Prevent recurrence c) Delay testing d) Skip coding | 3 |
| 50 | A test plan ensures: a) Random execution b) Organized testing c) No testing d) No defects | 3 |
| 51 | Applying defect classification improves: a) Testing cost b) Fix prioritization c) Coding errors d) UI design | 3 |

| | | |
|---|---|---|
| 52 | A tester uses historical defect trends. This helps in: a) Ignoring defects b) Risk-based testing c) Deployment d) Coding | 3 |
| 53 | Testing ensures product meets: a) Developer needs b) User requirements c) Tester goals d) Manager plans | 3 |
| 54 | A defect due to wrong requirement interpretation is: a) Coding defect b) Requirement defect c) UI defect d) Hardware defect | 3 |
| 55 | Applying process standards ensures: a) Poor quality b) Consistent quality c) No testing d) Random output | 3 |
| 56 | A tester documents defects clearly. This helps: a) Developers fix quickly b) Increase errors c) Delay release d) Reduce quality | 3 |
| 57 | A defect repository is analyzed to: a) Increase cost b) Improve testing strategy c) Skip testing d) Reduce quality | 3 |
| 58 | A tester applies black-box testing. This focuses on: a) Internal code b) External behavior c) Hardware d) Deployment | 3 |
| 59 | Defects found in testing phase indicate: a) Perfect design b) Earlier phase issues c) No issues d) Hardware problems | 3 |
| 60 | Applying structured testing improves: a) Random results b) Product reliability c) Coding errors d) Deployment delay | 3 |

***Code of Conduct:***

*I* M Ravi Sai Vinay(192311035) *certify that this submission is my original work and that I have adhered to the guidelines specified for this assessment.*
*I understand that any violation of academic integrity rules will result in disciplinary action.*

***Signature of the student:*** M Ravi Sai Vinay.

## RUBRICS FOR CALCULATION:

| Criteria | Weightage (%) | Level 4 (Exemplary) | Level 3 (Proficient) | Level 2 (Developing) | Level 1 (Beginning) |
|---|---|---|---|---|---|
| Conceptual Understanding | 30% | Demonstrates thorough understanding; answers all questions accurately | Shows good understanding with few errors | Partial understanding; several incorrect responses | Lacks understanding; majority of answers incorrect |
| Accuracy of Answers | 25% | All answers are correct | Most answers are correct with minor mistakes | Some correct answers; frequent errors | Mostly incorrect answers |
| Application of Knowledge | 20% | Correctly applies concepts to problem-based questions | Applies concepts with minor errors | Limited ability to apply concepts | Unable to apply concepts |
| Time Management | 15% | Completes quiz well within time efficiently | Completes on time with minor delays | Requires extra time or rushes through questions | Unable to complete within given time |
| Question Interpretation | 10% | Interprets all questions correctly and responds appropriately | Misinterprets a few questions | Often misinterprets questions | Unable to understand questions |

SUBJECT:SOFTWARE TESTING
CODE: CSA3712

CO1-AT3-MCQS TEST

1. b) Testing as an engineering activity
2. b) Increased defects in production
3. b) Process-driven testing
4. b) Test design technique
5. b) Process gap
6. b) Improved software quality
7. b) Executing test cases systematically
8. a) Efficiency in testing
9. b) Software quality process
10. b) Detect edge-case defects
11. b) Validation
12. b) Maintenance cost
13. b) Early defect detection
14. b) Exhaustive testing is impossible
15. b) Defect clustering principle
16. a) Reduce defects cost
17. b) Objectivity
18. b) Tester
19. b) Tester's responsibility
20. b) Teamwork
21. b) Requirements phase
22. c) Coding defect
23. b) Coding defects
24. b) Design defect
25. b) Coding defect
26. b) Prioritize fixing

27. b) Core functionality
28. c) Typo error
29. b) Organize defects
30. c) Store defect details
31. a) Predicting issues
32. b) Testing efficiency
33. b) Traceability
34. b) Experience-based testing
35. a) Functional defect
36. b) Performance defect
37. b) Security defect
38. a) Functional defect
39. b) UI defect
40. b) Redundant tests
41. b) Test execution
42. b) Poor traceability
43. b) Structured testing
44. b) High coverage
45. a) Defect cost
46. b) Poor process
47. b) Improve quality
48. b) Ensure fixes work
49. b) Prevent recurrence
50. b) Organized testing
51. b) Fix prioritization
52. b) Risk-based testing
53. b) User requirements
54. b) Requirement defect
55. b) Consistent quality
56. a) Developers fix quickly

57. b) Improve testing strategy

58. b) External behavior

59. b) Earlier phase issues

60. b) Product reliability

**TOTAL MARKS :55/60**