

- NOTE: just go through built-in docs at top all modules can be reviewed as necessary

# Python Docs

---

## Built-in Types

---

### Truth Value Testing

- any object in if or loop conditional
- falsey types:
  - None
  - False
  - 0, 0L, 0.0, 0j
  - empty sequence `''`, `()`, `[]`
  - empty mapping `{}`
  - user-defined class with `__nonzero__` or `__len__` that return integer 0 or false

### Boolean Operations - and, or, not (in ascending priority)

- or
- and
- not

### Comparisons

- `<`, `<=`, `>`, `>=`, `==`, `!=`, `is`, `is not`
- can override `__lt__` etc, but can also override `__cmp__`

### Numeric Types - int, float, long, complex

- booleans are a subtype of plain integers
- ints are always C longs (`sys.maxint`)
- floats are usually doubles (`sys.float_info`)
- complex - `z.imag`, `z.real`
- fractions - hold rationals
- decimal - floats with user-defined precision
- can use ctors `float()`, `int()`, `long()`, `complex()` etc
- general numeric operators with
  - `.conjugate()`
  - `divmod()`
  - `pow()` or `**`

- all numbers. Real types (int, long, and float) also include
  - `math.trunc(x)`
  - `round(x, n)`
  - `math.floor(x)`
  - `math.ceil(x)`

## Bitwise Operations on Integer Types

## Additional Methods on Integer Types

- `int.bit_length()`
- `long.bit_length()`

## Additional Methods on Float Types

- `float.as_integer_ratio()` - returns pair
- `float.is_integer()`
- `float.hex()`
- `float.fromhex()`

## Iterator Types

- `container.__iter__()`
- `iterator.__iter__()` - return self
- `iterator.next()` - raises `StopIteration` on end

## Sequence Types - str, unicode, list, tuple, bytearray, buffer, xrange

- string literals - `'fdsa'` or `"fkstdla"`
- unicode strings - `u'sjkdf'` or `u"dfsjakl"`
- lists - `[0, 1, 2]`
- tuple - `elem1, elem2, elem3` or `(elem1, elem2, elem3)` always `()` for an empty tuple and `(elem1,)` for a single item
- bytearray - built-in `bytearray()` function - mutable sequence of integers from `[0, 256)`
- buffer - not directly supported by Python syntax
- xrange - similar to buffer
- supports
  - `x in s`
  - `x not in s`
  - `s + t` - concatenation
  - `s * n` - add `s` to itself `n` times
  - `s[i]` - 0 indexed ith item
  - `s[i:j]` - slice
  - `s[i:j:k]` - slice with step

- `len(s)`
- `min(s)`
- `max(s)`
- `s.index(x)` - index of first occurrence
- `s.count(x)` - number of x in s

## String Methods

- `.capitalize()`
- `.center(width, fill character)`
- `.count(substring, start, end)` - num of non-overlapping occurrences
- `.decode(encoding, errors)`
- `.encode(encoding, errors)`
- `.endswith(suffix, start, end)`
- `.expandtabs(tabsize)`
- `.find(sub, start, end)`
- `.format()` - new standard for string formatting
- `.index(sub, start, end)` - like find but raises `ValueError`
- `.isalnum()`
- `.isalpha()`
- `.isdigit()`
- `.islower()`
- `.isspace()`
- `.istitle()`
- `.isupper()`
- `.join(iterable)` - concatenate elements of iterable with src string as separator
- `.ljust(width, fill character)`
- `.lower()`
- `.lstrip([chars])`
- `.partition(sep)`
- `.replace(old, new, count)`
- `.rfind(sub, start, end)`
- `.rindex(sub, start, end)`
- `.rjust(width, fill character)`
- `.rpartition(sep)`
- `.rsplit(sep, maxsplit)`
- `.rstrip([chars])`
- `.split(sep, maxsplit)`
- `.splitlines(sep, maxsplit)`
- `.splitlines([keepends])` - keeps

- .startswith(prefix, start, end)
- .strip([chars])
- .swapcase()
- .title() - title cased
- .translate(table, delete characters)
- .upper()
- .zfill(width) - filled with 0's
- unicode.isnumeric()
- unicode.isdecimal()

## **String Formatting Operations**

## **XRange Type**

## **Mutable Sequence Types**

## **Set Types - set, frozenset**

## **Mapping Types - dict**

## **File Objects**

## **memoryview type**

## **Context Manager Types**

## **Other Built-in Types**

- Modules
- Classes and Class instances
- Functions
- Methods
- Code Objects
- Type Objects
- The Null Object
- The Ellipsis Object
- The NotImplemented Object
- Boolean values
  - bool()

- Internal Objects

## Special Attributes

- `__dict__`
- `__methods__`
- `__members__`
- `__class__`
- `__bases__`
- `__name__`
- attributes for new-style classes (inherits from object, required for `__slots__` and `__getattr__`)
  - `__mro__`
  - `.mro()`
  - `__subclasses__`

## Note review the built-in functions, specifically chr

---

## HOWTOs

---

## Descriptors

---

- an object attribute with "binding behavior" -> one whose attribute access has been overridden by methods in the descriptor protocol
- `__get__()` , `__set__()` , `__delete__()`
- if any are defined for an object, it is a descriptor
- default behavior for attribute access is to get, set, or delete the attribute from an object's dictionary
- a.x lookup chain -> `a.__dict__['x']` -> `type(a).__dict__['x']` -> then base classes of type(a) excluding metaclasses
- mechanism behind properties, methods, static methods, class methods, and super()

- simplify underlying C-code

## Descriptor Protocol

---

```
descr.__get__(self, obj, type=None) --> value
descr.__set__(self, obj, value) --> None
descr.__delete__(self, obj) --> None
```

- overriding any of these makes an object a descriptor
- get & set -> data descriptor
- get -> non-data descriptors
- get, set causes AttributeError -> read-only data descriptor

## Invocation

---

- different for obj vs. class (object is an instance class is the type)
- object (using `object.__getattribute__()`):

```
b.x -> type(b).__dict__['x'].__get__(b, type(b))
```

```
- priority:
  - data descriptors
  - instance variables
  - non-data descriptors
  - `__getattr__()` if provided
- see PyObject_GenericGetAttr() in Objects/object.c
```

- class (using `type.__getattribute__()`):

```
B.x -> B.__dict__['x'].__get__(None, B)
```

- descriptors are invoked by the `__getattribute__()` method
- overriding `__getattribute__()` prevents automatic descriptor calls
- `object.__getattribute__()` and `type.__getattribute__()` make different calls to **get** ().
- data descriptors always override instance dictionaries.
- non-data descriptors may be overridden by instance dictionaries

- calls to super return objects with custom `__getattr__()` for invoking descriptors

## Properties

---

- can call `property()` to build a data descriptor that triggers function calls upon access to an attribute

```
property(fget=None, fset=None, fdel=None, doc=None) -> property attribute
```

## Functional Programming

---

### Iterators

---

- built on iterators
- must implement `__next__()` and throw `StopIteration` when called after end
- built-in `iter()` tries to return an iterator from an object

### Generator expressions and list comprehensions

---

```
line_list = [' line 1\n', 'line 2 \n', ...]

# Generator expression -- returns iterator
stripped_iter = (line.strip() for line in line_list)

# List comprehension -- returns list
stripped_list = [line.strip() for line in line_list]
```

- generator expressions are always in parentheses but can be inside function call parens

```
obj_total = sum(obj.count for obj in list_all_objects())
```

### Generators

---

```
def generate_ints(N):
    for i in range(N):
        yield i
```

- just requires the `yield` keyword, which is detected by Python's bytecode compiler and compiles the function differently as a result
- returns generator object that supports iterator protocol

## Built-in functions (using iterators)

---

- map
- filter
- enumerate
- sorted
- any
- all
- zip

## The itertools module

---

- functions that create a new iterator based on an existing iterator
- functions for treating an iterator's elements as function arguments
- functions for selecting portions of an iterator's output
- a function for grouping an iterator's output
- count
- cycle
- repeat
- chain
- islice
- tee
- starmap
- filterfalse
- dropwhile
- compress
- combinations
- permutations
- combinations\_with\_replacement



- groupby

## Calling functions on elements

---

- operator module ->
  - implements operators as functions

## The functools module

---

- partial -> binds an existing function to arguments
- reduce

## Small functions and the lambda expression

---

```
adder = lambda x, y: x + y
```

- creates an anonymous function that returns the value of the expression

## MRO

---