

Complete UI Specification for BusinessOS AI and a TallyPrime-like Accounting SaaS

Executive summary

This report defines a complete **no-code UI specification** for two products: **BusinessOS AI**, a multi-tenant work operating system with marketing, website publishing, CRM, work execution, invoicing, analytics, and AI assistance; and a **TallyPrime-like multi-tenant Accounting SaaS**, focused on chart of accounts, journals, invoicing, payments, tax, reconciliation, reporting, and auditability. Team size, budget, primary country, payment rails, deployment regions, and AI model vendors are **unspecified** and are treated as such throughout.

The core design recommendation is to build **one shared design system** and **two product shells**. Both products should share the same black-background/white-text visual language, layout primitives, data-entry patterns, accessibility baseline, keyboard model, and admin/developer/help portals. They should diverge at the workflow layer: BusinessOS AI needs more **breadth**, exploratory navigation, dashboards, card/list/canvas experiences, and an AI copilot woven into multiple surfaces; the accounting product needs more **depth**, denser forms and tables, stronger confirmation flows, immutable posting cues, reconciliation workspaces, and reporting states that optimize correctness over speed.

The visual and interaction baseline in this report is intentionally stricter than “looks good in dark mode.” It is designed to satisfy the practical expectations of the World Wide Web Consortium ¹’s **WCAG 2.2** guidance for contrast, keyboard access, focus visibility, target size, status messages, and error prevention, while following the accessible component semantics documented in WAI-ARIA Authoring Practices for dialogs, tabs, grids, comboboxes, and breadcrumbs. It also aligns with official dark-mode and touch-target guidance from Apple ² and accessible color/touch-target guidance from Google ³’s Material Design documentation. In practice, that means: visible 2px focus rings, minimum 44px touch targets for primary controls, 48px for navigation-heavy and mobile-primary controls, confirmation/reversal patterns for financial actions, and accessible status messages that do not rely only on toasts or color. ⁴

For delivery, the cleanest path is a **single component library**, **ten reusable layout templates**, and **page-level specs expressed as route inventories**. That lets a human design team, an AI UI generator, or both produce high-fidelity screens consistently. The estimated UI-only effort is lower for BusinessOS AI than for the accounting product, but the BusinessOS surface area is broader. The accounting product has fewer page archetypes overall, yet significantly higher detail density and more state complexity around posting, reconciliation, and reports. As a result, BusinessOS AI is broader and more exploratory; Accounting SaaS is narrower but more exacting and audit-sensitive.

Design system foundation

Assumptions and constraints

Assumption	Status
Team size	Unspecified
Budget	Unspecified
Primary country / tax jurisdiction	Unspecified
Payment rails	Unspecified
Deployment regions	Unspecified
AI model vendors	Unspecified
Theme model	Fixed: black background / white text system only
UI output	No code; specification only
Accessibility target	WCAG 2.2 AA baseline, with selective AAA-inspired focus treatment for critical controls ⁵

Product-wide design principles

Both products should inherit the same product-wide rules.

Principle	Specification
Visual posture	Strict dark UI: black canvas, near-black surfaces, white/near-white text, bright accent used sparingly.
Interaction posture	Calm, high-density when needed, but never cramped; motion should confirm state changes, not entertain.
Accessibility posture	Keyboard-first, screen-reader-safe, visible focus, live status messaging, high contrast, large touch targets. ⁶
Information architecture	Product shell first, task second, object third. Every major object gets a list page, detail page, and create/edit surface.
State communication	Every save/post/publish/import/reconcile operation must provide loading, success, error, and recoverability cues.
Mobile posture	Same routes as desktop; no feature parity reduction, but navigation and action surfaces collapse into bottom sheets, drawers, and sticky bottom action bars.
Financial posture	All irreversible or financially meaningful actions require confirm/review/reverse patterns. ⁷

Theme tokens

This token set is intentionally opinionated for a black-background system. Text on dark surfaces is always white or near-white. Bright accent fills use **black text/icons** when needed to maintain contrast.

Color tokens

Token	Hex / RGBA	Use
<code>color.bg.canvas</code>	<code>#000000</code>	App/page background
<code>color.bg.surface.1</code>	<code>#0A0A0A</code>	Primary cards, list rows, panels
<code>color.bg.surface.2</code>	<code>#111111</code>	Secondary/elevated panels
<code>color.bg.surface.3</code>	<code>#18181B</code>	Drawers, sticky bars, selected panels
<code>color.bg.surface.overlay</code>	<code>rgba(0,0,0,0.72)</code>	Modal scrim
<code>color.bg.surface.hover</code>	<code>rgba(255,255,255,0.06)</code>	Hover state on dark surfaces
<code>color.bg.surface.active</code>	<code>rgba(255,255,255,0.10)</code>	Pressed/active state
<code>color.bg.surface.selected</code>	<code>rgba(34,211,238,0.16)</code>	Selected row/card background
<code>color.text.primary</code>	<code>#FFFFFF</code>	Primary text
<code>color.text.secondary</code>	<code>#E5E7EB</code>	Subheads, form labels, supporting text
<code>color.text.tertiary</code>	<code>#D4D4D8</code>	Chart labels, table metadata
<code>color.text.muted</code>	<code>#A1A1AA</code>	Helper text, placeholder text, inactive counts
<code>color.text.disabled</code>	<code>#80808A</code>	Disabled labels and non-essential disabled text
<code>color.border.subtle</code>	<code>#61616B</code>	Dividers, input borders, card borders
<code>color.border.strong</code>	<code>#7C7C85</code>	Focus-adjacent outlines, selected borders
<code>color.accent.primary</code>	<code>#22D3EE</code>	Primary accent, active nav, focus-adjacent highlights
<code>color.accent.secondary</code>	<code>#A78BFA</code>	AI-related surfaces, secondary emphasis
<code>color.accent.info</code>	<code>#60A5FA</code>	Informational states, links, chart series

Token	Hex / RGBA	Use
<code>color.state.success</code>	<code>#22C55E</code>	Success, positive delta
<code>color.state.warning</code>	<code>#F59E0B</code>	Warning, draft, pending review
<code>color.state.error</code>	<code>#EF4444</code>	Errors, destructive actions
<code>color.focus.ring</code>	<code>#22D3EE</code>	Primary focus ring
<code>color.focus.ring.alt</code>	<code>#FFFFFF</code>	Focus ring on cyan-accented controls

Contrast rule: all default text tokens on `surface.1` and darker must meet or exceed WCAG AA for standard text; all meaningful borders, chart strokes, focus indicators, and control boundaries must meet the non-text contrast expectation of at least 3:1. The only exceptions allowed are deliberately inactive/decorative elements such as disabled affordances, background gridlines, and non-semantic chart fills. Apple's dark-mode guidance also explicitly recommends keeping foreground/background contrast at no lower than 4.5:1 and striving for 7:1 for custom colors. ⁸

Spacing, typography, elevation, and motion tokens

Token family	Tokens
Spacing	<code>space.0=0</code> , <code>space.1=4</code> , <code>space.2=8</code> , <code>space.3=12</code> , <code>space.4=16</code> , <code>space.5=20</code> , <code>space.6=24</code> , <code>space.8=32</code> , <code>space.10=40</code> , <code>space.12=48</code> , <code>space.16=64</code> , <code>space.20=80</code> , <code>space.24=96</code>
Radius	<code>radius.sm=8</code> , <code>radius.md=12</code> , <code>radius.lg=16</code> , <code>radius.xl=20</code> , <code>radius.round=9999</code>
Typography	<code>type.display.l=48/56/700</code> , <code>display.m=40/48/700</code> , <code>h1=32/40/700</code> , <code>h2=28/36/700</code> , <code>h3=24/32/650</code> , <code>title.l=20/28/650</code> , <code>title.m=18/26/650</code> , <code>body.l=16/24/400</code> , <code>body.m=14/20/400</code> , <code>label.l=14/20/600</code> , <code>label.m=13/18/600</code> , <code>mono.m=13/20/500</code>
Elevation	<code>elevation.0 = border only</code> , <code>elevation.1 = 0 8 24 rgba(0,0,0,0.32)</code> , <code>elevation.2 = 0 16 40 rgba(0,0,0,0.40)</code> , <code>elevation.3 = 0 24 56 rgba(0,0,0,0.48)</code>
Motion	<code>motion.fast=80ms</code> , <code>motion.std=160ms</code> , <code>motion.med=240ms</code> , <code>motion.slow=320ms</code> ; easing: <code>standard</code> , <code>decelerate</code> , <code>emphasized</code> , <code>exit</code>
Reduced motion	When OS/browser requests reduced motion, replace scale/slide animation with opacity and state-change only. WCAG 2.2 continues to emphasize avoiding interaction-triggered animation that can create access issues. ⁹

Layout templates and breakpoints

Breakpoints

Breakpoint	Width	Behavior
xs	0–479	Single column, stacked sections, bottom action bar optional
sm	480–767	Single column, drawers/sheets for filters and navigation
md	768–1023	Tablet; sidebar collapses to icon rail or drawer
lg	1024–1279	Small desktop; persistent sidebar, compact content width
x1	1280–1439	Standard desktop
2x1	1440–1919	Wide desktop
3x1	1920+	Dashboard/report density mode; max-width caps still apply

Page templates

Template ID	Desktop layout	Sidebar / header spec	Content max width	Tablet behavior	Mobile behavior	Best use
T-Marketing	12-col grid	Header 80px	1280–1440px	8-col	4-col stacked	Home, pricing, features
T-AuthSplit	5/7 split	No sidebar, top utility bar 56px	1200px	Stacks to 1-col + illustration drawer	Single column form	Login, signup, reset
T-Wizard	Centered 8-col content	Progress header 72px	720px form column	Same	Same	Onboarding/setup
T-AppShell	12-col content grid	Sidebar 280px, collapsed 72px; topbar 64px	1600px	Icon rail or slide-in sidebar	Hidden sidebar, topbar + bottom nav/ action bar	Dashboard shell
T-DataIndex	T-AppShell + sticky toolbar	Toolbar 56px	1600px	Filters compress to drawers	Filters in bottom sheet	Lists, queues, ledgers

Template ID	Desktop layout	Sidebar / header spec	Content max width	Tablet behavior	Mobile behavior	Best use
T-DetailSplit	8/4 or 7/5 split	T-AppShell shell	1600px	Right rail collapses under primary content	Single column with sticky summary card	Detail views
T-EditorCanvas	Left rail / center canvas / right inspector	Left 280px, right 320px, topbar 64px	Canvas 960–1200px	One rail drawer at a time	Full-screen canvas + bottom floating actions	Website builder, proposal editor
T-ReportWide	12-col wide report	Optional secondary report nav	1680px	Charts/tables stack	KPI cards stack first	Analytics, accounting reports
T-AdminConsole	Dense shell	Sidebar 280px + env bar 40px	1760px	Same with collapsed sidebar	Limited mobile use, admin warning banner	Super-admin pages
T-DocsPortal	3-column	Left nav 280px, right TOC 240px	840px reading column	Right TOC collapses	Single column docs	Help/docs/developer portal

State taxonomy

All pages inherit the following state taxonomy.

State	Required UI treatment
Loading	Skeletons for tables/cards/forms; never spinner-only on primary content
Refreshing	Inline progress bar or subtle loading badge; preserve existing content
Empty	Explain why it is empty and provide next best action
No results	Preserve query/filter context and provide reset action
Success	Persist status near the affected object and optionally toast it
Inline error	Attach to field/object, not only toast

State	Required UI treatment
Blocking error	Full-page recovery state with retry/support links
Permission denied	Explain missing role/plan and route to request/upgrade
Offline / network degraded	Sticky banner + queued actions if possible
Locked / archived	Read-only shell with reason and available next steps

Reusable component library

The naming system should be stable and machine-friendly for a UI generator.

Naming convention

Prefix	Meaning	Example
L -	Layout primitive	L-Stack , L-Grid , L-Section
Nav -	Navigation	Nav-Sidebar , Nav-Breadcrumbs
Data -	Data display	Data-Table , Data-KPI , Data-ChartLine
Form -	Inputs/validation	Form-TextField , Form-ErrorSummary
Ovl -	Overlays	Ovl-Modal , Ovl-Drawer , Ovl-Popover
Feed -	Timelines/activity/notifications	Feed-Timeline , Feed-Toast
AI -	AI surfaces	AI-Panel , AI-ContextPicker
Media -	File/media/player	Media-FileGrid , Media-Player
Dev -	Docs/code components	Dev-CodeBlock , Dev-EndpointCard

Component specification table

Component	Purpose	Key props / slots	Variants	States	Accessibility and keyboard
L-Stack	Vertical spacing primitive	gap, align, justify, wrap	dense, regular, relaxed	n/a	Structural only; no ARIA unless semantic wrapper needed
L-Grid	Grid layout	cols, gap, minColWidth, areas	2, 3, 4, 12-col	n/a	Respect meaningful source order for screen readers

Component	Purpose	Key props / slots	Variants	States	Accessibility and keyboard
L-Section	Section shell with title/ actions	title, subtitle, actions, aside	standard, bordered, elevated	loading, empty	Heading level must be provided explicitly
Nav-Sidebar	Primary app navigation	items, activeKey, collapsed, badges	expanded, icon-rail, temporary-drawer	active, hover, disabled	Landmarked as navigation; arrow-key optional; always tabbable
Nav-Topbar	Global actions and context	title, searchSlot, actions, profileMenu	marketing, app, admin	sticky, scrolled	landmark header; skip link target below
Nav-Breadcrumbs	Hierarchy and location	items, currentKey	inline, compact	truncation	Use navigation landmark; current item has <code>aria-current="page"</code> per APG. ¹⁰
Data-Table	Dense records grid	columns, rows, sort, selection, rowActions	compact, comfortable, report	loading, empty, noResults, error	Row/column headers, sortable headers announced, keyboard support follows grid/table choice; if interactive grid is used, manage focus explicitly. ¹¹
Data-KPI	Metric card	label, value, delta, sparkline, trendText	positive, neutral, warning	loading	Not color-only; include text indicators
Data-Chart*	Charts	series, xAxis, yAxis, legend, annotations	line, bar, area, donut	loading, empty	Use labels/tooltips accessible via focus; do not rely on color alone. ¹²

Component	Purpose	Key props / slots	Variants	States	Accessibility and keyboard
<code>Form-TextField</code>	Single-line input	label, hint, prefix, suffix, validation, format	default, search, currency, code	focus, error, disabled, readonly	Persistent label, accessible name, helper/error tied via description; 44px min target. ¹³
<code>Form-TextArea</code>	Multiline input	label, hint, resize, maxLength	plain, autosize	error, disabled	Same as text field
<code>Form-Select</code>	Single choice	label, options, value, search, async	native, combobox, grouped	loading, empty, error	Editable/ searchable versions follow combobox APG; do not steal browser text-editing keys. ¹⁴
<code>Form-DateRange</code>	Date range selection	from, to, presets, timezone	inline, popover, modal	invalidRange	Calendar dialogs must follow dialog + grid patterns
<code>Form-Checkbox/ Radio/Switch</code>	Boolean or one-of-many	label, checked, description	standalone, list row, card	disabled	Target size, name/ role/value, visible focus required. ¹⁵
<code>Form-ErrorSummary</code>	Form-wide validation summary	count, items, scrollTargets	dismissible, sticky	visible/hidden	Focus here after failed submit on long forms
<code>Ovl-Modal</code>	Blocking decision or focused form	title, description, body, actions, destructive	confirm, form, alert	opening, open, closing	Trap focus, <code>Escape</code> closes when safe, return focus to invoker, use <code>aria-modal</code> only for true modals. ¹⁶
<code>Ovl-Drawer</code>	Supplementary task	side, size, header, footer actions	left, right, bottom-sheet	open, dirty, closing	Prefer for non-blocking edits; same focus-return rules as dialog

Component	Purpose	Key props / slots	Variants	States	Accessibility and keyboard
<code>Data-Card</code>	Generic card surface	title, meta, actions, footer	flat, bordered, elevated	selected, hover	Entire card should not become a mysterious button without visible affordance
<code>Data-Kanban</code>	Deal/task pipeline board	columns, cards, WIP hints	compact, spacious	drag, blocked, empty	Drag must have keyboard alternative; columns announced as lists
<code>Feed-Timeline</code>	Activity stream	items, filters, actor, timestamp	compact, detailed	loading, empty	Use list semantics; announce new items in status region if injected live
<code>Media-FileManager</code>	Files/assets browser	folders, files, viewMode, sort	grid, list	dragging, upload, offline	Drag/drop must have button alternative; file type text must be present
<code>Form-RichTextEditor</code>	Long-form content	toolbar, blocks, mentions, media	simple, full, comment	readonly, dirty, conflict	Toolbar controls need names/roles; editor area must expose formatting state accessibly
<code>AI-Panel</code>	Copilot side panel	thread, sources, tools, suggestions	docked, modal, full-page	generating, stopped, error, needsConfirm	Prompt input labeled; tool actions explicit; generated actions require confirmation
<code>Dev-CodeBlock</code>	API examples and copyable snippets	language, title, wrap, copyLabel	inline, block	copied	Code needs copy button with status message; preserve tab stops logically

Component	Purpose	Key props / slots	Variants	States	Accessibility and keyboard
Media-Player	Optional video/audio playback	title, poster, transcript, captions, playbackRate	inline, modal, full	buffering, ended, error	If used, expose captions/ transcript and keyboard playback controls
Feed-Toast	Brief non-blocking notification	kind, title, description, action	success, warning, error, info	queued, visible	Important status updates must be programmatically exposed, not visual only. ¹⁷
Nav-CommandPalette	Global navigation and create actions	query, groups, shortcuts, recentItems	dialog, compact	open, searching, noResults	Combines dialog + combobox/listbox semantics; Cmd/Ctrl+K default
Data-Search	Local or global search	query, scope, suggestions	inline, toolbar, full-page	loading, noResults	Search suggestions follow combobox rules
Data-Filters	Faceted filters	chips, ranges, savedViews	inline-bar, drawer, sheet	dirty, applied	Chips need visible selected state beyond color
Data-Pagination	Page or cursor nav	page, size, total, cursor	pager, infinite, loadMore	disabled, loading	Targets follow size guidance; current page announced
Identity-Avatar	Person/org image	name, src, fallback, status	xs–xl	loading, missing	Fallback initials and accessible alt
Data-Badge	Small semantic label	label, tone, icon	success, warning, error, info, neutral	subtle, solid	Never color-only; include text

BusinessOS AI page inventory

Persona legend

Code	Persona
OWN	Workspace owner / admin
MKT	Marketer / website manager

Code	Persona
SAL	Sales / account manager
PM	Project manager / operations
FIN	Finance / billing operator
CLT	Client / portal guest
DEV	Developer / integration admin
SUP	Support / success
SA	Super-admin

All BusinessOS AI pages inherit the design system rules above. Unless stated otherwise, each page uses the relevant template from the layout table, supports keyboard-only navigation, visible focus, skip links, status-message announcements, and responsive collapse consistent with its template. Sticky bars must not obscure focused controls. ¹⁸

Public marketing, auth, onboarding, billing, help, and developer pages

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
/ Home	Position product, drive sign-up/demo. Personas: OWN, MKT, PM.	Hero copy, feature blocks, logos, pricing CTA, testimonials, product shots.	T-Marketing , hero, KPI cards, feature sections, footer CTA.	loading, fallback illustration, form-submit success/error.	Mobile stacks hero + CTA first; all screenshots need alt text; CTA buttons 48px min; subtle parallax disabled under reduced motion.
/features	Explain modules. Personas: OWN, MKT, SAL.	Feature group metadata, FAQ items, CTA slots.	T-Marketing , tabbed feature groups, cards, diagrams.	empty FAQ set, loading.	Tabs must follow APG semantics if interactive. ¹⁹

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
/solutions	Use-case landing. Personas: agencies, SMBs, consultants.	Persona-specific copy, workflow examples, ROI cards.	T-Marketing , segment switcher, comparison cards.	loading, no-segment.	Segment switcher should not trap focus; maintain announced heading changes.
/templates	Website and workflow templates. Personas: MKT, OWN.	Template tiles, preview media, categories, filters.	T-Marketing , gallery grid, filters, modal preview.	empty gallery, load, preview error.	On mobile, filters open as bottom sheet; preview modal follows Ov1-Modal .
/pricing	Plan comparison. Personas: OWN, FIN.	Plans, feature matrix, FAQs, annual/monthly toggle.	T-Marketing , pricing cards, comparison table.	loading, unavailable region info.	Comparison table collapses into accordions on mobile; plan toggle announced as state change.
/integrations	Connector catalog. Personas: DEV, OWN.	Integration cards, categories, auth type, docs links.	T-Marketing , searchable grid, docs cards.	no results, load.	Search uses combobox semantics if suggestions appear. ¹⁴
/security	Trust page. Personas: OWN, procurement.	Controls, FAQs, contact CTA.	T-Marketing , audit cards, policy links.	loading.	Dense text page with strong heading hierarchy and breadcrumb if nested.

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
<code>/docs</code>	Product docs home. Personas: DEV, OWN, PM.	Nav tree, featured guides, changelog, search index.	T- <code>DocsPortal</code> , docs nav, search, article cards.	empty search, 404 docs page.	Docs search suggestions follow combobox rules; keyboard focus must stay visible around sticky TOC.
<code>/contact</code> or <code>/demo</code>	Contact/demo request. Personas: prospects.	Form fields, routing rules, calendar embed props if used.	T- <code>Marketing</code> , lead form, availability callout.	inline validation, success, spam-prevent error.	Form labels persistent; success uses live region; avoid placeholder-only labels.
<code>/login</code>	Authentication entry. Personas: all.	Providers, email, password, magic-link option, SSO slug.	T- <code>AuthSplit</code> , auth form, legal footer.	inline error, locked account, email sent.	Password manager friendly naming and labels are mandatory. 20
<code>/signup</code>	New account creation. Personas: prospects.	Name, email, password, accepted terms, invite token if present.	T- <code>AuthSplit</code> , form, plan context card.	password error, email verification sent.	Show password requirements live; avoid motion-only validation cues.
<code>/forgot-password</code> / <code>/reset-password</code>	Recovery flow. Personas: all.	Email, token, new password, expiry state.	T- <code>AuthSplit</code> , recovery form.	email sent, expired token, weak password.	Status messages must be audible without forced modal. 21

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
<code>/workspace/select</code>	Choose or create tenant. Personas: all existing users.	Workspace list, roles, recent, plan badges.	<code>T-Wizard</code> , list cards, create CTA.	empty, loading.	Entire workspace card not sole affordance; provide visible button/enter semantics.
<code>/onboarding</code>	Workspace setup wizard. Personas: OWN.	Company name, logo, business type, goals, imported data, invite list.	<code>T-Wizard</code> , stepper, forms, checklist.	draft save, validation errors, completed.	Stepper must expose current step; wizard progress announced; router preserves progress.
<code>/billing</code>	Self-service subscription. Personas: OWN, FIN.	Current plan, usage meters, invoices, payment method props.	<code>T-DataIndex</code> , summary cards, usage chart, invoices table.	payment failure, upgrade success, proration preview.	Financial actions require review modal and inline invoice totals.
<code>/developer</code>	Developer portal landing. Personas: DEV.	Intro content, API groups, recent webhooks, keys summary.	<code>T-DocsPortal</code> or <code>T-AppShell</code> , nav, endpoint cards, code blocks.	access denied, loading.	Code blocks need copy feedback via status message. ²¹
<code>/help</code>	In-app help center home. Personas: all.	Article categories, tickets, search, contact pathways.	<code>T-DocsPortal</code> , category cards, search, recent articles.	empty KB, search no results.	Search must preserve focus, provide clear result count.

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
<code>/status / / changelog</code>	Reliability and release comms. Personas: all.	Incident feed, release notes, maintenance windows.	<code>T-DocsPortal</code> , timeline, badges, subscription CTA.	empty, degraded.	Timelines use list semantics; status colors always paired with text.

Core product pages

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
<code>/app</code> Dashboard	Workspace summary and launch point. Personas: OWN, PM, SAL, FIN.	KPIs, tasks due, site performance, pipeline, invoices due, AI suggestions.	<code>T-AppShell</code> , KPI cards, charts, timeline, quick actions, <code>AI-Panel</code> trigger.	first-run empty, refresh, widget error, partial data.	Cards reflow from 4-col to stacked; keyboard shortcut hints in topbar; widgets remember collapse state.
<code>/app/sites</code>	Site list. Personas: MKT, OWN.	Sites, status, domains, traffic summary, form counts.	<code>T-DataIndex</code> , table/card switch, filters, create CTA.	empty starter state, domain error, publishing in progress.	On mobile default to cards; primary action sticky bottom button.

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
<code>/app/sites/:siteId</code>	Site overview. Personas: MKT.	Site metadata, pages, recent deployments, forms, analytics summary.	T- <code>DetailSplit</code> , header summary, tabs, activity.	unpublished, domain verifying, no traffic.	Tabs manual-activation preferred to reduce accidental panel changes on keyboard. 19
<code>/app/sites/:siteId/editor</code>	Page/website builder. Personas: MKT.	Page tree, blocks, theme tokens, asset library, selected node props, preview mode.	T- <code>EditorCanvas</code> , left block library, center canvas, right inspector, topbar actions.	unsaved changes, publishing, block error, preview unavailable.	On tablet/mobile, left/right rails become drawers; block drag must have keyboard reorder alternative; visible dirty-state pill in header.
<code>/app/sites/:siteId/pages/:pageId/settings</code>	Page SEO/permalinks/settings. Personas: MKT.	Title, slug, metadata, visibility, redirects.	T- <code>DetailSplit</code> , forms, preview card.	validation, duplicate slug, published success.	Meta preview updates live; slug conflicts surface inline.
<code>/app/sites/:siteId/publish</code>	Domain and publish center. Personas: MKT, OWN.	Environment status, domain records, SSL state, release history, rollback options.	T- <code>DetailSplit</code> , release timeline, domain cards, destructive confirmations.	verifying DNS, publish success, publish failure, rollback pending.	Financial/legal-style confirmation pattern for destructive rollback or unpublish because site changes can affect customer-facing data.

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
<code>/app/forms</code>	Form submissions and routing. Personas: MKT, SAL, SUP.	Form schemas, submissions, spam flags, lead routing rules.	<code>T-DataIndex</code> , tabs, table, detail drawer.	no submissions, filtered no results, delivery failure.	Row enter opens drawer; selection controls have explicit labels.
<code>/app/crm/contacts</code>	Contact list. Personas: SAL, OWN.	Contact rows, accounts, tags, source, status, owner.	<code>T-DataIndex</code> , table, filters, saved views.	empty, no results, import failure.	Dense table switches to stacked cards on mobile; selection summary sticky.
<code>/app/crm/contacts/:id</code>	Contact detail. Personas: SAL, PM, SUP.	Profile, timeline, notes, tasks, deals, files, activity.	<code>T-DetailSplit</code> , profile card, tabs, timeline.	no activity, sync error, archived.	Timeline uses list semantics; note editor shortcut <code>N</code> .
<code>/app/crm/deals</code>	Pipeline board. Personas: SAL, OWN.	Stages, cards, values, SLA, owner, next steps.	<code>T-AppShell</code> , kanban board + list toggle.	empty pipeline, stage overload, drag blocked.	Must support keyboard move between columns/ cards; drag is not the only method.
<code>/app/crm/deals/:id</code>	Deal detail and conversion hub. Personas: SAL, FIN.	Account link, expected revenue, docs, proposals, invoice link, tasks.	<code>T-DetailSplit</code> , summary card, tabs, activity, action rail.	lost/won state, missing owner, conversion success.	"Convert to invoice" opens review drawer with explicit confirm step.

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
<code>/app/projects</code>	Projects index. Personas: PM, OWN.	Project rows, health, clients, due dates, margin, assignees.	<code>T-DataIndex</code> , tables/cards, filters.	empty, stale integration.	Health colors paired with text and icon.
<code>/app/projects/:id</code>	Project workspace. Personas: PM, CLT.	Milestones, tasks, files, comments, client visibility.	<code>T-DetailSplit</code> , tabs, kanban/list, file pane, timeline.	empty milestone set, overdue warning, locked for closed project.	Client-visible items require clear badge and privacy toggle.
<code>/app/tasks</code>	My work / team tasks. Personas: PM, SAL, OWN.	Task rows, due dates, assignees, linked records.	<code>T-DataIndex</code> , list/calendar toggle.	no tasks, overdue state.	Keyboard shortcuts for mark done, assign, date bump.
<code>/app/files</code>	Shared files and knowledge. Personas: PM, OWN, MKT.	Folder tree, files, previews, permissions, AI indexing state.	<code>T-DetailSplit</code> , file grid/list, preview drawer, metadata rail.	upload in progress, processing, preview error, no files.	Drag/drop must have button path; file selection announced.
<code>/app/proposals</code>	Proposal list. Personas: SAL, FIN.	Proposals, statuses, client, amount, last edited, approvals.	<code>T-DataIndex</code> , table.	none, expired, approval blocked.	Row quick actions via hover on desktop, explicit kebab on mobile.

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
<code>/app/proposals/:id/editor</code>	Proposal editor. Personas: SAL, FIN.	Sections, pricing blocks, signatures, approval chain, version history.	T-EditorCanvas, blocks, inspector, comments.	unsaved draft, sent, accepted, expired.	Rich text toolbar fully keyboard reachable; send action requires preflight summary.
<code>/app/invoices</code>	Invoice list. Personas: FIN, OWN.	Invoice rows, status, due dates, client, amount owed.	T-DataIndex, table, aging chips.	none, overdue, payment sync error.	Status changes announced through live region and row badge.
<code>/app/invoices/:id</code>	Invoice detail. Personas: FIN, CLT.	Header, line items, taxes, payment link, timeline, PDF metadata.	T-DetailSplit, invoice preview, summary, timeline, actions.	draft, sent, partially paid, paid, failed reminder.	Monetary values right-aligned and read clearly; destructive actions require confirm/reverse affordance.
<code>/app/portal/:clientId</code>	Client portal. Personas: CLT.	Shared projects, invoices, files, messages, approvals.	T-AppShell simplified, cards, tables, timeline.	no shared items, expired invite, permission denied.	Client shell removes internal-only navigation; keyboard path remains complete.
<code>/app/automations</code>	Workflow list and run history. Personas: OWN, PM, DEV.	Trigger definitions, statuses, last runs, error counts.	T-DataIndex, cards/table, run drawer.	no workflows, paused, failed run.	Error states need plain-language cause, not code only.

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
<code>/app/automations/:id/builder</code>	Rule builder. Personas: OWN, DEV.	Trigger schema, actions, conditions, test payload, validation.	T-EditorCanvas, node canvas or step list, inspector, run logs.	invalid flow, test success/failure, dirty.	Node graph must also expose step-list editing for accessibility.
<code>/app/reports</code>	Analytics and business reports hub. Personas: OWN, PM, FIN.	Report cards, saved views, scheduled reports, date range.	T-ReportWide, cards, charts, tables.	no data, stale connector, export started.	Charts need text summaries and export routes.
<code>/app/ai</code>	AI copilot hub. Personas: all internal roles.	Threads, saved prompts, context sets, recent actions, evaluations.	T-AppShell, chat panel, prompt library, source chips.	generating, needs confirmation, blocked action, model unavailable.	Generated actions never auto-commit for invoices, publishing, or client-facing sends without explicit confirmation.

Settings, admin, and super-admin pages

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
<code>/app/settings/general</code>	Workspace profile, branding, defaults. Personas: OWN.	Name, logo, timezone, locale, brand tokens.	T-DetailSplit, forms, uploaders.	dirty, save success, validation failure.	Show last-saved timestamp; upload progress announced.

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
<code>/app/settings/team</code>	Members and roles. Personas: OWN.	Members, roles, invites, seat counts.	<code>T-DataIndex</code> , table, invite drawer.	license cap reached, invite sent, remove blocked.	Removal confirmation returns focus to triggering row action.
<code>/app/settings/integrations</code>	Connector setup. Personas: OWN, DEV.	Integration cards, auth status, scopes, test connections.	<code>T-DataIndex</code> , cards, drawers.	disconnected, auth failed, retry success.	Scope changes require review modal.
<code>/app/settings/branding</code>	Theme/logo/email appearance. Personas: OWN, MKT.	Tokens, logos, preview surfaces.	<code>T-DetailSplit</code> , theme preview cards, upload forms.	contrast warning, preview unavailable.	Contrast checker badge visible for custom brand overrides.
<code>/app/settings/api-keys</code>	Keys and webhooks. Personas: DEV.	Existing keys, scopes, last used, webhook endpoints.	<code>T-DataIndex</code> , table, reveal modal, code blocks.	revoked, never used, delivery errors.	Secret reveal requires confirm and obscured default display.
<code>/admin</code>	Super-admin dashboard. Personas: SA.	Tenants, system health, usage spikes, incidents.	<code>T-AdminConsole</code> , KPI cards, charts, tables.	partial outages, stale worker metrics.	Admin-only warning banner, denser data-friendly layout.
<code>/admin/tenants</code>	Tenant management. Personas: SA.	Tenant rows, plans, status, tickets, growth.	<code>T-DataIndex</code> , table with detail drawer.	none, suspended, restore pending.	Bulk actions need strong confirmation.
<code>/admin/users</code>	Cross-tenant user ops. Personas: SA.	User rows, memberships, flags, locks.	<code>T-DataIndex</code> , table.	no results, locked user.	Treat impersonation as destructive-risk flow with confirmations and audit banner.

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
<code>/admin/plans</code>	feature gating and plans	Plan definitions, quotas, overrides.	T- <code>DetailSplit</code> , tables, editable forms.	invalid quota schema, save success.	Numeric inputs must have labels/units and clear error text.
<code>/admin/audit</code>	Audit stream. Personas: SA.	Actor, action, target, before/after summary, filters.	T- <code>ReportWide</code> , table, diff drawer, timeline.	huge result sets, export pending.	Diffs need text labels, not color-only additions/removals.

Accounting SaaS page inventory

Persona legend

Code	Persona
<code>OWN</code>	Business owner / admin
<code>ACC</code>	Accountant
<code>BK</code>	Bookkeeper
<code>AR</code>	Accounts receivable clerk
<code>AP</code>	Accounts payable clerk
<code>TAX</code>	Tax manager
<code>AUD</code>	Auditor / reviewer
<code>DEV</code>	Integration admin
<code>SA</code>	Super-admin

All accounting pages inherit the same page-level accessibility baseline, but they also inherit one additional rule: **financial actions must support confirm, correct, or reverse**. That is particularly important for journal posting, invoice issuance, payment application, tax filing, and period close. ⁷

Public, auth, onboarding, billing, help, and developer pages

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
/ Home	Product positioning for accounting SaaS. Personas: OWN, ACC.	Value prop, feature clusters, trust, pricing CTA.	T- Marketing, hero, feature comparisons, trust blocks.	loading, CTA success/error.	Keep hero concise; avoid animated number counters under reduced motion.
/features	Explain accounting capabilities. Personas: OWN, ACC, TAX.	Feature groups, report examples, localization notes.	T- Marketing, cards, report previews, FAQs.	loading.	Report screenshots need textual companion descriptions.
/pricing	Plan matrix and limits. Personas: OWN, FIN-equivalent buyer.	Plans, companies, users, filing/reconciliation features.	T- Marketing, pricing cards, matrix.	unavailable payment rail, lead form fallback.	Tables collapse into feature accordions on mobile.
/localizations	Country/tax pack explanation. Personas: OWN, TAX.	Country list, supported features, disclaimers.	T- Marketing, cards, search.	no country match.	Search suggestions must be accessible; legal disclaimers readable and contrast-safe.
/security	Trust and audit page. Personas: ACC, procurement.	Controls, retention, backup, auditability claims.	T- Marketing, cards, policy links.	loading.	Dense content page; strong hierarchy.

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
<code>/docs</code>	Docs and API knowledge. Personas: ACC, DEV.	Navigation tree, implementation guides, release notes.	T- <code>DocsPortal</code> .	search empty, 404.	Long-form reading column optimized for keyboard and screen readers.
<code>/contact / /demo</code>	Sales and support intake. Personas: prospects.	Form and routing metadata.	T- <code>Marketing</code> , forms.	success, validation error.	Use grouped inputs cautiously; keep labels persistent.
<code>/login</code>	Auth entry. Personas: all.	Org slug, email, password, SSO.	T- <code>AuthSplit</code> .	locked account, wrong company, reset link sent.	Password manager compatibility required. 20
<code>/signup</code>	New organization sign-up. Personas: OWN.	User, company, terms, plan seed.	T- <code>AuthSplit</code> .	validation, email verify.	Company setup continues through onboarding wizard to avoid long initial form.
<code>/company/select</code>	Choose organization. Personas: users with multiple companies.	Company cards, roles, fiscal-year badges.	T- <code>Wizard</code> .	empty, loading.	Enter key activates selected card; active state must be visible.

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
<code>/onboarding</code>	Company setup wizard. Personas: OWN, ACC.	Company profile, currency, fiscal year, tax registration, COA template, import options.	<code>T-Wizard</code> , stepper, preview cards.	draft, validation, completion.	Step list must use clear labels; country-dependent steps only appear when relevant to chosen localization.
<code>/billing</code>	Plan, usage, payment method. Personas: OWN.	Users, companies, documents processed, storage, invoices.	<code>T-DataIndex</code> .	payment failed, upgrade success.	Billing tables use right alignment and explicit currency codes.
<code>/help</code>	Knowledge base and support. Personas: ACC, BK, OWN.	How-to articles, accounting glossary, ticket links.	<code>T-DocsPortal</code> .	no results, stale docs.	Include glossary hover/disclosure for accounting jargon.
<code>/developer</code>	API and integration hub. Personas: DEV.	API groups, webhooks, import endpoints, OAuth placeholders if any.	<code>T-DocsPortal</code> or <code>T-AppShell</code> .	access denied, loading.	Code examples need copy/live status messages.
<code>/status</code> / <code>/changelog</code>	Service and release comms. Personas: all.	incident feed, maintenance, accounting/tax changes.	<code>T-DocsPortal</code> , timeline.	no incidents, maintenance window active.	Tax-impacting changes should carry warning badge and summary.

Core accounting pages

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
<code>/app</code> Dashboard	Operations and finance overview. Personas: OWN, ACC, BK.	Cash, receivables, payables, tax due, reconciliation queue, close-period warnings.	<code>T-AppShell</code> , KPI cards, charts, aging cards, alerts.	first-run, stale bank feed, tax warning.	Avoid over-visualization; top section should answer "what needs action now."
<code>/app/accounts</code>	Chart of accounts list. Personas: ACC, AUD.	Account code, name, type, parent, active state, balances.	<code>T-DataIndex</code> , tree-table, filters, create drawer.	empty COA, import in progress, locked template.	Tree-table needs clear expand/collapse names and keyboard support.
<code>/app/accounts/:id</code>	Account detail. Personas: ACC, AUD.	Metadata, opening balance, transactions, related tax code, permissions.	<code>T-DetailSplit</code> , summary card, ledger table.	inactive, period-locked edits.	Balance presentation must include debit/credit context, not only sign.
<code>/app/journals</code>	Journal entry list. Personas: ACC, BK, AUD.	Journal entries, source doc, posted state, period, reversal link.	<code>T-DataIndex</code> , table, filters, saved views.	none, posting queue delay, import error.	Posted state badge and lock icon always visible.

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
<code>/app/journals/new</code>	Create journal entry. Personas: ACC.	Header, lines, debits/credits, dimensions, attachments, notes.	T- DetailSplit or form-focused T-Wizard, line grid, totals footer.	unbalanced, validation, draft saved.	Keyboard-heavy entry surface; line items must support fast tabbing and row add/remove without breaking focus.
<code>/app/journals/:id/review</code>	Review and post journal. Personas: ACC, AUD.	Draft entry, diff, warnings, period status, posting metadata.	T- DetailSplit, read-only line grid, alert stack, confirm actions.	balanced ready, blocked, posted, reversal created.	Because this can trigger financial transactions/data changes, provide review-confirm-reverse affordances. 7
<code>/app/customers</code>	Customer directory. Personas: AR, ACC.	Customer rows, balances, credit limits, terms.	T- DataIndex, table/cards.	none, import failure.	Financial badges not color-only.
<code>/app/vendors</code>	Vendor directory. Personas: AP, ACC.	Vendor rows, payable balances, terms, tax IDs.	T- DataIndex.	none, validation error.	Same as customers.
<code>/app/sales-invoices</code>	AR invoice list. Personas: AR, OWN.	Invoice rows, status, due date, amount, paid amount.	T- DataIndex, table, aging filters.	none, overdue-focus, email failure.	Right-align numbers; overdue badge includes text and icon.

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
<code>/app/sales-invoices/new</code>	Create and review sales invoice. Personas: AR.	Customer, line items, tax, terms, payment link, attachments.	T- DetailSplit , form + totals card.	draft, tax warning, validation, sent.	Before sending/posting, show review panel with totals and tax breakdown.
<code>/app/sales-invoices/:id</code>	Invoice detail. Personas: AR, ACC, OWN.	Header, ledger impact summary, timeline, payments, PDF.	T- DetailSplit , invoice preview, timeline, summary cards.	draft, posted, partially paid, voided.	"Void" and "credit note" actions must be distinct and clearly explained.
<code>/app/purchase-bills</code>	AP bill list. Personas: AP, ACC.	Bill rows, due dates, vendor, amount, status.	T- DataIndex .	none, duplicate suspicion.	Duplicate bill warnings visible before final post.
<code>/app/purchase-bills/new</code>	Create bill. Personas: AP.	Vendor, items, expense accounts, tax, due date, attachments.	T- DetailSplit , form + summary rail.	OCR pending if used, validation, saved.	Attachment upload must not steal focus; post action gated behind review step.
<code>/app/payments</code>	Payment and receipt list. Personas: AR, AP, ACC.	Payments, methods, allocations, unapplied amount.	T- DataIndex .	none, sync error, reversal pending.	Allocation chips should have text labels and keyboard-removable items.
<code>/app/payments/new</code>	Record payment/receipt. Personas: AR, AP.	Counterparty, amount, account, allocations, taxes/fees if needed.	T- DetailSplit , step form, allocations table.	over-allocation, partial allocation, success.	Numeric keypad friendliness on mobile; review before final submit.

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
<code>/app/bank-accounts</code>	Bank account management. Personas: ACC, OWN.	Account names, masked numbers, status, last sync.	T- <code>DataIndex</code> , cards/table.	disconnected, stale sync.	Masking default and explicit reveal.
<code>/app/reconciliation</code>	Bank reconciliation workspace. Personas: ACC, BK.	Statement lines, suggested matches, ledger hits, confidence, rules.	T- <code>ReportWide</code> , split-pane list + match panel + action tray.	no statement lines, all reconciled, conflicting match, offline.	Highest-density page in product; keyboard shortcuts essential (<code>J/K</code> , accept/reject, next unresolved).
<code>/app/tax/settings</code>	Tax engine setup. Personas: TAX, ACC.	Jurisdiction, registrations, tax codes/ rates, invoice behaviors.	T- <code>DetailSplit</code> , forms, tables, effective-date history.	missing registration, overlapping rate periods.	Effective dates and rate changes need timeline clarity.
<code>/app/tax/returns</code>	Return list and filing prep. Personas: TAX.	Periods, statuses, due dates, amounts, working papers.	T- <code>DataIndex</code> , table + status filters.	due soon, draft, filed, amendment required.	Filing actions must use confirm/review steps.
<code>/app/reports</code>	Reports hub. Personas: OWN, ACC, AUD.	Report catalog, favorites, schedules, date ranges.	T- <code>ReportWide</code> , report cards, recent reports.	no reports configured.	Reports grouped by task: compliance, management, audit.
<code>/app/reports/p-and-l</code>	P&L report. Personas: OWN, ACC.	Date range, comparison period, account groupings.	T- <code>ReportWide</code> , table, charts, export bar.	no data, comparison unavailable.	Must expose textual totals before charts.

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
<code>/app/reports/balance-sheet</code>	Balance sheet. Personas: OWN, ACC, AUD.	Assets/liabilities/equity by date.	T-ReportWide, hierarchical table.	no data, unposted opening balance warning.	Hierarchical expansion controlled by keyboard and persistable.
<code>/app/reports/general-ledger</code>	Transaction-level ledger report. Personas: ACC, AUD.	Accounts, periods, entries, filters, export.	T-ReportWide, table, filter rail.	huge dataset, export pending.	Dense table must remain performant and keyboard-readable.
<code>/app/reports/trial-balance</code>	Trial balance. Personas: ACC, AUD.	Debit/credit balances by account.	T-ReportWide, table.	imbalance alert if system issue.	Zero-balance toggles announced and preserved.
<code>/app/reports/ar-aging</code> and <code>/app/reports/ap-aging</code>	Aging analysis. Personas: AR, AP, OWN.	Buckets, counterparties, overdue totals.	T-ReportWide, table, histogram optional.	no overdue, no open docs.	Histogram never replaces numeric table.
<code>/app/period-close</code>	Close and reopen periods. Personas: ACC, OWN, AUD.	Period states, exceptions, unresolved items, checklist.	T-DetailSplit, checklist, warning cards, confirmations.	blocked close, closed, reopen requested.	This is a legally/financially sensitive flow; requires review-confirm with clear reversibility or role escalation.

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
<code>/app/imports</code>	Import jobs and opening balances. Personas: ACC, BK, DEV.	Job status, mappings, file history, errors.	T- <code>DataIndex</code> , job table, diff drawer.	parsing, validation errors, applied.	Preserve column mapping labels and keyboard-navigable review grid.

Settings, admin, and super-admin pages

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
<code>/app/settings/company</code>	Company identity and defaults. Personas: OWN, ACC.	Company name, tax IDs, fiscal year, currency, locale.	T- <code>DetailSplit</code> , form sections.	dirty, validation, save success.	Tax IDs and dates need explicit format help.
<code>/app/settings/users-roles</code>	Users, roles, approvals. Personas: OWN.	User list, roles, invite states, approval roles.	T- <code>DataIndex</code> , table + invite drawer.	invite pending, seat warning.	Approval-role changes require confirmation summary.
<code>/app/settings/localization</code>	Fiscal localization settings. Personas: TAX, ACC.	Country pack, language, numbering, invoice rules.	T- <code>DetailSplit</code> .	unsupported locale, migration warning.	Localization warnings should be prominent, not hidden in helper text.
<code>/app/settings/api-keys</code>	Keys, webhooks, audit access. Personas: DEV.	API keys, scopes, event subscriptions, endpoint status.	T- <code>DataIndex</code> , table, code blocks.	revoked, delivery failure.	Secret actions with confirm/reveal rules.

Route / page	Purpose and personas	Required data / props	Key UI components and template	States	Responsive, accessibility, and micro-interaction notes
<code>/admin</code>	Platform dashboard. Personas: SA.	Tenants, tax-pack health, job failures, reports queue.	T-AdminConsole	degraded import service, queue backlogs.	Ops-critical banners persist above content.
<code>/admin/tenants</code>	Organization management. Personas: SA.	Tenants, plans, localization, last activity.	T-DataIndex	suspended, restore pending.	Dangerous actions require a typed confirmation.
<code>/admin/localization-packs</code>	Tax and locale pack management. Personas: SA.	Versions, countries, effective dates, rollout states.	T-DetailSplit, tables, timelines.	deprecated pack, rollout blocked.	Effective date comparisons need explicit text and diff view.
<code>/admin/audit</code>	Global audit stream. Personas: SA, internal audit.	Actor, company, module, action, evidence.	T-ReportWide, table, details drawer.	very large result set, export pending.	Audit rows must be copyable and filterable without losing context.

Key UX flows and wireframe descriptions

Combined page-flow map

```

flowchart TD
    subgraph BusinessOS_AI
        B1[Marketing Home]
        B2[Signup / Login]
        B3[Workspace Select]
        B4[Onboarding Wizard]
        B5[Dashboard]
        B6[Sites List]
        B7[Site Editor]
        B8[Publish Center]
        B9[Live Site]
    end

```

```

    B10[Contacts]
    B11[Deal Detail]
    B12[Proposal Editor]
    B13[Invoice Detail]
    B14[AI Copilot]

    B1 --> B2 --> B3 --> B4 --> B5
    B5 --> B6 --> B7 --> B8 --> B9
    B5 --> B10 --> B11 --> B12 --> B13
    B5 --> B14
    B7 --> B14
    B11 --> B14
end

subgraph Accounting_SaaS
    A1[Marketing Home]
    A2[Signup / Login]
    A3[Company Setup Wizard]
    A4[Accounting Dashboard]
    A5[Chart of Accounts]
    A6[Journal Draft]
    A7[Journal Review and Post]
    A8[Sales Invoice Draft]
    A9[Invoice Review and Post]
    A10[Payments]
    A11[Reconciliation Workspace]
    A12[Reports]
    A13[Period Close]
    A14[AI Copilot]

    A1 --> A2 --> A3 --> A4
    A4 --> A5
    A4 --> A6 --> A7 --> A12
    A4 --> A8 --> A9 --> A10 --> A12
    A4 --> A11 --> A12 --> A13
    A4 --> A14
    A11 --> A14
end

subgraph Optional_Media_Module
    M1[Asset Library]
    M2[Upload]
    M3[Processing / Transcode]
    M4[Embed / Player Config]
    M1 --> M2 --> M3 --> M4
end

```

Signup and onboarding

BusinessOS AI wireframe:

Desktop uses `T-AuthSplit`: left 40% brand/value panel; right 60% task form. After account creation, the user lands on `Workspace Select`, then a `T-Wizard` onboarding flow with 5–7 steps: company basics, goals, key modules, first site/project/CRM import, branding, invite team, done. At the top there is a 72px progress header with current step, percent complete, and “save and finish later.” Bottom actions are back/continue, never more than two primary CTAs visible.

Accounting SaaS wireframe:

Same shell, but company creation starts earlier. The wizard steps are: company profile, fiscal year and currency, country/tax mode, chart-of-accounts template, opening balances/import choice, invite users, complete. This flow uses more inline help panels and examples than BusinessOS AI, because domain correctness matters more than fast completion.

Create website and publish

Pages and progression:

`/app/sites` → `/app/sites/:siteId` → `/app/sites/:siteId/editor` → `/app/sites/:siteId/pages/:pageId/settings` → `/app/sites/:siteId/publish`.

Wireframe structure:

The editor is a three-rail layout:

- **Left rail:** page tree, section library, assets
- **Center canvas:** live page preview at desktop/tablet/mobile widths
- **Right rail:** selected block/page/theme properties

The top bar contains page name, draft status, preview toggle, undo/redo, AI generate, save, publish. The bottom bar is optional and only appears during responsive preview. On tablet, only one side rail is open at a time; on mobile, the canvas goes full width and both rails are drawers.

Critical micro-interactions:

- Selected block gets an accent outline and floating context actions.
- Unsaved state appears as a persistent “Draft unsaved” pill, not just a toast.
- Publish CTA opens a two-step drawer: preflight summary, then success view with live URL and rollback link.
- DNS verification uses inline progress with last-checked timestamp, not just animated dots.

Create lead, convert to deal, then invoice

Pages and progression:

`/app/crm/contacts` → `/app/crm/contacts/:id` → `/app/crm/deals/:id` → `/app/proposals/:id/editor` → `/app/invoices/:id`.

Wireframe structure:

The contact and deal pages use `T-DetailSplit`: main activity/document body on the left, summary/action rail on the right. The right rail contains relationship-level KPIs, next step, ownership, pipeline stage, and quick actions. “Create proposal” and “Create invoice” are prominent but separated by role and stage rules. Proposal editing uses the same editor archetype as the website builder, but with pricing and approval components instead of layout blocks.

Critical micro-interactions:

- Converting lead to deal animates the card movement but preserves focus on the resulting confirmation drawer.
- Proposal sending triggers a “review send package” drawer with recipients, version, amount, and expiry.
- Invoice creation pre-populates customer and line-item context and displays a “linked to deal” badge.

Create invoice and post journal

Pages and progression:

`/app/sales-invoices/new` → review panel → `/app/sales-invoices/:id` → behind the scenes linked journal or visible journal review surface depending on accounting mode.

Or for pure journals: `/app/journals/new` → `/app/journals/:id/review`.

Wireframe structure:

Invoice and journal entry forms use `T-DetailSplit` with a fixed totals rail on the right. The line-entry grid occupies the main left column. The footer displays running debit/credit equality or invoice totals/tax totals. Any imbalance or missing tax treatment pins an error summary above the footer and disables final posting.

Critical micro-interactions:

- Fast tab entry across line grid.
- Sticky totals footer with “balanced” or “out of balance” state.
- Review modal or review step before posting with keyboard focus placed logically inside the review title/body, per dialog guidance. ²²
- After posting, the UI changes from editable to immutable-read mode and offers “reverse” or “issue note,” not “edit posted record.”

Upload media, transcode, and embed

This is **optional** and should be enabled only if a media module exists in either product.

Pages and progression:

Asset library → upload surface → processing detail → embed/player config.

Wireframe structure:

Use `T-DetailSplit` or `T-EditorCanvas` light variant:

- Left: asset list and upload queue
- Center: preview/player
- Right: metadata, processing status, embed options

Critical micro-interactions:

- Drag/drop plus “browse file” parity
- Processing status in both row badge and detail timeline
- Copy embed code button with live screen-reader status announcement

AI copilot interactions

The AI copilot should not be a floating toy; it should be a **context-aware side panel**.

Core interaction model:

- Prompt box at bottom
- Context chips above input: “This page,” “Selected deal,” “All invoices in date range,” “Current site page,” “Reconciliation batch”
- Tool/action section below generated answer: draft, summarize, compare, extract, propose action
- **Confirm action drawer** whenever an output affects external state, client-visible content, financial state, or publishing

Wireframe notes:

- On desktop, the panel docks right at 400–440px wide.
- On tablet, it opens as a full-height drawer.
- On mobile, it opens full screen with persistent context chips and a bottom-safe input zone.
- Every answer cites its context set and includes “used data sources” chips.

Accessibility, keyboard shortcuts, and ARIA rules

Core accessibility rules

The product-wide accessibility baseline should be explicit, not implied.

Rule	Specification	Basis
Contrast	Normal text on dark surfaces must meet AA; meaningful control boundaries and focus indicators must meet non-text contrast expectations.	WCAG contrast and non-text contrast. 23
Focus visibility	Every keyboard-operable control needs a visible indicator; default ring = 2px outline plus 2px offset where feasible.	WCAG focus visible and focus appearance. 24

Rule	Specification	Basis
Target size	Minimum 44px for all primary controls; 48px for nav-heavy mobile areas; never below WCAG's 24×24 minimum unless an allowed exception applies.	WCAG target size, Apple 44pt, Material 48dp. ²⁵
Keyboard-only access	All flows must be fully operable without pointer input.	WCAG keyboard and APG patterns. ²⁶
Name, role, value	Custom controls must expose correct accessible name, role, state, and value.	WCAG 4.1.2. ²⁷
Status messaging	Save, publish, invite, import, post, and reconcile updates must be announced without stealing focus.	WCAG 4.1.3. ¹⁷
Sticky obstruction	Sticky headers/footers may not cover focused elements.	WCAG 2.4.11. ²⁸
Financial/error prevention	Invoice posting, journal posting, period close, and billing changes must support confirm/correct/reverse.	WCAG 3.3.4. ⁷
Dark mode discipline	Because the theme is permanently dark, avoid bright flashes, inconsistent light surfaces, and low-contrast custom combinations.	Apple dark-mode guidance and WCAG contrast standards. ²⁹

ARIA and component rules

Component / pattern	Required semantics and behavior
Modal dialog	Use dialog semantics, trap focus, <code>Escape</code> closes where safe, return focus to invoker, and mark <code>aria-modal=true</code> only for true modals that make background content inert. ¹⁶
Command palette	Implement as dialog + combobox/listbox hybrid: search input stays in tab order; suggestions are navigable without breaking browser text editing behavior. ³⁰
Tabs	Use manual activation for analytics/workspace tabs when panel content is heavy; active tab linked to its tabpanel and visibly differentiated. ¹⁹
Data tables / interactive grids	Use semantic table when rows are mostly read-only. Use grid only when cells are actively editable/navigable and focus is intentionally managed inside the widget. ³¹
Breadcrumbs	Place inside navigation landmark, label the landmark, set the current page to <code>aria-current="page"</code> . ¹⁰
Toasts / inline status	Important results must map to a live/status region rather than appear visually only. ¹⁷

Component / pattern	Required semantics and behavior
Search/autocomplete	Support arrow navigation, <code>Escape</code> , <code>Enter</code> , and preserve native text-editing keys. ¹⁴
Icons	Never icon-only unless accessible label is explicit; text + icon preferred for destructive/financial actions.
Charts	Must have text summary, axis labels, keyboard-readable legend, and non-color redundancy (pattern, marker, direct labels).

Keyboard shortcut model

Global shortcuts

Shortcut	Action	Products
<code>Cmd/Ctrl + K</code>	Open command palette	Both
<code>G then D</code>	Go to dashboard	Both
<code>G then S</code>	Go to sites / sales invoices depending on product context	Both
<code>G then C</code>	Go to contacts / chart of accounts depending on product	Both
<code>G then R</code>	Go to reports	Both
<code>N</code>	New primary record for current context	Both
<code>/</code>	Focus local search where present	Both
<code>?</code>	Open keyboard shortcuts help	Both
<code>Esc</code>	Close top-most dismissible surface	Both
<code>[</code> / <code>]</code>	Previous / next tab where tabbed page exists	Both

BusinessOS AI contextual shortcuts

Shortcut	Action
<code>N then S</code>	New site
<code>N then D</code>	New deal
<code>N then I</code>	New invoice
<code>N then P</code>	New proposal
<code>Shift + A</code>	Open AI copilot with current page context
<code>.</code>	Open row actions menu on selected record

Shortcut	Action
E	Edit current entity
P	Publish from editor if validation passes
Cmd/Ctrl + Enter	Save / confirm in editor-like surfaces

Accounting SaaS contextual shortcuts

Shortcut	Action
N then J	New journal
N then I	New sales invoice
N then B	New purchase bill
N then P	New payment
R	Start or resume reconciliation on highlighted statement line
A	Accept suggested reconciliation match
X	Reject suggested match
Cmd/Ctrl + Shift + P	Open post/review action on current draft record
L	Jump to linked ledger or ledger impact view

Delivery checklist for an AI UI generator or design team

Inputs and artifacts checklist

Category	Required artifact	Notes
Information architecture	Route map per product, nav labels, module hierarchy	Must match page inventory tables exactly
Design tokens	Color, spacing, typography, elevation, motion tokens	Use names from this spec, no ad hoc local values
Layout primitives	Templates T - * and shell variants	Required before page composition begins
Copy	Page titles, empty-state copy, error copy, CTA labels, helper text	Draft microcopy must exist before accessibility QA
Icon set	Monochrome icon library with semantic naming	Avoid decorative-only icons for critical states

Category	Required artifact	Notes
Sample data	Realistic records for CRM, projects, invoices, journals, reconciliation, reports	Include long names, missing values, extreme totals, multi-currency where applicable
API stubs	JSON-shaped mock payloads for each page route	Needed for realistic loading/error/empty/success states
Status taxonomy	Shared enum set: loading, empty, error, success, locked, permission	Prevents inconsistent state design
Accessibility scripts	Keyboard paths, screen-reader labels inventory, focus order maps	Must be created for critical journeys before sign-off
Localization keys	Message IDs and placeholders for every visible string	Even if only English ships first
QA scenarios	Responsive screenshots, state matrix, role/permission matrix	Design QA should include blocked and degraded states
Policy content	Legal, security, privacy, billing text	Required for public pages and deletion/financial confirmations

Role matrix and sample data requirements

Need	BusinessOS AI	Accounting SaaS
Role-based mockups	OWNER, Sales, PM, Finance, Client, Super-admin	Owner, Accountant, AR, AP, Tax, Auditor, Super-admin
Empty-state samples	No site, no leads, no projects, no invoices	New company, empty COA, no invoices, no statements
Error-state samples	Publish failed, webhook failed, AI unavailable	Journal unbalanced, tax mismatch, reconciliation conflict
Dense-data samples	100+ contacts, multi-stage pipeline, long file names	500+ ledger lines, 50+ statement rows, multi-period reports
Long-text samples	proposal clauses, AI outputs, project comments	memo fields, tax registration notes, bank descriptions
Numeric extremes	high invoice totals, negative adjustments	debit/credit with many decimals, partial allocations

UI production plan

Prioritized 30–60 day plan

Person-weeks are used because team size is **unspecified**.

Phase	Deliverables	Estimated effort
Design system foundation	Tokens, type scale, elevation, motion, iconography, accessibility conventions, shell templates	4–5 pw
Shared component library	Navigation, table, forms, cards, modals, drawers, charts, timeline, AI panel, command palette, toasts	6–8 pw
BusinessOS AI IA and page specs	Route inventory, page wireframes, object models, shell + website editor + CRM + invoices + AI flows	9–11 pw
Accounting IA and page specs	Route inventory, journals, invoices, payments, reconciliation, tax, reports, period close	10–12 pw
Responsive and state expansion	Mobile/tablet adaptations, empty/load/error/success variants for all core pages	5–6 pw
Accessibility pass	Keyboard maps, focus order reviews, contrast review, ARIA annotations, status-message coverage	4–5 pw
AI generator packaging	Design tokens export, page manifests, component matrix, sample data library, copy manifest	3–4 pw
Final QA and review	Stakeholder review, consistency fixes, annotation cleanup, handoff package	3–4 pw

Estimated total UI-only effort:

- BusinessOS AI: **19–24 person-weeks**
- Accounting SaaS: **21–27 person-weeks**
- Shared system and packaging: **10–13 person-weeks**

sixty-day Gantt

```

gantt
  title 60-day UI production timeline
  dateFormat YYYY-MM-DD
  axisFormat %d %b

  section Shared system
  Tokens, theme, layout shells           :a1, 2026-05-05, 8d
  Component library v1                   :a2, after a1, 12d
  Accessibility conventions and keyboard :a3, 2026-05-15, 10d
  Sample data and copy system            :a4, 2026-05-24, 8d

  section BusinessOS AI
  IA and nav model                       :b1, 2026-05-07, 6d
  Marketing, auth, onboarding            :b2, after b1, 8d
  Core shell, dashboard, CRM             :b3, 2026-05-18, 12d

```

Website builder and publish flows	:b4, 2026-05-28, 12d
Proposals, invoices, portal, AI	:b5, 2026-06-08, 10d
Responsive/state variants	:b6, 2026-06-18, 8d
section Accounting SaaS	
IA and nav model	:c1, 2026-05-07, 6d
Marketing, auth, onboarding	:c2, after c1, 8d
Dashboard, COA, journals	:c3, 2026-05-18, 12d
Sales/AP, payments, reconciliation	:c4, 2026-05-30, 12d
Tax, reports, period close	:c5, 2026-06-11, 10d
Responsive/state variants	:c6, 2026-06-21, 8d
section Packaging and QA	
ARIA/page annotation pack	:d1, 2026-06-10, 8d
AI UI generator manifest	:d2, 2026-06-18, 6d
Final QA and handoff	:d3, 2026-06-24, 6d

Side-by-side complexity summary

Dimension	BusinessOS AI	Accounting SaaS
Primary UI challenge	Breadth, module switching, editor surfaces, role complexity	Dense transactional forms, posting review, reconciliation, report readability
Page archetypes	More archetypes overall	Fewer archetypes, but heavier states inside each
Highest-complexity page	Website/page editor	Reconciliation workspace
Most demanding accessibility area	Canvas/editor interactions and AI-copilot confirmations	Journal line grids, financial confirmations, reconciliation keyboard model
Most state-heavy module	Publish center + automations + AI actions	Journals + invoices + payments + tax + period close
Most mobile-sensitive area	Site editor and deal/proposal flows	Reconciliation and dense ledger/report tables
UI-only effort estimate	19–24 pw	21–27 pw
Overall risk	Medium-high from sprawl	High from precision and irreversible actions
Recommended sequencing	Build shell, CRM, sites, invoices, AI; leave niche modules later	Build shell, onboarding, COA, journals, invoices, payments, reports; defer advanced tax/localization depth until country is known

Final recommendation

If both products must share one visual language, do **not** force them to share one interaction style. The right approach is:

- **One token system**
- **One component library**
- **One accessibility contract**
- **Two workflow grammars**

BusinessOS AI should feel **exploratory, compositional, and assistant-friendly**.

The accounting product should feel **controlled, legible, confirmable, and audit-safe**.

That split produces the most coherent black-and-white UI system while still respecting the fundamentally different cognitive load of a work operating system versus an accounting system.

1 16 22 30 Dialog (Modal) Pattern | APG | WAI | W3C

<https://www.w3.org/WAI/ARIA/apg/patterns/dialog-modal/>

2 3 4 5 8 23 <https://www.w3.org/TR/WCAG22/>

<https://www.w3.org/TR/WCAG22/>

6 24 <https://www.w3.org/WAI/WCAG22/Understanding/focus-visible.html>

<https://www.w3.org/WAI/WCAG22/Understanding/focus-visible.html>

7 <https://www.w3.org/WAI/WCAG21/Understanding/error-prevention-legal-financial-data.html>

<https://www.w3.org/WAI/WCAG21/Understanding/error-prevention-legal-financial-data.html>

9 12 26 <https://www.w3.org/WAI/WCAG22/quickref/>

<https://www.w3.org/WAI/WCAG22/quickref/>

10 <https://www.w3.org/WAI/ARIA/apg/patterns/breadcrumb/>

<https://www.w3.org/WAI/ARIA/apg/patterns/breadcrumb/>

11 31 <https://www.w3.org/WAI/ARIA/apg/patterns/grid/>

<https://www.w3.org/WAI/ARIA/apg/patterns/grid/>

13 27 <https://www.w3.org/WAI/WCAG21/Understanding/name-role-value.html>

<https://www.w3.org/WAI/WCAG21/Understanding/name-role-value.html>

14 Combobox Pattern | APG | WAI | W3C

<https://www.w3.org/WAI/ARIA/apg/patterns/combobox/>

15 25 <https://www.w3.org/WAI/WCAG22/Understanding/target-size-minimum.html>

<https://www.w3.org/WAI/WCAG22/Understanding/target-size-minimum.html>

17 21 <https://www.w3.org/WAI/WCAG22/Understanding/status-messages.html>

<https://www.w3.org/WAI/WCAG22/Understanding/status-messages.html>

18 28 <https://www.w3.org/WAI/standards-guidelines/wcag/new-in-22/>

<https://www.w3.org/WAI/standards-guidelines/wcag/new-in-22/>

¹⁹ <https://www.w3.org/WAI/ARIA/apg/patterns/tabs/>

<https://www.w3.org/WAI/ARIA/apg/patterns/tabs/>

²⁰ <https://www.w3.org/WAI/WCAG22/Understanding/accessible-authentication-minimum.html>

<https://www.w3.org/WAI/WCAG22/Understanding/accessible-authentication-minimum.html>

²⁹ <https://developer.apple.com/design/human-interface-guidelines/dark-mode>

<https://developer.apple.com/design/human-interface-guidelines/dark-mode>