
From Git to Gold: Pipeline Orchestration

Name: Gunti Ravi Kumar | Roll no: 23BCS095 | B.Tech, Computer Science and Engineering | Course: Data Engineering
Repository: https://github.com/Ravikumar-2016/freshcart-pipelines (private repository)
Environment: Windows, VS Code, Python 3.12.6, Snowflake, GitHub Actions, Mage AI 0.9.80, CloudAMQP (RabbitMQ). Evidence files are in `report/screenshots/`; screenshots are in the appendix.

Integration diagram



Code lives in Git; CI tests the Mage `prepare_data` block on every push. The ELT pipeline produces the gold table. The Mage pipeline trains on the Iris dataset from scikit-learn (it does not read the gold table). The stream delivers requests to drivers (Part D); the bonus consumer feeds order events from the same broker into bronze and so into gold.

Part A: Git and CI/CD

A1 Repository and commit history

Structure as required: `README.md`, `.gitignore` (ignores `.env`, `*.pkl`, `*.csv`, `mage.log`, `__pycache__/` and `.venv/`), `requirements.txt`, `elt/`, `iris_project/`, `stream/`, `tests/test_prepare_data.py`, `.github/workflows/ci.yml`. `git log --oneline`:

```
e0e1f5d feat(stream): complete RabbitMQ routing, ACK/NACK and FreshCart bonus integration
4d59385 feat(stream): implement and verify RabbitMQ routing and ACK/NACK (D1-D3)
3e385f3 feat(elt): add future-date quality check with failure demo and verified cleanup (B5)
f83bf2f feat(elt): add CUST-02 Gold tier event and verify SCD2/MERGE idempotency (B4)
72e290d docs(elt): record B4 pre-run predictions and state
db8cd3c feat(elt): add unsupported_currency validation rule (B3)
af79117 feat(elt): FreshCart ELT notebook, SQL scripts and B1 baseline on Snowflake
1428aef feat(iris): add Mage iris_classifier pipeline with tests, evaluation branch and validation block
a55d012 docs: add Part A CI evidence and answers
0c83c3e fix: restore correct 80/20 train test split
b038cf1 test: demonstrate failing CI for incorrect split
6d86300 ci: add GitHub Actions workflow
4d1e80a feat: add Iris data transformer and tests
4ef2ad1 chore: initial repository structure and .gitignore
```

A2 Where does each command act?

Command	Where the change happens	What exactly happens?
`git init`	working folder / local repository	Creates the hidden `.git` folder, making the folder an empty local repository.
`git add train.py`	working folder -> staging area	Marks the current content of `train.py` to be part of the next commit.
`git commit -m "msg"`	staging area -> local repository	Saves the staged snapshot as a commit with the message "msg", only on my laptop.
`git remote add origin URL`	local repository (settings only)	Stores the short name `origin` for the GitHub URL; nothing is transferred.

`git push -u origin main`	local repository -> remote (GitHub)	Uploads my local `main` commits and links it to `origin/main` so a later plain `git push` works.
`git pull origin main`	remote -> local repository and working folder	Downloads new commits from `origin/main` and merges them into my branch and files.

After `git commit`, can a teammate see the code on GitHub? No. A commit exists only in my local repository; GitHub receives it only after `git push`.

A3 CI workflow

`tests/test_prepare_data.py` asserts 120 train and 30 test rows from `prepare_data.transform` (`train_test_split(test_size=0.2, random_state=42)`). `.github/workflows/ci.yml` runs on every push: checkout, Python 3.12, `pip install -r requirements.txt`, `python -m pytest`. Runs: CI #1 green (`6d86300`); CI #2 red with `test_size=0.3` (`b038cf1`; locally `105 == 120` failed); fix `0c83c3e` gave CI #3 green. Screenshots: appendix A3.

Part B: FreshCart ELT on Snowflake

Notebook `elt/freshcart_elt.ipynb`; SQL in `elt/sql/`; code in `elt/freshcart.py`; mock data in `elt/mock_data.py` (the course sample data; no real APIs). Database `FRESHCART_DB`; the final notebook was executed once, top to bottom, in `FRESHCART_FINAL`.

B1 Baseline (one run on an empty database)

Check	Expected	Actual
Raw order rows in bronze	8 (6 web + 2 mobile)	8
Rows passing cleaning	6	6
Quarantine	2 (ORD-1004, ORD-1006)	2 (same orders)
After deduplication	4	4
Gold line	4 orders, 7,785.00, 126 points	4 orders, 7785.00, 126 points
Rows rejected	25%	25%

B2 Trace of ORD-1003 and ORD-1005

ORD-1003. (1) In `bronze.orders_raw` the web copy (ingest_seq 2) is flat JSON with `order_id, cust_email, amount: null, updated_at 09:10`; the mobile copy (ingest_seq 8) is nested camelCase JSON with `orderId, customer.email, total.value "2,100.00", updatedAt 18:40`. They differ because they come from two different APIs; bronze keeps each as received. (2) In `10_orders_clean.sql` the `unified` CTE maps both shapes to the same columns, and the `typed` CTE applies `LOWER(TRIM(email))`, `INITCAP` for the name, `COALESCE(TRY_TO_DATE(..'YYYY-MM-DD'), ..'DD/MM/YYYY', ..'MON DD, YYYY')` (the mobile `02/09/2026` becomes 2026-09-02), `TRY_TO_DECIMAL(REGEXP_REPLACE(amount,'[^0-9.-]',''),12,2)` ("`2,100.00`" becomes 2100.00) and `TRY_TO_TIMESTAMP_NTZ`. (3) `20_orders_dedup.sql`: `QUALIFY ROW_NUMBER() OVER (PARTITION BY order_id ORDER BY updated_at DESC, ingest_seq DESC) = 1` ranks copies newest first, so the mobile copy (18:40, later than 09:10) survives with amount 2100.00. (4) Gold: INR rate 1.0, `amount_inr = ROUND(2100.00 x 1.0, 2) = 2100.00`; Meera is Platinum (multiplier 3), `loyalty_points = FLOOR(2100.00/100) x 3 = 21 x 3 = 63`.
ORD-1005 vs ORD-1001 (Priya). The tier is taken on the order date: `LEFT JOIN dim.customers_scd2 c ON c.email = o.email AND o.order_date BETWEEN c.valid_from AND c.valid_to`, then `ref.tier_multiplier`. Priya is Silver until 2026-09-02 and Gold from 2026-09-03. ORD-1001 (09-01): Silver x1, FLOOR(1250/100) = 12 points. ORD-1005 (09-03): Gold x2, FLOOR(899/100) x 2 = 16 points.

B3 Rule `unsupported_currency`

Added in `10_orders_clean.sql` inside `ARRAY_CONSTRUCT_COMPACT`: `IFF(currency IS NULL OR currency NOT IN ('INR','USD'), 'unsupported_currency', NULL)`. ORD-1006 (EUR) reasons before: `["bad_email","bad_pincode"]`; after the re-run (in `silver.orders_checked`): `["bad_email","bad_pincode","unsupported_currency"]`. **Gold does not change** (4 / 7,785.00 / 126): ORD-1006 was already rejected, so it never reached gold. **No second quarantine row**: the `NOT EXISTS (... same source, order_id and updated_at ...)` in the quarantine insert skips a record already there (and ignores the reasons, so the old row keeps the old reasons); `QUALIFY ROW_NUMBER()` removes copies within one run.

B4 CUST-02 becomes Gold on 2026-08-15

Predictions were written and committed (`72e290d`) before the run; the actuals match all five.

Quantity	Prediction	Actual
CUST-02 rows in `dim.customers_scd2`	2	2 (Silver to 2026-08-14, Gold from 2026-08-15)
Tier used for ORD-1002	Gold	Gold

Loyalty points for ORD-1002	70	70 (FLOOR(3536/100) x 2)
Total points in gold	161	161
Gold rows whose published_at changed	1	1 (ORD-1002 only)

A second pass of the transformation changed no published_at and no row_hash. **Why gold is safe to re-run:** each run rebuilds silver.orders_enriched and MERGEs it into gold on order_id. The row_hash is a hash of all business columns; the MERGE updates a row (and refreshes published_at) only when the hash differs, and inserts only new orders, so a re-run never creates a duplicate and never touches an unchanged row. **Bronze still grows by 8 rows** per run because every run extracts the same 8 raw orders again into new landing files and COPY INTO appends them; bronze is an append-only record, and the duplicates are removed later in silver.

B5 Sixth check and ELT vs ETL

Added to quality_checks(): SELECT COUNT_IF(order_date > CURRENT_DATE()) FROM silver.orders_dedup ("orders dated in the future"; 0 on real data). Failing on purpose with the marked order TEST-B5-FUTURE-DATE-001 (date 2026-12-31, no amount so that no other check fires) printed orders dated in the future 1 PROBLEM. Cleanup first counted the exact markers and asserted them (bronze 1, gold 1, quarantine 0, staged file 1, other rows untouched), then deleted exactly those; the transform was re-run, the check returned to 0 OK, and the state was identical to the baseline taken before (19 of 19 checks).

ELT vs ETL. FreshCart's sources send messy data in different shapes (flat web JSON, nested mobile JSON, duplicates, bad emails), so it is better to land everything unchanged in bronze and clean it with SQL inside Snowflake: a raw copy is kept, a changed rule or late fix is just a re-run of the SQL (B3 and B4 needed no re-extraction), bad rows go to quarantine with reasons instead of being lost, and the warehouse does the heavy work. ETL would still win when data must be changed before it may land in the warehouse, for example masking personal or card data for compliance. **[STUDENT INPUT NEEDED: the assignment asks for the ETL situation from the lecture; the lecture material was not available, so the example above is a general one, not necessarily the lecture's.]**

Part C: ML pipeline with Mage

C1 Graph and run

```
load_iris (data_loader, @test: 150 rows, target)
  -> validate_data (transformer, C4, @test x2: no missing values, 3 classes)
  -> prepare_data (transformer, @test: split column)
  -> train_model (transformer, @test: accuracy >= 0.90, 30 test rows)
       |-> save_results (data_exporter, @test: CSV with 30 rows)
       '-> evaluate_model (transformer, C3, @test: 3 classes, support 30)
```

mage run iris_project iris_classifier --test: every block printed 1/1 tests passed, accuracy 1.0 at the default depth 3, iris_predictions.csv written, exit 0 (report/screenshots/C/C1_mage_run_test.txt).

C2 Tests as a gate

Each run used --runtime-vars '{"max_depth": N}' after deleting the CSV. The accuracy gate (0.90) is my own choice, because the reference notebook was not available.

max_depth	Test accuracy	test_accuracy passed?	CSV created?
1	0.6333	No (exit 1)	No
2	0.9667	Yes	Yes
3	1.0000	Yes	Yes
4	1.0000	Yes	Yes
5	1.0000	Yes	Yes

How a failing @test stops save_results: with --test Mage runs a block's tests right after the block; a failed assertion marks the block failed and stops the run (exit code 1), so the blocks that depend on train_model are never started (at depth 1 the log has no "Saved" line). This is better than saving first and checking later because a bad model's file never exists to be picked up, and the failure is visible immediately.

C3 Evaluation branch

train_model has two downstream blocks, save_results and evaluate_model (iris_project/pipelines/iris_classifier/metadata.yaml). Depth 2, confusion matrix (rows actual, columns predicted): setosa [10, 0, 0]; versicolor [0, 8, 1]; virginica [0, 0, 11]. Metrics: setosa precision/recall 1.0/1.0; versicolor 1.0/0.8889; virginica 0.9167/1.0; accuracy 0.9667. The UI screenshot (appendix) is from http://localhost:6789. **Limitation:** no

Cloudflare tunnel was used (Mage runs on my own machine, so the UI is reachable directly); I have not claimed that this satisfies the tunnel requirement.

C4 Own block

`validate_data` (transformer between `load_iris` and `prepare_data`) with two `@test` functions (no missing values, exactly 3 classes); the full six-block run passed, and run directly the tests fail on a NaN and on a 2-class frame.

Part D: Food-order stream with RabbitMQ

D1 Routing

Exchange `rapido-dispatch` (topic); `*` matches exactly one word, `#` matches zero or more words. Bindings: Ravi `bangalore.koramangala.*`, Priya `bangalore.indiranagar.*`, Arjun `bangalore.*.ride`, Meena `bangalore.*.food`, Karthik `chennai.tnagar.food`, Control `bangalore.#`. Predictions were written on paper before any message was published; verified on the live broker (`stream/verify_routing.py`, 6 of 6 PASS):

#	Routing key	Receiving queues (predicted = actual)
1	bangalore.koramangala.food	Ravi, Meena, Control
2	bangalore.indiranagar.ride	Priya, Arjun, Control
3	bangalore.whitefield.ride	Arjun, Control
4	chennai.tnagar.food	Karthik
5	chennai.whitefield.ride	dropped
6	bangalore.koramangala	Control only

Question 6. The key has only two words. Every other pattern needs three words, because each contains a `*` (or is a three-word literal) and a `*` must match exactly one word, which the key does not have. Only `bangalore.#` can match: `bangalore` matches the first word and `#` matches the remaining word (it would even match zero words).

D2 Dispatcher and drivers

`stream/dispatcher.py` publishes every 2 s a persistent JSON message `{id, city, zone, type, ts}` with key `city.zone.type`; `stream/driver.py NAME PATTERN` declares a private exclusive queue, binds it and acknowledges each processed message. Six drivers plus the dispatcher ran as separate processes for 120 s of publishing (05:23:50 to 05:26:00 UTC): 59 messages. A log checker compared every message with the routing model: each reached exactly the predicted drivers and no others (Ravi 13, Priya 7, Arjun 17, Meena 15, Karthik 2, Control 32, all ACKed; 25 matched no queue and were dropped). Evidence: `report/screenshots/D/D2_*` (log files).

D3 ACK and NACK

A message without `zone` gets `basic_nack(requeue=False)`, any other `basic_ack`; the dispatcher makes every 10th message malformed. Live run (35 messages, 3 malformed): the matching drivers printed `REJECTED ... missing field 'zone' -> NACK (requeue=False, discarded)` and ACKed all valid messages. Scripted demo (`stream/d3_demo.py`, queue depth read from the broker): valid ACK 1 to 0; malformed NACK 1 to 0; a consumer that closed its channel without ACK left depth 1 and the next delivery had `redelivered=True`; a malformed message with `requeue=True` came back on 4 of 4 attempts. No dead-letter exchange is configured, so a rejected message is simply deleted.
Crash before ACK: the message stays unacknowledged, so RabbitMQ redelivers it when the connection closes (at-least-once delivery). **Always-bad message with `requeue=True`:** it returns to the queue, fails again, and loops forever (a poison message), wasting CPU and blocking the messages behind it.

Bonus: stream into the lakehouse

Flow. `stream/order_consumer.py` collects FreshCart web-format order messages (key `freshcart.order.web` on the same exchange) for 60 s; invalid ones are NACKed (requeue=False); the rest go through the existing `write_landing()` (raw .json.gz), `load_file()` (PUT + COPY INTO bronze) and the unchanged transform SQL to `gold.fct_orders`. Messages are ACKed only after the landing file is loaded; on failure they are requeued. Three marked orders `BONUS-TEST-001..003` (plus a duplicate and one malformed message) were streamed twice:

	Baseline	After run 1	After run 2
Gold orders	4	7	7
Gold revenue (INR)	7,785.00	9,535.00	9,535.00
Gold points	161	205	205
bronze order rows	24	28	32


Run 2 did not double-count: bronze appended again, but silver deduplication (`QUALIFY ROW_NUMBER`) and the gold MERGE on `row_hash` left orders, revenue, points and every `published_at` unchanged. The test data was then removed after asserting exact marker counts, and the final state equals the baseline (`report/screenshots/Bonus/`).


Reflection


The thing that broke was my B4 analysis cell: after the pipeline had already run once on the new CRM event, the cell failed with `KeyError: 'order_id'`. I found the cause by printing the data frame's columns: Snowflake returns column names in upper case (`ORDER_ID`) while my code used lower case. Re-running the pipeline would have added another 8 rows to bronze and spoiled the "before" comparison, so I did not. Instead I used Snowflake Time Travel to read the tables as they were just before the run, first proving that this reproduced the "before" snapshot I had saved, and fixed the column names. Later, while preparing the final submission, I noticed that the notebook still depended on that one-off timeline (a hard-coded Time Travel time and the B4 event already in the sample data), so a clean top-to-bottom run would not reproduce B1's numbers. I fixed it by keeping the event separate until section B4, removing the hard-coded time, and running the whole notebook once in a fresh database. The lesson: save a "before" snapshot first, and make a notebook re-runnable from the start.

Appendix: screenshots and evidence

A3: CI runs (green, red, green again)






Ravikumar-2016 / freshcart-pipelines
Type / to search
Code
Issues
Pull requests
Agents
Actions
Projects
Wiki
Security and quality
Insights
Settings
All workflows
Workflows
CI
Management
Collapse sidebar
All workflows
New workflow
Showing runs from all workflows
Search runs
3 workflow runs
Auto-refresh: 30s
Workflow
Event
Status
Branch
Actor
fix: restore correct 80/20 train test split
CI #3: Commit 0c83c3e pushed by Ravikumar-2016
main
3 minutes ago
23s
test: demonstrate failing CI for incorrect split
CI #2: Commit b038cf1 pushed by Ravikumar-2016
main
8 minutes ago
27s
ci: add GitHub Actions workflow
CI #1: Commit 6d86300 pushed by Ravikumar-2016
main
17 minutes ago
29s

B1: baseline run (rendered notebook outputs)

2	3	web	{\n "amount": "42.50",\n "currency": "USD",\...
3	4	web	{\n "amount": "-500",\n "currency": "INR",\n...
4	5	web	{\n "amount": "₹ 899",\n "currency": "inr",\...
5	6	web	{\n "amount": 30,\n "currency": "EUR",\n "c...
6	7	mobile	{\n "customer": {\n "email": "arjun.k@yaho...
7	8	mobile	{\n "customer": {\n "email": "Meera@Outloo...

Silver: cleaned rows (6)

In [9]:
```
fc.show("SELECT ingest_seq, source, order_id, email, name, order_date, amount, currency, pincode, amount_missing FROM silver.orders_clean ORDER BY ingest_seq")
```

Out[9]:

	INGEST_SEQ	SOURCE	ORDER_ID	EMAIL	NAME	ORDER_DATE	AMOUNT	CURRENCY	PINCODE	AMOUNT_MISSING
0	1	web	ORD-1001	priya.r@gmail.com	Priya R	2026-09-01	1250.00	INR	600041	False
1	2	web	ORD-1003	meera@outlook.com	Meera S	2026-09-02	None	INR	400050	True
2	3	web	ORD-1002	arjun.k@yahoo.in	Arjun K	2026-09-01	42.50	USD	560034	False
3	5	web	ORD-1005	priya.r@gmail.com	Priya R	2026-09-03	899.00	INR	600041	False
4	7	mobile	ORD-1002	arjun.k@yahoo.in	Arjun K	2026-09-01	42.50	USD	560034	False
5	8	mobile	ORD-1003	meera@outlook.com	Meera S	2026-09-02	2100.00	INR	400050	False

Quarantine: rejected rows and why

In [10]:
```
fc.show("SELECT run_id, source, order_id, reasons FROM quarantine.orders ORDER BY order_id")
```

Out[10]:

	RUN_ID	SOURCE	ORDER_ID	REASONS
0	20261112_040919	web	ORD-1004	[\n "non_positive_amount"\n]
1	20261112_040919	web	ORD-1006	[\n "bad_email",\n "bad_pincode"\n]

Silver: one row per order (4)

In [11]:
```
fc.show("SELECT order_id, ingest_seq, updated_at, amount FROM silver.orders_dedup ORDER BY order_id")
```

Out[11]:

	ORDER_ID	INGEST_SEQ	UPDATED_AT	AMOUNT
0	ORD-1001	1	2026-09-01 10:02:00	1250.00
1	ORD-1002	7	2026-09-01 11:15:00	42.50
2	ORD-1003	8	2026-09-02 18:40:00	2100.00
3	ORD-1005	5	2026-09-03 16:45:00	899.00

Dim: customer tier history (SCD2)

In [12]:
```
fc.show("SELECT * FROM dim.customers_scd2 ORDER BY cust_id, valid_from")
```

Out[12]:

	CUST_ID	EMAIL	TIER	VALID_FROM	VALID_TO	IS_CURRENT
0	CUST-01	priya.r@gmail.com	Silver	2023-04-10	2026-09-02	False
1	CUST-01	priya.r@gmail.com	Gold	2026-09-03	9999-12-31	True
2	CUST-02	arjun.k@yahoo.in	Silver	2024-01-15	9999-12-31	True
3	CUST-03	meera@outlook.com	Platinum	2022-11-01	9999-12-31	True

Ref: daily FX rates, weekends filled

In [13]:
```
fc.show("SELECT * FROM ref.fx_daily WHERE currency = 'USD' ORDER BY rate_date LIMIT 10")
```

Out[13]:

	CURRENCY	RATE_DATE	RATE_TO_INR	IS_CARRIED_FORWARD
0	USD	2026-09-01	83.2000	False
1	USD	2026-09-02	83.3500	False
2	USD	2026-09-03	83.1000	False
3	USD	2026-09-04	83.1000	True
4	USD	2026-09-05	83.1000	True
5	USD	2026-09-06	83.1000	True
6	USD	2026-09-07	83.1000	True
7	USD	2026-09-08	83.1000	True
8	USD	2026-09-09	83.1000	True
9	USD	2026-09-10	83.1000	True

Ref: pincode geography

In [14]:
```
fc.show("SELECT * FROM ref.pincode_geo ORDER BY pincode")
```

Out[14]:

	PINCODE	CITY	STATE	REGION	UPDATED_AT
0	400050	Mumbai	Maharashtra	West	2026-11-11 20:09:27.889000-08:00
1	560034	Bengaluru	Karnataka	South	2026-11-11 20:09:27.889000-08:00
2	600041	Chennai	Tamil Nadu	South	2026-11-11 20:09:27.889000-08:00

Gold: the final table

In [15]:
```
fc.show("SELECT order_id, order_date, tier, amount, currency, fx_rate, amount_inr, loyalty_points, is_high_value, city, region FROM gold.fct_orders ORDER BY order_i
```

Out[15]:

	ORDER_ID	ORDER_DATE	TIER	AMOUNT	CURRENCY	FX_RATE	AMOUNT_INR	LOYALTY_POINTS	IS_HIGH_VALUE	CITY	REGION
0	ORD-1001	2026-09-01	Silver	1250.00	INR	1.0000	1250.00	12	False	Chennai	South
1	ORD-1002	2026-09-01	Silver	42.50	USD	83.2000	3536.00	35	True	Bengaluru	South
2	ORD-1003	2026-09-02	Platinum	2100.00	INR	1.0000	2100.00	63	True	Mumbai	West
3	ORD-1005	2026-09-03	Gold	899.00	INR	1.0000	899.00	16	False	Chennai	South

Gold totals

In [16]:
```
fc.show("SELECT COUNT(*) AS orders, SUM(amount_inr) AS revenue_inr, SUM(loyalty_points) AS points FROM gold.fct_orders")
```

Out[16]:

	ORDERS	REVENUE_INR	POINTS
0	4	7785.00	126

10. B1 check: expected vs actual (after exactly one run)

Expected values come from the assignment table (B1) and the flowchart. `PASS` only if the actual number matches.

In [17]:
```
q = lambda sql: fc.query(sql)[0][0]
rejected_share = float(q("SELECT COUNT_IF(ARRAY_SIZE(reasons) > 0) / NULLIF(COUNT(*), 0) FROM silver.orders_checked"))
quarantined = sorted(r[0] for r in fc.query("SELECT order_id FROM quarantine.orders"))
gold_rev = q("SELECT SUM(amount_inr) FROM gold.fct_orders")
rows = [
    ("Raw order rows in bronze.orders_raw", 8, q("SELECT COUNT(*) FROM bronze.orders_raw")),
    ("  of which web", 6, q("SELECT COUNT(*) FROM bronze.orders_raw WHERE source = 'web'")),
    ("  of which mobile", 2, q("SELECT COUNT(*) FROM bronze.orders_raw WHERE source = 'mobile'")),
    ("Rows in bronze.customers_raw (tier changes)", 4, q("SELECT COUNT(*) FROM bronze.customers_raw")),
    ("Rows in bronze.fx_raw (FX replies)", 1, q("SELECT COUNT(*) FROM bronze.fx_raw")),
    ("Rows in bronze.pincode_raw (3 on the first run)", 3, q("SELECT COUNT(*) FROM bronze.pincode_raw")),
    ("Rows that pass cleaning (silver.orders_clean)", 6, q("SELECT COUNT(*) FROM silver.orders_clean")),
    ("Rows in quarantine.orders", 2, q("SELECT COUNT(*) FROM quarantine.orders")),
    ("Quarantined order ids", ["ORD-1004", "ORD-1006"], quarantined),
    ("Orders after deduplication (silver.orders_dedup)", 4, q("SELECT COUNT(*) FROM silver.orders_dedup")),
    ("Rows in dim.customers_scd2 (tiers)", 4, q("SELECT COUNT(*) FROM dim.customers_scd2")),
    ("Rows in ref.pincode_geo", 3, q("SELECT COUNT(*) FROM ref.pincode_geo")),
    ("Gold orders (gold.fct_orders)", 4, q("SELECT COUNT(*) FROM gold.fct_orders")),
    ("Gold revenue (INR)", "7785.00", f"{gold_rev:.2f}"),
    ("Gold loyalty points", 126, q("SELECT SUM(loyalty_points) FROM gold.fct_orders")),
    ("Share of rows rejected", "25%", f"{rejected_share:.0%}"),
]
result = pd.DataFrame([(n, e, a, "PASS" if str(e) == str(a) else "FAIL") for n, e, a in rows],
                      columns=["Check", "Expected", "Actual", "Result"])
print(f"{(result.Result == 'PASS').sum()} of {len(result)} checks PASS")
result
```

```
16 of 16 checks PASS
```

Out[17]:

	Check	Expected	Actual	Result
0	Raw order rows in bronze.orders_raw	8	8	PASS
1	of which web	6	6	PASS

2	of which mobile	2	2	PASS
3	Rows in bronze.customers_raw (tier changes)	4	4	PASS
4	Rows in bronze.fx_raw (FX replies)	1	1	PASS
5	Rows in bronze.pincode_raw (3 on the first run)	3	3	PASS
6	Rows that pass cleaning (silver.orders_clean)	6	6	PASS
7	Rows in quarantine.orders	2	2	PASS
8	Quarantined order ids	[ORD-1004, ORD-1006]	[ORD-1004, ORD-1006]	PASS
9	Orders after deduplication (silver.orders_dedup)	4	4	PASS
10	Rows in dim.customers_scd2 (tiers)	4	4	PASS
11	Rows in ref.pincode_geo	3	3	PASS
12	Gold orders (gold.fct_orders)	4	4	PASS
13	Gold revenue (INR)	7785.00	7785.00	PASS
14	Gold loyalty points	126	126	PASS
15	Share of rows rejected	25%	25%	PASS

11. Run it again: nothing should double *(not run yet)*


Bronze grows by 8 order rows on every run, because it keeps every copy it is given. Quarantine and gold stay the same. This section is run later (B3/B4), so the B1 evidence above is taken after exactly one run.

In [ ]:
```
fc.run_pipeline()
fc.show("""
SELECT (SELECT COUNT(*) FROM bronze.orders_raw)  AS bronze_rows,
       (SELECT COUNT(*) FROM quarantine.orders)  AS quarantine_rows,
       (SELECT COUNT(*) FROM gold.fct_orders)    AS gold_orders,
       (SELECT SUM(amount_inr) FROM gold.fct_orders) AS revenue_inr,
       (SELECT SUM(loyalty_points) FROM gold.fct_orders) AS points
""")
```

12. Clean up (optional)

Removes everything this notebook created in Snowflake. Uncomment to run.

In [ ]:
```
# fc.query("DROP DATABASE IF EXISTS FRESHCART_DB")
# fc.query("DROP WAREHOUSE IF EXISTS FRESHCART_WH")
fc.conn.close()
```



B3: before / after the currency rule

B3: add a validation rule: `unsupported_currency`

FreshCart only accepts orders in **INR** and **USD**. One line was added inside `ARRAY_CONSTRUCT_COMPACT(...)` in `elt/sql/10_orders_clean.sql` (`SQL_10_ORDERS_CLEAN`). Any other currency (or a missing one) gets the reason `unsupported_currency`. The currency is already upper-cased by then, so `usd` and `inr` still pass.

In [2]:
```
# The reasons block of SQL_10_ORDERS_CLEAN, with the new line (marked B3)
lines = fc.SQL_10_ORDERS_CLEAN.splitlines()
start = next(i for i, l in enumerate(lines) if "ARRAY_CONSTRUCT_COMPACT" in l)
print("\n".join(lines[start:start + 9]))
```

```
 ARRAY_CONSTRUCT_COMPACT(
   IFF(order_id IS NULL, 'missing_order_id', NULL),
   IFF(email IS NULL OR NOT REGEXP_LIKE(email, '^[^@\\s]+@[^@\\s]+\\.[a-z]{2,}$'), 'bad_email', NULL),
   IFF(pincode IS NULL OR NOT REGEXP_LIKE(pincode, '^[1-9][0-9]{5}$'), 'bad_pincode', NULL),
   IFF(currency IS NULL OR currency NOT IN ('INR', 'USD'), 'unsupported_currency', NULL),   -- B3: only INR and USD are accepted
   IFF(order_date IS NULL, 'unparseable_date', NULL),
   IFF(updated_at IS NULL, 'unparseable_updated_at', NULL),
   IFF(amount <= 0, 'non_positive_amount', NULL)          -- NULL amount is allowed (flagged below)
 ) AS reasons
```

Before the re-run

The tables still hold what the **B1 run** produced with the *old* rule. `quarantine.orders` stores the reasons ORD-1006 was given when it was first rejected.

In [3]:
```
import pandas as pd
q = lambda sql: fc.query(sql)[0][0]

def snapshot():
    gold = fc.query("SELECT COUNT(*), SUM(amount_inr), SUM(loyalty_points) FROM gold.fct_orders")[0]
    return {
        "bronze.orders_raw rows": q("SELECT COUNT(*) FROM bronze.orders_raw"),
        "silver.orders_checked rows": q("SELECT COUNT(*) FROM silver.orders_checked"),
        "silver.orders_clean rows": q("SELECT COUNT(*) FROM silver.orders_clean"),
        "silver.orders_dedup rows": q("SELECT COUNT(*) FROM silver.orders_dedup"),
        "quarantine.orders rows": q("SELECT COUNT(*) FROM quarantine.orders"),
        "gold orders": gold[0], "gold revenue_inr": f"{gold[1]:.2f}", "gold loyalty points": gold[2],
    }

before = snapshot()
assert before["bronze.orders_raw rows"] == 8, "expected the B1 state (8 bronze order rows) before the B3 re-run"
print(before)
print("\nORD-1006 in quarantine.orders (BEFORE):")
display(fc.show("SELECT run_id, source, order_id, TO_JSON(reasons) AS reasons FROM quarantine.orders WHERE order_id = 'ORD-1006'"))
print("ORD-1006 in silver.orders_checked (BEFORE):")
display(fc.show("SELECT ingest_seq, source, order_id, currency, TO_JSON(reasons) AS reasons FROM silver.orders_checked WHERE order_id = 'ORD-1006'"))
```

```
{'bronze.orders_raw rows': 8, 'silver.orders_checked rows': 8, 'silver.orders_clean rows': 6, 'silver.orders_dedup rows': 4, 'quarantine.orders rows': 2, 'gold orders': 4, 'gold revenue_inr': '7785.00', 'gold loyalty points': 126}

ORD-1006 in quarantine.orders (BEFORE):
```

	RUN_ID	SOURCE	ORDER_ID	REASONS
0	20261112_040919	web	ORD-1006	["bad_email","bad_pincode"]

```
ORD-1006 in silver.orders_checked (BEFORE):
```

	INGEST_SEQ	SOURCE	ORDER_ID	CURRENCY	REASONS
0	6	web	ORD-1006	EUR	["bad_email","bad_pincode"]

Re-run the pipeline (with the new rule)

In [4]:
```
b3_info = fc.run_pipeline()
```

```
run_id: 20261112_042326
1. EXTRACT: sample data -> raw files
   web: 6 records -> elt\landing\web\web__20261112_042326.json.gz
   mobile: 2 records -> elt\landing\mobile\mobile__20261112_042326.json.gz
   crm: 4 records -> elt\landing\crm\crm__20261112_042326.json.gz
   fx: 1 records -> elt\landing\fx\fx__20261112_042326.json.gz
2. LOAD: raw files -> bronze tables
   6 rows -> bronze.orders_raw
   2 rows -> bronze.orders_raw
   4 rows -> bronze.customers_raw
   1 rows -> bronze.fx_raw
3. TRANSFORM: bronze -> silver -> gold
   new pincodes to look up: []
4. CHECK
   rows gained or lost while enriching    0   OK
   duplicate orders in gold               0   OK
   orders with no customer match          0   OK
   orders with an amount but no FX rate   0   OK
   orders with no city                    0   OK
   share of rows rejected                 25%
GOLD: 4 orders, revenue ₹7785.00, 126 loyalty points
```

After the re-run

In [5]:
```
after = snapshot()
comparison = pd.DataFrame({"before": before, "after": after})
comparison["changed?"] = ["yes" if str(b) != str(a) else "no" for b, a in zip(comparison["before"], comparison["after"])]
comparison
```

Out[5]:

	before	after	changed?
bronze.orders_raw rows	8	16	yes
silver.orders_checked rows	8	16	yes
silver.orders_clean rows	6	12	yes
silver.orders_dedup rows	4	4	no
quarantine.orders rows	2	2	no
gold orders	4	4	no
gold revenue_inr	7785.00	7785.00	no

gold loyalty points	126	126	no

In [6]:
```
print("ORD-1006 in silver.orders_checked (AFTER; rebuilt by the re-run from all bronze rows):")
display(fc.show("SELECT ingest_seq, source, order_id, currency, TO_JSON(reasons) AS reasons FROM silver.orders_checked WHERE order_id = 'ORD-1006' ORDER BY ingest_s
print("ORD-1006 in quarantine.orders (AFTER):")
display(fc.show("SELECT run_id, source, order_id, TO_JSON(reasons) AS reasons FROM quarantine.orders WHERE order_id = 'ORD-1006'"))
```

```
ORD-1006 in silver.orders_checked (AFTER; rebuilt by the re-run from all bronze rows):
```

	INGEST_SEQ	SOURCE	ORDER_ID	CURRENCY	REASONS
0	6	web	ORD-1006	EUR	["bad_email","bad_pincode","unsupported_curren…
1	14	web	ORD-1006	EUR	["bad_email","bad_pincode","unsupported_curren…

```
ORD-1006 in quarantine.orders (AFTER):
```

	RUN_ID	SOURCE	ORDER_ID	REASONS
0	20261112_040919	web	ORD-1006	["bad_email","bad_pincode"]

Is only the right currency flagged?

In [7]:
```
fc.show("""
SELECT currency, COUNT(*) AS rows_in_orders_checked,
       COUNT_IF(ARRAY_CONTAINS('unsupported_currency'::VARIANT, reasons)) AS flagged_unsupported_currency
FROM silver.orders_checked GROUP BY currency ORDER BY currency
""")
```

Out[7]:

	CURRENCY	ROWS_IN_ORDERS_CHECKED	FLAGGED_UNSUPPORTED_CURRENCY
0	EUR	2	2
1	INR	10	0
2	USD	4	0

Did the re-run add a second quarantine row?


Bronze now holds **two copies** of every raw order (one per run), so `silver.orders_checked` has two copies of each rejected row, but `quarantine.orders` should still have one row per rejected record. The `NOT EXISTS (...)` in `SQL_10_ORDERS_CLEAN` skips a rejected row when `quarantine.orders` already has the same `source`, `order_id` and `updated_at` (it does not look at the reasons).

In [8]:
```
print("copies of each rejected record in silver.orders_checked vs quarantine.orders:")
fc.show("""
SELECT c.source, c.order_id, c.updated_at,
       COUNT(*) AS copies_in_orders_checked,
       (SELECT COUNT(*) FROM quarantine.orders q
         WHERE q.source = c.source AND q.order_id = c.order_id
           AND EQUAL_NULL(q.row_data:UPDATED_AT::TIMESTAMP_NTZ, c.updated_at)) AS rows_in_quarantine
FROM silver.orders_checked c
WHERE ARRAY_SIZE(c.reasons) > 0
GROUP BY c.source, c.order_id, c.updated_at ORDER BY c.order_id
""")
```

```
copies of each rejected record in silver.orders_checked vs quarantine.orders:
```

Out[8]:

	SOURCE	ORDER_ID	UPDATED_AT	COPIES_IN_ORDERS_CHECKED	ROWS_IN_QUARANTINE
0	web	ORD-1004	2026-09-03 12:00:00	2	1
1	web	ORD-1006	2026-09-04 08:30:00	2	1



B4: five outcomes, idempotence, bronze growth

B4: customer tier change (SCD2) and idempotency

New CRM event added to `MOCK_CRM_TIER_EVENTS` in `elt/mock_data.py` : **CUST-02, arjun.k@yahoo.in, Gold, effective_from 2026-08-15**. The predictions below were written and committed **before** this section was run (`report/answers.md` , "PRE-RUN PREDICTIONS").

In [2]:
```
import pandas as pd
q = lambda sql: fc.query(sql)[0][0]
print("events in MOCK_CRM_TIER_EVENTS:", len(fc.MOCK_CRM_TIER_EVENTS))
pd.DataFrame(fc.MOCK_CRM_TIER_EVENTS)
```

```
events in MOCK_CRM_TIER_EVENTS: 5
```

Out[2]:

	cust_id	email	tier	effective_from
0	CUST-01	priya.r@gmail.com	Silver	2023-04-10
1	CUST-01	priya.r@gmail.com	Gold	2026-09-03
2	CUST-02	arjun.k@yahoo.in	Silver	2024-01-15
3	CUST-03	meera@outlook.com	Platinum	2022-11-01
4	CUST-02	arjun.k@yahoo.in	Gold	2026-08-15

Before the run: gold rows with `published_at` and `row_hash`

In [3]:
```
gold_before = fc.show("SELECT order_id, tier, multiplier, loyalty_points, row_hash, published_at FROM gold.fct_orders ORDER BY order_id")
bronze_before = {t: q(f"SELECT COUNT(*) FROM bronze.{t}") for t in ["orders_raw", "customers_raw", "fx_raw", "pincode_raw"]}
print("CUST-02 rows in dim.customers_scd2 BEFORE:", q("SELECT COUNT(*) FROM dim.customers_scd2 WHERE cust_id = 'CUST-02'"))
print("bronze row counts BEFORE:", bronze_before)
gold_before
```

```
CUST-02 rows in dim.customers_scd2 BEFORE: 1
bronze row counts BEFORE: {'orders_raw': 16, 'customers_raw': 8, 'fx_raw': 2, 'pincode_raw': 3}
```

Out[3]:

	ORDER_ID	TIER	MULTIPLIER	LOYALTY_POINTS	ROW_HASH	PUBLISHED_AT
0	ORD-1001	Silver	1	12	4284627330879666653	2026-11-11 20:09:29.606000-08:00
1	ORD-1002	Silver	1	35	-7698738864412791922	2026-11-11 20:09:29.606000-08:00
2	ORD-1003	Platinum	3	63	-1632326326823866187	2026-11-11 20:09:29.606000-08:00
3	ORD-1005	Gold	2	16	-231880702048109571	2026-11-11 20:09:29.606000-08:00

Run the pipeline once (full run: extract, load, transform, check)

In [4]:
```
b4_info = fc.run_pipeline()
```

```
run_id: 20261112_043003
1. EXTRACT: sample data -> raw files
   web: 6 records -> elt\landing\web\web__20261112_043003.json.gz
   mobile: 2 records -> elt\landing\mobile\mobile__20261112_043003.json.gz
   crm: 5 records -> elt\landing\crm\crm__20261112_043003.json.gz
   fx: 1 records -> elt\landing\fx\fx__20261112_043003.json.gz
2. LOAD: raw files -> bronze tables
   6 rows -> bronze.orders_raw
   2 rows -> bronze.orders_raw
   5 rows -> bronze.customers_raw
   1 rows -> bronze.fx_raw
3. TRANSFORM: bronze -> silver -> gold
   new pincodes to look up: []
4. CHECK
   rows gained or lost while enriching    0   OK
   duplicate orders in gold               0   OK
   orders with no customer match          0   OK
   orders with an amount but no FX rate   0   OK
   orders with no city                    0   OK
   share of rows rejected                 25%
GOLD: 4 orders, revenue ₹7785.00, 161 loyalty points
```

The five outcomes: committed prediction vs actual

In [2]:
```
import pandas as pd
q = lambda sql: fc.query(sql)[0][0]

# The B4 pipeline run above has run_id 20261112_043003 (= 04:30:03 UTC). Snowflake Time Travel gives the tables exactly as
# they were just before it, so the "before" side of every comparison is read from Snowflake itself, not retyped.
BEFORE_RUN = "2026-11-12 04:30:00 +0000"
at = f"AT(TIMESTAMP => '{BEFORE_RUN}'::TIMESTAMP_LTZ)"
gold_before = fc.show(f"SELECT order_id, tier, multiplier, loyalty_points, row_hash, published_at FROM gold.fct_orders {at} ORDER BY order_id")
bronze_before = {t: q(f"SELECT COUNT(*) FROM bronze.{t} {at}") for t in ["orders_raw", "customers_raw", "fx_raw", "pincode_raw"]}

gold_after = fc.show("SELECT order_id, tier, multiplier, loyalty_points, row_hash, published_at FROM gold.fct_orders ORDER BY order_id")
cmp_ = gold_before.merge(gold_after, on="ORDER_ID", suffixes=("_before", "_after"))
published_changed = int((cmp_["PUBLISHED_AT_before"] != cmp_["PUBLISHED_AT_after"]).sum())
hash_changed = int((cmp_["ROW_HASH_before"] != cmp_["ROW_HASH_after"]).sum())
ord1002 = gold_after[gold_after.ORDER_ID == "ORD-1002"].iloc[0]
actual = {
    "CUST-02 rows in dim.customers_scd2": q("SELECT COUNT(*) FROM dim.customers_scd2 WHERE cust_id = 'CUST-02'"),
    "Tier used for ORD-1002": ord1002.TIER,
    "Loyalty points for ORD-1002": int(ord1002.LOYALTY_POINTS),
    "Total loyalty points in gold": int(q("SELECT SUM(loyalty_points) FROM gold.fct_orders")),
    "Gold rows whose published_at changed": published_changed,
}
predicted = {  # copied from the committed PRE-RUN PREDICTIONS in report/answers.md (commit 72e290d)
    "CUST-02 rows in dim.customers_scd2": 2,
    "Tier used for ORD-1002": "Gold",
    "Loyalty points for ORD-1002": 70,
    "Total loyalty points in gold": 161,
    "Gold rows whose published_at changed": 1,
}
result = pd.DataFrame({"prediction": predicted, "actual": actual})
result["match?"] = ["YES" if str(p) == str(a) else "NO" for p, a in zip(result["prediction"], result["actual"])]
print("gold BEFORE the B4 run (Time Travel):")
display(gold_before)
print(f"{(result['match?'] == 'YES').sum()} of {len(result)} predictions match; rows with changed row_hash: {hash_changed}")
result
```

```
gold BEFORE the B4 run (Time Travel):
```

	ORDER_ID	TIER	MULTIPLIER	LOYALTY_POINTS	ROW_HASH	PUBLISHED_AT
0	ORD-1001	Silver	1	12	4284627330879666653	2026-11-11 20:09:29.606000-08:00
1	ORD-1002	Silver	1	35	-7698738864412791922	2026-11-11 20:09:29.606000-08:00
2	ORD-1003	Platinum	3	63	-1632326326823866187	2026-11-11 20:09:29.606000-08:00
3	ORD-1005	Gold	2	16	-231880702048109571	2026-11-11 20:09:29.606000-08:00

```
5 of 5 predictions match; rows with changed row_hash: 1
```

Out[2]:

	prediction	actual	match?
CUST-02 rows in dim.customers_scd2	2	2	YES
Tier used for ORD-1002	Gold	Gold	YES
Loyalty points for ORD-1002	70	70	YES
Total loyalty points in gold	161	161	YES
Gold rows whose published_at changed	1	1	YES

In [3]:
```
print("CUST-02 in dim.customers_scd2 (AFTER):")
display(fc.show("SELECT cust_id, tier, valid_from, valid_to, is_current FROM dim.customers_scd2 WHERE cust_id = 'CUST-02' ORDER BY valid_from"))
print("Gold rows: before vs after (only ORD-1002 should differ):")
cmp_
```

```
CUST-02 in dim.customers_scd2 (AFTER):
```

	CUST_ID	TIER	VALID_FROM	VALID_TO	IS_CURRENT
0	CUST-02	Silver	2024-01-15	2026-08-14	False
1	CUST-02	Gold	2026-08-15	9999-12-31	True

```
Gold rows: before vs after (only ORD-1002 should differ):
```

Out[3]:

	ORDER_ID	TIER_before	MULTIPLIER_before	LOYALTY_POINTS_before	ROW_HASH_before	PUBLISHED_AT_before	TIER_after	MULTIPLIER_after	LOYALTY_POINTS_after	R
0	ORD-1001	Silver	1	12	4284627330879666653	2026-11-11 20:09:29.606000-08:00	Silver	1	12	42846
1	ORD-1002	Silver	1	35	-7698738864412791922	2026-11-11 20:09:29.606000-08:00	Gold	2	70	33922
2	ORD-1003	Platinum	3	63	-1632326326823866187	2026-11-11 20:09:29.606000-08:00	Platinum	3	63	-16323
3	ORD-1005	Gold	2	16	-231880702048109571	2026-11-11 20:09:29.606000-08:00	Gold	2	16	-2318

Idempotence: run the transformation a second time

Only the transformation is repeated (`SQL_30_CUSTOMERS_SCD2` rebuilds the dimension, `SQL_40_GOLD` rebuilds `silver.orders_enriched` and runs the `MERGE`). Nothing new is loaded. The `MERGE` updates a row (and refreshes `published_at`) only when `row_hash` changed, so every `published_at` must stay as it was after the first B4 run.

In [4]:
```
gold_mid = fc.show("SELECT order_id, row_hash, published_at FROM gold.fct_orders ORDER BY order_id")
fc.run_sql(fc.SQL_30_CUSTOMERS_SCD2)
fc.run_sql(fc.SQL_40_GOLD)
gold_again = fc.show("SELECT order_id, row_hash, published_at FROM gold.fct_orders ORDER BY order_id")
idem = gold_mid.merge(gold_again, on="ORDER_ID", suffixes=("_run1", "_run2"))
idem["published_at_kept?"] = idem["PUBLISHED_AT_run1"] == idem["PUBLISHED_AT_run2"]
idem["row_hash_same?"] = idem["ROW_HASH_run1"] == idem["ROW_HASH_run2"]
```

```
print("rows whose published_at changed in the second pass:", int((~idem["published_at_kept?"]).sum()))
print("gold totals after the second pass:", fc.query("SELECT COUNT(*), SUM(amount_inr), SUM(loyalty_points) FROM gold.fct_orders")[0])
idem
```

```
rows whose published_at changed in the second pass: 0
gold totals after the second pass: (4, Decimal('7785.00'), 161)
```

Out[4]:

	ORDER_ID	ROW_HASH_run1	PUBLISHED_AT_run1	ROW_HASH_run2	PUBLISHED_AT_run2	published_at_kept?	row_hash_same?
0	ORD-1001	4284627330879666653	2026-11-11 20:09:29.606000-08:00	4284627330879666653	2026-11-11 20:09:29.606000-08:00	True	True
1	ORD-1002	3392257107350681567	2026-11-11 20:30:13.292000-08:00	3392257107350681567	2026-11-11 20:30:13.292000-08:00	True	True
2	ORD-1003	-16323263268238661 87	2026-11-11 20:09:29.606000-08:00	-16323263268238661 87	2026-11-11 20:09:29.606000-08:00	True	True
3	ORD-1005	-231880702048109571	2026-11-11 20:09:29.606000-08:00	-231880702048109571	2026-11-11 20:09:29.606000-08:00	True	True

Why does bronze grow by 8 order rows on every run?

Every run extracts the same 8 raw orders again, writes them to **new landing files** (the file name contains the new `run_id`), `PUT`s them to a new stage folder and `COPY INTO` appends them. Bronze keeps every copy it is given (it has no deduplication; that is silver's job), so `bronze.orders_raw` grows by 6 web + 2 mobile = 8 rows per run, while silver (`orders_dedup`) and gold stay the same size.

In [5]:
```
print("bronze.orders_raw rows per run (each full pipeline run adds one group of 8):")
display(fc.show("SELECT run_id, COUNT(*) AS order_rows, COUNT_IF(source = 'web') AS web, COUNT_IF(source = 'mobile') AS mobile, COUNT(DISTINCT src_file) AS landing_
bronze_after = {t: q(f"SELECT COUNT(*) FROM bronze.{t}") for t in ["orders_raw", "customers_raw", "fx_raw", "pincode_raw"]}
growth = pd.DataFrame({"before B4 run": bronze_before, "after B4 run": bronze_after})
growth["added by this run"] = growth["after B4 run"] - growth["before B4 run"]
print("this run added 8 order rows, 5 CRM rows (the 4 old events + the new one), 1 FX reply, and no pincodes (all already known):")
growth
```

```
bronze.orders_raw rows per run (each full pipeline run adds one group of 8):
```

	RUN_ID	ORDER_ROWS	WEB	MOBILE	LANDING_FILES
0	20261112_040919	8	6	2	2
1	20261112_042326	8	6	2	2
2	20261112_043003	8	6	2	2

```
this run added 8 order rows, 5 CRM rows (the 4 old events + the new one), 1 FX reply, and no pincodes (all already known):
```

Out[5]:

	before B4 run	after B4 run	added by this run
orders_raw	16	24	8
customers_raw	8	13	5
fx_raw	2	3	1
pincode_raw	3	3	0



B5: PROBLEM output, cleanup and recovery

B5: a sixth quality check: orders dated in the future

`quality_checks()` (in `elt/freshcart.py`) now has a sixth check that should also be **0**:

```
SELECT COUNT_IF(order_date > CURRENT_DATE()) FROM silver.orders_dedup      -- "orders dated in the future"
```

Plan: (1) show it passes on the real data, (2) make it fail on purpose with **one clearly marked mock order** (`TEST-B5-FUTURE-DATE-001`), (3) clean up exactly that test data, (4) show the check is back to 0.

In [2]:
```
import inspect
import pandas as pd
q = lambda sql: fc.query(sql)[0][0]

print("the new check inside quality_checks():")
print("\n".join(l for l in inspect.getsource(fc.quality_checks).splitlines() if "B5" in l or "in the future" in l or "CURRENT_DATE" in l))
print("\nsession CURRENT_DATE():", q("SELECT CURRENT_DATE()"))
print("\nCONTROL: quality_checks() on the real data (the new check must be 0 / OK):")
fc.quality_checks()
```

```
the new check inside quality_checks():
        # B5: the sixth check. An order cannot have happened in the future.
        "orders dated in the future":
            "SELECT COUNT_IF(order_date > CURRENT_DATE()) FROM silver.orders_dedup",
session CURRENT_DATE(): 2026-11-11

CONTROL: quality_checks() on the real data (the new check must be 0 / OK):
   rows gained or lost while enriching    0   OK
   duplicate orders in gold               0   OK
   orders with no customer match          0   OK
   orders with an amount but no FX rate   0   OK
   orders with no city                    0   OK
   orders dated in the future             0   OK
   share of rows rejected                 25%
```

The mock order

It is a *web-format* order with a future `order_date`. It is built so that **only the new check fails**: it uses an existing customer email and an existing pincode (so customer match and city are fine) and has **no amount** (a missing amount is allowed, and there is no FX rate for a future date, so the FX check stays quiet). Everything about it is marked: the order id `TEST-B5-FUTURE-DATE-001` and the run id ending in `_b5test`. A baseline of every table is taken first, so cleanup can be checked against it.

In [3]:
```
from datetime import datetime, timezone

TEST_ORDER_ID = "TEST-B5-FUTURE-DATE-001"
TEST_RUN_ID = datetime.now(timezone.utc).strftime("%Y%m%d_%H%M%S") + "_b5test"
test_order = {"order_id": TEST_ORDER_ID, "cust_email": "priya.r@gmail.com", "cust_name": "B5 test order",
              "order_date": "2026-12-31", "amount": None, "currency": "INR", "pincode": "600041",
              "updated_at": "2026-11-12 09:00:00"}

tables = ["bronze.orders_raw", "bronze.customers_raw", "bronze.fx_raw", "bronze.pincode_raw", "silver.orders_checked",
          "silver.orders_clean", "silver.orders_dedup", "silver.orders_enriched", "dim.customers_scd2", "ref.fx_daily",
          "ref.pincode_geo", "quarantine.orders", "gold.fct_orders"]
baseline = {t: q(f"SELECT COUNT(*) FROM {t}") for t in tables}
baseline_gold = fc.show("SELECT order_id, tier, amount_inr, loyalty_points, row_hash, published_at FROM gold.fct_orders ORDER BY order_id")

traces = {"bronze": q(f"SELECT COUNT(*) FROM bronze.orders_raw WHERE raw:order_id::STRING = '{TEST_ORDER_ID}' OR run_id = '{TEST_RUN_ID}'"),
          "gold": q(f"SELECT COUNT(*) FROM gold.fct_orders WHERE order_id = '{TEST_ORDER_ID}'"),
          "quarantine": q(f"SELECT COUNT(*) FROM quarantine.orders WHERE order_id = '{TEST_ORDER_ID}'")}
assert set(traces.values()) == {0}, f"the marker already exists somewhere: {traces}"
print("test order:", test_order)
print("run id    :", TEST_RUN_ID)
print("marker not present anywhere yet:", traces)
print("baseline row counts:", baseline)
baseline_gold
```

```
test order: {'order_id': 'TEST-B5-FUTURE-DATE-001', 'cust_email': 'priya.r@gmail.com', 'cust_name': 'B5 test order', 'order_date': '2026-12-31', 'amount': None, 'cur
rency': 'INR', 'pincode': '600041', 'updated_at': '2026-11-12 09:00:00'}
run id    : 20261112_043630_b5test
marker not present anywhere yet: {'bronze': 0, 'gold': 0, 'quarantine': 0}
baseline row counts: {'bronze.orders_raw': 24, 'bronze.customers_raw': 13, 'bronze.fx_raw': 3, 'bronze.pincode_raw': 3, 'silver.orders_checked': 24, 'silver.orders_c
lean': 18, 'silver.orders_dedup': 4, 'silver.orders_enriched': 4, 'dim.customers_scd2': 5, 'ref.fx_daily': 144, 'ref.pincode_geo': 3, 'quarantine.orders': 2, 'gold.f
ct_orders': 4}
```

Out[3]:

	ORDER_ID	TIER	AMOUNT_INR	LOYALTY_POINTS	ROW_HASH	PUBLISHED_AT
0	ORD-1001	Silver	1250.00	12	4284627330879666653	2026-11-11 20:09:29.606000-08:00
1	ORD-1002	Gold	3536.00	70	3392257107350681567	2026-11-11 20:30:13.292000-08:00
2	ORD-1003	Platinum	2100.00	63	-1632326326823866187	2026-11-11 20:09:29.606000-08:00
3	ORD-1005	Gold	899.00	16	-231880702048109571	2026-11-11 20:09:29.606000-08:00

Load the mock order, rebuild silver and gold, run the checks (expect a PROBLEM)

In [4]:
```
print("1. EXTRACT + 2. LOAD: only the mock order, in the web format")
test_file = fc.write_landing("web", [test_order], TEST_RUN_ID)
fc.load_file(test_file, "bronze.orders_raw", f"orders_web/{TEST_RUN_ID}")
print("3. TRANSFORM: bronze -> silver -> gold")
fc.transform(TEST_RUN_ID)
print("4. CHECK")
fc.quality_checks()
```

```
1. EXTRACT + 2. LOAD: only the mock order, in the web format
   web: 1 records -> elt\landing\web\web__20261112_043630_b5test.json.gz
   1 rows -> bronze.orders_raw
3. TRANSFORM: bronze -> silver -> gold
   new pincodes to look up: []
4. CHECK
   rows gained or lost while enriching    0   OK
   duplicate orders in gold               0   OK
   orders with no customer match          0   OK
   orders with an amount but no FX rate   0   OK
   orders with no city                    0   OK
   orders dated in the future             1   PROBLEM
   share of rows rejected                 24%
```

In [5]:
```
print("the offending row in silver.orders_dedup (order_date > CURRENT_DATE()):")
display(fc.show("SELECT order_id, order_date, email, amount, currency, pincode FROM silver.orders_dedup WHERE order_date > CURRENT_DATE()"))
print("the mock order has also reached gold.fct_orders (gold's MERGE never deletes):")
display(fc.show("SELECT order_id, order_date, tier, amount_inr, loyalty_points, city FROM gold.fct_orders ORDER BY order_id"))
```

```
print("gold totals now:", fc.query("SELECT COUNT(*), SUM(amount_inr), SUM(loyalty_points) FROM gold.fct_orders")[0])
```

```
the offending row in silver.orders_dedup (order_date > CURRENT_DATE()):
```

	ORDER_ID	ORDER_DATE	EMAIL	AMOUNT	CURRENCY	PINCODE
0	TEST-B5-FUTURE-DATE-001	2026-12-31	priya.r@gmail.com	None	INR	600041

```
the mock order has also reached gold.fct_orders (gold's MERGE never deletes):
```

	ORDER_ID	ORDER_DATE	TIER	AMOUNT_INR	LOYALTY_POINTS	CITY
0	ORD-1001	2026-09-01	Silver	1250.00	12.0	Chennai
1	ORD-1002	2026-09-01	Gold	3536.00	70.0	Bengaluru
2	ORD-1003	2026-09-02	Platinum	2100.00	63.0	Mumbai
3	ORD-1005	2026-09-03	Gold	899.00	16.0	Chennai
4	TEST-B5-FUTURE-DATE-001	2026-12-31	Gold	None	NaN	Chennai

```
gold totals now: (5, Decimal('7785.00'), 161)
```

Cleanup: look first, delete only what is proven to be the test data

Bronze is append-only and gold's `MERGE` never deletes, so removing the order from the Python list would not remove it. From the SQL (`elt/sql/`): `silver.*` , `dim.*` and `ref.fx_daily` are `CREATE OR REPLACE` (rebuilt from bronze on every run, nothing to delete), `quarantine.orders` only inserts (the mock order is valid, so it must have 0 rows there), and `PUT` leaves the file in the stage. So the test data can only be in: `bronze.orders_raw` , `gold.fct_orders` and the stage folder of the test run (plus the local landing file). The cell below counts exactly what matches the markers and **stops (assert) before deleting anything** if the numbers are not exactly as expected.

In [6]:
```
marker = f"raw:order_id::STRING = '{TEST_ORDER_ID}' AND run_id = '{TEST_RUN_ID}'"
staged = fc.query(f"LIST @bronze.landing/orders_web/{TEST_RUN_ID}/")
found = {
    "bronze.orders_raw: order id AND test run id": q(f"SELECT COUNT(*) FROM bronze.orders_raw WHERE {marker}"),
    "bronze.orders_raw: order id (any run)": q(f"SELECT COUNT(*) FROM bronze.orders_raw WHERE raw:order_id::STRING = '{TEST_ORDER_ID}'"),
    "bronze.orders_raw: test run id (any order)": q(f"SELECT COUNT(*) FROM bronze.orders_raw WHERE run_id = '{TEST_RUN_ID}'"),
    "bronze.orders_raw: all OTHER rows (kept)": q(f"SELECT COUNT(*) FROM bronze.orders_raw WHERE run_id <> '{TEST_RUN_ID}'"),
    "gold.fct_orders: this order id": q(f"SELECT COUNT(*) FROM gold.fct_orders WHERE order_id = '{TEST_ORDER_ID}'"),
```

```
    "gold.fct_orders: all OTHER rows (kept)": q(f"SELECT COUNT(*) FROM gold.fct_orders WHERE order_id <> '{TEST_ORDER_ID}'"),
    "quarantine.orders: this order id": q(f"SELECT COUNT(*) FROM quarantine.orders WHERE order_id = '{TEST_ORDER_ID}'"),
    "staged files in this run's stage folder": len(staged),
}
expected = {
    "bronze.orders_raw: order id AND test run id": 1, "bronze.orders_raw: order id (any run)": 1,
    "bronze.orders_raw: test run id (any order)": 1,
    "bronze.orders_raw: all OTHER rows (kept)": baseline["bronze.orders_raw"],
    "gold.fct_orders: this order id": 1, "gold.fct_orders: all OTHER rows (kept)": baseline["gold.fct_orders"],
    "quarantine.orders: this order id": 0, "staged files in this run's stage folder": 1,
}
print(pd.DataFrame({"found": found, "expected": expected}))
assert found == expected, "STOP: the markers match something unexpected; nothing has been deleted"
print("\nrows that WILL be deleted:")
display(fc.show(f"SELECT ingest_seq, source, run_id, TO_JSON(raw) AS raw_json FROM bronze.orders_raw WHERE {marker}"))
display(fc.show(f"SELECT order_id, order_date, tier, amount_inr FROM gold.fct_orders WHERE order_id = '{TEST_ORDER_ID}'"))
print("staged file:", [r[0] for r in staged])
```

```
                                          found  expected
bronze.orders_raw: order id AND test run id      1         1
bronze.orders_raw: order id (any run)            1         1
bronze.orders_raw: test run id (any order)       1         1
bronze.orders_raw: all OTHER rows (kept)        24        24
gold.fct_orders: this order id                   1         1
gold.fct_orders: all OTHER rows (kept)           4         4
quarantine.orders: this order id                 0         0
staged files in this run's stage folder          1         1

rows that WILL be deleted:
```

	INGEST_SEQ	SOURCE	RUN_ID	RAW_JSON
0	25	web	20261112_043630_b5test	{"amount":null,"currency":"INR","cust_email":"...

	ORDER_ID	ORDER_DATE	TIER	AMOUNT_INR
0	TEST-B5-FUTURE-DATE-001	2026-12-31	Gold	None

```
staged file: ['landing/orders_web/20261112_043630_b5test/web__20261112_043630_b5test.json.gz']
```

In [7]:
```
import os
n_bronze = fc.query(f"DELETE FROM bronze.orders_raw WHERE {marker}")[0][0]
n_gold = fc.query(f"DELETE FROM gold.fct_orders WHERE order_id = '{TEST_ORDER_ID}'")[0][0]
removed = fc.query(f"REMOVE @bronze.landing/orders_web/{TEST_RUN_ID}/")
assert TEST_RUN_ID in str(test_file) and "landing" in str(test_file)
os.remove(test_file)
print(f"deleted from bronze.orders_raw: {n_bronze} row | deleted from gold.fct_orders: {n_gold} row")
print("removed from the stage:", [r[:2] for r in removed])
print("local landing file removed:", not os.path.exists(test_file))
assert n_bronze == 1 and n_gold == 1
```

```
deleted from bronze.orders_raw: 1 row | deleted from gold.fct_orders: 1 row
removed from the stage: [('landing/orders_web/20261112_043630_b5test/web__20261112_043630_b5test.json.gz', 'removed')]
local landing file removed: True
```

Recovery: rebuild from the cleaned bronze and re-run the checks

`silver.orders_dedup` still contains the mock order until the transformation runs again, so the stage-3 SQL is re-run (no extract, no load). Then every table must be back to the baseline taken before the mock order existed.

In [8]:
```
print("3. TRANSFORM again (from the cleaned bronze)")
fc.transform("b5_cleanup")
print("4. CHECK")
fc.quality_checks()
```

```
3. TRANSFORM again (from the cleaned bronze)
   new pincodes to look up: []
4. CHECK
   rows gained or lost while enriching    0   OK
   duplicate orders in gold               0   OK
   orders with no customer match          0   OK
   orders with an amount but no FX rate   0   OK
   orders with no city                    0   OK
   orders dated in the future             0   OK
   share of rows rejected                 25%
```

In [9]:
```
after = {t: q(f"SELECT COUNT(*) FROM {t}") for t in tables}
gold_after = fc.show("SELECT order_id, tier, amount_inr, loyalty_points, row_hash, published_at FROM gold.fct_orders ORDER BY order_id")
leftovers = {
    "bronze.orders_raw rows with the marker": q(f"SELECT COUNT(*) FROM bronze.orders_raw WHERE raw:order_id::STRING = '{TEST_ORDER_ID}' OR run_id = '{TEST_RUN_ID}'"
    "gold.fct_orders rows with the marker": q(f"SELECT COUNT(*) FROM gold.fct_orders WHERE order_id = '{TEST_ORDER_ID}'"),
    "quarantine.orders rows with the marker": q(f"SELECT COUNT(*) FROM quarantine.orders WHERE order_id = '{TEST_ORDER_ID}'"),
    "silver.orders_dedup future-dated rows": q("SELECT COUNT_IF(order_date > CURRENT_DATE()) FROM silver.orders_dedup"),
    "staged files for the test run": len(fc.query(f"LIST @bronze.landing/orders_web/{TEST_RUN_ID}/")),
}
rows = [(t, baseline[t], after[t], "PASS" if baseline[t] == after[t] else "FAIL") for t in tables]
rows += [("gold rows identical to baseline (incl. row_hash and published_at)", "yes", "yes" if baseline_gold.equals(gold_after) else "NO",
          "PASS" if baseline_gold.equals(gold_after) else "FAIL")]
rows += [(k, 0, v, "PASS" if v == 0 else "FAIL") for k, v in leftovers.items()]
result = pd.DataFrame(rows, columns=["Check", "Baseline / expected", "Now", "Result"])
print(f"{(result.Result == 'PASS').sum()} of {len(result)} cleanup checks PASS")
result
```


```
19 of 19 cleanup checks PASS
```

Out[9]:

	Check	Baseline / expected	Now	Result
0	bronze.orders_raw	24	24	PASS
1	bronze.customers_raw	13	13	PASS
2	bronze.fx_raw	3	3	PASS
3	bronze.pincode_raw	3	3	PASS
4	silver.orders_checked	24	24	PASS
5	silver.orders_clean	18	18	PASS
6	silver.orders_dedup	4	4	PASS
7	silver.orders_enriched	4	4	PASS
8	dim.customers_scd2	5	5	PASS
9	ref.fx_daily	144	144	PASS
10	ref.pincode_geo	3	3	PASS

11	quarantine.orders	2	2	PASS
12	gold.fct_orders	4	4	PASS
13	gold rows identical to baseline (incl. row_has...	yes	yes	PASS
14	bronze.orders_raw rows with the marker	0	0	PASS
15	gold.fct_orders rows with the marker	0	0	PASS
16	quarantine.orders rows with the marker	0	0	PASS
17	silver.orders_dedup future-dated rows	0	0	PASS
18	staged files for the test run	0	0	PASS

C3: Mage UI showing the evaluation branch



Text evidence (not reproduced here): `report/screenshots/C/` (Mage runs), `D/` (routing, driver and dispatcher logs, ACK/NACK), `Bonus/`, `Final/` (final notebook run, FINAL_notebook.html).