

## opinion mining with deep recurrent nets

[back](#) **Paper**: [Opinion Mining with Deep Recurrent Neural Networks](#)

*O. Irsoy, C. Cardie* EMNLP, 2014, Doha, Qatar.

**Abstract**: Recurrent neural networks (RNNs) are connectionist models of sequential data that are naturally applicable to the analysis of natural language. Recently, ``depth in space" --- as an orthogonal notion to ``depth in time" --- in RNNs has been investigated by stacking multiple layers of RNNs and shown empirically to bring a temporal hierarchy to the architecture. In this work we apply these deep RNNs to the task of opinion expression extraction formulated as a token-level sequence-labeling task. Experimental results show that deep, narrow RNNs outperform traditional shallow, wide RNNs with the same number of parameters. Furthermore, our approach outperforms previous CRF-based baselines, including the state-of-the-art semi-Markov CRF model, and does so without access to the powerful opinion lexicons and syntactic features relied upon by the semi-CRF, as well as without the standard layer-by-layer pre-training typically required of RNN architectures.

**Slides**: Oral presentation is [here](#).

**More slides**: Part of [this](#) talk I gave at Cornell AI seminar was based on this work.

**Code**: My C++ code is [here](#). Please cite the paper if you use it.

**Data**: Preprocessed version of the dataset is [here](#), which you can use to replicate the results. The original MPQA corpus can be found [here](#). You should cite the appropriate paper by Wiebe et al (2005) if you use the data.

**Bibtex**:

```
@InProceedings{irsoy-drnt,  
  author = {\.Irsoy, Ozan and Cardie, Claire},  
  title = {Opinion Mining with Deep Recurrent Neural  
Networks},  
  booktitle = {Proceedings of the Conference on Empirical  
Methods in Natural Language Processing},  
  pages = {720--728},  
  year = {2014},  
  location = {Doha, Qatar},  
  url = {http://aclweb.org/anthology/D14-1080}  
}
```