Rajalakshmi Engineering College

Name: Ravi Sankar 1

Email: 240701424@rajalakshmi.edu.in

Roll no: 240701424 Phone: 8122932671

Branch: REC

Department: I CSE FD

Batch: 2028

Degree: B.E - CSE



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 4_COD_Question 3

Attempt : 1 Total Mark : 10 Marks Obtained : 10

Section 1: Coding

1. Problem Statement

Write a program to implement a queue using an array and pointers. The program should provide the following functionalities:

Insert an element into the queue. Delete an element from the queue. Display the elements in the queue.

The queue has a maximum capacity of 5 elements. If the queue is full and an insertion is attempted, a "Queue is full" message should be displayed. If the queue is empty and a deletion is attempted, a "Queue is empty" message should be displayed.

Input Format

Each line contains an integer representing the chosen option from 1 to 3.

01424

Option 1: Insert an element into the queue followed by an integer representing the element to be inserted, separated by a space.

Option 2: Delete an element from the queue.

Option 3: Display the elements in the queue.

Output Format

For option 1 (insertion):-

- 1. The program outputs: "<data> is inserted in the queue." if the data is successfully inserted.
- 2. "Queue is full." if the queue is already full and cannot accept more elements.

For option 2 (deletion):-

- 1. The program outputs: "Deleted number is: <data>" if an element is successfully deleted and returns the value of the deleted element.
- 2. "Queue is empty." if the queue is empty no elements can be deleted.

For option 3 (display):-

- 1. The program outputs: "Elements in the queue are: <element1> <element2> ... <elementN>" where <element1>, <element2>, ..., <elementN> represent the elements present in the queue.
- 2. "Queue is empty." if the queue is empty no elements can be displayed.

For invalid options, the program outputs: "Invalid option."

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1 10

24070742

```
Output: 10 is inserted in the queue.
     Elements in the queue are: 10
     Invalid option.
     Answer
     #include <stdio.h>
     #include <stdlib.h>
     #define max 5
     int queue[max];
     int front = -1, rear = -1;
int insertq(int *data)
{
       if ((rear + 1) \% max == front) {
          return 0;
       if (front == -1) {
          front = rear = 0;
       } else {
          rear = (rear + 1) \% max;
       queue[rear] = *data;
        return 1;
     int delq()
       if (front == -1) {
          printf("Queue is empty.\n");
          return -1;
       }
       int data = queue[front];
       if (front == rear) {
front = (front + 1) % max;
printf("Deleted pure
       printf("Deleted number is: %d\n", data);
```

```
240707424
                                                   240707424
                       240707424
  return data;
void display()
  if (front == -1) {
    printf("Queue is empty.\n");
    return;
  }
  printf("Elements in the queue are: ");
  int i = front:
  while (1) {
     printf("%d ", queue[i]);
   oif (i == rear) break;
    i = (i + 1) \% max;
  printf("\n");
int main()
  int data, reply, option;
  while (1)
    if (scanf("%d", &option) != 1)
       break;
     switch (option)
       case 1:
         if (scanf("%d", &data) != 1)
            break;
         reply = insertq(&data);
         if (reply == 0)
            printf("Queue is full.\n");
         else
            printf("%d is inserted in the queue.\n", data);
         break;
       case 2:
                     Called without arguments
         delq(); //
                                                                                240707424
         break;
       case 3:
         display();
         break:
```

return 0; }	nvalid option.\n");	2407014.24	2407014.24
Status: Correct	240707424	240701424	Marks: 10/10
240707424	240707424	240707424	240707424