# Assignment 2

```
Name : Ravish Ranjan
Course : MCA
Semester : 2nd semester
```

## TASK 1: WHOIS/RDAP Analysis

Choose one publicly accessible domain belonging to:

- a university,
- a public sector organisation
- a commercial organisation with a publicly visible web presence.

| Organization | Website |
|---|---|
| Central University of haryana | cuh.ac.in |
| Staff Selection Commission | ssc.gov.in |
| Amazon.com | amazon.com |

**Step 1: Perform the WHOIS or RDAP Lookup**

Use an online tool such as the WHOIS/ RDAP service or the command line to retrieve registration information for your chosen domain.

1. Central University of haryana `cuh.ac.in`



| | |
|---|---|
| Domain Status | active |
| Name Servers | cucc.cuh.ac.in<br>cc.cuh.ac.in |

## Registrant Contact

| | |
|---|---|
| Name | - |
| Organization | Central University of Haryana |
| Phone | - |
| Fax | - |
| Email | - |
| Mailing Address | - |

## Technical Contact

| | |
|---|---|
| Name | - |
| Organization | - |
| Phone | - |
| Fax | - |
| Email | - |
| Mailing Address | - |

## Registrar Information

| | |
|---|---|
| Name | ERNET India |
| IANA ID | 800068 |

| | |
|---|---|
| Abuse Contact Email | tejalt@eis.ernet.in |
| Abuse Contact Phone | tel:+91.1123358248 |

## DNSSEC Information

| | |
|---|---|
| Delegation Signed | Unsigned |

2. Staff Selection Commission `ssc.gov.in`

## WHOIS search results

### Domain Information

| | |
|---|---|
| Name | ssc.gov.in |
| Registry Domain ID | D848E18EE3C92490BADBD4C8AD64453CC-IN |
| Registered On | 2024-02-09T06:50:59.500Z |
| Expires On | 2027-02-09T06:50:59.500Z |
| Updated On | 2026-03-26T06:54:20.793Z |
| Domain Status | active |
| Name Servers | ns7.nic.in<br>ns1.nic.in<br>ns10.nic.in<br>ns2.nic.in |

### Registrant Contact

| | |
|---|---|
| Name | - |
| Organization | Staff Selection Commission |

| | |
|---|---|
| Phone | - |
| Fax | - |
| Email | - |
| Mailing Address | - |

## Technical Contact

| | |
|---|---|
| Name | - |
| Organization | - |
| Phone | - |
| Fax | - |
| Email | - |
| Mailing Address | - |

## Registrar Information

| | |
|---|---|
| Name | National Informatics Centre |
| IANA ID | 800111 |
| Abuse Contact Email | sunita.singh@nic.in |
| Abuse Contact Phone | tel:+91.1124305395 |

## DNSSEC Information

| | |
|---|---|
| Delegation Signed | Unsigned |

3. Amazon `amazon.com`

```
The Registry database contains ONLY .COM, .NET, .EDU domains and
Registrars.
Domain Name: amazon.com
Registry Domain ID: 281209_DOMAIN_COM-VRSN
Registrar WHOIS Server: whois.markmonitor.com
Registrar URL: http://www.markmonitor.com
Updated Date: 2025-07-31T17:49:55+0000
Creation Date: 1994-11-01T05:00:00+0000
Registrar Registration Expiration Date: 2026-10-31T00:00:00+0000
Registrar: MarkMonitor, Inc.
Registrar IANA ID: 292
Registrar Abuse Contact: https://corp.markmonitor.com/domain/ui/abuse-report
Registrar Abuse Contact Phone: +1.2086851750
Domain Status: clientUpdateProhibited (https://www.icann.org/epp#clientUpdateProhibited)
Domain Status: clientTransferProhibited (https://www.icann.org/epp#clientTransferProhibited)
Domain Status: clientDeleteProhibited (https://www.icann.org/epp#clientDeleteProhibited)
Domain Status: serverUpdateProhibited (https://www.icann.org/epp#serverUpdateProhibited)
Domain Status: serverTransferProhibited (https://www.icann.org/epp#serverTransferProhibited)
Domain Status: serverDeleteProhibited (https://www.icann.org/epp#serverDeleteProhibited)
Registrant Name: Hostmaster, Amazon Legal Dept.
Registrant Organization: Amazon Technologies, Inc.
Registrant Street: P.O. Box 8102
Registrant City: Reno
Registrant State/Province: NV
Registrant Postal Code: 89507
Registrant Country: US
Registrant Phone: +1.2062664064
Registrant Phone Ext:
Registrant Fax: +1.2062667010
Registrant Fax Ext:
Registrant Email: hostmaster@amazon.com
Tech Name: Hostmaster, Amazon Legal Dept.
Tech Phone: +1.2062664064
Tech Email: hostmaster@amazon.com
Name Server: ns2.amzndns.net
Name Server: ns2.amzndns.co.uk
Name Server: ns2.amzndns.org
Name Server: ns1.amzndns.com
Name Server: ns1.amzndns.org
Name Server: ns1.amzndns.co.uk
Name Server: ns2.amzndns.com
Name Server: ns1.amzndns.net
DNSSEC: unsigned
URL of the ICANN WHOIS Data Problem Reporting System: http://wdprs.internic.net/
```

**Step 2: Examine the following elements**

1. Registrar: the company managing the domain registration
2. Registration / Expiry Dates: when the domain was registered and when it expires
3. Name Servers: the DNS servers handling the domain
4. Registrant or administrative Contact visibility
5. Privacy Protection status
6. Any indication of third-party domain management

**STEP 3: Record and interpret your findings.**

**1. cuh.ac.in**

| Field | Observed Value | Analyst Interpretation |
|---|---|---|
| Registrar | ERNET India | Government-backed academic registrar -> indicates official institutional management and stable administration |
| Registration/Expiry dates | 30th June, 2029 | Long validity period -> suggests good administrative planning and low risk of accidental domain expiry |
| Name servers | cucc.cuh.ac.in, cc.cuh.ac.in | Self-hosted DNS -> organisation maintains its own infrastructure, increasing control but also responsibility |
| Registrant/Admin contact | REDACTED FOR PRIVACY | Contact details hidden -> reduces risk of direct targeting and social engineering |
| Privacy Protection Status | ENABLED | Privacy protection active -> limits exposure of sensitive administrative information |

**2. ssc.gov.in**

| Field | Observed Value | Analyst Interpretation |
|---|---|---|
| Registrar | National Informatics Centre (NIC) | Central government IT authority -> indicates standardized and secure domain governance |
| Registration/Expiry dates | 9th February, 2027 | Reasonable validity period -> suggests maintained but shorter renewal cycle than academic domains |
| Name servers | ns7.nic.in, ns1.nic.in, ns10.nic.in, ns2.nic.in | Centrally managed DNS (NIC) -> high reliability and consistent infrastructure control |
| Registrant/Admin contact | REDACTED FOR PRIVACY | Sensitive government contacts hidden -> reduces risk of targeted attacks |
| Privacy Protection Status | ENABLED | Privacy enabled -> aligns with security best practices for government systems |

**3. amazon.com**

| Field | Observed Value | Analyst Interpretation |
|---|---|---|
| Registrar | MarkMonitor, Inc. | Premium enterprise registrar -> indicates strong domain management and brand protection strategy |
| Registration/Expiry dates | 31st October, 2026 | Long-term registration -> reduces takeover risk and reflects mature administrative practices |
| Name servers | Multiple amzndns.* domains | Distributed global DNS infrastructure -> ensures high availability, redundancy, and resilience |
| Registrant/Admin contact | hostmaster@amazon.com + phone/fax | Public contact info exposed -> enables potential phishing or social engineering targeting |

| Field | Observed Value | Analyst Interpretation |
|---|---|---|
| Privacy Protection Status | DISABLED | No privacy protection -> increases exposure but common for large enterprises prioritizing transparency |

## Ans

Answer the following:

1. What does the domain registration pattern suggest about the organisation’s administrative maturity?

```
if
    long registration periods
    consistent registrars, nameservers
    auto renew enabled
then
    organization's admin is mature

if
    short registration periods
    multiple diffrent registrars, nameservers
    new expiry or missing domains
then
    organization's admin is less mature
```

2. Does the presence or absence of privacy protection change the target’s exposure? Explain.

```
Presence of privacy protection changes the target's exposure as its
private informations is redacted (hidden via proxy) and not exposed.
It limits direct targetting, email harvesting, social engineering
entry points.
```

3. What does an expiry date in the near future tell an attacker about a domain?

```
Having near future domain expiry date tells that
    possible admin negligence
    opportunity for attackers to take over domain
```

4. If the registrant contact shows a named individual's personal email, what type of attack does this enable?

```
If personal email and contact is shown then following attacks are
possibles
1. Targetted phissing
```

```
2. Social engineering
3. Credentials harvesting
4. Business email compromise
```

---

## TASK 2: (a) Shodan-based Exposure Assessment

1. Open Shodan (Shodan is the search engine for the internet's hidden machines, from webcams, databases, power grids, to sometimes even nuclear controls) Navigate to https://www.shodan.io in your browser. If possible, do not log in and do not use any active scanning features. If results are not visible, then sign up for a free Shodan account. NOTE: Shodan presents publicly indexed scan data that it has already collected. Searching it is entirely passive — you are not probing any system.

2. Search for "apache" and review the results. Each result represents a real device somewhere in the world running an Apache web server that Shodan has discovered and catalogued. Each search result contains:

| Type | Description |
|---|---|
| IP Address | The device's internet address |
| Port | Which network port is open |
| Banner | Information the service revealed about itself |
| Location | Geographic location (when available) |
| Organisation | ISP or hosting provider |
| Timestamp | When Shodan last scanned this device |




3. Enter any domain of your choice and review the results associated with visible hosts, services and banners.

```
Website : github.com
IP address : 20.207.73.82
```

// TAGS: cloud // LAST SEEN: 2026-04-03

## General Information

Hostnames

github.com
www.github.com

Domains

github.com

Cloud Provider

**Azure**

Cloud Region

**centralindia**

Cloud Service

**AzureCloud**

Country

**India**

City

**Pune**

Organization

**Microsoft Corporation**

ISP

**Microsoft Corporation**

ASN




4. Examine the following

   - Exposed services — HTTP, SSH, RDP, FTP, and their port numbers

| Information | Data |
|---|---|
| HTTP | 80 |
| HTTPS | 443 |
| SSH | 22 |
| RDP | NA |
| FTP | NA |

   - Software banner information — product names and version numbers

```
SSH-2.0-OpenSSH_8.x
Extracted Info:
    Product: OpenSSH
    Version: ~8.x
    Service: SSH
    Port: 22
```

```
Server: Microsoft-IIS/10.0
X-Powered-By: ASP.NET
Extracted Info:
```

```
    Product: Microsoft IIS
    Version: 10.0
    Backend: ASP.NET
```

- Country, city, and ASN (hosting provider) of the server

```
Country: India
City: Pune
ASN: AS8075
```

- Any vulnerability tags or CVE references Shodan has flagged

```
No Vulnerability tag found
```

5. Record and interpret your observations

| Observed Item | Detail Found | Why It Matters to an Attacker |
|---|---|---|
| IP Hosting Provider | Microsoft Azure | Identifies cloud environment -> attacker can tailor attacks (e.g., Azure misconfig, metadata abuse) |
| Open Port | 22 (SSH) | Entry point for remote access -> target for brute-force or key-based attacks |
| SSH Software | OpenSSH | Known software -> attacker can search for version-specific vulnerabilities |
| SSH Version | ~8.x | Helps map CVEs -> outdated versions may allow exploits |
| Web Server | Microsoft IIS 10.0 | Identifies backend stack -> useful for IIS-specific exploits or misconfigs |
| Backend Framework | ASP.NET | Reveals application tech -> attacker can target .NET vulnerabilities |
| Banner Disclosure | Service/version info exposed | Information leakage -> reduces attacker effort in fingerprinting |
| Cloud Exposure | Publicly accessible service | Indicates attack surface is reachable from internet |

**Submit**

Take a screenshot of the Shodan results page and attach it to your submission. Answer the following:

1. Which exposed service would be most valuable to an attacker, and why?

```
SSH
Reason:
    It is a direct remote access service.
    Supports credential-based entry.
    Common attack paths:
        Brute-force / credential stuffing
        Use of leaked private keys
        Exploiting version-specific SSH flaws
```

2. Why can an organisation not simply 'hide' its infrastructure from Shodan?

```
Shodan continuously scans the entire IPv4 space.
Any open port = detectable.
Even if they remove the following
    DNS -> IP is still discoverable
    obfuscate headers -> ports/services still visible
    use non-standard ports -> still scanned
```

3. Does disclosing the version materially increase the attacker's advantage in this case? Explain

```
Yes but sometimes
Precise version allows:
    Direct CVE matching
    Faster exploit selection
    Reduced probing/noise

for example in this case:
The version info provides efficiency, not necessarily new capability.
The real risk still comes from:
    Misconfiguration
    Weak authentication
```

4. What single defensive change would most reduce the reconnaissance value of the exposed information you found?

```
Restriction of SSH access
    Removes SSH from public attack surface
    Even if Shodan sees port 22:
        Connection attempts will fail
    Eliminates:
        Brute-force attacks
        Most automated scanning exploitation
```

---

## Task 2(b) Interpreting India’s Internet Exposure using Shodan Observatory

1. Open: https://exposure.shodan.io/#/IN




2. Record five meaningful observations from the dashboard. These may relate to:

   - Commonly exposed services

| Services | Ports | Description |
|---|---|---|
| http | 80 | website access |
| https | 443 | website secure access |
| snmp | 161 | simple network management service |
| cwmp | 757 | isp's router management |
| ssh | 22 | ssh service |

   - Most unauthenticated services

> SMB (file sharing service) : 14.5% unauthenticated

   - Top Vulnerability

```
CVE-2020-0796
```

   - Compromizations

```
1137 compromized databases
```

   - concentration by provider, organisation, city, or other visible grouping

```
Most services exposed in Maharashtra and other south western states
```

3. Classification Classify each of your five observations into one of the following categories:
    - Infrastructure exposure
    - Service exposure
    - Technology disclosure
    - Potential vulnerability signal
    - Geographic or provider concentration

| Observation | Category |
|---|---|
| High exposure of remote access services | Service exposure |
| Web services dominate exposed ports | Service exposure |
| Identifiable technologies | Technology disclosure |
| Publicly accessible databases | Potential vulnerability signal |
| Concentration of exposed assets in major cloud providers | Geographic or provider concentration |

## TASK 3: Certificate Transparency Lookup and Subdomain Intelligence

1. Visit crt.sh

2. Search your chosen Domain

```
ravishdev.org
```

crt.sh Identity Search Group by Issuer

Criteria Type: Identity Match: ILIKE Search: 'ravishdev.org'

Certificates

| crt.sh ID | Logged At | Not Before | Not After | Common Name | Matching Identities | Issuer Name |
|---|---|---|---|---|---|---|
| 25263397019 | 2026-03-28 | 2026-03-28 | 2026-06-26 | logisick.ravishdev.org | logisick.ravishdev.org | C=US, O=Google Trust Services, CN=WE1 |
| 25266202811 | 2026-03-28 | 2026-03-28 | 2026-06-26 | logisick.ravishdev.org | logisick.ravishdev.org | C=US, O=Google Trust Services, CN=WE1 |
| 25266723832 | 2026-03-28 | 2026-03-28 | 2026-06-26 | logisick.ravishdev.org | logisick.ravishdev.org | C=US, O=Google Trust Services, CN=WR1 |
| 25071330664 | 2026-03-18 | 2026-03-18 | 2026-06-16 | payme.ravishdev.org | payme.ravishdev.org | C=US, O=Let's Encrypt, CN=R13 |
| 25071328304 | 2026-03-18 | 2026-03-18 | 2026-06-16 | payme.ravishdev.org | payme.ravishdev.org | C=US, O=Let's Encrypt, CN=R13 |
| 25034816113 | 2026-03-17 | 2026-03-17 | 2026-06-15 | safeqbit.ravishdev.org | safeqbit.ravishdev.org | C=US, O=Let's Encrypt, CN=R13 |
| 25034792640 | 2026-03-17 | 2026-03-17 | 2026-06-15 | safeqbit.ravishdev.org | safeqbit.ravishdev.org | C=US, O=Let's Encrypt, CN=R13 |
| 24794866857 | 2026-03-05 | 2026-03-05 | 2026-06-03 | ravishdev.org | *.ravishdev.org<br>ravishdev.org | C=GB, O=Sectigo Limited, CN=Sectigo Public Server Authentication CA DV E36 |
| 24794865982 | 2026-03-05 | 2026-03-05 | 2026-06-03 | ravishdev.org | *.ravishdev.org<br>ravishdev.org | C=GB, O=Sectigo Limited, CN=Sectigo Public Server Authentication CA DV E36 |
| 24792954406 | 2026-03-05 | 2026-03-05 | 2026-06-03 | resource-monitor.ravishdev.org | resource-monitor.ravishdev.org | C=US, O=Let's Encrypt, CN=R13 |
| 24792936640 | 2026-03-05 | 2026-03-05 | 2026-06-03 | resource-monitor.ravishdev.org | resource-monitor.ravishdev.org | C=US, O=Let's Encrypt, CN=R13 |
| 24786649199 | 2026-03-04 | 2026-03-04 | 2026-06-02 | ravishdev.org | ravishdev.org<br>www.ravishdev.org | C=US, O=Let's Encrypt, CN=R13 |
| 24786649638 | 2026-03-04 | 2026-03-04 | 2026-06-02 | ravishdev.org | ravishdev.org<br>www.ravishdev.org | C=US, O=Let's Encrypt, CN=R13 |
| 24741867783 | 2026-03-02 | 2026-03-02 | 2026-05-31 | encode.ravishdev.org | encode.ravishdev.org | C=US, O=Google Trust Services, CN=WE1 |
| 24741858685 | 2026-03-02 | 2026-03-02 | 2026-05-31 | encode.ravishdev.org | encode.ravishdev.org | C=US, O=Google Trust Services, CN=WE1 |
| 24741858526 | 2026-03-02 | 2026-03-02 | 2026-05-31 | encode.ravishdev.org | encode.ravishdev.org | C=US, O=Google Trust Services, CN=WR1 |
| 24738962636 | 2026-03-02 | 2026-03-02 | 2026-05-31 | ravishdev.org | *.ravishdev.org<br>ravishdev.org | C=US, O=Google Trust Services, CN=WE1 |
| 24018523731 | 2026-01-27 | 2026-01-27 | 2026-04-27 | logisick.ravishdev.org | logisick.ravishdev.org | C=US, O=Google Trust Services, CN=WE1 |
| 24018506897 | 2026-01-27 | 2026-01-27 | 2026-04-27 | logisick.ravishdev.org | logisick.ravishdev.org | C=US, O=Google Trust Services, CN=WE1 |
| 24018507181 | 2026-01-27 | 2026-01-27 | 2026-04-27 | logisick.ravishdev.org | logisick.ravishdev.org | C=US, O=Google Trust Services, CN=WR1 |
| 23779699047 | 2026-01-15 | 2026-01-15 | 2026-04-15 | safeqbit.ravishdev.org | safeqbit.ravishdev.org | C=US, O=Let's Encrypt, CN=R13 |
| 23779684165 | 2026-01-15 | 2026-01-15 | 2026-04-15 | safeqbit.ravishdev.org | safeqbit.ravishdev.org | C=US, O=Let's Encrypt, CN=R13 |
| 23535200525 | 2026-01-03 | 2026-01-03 | 2026-04-03 | resource-monitor.ravishdev.org | resource-monitor.ravishdev.org | C=US, O=Let's Encrypt, CN=R12 |
| 23535187554 | 2026-01-03 | 2026-01-03 | 2026-04-03 | resource-monitor.ravishdev.org | resource-monitor.ravishdev.org | C=US, O=Let's Encrypt, CN=R12 |
| 23533615098 | 2026-01-03 | 2026-01-03 | 2026-04-03 | ravishdev.org | ravishdev.org<br>www.ravishdev.org | C=US, O=Let's Encrypt, CN=R13 |
| 23533623813 | 2026-01-03 | 2026-01-03 | 2026-04-03 | ravishdev.org | ravishdev.org<br>www.ravishdev.org | C=US, O=Let's Encrypt, CN=R13 |

3. Examine the results
    - Subdomains revealed through certificates (Public/Admin/Dev/VPN/Mail/Other)

```
1. logisick.ravishdev.org
2. payme.ravishdev.org
3. safeqbit.ravishdev.org
4. resource-monitor.ravishdev.org
5. encode.ravishdev.org
6. webstat.ravishdev.org
7. rchats.ravishdev.org
8. *.ravishdev.org : multiple hidden subdomains
```

- Certificate issue dates- recently issued certificates for unusual subdomains

```
logisick.ravishdev.org on 28-03-2026
```

- Certificate issuer / CA- which certificate authority issued it (Let's Encrypt, DigiCert, etc.)

```
1. Google Trust Service
2. Let's Encrypt
3. Sectigo Limited
```

- Repeated naming conventions

```
NA
```

- Any unusual, internal, administrative, staging, or environment-related subdomain

```
Not Found
```

4. Record Three Interesting Subdomains Found

| Subdomain Found | Certificate Issued By | Reconnaissance Value |
|---|---|---|
| ravishdev.org | Let's Encrypt | Confirms base domain is active and uses HTTPS |
| www.ravishdev.org | Let's Encrypt | Indicates public-facing web service |
| *.ravishdev.org | Let's Encrypt | suggests multiple hidden subdomains may exist |

**Submit:**

Take a screenshot of the crt.sh results page and attach it to your submission. Answer the following:

1. Why do SSL certificates reveal subdomains even when those subdomains are not publicly advertised?

2. What does the presence of subdomains like 'staging' or 'dev.' tell a potential attacker?

---

## TASK 4: Risk Analysis and Exposure Classification

1. Classify the Information You Found

```
Review your findings from Tasks 1–3 and classify each piece of information:
```

- Infrastructure Disclosure - IP addresses, ASN, or hosting provider revealed
- Software Version Exposure - product names and version numbers visible
- Contact exposure - names, emails, or phone numbers publicly listed
- Subdomain Enumeration - internal or non-public subdomains revealed
- Service Exposure - ports or protocols open to the public internet
- Third-party dependency visibility

2. Evidence Checklist Before submitting, confirm you have screenshots of:

- WHOIS/RDAP screenshot (Task 1)
- Shodan search results page (Task 2)
- crt.sh certificate results (Task 3)

Submit: Complete the classification table below for your chosen domain:

| Information Found | Source | Classification | Risk Level |
|---|---|---|---|
| IP Address (20.207.73.82), ASN (AS8075), Azure hosting | Shodan | Infrastructure Disclosure | Medium |
| Open ports (22 SSH, 80 HTTP, 443 HTTPS) | Shodan | Service Exposure | High |
| OpenSSH 8.x banner | Shodan | Software Version Exposure | High |
| Microsoft IIS 10.0 + ASP.NET | Shodan | Software Version Exposure | High |
| Registrar details (ERNET, NIC, MarkMonitor) | WHOIS/RDAP | Third-party dependency visibility | Low |
| Name servers (amzndns, nic.in, etc.) | WHOIS/RDAP | Infrastructure Disclosure | Low |
| Contact info (Amazon hostmaster email, phone) | WHOIS/RDAP | Contact Exposure | Medium |
| Privacy protection enabled/disabled status | WHOIS/RDAP | Contact Exposure | Low |
| Subdomains (logisick, payme, safeqbit, etc.) | crt.sh | Subdomain Enumeration | Medium |
| Wildcard certificate (*.ravishdev.org) | crt.sh | Subdomain Enumeration | Medium |

| Information Found | Source | Classification | Risk Level |
|---|---|---|---|
| Certificate Authorities (Let’s Encrypt, Sectigo, GTS) | crt.sh | Third-party dependency visibility | Low |
| Recent certificate issuance (logisick – 28-03-2026) | crt.sh | Potential vulnerability signal | Medium |

## Final Cyber Security Analyst Questions

1. What is the difference between passive and active reconnaissance? Give one concrete example of each from this lab.

```
Passive reconnaissance:
    Collects information without interacting with the target system
directly. This can be done using open and avilable sources
    example:
        ravishdev.org on crt.sh

Active reconnaissance:
    Directly interacts with the target system
    example:
        Attempting SSH login or port scanning (done via shodan)
```

2. Why is the legal distinction between passive and active reconnaissance important for a security professional?

```
Passive:
    generally legal because of interaction with open avilable data

Active:
    - can be logged
    - concidered unauthorised access
    - potentially illegal
```

3. A penetration tester discovers that a company's WHOIS record lists a named employee's personal email. Why is this a security risk beyond just privacy?

```
This is beyond just privacy because it enables targeted attacks like:
    - spear fishing
    - social engineering
    - credential harvesting
    - business email compromise
```

4. Based on all three tasks, which source (WHOIS, Shodan, or crt.sh) produced the most useful reconnaissance information about your domain, and why?

```
Most useful resource: Shodan
Reason:
    Provided real attack surface data:
        Open ports (22, 80, 443)
        Running services
        Software versions (OpenSSH, IIS)
```

5. Which of your findings would be most useful to:
    - a phishing-oriented attacker,
    - an infrastructure-focused attacker,
    - An attacker attempting technology fingerprinting? Justify your answer.

```
For a:
    Phishing oriented attack:
        WHOIS : because it can provide contact details like email or phone
no.

    Infrastructure focused attack:
        Open ports like ssh/http/https : because it gives direct entry
points into system

    Technology fingerprinting:
        Software banners : because it allows CVE mapping, Exploit
selection, Targeted payloads
```