

Introduction to Drones - 22AIE448

3D Mapping using a Monocular Camera and Control by Visual-Inertial Odometry (VIO)

Group CD2 : Ravishanmugam K, Ishwarya Murugesan, Aparna Bharani, Cibikumar B, Akhilan S

School of Artificial Intelligence, Amrita Vishwa Vidyapeetham

Toy model 3 - Model 2, Part 3 : control with limits - MPC, QP, receding horizon, apply to the drone (blocks 7 to 10)

Run M2_1 and M2_2 first (they create dmdc_model.mat).

```
clearvars
clear all
ready = true;
PUBLISH = not(ready); % make this PUBLISH = ready; to export the file as PDF
```

```
clearvars -except PUBLISH ready
```

Block 7 - Model Predictive Control

LQR has no limits. A real drone has: thrust between 5 and 25 N, max_velocity = 1 m/s, a maximum tilt for the camera. MPC plans only N steps ahead and writes the limits into the problem:

$$\min_{u_0, \dots, u_{N-1}} \sum_{k=0}^{N-1} (x_k^T Q x_k + u_k^T R u_k) + x_N^T P_f x_N$$

$$\text{subject to } x_{k+1} = Ax_k + Bu_k, \quad x_0 = \text{measured state}, \quad u_{\min} \leq u_k \leq u_{\max}, \quad |Cx_k| \leq x_{\max} \quad \rightarrow (M2.12)$$

Why the terminal weight is the DARE matrix, $P_f = P$: $x_N^T P x_N$ is exactly the cost of the rest of the flight when no limit is active after step N . So when no limit is active, MPC gives **exactly** the LQR answer.

Block 8 - Quadratic Program

Prediction. Apply the model again and again: $x_1 = Ax_0 + Bu_0$, $x_2 = A^2x_0 + ABu_0 + Bu_1$, ...

$$\mathbf{X} = S_x x_0 + S_u \mathbf{U}, \quad S_x = \begin{bmatrix} A \\ A^2 \\ \vdots \\ A^N \end{bmatrix}, \quad S_u = \begin{bmatrix} B & 0 & \dots & 0 \\ AB & B & \dots & 0 \\ \vdots & & \ddots & \vdots \\ A^{N-1}B & \dots & AB & B \end{bmatrix} \quad \rightarrow (M2.13)$$

Cost. Substitute $\mathbf{X}$ and drop the part that does not depend on $\mathbf{U}$:

$$\min_{\mathbf{U}} \frac{1}{2} \mathbf{U}^T H \mathbf{U} + f^T \mathbf{U}, \quad H = 2(S_u^T \bar{Q} S_u + \bar{R}), \quad f = 2S_u^T \bar{Q} S_x x_0 \quad \rightarrow (M2.14)$$

$$\text{s.t. } G \mathbf{U} \leq h, \quad A_{eq} \mathbf{U} = b_{eq} \quad \rightarrow (M2.15)$$

with $\bar{Q} = \text{diag}(Q, \dots, Q, P_f)$, $\bar{R} = \text{diag}(R, \dots, R)$. H is positive definite: a bowl with one bottom inside a fence, so the answer is unique.

Toy example by hand. $a = 1.1$, $b = 0.5$, $q = r = 1$, $N = 2$, $P_f = 3.1215$, $x_0 = 1$:

$$S_x = \begin{bmatrix} 1.1 \\ 1.21 \end{bmatrix}, \quad S_u = \begin{bmatrix} 0.5 & 0 \\ 0.55 & 0.5 \end{bmatrix}, \quad H = \begin{bmatrix} 4.3885 & 1.7168 \\ 1.7168 & 3.5607 \end{bmatrix}, \quad f = \begin{bmatrix} 5.2547 \\ 3.7770 \end{bmatrix}$$

```
a = 1.1; b = 0.5; Pf = 3.12146; x0 = 1;
Sx = [a; a^2];
Su = [b 0; a*b b];
Qbar = diag([1 Pf]); Rbar = eye(2);
H = 2*(Su'*Qbar*Su + Rbar)
```

```
H = 2x2
    4.3885    1.7168
    1.7168    3.5607
```

```
f = 2*Su'*Qbar*Sx*x0
```

```
f = 2x1
    5.2547
    3.7770
```

(i) No limits: $U^* = -H^{-1}f$. The first move equals the LQR move $-Kx_0 = -0.9643$.

```
U_free = (-H\f)'
```

```
U_free = 1x2
   -0.9643   -0.5958
```

(ii) With limits, $|u_k| \leq 0.5$: both moves sit on the limit.

```
G = [eye(2); -eye(2)]; h = 0.5*ones(4,1);
U_limited = DroneLib.qp(H, f, G, h)'
```

```
U_limited = 1x2
   -0.5000   -0.5000
```

(iii) With an equality that forces $x_2 = 0$: $\begin{bmatrix} 0.55 & 0.5 \end{bmatrix} U = -1.21$.

```
U_equality = DroneLib.qp(H, f, zeros(0,2), zeros(0,1), [a*b b], -a^2)'
```

```
U_equality = 1x2
   -1.3057   -0.9837
```

```
check_x2 = a^2*x0 + [a*b b]*U_equality'
```

```
check_x2 = 0
```

The drone MPC problem

$N = 25$ (1 s look-ahead), $5 \leq T \leq 25$ N, $|\tau_{x,y}| \leq 0.3$ N m, $|\tau_z| \leq 0.05$ N m, $|v_i| \leq 1$ m/s (max_velocity) and roll, pitch $\leq 20^\circ$.

```
clearvars -except PUBLISH ready
load('dmdc_model.mat');           % A, B (learned), P (drone), P_dare, K, Q, R, dt,
nSub, u_trim
N = 25;
u_min = [5 - P.m*P.g0; -0.3; -0.3; -0.05];
u_max = [25 - P.m*P.g0; 0.3; 0.3; 0.05];
C = zeros(5,12); C(1,4) = 1; C(2,5) = 1; C(3,6) = 1; C(4,7) = 1; C(5,8) = 1;
x_max = [1; 1; 1; 0.35; 0.35];
mpc = DroneLib.mpc_build(A, B, Q, R, P_dare, N, u_min, u_max, C, x_max);
decision_variables = size(mpc.H, 1)
```

```
decision_variables = 100
```

```
inequality_constraints = size(mpc.G, 1)
```

```
inequality_constraints = 450
```

Small offset (5 cm): no limit is active, so MPC = LQR.

```
x_small = [0.05; -0.05; 0.05; zeros(9,1)];
u_mpc = DroneLib.mpc_solve(mpc, x_small)'
```

```
u_mpc = 1x4
    -0.4557    -0.0138    -0.0137    -0.0004
```

```
u_lqr = (-K*x_small)'
```

```
u_lqr = 1x4
    -0.4557    -0.0138    -0.0137    -0.0004
```

Large offset (2 m): LQR would ask for more than allowed, MPC respects every limit.

```
x_big = [0; 0; -2; zeros(9,1)];
u_lqr_big = (-K*x_big)'
```

```
u_lqr_big = 1x4
    18.0771    -0.0007    -0.0015     0.0082
```

```
[u_mpc_big, U] = DroneLib.mpc_solve(mpc, x_big);
u_mpc_big = u_mpc_big'
```

```
u_mpc_big = 1x4
    10.2850    -0.0018    -0.0002     0.0172
```

```
X_plan = reshape(mpc.Sx*x_big + mpc.Su*U, 12, N);
planned_max_vz = max(abs(X_plan(6,:)))
```

```
planned_max_vz = 1.0000
```

Block 9 - Receding horizon

$$\mathbf{U}^*(x_k) = [u_0^*, u_1^*, \dots, u_{N-1}^*] \Rightarrow \text{apply only } u_0^*, \text{ measure } x_{k+1}, \text{ solve again} \rightarrow (M2.16)$$

Plan 1 s ahead, act for 40 ms, look again. Re-solving from fresh measurements turns the plan into feedback.

```
x0 = [1.5; -1.0; -1.2; zeros(9,1)];
Kn = 200; t = (0:Kn)*dt;
Xm = zeros(12, Kn+1); Xl = Xm; Xm(:,1) = x0; Xl(:,1) = x0; tsolve = zeros(1,Kn);
for k = 1:Kn
    tic; um = DroneLib.mpc_solve(mpc, Xm(:,k)); tsolve(k) = toc;
    ul = min(max(-K*Xl(:,k), u_min), u_max); % LQR, clipped to the same
input limits
    Xm(:,k+1) = A*Xm(:,k) + B*um;
    Xl(:,k+1) = A*Xl(:,k) + B*ul;
end
max_speed_MPC = max(abs(Xm(4:6,:)), [], 'all')
```

```
max_speed_MPC = 1.0000
```


```
max_speed_LQR = max(abs(Xl(4:6,:)), [], 'all')
```

```
max_speed_LQR = 1.1722
```

```
median_solve_time_ms = 1000*median(tsolve) % budget: 40 ms per sample
```

```
median_solve_time_ms = 2.8670
```

```
figure
plot(t, max(abs(Xm(4:6,:))), t, max(abs(Xl(4:6,:))), '--', LineWidth=1.5); hold on
yline(1, 'k:', "max\_velocity"); hold off; grid on
xlabel("t [s]"); ylabel("max |v_i| [m/s]"); legend("MPC", "LQR (clipped)")
title("Only MPC keeps the speed limit")
```



Block 10 - Apply to the drone

The controllers work with deviations, the motors need absolute values:

$$u_k = u_{trim} + \begin{cases} u_0^* & \text{(MPC)} \\ -Kx_k & \text{(LQR)} \end{cases} = \begin{bmatrix} T_k \\ \tau_k \end{bmatrix}, \quad f = \Gamma^{-1}u_k, \quad \Omega_i = \sqrt{f_i k_f} \quad \rightarrow (M2.17, M2.18)$$

One sample by hand: the drone is at $[1.5, -1.0, 0.8]$ m, at rest; the target is $[0, 0, 2]$.

```
x_world = DroneLib.pack(P.p_hover + [1.5; -1.0; -1.2], zeros(3,1), eye(3),
zeros(3,1));
xd = DroneLib.to_dev(x_world, P.p_hover);
du = DroneLib.mpc_solve(mpc, xd);
u = u_trim + du;
[Omega, f] = DroneLib.mixer(u, P);
u_abs = u'
```

```
u_abs = 1x4
    25.0000    -0.2789    -0.3000     0.0019
```

```
f_rotors = f'
```

```
f_rotors = 1x4
     7.1147     5.3271     6.5391     6.0191
```

```
Omega_rad_s = Omega'
```

```
Omega_rad_s = 1x4
912.2875 789.4006 874.6073 839.1083
```


The real test: the **nonlinear** drone with wind and sensor noise, flown by controllers that were designed only on the model learned from data.

```
figure
rng(10);
Kn = 250; t = (0:Kn)*dt; names = ["MPC", "LQR"];
for c = 1:2
    x = x_world; Xw = zeros(18, Kn+1); Xw(:,1) = x; Om = zeros(4, Kn);
    for k = 1:Kn
        xm = DroneLib.to_dev(x, P.p_hover) + [0.01*ones(3,1); 0.02*ones(3,1);
0.005*ones(3,1); 0.01*ones(3,1)].*randn(12,1);
        if c == 1
            du = DroneLib.mpc_solve(mpc, xm);
        else
            du = min(max(-K*xm, u_min), u_max);
        end
        [Om(:,k), ~, u_app] = DroneLib.mixer(u_trim + du, P);
        d = [0.2*randn(3,1); 5e-4*randn(3,1)];
        for j = 1:nSub, x = DroneLib.rk4(x, u_app, dt/nSub, P, d); end
        Xw(:,k+1) = x;
    end
    fprintf("%s : max |v| = %.3f m/s, error at 10 s = %.3f m, motors %.0f - %.0f
rad/s\n", names(c), ...
        max(abs(Xw(4:6,:))), [], 'all'), norm(Xw(1:3,end) - P.p_hover), min(Om(:)),
max(Om(:)));
    plot3(Xw(1,:), Xw(2,:), Xw(3,:), LineWidth=1.5); hold on
end
```

```
MPC : max |v| = 0.994 m/s, error at 10 s = 0.015 m, motors 584 - 913 rad/s
LQR : max |v| = 1.118 m/s, error at 10 s = 0.031 m, motors 613 - 911 rad/s
```

```
plot3(0, 0, 2, 'kp', MarkerSize=14, MarkerFaceColor='y'); hold off
grid on; axis equal; view(35, 25); xlabel("x [m]"); ylabel("y [m]"); zlabel("z [m]")
legend("MPC", "LQR (clipped)", "setpoint"); title("Nonlinear drone flown with
controllers learned from data")
```

Nonlinear drone flown with controllers learned from data



In the real drone: the measured state x_k comes from the EKF of Model 1 (/ap/v1/pose/filtered and /ap/v1/twist/filtered), the command goes through the same motor mixer, and new logs can be fed back into M2_1 to re-learn A, B .

```
if(PUBLISH == ready)
    mlxfile = matlab.desktop.editor.getActive().Filename;
    [folder, name, ext] = fileparts(mlxfile);
    outfilepdf = fullfile(folder, 'pdf', [name, ext, '.pdf']);
    export(mlxfile, outfilepdf);
    if ispc
        winopen(outfilepdf);
    elseif ismac
        system(['open ' char(outfilepdf)]);
    else
        system("env -u LD_LIBRARY_PATH xdg-open '" + outfilepdf + "' &");
    end
end
```