Your first database

In Ep 02 you saw what a database is, set up MySQL Workbench and made a database called **shop**. Here is every step in one place, so you can do it yourself.

Database
A place that keeps your tables: your orders, customers, products and all of it.

SQL
The language the database understands. You ask for all London orders, it sends them straight back.

MySQL Workbench
The app where you type your SQL. Free.

MySQL Server
The part that actually stores your data. Workbench talks to it.

Set it up

about 15 minutes · free

1. **Google "MySQL downloads" and open the official site**
   It's `dev.mysql.com/downloads`. Skip download sites you don't know.

2. **Grab MySQL Workbench and MySQL Server**
   Windows: pick **MySQL Installer for Windows**. It brings both in one go (that's what I used in the video).
   Mac: download **MySQL Community Server** and **MySQL Workbench**, one after the other. Pick the macOS file for your Mac: ARM for M1 to M4 chips, x86 for Intel.

3. **It asks you to log in. Don't bother**
   Scroll down and click **"No thanks, just start my download."**

4. **Install both**
   Open the file you downloaded. On Windows, choose **Custom**, add MySQL Server and MySQL Workbench, then click Next and Execute until it's done.

5. **Set a password. Write it down**
   The installer asks for a **root password**. Write it somewhere safe: Workbench asks for it every time it connects.

6. **Open MySQL Workbench**
   Click the **Local instance** box on the home screen, type your root password, and a blank Query tab opens. That's where you type.

Workbench says it can't connect? The Server isn't running. On Windows, open **Services** and start `MySQL80`. On a Mac, open **System Settings**, find **MySQL** and click Start.

EP 02 · BUILD IT

Type these in the Query tab

Three lines, one database

To run a line, click in it and press **Ctrl + Enter** (**Cmd + Return** on a Mac), or click the lightning icon. The same three lines are in `ep02_shop.sql`.

```
1  CREATE DATABASE shop;
```

Makes an empty database called shop. That's it, you've made a database.

```
✓ create database shop · 1 row(s) affected
```

```
2  SHOW DATABASES;
```

Lists every database. There it is: **shop** in the list, next to MySQL's own four (information_schema, mysql, performance_schema, sys). Leave those alone.

```
3  USE shop;
```

Tells SQL which database to work in. You might have lots of databases; from now on everything you make goes inside shop.

```
✓ use shop · 0 row(s) affected
```



The little semicolon is SQL's full stop. It tells SQL where one command ends and the next one starts. End every command with it.

Check yourself

answers right under each one

1. You run `CREATE DATABASE shop;` a second time. What happens?

An error: *Can't create database 'shop'; database exists*. Nothing is lost. shop is already there, so you don't need to make it again.

2. You type two commands on one line and leave out the semicolon between them. What happens?

Error 1064. SQL can't tell where the first command ends. Put a `;` after each one.

3. Which line do you run so that your next table is made inside shop?

`USE shop;`

On Friday · Ep 03 · Your first table

We make our first table inside the shop database.

Comment **WEEK1** on the reel if a friend needs these files.