# Your first database

In Ep 02 you saw what a database is, set up MySQL Workbench and made a database called **shop**. Here is every step in one place, so you can do it yourself.

**Database**
A place that keeps your tables: your orders, customers, products and all of it.

**SQL**
The language the database understands. You ask for all London orders, it sends them straight back.

**MySQL Workbench**
The app where you type your SQL. Free.

**MySQL Server**
The part that actually stores your data. Workbench talks to it.

## Set it up

about 15 minutes · free

1. **Google "MySQL downloads" and open the official site**
   It's `dev.mysql.com/downloads`. Skip download sites you don't know.

2. **Grab MySQL Workbench and MySQL Server**
   **Windows:** pick **MySQL Installer for Windows**. It brings both in one go (that's what I used in the video).
   **Mac:** download **MySQL Community Server** and **MySQL Workbench**, one after the other. Pick the macOS file for your Mac: ARM for M1 to M4 chips, x86 for Intel.

3. **It asks you to log in. Don't bother**
   Scroll down and click **"No thanks, just start my download."**

4. **Install both**
   Open the file you downloaded. On Windows, choose **Custom**, add MySQL Server and MySQL Workbench, then click Next and Execute until it's done.

5. **Set a password. Write it down**
   The installer asks for a **root password**. Write it somewhere safe: Workbench asks for it every time it connects.

6. **Open MySQL Workbench**
   Click the **Local instance** box on the home screen, type your root password, and a blank Query tab opens. That's where you type.

**Workbench says it can't connect?** The Server isn't running. On Windows, open **Services** and start `MySQL80`. On a Mac, open **System Settings**, find **MySQL** and click Start.

EP 02 · BUILD IT

Type these in the Query tab

# Three lines, one database

To run a line, click in it and press **Ctrl + Enter** (**Cmd + Return** on a Mac), or click the lightning icon. The same three lines are in `ep02_shop.sql`.

```
1  CREATE DATABASE shop;
```

**Makes an empty database called shop.** That's it, you've made a database.

`✓ create database shop · 1 row(s) affected`

```
2  SHOW DATABASES;
```

**Lists every database.** There it is: **shop** in the list, next to MySQL's own four (information_schema, mysql, performance_schema, sys). Leave those alone.

```
3  USE shop;
```

**Tells SQL which database to work in.** You might have lots of databases; from now on everything you make goes inside shop.

`✓ use shop · 0 row(s) affected`



**The little semicolon is SQL's full stop.** It tells SQL where one command ends and the next one starts. End every command with it.

## Check yourself

answers right under each one

**1. You run `CREATE DATABASE shop;` a second time. What happens?**

An error: *Can't create database 'shop'; database exists*. Nothing is lost. shop is already there, so you don't need to make it again.

**2. You type two commands on one line and leave out the semicolon between them. What happens?**

Error 1064. SQL can't tell where the first command ends. Put a `;` after each one.

**3. Which line do you run so that your next table is made inside shop?**

`USE shop;`

### On Friday · Ep 03 · Your first table

We make our first table inside the shop database.

`week1_orders.sql` already builds the 40 orders from Ep 01 as a table inside shop, if you want a head start.

Comment **WEEK1** on the reel if a friend needs these files.