Your first table

In Ep 03 you made a table called **orders** inside the shop database, filled it with three orders and looked at it. Here is every line, with what each part means, so you can type along.

Table
Like an Excel sheet: column names on the top, one order in each row.

Column
Each column gets two things: a name, and what kind of value goes in.

Row
One order. Three orders means three rows.

PRIMARY KEY
Like the roll number on a marksheet: every row gets a different one.

Before step 1 `make sure you're in shop`

```
1  USE shop;
```

Tells SQL which database you are in. Click your connection in Workbench, type it and run it.

`✓ use shop · 0 row(s) affected`

Step 1 · make the table `CREATE TABLE`

```
CREATE TABLE orders (
  order_id INT PRIMARY KEY,
  city VARCHAR(40),
  amount DECIMAL(10,2)
);
```

Type CREATE TABLE, then its name, orders, and open the bracket. Everything inside the bracket is a column: its name, then what kind of value goes in.

`order_id INT`
Whole numbers, like 1, 2 or 1001. **PRIMARY KEY** means every order gets a different ID.

`city VARCHAR(40)`
Just text, and up to 40 letters.

`amount DECIMAL(10,2)`
Money. The 2 means 2 numbers after the point, so 12.99 stays 12.99. `DEC(10,2)` works too.

A comma after every column, but not after the last one. Then close the bracket, add the semicolon, and run it.

It says 0 row(s) affected. Don't worry, that's correct. The table is ready, it's just empty right now. Click **Schemas** on the left, press **refresh**, and you'll see **orders** inside shop, under Tables. Click it and the Information box at the bottom shows its 3 columns.

Step 2 · fill it INSERT INTO

```sql
INSERT INTO orders VALUES
(1001, 'london', 12.99),
(1002, 'leeds', 4.50),
(1003, 'hatfield', 21.50);
```

Each bracket you write is one order. The values go in the same order as the columns: first ID, then the city, then the amount. Words go inside single quotes, numbers don't.

✓ 3 row(s) affected · so 3 orders are in

Step 3 · see it SELECT

```sql
SELECT * FROM orders;
```

Star means show every column. Run it, and here is your table:

order_id	city	amount
1001	london	12.99
1002	leeds	4.50
1003	hatfield	21.50

Break it on purpose

```sql
INSERT INTO orders VALUES (1001, 'london', 11.00);
```

Order 1001 again gives an error: a duplicate entry. Remember the roll number rule? SQL doesn't let two orders have the same ID.

✗ Error Code: 1062. Duplicate entry '1001' for key 'orders.PRIMARY'

Got an error? Don't panic it's usually one of these

1 · A missing quote
`'london` needs its closing '. Words start and end with a single quote.

2 · An extra comma
`amount DECIMAL(10,2),` No comma after the last column.

3 · Made the table twice
Table 'orders' already exists (Error 1050). It's already made, so carry on with step 2.

Your turn

Add order **1004, Bristol, 15 pounds**, then run `SELECT * FROM orders;` again. Have you got 4 rows? Then you've made your first table.

Next: **Week 2 starts Monday**. Comment **WEEK1** on the reel if a friend needs these files.

Answer: INSERT INTO orders VALUES (1004, 'Bristol', 15.00); then SELECT * FROM orders; gives 4 rows, with 1004 at the bottom.