ULTRAVIOLETTE

SUPER STREET SPEC SHEET

30 KW	155 KM/H	100 NM	323 KM
PEAK POWER	MAX SPEED	PEAK MOTOR TORQUE	RANGE (IDC)



DESIGN

AERO SURFACES

LASER



Afterburner Yellow

LASER



Turbo Red

SHADOW



Cosmic Black

AIRSTRIKE



Stellar White

F SERIES - JET INSPIRED	DYNAMIC, STREET-ORIENTED	PARALLAX & RADAR
DESIGN SERIES	STANCE	CONSOLE THEMES

ULTRAVIOLETTE

SUPER STREET SPEC SHEET

	SUPERSTREET	SUPERSTREET RECON
PERFORMANCE		
PEAK POWER	27 kW (36.2 hp)	30 kW (40.2 hp)
PEAK TORQUE	90 Nm	100 Nm
MAX SPEED	155 km/h	155 km/h
ACCELERATION (0-60 KMPH)	2.9 sec	2.8 sec
ACCELERATION (0-100 KMPH)	7.8 sec	7.7 sec
DYNAMIC REGENERATIVE BRAKING	Included	Included
LEVELS OF REGENERATIVE BRAKING	3 levels included 10 levels optional	10 levels
RIDE MODES	Glide, Combat, Ballistic	Glide, Combat, Ballistic
RANGE ESTIMATES		
RANGE (IDC EST.)	211 km	323 km
RANGE GLIDE (AVG. 40 WH/KM)	183 km	266 km
RANGE COMBAT (AVG. 52 WH/KM)	144 km	209 km
RANGE BALLISTIC (AVG. 60 WH/KM)	128 km	186 km
SMART TECH		
VIOLETTE A.I.	Optional	Optional
DELTA WATCH	Optional	Optional
LOCKDOWN	Optional	Optional
ANTI-COLLISION WARNING SYSTEM	Optional	Optional
CRASH ALERT	Optional	Optional
DAILY RIDE ANALYTICS	Optional	Optional
CONTROL CENTER	Multi-function 5" TFT display with tactile input switch console (L+R)	Multi-function 5" TFT display with tactile input switch console (L+R)
OPERATING SYSTEM	UV Automotive Linux OS	UV Automotive Linux OS

ULTRAVIOLETTE

SUPER STREET SPEC SHEET

	SUPERSTREET	SUPERSTREET RECON
SAFETY		
	Auto dimming LED Headlight with Ultra-V position lamp	Auto dimming LED Headlight with Ultra-V position lamp
	Dual LED tail light assembly with central brake light	Dual LED tail light assembly with central brake light
	Front and Rear LED Hazard Lights	Front and Rear LED Hazard Lights
	Sidestand Sensor	Sidestand Sensor
TRACTION CONTROL	Optional	4 levels
HILL HOLD	Included	Included
ABS	Mono & Dual channel	Mono & Dual channel
D.S.C - DYNAMIC STABILITY CONTROL	Included	Included
UTILITY		
CHARGE LIMIT	Included	Included
PARK ASSIST	Included	Included
FIND MY F77	Included	Included
DEEP SLEEP	Included	Included
TPMS	Optional	Optional
BATTERY SYSTEM		
BATTERY PACK	SRB7	SRB10
ENERGY CAPACITY	7.1 kWh	10.3 kWh
BMS & SAFETY PROTOCOLS	Battery Management System with Patented 5-level Safety System - Mechanical, Thermal, Electrical, Electronic & Software Protection	Battery Management System with Patented 5-level Safety System - Mechanical, Thermal, Electrical, Electronic & Software Protection
ENCLOSURE	All-Aluminum IP67-rated Enclosure	All-Aluminum IP67-rated Enclosure

ULTRAVIOLETTE

SUPER STREET SPEC SHEET

	SUPERSTREET	SUPERSTREET RECON
BATTERY & DRIVETRAIN WARRANTY		
UV CARE	3 years or 60,000 km included	--
UV CARE PLUS	5 years or 1,00,000 km optional	5 years or 1,00,000 km included
UV CARE MAX	N/A	8 years or 8,00,000 km optional
VEHICLE WARRANTY		
STANDARD WARRANTY (VEHICLE)	3 years or 30,000km*	3 years or 30,000km*
CHARGING		
CHARGING PORT	IEC 62196-6	IEC 62196-6
UV SUPERNOVA PLUS (12KW DC FAST CHARGING NETWORK)	Compatible 20% - 80% in 45 min	Compatible 20% - 80% in 60 min
UVLYNC INTERFACE (COMPATIBLE WITH TYPE 2 AC CAR CHARGING NETWORK)	Optional	Optional
STANDARD CHARGER	Included	Included
CHARGE RATE	Up to 35 km of range per hour of charge 20% - 80% in 3 hrs	Up to 35 km of range per hour of charge 20% - 80% in 5 hrs
BOOST CHARGER	Optional	Optional
CHARGE RATE	Up to 75 km of range per hour of charge 20% - 80% in 1.5 hrs	Up to 75 km of range per hour of charge 20% - 80% in 2.5 hrs
DRIVETRAIN		
MOTOR	Permanent Magnet AC Motor	Permanent Magnet AC Motor
THROTTLE CONTROL	Ride-by-wire	Ride-by-wire

ULTRAVIOLETTE

SUPER STREET SPEC SHEET

	SUPERSTREET	SUPERSTREET RECON
MECHANICAL		
FRAME	Steel Trellis with Aluminium Bulk Head	Steel Trellis with Aluminium Bulk Head
FRONT SUSPENSION	Upside-down Telescopic fork with a diameter of 41 mm. Preload adjustable	Upside-down Telescopic fork with a diameter of 41 mm. Preload adjustable
REAR SUSPENSION	Monoshock - preload adjustable	Monoshock - preload adjustable
BRAKE SYSTEM	Hydraulic disc brakes with dual-channel BOSCH ABS	Hydraulic disc brakes with dual-channel BOSCH ABS
BRAKE CALIPERS	Front: Fixed 4-Radial Piston Type Rear: Single Piston Floating Caliper Type	Front: Fixed 4-Radial Piston Type Rear: Single Piston Floating Caliper Type
BRAKE ROTOR	Front: 320mm disc Rear: 230mm disc	Front: 320mm disc Rear: 230mm disc
TYRES	Front: 110/70 R17 Rear: 150/60 R17	Front: 110/70 R17 Rear: 150/60 R17
CONNECTIVITY		
NETWORK	LTE connectivity with integrated eSIM	LTE connectivity with integrated eSIM
WLAN	Supports 802.11a/b/g/n/ac Wi-Fi standards	Supports 802.11a/b/g/n/ac Wi-Fi standards
BLUETOOTH	Supports Bluetooth 5, Bluetooth low energy	Supports Bluetooth 5, Bluetooth low energy
POSITIONING	GPS/GLONASS	GPS/GLONASS
DIMENSIONS		
WHEEL BASE	1340 mm	1340 mm
SEAT HEIGHT	800 mm	800 mm
KERB WEIGHT	197 kg	207 kg
GROUND CLEARANCE	160 mm	160 mm