

AdventureWorks Database — Schema Reference

Source: [chriseaton/adventureworks:postgres](#) Docker image, connected to database [postgres](#), container [adventureworks-db](#).

Note: All schema and table names below are case-sensitive in Postgres and must be double-quoted in SQL (e.g. `"Sales"."SalesOrderHeader"`).

Schema: Person

Table	Row Count	Key Columns (sample)
Address	19,614	AddressID, AddressLine1, City, PostalCode
AddressType	6	AddressTypeID, Name
BusinessEntity	20,777	BusinessEntityID
BusinessEntityAddress	19,614	BusinessEntityID, AddressID, AddressTypeID
BusinessEntityContact	909	BusinessEntityID, PersonID, ContactTypeID
ContactType	20	ContactTypeID, Name
CountryRegion	238	CountryRegionCode, Name
EmailAddress	19,972	BusinessEntityID, EmailAddressID, EmailAddress
Password	19,972	BusinessEntityID, PasswordHash
Person	19,972	BusinessEntityID, PersonType, FirstName, LastName

Table	Row Count	Key Columns (sample)
PersonPhone	19,972	BusinessEntityID, PhoneNumber, PhoneNumberTypeID
PhoneNumberType	3	PhoneNumberTypeID, Name
StateProvince	181	StateProvinceID, StateProvinceCode

Schema: Production

Table	Row Count	Key Columns (sample)
BillOfMaterials	2,679	BillOfMaterialsID, ProductAssemblyID, ComponentID
Culture	8	CultureID, Name
Document	13	DocumentNode, DocumentLevel
Illustration	5	IllustrationID, Diagram
Location	14	LocationID, Name, CostRate, Availability
Product	504	ProductID, Name
ProductCategory	4	ProductCategoryID, Name
ProductCostHistory	395	ProductID, StartDate, EndDate, StandardCost
ProductDescription	762	ProductDescriptionID
ProductDocument	32	ProductID, DocumentNode
ProductInventory	1,069	ProductID, LocationID, Shelf, Bin, Quantity
ProductListPriceHistory	395	ProductID, StartDate, EndDate, ListPrice

Table	Row Count	Key Columns (sample)
ProductModel	128	ProductModelID, Name
ProductModelIllustration	7	ProductModelID, IllustrationID
ProductModelProductDescriptionCulture	762	ProductModelID, ProductDescriptionID, CultureID
ProductPhoto	101	ProductPhotoID
ProductProductPhoto	504	ProductID, ProductPhotoID, Primary
ProductReview	4	ProductReviewID, ProductID, ReviewerName, Rating
ProductSubcategory	37	ProductSubcategoryID, ProductCategoryID, Name
ScrapReason	16	ScrapReasonID, Name
TransactionHistory	113,443	TransactionID, ProductID, ReferenceOrderID, TransactionType, Quantity
TransactionHistoryArchive	89,253	TransactionID, ProductID, ReferenceOrderID, TransactionType
UnitMeasure	38	UnitMeasureCode, Name
WorkOrder	72,591	WorkOrderID, ProductID, OrderQty, StartDate, EndDate, DueDate
WorkOrderRouting	67,131	WorkOrderID, ProductID, OperationSequence, LocationID

Schema: Sales

Table	Row Count	Key Columns (sample)
CountryRegionCurrency	109	CountryRegionCode, CurrencyCode
CreditCard	19,118	CreditCardID, CardType, CardNumber, ExpMonth, ExpYear
Currency	105	CurrencyCode, Name
CurrencyRate	13,532	CurrencyRateID, FromCurrencyCode, ToCurrencyCode, AverageRate
Customer	19,820	CustomerID, PersonID, StoreID, AccountNumber
PersonCreditCard	19,118	BusinessEntityID, CreditCardID
SalesOrderDetail	121,317	SalesOrderID, SalesOrderDetailID, LineTotal
SalesOrderHeader	31,465	SalesOrderID, RevisionNumber, OrderDate, Comment
SalesOrderHeaderSalesReason	27,647	SalesOrderID, SalesReasonID
SalesPerson	17	BusinessEntityID, TerritoryID, SalesQuota, SalesLastYear
SalesPersonQuotaHistory	163	BusinessEntityID, QuotaDate, SalesQuota
SalesReason	10	SalesReasonID, Name, ReasonType
SalesTaxRate	29	SalesTaxRateID, StateProvinceID

Table	Row Count	Key Columns (sample)
SalesTerritory	10	TerritoryID, Name, CountryRegionCode, CostLastYear
SalesTerritoryHistory	17	BusinessEntityID, TerritoryID, StartDate, EndDate
ShoppingCartItem	3	ShoppingCartItemID, ShoppingCartID, Quantity, ProductID
SpecialOffer	16	SpecialOfferID, Description, DiscountPct, MaxQty
SpecialOfferProduct	538	SpecialOfferID, ProductID
Store	701	BusinessEntityID, Name
vIndividualCustomer (view)	18,508	BusinessEntityID, FirstName, PostalCode, CountryRegionName, Demographics
vSalesPerson (view)	17	BusinessEntityID, FirstName, TerritoryGroup, SalesQuota, SalesYTD
vStoreWithAddresses (view)	712	BusinessEntityID, Name, AddressType, StateProvinceName
vStoreWithContacts (view)	753	BusinessEntityID, Name, EmailAddress, EmailPromotion

Notable relationships (for Knowledge Graph construction)

- `Person.BusinessEntity` is the central entity — `Person.Person`, `Sales.Store`, and `Sales.SalesPerson` all key off `BusinessEntityID`.

- `Sales.Customer` links to either a `PersonID` (individual customer) or `StoreID` (business customer) — not both.
- `Sales.SalesOrderHeader` → `Sales.SalesOrderDetail` (order header/line-item pattern), joined on `SalesOrderID`.
- `Production.Product` → `Production.ProductSubcategory` → `Production.ProductCategory` (product hierarchy).
- `Production.ProductInventory` links `Product` to `Location` (warehouse/stock location).
- `Sales.SalesTerritory` connects sales people, customers, and country/region data geographically.
- `Person.BusinessEntityAddress` is the join table between any business entity (person or store) and `Person.Address`.

Known setup notes

- Schema/table names are case-sensitive — always double-quote in SQL.
- The `chriseaton/adventureworks:postgres` image ships with the data **pre-baked** into the image; `POSTGRES_PASSWORD` is not applied via `initdb` on first run, so it may not match what's set in `.env/docker-compose.yml`. If auth fails, reset it manually inside the running container:

```
ALTER USER postgres WITH PASSWORD 'your_password';
```

- This is the Postgres **"light"** port of AdventureWorks — no stored procedures, functions, or custom types; some XML/CROSS APPLY views are omitted.