

Lab 2: SimSpace
Student Name: Raymond Ng

IS 3513 Summer 2023
Instructor Name: Dr. William Pugh
June 26, 2023

Introduction

This lab aims to introduce and familiarize the user with the use of SimSpace. Additionally, the lab will explore the use of the *nmap* utility for network discovery and security auditing via virtual machine (VM). Further, the user will experiment and demonstrate the use of applications useful for a security practitioner via VM.

Procedure

Step 1

To begin the lab, I created a user account via SimSpace Portal. Below is a screenshot of a SimSpace Portal after a successful login attempt (*Figure 1*).




Figure 1: SimSpace Portal.

Step 2

I accessed the User Guide by clicking in the lower left corner of Sim Space Portal, where my initials were located (*Figure 2*):




Figure 2: Accessing SimSpace User Guide.

After accessing the *User Guide*, I reviewed the content of the *SimSpace Cyber Range User Guide* (*Figure 3*).




Figure 3: SimSpace Cyber Range User Guide.

Step 3

To access the 'Events' application, I clicked on the application's icon underneath the SimSpace logo in the upper left corner (*Figure 4*).



Figure 4: Accessing SimSpace applications.

Next, I clicked 'Events' (*Figure 5*), which took me to the Structured Content Event Outlook (*Figure 6*).




Figure 5: SimSpace applications.




Figure 6: Structured Content Event Outlook.

Next, I accessed the 'Live Action Events' and observed only one option/range, [IS 3513.02T Pugh Summer 2023](#), provided by Dr. Pugh (Figure 7).




Figure 7: Accessing 'Live Action Events' via SimSpace.

Next, I clicked [IS 3513.02T Pugh Summer 2023](#), from the previous screen (Figure 7), and explored the 'Virtual Machines' and 'Network Map' options/ranges. Additionally, I observed the username/passwords associated with each VM, underneath the 'VM Description' section (Figure 8).




Figure 8: Observing options/ranges in 'Live Action Events' via SimSpace.

Step 4

Per the lab instructions, I was directed to access one of the [win-hunt-xx](#) VMs. I observed no Users in the [win-hunt-01](#) VM so I opened the console (*Figure 9*).




Figure 9: Opened [win-hunt-01](#) VM via SimSpace.

Step 5

Per the lab's instructions, I opened Windows PowerShell via Hunt image ([win-hunt-01](#)) by searching for PowerShell in the VM. Next, I executed *nmap* via PowerShell. (*Figure 10*)




Figure 10: Opened PowerShell in VM and executed nmap via PowerShell.

Step 6

After typing in nmap via PowerShell, I observed and analyzed the output. The output seemed to depict the capabilities of *nmap*, including all the switches that can be used with *nmap* (Figure 10)

Step 7

Next, I initiated my first scan by typing *nmap -v 172.16.3.0/24* (Figure 11).




Figure 11: Executing first scan using nmap via PowerShell.

-v is a switch/option used for verbosity, providing more detailed information about the scan it is performing. This can be useful for understanding exactly what **nmap** is doing, what stages of the scan it's at, and whether or not it's experiencing any difficulties (NMAP.org, n.d.).

Step 8

After executing the Linux command from [Step 7](#), there was an overwhelming amount of output that was produced so I proceeded to [Step 9](#) where it directed me to “redirect” the output to a file.

Step 9

Here, I executed another scan but redirected the output to a file by typing **nmap -v 172.16.3.0/24 > yournamescan1.txt** ([Figure 12](#)).

```
PS C:\Users\Administrator> nmap -v 172.16.3.0/24 > yournamescan1.txt
PS C:\Users\Administrator>
```

Figure 12: Executed next scan and redirected output to a file.

Step 10

To observe the files in my directory, I executed **ls** command ([Figure 13](#)).

```
PS C:\Users\Administrator> ls

Directory: C:\Users\Administrator

Mode                LastWriteTime         Length Name
----                -
d-----          12/12/2020   10:44 AM             .config
d-----          12/12/2020   10:44 AM             .ghidra
d-r---           2/1/2021    10:52 PM        3D Objects
d-r---           2/1/2021    10:52 PM        Contacts
d-r---           8/11/2021    11:38 AM        Desktop
d-r---           2/7/2021     4:03 PM        Documents
d-r---           8/11/2021    11:00 AM        Downloads
d-r---           2/1/2021    10:52 PM        Favorites
d-r---           2/1/2021    10:52 PM        Links
d-r---           2/1/2021    10:52 PM        Music
d-----           7/26/2021     7:44 PM        mysnort
d-r---           2/1/2021    10:55 PM        OneDrive
d-r---           2/1/2021    10:54 PM        Pictures
d-r---           2/1/2021    10:52 PM        Saved Games
d-r---           2/1/2021    10:54 PM        Searches
d-r---           2/1/2021    10:52 PM        Videos
-a----           6/26/2023    12:00 PM        53442 yournamescan1.txt

PS C:\Users\Administrator>
```

Figure 13: Observing files in my directory.

Step 11

To observe my output type I executed **cat yournamescan1.txt** in PowerShell ([Figure 14](#)). The output was same/similar as the output produced in [Step 7](#).


```

PS C:\Users\Administrator> cat yournamescan1.txt
Starting Nmap 7.70 ( https://nmap.org ) at 2023-06-26 11:59 Eastern Daylight Time
Initiating ARP Ping Scan at 11:59
Scanning 255 hosts [1 port/host]
Completed ARP Ping Scan at 12:00, 1.49s elapsed (255 total hosts)
Initiating Parallel DNS resolution of 255 hosts. at 12:00
Completed Parallel DNS resolution of 255 hosts. at 12:00, 26.03s elapsed
Nmap scan report for 172.16.3.0 [host down]
Nmap scan report for 172.16.3.2 [host down]
Nmap scan report for 172.16.3.3 [host down]
Nmap scan report for 172.16.3.4 [host down]
Nmap scan report for 172.16.3.21 [host down]
Nmap scan report for 172.16.3.22 [host down]
Nmap scan report for 172.16.3.23 [host down]

```

Figure 14: Observing contents of yournamescan1.txt.

Step 12

From reviewing the output in Step 11, I know that when I executed the nmap command to scan for 172.16.3.0/24 I was scanning the network 172.16.3.0 with a netmask of 255.255.255.0. The /24 is a classless inter-domain routing (CIDR) notation; therefore, I was scanning IPs from 172.16.3.0 through 172.16.3.255. Looking at *Figure 14*, 255 total hosts, or 255 total addresses were scanned.

Step 13

Further reviewing/analyzing output after scanning 172.16.3.0/24 I could determine that 36 hosts were up because the **nmap** output later depicts it scanned 36 hosts (*Figure 15*) because the others were down.

```

Initiating SYN Stealth Scan at 12:00
Scanning 36 hosts [1000 ports/host]
Discovered open port 139/tcp on 172.16.3.211

```

Figure 15: NMAP scanning hosts that were up.

Step 14

After reviewing the Network Map (*Figure 16*) via SimSpace further validated the number of hosts that I observed were up from Step 13. From the Network Map, I could see that exactly 36 hosts were up.




Figure 16: Network Map of 172.16.3.0/24 subnet via SimSpace

Step 15

Per the lab instructions, I executed **`nmap -v -sU 172.16.2.2 > yournamemachine10scan.txt`** (Figure 17). Next, I executed **`cat yournamemachine10scan.txt`** to view my output.

```
PS C:\Users\Administrator> nmap -v -sU 172.16.2.2 > yournamemachine10scan.txt
PS C:\Users\Administrator> cat yournamemachine10scan.txt
Starting Nmap 7.70 ( https://nmap.org ) at 2023-06-26 13:29 Eastern Daylight Time
Initiating Ping Scan at 13:29
Scanning 172.16.2.2 [4 ports]
Completed Ping Scan at 13:29, 3.44s elapsed (1 total hosts)
Nmap scan report for 172.16.2.2 [host down]
Read data files from: c:\program files (x86)\nmap
Note: Host seems down. If it is really up, but blocking our ping probes, try -Pn
Nmap done: 1 IP address (0 hosts up) scanned in 3.97 seconds
Raw packets sent: 8 (304B) | Rcvd: 0 (0B)
```

Figure 17: NMAP scanning for open UDP ports at IP address 172.16.2.2

In [Step 7](#) we used **`-v`** option/switch to increase verbosity of **`nmap`** output. Here we added **`-v -sU`**. **`-sU`** is an option that tells NMAP to perform a User Datagram Protocol (UDP) scan (NMAP.org, n.d.). This scan looks for open UDP ports. Therefore, I am telling **`nmap`** to perform a detailed scan for UDP ports at IP address 172.16.2.2 and give a verbose output as seen in [Figure 17](#).

Looking at *Figure 17*, NMAP scanned for 4 ports at IP address 172.16.2.2; however, the host itself seemed to be down.

Further, per the lab instructions, I executed ***nmap -v -sn 172.16.2.2***. To compare the outputs. Adding ***-sn***, ping scan, I can determine which hosts on a network are online and responding to pings, but it does not scan the ports of the target hosts. Essentially, it's a quick way to identify hosts on the network without going through the longer process of port scanning. So here, I'm performing a verbose ping scan at IP address 172.16.2.2 and providing a detailed output.

```
PS C:\Users\Administrator> nmap -v -sU 172.16.2.2 > yournamemachine10scan.txt
PS C:\Users\Administrator> cat yournamemachine10scan.txt
Starting Nmap 7.70 ( https://nmap.org ) at 2023-06-26 13:29 Eastern Daylight Time
Initiating Ping Scan at 13:29
Scanning 172.16.2.2 [4 ports]
Completed Ping Scan at 13:29, 3.44s elapsed (1 total hosts)
Nmap scan report for 172.16.2.2 [host down]
Read data files from: c:\program files (x86)\nmap
Note: Host seems down. If it is really up, but blocking our ping probes, try -Pn
Nmap done: 1 IP address (0 hosts up) scanned in 3.97 seconds
Raw packets sent: 8 (304B) | Rcvd: 0 (0B)
PS C:\Users\Administrator> nmap -v -sn 172.16.2.2
Starting Nmap 7.70 ( https://nmap.org ) at 2023-06-26 13:54 Eastern Daylight Time
Initiating Ping Scan at 13:54
Scanning 172.16.2.2 [4 ports]
Completed Ping Scan at 13:54, 3.45s elapsed (1 total hosts)
Nmap scan report for 172.16.2.2 [host down]
Read data files from: c:\program files (x86)\nmap
Note: Host seems down. If it is really up, but blocking our ping probes, try -Pn
Nmap done: 1 IP address (0 hosts up) scanned in 4.00 seconds
Raw packets sent: 8 (304B) | Rcvd: 0 (0B)
PS C:\Users\Administrator>
```

Figure 18: Comparing output of NMAP scan using -v -sU versus -v -sn.

Looking at *Figure 18*, I observed no difference in output between ***nmap -v -sU*** versus ***nmap -v -sn*** scans.

Step 16

Lastly, I deleted ***yournamescan1.txt*** and ***yournamemachine10scan.txt*** from VM (*Figure 19*).

```
PS C:\Users\Administrator> del yournamescan1.txt
PS C:\Users\Administrator> del yournamemachine10scan.txt
```

Figure 19: Using del command to delete text files via PowerShell.

Step 17

In this part of the lab, per the lab instructions, I was directed to log into one of the [kali-hunt-xx](#) VMs and pick 3 applications that could be useful for a security practitioner. I logged into [kali-hunt-01](#) VM and began exploring applications.

Metasploit

Metasploit is a powerful and widely used penetration testing framework that is highly valuable for network cybersecurity professionals (Simplilearn, 2023). According to Okta, Metasploit comes with three components used to exploit network vulnerabilities: exploit, payloads, and

auxiliaries. Exploits act as carriers, executing specific actions based on known vulnerabilities, while payloads function as viruses, deployed by the exploits. Additionally, auxiliaries are custom functions that handle tasks unrelated to system exploits, such as scanning and sniffing (Okta, 2022).

In an effort to familiarize myself with Metasploit, I followed a tutorial via YouTube provided the C4 Cyber Club (C4 Cyber Club, 2021).

Continuing on the [kali-hunt-01](#) VM, I opened up the Metasploit application. Per the YouTube video instructions, I needed execute a few command sequences to initialize, configure and launch a console, but upon opening up the application I noticed that it executed the aforementioned on its own.

Here, I executed *show exploits* and viewed all the exploits available (Figure 20).

```
msf5 > show exploits


Exploits
=====

Name                                     Disclosure
Date Rank      Check Description
----
-----
aix/local/ibstat_path                    2013-09-24
  excellent Yes    ibstat $PATH Privilege Escalation
aix/rpc_cmds_opcode21                    2009-10-07
  great      No     AIX Calendar Manager Service Daemon (rpc.cmsd) Opcode 21
Buffer Overflow
aix/rpc_ttdbserverd_realpath              2009-06-17
  great      No     ToolTalk rpc.ttdbserverd _tt_internal_realpath Buffer Ov
erflow (AIX)
android/adb/adb_server_exec                2016-01-01
  excellent Yes    Android ADB Debug Server Remote Payload Execution
android/browser/samsung_knox_smdm_url      2014-11-12
  excellent No     Samsung Galaxy KNOX Android Browser RCE
android/browser/stagefright_mp4_tx3g_64bit 2015-08-13
  normal     No     Android Stagefright MP4 tx3g Integer Overflow
android/browser/webview_addjavascriptinterface 2012-12-21
```

Figure 20: Executing *show exploits* command via Metasploit.

The *show exploits* command in Metasploit is an invaluable tool for security professionals. It allows them to explore and research various exploits within the framework, gain insights into vulnerabilities and target platforms, and stay updated on emerging threats. By examining the list of exploits, practitioners can identify vulnerabilities in their target systems, prioritize security efforts, and make informed decisions about exploit selection based on reliability and compatibility. They can also customize exploits to suit specific needs, leveraging the command's parameters and configurations. Additionally, the command provides detailed documentation for each exploit, offering functionality explanations and usage instructions.

Here, I executed *show payloads* and viewed all the payloads available (Figure 21).



```

Terminal
File Edit View Search Terminal Help
msf5 > show payloads

Payloads
=====


Name                Disclosure Date  Rank
Check Description  -----
-----
aix/ppc/shell_bind_tcp      normal
No    AIX Command Shell, Bind TCP Inline
aix/ppc/shell_find_port    normal
No    AIX Command Shell, Find Port Inline
aix/ppc/shell_interact     normal
No    AIX execve Shell for inetd
aix/ppc/shell_reverse_tcp  normal
No    AIX Command Shell, Reverse TCP Inline
android/meterpreter/reverse_http  normal
No    Android Meterpreter, Android Reverse HTTP Stager
android/meterpreter/reverse_https  normal
No    Android Meterpreter, Android Reverse HTTPS Stager
android/meterpreter/reverse_tcp    normal
No    Android Meterpreter, Android Reverse TCP Stager
android/meterpreter reverse http    normal

```

Figure 21: Executing *show payloads* command via Metasploit.

show payloads in Metasploit provides security professionals with a comprehensive list of available payloads in the framework. Payloads are code or scripts that are executed on a target system after a successful exploit. Security professionals can use this command to select payloads tailored to their specific testing goals, customize payload parameters for compatibility and evasion, identify payloads for post-exploitation activities, and access detailed documentation for functionality and usage guidance. By leveraging the *show payloads* command, practitioners enhance the effectiveness and efficiency of security testing, assessment, and post-exploitation activities conducted with Metasploit.

Metasploit also contains vulnerability scanning modules. Per the video, I loaded *wmap* (Figure 22).



```
msf5 > load wmap

[WMAP 1.5.1] === et [ ] metasploit.com 2012
[*] Successfully loaded plugin: wmap
msf5 > wmap_sites -h
[*] Usage: wmap_sites [options]
    -h          Display this help text
    -a [url]    Add site (vhost,url)
    -d [ids]    Delete sites (separate ids with space)
    -l          List all available sites
    -s [id]     Display site structure (vhost,url|ids) (level) (unicode output true/false)
msf5 >
```

Figure 22: Loaded WMAP via Metasploit.

wmap is a module within Metasploit that focuses on web application scanning and vulnerability assessment. It provides a range of automated functionalities to aid security professionals in identifying and assessing vulnerabilities in web applications.

Armitage

Armitage is essentially a GUI version of Metasploit, simplifying network penetration testing and post-exploitation tasks. It provides visual representations of the target network, aiding security practitioners in understanding the network's structure and identifying attack paths (Artykov, 2021). Armitage facilitates collaboration among team members, automates exploit execution, generates detailed reports, and includes a task management system for organizing and prioritizing activities. These features make Armitage valuable to cybersecurity professionals, improving efficiency, simplifying exploit execution, enabling comprehensive reporting, and aiding in task management during penetration testing engagements.

By following another YouTube tutorial by HackerSploit (HackerSploit, 2018), I opened Armitage and began observing the interfaces. (*Figure 23*).




Figure 23: Successful loading of Armitage via VM.

Armitage has the *nmap* utility built into the toolbar in the upper left, under the ‘Hosts’ option. Per the video, I executed a ‘Quick Scan (OS detect)’.




Figure 24: Accessing Nmap Quick Scan (OS detect) via Armitage.

Instead of using the IP address from the video I used the IP address from [Step 7](#), 172.16.3.0/24 and executed the *nmap* scan via Armitage. After the scan was complete, I noticed that in the second interface—the space that depicts active targets—depicted 36 hosts (Figure 25), which further validates the 36 hosts that I found in [Step 13](#) during the *nmap* scan via PowerShell.




Figure 25: Executed Nmap scan via Armitage.

There many ways to use Armitage to exploit vulnerabilities including the options in the preconfigured modules and/or simply by right clicking one of the active targets. The one I found most interesting was the option to find exploits automatically by going to the tool bar, and selecting 'Attacks', then 'Find Attacks' (Figure 26).




Figure 26: Selecting 'Find Attacks' via Armitage.

Next, Armitage begins querying for exploits. After it was complete, I right clicked on the first host and observed all the vulnerabilities/exploits that Armitage could find (Figure 27).




Figure 27: Observing exploits/vulnerabilities Armitage found in the first host.

The 'Find Attack' feature in Armitage is a useful tool for cybersecurity professionals as it allows for automated mapping of known exploits to discovered vulnerabilities on a target. This function significantly streamlines the exploit selection process, reducing manual effort, and potentially increasing accuracy by cross-referencing identified services and versions against a comprehensive database of known vulnerabilities and exploits. Moreover, the feature aids in efficient utilization of Armitage's capabilities, and the attacks can be sorted based on their reliability or impact, thereby assisting in prioritization.

Wireshark

Wireshark is a free application that allows security professionals to capture and interactively browse the traffic running on a computer network. It's useful for security practitioners because it provides detailed insight into network activities, helping identify malicious activities, analyze packets, troubleshoot network issues, and understand network protocols in-depth. It's features like filtering, color coding, and protocol dissectors, Wireshark aids in visualizing complex network interactions, which can be valuable for intrusion detection, network forensics, and monitoring network health. Therefore, Wireshark serves as a critical tool in a security professional's toolkit for diagnosing both routine and complex network-related issues (CompTIA, n.d.).

When opening the application for the first time, I'm welcomed by the welcome screen along with what appears to be network traffic (*Figure 28*).




Figure 28: Wireshark welcome screen.

I began my first packet capture by pressing the little blue shark fin button located in the upper left corner. I ran the feature for approximately one minute in hopes of capturing some data packets (Figure 29).




Figure 29: Wireshark packet capture.

Analyzing the data packets via the packet list pane, most packets looked similar except I found one that stood out. Wireshark also highlighted the packet in yellow to delineate the difference. (Figure 30)

97	78.000791661	Intel_00:00:00	Broadcast	ARP	60	Who has 10.10.200.
98	79.000681670	Intel_00:00:00	Broadcast	ARP	60	Who has 10.10.200.
99	80.000845212	Intel_00:00:00	Broadcast	ARP	60	Who has 10.10.200.
100	81.000434758	Intel_00:00:00	Broadcast	ARP	60	Who has 10.10.200.
101	82.000138841	Intel_00:00:00	Broadcast	ARP	60	Who has 10.10.200.
102	83.000258707	Intel_00:00:00	Broadcast	ARP	60	Who has 10.10.200.
103	83.770689935	10.10.0.14	10.10.255.255	BROWSER	243	Host Announcement
104	83.999940231	Intel_00:00:00	Broadcast	ARP	60	Who has 10.10.200.
105	84.999911287	Intel_00:00:00	Broadcast	ARP	60	Who has 10.10.200.
106	85.999661654	Intel_00:00:00	Broadcast	ARP	60	Who has 10.10.200.
107	86.999557514	Intel_00:00:00	Broadcast	ARP	60	Who has 10.10.200.
108	87.999451580	Intel_00:00:00	Broadcast	ARP	60	Who has 10.10.200.
109	88.999541247	Intel_00:00:00	Broadcast	ARP	60	Who has 10.10.200.
110	89.999248087	Intel_00:00:00	Broadcast	ARP	60	Who has 10.10.200.
111	90.999041938	Intel_00:00:00	Broadcast	ARP	60	Who has 10.10.200.

Figure 30: Analyzing data packets from Wireshark scan.

I noticed one of the IPs, 10.10.255.255, from *Figure 30*, they have appeared in my exploration of other application via [kali-hunt-01](#) VM. So, I opened the terminal via Kali and executed *ifconfig*.

```

root@kali-hunt-01: ~
File Edit View Search Terminal Help
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
    inet 10.10.0.100 netmask 255.255.0.0 broadcast 10.10.255.255
    inet6 fe80::202:b3ff:fe00:900 prefixlen 64 scopeid 0x20<link>
    ether 00:02:b3:00:09:00 txqueuelen 1000 (Ethernet)
    RX packets 2438255 bytes 186618674 (177.9 MiB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 53377 bytes 61666322 (58.8 MiB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

```

Figure 31: Executed *ifconfig* via command terminal.

Later I clicked on the same data packets and analyzed the contents in the Packet Details and the Packet Bytes pane (*Figure 32*).




Figure 32: Analyzing packet details and packet bytes panes.

From previous courses, I recognized the raw bits in the Packet Bytes pane from Figure 32. The left section is a hexadecimal dump of data bytes in the packet and the right side is ASCII interpretation.

The ability of Wireshark to capture raw data from network traffic provides vital insights for security practitioners. This raw data assists in detecting anomalies and potential security threats like malware or DDoS attacks, as well as in understanding and identifying misuse or non-standard implementations of network protocols. Moreover, it can assist in troubleshooting network or application issues and serves as a key forensic tool, supplying critical evidence post-security incidents to prevent similar occurrences in the future. Further, this data enhances network optimization by providing a detailed view of network traffic, thus improving both security and efficiency.

Bonus

The NMAP utility was used in one of the Matrix trilogies films, specifically The Matrix Reloaded (2003), one of the characters, Trinity, in the movie uses NMAP to change a power station's root password to gain access (Figure 20).



Figure 33: Scene from *The Matrix Reloaded* of Trinity using NMAP utility.
Image sourced from YouTube (YouTube, 2012).

Bibliography

- Artykov, D. (2021, March 26). *Scan the network with Armitage*. Retrieved from Medium: <https://medium.com/purple-team/scan-the-network-with-armitage-62aaae5631e9#:~:text=Armitage%20is%20a%20scriptable%20apparatus%20for%20Metasploit%20that%20visualizes%20targets,power%20and%20potential%20of%20Metasploit.>
- C4 Cyber Club. (2021, February 15). *Ethical Hacking Lab - NETLAB+ 09 Metasploit Framework Fundamentals and Armitage*. Retrieved from YouTube: <https://www.youtube.com/watch?v=12WR7dv57G0>
- CompTIA. (n.d.). *What Is Wireshark and How Is It Used?* Retrieved from <https://www.comptia.org/content/articles/what-is-wireshark-and-how-to-use-it#:~:text=What%20Is%20Wireshark%20Used%20For,identify%20bursts%20of%20network%20traffic.>
- HackerSploit. (2018, April 12). *Armitage Kali Linux Complete Tutorial*. Retrieved from YouTube: <https://www.youtube.com/watch?v=JALmoY4LuT8>
- NMAP.org. (n.d.). *Chapter 18. Nping Reference Guide*. Retrieved from [nmap.org](https://nmap.org/book/nping-man.html): <https://nmap.org/book/nping-man.html>
- NMAP.org. (n.d.). *Command-line Flags*. Retrieved from NMAP.org: <https://nmap.org/book/output-formats-commandline-flags.html#:~:text=Nmap%20always%20prints%20warnings%20about,more%20warnings%20to%20be%20printed.>
- Okta. (2022, April 21). *Understanding the Metasploit Project and Why It's Useful*. Retrieved from <https://www.okta.com/identity-101/metasploit/>
- Simplilearn. (2023, February 2). *What is Metasploit: Overview, Framework, and How is it Used*. Retrieved from <https://www.simplilearn.com/what-is-metasploit-article#:~:text=Metasploit%20is%20a%20powerful%20tool,by%20security%20engineers%20across%20industries.>
- YouTube. (2012, November 14). *Trinity uses nmap in The Matrix Reloaded*. Retrieved from YouTube: <https://www.youtube.com/watch?v=0PxTAn4g20U>