

Mark Scheme (Results)

January 2023

Pearson Edexcel International Advanced Level In Mechanics M2 (WME02) Paper 01

## **Edexcel and BTEC Qualifications**

Edexcel and BTEC qualifications are awarded by Pearson, the UK's largest awarding body. We provide a wide range of qualifications including academic, vocational, occupational and specific programmes for employers. For further information visit our qualifications websites at <a href="https://www.edexcel.com">www.btec.co.uk</a>. Alternatively, you can get in touch with us using the details on our contact us page at <a href="https://www.edexcel.com/contactus">www.edexcel.com/contactus</a>.

# Pearson: helping people progress, everywhere

Pearson aspires to be the world's leading learning company. Our aim is to help everyone progress in their lives through education. We believe in every kind of learning, for all kinds of people, wherever they are in the world. We've been involved in education for over 150 years, and by working across 70 countries, in 100 languages, we have built an international reputation for our commitment to high standards and raising achievement through innovation in education. Find out more about how we can help you and your students at: www.pearson.com/uk

January 2023

Question Paper Log Number P72071A

Publications Code WME02\_01\_MS\_2301

All the material in this publication is copyright

© Pearson Education Ltd 2023

# **General Marking Guidance**

- All candidates must receive the same treatment. Examiners must mark the first candidate in exactly the same way as they mark the last.
- Mark schemes should be applied positively. Candidates must be rewarded for what they have shown they can do rather than penalised for omissions.
- Examiners should mark according to the mark scheme not according to their perception of where the grade boundaries may lie.
- There is no ceiling on achievement. All marks on the mark scheme should be used appropriately.
- All the marks on the mark scheme are designed to be awarded. Examiners should always award full marks if deserved, i.e. if the answer matches the mark scheme. Examiners should also be prepared to award zero marks if the candidate's response is not worthy of credit according to the mark scheme.
- Where some judgement is required, mark schemes will provide the principles by which marks will be awarded and exemplification may be limited.
- When examiners are in doubt regarding the application of the mark scheme to a candidate's response, the team leader must be consulted.
- Crossed out work should be marked UNLESS the candidate has replaced it with an alternative response.

#### PEARSON EDEXCEL IAL MATHEMATICS

## **General Instructions for Marking**

- 1. The total number of marks for this paper is 75.
- 2. The Edexcel Mathematics mark schemes use the following types of marks:

### 'M' marks

These are marks given for a correct method or an attempt at a correct method. In Mechanics they are usually awarded for the application of some mechanical principle to produce an equation.

e.g. resolving in a particular direction, taking moments about a point, applying a suvat equation, applying the conservation of momentum principle etc.

The following criteria are usually applied to the equation.

To earn the M mark, the equation

- (i) should have the correct number of terms
- (ii) be dimensionally correct i.e. all the terms need to be dimensionally correct
- e.g. in a moments equation, every term must be a 'force x distance' term or 'mass x distance', if we allow them to cancel 'g' s.

For a resolution, all terms that need to be resolved (multiplied by sin or cos) must be resolved to earn the M mark.

M marks are sometimes dependent (DM) on previous M marks having been earned. e.g. when two simultaneous equations have been set up by, for example, resolving in two directions and there is then an M mark for solving the equations to find a particular quantity – this M mark is often dependent on the two previous M marks having been earned.

#### 'A' marks

These are dependent accuracy (or sometimes answer) marks and can only be awarded if the previous M mark has been earned. e.g. M0 A1 is impossible.

#### 'B' marks

These are independent accuracy marks where there is no method (e.g. often given for a comment or for a graph).

A few of the A and B marks may be f.t. – follow through – marks.

#### 3. General Abbreviations

These are some of the traditional marking abbreviations that will appear in the mark schemes.

- bod benefit of doubt
- ft follow through
- the symbol  $\sqrt{\text{ will be used for correct ft}}$
- cao correct answer only
- cso correct solution only. There must be no errors in this part of the question to obtain this mark
- isw ignore subsequent working
- awrt answers which round to
- SC special case
- oe or equivalent (and appropriate)
- dep dependent
- indep independent
- dp decimal places
- sf significant figures
- \* The answer is printed on the paper
- 4. All A marks are 'correct answer only' (cao), unless shown, for example as A1 ft to indicate that previous wrong working is to be followed through. After a misread however, the subsequent A marks are treated as A ft, but manifestly absurd answers should never be awarded A marks.
- 5. For misreading which does not alter the character of a question or materially simplify it, deduct two from any A or B marks gained, in that part of the question affected.
- 6. If a candidate makes more than one attempt at any question:
  - If all but one attempt is crossed out, mark the attempt which is NOT crossed out.
  - If either all attempts are crossed out or none are crossed out, mark all the attempts and score the highest single attempt.
- 7. Ignore wrong working or incorrect statements following a correct answer.

# **General Principles for Mechanics Marking**

(But note that specific mark schemes may sometimes override these general priniciples)

- Rules for M marks: correct no. of terms; dimensionally correct; all terms that need resolving (i.e. multiplied by cos or sin) are resolved.
- Omission or extra g in a resolution is an accuracy error not method error.
- Omission of mass from a resolution is a method error.
- Omission of a length from a moments equation is a method error.
- Omission of units or incorrect units is not (usually) counted as an accuracy error.
- DM indicates a dependent method mark i.e. one that can only be awarded if a previous specified method mark has been awarded.
- Any numerical answer which comes from use of g = 9.8 should be given to 2 or 3 SF
- Use of g = 9.81 should be penalised once per (complete) question.
   N.B. Over-accuracy or under-accuracy of correct answers should only be penalized once per complete question. However, premature approximation should be penalised every time it occurs.
- Marks must be entered in the same order as they appear on the mark scheme.
- In all cases, if the candidate clearly labels their working under a particular part of a question i.e. (a) or (b) or (c),.....then that working can only score marks for that part of the question.
- Accept column vectors in all cases.
- Misreads if a misread does not alter the character of a question or materially simplify it, deduct two from any A or B marks gained, bearing in mind that after a misread, the subsequent A marks affected are treated as A ft
- Mechanics Abbreviations

M(A) Taking moments about A

N2L Newton's Second Law (Equation of Motion)

NEL Newton's Experimental Law (Newton's Law of Impact

HL Hooke's Law

SHM Simple harmonic motion

PCLM Principle of conversation of linear momentum

RHS, LHS Right hand side, left hand side

1a	Equation of motion	M1	Dimensionally correct. Condone sign
1a	-	IVII	error.
	F - R = 1500a	A1	Correct unsimplified equation in <i>F</i> or <i>P</i>
	Use of $P = Fv : \left(\frac{30000}{20} - R = 1500 \times 0.6\right)$	M1	Must be trying to use 30 kW but condone error in zeros
	R = 600	A1	Correct answer only
		4	
1b	Equation of motion	M1	Dimensionally correct. Need all relevant terms.  Condone sign errors and sin/cos confusion.  Allow with <i>F</i> .
	$\frac{30000}{V} - 1500g \times \frac{1}{8} - 500 = -1500 \times 0.2$	A1 A1	Unsimplified equation with <i>F</i> substituted and at most one error  Correct unsimplified equation with <i>F</i> substituted.
		711	If F is never substituted, A0A0
	V = 14.7  (15)	A1	3 sf or 2 sf
		4	
		(8)	
2	1 <sup>st</sup> equation e.g. Equation for change in KE	M1	Dimensionally correct. Must be subtracting but condone sign error.
	$\frac{1}{2} \times 0.5 \left( x^2 + y^2 - \left( 5^2 + 3^2 \right) \right) = 22$ $\left( x^2 + y^2 = 122 \right) \left( 1^2 + \left( 2\lambda + 3 \right)^2 = 122 \right)$	A1	Correct unsimplified equation seen or implied (They might have used impulse-momentum first and done some work before substituting <i>x</i> and <i>y</i> .)
	2 <sup>nd</sup> equation e.g. Impulse-momentum equation	M1	Dimensionally correct. Must be subtracting but condone sign error.
	$0.5(x\mathbf{i} + y\mathbf{j}) - 0.5(5\mathbf{i} + 3\mathbf{j}) = (-2\mathbf{i} + \lambda\mathbf{j})$ $((x-5)\mathbf{i} + (y-3)\mathbf{j} = -4\mathbf{i} + 2\lambda\mathbf{j})$	A1	Correct unsimplified equation
	NB: epen has M1A1A1 for the final 3 mark	ks but th	is should be marked DM1DM1A1
	Form a quadratic equation in $\lambda$	DM1	e.g. $1^2 + (3+2\lambda)^2 = 122$ Dependent on the 2 preceding M marks
	Solve for 2 values of $\lambda$	DM1	e.g. solve $4\lambda^2 + 12\lambda - 112 = 0$ or $(3+2\lambda)^2 = 121$ Dependent on the preceding M1
	$\Rightarrow \lambda = 4$ or $\lambda = -7$	A1	Correct only and no errors seen (watch out for $x = -1$ used)
alt	Form a quadratic in y	DM1	e.g. $1+y^2 = 122$ $(y^2 = 121)$ Dependent on the 2 preceding M marks
	Solve for 2 values of $y$ and use these to obtain 2 values of $\lambda$	DM1	Dependent on the preceding M1
	$\Rightarrow \lambda = 4$ or $\lambda = -7$	A1	
	_	7	

3a		area	distance from			
			AE	B1	Mass ratio correct	
	rectangle	$48a^{2}$	4 <i>a</i>			
	triangle	$18a^2$	8a-2a(=6a)	B1	Distances from AE (or parallel axis) correct	
	lamina	$30a^2$				
	M(AE)		M1	M1 Allow use of a parallel axis. The moments equation should include <i>a</i> but condone if the mass ratio does not include a factor of		
					$a^2$ . Dimensionally correct.	
					Correct unsimplified equation for their	
	$48a^2 \times 4a - 18$	$8a^2 \times 6a = 1$	$=30a^2\overline{x}$	A1	axis.	
				Accept as part of a vector equation.		
	$\bar{x} = \frac{84}{30}a = \frac{14}{5}a$ *		A1*	Obtain <b>given answer</b> from correct working (including correct use of <i>a</i> )		
					If they take moments about <i>BD</i> they get	
					d = 5.2a Allow B1B1M1A1A0 if they	
					get this far.	
				5		
3b	Find trig ratio	of a relev	ant angle	M1	Correct use of trig.	
	$\tan \theta^{\circ} = \frac{3a}{2.8a}$		A1	Correct equation for the required angle. (DO NOT ISW: If they obtain 47 and then use $90 - 47 = 43$ they score M1A0A0)		
	$\theta = 47$	1		A1	The Q asks for a whole number of degrees. 0.82 radians scores M1A1A0	
				3	0.02 facialis scores WITATAU	
				(8)		
				(0)		

4a	Use $t = 2$ and $3t^2 + 2t = t^3 + kt$ (12+4=8+2k)	M1	Allow verification.
	k = 4 *	A1*	Obtain given answer from correct working. Verification requires a clear conclusion.
		2	
4b	Use of $\mathbf{a} = \frac{\mathrm{d}\mathbf{v}}{\mathrm{d}t}$	M1	Differentiate the vector <b>v</b> Majority of powers going down
	$\mathbf{a} = (6t+2)\mathbf{i} + (3t^2+4)\mathbf{j}$	A1	Correct only
	Use $ \mathbf{F}  = m \mathbf{a} $	DM1	Correct use of Pythagoras and N2L Dependent on the preceding M1
	$ \mathbf{F}  = 1.5 \times \sqrt{14^2 + 16^2} = 3\sqrt{113}$	A1	Or $\frac{3}{2}\sqrt{452}$ or 32 or better (31.89)
		4	
4c	Use of $\mathbf{r} = \int \mathbf{v}  \mathrm{d}t$	M1	Majority of powers going up
	$\mathbf{r} = \left(t^3 + t^2(+A)\right)\mathbf{i} + \left(\frac{1}{4}t^4 + \frac{4}{2}t^2(+B)\right)\mathbf{j}$	A1	Allow without constant of integration
	Correct use of $\mathbf{r} = 3\mathbf{i} + 4\mathbf{j}$ when $t = 0$ to find $\mathbf{r}$ when $t = 2$	DM1	$\left(\mathbf{r} = \left(t^3 + t^2 + 3\right)\mathbf{i} + \left(\frac{1}{4}t^4 + \frac{4}{2}t^2 + 4\right)\mathbf{j}\right)$ Dependent on the preceding M1 Use of $\mathbf{r} = -3\mathbf{i} - 4\mathbf{j}$ is M0
	$\mathbf{r} = 15\mathbf{i} + 16\mathbf{j}$	A1	Correct answer only.
			Accept column vector
		4	
		(10)	

5a	Use of $F_{\text{max}} = \mu R$ : $F_{\text{max}} = \frac{2}{7} \times 1.5 g \cos \theta$		(3.87) Condone trig confusion.
		3.61	Trig substitution not required.
		M1	Allow M1 if there is a clear statement for
			$F_{\text{max}}$ "correct" and then used in a
			calculation including the gain in GPE
	Use of WD = $2.5 F_{\text{max}}$	M1	Trig substitution not required.
	max		M0 if they have included the gain in GPE
			If the method for <i>F</i> is incorrect but
			involves the use of $\mu$ to obtain $F$ and then
			they use the "work done" formula correctly
			allow M0M1
	WD 0.00 (0.7)(I)	A1	
	WD = 9.69  (9.7)(J)	Ai	3 sf or 2 sf not $\frac{126}{13}$
			13
		3	
5b	Work-energy equation	M1	The Q asks for work-energy. Need all
			terms and dimensionally correct. Condone
			sign errors and sin / cos confusion
	If their answer to (a) included the GPE then it must be used for the total work done here to see the M1		
	1	A1ft	Unsimplified equation with at most one
	$\frac{1}{2} \times 1.5U^2 = WD + 1.5 \times 9.8 \times 2.5 \times \sin \theta$		error.
		A1ft	Correct unsimplified equation Follow
			their WD against friction
	U = 5.64  (5.6)	A1	3 sf or 2 sf
		4	
5c	Work-energy equation for A to A	M1	The Q asks for work-energy. Need all
			terms and dimensionally correct.
	$\frac{1}{2} \times 1.5v^2 - \frac{1}{2} \times 1.5U^2 - 2WD$	A1ft	Correct unsimplified equation. Follow
	$\frac{1}{2} \times 1.5v^2 = \frac{1}{2} \times 1.5U^2 - 2WD$	AIII	their WD against friction and their U
	$v = 2.43 (2.4) (m s^{-1})$	A1	3 sf or 2 sf
		3	
5c	Work-energy equation for <i>B</i> to <i>A</i>	M1	The Q asks for work-energy. Need all
alt			terms and dimensionally correct.
	1 2	A1ft	Correct unsimplified equation. Follow
	$\frac{1}{2} \times 1.5v^2 = 1.5 \times 9.8 \times 2.5 \times \sin \theta - WD$	11110	their WD
		A 1	
	$v = 2.43 (2.4) (m s^{-1})$	A1	3 sf or 2 sf
		3	
		(10)	

6a	1 m C 2 m B 1 m C WN 4 m 50 N		
	M(A)	M1	Or equivalent method to form an equation in <i>W</i> only. Equation(s) must be dimensionally correct and contain all relevant terms. Condone sin / cos confusion and sign error(s)
	$50 \times 3\cos 30^\circ + W \times 6\cos 30^\circ = 60\sqrt{3} \times 4\sin 30^\circ$		Unsimplified equation with at most one error.
	TT7 15 w	Al	Correct unsimplified equation
	W = 15 *	A1*	Correct answer only
(1	T' ( ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' ' '	4	0 1 11.1. 1
6b	First equation e.g. Resolve vertically	M1	Or resolve parallel to pole
	$(\pm)V + 50 + 15 = T\cos 30^{\circ} \ (V = 25)$	A1	Or: $P + 50\cos 60^{\circ} + 15\cos 60^{\circ} = 60\sqrt{3} \times \frac{\sqrt{3}}{2}$
	Second equation e.g. Resolve horizontally	M1	Or resolve perpendicular to the pole
	$(\pm)H = T\cos 60^{\circ} (= 30\sqrt{3} = 51.96)$	A1	Or: $50\cos 30^{\circ} + 15\cos 30^{\circ} = 60\sqrt{3}\cos 60^{\circ} + Q$
	NB: One of the equations could be a second m	oments	
	$ R  = \sqrt{25^2 + (30\sqrt{3})^2}$	DM 1	Dependent on the 2 preceding M marks $\left(\sqrt{57.5^2 + 3 \times 6.25}\right)$
	$=5\sqrt{133}(57.662)$ (N)	A1	58 N or better
		6	Full marks available using $\pm V, \pm H, \pm P, \pm Q$
6b alt	Form vector triangle for the vertical forces, the thrust and the resultant Correct triangle	M1 A1	50+15 T
	Use cosine rule	M1	
	$R^{2} = T^{2} + (50 + W)^{2} - 2T(50 + W)\cos 30^{\circ}$	A1	Correct unsimplified equation
	$R^{2} = (60\sqrt{3})^{2} + (65)^{2} - 2 \times 60\sqrt{3} \times 65\cos 30^{\circ}$	DM 1	Substitute values and solve for $ R $
	$ R  = 5\sqrt{133} (57.662) (N)$	A1	58 N or better
		(10)	
		(10)	

7a	2 <i>u</i> — 3 <i>u</i>		
	$2u \longrightarrow 3u$		
	$\left( egin{array}{c} P \ 3m \end{array}  ight) \qquad \left( egin{array}{c} Q \ km \end{array}  ight)$		
	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		
	$\longrightarrow u \longrightarrow v$		
	/ / /	2.61	N 1 II. 1 II.
	Use CLM	M1	Need all terms and dimensionally correct. Condone sign errors.
			Might see them using equal (and
			opposite) impulses.
	$6mu - 3kmu = 3mu + kmv \left( (3 - 3k)u = kv \right)$	A1	Correct unsimplified equation
	$\Rightarrow v = \frac{(3-3k)}{k}u$ *	A1*	Obtain <b>given answer</b> from full and
	k = k		correct working
7b	Has af Immulas — shansa in managina	3 M1	Must be subtracting
/6	Use of Impulse = change in momentum	M1	Must be subtracting. Can be for either particle.
	$ I_{Q}  =  I_{P}  =  3mu - 3m \cdot 2u  = 3mu$		Correct only
	or		(Do not need to state that $ I_Q  =  I_P $ if find
	$\left kmv - (-3mku)\right  = \left km \cdot \frac{3 - 3k}{k}u + 3mku\right  = 3mu$	A1	· ' '
	$ kmv - (-3mku)  =  km \cdot \frac{1}{k}u + 3mku  = 3mu$		$ I_P $ )
		2	
7c	Use impact law:		Seen or implied. If stated in (a) must be used here.
		M1	Must be used correctly but condone sign
			errors
	$\frac{v-u}{5u} = e \text{ or } \frac{3-3k}{k}u - u = 5ue$	A1	Correct unsimplified equation
			1
	NB: the second and third M mark are not depen		
	Use $v > u$ or $e > 0$ to form an inequality in $k$	M1	Could use $e0$ followed by $v \neq u$
	Use $e_{,,}$ 1 to form an inequality in $k$	M1	
	$\frac{3-3k}{k} > 1$ and $3-3k$ , $6k \Rightarrow \frac{1}{3}$ , $k < \frac{3}{4}$	A1	Correct answer only.
		5	
		(10)	

8a	Condone use of $\theta$ or a mixture of $\theta$ and $\alpha$ throughout but final answer should be in one variable.				
	Equation for horizontal distance	M1	Complete method using <i>suvat</i> . Condone sine / cosine confusion		
	$x = u \cos \alpha t$	A1	Correct only		
	Equation for vertical distance	M1	Complete method using <i>suvat</i> . Condone sine / cosine confusion and sign error		
	$y = u \sin \alpha t - \frac{1}{2} g t^2$	A1	Correct only		
	$t = \frac{x}{u \cos \alpha} \Rightarrow$ $y = u \sin \alpha \cdot \frac{x}{u \cos \alpha} - \frac{g}{2} \left(\frac{x}{u \cos \alpha}\right)^{2}$	DM1	Substitute for $t$ to obtain $y$ in terms of $x$ and $\alpha$ Dependent on the 2 preceding M marks		
	$\Rightarrow y = x \tan \alpha - \frac{gx^2}{2u^2} (1 + \tan^2 \alpha) *$	A1*	Obtain <b>given answer</b> from full and correct working. Need some evidence for the final step. $\frac{1}{\cos^2 \alpha} = 1 + \tan^2 \alpha$ is not sufficient.		
		6			
8b	Conservation of energy:	M1	Method specified in the question. Need all terms and dimensionally correct. Condone sign errors		
	$\frac{1}{2}m \times 25^2 = \frac{1}{2}mU^2 + mg \times 20$ $U = 15.3 (15)$	A1	Correct unsimplified equation		
	U = 15.3 (15)	A1	3 sf or 2 sf only		
		3			
8c	Use part (a) or work from first principles to form an equation in $\tan \theta$	M1	$\left(-20 = 30 \tan \theta - \frac{9.8 \times 900}{2U^2} \left(1 + \tan^2 \theta\right)\right)$		
	Obtain $18.9 \tan^2 \theta - 30 \tan \theta - 1.07 = 0$ $\left(\frac{4410}{233} \tan^2 \theta - 30 \tan \theta - \frac{250}{233} = 0\right)$	A1ft	Or 3 term equivalent Follow their $U$ Can be implied by a correct final answer		
	$\Rightarrow \theta = 58.3^{\circ} \text{ or } 58^{\circ}$	A1	3 sf or 2 sf only		
		3			
		(12)			