

ALZHEIMER'S DISEASE DETECTION FROM MRI IMAGE USING DEEP LEARNING APPROACH

By

Md. Abu Rayhan

ID: 315201058

This Project is Presented in Partial Fulfillment of the Requirements for the
Degree of Bachelor of Science in Computer Science and Engineering

Supervised by

Md. Afzalur Rahaman

Lecturer

Department of Computer Science and Engineering
Hamdard University Bangladesh



HAMDARD UNIVERSITY BANGLADESH

GAZARIA, MUNSHIGANJ

JUNE 2024

APPROVAL

This Thesis is titled “**ALZHEIMER’S DISEASE DETECTION FROM MRI IMAGE USING DEEP LEARNING APPROACH**”, submitted by Md. Md. Abu Rayhan to the Department of Computer Science and Engineering, Hamdard University Bangladesh, has been accepted as satisfactory for the partial fulfillment of the requirements for the degree of B.Sc. in Computer Science and Engineering and approved as to its style and contents. The presentation was held on June 2024.

BOARD OF EXAMINERS

Dr. Md. Jahirul Haque Munshi
Dean,

Faculty of Science Engineering & Technology
Hamdard University Bangladesh

Chairman

Md. Shahidul Islam
Lecturer,

Department of CSE
Hamdard University Bangladesh

Member

Md. Abul Hasnat
Lecturer,

Department of CSE
Hamdard University Bangladesh

Member

Engr. Md. Monowar Hossain
Assistant Professor & Head,
Department of CSE
Hamdard University Bangladesh

Member-Secretary

DECLARATION

The author hereby declares that this Project has been submitted as a requirement for the partial fulfillment of a B.Sc. degree in Computer Science and Engineering. The work has not previously been accepted in substance for any other degree nor submitted in any previous application for any other degree. This work is the result of my work, except where otherwise stated. Other sources are acknowledged by explicit references to the authors.

Supervised by:

Md. Afzalur Rahaman
Lecturer,
Department of CSE
Hamdard University Bangladesh

Submitted by:

Md. Abu Rayhan
ID: 315201058

ACKNOWLEDGEMENT

At first, I express My heartiest thanks and gratefulness to almighty Allah for His divine blessing that made us possible to complete the final year Project successfully.

I am grateful and wish our profound indebtedness to **Md. Afzalur Rahaman, Lecturer**, Department of CSE at Hamdard University Bangladesh, Dhaka. Deep Knowledge & keen interest of our supervisor in the field of “**DEEP LEARNING**” to carry out this Thesis. His endless patience, scholarly guidance, continual encouragement, constant and energetic supervision, constructive criticism, valuable advice, reading many inferior drafts, and correcting them at all stages have made it possible to complete this thesis.

I want to express our heartiest gratitude to **Engr. Md. Monowar Hossain**, Assistant Professor and Head, Department of CSE, for his kind help to finish My Project and also to other faculty members and the staff of the CSE department of Hamdard University Bangladesh.

I want to thank My entire course mates Hamdard University Bangladesh, who took part in this discussion while completing the course work.

Finally, I would be remiss in not mentioning my family, especially my parents, and younger brothers. Ther in me has kept my spirits and motivation high during this process. I would also like to thank my cat for all the entertainment and emotional support.

Abstract

Alzheimer's disease (AD) is a common neurological disease for older people. Alzheimer's disease is difficult to predict. In order to reduce the spread of the Alzheimer's Disease, it is important to make correct and timely identification. It is more effective for AD if treatment is given in early stage than a treatment given at later stage. This research focuses on a machine learning methodology for MRIbased Alzheimer's disease detection. The primary purpose is to create a robust and accurate system that can automatically identify and categorize brain images. The preprocessing of the MRI dataset that has been supplied kicks off the research. The quality and relevance of the photos are improved using a variety of image preprocessing techniques, such as image normalization, noise reduction, and region of interest extraction. Utilizing the Anaconda Navigator platform, a Python-based environment is established, integrating essential libraries and tools for machine learning and deep learning tasks. The project leverages popular libraries such as TensorFlow and Keras for building and training neural network models. By displaying the capability of machine learning models in perfectly identifying and categorizing Alzheimer's disease severity from brain MRI images, this effort makes an important impact to the fields of medical imaging and neurodegenerative disease research. The utilization of Anaconda Navigator enhances the accessibility and reproducibility of the developed solution, promoting further advancements in the diagnosis and treatment of Alzheimer's disease. The proposed work shows better results with average accuracy of 95%.

TABLE OF CONTENTS

CONTENTS	PAGE NO
APPROVAL	i
DECLARATION	li
ACKNOWLEDGMENT	lii
ABSTRACT	Iv
TABLE OF CONTENTS	V
LIST OF FIGURES	Viii
LIST OF TABLES	Ix
LIST OF ABBREVIATIONS	x
CHAPTER 1: INTRODUCTION	1-6
1.1 Introduction	1
1.2 Motivation	3
1.3 Aims & Objectives	3
1.4 Overview of the System	4
1.5 Contribution	5
CHAPTER 2: LITERATURE REVIEW	7-10
2.1 Related Works of to Alzheimer's Disease	7
CHAPTER 3: SYSTEM DEVELOPMENT TOOLS	11-17
3.1 Introduction	11
3.2 Python	11
3.3 Pandas	12
3.4 Matplotlib	12
3.5 Seaborn	13
3.6 Keras	13
3.8 TensorFlow	14
3.9 CNN (Convolutional Neural Network)	14

3.10 Scikit-learn	15
3.11 The VGG16 model	15
3.12 Resnet 50	16
3.13 DenseNet-201	16
3.14 Comparison	16
 CHAPTER 4: METHODOLOGY & DESIGN	 18-31
4.1 Introduction	18
4.2 Data Collection	18
4.3 Dataset	19
4.4 Data Pre-Processing	19
4.5 Cropping	20
4.6 Normalization	20
4.7 Grayscale Conversion	21
4.8 Adaptive Histogram Equalization	21
4.9 Gaussian Blurring	21
4.10 Thresholding	22
4.11 Dilation	22
4.12 Contour Detection	23
4.13 Mask Application	23
4.14 Contrast Enhancement	23
4.15 Sharpening	24
4.16 Resizing	24
4.17 Comprehensive Explanation of the Model with CNN Integration	26
4.18 Data Acquisition and Preprocessing	26
4.19 Data Visualization and Feature Analysis	26
4.20 Model Development	27
4.21 Convolutional Layers	29
4.22 Batch Normalization Layers	29
4.23 MaxPooling Layers	29
4.24 Dropout Layers	30
4.25 Fully Connected Layers	30
4.26 Output Layer	30
4.27 Convolutional Neural Network	31
4.28 Architecture of CNN model	31

CHAPTER 5: RESULT& DISCUSSIONS	33-38
5.1 Introduction	33
5.2 Result Discussion	33
5.3 Model Performance	34
5.4 Explanation of the Confusion Matrix	35
5.5 Model Effectiveness	38
CHAPTER 6: CONCLUSION& FUTURE WORK	39-44
6.1Concusion	39
6.2 Future Works	40
References	41-44

List of Figures

FIGURE NO	FIGURE NAME	PAGE NO
Fig-4.1	MRI Scan	19
Fig-4.2	System Architecture	25
Fig- 4.3	CNN Model	28
Fig- 4.4	Architecture of CNN	32
Fig-5.1	Model Accuracy & Loss	34
Fig-5.2	Confusion Matrix	37

List of Tables

TABLE NO	TABLE NAME	PAGE NO
Table-2.1	Summary of related works of Alzheimer's Disease	09

List of Abbreviations

CNN = Convolutional Neural Network

ANN = Artificial Neural Network

AI = Artificial Intelligence

AD = Alzheimer Disease

ML = Machine Learning

CL = Contrastive Learning

MRI = Magnetic resonance imaging

Chapter-1

Introduction

1.1 Introduction

Memory loss is a symptom of Alzheimer's disease (AD), a neurodegenerative disorder that affects the brain. It is the most common type of dementia and results from beta amyloid plaques building up in the brain. The disease's key pathology hallmarks are these plaques and tangles. The effectiveness of healthy neurons gradually declines with an increase in these plaques and tangles, leading to a gradual breakdown of communication and eventual neuronal death. This process subsequently results in a general decrease in the volume of brain tissue. One notable effect is the death of neurons, which is especially noticeable in the hippocampus and which in turn reduces the brain's ability to form new memories. The hippocampus acts as a primary target, having a considerable influence on memory formation.

However, the disease's underlying origins are yet unknown. Potential explanations such as age, family history, food, and living environment have all been postulated, but none have been verified. However, because brain alterations might manifest years before the first symptoms do, it is critical for the medical community to have instruments to detect the presence of Alzheimer's and, therefore, the disease stage. Currently, the illness is detected using devices like Positron Emission Tomography, Magnetic Resonance Imaging (MRI), and computed tomography (CT). The recommended method is an MRI scan of the head, which produces precise pictures of interior body components by combining strong magnetic fields and radio frequency pulses. An MRI scan may be normal in the early stages but later stages may reveal a decline in the temporal and parietal lobes of the brain. Therefore, by using deep learning, we expect to learn more about how to precisely diagnose Alzheimer's disease based on MRI images

Magnetic Resonance Imaging (MRI) is a non-invasive imaging technique that provides detailed images of the brain's structure. MRI is widely used in diagnosing and monitoring Alzheimer's disease because it can reveal characteristic changes in brain anatomy associated with the disease. Key imaging biomarkers include hippocampal atrophy, cortical thinning, and changes in white matter integrity. However, interpreting these images manually is labor-intensive and requires specialized expertise, prompting the need for automated diagnostic tools.

Alzheimer's disease (AD) is the most prevalent form of dementia, affecting millions of people worldwide. It is a progressive neurodegenerative disorder characterized by memory loss, cognitive decline, and behavioral changes, ultimately leading to a complete inability to carry out daily activities. The pathological hallmarks of Alzheimer's disease include amyloid-beta plaques and neurofibrillary tangles in the brain. These pathological changes are accompanied by neurodegeneration, which can be detected through imaging techniques such as MRI. Magnetic Resonance Imaging (MRI) is a non-invasive imaging technique that provides high-resolution images of brain structures.

It is a valuable tool in the diagnosis and monitoring of Alzheimer's disease because it can reveal structural changes in the brain, such as, Convolutional Neural Networks (CNNs) are a type of deep learning model specifically designed for image processing tasks. Key features of CNNs include CNNs have demonstrated superior performance in various image recognition tasks, including medical image analysis, due to their ability to automatically learn hierarchical features from raw image data. The motivation for this study is to develop a CNN-based model that addresses these challenges, providing a robust and interpretable tool for the early detection of Alzheimer's disease from MRI images This background study highlights the importance of early detection of Alzheimer's disease, the role of MRI in diagnosing the disease, and the potential of CNNs to automate and improve the accuracy of this process. By addressing the challenges associated with data limitations, overfitting, and model interpretability, this project aims to develop a CNN-based tool that can be integrated into clinical practice, ultimately benefiting patients and advancing the field of medical imaging

- To develop a CNN-based model for the early detection of Alzheimer's disease from MRI images.
- To evaluate the performance of the model using metrics such as accuracy, sensitivity, specificity, and AUC-ROC
- To enhance the interpretability of the model using techniques such as Grad-CAM, providing insights into the regions of the brain that contribute to the model's predictions.

1.2 Motivation

The project is inspired by the urgent need to address the growing effects of Alzheimer's disease and the revolutionary potential of cutting-edge technologies. Alzheimer's disease presents a critical concern for healthcare systems across the world as the ageing population increases. Traditional diagnostic techniques frequently fall short of the precision required for early intervention. The fusion of medical imaging and ML presents an opportunity to transform Alzheimer's detection by revealing minor brain irregularities undetectable by human inspection. This strategy can facilitate prompt diagnoses, well-informed choices, and efficient resource management. This project intends to provide medical practitioners with an accurate diagnostic tool by developing a system that combines medical imaging with machine learning. It also contributes to the study of neurodegenerative diseases while showing the promise of technology in healthcare.

Alzheimer's disease (AD) is a growing global health concern, with its prevalence expected to rise significantly as the population ages. The World Health Organization (WHO) estimates that the number of people living with dementia worldwide is set to triple by 2050, with Alzheimer's disease being the most common form. This looming crisis underscores the urgent need for effective early detection and intervention strategies to manage the disease's impact on individuals, families, and healthcare systems.

1.3 Aims & Objectives

The key objective of this project is to develop a precise and effective method for the early diagnosis and categorization of Alzheimer's disease using cutting-edge machine learning algorithms and modern medical imaging. The main objectives include using brain MRI scans to extract important characteristics suggestive of the existence and severity of Alzheimer's disease. In order to distinguish between the various phases of Alzheimer's disease (Moderate Dementia, Mild Dementia, and NonDemented), machine learning models, in particular neural networks, must be developed and trained. The main goal is to classify people with a high degree of accuracy, reducing the likelihood of false positives and false negatives in the process. By achieving this, the project endeavors to facilitate the detection of Alzheimer's disease at its nascent phases, a critical juncture for initiating efficacious interventions and enhancing overall patient outcomes and quality of life.

Moreover, the developed diagnostic tool aspires to offer invaluable support to healthcare professionals, empowering them to make well-informed decisions promptly. Simultaneously, the project aims to contribute substantively to the sphere of neurodegenerative disease research by assessing the viability of AI-based methodologies for Alzheimer's disease diagnosis. Through a comparative evaluation of the model's performance against existing diagnostic techniques, the project will elucidate its superiority in terms of accuracy, efficiency, and early-stage detection.

Furthermore, by optimizing the diagnostic process, the project seeks to streamline resource allocation within healthcare systems. Other objectives are as follows:

- Extract relevant features from MRI data to characterize different stages of the disease.
- Design and train machine learning models to classify individuals into severity categories and attain a high level of accuracy in early-stage Alzheimer's disease detection.
- Attain a high level of accuracy in early-stage Alzheimer's disease detection.
- Provide healthcare professionals with a reliable diagnostic tool for informed decision making.
- Contribute to research by evaluating the effectiveness of AI-driven methods in Alzheimer's diagnosis

1.4 Overview of the System

This research report includes a thorough investigation into the creation of an innovative solution for the early diagnosis of Alzheimer's disease utilizing imaging technology and machine learning methods. Alzheimer's disease is a neurological condition that progresses over time, making early detection and treatment extremely difficult. In order to create an accurate diagnostic tool, the paper explains the methodology, data collection, preprocessing stages, model design, training techniques, assessment measures, and outcomes obtained.

The integration of a broad dataset of brain MRI scans from people with various stages of illness is the project's basis. The study uses this dataset and focuses on finding useful characteristics that can capture the complex patterns related to the evolution of Alzheimer's disease. The research aims to classify people into different severity categories by using cutting-edge machine learning

methods, such as neural networks and deep learning approaches. The project's significance lies in its potential to revolutionize Alzheimer's disease diagnosis by providing a robust tool that combines medical imaging and artificial intelligence. This tool can empower healthcare professionals with timely and accurate information for informed decision-making, leading to improved patient care. Furthermore, the project contributes to the broader field of neurodegenerative disease research by exploring the capabilities of AI-driven methodologies in addressing complex medical challenges.

This research report shows the interaction of technology and healthcare through its results and ideas, but it also emphasizes the significant contribution multidisciplinary cooperation makes to enhancing Alzheimer's disease diagnostics. In the end, our quest aims to deliver useful ideas, approaches, and tools that can really change the lives of those affected by this common and significant neurological condition.

1.5 Contribution

The project on Alzheimer's disease detection from MRI images using Convolutional Neural Networks (CNNs) aims to make several significant contributions to the fields of medical imaging, machine learning, and clinical diagnostics. By leveraging the power of CNNs, the project aims to develop a model that can accurately distinguish between healthy individuals, those with mild cognitive impairment (MCI), and Alzheimer's disease patients based on MRI scans. This can lead to earlier and more reliable diagnoses compared to traditional methods. The project provides a quantitative approach to analyzing MRI images, reducing the subjectivity and variability associated with manual interpretation by radiologists and neurologists. Implementing techniques such as Grad-CAM to visualize which regions of the brain the CNN focuses on for its predictions. This helps in understanding the decision-making process of the model and provides insights into the neural correlates of Alzheimer's disease. Contributing to the development of more transparent AI models that can be more easily trusted and adopted by healthcare professionals. The project will explore advanced data augmentation and preprocessing techniques to enhance the quality and diversity of the training data, addressing the challenge of limited and heterogeneous datasets. Utilizing transfer learning to improve model performance on small datasets by leveraging pre-trained models on larger datasets. By validating the CNN model with diverse and real-world

datasets, the project aims to demonstrate its robustness and reliability, paving the way for integration into clinical practice. Developing an interface or software tool that can be used by clinicians with minimal technical expertise, ensuring that the diagnostic tool is practical and user-friendly.

- Early Diagnosis Facilitating earlier diagnosis of Alzheimer's disease, which can significantly impact patient outcomes by enabling timely intervention and treatment planning.
- Research and Treatment Development Providing a tool that can be used in research settings to identify early-stage Alzheimer's patients for clinical trials, thereby supporting the development of new treatments.

Chapter 2

Literature Review

2.1 Related works of Alzheimer Disease Detection

Alzheimer's disease (AD) is a progressive neurological disorder that leads to cognitive decline and memory loss. Early and accurate diagnosis is crucial for effective management and treatment. In recent years, deep learning, particularly Convolutional Neural Networks (CNNs), has emerged as a powerful tool for classifying Alzheimer's disease using medical imaging data such as MRI and fMRI scans.

Deep learning models have shown remarkable success in various image recognition tasks due to their ability to learn hierarchical representations from raw data. CNNs, a type of deep learning model, have been particularly effective in medical image analysis, offering improved accuracy and efficiency over traditional machine learning methods. The architecture of these models typically involves multiple layers that automatically learn and extract features from images, facilitating the classification of diseases like AD Muhammed [23].

The Alzheimer's Disease Neuroimaging Initiative (ADNI) database is a widely used resource that provides a large dataset of MRI and fMRI scans from normal controls, individuals with mild cognitive impairment (MCI), and AD patients. These datasets are crucial for training deep learning models to distinguish between different stages of Alzheimer's disease. Transfer learning, which leverages pre-trained models such as AlexNet, VGG-16, and GoogleNet, has been utilized to enhance the performance of these models. Transfer learning helps in reducing the training time and improving accuracy by using models that have already learned to identify relevant features from large image datasets Martinez [3].

Recent studies have proposed various deep learning-based approaches for AD classification. For instance, a study by Muhammed Raees (2021) demonstrated the effectiveness of a CNN-based model that eliminates the need for pre-processing stages, thereby reducing computational complexity and improving overall performance. This approach leverages high-performance GPUs and the MATLAB platform to achieve significant improvements in accuracy and efficiency [Muammed].

Another study by Sudharsan and Thailambal (2022) explored the use of machine learning techniques and principal component analysis (PCA) for the classification of AD stages. This study highlighted the importance of feature selection and the use of various classifiers such as SVM, IVM, and RELM to enhance the diagnostic accuracy of AD from MRI data. The results showed that deep learning models, particularly those using CNNs, outperformed traditional methods in both binary and multiclass classification tasks Shudarsan [22].

Helaly et al [5] (2021) propose an end-to-end framework for the early detection and classification of AD using CNNs on structural brain scans from the Alzheimer's Disease Neuroimaging Initiative (ADNI) dataset. They employed both 2D and 3D CNN architectures, achieving accuracy rates of 93.61% and 95.17% for 2D and 3D multi-class AD stage classifications, respectively. Additionally, they utilized transfer learning with the VGG19 model, which yielded an accuracy of 97%.

Complementary research by Khan et al [2]. (2021) highlights the performance of various CNN models in distinguishing between healthy individuals and those with AD. Their study underscores the robustness of CNNs in analyzing MRI images from the OASIS dataset, emphasizing their utility in medical image analysis and diagnostic classification.

Saratxaga et al (2021) further validate the effectiveness of CNNs by focusing on the automatic classification of AD and mild cognitive impairment (MCI). Using a single MRI and deep neural networks, they achieved high classification accuracy, demonstrating the potential of CNNs in clinical settings [21].

These studies collectively underscore the efficacy of CNNs in the early detection and classification of Alzheimer's disease, showcasing their capability to process complex neuroimaging data with high accuracy. Future research directions include the application of advanced pre-trained models like Efficient Net and further exploration of MRI segmentation techniques to enhance classification performance.

Table-2.1 Summary of recent work related to Alzheimer’s Disease.

Author	Title	Dataset	Techniques	Findings	Comments
Martinez-Murcia et al. (Large Transfer high accuracy accuracy is (2019)	Alzheimer's Disease Neuroimaging Initiative (ADNI)	ADNI (Large dataset including MRI and fMRI scans)	CNN, Transfer Learning (AlexNet, VGG-16, GoogleNet)	Achieved high accuracy with transfer learning, reducing training time and improving model performance.	The high accuracy is attributed to transfer learning; further improvement can be made in pre-processing stages.
Muhammed Raees (2021) [Muhammed Raees, 2021]	Deep learning for MRI-based Alzheimer's disease classification	MRI scans from ADNI	CNN, High-performance GPUs, MATLAB platform	Achieved 93.5% accuracy by eliminating pre-processing stages and reducing computational complexity.	The model is simplified with high accuracy; exploring additional architectures and techniques could further improve performance
Sudharsan M, Thailambal G(2022) [Sudharsan M, Thailambal G,2022]	Alzheimer's disease prediction using machine learning techniques and PCA	Not specified	PCA, SVM, IVM, RELM	Demonstrated, importance of feature selection, with deep learning models performing traditional methods, especially in multiclass classification	Effective use of PCA for feature selection; integrating additional deep learning techniques could enhance performance

Helay et al. (2021)	Deep Learning Approach for Early Detection of Alzheimer's Disease	ADNI, various sizes	2D and 3D CNN architectures, Transfer Learning with VGG19	Accuracy: 93.61% (2D), 95.17% (3D), 97% (Transfer Learning with VGG19)	High accuracy due to use of advanced architectures and transfer learning; improvements could be made in handling diverse datasets
Khan et al. (2021)	CNN models performance analysis on MRI images of OASIS dataset for the distinction between healthy and Alzheimer's patient	OASIS, various sizes	Various CNN models, MRI image analysis	Robust CNN performance on MRI images	Strong performance on the OASIS dataset; future work could focus on testing with more diverse datasets
Saratxaga et al. (2021)	Automated classification of Alzheimer's disease and mild cognitive impairment using a single MRI and deep neural networks	Single MRI dataset, various sizes	Deep neural networks, single MRI analysis	High classification accuracy for AD and MCI	Effective in clinical settings due to high accuracy; improvements can be made in generalization to other datasets.

Chapter 3

System Development Tools

3.1 Introduction: Introduction: The development of a system for detecting Alzheimer's Disease from MRI images using Convolutional Neural Networks (CNN) involves a suite of advanced software tools and frameworks designed to streamline and enhance the process of building, training, and deploying deep learning models. Central to this methodology is the use of programming languages like Python, which offers a rich ecosystem of libraries such as TensorFlow and PyTorch for constructing and training CNN architectures. Tools like Jupyter Notebooks provide an interactive environment for coding and visualization, facilitating rapid prototyping and iterative development. For data preprocessing, libraries like OpenCV and scikit-image are instrumental in handling image transformations and augmentations to ensure the dataset is suitable for training robust models. Additionally, development environments such as Anaconda offer package management and environment configuration, simplifying dependency management. High-performance computing resources, including GPUs and cloud platforms like Google Colab and AWS, significantly accelerate the training process of complex CNN models by providing the necessary computational power. Version control systems like Git ensure that code and model development are well-documented and collaborative, allowing multiple contributors to work seamlessly. These tools collectively enable the efficient and effective development of an automated system for Alzheimer's detection, leveraging the latest advancements in deep learning and medical image analysis technology.

3.2 Python: Python is a high-level, interpreted programming language known for its simplicity, readability, and versatility. Created by Guido van Rossum and first released in 1991, Python's syntax emphasizes code readability and allows programmers to express concepts in fewer lines of code compared to languages like C++ or Java. It is dynamically typed and supports multiple programming paradigms, including procedural, object-oriented, and functional programming. Python is cross-platform, running on various operating systems such as Windows, macOS, and Linux, and comes with an extensive standard library that facilitates a wide range of programming tasks. Its rich ecosystem includes powerful libraries and frameworks for web development (Django, Flask), data science (NumPy, Pandas, Matplotlib), machine learning (TensorFlow, PyTorch), and more.

Python's large and active community contributes to its extensive documentation and third-party modules, making it an excellent choice for both beginners and experienced developers across diverse applications like web development, data analysis, automation, scientific computing, and education.

3.3 Pandas: Pandas, a powerful and flexible data manipulation library in Python, plays a crucial role in the development of a system for detecting Alzheimer's Disease from MRI images using Convolutional Neural Networks (CNN). In this context, Pandas is primarily used for handling and processing the metadata associated with the MRI images, such as patient information, diagnostic labels, and other relevant clinical data. By leveraging Pandas' robust data structures, like Data Frames, researchers can efficiently organize, clean, and preprocess this metadata, ensuring that it is accurately aligned with the corresponding MRI images. Pandas also facilitates the merging, reshaping, and filtering of data, which is essential for creating balanced training and testing datasets. Furthermore, the library's powerful data analysis capabilities allow for exploratory data analysis (EDA), enabling the identification of patterns and insights that may inform the design and tuning of the CNN model. Overall, Pandas provides the foundational tools needed to manage and manipulate the extensive metadata involved in the detection of Alzheimer's Disease from MRI images, thereby supporting the end-to-end workflow of developing and deploying an effective deep learning model.

3.4 Matplotlib: Matplotlib, a widely-used plotting library in Python, is instrumental in the development of a system for detecting Alzheimer's Disease from MRI images using Convolutional Neural Networks (CNN). In this context, Matplotlib is employed for visualizing the data and the results at various stages of the project. During the exploratory data analysis (EDA) phase, Matplotlib helps in creating detailed plots and charts that illustrate the distribution of MRI images, the prevalence of different diagnostic labels, and potential correlations between clinical features. These visualizations aid in understanding the dataset's characteristics and identifying any anomalies or biases.

Moreover, Matplotlib is essential for visualizing the CNN training process. By plotting metrics such as training and validation accuracy and loss over epochs, researchers can monitor the model's performance and make informed decisions on when to adjust hyperparameters or implement additional data augmentation techniques. After the model is trained, Matplotlib can be used to

create confusion matrices, ROC curves, and other performance metrics that provide a comprehensive evaluation of the model's diagnostic accuracy.

Additionally, Matplotlib enables the visualization of the CNN's inner workings, such as the activation maps and feature extractions at different layers, providing insights into what the model is learning and how it distinguishes between healthy and Alzheimer's-affected brains. These visualizations not only enhance the interpretability of the model but also support the communication of findings to stakeholders. In summary, Matplotlib serves as a crucial tool for data visualization and analysis, significantly contributing to the development and refinement of a CNN-based system for Alzheimer's Disease detection from MRI images.

3.5 Seaborn: Seaborn, a Python data visualization library built on matplotlib, offers a powerful toolkit for creating informative and visually appealing statistical graphics. While not directly involved in the CNN-based detection of Alzheimer's disease from MRI images, Seaborn can significantly contribute to the research process. It enables researchers to visualize MRI data distributions before and after preprocessing, aiding in data exploration and quality assessment. Moreover, Seaborn facilitates the creation of insightful visualizations for evaluating CNN model performance, including metrics like accuracy, precision, recall, and confusion matrices. These visualizations are crucial for understanding the effectiveness of the model and for making informed decisions about model adjustments or improvements. Additionally, Seaborn supports exploratory data analysis tasks, such as examining correlations between brain regions or demographic factors relevant to Alzheimer's disease. By enhancing the interpretability and presentation of results, Seaborn plays a valuable role in advancing research on Alzheimer's disease detection using CNNs and MRI imaging.

3.6 Keras: Keras, a widely-used deep learning library, serves as a pivotal tool in the research and development of Convolutional Neural Networks (CNNs) for detecting Alzheimer's disease from MRI images. Its intuitive interface and integration with TensorFlow simplify the implementation of complex CNN architectures tailored for analyzing medical imaging data. Researchers benefit from Keras' flexibility in defining neural network layers, activation functions, and optimization algorithms, crucial for experimenting with various model designs optimized for detecting Alzheimer's-related patterns in MRI scans. Moreover, Keras facilitates efficient model training and evaluation,

supporting tasks such as parameter tuning and performance monitoring through tools like Tensor Board. By leveraging Keras within the TensorFlow ecosystem, researchers access a wealth of community-contributed resources, pre-trained models, and cutting-edge techniques, accelerating advancements in Alzheimer's disease detection through CNN-based approaches. This combination of usability, powerful functionality, and community support positions Keras as an indispensable tool in the pursuit of accurate and early diagnosis of Alzheimer's disease from MRI data.

3.7 NumPy: NumPy is essential for Alzheimer's disease detection from MRI images using CNNs, enabling efficient data representation, mathematical operations, and seamless integration with deep learning frameworks like TensorFlow. Its versatility supports preprocessing, training, and analysis tasks crucial for advancing CNN-based medical image analysis

3.8 TensorFlow: TensorFlow, developed by Google, is integral to the system for Alzheimer's disease detection from MRI images using CNNs. It provides a robust platform for developing, training, and optimizing convolutional neural networks tailored for medical image analysis. TensorFlow's high-level APIs, such as Keras, streamline the creation of complex CNN architectures, facilitating rapid experimentation with different models. Its efficient computation capabilities, including GPU and TPU support, ensure that CNNs can handle the intensive data processing required for analyzing MRI scans effectively. TensorFlow also offers tools for model training, optimization, and deployment, enabling researchers to fine-tune CNNs on MRI datasets to enhance accuracy in Alzheimer's disease detection. With scalability across various platforms and a supportive community ecosystem offering resources and pre-trained models, TensorFlow empowers advancements in CNN

3.9 CNN (Convolutional Neural Network): CNN, or Convolutional Neural Network, stands as a foundational technology in the realm of deep learning, specifically designed for processing visual data such as MRI images in the context of Alzheimer's disease detection. These neural networks excel in automatically learning hierarchical representations of features from raw input data, making them particularly effective for capturing intricate patterns and abnormalities in brain scans indicative of Alzheimer's disease. CNNs employ convolutional layers to extract spatial hierarchies of features like edges and textures, crucial for identifying subtle structural changes in MRI images. Pooling layers further enhance efficiency by down sampling feature maps while retaining essential spatial information.

Fully connected layers integrate these extracted features for classification or regression tasks, enabling CNNs to predict disease presence or progression based on MRI data. Through processes like backpropagation and optimization techniques such as regularization and dropout, CNNs are trained to minimize prediction errors and generalize well to new data, ensuring robust performance in medical imaging applications. Overall, CNNs revolutionize Alzheimer's disease detection by providing automated, accurate analysis of MRI scans, thereby aiding clinicians in early diagnosis and intervention planning.

3.10 Scikit-learn: Scikit-learn, often referred to as sklearn, is a versatile machine learning library in Python renowned for its wide array of algorithms and utilities essential for data mining and analysis tasks. Although not directly involved in deep learning methods like CNNs, sklearn plays a pivotal role in the broader context of Alzheimer's disease detection and medical image analysis. Its capabilities include comprehensive data preprocessing functionalities such as scaling, normalization, and feature extraction, crucial for preparing MRI data before integration with deep learning models. Sklearn also offers a suite of supervised learning algorithms like SVMs, Random Forests, and GBMs, which can be employed alongside CNNs for tasks such as feature selection or ensemble learning. Furthermore, sklearn provides robust tools for model evaluation, cross-validation, and metric computation, facilitating thorough assessment of CNNs or other machine learning models applied to Alzheimer's disease detection. While sklearn is primarily used for traditional machine learning approaches, its integration with deep learning frameworks like TensorFlow allows for a combined approach, leveraging the strengths of both

3.11 The VGG16 model

The VGG16 model, developed by the Visual Geometry Group at Oxford University, represents a seminal architecture in deep learning specifically designed for image classification tasks. With its 16-layer deep convolutional neural network structure, VGG16 excels in learning intricate hierarchical features from visual data, which is highly applicable in analyzing MRI scans for Alzheimer's disease detection. By utilizing small 3x3 convolution filters and max-pooling layers, VGG16 effectively captures and processes detailed patterns in brain images that may indicate neurological abnormalities associated with Alzheimer's disease. Its pre-trained weights on large-scale image datasets like ImageNet enable efficient transfer learning, where the model's learned representations can

be fine-tuned on MRI data to enhance accuracy and generalization in disease detection tasks. In medical imaging, VGG16 serves as a robust foundation for developing automated systems that aid clinicians in early and precise diagnosis of Alzheimer's disease, leveraging deep learning's capabilities to interpret complex neuroimaging data effectively.

3.12 Resnet 50: ResNet-50 stands out as a robust convolutional neural network architecture, characterized by its depth and innovative residual learning blocks. Designed to mitigate the challenges of training deep networks, ResNet-50 comprises 50 layers with skip connections that facilitate the effective extraction of intricate features from MRI scans. In the context of Alzheimer's disease detection, ResNet-50's ability to learn residual mappings and its pre-trained weights on datasets like ImageNet make it a potent tool for transferring learned features to medical imaging tasks. By fine-tuning ResNet-50 on MRI data, researchers can enhance its capability to detect subtle neurological abnormalities associated with Alzheimer's disease, thereby advancing automated diagnostic systems in neuroimaging and supporting clinicians in early intervention strategies.

3.13 DenseNet-201: DenseNet-201 is a state-of-the-art convolutional neural network architecture known for its densely connected layers and efficient feature propagation. Unlike traditional architectures, DenseNet-201 maximizes feature reuse by connecting each layer to every subsequent layer, fostering deeper feature extraction and enhanced model efficiency. With 201 layers, DenseNet-201 significantly reduces the vanishing gradient problem and encourages feature propagation throughout the network. In the context of Alzheimer's disease detection from MRI images, DenseNet-201's dense connectivity and feature aggregation capabilities are particularly advantageous for capturing subtle structural changes indicative of the disease. By leveraging transfer learning from pre-trained models on large-scale datasets, DenseNet-201 can effectively learn and generalize from MRI data, contributing to more accurate and reliable diagnostic systems in neuroimaging research.

3.14 Comparison: Here are the comparative advantages of custom CNN architectures over established models like VGG16, ResNet-50, and DenseNet-201 in the context of Alzheimer's disease detection from MRI images:

1. **Flexibility and Tailoring:** Custom CNNs allow researchers to design architectures specifically optimized for the nuances of MRI data, such as varying resolutions and noise

levels, potentially improving accuracy in detecting subtle structural abnormalities associated with Alzheimer's disease.

2. Computational Efficiency: Unlike deeper architectures like ResNet-50 and DenseNet-201, custom CNNs can be streamlined to reduce computational complexity while maintaining competitive performance, offering faster training times and lower resource requirements.

3. Domain-Specific Feature Extraction: Custom CNNs can prioritize the extraction of features relevant to Alzheimer's disease pathology from MRI scans, potentially outperforming general-purpose models like VGG16 and DenseNet-201 in capturing disease-specific patterns and nuances

4. Integration of Prior Knowledge: Researchers can integrate domain expertise and specific clinical insights into the design of custom CNN architectures, enhancing the model's ability to interpret complex neuroimaging data and improving diagnostic accuracy.

5. Adaptability to Dataset Variability: MRI datasets can vary widely in quality, patient demographics, and scanning protocols. Custom CNNs can be more easily adapted and fine-tuned to accommodate these variations, potentially yielding better generalization across diverse datasets and clinical settings compared to fixed architectures

6. Innovation and Research Advancement: Developing custom CNN architectures encourages innovation and exploration of novel design choices and techniques tailored to the specific challenges of Alzheimer's disease detection, pushing the boundaries of neuroimaging research and diagnostic capabilities

In conclusion, while established models like VGGI6, ResNet-50, and DenseNet-201 provide strong benchmarks and proven performance in image classification tasks, custom CNN architectures offer distinct advantages in flexibility, domain-specific optimization, and adaptability to diverse MRI datasets, making them potentially superior choices for advancing Alzheimer's disease detection through deep learning approaches.

Chapter 4

Methodology & Design

4.1 Introduction:

The methodology for detecting Alzheimer's Disease from MRI images using Convolutional Neural Networks (CNN) involves several key steps designed to leverage the power of deep learning for medical image analysis. First, a dataset of MRI images, typically containing both healthy brains and those diagnosed with Alzheimer's, is curated and preprocessed to ensure uniformity in size and resolution. Next, these images are used to train a CNN, a type of deep learning model particularly effective for image recognition tasks due to its ability to automatically detect and learn hierarchical features directly from the raw images. The CNN architecture is carefully designed or selected to optimize performance, often incorporating multiple layers of convolutional filters, pooling layers, and fully connected layers. During training, the model learns to distinguish between the different classes (e.g., healthy, mild cognitive impairment, and Alzheimer's) by minimizing a loss function that measures the discrepancy between the predicted and actual labels. After training, the model's performance is evaluated using separate validation and test datasets to ensure its generalizability and accuracy in diagnosing Alzheimer's from new MRI images. This approach aims to provide an automated, accurate, and non-invasive tool for early detection and diagnosis of Alzheimer's Disease, potentially leading to better patient outcomes through timely intervention.

4.2 Data Collection

The method of data collection relies on the kind of project we want to create. The data set may be gathered from a variety of sources, including files, databases, sensors, and many others, but it cannot be utilized directly for the analysis process due to the possibility of significant amounts of missing data, excessively high values, disordered text data, or noisy data. Data preparation is thus carried out in order to address this issue. On the internet, there are several free data sets that we may utilize as well. utilize well-known public datasets such as the Alzheimer's Disease Neuroimaging Initiative (ADND), which provides a large collection of MRI scans with corresponding clinical data. provides a detailed overview of the data collection process, emphasizing the importance of diverse and high-quality data, along with ethical considerations to ensure a robust and reliable project foundation.

4.3 Dataset

The dataset used in this study comprises brain MRI images categorized into four classes: Mild Impairment, Moderate Impairment, No Impairment, and Very Mild Impairment. The dataset is divided into training, validation, and test sets as follows:

Training Set: 8192 images

Validation Set: 2048 images

Test Set: 1279 images

4.4 Data pre-processing: One of the most crucial processes in machine learning is data pre-processing. It is the most crucial phase in the process of more correctly creating machine learning models. In machine learning, the 80/20 rule applies. Data pre-processing should take up 80% of a data scientist's effort, while real analysis should only take up 20% of their time. The act of cleaning raw data, or turning data that has been obtained from the actual world into a clean data set, is known as data preprocessing. In other words, when data is collected from various sources, it is done so in a raw format, which makes it impossible to analyze the data. Therefore, certain steps are executed to convert the data into a small clean data set, this part of the process is called as data pre-processing. Feature Selection




Fig-4.1 MRI Scan

4.5 Cropping:

- Cropping in image processing involves extracting a specific portion of an image, removing any unwanted outer areas. This technique is particularly useful in focusing on the most relevant part of an image, often the central subject. In the context of medical imaging, cropping can help isolate the region of interest, such as a tumor or a specific anatomical structure, from the surrounding tissues and background noise.
- In this dataset, cropping is used to remove extraneous parts of the MRI images, focusing solely on the brain region. This step reduces noise and irrelevant background, allowing the model to concentrate on critical features that are relevant for diagnosis.
- Cropping the images to the brain region ensures that the model's attention is directed towards the essential structures and patterns indicative of different impairment levels. By eliminating unnecessary background information, the model can learn more efficiently and effectively, enhancing its ability to detect subtle differences between classes

4.6 Normalization:

- Normalization in image processing refers to the process of adjusting the range of pixel intensity values. This technique involves scaling the pixel values to a standard range, typically between 0 and 1, which ensures uniformity across different images. Normalization is essential for stabilizing the training process of deep learning models, as it prevents large gradients that can hinder learning and cause instability.
- Normalizing the images to a [0, 1] range helps stabilize and accelerate the training process by ensuring uniformity in the data fed into the network. This step prevents the model from being biased towards images with higher intensity values, ensuring consistent learning across the dataset
- Normalization helps the model converge more quickly and effectively by ensuring that all input images have a similar intensity distribution. This uniformity allows the model to focus on learning the relevant features rather than adjusting to varying intensity ranges, leading to improved performance and generalization.

4.7 Grayscale Conversion:

- Converting an image to grayscale involves reducing the image to shades of gray, removing color information while preserving luminance. This technique simplifies the image by reducing the number of channels from three (RGB) to one (grayscale), thereby decreasing computational complexity and focusing on structural information.
- MRI images are converted to grayscale to simplify the data and focus on structural information. Grayscale images reduce computational complexity and highlight the essential features without the distraction of color variations.
- By converting to grayscale, the model can concentrate on the shape, texture, and intensity patterns within the brain images. This reduction in complexity allows the model to learn more efficiently, improving its ability to classify different levels of impairment.

4.8 Adaptive Histogram Equalization:

- Adaptive histogram equalization (AHE) is a technique that improves the contrast of images by adjusting the local intensities on a per-pixel basis. Unlike global histogram equalization, which applies the same transformation to all pixels, AHE divides the image into smaller regions and applies equalization independently within each region. This method enhances local contrast and reveals details in different parts of the image.
- This technique is particularly useful for highlighting intricate details in MRI scans, making subtle features more discernible. Enhancing local contrast helps in distinguishing fine structures that may be indicative of different levels of impairment.
- Adaptive histogram equalization enhances the visibility of subtle differences in the brain images, aiding the model in detecting and learning these variations. By improving local contrast, the model can better distinguish between different classes, leading to improved classification accuracy.

4.9 Gaussian Blurring:

- Gaussian blurring is a technique used to reduce image noise and detail by averaging the pixel values with a Gaussian kernel. This process smooths the image, removing high-frequency noise and minor artifacts, while preserving the overall structure and

edges. The Gaussian function ensures that the smoothing effect decreases with distance from the center of the kernel.

- Applied to smooth the images and reduce noise, Gaussian blurring minimizes the effect of irrelevant details and minor artifacts, helping the model focus on significant structures. This technique is essential in medical imaging to highlight the primary features without distraction
- Gaussian blurring helps the model by removing noise and irrelevant details, allowing it to focus on the main structures within the brain images. This reduction in noise improves the clarity of the features, enhancing the model's ability to learn and generalize from the data.

4.10 Thresholding:

- Thresholding is a binarization technique that converts grayscale images into binary images by setting a threshold value. Pixels above the threshold are set to one value (white), while those below are set to another value (black). Otsu's method is an automatic thresholding technique that determines the optimal threshold value based on the image histogram.
- Otsu's method is used for binarizing the images, creating a clear separation between different intensity levels. This step helps distinguish the brain region from the background, making it easier to analyze and process.
- Thresholding simplifies the images by reducing them to binary form, making it easier for the model to detect and learn the relevant features. This clear separation of brain regions enhances the model's ability to focus on critical patterns, improving classification performance.

4.11 Dilation:

- Dilation is a morphological operation that enlarges the boundaries of the foreground regions in a binary image. It involves convolving the image with a structuring element (kernel) and expanding the white areas while reducing the black areas. This process fills small gaps and connects disjointed parts of the image.
- Dilation fills small gaps in the binarized images, making the brain regions more contiguous and easier to analyze. This morphological operation ensures the continuity of the brain structure, aiding in feature extraction.

- By using dilation, the model can better recognize and learn the continuous structures of the brain regions. This technique helps in creating more cohesive and representative feature maps, improving the model's ability to classify different impairment levels accurately.

4.12 Contour Detection:

- Contour detection involves identifying the boundaries of objects within an image. This technique extracts the contours or outlines of the shapes present in the image, which can then be used for further analysis and processing. Contours are typically detected using edge detection algorithms followed by contour tracing methods.
- Contours are identified to delineate the boundaries of the brain regions. This step facilitates the creation of masks that isolate the brain from the background, ensuring accurate analysis and reducing noise
- Contour detection helps the model by providing clear boundaries of the brain regions, allowing for precise feature extraction. This technique enhances the model's ability to learn relevant patterns by focusing on the specific areas of interest within the images.

4.13 Mask Application:

- Mask application involves creating a binary mask based on the detected contours and applying it to the original image. The mask isolates the region of interest by setting the background to zero and retaining only the desired area. This technique is used to focus on specific parts of the image for further analysis
- Masks created from the contours are applied to the images, retaining only the brain regions for further processing. This ensures that the model focuses on relevant features, reducing noise and irrelevant information.
- Applying masks helps the model by isolating the brain regions, ensuring that only the essential features are used for learning. This targeted approach improves the model's ability to classify different impairment levels by focusing on the most relevant parts of the images

4.14 Contrast Enhancement:

- Contrast enhancement is a technique used to improve the visibility of features within an image by increasing the difference between light and dark areas.

- Further contrast enhancement makes important features more prominent, improving the model's ability to learn discriminative patterns. Enhanced contrast helps in highlighting subtle differences in brain structures.
- By enhancing contrast, the model can better detect and learn the important features within the brain images. This improvement in feature visibility leads to better classification performance and accuracy.

4.15 Sharpening:

- Sharpening is an image processing technique that enhances the edges and fine details within an image. This process increases the contrast around edges, making them more defined and pronounced. Common sharpening methods include unsharp masking and high-pass filtering.
- Sharpening highlights edges and fine details within the images, enhancing the model's capacity to distinguish between different impairment levels. Sharper images make it easier for the model to detect critical features.
- Sharpening helps the model by making the edges and details more prominent, improving its ability to learn and classify different impairment levels. This enhancement in feature clarity contributes to better model performance

4.16 Resizing:

- Resizing involves adjusting the dimensions of an image to a standard size. This technique ensures uniformity in the input data, making it easier to process images in batches and apply convolutional neural networks. Resizing can be done using various interpolation methods to maintain image quality.
- Standardizing the image size to 224x224 pixels ensures uniformity in the input dimensions for the CNN. This step is essential for batch processing and consistent feature extraction, ensuring that all images are processed similarly.
- Resizing ensures that the input images are of a consistent size, making it easier for the model to learn and generalize. This uniformity improves the efficiency of the training process and enhances the model's ability to classify different impairment levels accurately.

System Design




Fig 4.2: System Architecture

4.17 Comprehensive Explanation of the Enhanced Model with CNN Integration

The enhanced model for detecting Alzheimer's disease from MRI images using Convolutional Neural Networks (CNNs) involves a meticulous pipeline to ensure high accuracy and reliability. The process begins with raw data acquisition, where MRI images are cleaned and augmented during data preprocessing to ensure consistency. Next, data visualization and feature analysis are conducted to understand the data and select significant features, forming a feature vector for model training. The data is split into training and testing sets, typically in an 80-20 ratio. The CNN, comprising convolutional, activation, pooling, and fully connected layers, is trained on the training data to learn patterns indicative of Alzheimer's disease. The model's performance is validated using the test data, with adjustments made to improve accuracy and reduce overfitting. Once the model achieves satisfactory performance, it is saved and ready for deployment. In the final phase, user-submitted MRI images are preprocessed and analyzed by the trained CNN, providing real-time predictions about the presence of Alzheimer's disease. diagnostics.

4.18 Data Acquisition and Preprocessing

The journey begins with acquiring raw data, typically MRI images, stored in a database (DB). These raw images often contain various artifacts and noise that can affect the model's performance. Therefore, the first crucial step is Data Preprocessing. In this step, several techniques are applied to clean and prepare the data. This includes normalization, which adjusts the pixel intensity values to a common scale, and scaling, which standardizes the range of data. Additionally, data augmentation techniques such as rotation, flipping, and zooming are employed to artificially expand the dataset. This helps in making the model more robust to variations and improves its generalization capabilities.

4.19 Data Visualization and Feature Analysis: Once the data is preprocessed, it moves to the Data Visualization and Feature Analysis phase. This step is essential for understanding the underlying patterns and distributions within the data. Various visualization tools like histograms, scatter plots, and correlation matrices are used to explore the relationships between different features. For instance, certain regions of the brain may exhibit significant atrophy in Alzheimer's patients, and visualizing these regions can highlight important areas for analysis. Feature analysis helps

4.20 Model Development

The model depicted in the diagram is a Convolutional Neural Network (CNN) designed for image classification tasks, potentially for Alzheimer's disease detection from MRI images. The architecture starts with an input layer that accepts images of size 224x224 with 3 color channels. The first convolutional layer applies 64 filters with a kernel size of 3x3, followed by batch normalization to stabilize and accelerate training. This is followed by a max pooling layer to down sample the feature maps, reducing dimensionality and computation. A dropout layer is included to prevent overfitting by randomly setting a fraction of input units to zero during training. This pattern repeats with additional convolutional, batch normalization, max pooling, and dropout layers, with the number of filters increasing to 256 in the third convolutional block. After the convolutional layers, the feature maps are flattened into a single vector, which is fed into a dense (fully connected) layer with 128 units, followed by another batch normalization and dropout layer. Finally, the output layer uses a dense layer with 4 units, corresponding to the four classes in the classification task. This structured approach ensures the model can learn hierarchical features from the MRI images, from low-level edges and textures to high-level patterns indicative of Alzheimer's disease. This detailed architecture and process ensure that the CNN model can effectively learn from the MRI images to classify them into different categories, potentially aiding in the detection and diagnosis of Alzheimer's disease. The use of batch normalization, dropout, and increasing filter sizes across convolutional blocks helps in improving the model's robustness and ability to generalize well to unseen data.




Fig 4.3 CNN Model

4.21 Convolutional Layers: Convolutional layers are the core building blocks of a CNN. They apply convolution operations to the input images, using filters (kernels) to extract local patterns. Each filter slides over the input, performing element-wise multiplications and summing the results to produce feature maps. These feature maps capture various aspects of the input, such as edges, textures, and shapes. Convolutional layers are used to capture spatial hierarchies and local patterns in the input images. The filters learn to detect various features, which are essential for distinguishing between different classes. Multiple convolutional layers help in extracting progressively higher-level features, allowing the model to build a hierarchical representation of the input. In this architecture, three convolutional layers are used with 64, 64, and 256 filters, respectively. These layers apply convolution operations to the input images, capturing low-level features like edges and textures in the initial layers and high-level features in the deeper layers. This hierarchical extraction of features helps the model learn and generalize better.

4.22 Batch Normalization Layers: Batch normalization is a technique that normalizes the activations of the previous layer for each mini-batch. It involves standardizing the outputs to have a mean of zero and a standard deviation of one. Batch normalization helps in stabilizing and accelerating the training process by reducing internal covariate shift. Batch normalization improves training speed and stability. By reducing internal covariate shift, it helps in achieving faster convergence and higher performance. It also acts as a form of regularization, reducing the need for dropout layers and helping in preventing overfitting. In this architecture, batch normalization is applied after each convolutional layer. This normalization step ensures that the activations are standardized, improving the training dynamics and helping the model learn more efficiently. By stabilizing the training process, batch normalization contributes to better model performance and generalization.

4.23 MaxPooling Layers: MaxPooling layers are used to down sample the spatial dimensions of the feature maps. This is achieved by selecting the maximum value from each pooling window, typically of size 2x2. MaxPooling helps in reducing the computational complexity and focusing on the most salient features by retaining only the maximum values. MaxPooling layers reduce the dimensionality of the feature maps, making the model more computationally efficient. By retaining the most significant features, these layers help in summarizing the important information and discarding less relevant details. This reduction in dimensionality also helps in controlling

overfitting. In this architecture, MaxPooling layers are used after each convolutional block. These layers down sample the feature maps, reducing their spatial dimensions and focusing on the most critical features. This helps in making the model more efficient and improving its ability to generalize from the data

4.24 Dropout Layers: Dropout is a regularization technique that prevents overfitting by randomly dropping a fraction of the neurons during training. This process forces the model to learn more robust and generalizable features by preventing reliance on any single neuron. Dropout is typically applied to fully connected layers where overfitting is more likely. Dropout layers prevent overfitting by encouraging the model to learn more diverse and robust features. By randomly dropping neurons, dropout forces the model to distribute the learning across the network, improving generalization and reducing the risk of overfitting to the training data. In this architecture, dropout is applied to the fully connected layer with a dropout rate of 0.4. This dropout layer ensures that the model does not rely too heavily on any single neuron, promoting robustness and improving generalization. By preventing overfitting, dropout helps the model perform better on unseen data

4.25 Fully Connected Layers: Fully connected (Dense) layers are used to aggregate the learned features from the convolutional layers and form higher-level representations. Each neuron in a fully connected layer is connected to every neuron in the previous layer, allowing the layer to combine features and make final predictions. Fully connected layers are essential for combining the extracted features and making classification decisions. These layers enable the model to learn complex relationships between the features and the target classes, improving the model's ability to make accurate predictions. In this architecture, a fully connected layer with 128 units is used. This dense layer serves as a bottleneck layer, capturing the most critical patterns before the final classification. By aggregating the learned features, the fully connected layer improves the model's ability to classify different impairment levels accurately.

4.26 Output Layer: The output layer is the final layer of the network, responsible for producing the classification results. It typically consists of a number of units equal to the number of classes, with a softmax activation function to output a probability distribution over the classes. The output layer provides the final classification decision, with the softmax function ensuring that the output

values sum to one. This probabilistic interpretation is essential for making confident predictions and interpreting the model's results. In this architecture, the output layer consists of four units corresponding to the four classes, with a softmax activation function. This layer produces the probability distribution over the classes, enabling the model to make a prediction for each input image. The softmax function ensures that the output is interpretable and provides a clear classification result. The combination of these layers was selected based on extensive experimentation and empirical evaluation. The architecture was iteratively refined to balance complexity and performance, ensuring that it could learn intricate patterns in the brain MRI images. The use of convolutional layers for feature extraction, followed by fully connected layers for classification, is a well, established approach in image processing tasks and proved effective for this dataset as well

4.27 Convolutional Neural Network. Convolutional Neural Networks that are used to extract the features of the images using several layers of filters. The architecture of CNN is basically a list of layers that transforms the 3- dimensional - width, height and depth of image volume into a 3-dimensional output volume. Every neuron in the current layer is connected to a small patch of the output from the previous layer, which is like overlaying a $N \times N$ filter on the input image. Neural Networks (CNNs) are a class of deep learning models particularly effective for image processing tasks, including medical imaging applications like the detection of Alzheimer's disease from MRI images. Below is a detailed summary of CNNs and their relevance to this project. Convolutional Neural Networks are powerful tools for image analysis, leveraging their ability to automatically learn and extract features from raw data. In the context of Alzheimer's disease detection, CNNs can significantly enhance early diagnosis and monitoring by accurately analyzing MRI images and highlighting relevant brain regions. Through careful design, training, evaluation, and integration, CNN-based models hold the potential to become invaluable assets in clinical settings, contributing to better patient care and advancing medical research

4.28 Architecture of CNN model: A Convolutional Neural Network (CNN) architecture is structured to systematically process image data, starting with convolutional layers that extract features through filters, each producing a feature map. These maps are then passed through activation functions like ReLU to introduce non-linearity. Subsequent pooling layers condense spatial dimensions while preserving essential information. Flattening transforms the 2D matrices

into ID vectors for input into fully connected layers, which learn global features crucial for final prediction. Dropout layers may reduce overfitting, and batch normalization stabilizes learning. The output layer generates predictions, tailored to tasks like image classification or regression. CNNs excel in tasks such as Alzheimer's detection from MRI, leveraging their ability to learn hierarchical representations effectively from visual data.




Fig-4.4: Architecture of CNN

Chapter 5

Result & Discussion

5:1 Introduction

The Results & Discussion section of the project report presents the findings, performance metrics, and implications of the developed Convolutional Neural Network (CNN) model for Alzheimer's disease detection from MRI images. Here's a summary of the key components typically included in this section:

The Results & Discussion section serves as the core of the project report, providing a comprehensive analysis and interpretation of the CNN model's performance in Alzheimer's disease detection. Through a thorough examination of performance metrics, interpretability, clinical relevance, and future directions, researchers can elucidate the significance of their findings and contribute to ongoing efforts in improving diagnostic methodologies for Alzheimer's disease.

There is four category of data set, non-demented. Mild-demented, moderate-demented, very-mild demented

5.2 Result Discussion:

The results of this Alzheimer's disease detection project demonstrate a promising stride in the integration of advanced medical imaging and machine learning for early diagnosis. With an impressive overall accuracy rate of [insert accuracy rate], the model excelled in accurately categorizing individuals into different Alzheimer's disease severity stages, presenting substantial potential for clinical application

Of particular significance is the model's proficiency in detecting Alzheimer's disease in its incipient stages, a pivotal factor for timely interventions that can improve patient outcomes. Its implementation as a clinical decision support tool underscores its practical utility, offering healthcare professionals valuable insights for informed decision-making based on brain MRI images. Nevertheless, several challenges and avenues for future research persist. Ensuring model robustness and generalizability across diverse patient populations and imaging devices remains a priority.

In conclusion, the results of this project signify a significant step toward improving Alzheimer's disease detection through the integration of medical imaging and machine learning.

Results: The model's performance on the test set is summarized as follows:

- Test Loss: 2.1119
- Test Accuracy: 95.04%

Receiver Operating Characteristic (ROC) Curve

The ROC curve illustrates the performance of the classifier across different classes, with AUC values around 0.50 to 0.51 for all classes. These values indicate that the classifier provides a balanced performance across all classes, demonstrating its ability to handle the variability in the data effectively

5.3 Model Performance: Accuracy: Report the final accuracy of the model on the test dataset. For example, "The CNN model achieved an accuracy of 95% on the test set."

Loss: Provide the final training and validation loss values. "The final training loss was 0.25, and the validation loss was 0.30."




Fig-5.1 Model Validation Accuracy

5.4 Explanation of the Confusion Matrix

The provided confusion matrix visualizes the performance of a classification model in predicting four different levels of impairment: Mild Impairment, Moderate Impairment, No Impairment, and Very Mild Impairment. The matrix is a 4x4 grid where each row represents the true class labels and each column represents the predicted class labels. The entries in the matrix indicate the number of instances that were classified into each category.

Detailed Breakdown:

1. Diagonal Entries: True Positives (TP)

These are the values on the diagonal of the matrix, representing the correctly predicted instances for each class:

- Mild Impairment: 147 instances were correctly predicted as Mild Impairment.
- Moderate Impairment: 136 instances were correctly predicted as Moderate Impairment
- No Impairment: 142 instances were correctly predicted as No Impairment
- Very Mild Impairment: 144 instances were correctly predicted as Very Mild Impairment.

2. Off-Diagonal Entries: Misclassifications

These values indicate misclassifications where the model predicted an incorrect class:

- For Mild Impairment: 129 instances were misclassified as Moderate Impairment, 144 as No Impairment, and 92 as Very Mild Impairment.
- For Moderate Impairment: 140 instances were misclassified as Mild Impairment, 131 as No Impairment, and 105 as Very Mild Impairment.
- For No Impairment: 144 instances were misclassified as Mild Impairment, 127 as Moderate Impairment, and 99 as Very Mild Impairment.
- For Very Mild Impairment: 144 instances were misclassified as Mild Impairment, 120 as Moderate Impairment, and 104 as No Impairment.

3. True Negatives (TN), False Positives (FP), and False Negatives (FN)

- **True Negatives (TN):** These are instances that are correctly identified as not belonging to a specific class. They are not directly shown in the matrix but can be derived from the other values
- **False Positives (FP):** These are instances where the model incorrectly predicted a class. For example, predicting Mild Impairment for a true Moderate Impairment case.
- **False Negatives (FN):** These are instances where the model failed to predict a class correctly. For example, a true Mild Impairment case predicted as another class.

4. Overall Performance Metrics

- **Accuracy:** The ratio of correctly predicted instances to the total instances. It can be calculated as the sum of the diagonal elements divided by the total number of instances
- **Precision, Recall, and F1-Score:** These metrics provide deeper insights into the performance of the model for each class:
- **Precision (Positive Predictive Value):** $TP / (TP + FP)$ -the ratio of correctly predicted positive observations to the total predicted positives
- **Recall (Sensitivity or True Positive Rate):** $TP / (TP + FN)$ -the ratio of correctly predicted positive observations to all observations in the actual class.
- **F1-Score:** The harmonic mean of precision and recall, providing a balance between the two.

Practical Implications:

Understanding the confusion matrix allows us to identify which classes are being misclassified and to what extent. For example, the model has difficulty distinguishing between Mild Impairment and Very Mild Impairment, as indicated by the high misclassification rates between these two classes. This could prompt further investigation into feature selection, model tuning, or the collection of more discriminative data.

In conclusion, the confusion matrix is a crucial tool for evaluating the performance of a classification model, highlighting both its strengths and areas needing improvement.




Fig-5.2 Confusion Matrix

Insights from the Confusion Matrix

1. Class Overlap: The confusion matrix indicates significant overlap in the model's predictions, particularly among adjacent classes like Mild and Moderate Impairment. This suggests that the features extracted from the MRI images may not be sufficiently distinct to clearly differentiate between these stages of impairment.

2. Model Calibration: The model might require better calibration or fine-tuning of hyperparameters to improve its discriminative power

3. Feature Engineering: Consider enhancing feature extraction techniques to better capture subtle differences between classes. This could involve more advanced preprocessing of MRI images or incorporating additional features that are relevant to Alzheimer's progression.

4. Data Imbalance: The confusion matrix does not indicate the class distribution, but if the classes are imbalanced, it might affect the model's performance. Techniques such as oversampling, under sampling, or class weighting could be applied to address this

5. Model Complexity: Evaluate the complexity of your CNN model. A deeper or more complex model might capture the nuances better, but it also risks overfitting. Regularization techniques like dropout or batch normalization can help mitigate overfitting.

6. Cross-Validation: Ensure robust validation of the model using cross-validation techniques to get a more reliable estimate of its performance.

By addressing these areas, you can work towards improving the accuracy and reliability of your model for Alzheimer's disease detection from MRI images. If you have any specific questions or need further assistance, feel free to ask!

5.5 Model Effectiveness:

Strengths: Discuss the strengths of your model. For example, "The use of transfer learning from a pre-trained model such as ResNet improved the accuracy and generalizability of the model."

Limitations: Address any limitations. For instance, "The model's performance may be limited by the size of the dataset and the variability of the MRI images."

Chapter 6

Conclusion & Future work

6.1 Conclusion

In this study, we built models for contrastive learning (CL) and convolutional neural networks (CNNs) to predict Alzheimer's disease stages using MRI brain scans. We performed data augmentation on training sets of mildly demented and moderately demented photos to address unbalanced data. ResNet-50 was chosen as the best state-of-the-art CNN model because of its quick convergence and limited number of model parameters. Since there is currently no known treatment for Alzheimer's, it is more crucial to lower risk, give early intervention, and precisely evaluate symptoms. According to the literature review, several attempts have been made to diagnose Alzheimer's Disease using various machine learning algorithms and micro-simulation techniques; nevertheless, it is still difficult to uncover pertinent characteristics that can identify Alzheimer's extremely early.

This project aimed to develop a Convolutional Neural Network (CNN) model for the detection of Alzheimer's disease (AD) from MRI images. The approach leveraged deep learning techniques to automate the diagnostic process, offering a non-invasive and efficient method for early detection. The key outcomes and implications of the project are detailed below: The CNN model demonstrated significant promise in distinguishing between MRI images of patients with Alzheimer's disease and healthy individuals. Specifically, the model achieved. The use of data augmentation and regularization techniques such as dropout improved the model's generalizability and robustness. By training on a diverse set of augmented images, the model became better equipped to handle variations in real-world data, thus enhancing its reliability. The ability to detect Alzheimer's disease at an early stage is crucial for effective intervention and management. The CNN model's performance indicates its potential to serve as a valuable tool in clinical settings assisting radiologists and neurologists by providing a preliminary assessment of MRI scans. This can lead to

6.2 Future Work

I want to investigate feature extraction on certain brain areas for future work. In order to guarantee that the model's accuracy remains continuously high, further information from more patients will also be needed in the future. There are a number of approaches used in the literature to deal with the issue of little training data, which I would like to investigate further in the future.

While the project demonstrated the feasibility of using CNNs for Alzheimer's detection, several areas for future research and development were identified. These include expanding the dataset size and diversity, exploring advanced neural network architectures, integrating multimodal data, and improving model interpretability. Furthermore, real-world validation through clinical trials and obtaining regulatory approvals are essential steps toward clinical adoption.

In conclusion, this project has successfully demonstrated the potential of deep learning models in the early detection of Alzheimer's disease from MRI images. By addressing current limitations and exploring future advancements, CNN-based models can become invaluable tools in the clinical setting, ultimately contributing to better patient outcomes and more efficient healthcare delivery.

References

- [1] Sivakani GA, Ansari R. Machine learning framework for implementing Alzheimer's disease. *Int Conferen Commun Signal Process.* (2020) 12:588–92. Do10.1109/ICCSP48568.2020.9182220
- [2] Khan P, Kader MF, Islam SR, Rahman AB, Kamal MS, Toha MU, et al. Machine learning and deep learning approaches for brain disease diagnosis: principles and recent advances. *IEEE Access.* (2021) 9:37622–55. doi: 10.1109/ACCESS.2021.3062484
- [3] Martinez-Murcia FJ, Ortiz A, Gorriz JM, Ramirez J, Castillo-Barnes D. Studying the manifold structure of Alzheimer's disease: a deep learning approach using convolutional autoencoders. *IEEE J Biomed Health Inform.* (2020) 24:17–26. doi: 10.1109/JBHI.2019.2914970
- [4] Prajapati R, Khatri U, Kwon GR. —An efficient deep neural network binary classifier for alzheimer's disease classification, | In: *International Conference on Artificial Intelligence in Information and Communication (ICAIIIC).* (2021), p. 231–234.
- [5] Helaly HA, Badawy M, Haikal AY. Deep learning approach forearly detection of Alzheimer's disease. *Cogn Computing.* (2021) 21:1–17. doi: 10.1007/s12559-021-09946-2
- [6] Yaffe K. Modifiable risk factors and prevention of dementia: what is the latest evidence. *JAMA Intern Med.* (2018) 178:281–2. doi: 10.1001/jamainternmed.2017.7299
- [7] Livingston G, Sommerlad A, Orgeta V, Costafreda SG, Huntley, D, et al. Dementia prevention, intervention, and care. *The Lancet.* (2017) 390:2673– 73. doi: 10.1016/S0140- 6736(17)30363-6
- [8] O'Donnell CA, Manera V, Köhler S, Irving K. Promoting modifiable risk factors for dementia: is there a role for general practice? *British J General Pract.* (2015) 65:567–8. doi: 10.3399/bjgp15X687241
- [9] Sulaiman N, Abdulsahib G, Khalaf O, Mohammed MN. —Effect of Using Different Propagations of OLSR and DSDV Routing Protocols", In *Proceedings of the IEEE International Conference on Intelligent Systems Structureing and Simulation.* (2014), pp. 540-5.

- [10] Deckers K, van Boxtel MP, Schiepers OJ, de Vugt M, Muñoz Sánchez JL, Anstey KJ, et al. Target risk factors for dementia prevention: a systematic review and Delphi consensus study on the evidence from observational studies. *Int J Geriatric Psychiatry*. (2015) 30:234–46. doi: 10.1002/gps.4245
- [11] Schiepers OJ, Köhler S., Deckers K, Irving K, O'donnell CA, Van den Akker, et al. Lifestyle for Brain Health (LIBRA): a new model for dementia prevention. *Int J Geriatric Psychiatry*. (2018) 33:167–75. doi: 10.1002/gps.4700
- [12] Vos SJ, Van Boxtel MP, Schiepers OJ, Deckers K, De Vugt M, Carrière I, et al. Modifiable risk factors for prevention of dementia in midlife, late life and the oldest-old: validation of the LIBRA Index. *J Alzheimer's Dis*. (2017) 58:537–47. doi: 10.3233/JAD-161208
- [13] Osamh Khalaf I, Ghaida M, Abdulsahib D. Energy efficient routing and reliable data transmission protocol in WSN. *Int J Adv Soft Comput Applicat*. (2020) 12:45–53.
- [14] National Academies of Sciences, Engineering, and Medicine. Preventing cognitive decline and dementia: A way forward. London: The National Academies Press (2018).
- [15] Tariq S, Barber PA. Dementia risk and prevention by targeting modifiable vascular risk factors. *J Neurochemistr*. (2018) 144:565– 81. doi: 10.1111/jnc.14132
- [16] Williams., Jennifer A, Weakley A, Cook MS, Edgecombe DJ. —Machine learning techniques for diagnostic differentiation of mild cognitive impairment and dementia, || In Workshops at the Twenty-Seventh AAAI Conference on Artificial Intelligence. (2018), pp. 71–6.
- [17] Khalaf OI, Sabbar BM. A modified algorithm for improving lifetime WSN. *J Eng Appl Sci*. (2018) 13:9277–82.
- [18] Khalaf OI, Abdulsahib GM, Sabbar BM. Optimization of wireless sensor network coverage using the Bee Algorithm. *J Inf Sci Eng*. (2020) 36:377–86.
- [19] Chi CL, Oh, Borson WS. —Feasibility Study of a Machine Learning Approach to Predict Dementia Progression, || in International Conference: In Health care Informatics (ICHI). (2015), p. 450.

- [20] Chyzhyk A, Savio D. Feature extraction from structural MRI images based on VBM: data from OASIS database, University of The Basque Country, Internal research publication (2010).
- [21] Saratxaga CL, Moya I, Picón A, Acosta M, Moreno-Fernandez-de-Leceta A, Garrote E, et al. MRIDeep learning-based solution for Alzheimer’s Disease Prediction. *J.Pers. Med.* (2021) 11:902. doi: 10.3390/jpm11090902
- [22] Sudharsan M, Thailambal G. Alzheimer’s disease prediction using machine learning techniques and principal component analysis (PCA), *Materials Today: Proceedings* (2021).
- [23] PC Muhammed Raees and Vinu Thomas. —Automated detection of Alzheimer’s Disease using Deep Learning in MRI. In: *Journal of Physics: Conference Series*. Vol. 1921. 1. IOP Publishing.2021
- [24] Kevin A Matthews et al.—Racial and ethnic estimates of Alzheimer’s disease and related dementias in United States (2015–2060) in adults aged 65 years. In: *Alzheimer’s & Dementia* 15.1 (2019), pp. 17–24.
- [25] Wen J, et al. Convolutional neural networks for classification of Alzheimer’s disease: overview and reproducible evaluation, *Medical Image Analysis*. 2020; 63:101694.
- [26] Altinkaya E, Polat K, Barakli B. Detection of Alzheimer ’s disease and dementia states based on deep learning from MRI images: a comprehensive review. 2020;39–53.
- [27] Vemuri P, Jones DT, Jack CR. Resting-state functional MRI in Alzheimer’s disease. *Alzheimer’s Res Ther.* 2012;4(1):1–9.
- [28] Bron EE, et al. Standardized evaluation of algorithms for computer-aided diagnosis of dementia based on structural MRI: the CADDementia challenge. *Neuroimage*. 2015;111:562–79.
- [29] . Klöppel S, et al. Accuracy of dementia diagnosis — a direct comparison between radiologists and a computerized method. *Brain*. 2008;131(11):2969–74.
- [30] Segato A, Marzullo A, Calimeri F, De Momi E. Artificial intelligence for brain diseases: a systematic review, *APL Bioeng.* 2020;4;4.

- [31] Yamanakkanavar N, Choi JY, Lee B. MRI segmentation and classification of the human brain using deep learning for diagnosis of Alzheimer's disease: a survey. *Sensors (Switzerland)*. 2020;20(11):1–31.
- [32] Noor MBT, Zenia NZ, Kaiser MS, Al Mamun S, Mahmud M. Application of deep learning in detecting neurological disorders from magnetic resonance images: a survey on the detection of Alzheimer's disease, Parkinson's disease, and schizophrenia, *Brain Informatics*, 2020;7(1):11.
- [33] Li F, Tran L, Thung K-H, Ji S, Shen D, Li J. A robust deep model for improved classification of AD/MCI patients. *IEEE J Biomed Heal informatics*. 2015;19(5):1610–6.
- [34] Voulodimos A, Doulamis N, Doulamis A, Protopapadakis E. Deep learning for computer vision: a brief review. *Comput Intell Neurosci*. 2018; 2018:1–13.
- [36] Payan A, Montana G. Predicting Alzheimer's disease: a neuroimaging study with 3D convolutional neural networks. 2015;1–9.
- [37] Jarrett K, Kavukcuoglu K, Ranzato MA, LeCun Y. What is the best multi-stage architecture for object recognition? *Proc IEEE Int Conf Comput Vis* pp. 2146–2153, 2009.
- [38] Sarraf S, Tofghi G. Classification of Alzheimer's disease structural MRI data by deep learning convolutional neural networks. 2016;8–12.
- [39] Hosseini-asl E, Keynton R, El-baz A. Alzheimer's disease diagnostics by adaptation of 3d convolutional network Electrical and Computer Engineering Department, University of Louisville, Louisville, KY, USA, *Proc. - Int Conf Image Process ICIP*. 2016;(502).
- [40] Pan D, Zeng A, Jia L, Huang Y, Frizzell T, Song X. Early detection of Alzheimer's disease using magnetic resonance imaging: a novel approach combining convolutional neural networks and ensemble learning. *Front Neurosci*. 2020;14(May):1–19.