

**Bangladesh Army International University of Science & Technology**  
**Department of Computer Science and Engineering**

**Lab Report**

<b>Lab Report No</b>	<b>04</b>						
<b>Lab Report Name</b>	<b>Implementation of Dijkstra's Algorithm</b>						
<b>Course Title</b>	<b>Computer Algorithms &amp; Complexity Sessional</b>						
<b>Course Code</b>	<b>CSE 222</b>						
<b>Name</b>	Rayhan Alam Towhid						
<b>ID</b>	1119007						
<b>Level</b>	2	<b>Term</b>	II	<b>Section</b>	A	<b>Group</b>	G1
<b>Date of Submission</b>	02-11-2025			<b>Session</b>	Fall-2025		

**Marking Rubric:**

<b>Problem Understanding &amp; Report Clarity (3)</b>	<b>Implementation (5)</b>	<b>Results &amp; Analysis (2)</b>	<b>Total (10)</b>

## Key Learnings:

I have learned how to count equal items using a frequency array. I have understood that a regular polygon needs at least three sticks of the same length and learn to divide the sticks into groups of three to find how many polygons you can form. Finally, I have combined all groups to get the total number of polygons possible.

## Code Implementation:

```
1  #include <iostream>
2  using namespace std;
3
4  void quickSort(int arr[], int low, int high)
5  {
6      if (low > high)
7          return;
8
9      int pivot = arr[high];
10     int i = low;
11
12     for (int j = low; j < high; j++)
13     {
14         if (arr[j] < pivot)
15         {
16             int temp = arr[i];
17             arr[i] = arr[j];
18             arr[j] = temp;
19             i++;
20         }
21     }
22
23     int temp = arr[i];
24     arr[i] = arr[high];
25     arr[high] = temp;
26
27     quickSort(arr, low, i - 1);
28     quickSort(arr, i + 1, high);
29 }
30
31 int main()
32 {
33     int arr[] = {64, 34, 25, 12, 22, 11, 90, 5};
34     int size = sizeof(arr) / sizeof(arr[0]);
35
36     quickSort(arr, 0, size - 1);
37
38     for (int i = 0; i < size; i++)
39     {
40         cout << arr[i] << " ";
41     }
42     cout << endl;
43
44     return 0;
45 }
```

## Sample Input - Output:

### →Judgement Protocol

Test: #1, time: 31 ms., memory: 0 KB, exit code: 0, checker exit code: 0, verdict: OK

Input

```
4
1
1
2
1 1
6
2 2 3 3 3 3
9
4 2 2 2 2 4 2 4 4
```

Output

```
0
0
1
2
```

Answer

```
0
0
1
2
```

Checker Log

```
ok 4 number(s): "0 0 1 2"
```

Test: #2, time: 31 ms., memory: 0 KB, exit code: 0, checker exit code: 0, verdict: OK

Input

```
100
2
1 1
4
1 1 1 1
7
1 1 1 1 1 1 1
```

## Result Analysis / Discussion:

In this problem, we use a frequency array to count how many sticks of each length we have. Since a regular polygon needs at least three equal-length sticks, we divide the count of each length by three to find out how many polygons can be formed. Adding all these gives the maximum number of polygons possible. This teaches counting, grouping, and simple logical reasoning with constraints.