

Bridge Substructures: Advanced Monitoring Technologies and Real- World Applications (2020-2025)

by

Raylen Williams

Civil and Environmental Engineering Department

Prairie View A&M University

ABTC Project

Dr. R. Radhakrishnan

9.26.2025

Table of Contents

Abstract	3
1. Understanding Bridge Substructures: The Hidden Foundation	3
1.1 What Are Bridge Substructures?	3
1.2 The Challenge of Monitoring Hidden Structures	4
2. Revolutionary Monitoring Technologies	4
2.1 Sonar Technology: Seeing Through Water	4
2.2 Ultrasonic Testing: Listening Inside Concrete	7
3. Real-World Case Studies: Measuring Actual Damage	11
3.1 Missouri Bridge Robotic Underwater Inspection (2024)	11
3.2 Kelanisiri Bridge Scour Analysis (2024)	11
3.3 I-95 Bridge Foundation Analysis (2024)	12
3.4 Skerries Pier Steel Pile Assessment (2021)	12
3.5 Illinois Scour Monitoring Implementation (2024)	13
4. Cost Analysis: Investment vs. Safety Returns	14
4.1 Technology Investment Comparison	14
4.2 Return on Investment Through Damage Prevention	14
5. Climate Considerations and Technology Selection	15
5.1 Environmental Factors Affecting Technology Performance	15
5.2 Technology Selection Based on Specific Conditions	15
6. Technology Limitations and Realistic Expectations	16
6.1 Understanding System Capabilities	2
6.2 When Multiple Technologies Are Necessary	22
7. The Future of Substructure Monitoring	22
7.1 Emerging Integration Capabilities	22
7.2 Cost-Effectiveness Improvements	23
8. Recommendations for Implementation	23
8.1 Prioritizing Bridges for Advanced Monitoring	23
8.2 PVAMU Implementation Strategy	24
9. Conclusion	24
10. References	25

Abstract

This comprehensive report focuses exclusively on the underground and underwater parts of bridges, called substructures. Think of a bridge like a tree what you see above ground (the road deck) is like the branches and leaves, but the real strength comes from what's hidden below the surface. Bridge substructures include all the concrete foundations, steel piles, pile caps, and columns that hold up the entire bridge from underneath the water or ground.

1. Understanding Bridge Substructures: The Hidden Foundation

1.1 What Are Bridge Substructures?

Bridge substructures are the critical support elements that you cannot see from the road above. These include several key components that work together like the foundation of a house but are much more complex because they must handle enormous weights and forces from traffic, wind, and water.

Piles are like giant concrete or steel poles driven deep into the ground or riverbed, sometimes reaching 30 to 60 feet deep. **Pile caps** are thick concrete slabs that sit on top of groups of piles, spreading the bridge's weight across multiple piles like a platform. Piers are the visible columns that rise from pile caps to support the bridge deck above water. **Foundations** include all the concrete footings and supports that transfer the bridge weight to the solid ground below. **Bridge Pier** This is the tall vertical column that supports the bridge deck above; it transfers loads from the bridge traffic and decks down into the ground or riverbed. **Ground Penetrating Radar**: A sensor placed near the pier that sends waves through water and ground to find voids, cracks, or areas where material is missing near or beneath the pier. **Sonic Fathometer** A device attached to the pier that uses sound waves to measure the distance to the bottom of the riverbed or scour hole, tracking how much material has been washed away. **Magnetic Sliding Collar** Mounted to the pier at the sediment level. It moves down as the scour gets worse; its change in position tells engineers how much material was lost. **Float-Out Device** Anchored near the pier, this sensor floats up and away if the riverbed erodes badly under the foundation, giving an early alert to hidden danger.

Accelerometer: Attached to the pier, this tool senses tiny shifts or vibrations so engineers can detect if the pier is moving or settling, which might mean a problem in the substructure. [1,2,3]




Figure 1. Schematic of bridge substructure monitoring technologies including sonar, ground penetrating radar, accelerometer, and data logging for scour and foundation health assessment.[4]

1.2 The Challenge of Monitoring Hidden Structures

The biggest challenge with bridge substructures is that most problems occur where nobody can see them underwater or underground. Unlike checking a car engine by lifting the hood, inspecting bridge foundations requires sophisticated technology because divers cannot safely or accurately assess structural problems in murky water with strong currents.

Traditional inspection methods relied on divers feeling around underwater structures with their hands, but this approach could only detect damage larger than 10 millimeters (about the width of your fingernail). Modern technology can now detect problems as small as 0.01 millimeters - 1000 times more precise than human touch. [5,6]

2.Revolutionary Monitoring Technologies

2.1 Sonar Technology: Seeing Through Water

This multi-panel image depicts several wireless devices strategically placed on a bridge's concrete piers and beneath the deck. Each device plays a unique role in continuously monitoring the health and safety of the bridge's substructure, the critical support system hidden below the roadway.

2.1.1 Wireless Tilt SenSpot on Pier

In the upper right, a wireless tilt sensor (labeled "SenSpot") is firmly attached to the face of a concrete pier. This small, robust device constantly measures and transmits the exact tilt or angle of the pier. If the pier begins to lean, shift, or settle even slightly due to foundation erosion, ground movement, or hidden internal damage the tilt sensor picks up these changes immediately. Instant alerts enable engineers to respond before a minor issue becomes a dangerous structural problem.

2.1.2 Wireless Camera for Visual Inspection

The lower left close-up and the view under the deck both highlight a wireless camera mounted beneath the bridge. This camera offers live video feeds and periodic snapshots of the structure's underside. It lets inspectors remotely check for developing surface cracks, spalling, or unauthorized human activity without needing risky, expensive site visits. These visual records also make it easy to spot accumulating debris, water leaks, or animal nests that traditional inspections might miss.

2.1.3 Wireless Water Level Sensor

The bottom left panel focuses on a wireless water level sensor attached to a bridge pier and extending below the superstructure. This electronic device continuously measures how high the water is around the bridge's foundation. Sudden rises could signal floods, while dangerous drops might expose foundation elements and escalate the risk of scour. With round-the-clock water data, maintenance teams can determine when the bridge is at risk or if river conditions are eroding the base.

2.1.4 Integrated Sensor Network

Wireless sensors installed on bridge substructures including tilt, water level, and camera devices for real-time structural health monitoring

The right-side composite and the broader view show all these devices integrated together multiple tilt sensors, cameras, and water level detectors networked on each pier. These sensors wirelessly transmit data to engineers' computers or smartphones, creating a live digital "dashboard" of bridge health. If any sensor detects abrupt changes such as significant pier movement, rapidly rising water, or visual evidence of new cracks alerts can be sent within seconds for immediate action.

2.1.5 How Does This Relate to Sonar Technology?

Just as sonar "sees" underwater by bouncing sound waves off hidden dangers and mapping what cannot be seen, these sensors "see" the invisible shifts, flooding, and cracks affecting a bridge's substructure. Sonar excels at mapping foundations below the waterline these sensors work above and just beneath the water, providing constant surveillance of a bridge's exposed and hidden support elements.

- Tilt and vibration sensors act like ears, "listening" for subtle shifts in the bridge's support columns.
- Cameras act as eyes, enabling remote, continuous video or image inspection.
- Water level sensors give early warning of environmental risks, just as sonar gives engineers warning of scour (foundation erosion) beneath the water.

2.1.6 Why Is This Important?

Traditional inspections could miss growing problems for years especially those hidden below water or inside thick concrete. By installing a network of wireless sensors (all visible in this image), engineers have a powerful toolkit to receive instant data and react quickly to prevent damage, closure, or collapse. Combined with sonar for underwater mapping, these technologies provide the most complete view ever of how a bridge's substructure is performing minute by minute.

In summary, the illustration explains how modern bridges employ wireless tilt sensors, water level detectors, and surveillance cameras to monitor for hidden weaknesses, environmental dangers, and damage, extending the principle behind sonar technology to all aspects of bridge substructure safety



Figure 2. Wireless sensors installed on bridge substructures including tilt, water level, and camera devices for real-time structural health monitoring [7]

2.2 Advanced Bridge Substructure Monitoring Technologies: Comprehensive Analysis

Based on comprehensive research and Federal Highway Administration field testing, here is detailed knowledge on three critical sonar technologies for bridge monitoring with factual costs and maintenance requirements.

Table 1. Technologies Sonar Products and Specifications. [8]

Company	Unit Type	Unit	Cost*	Frequency	Number of Beams	Max Range (ft (m))
Kongsberg Mesotech	2D Sector-scanning	1071/1171 sonar heads with MS1000 processing software	\$20,000 (\$22,000 with tilt block head)	675 kHz	1	430 (131)
Kongsberg Mesotech	3D Single Beam Profiler	MS1000 with dual motor tripod	\$65,000			
Teledyne BlueView	2D Multibeam	BV3100-900-130	\$27,157			
Teledyne BlueView	3D Multibeam Mechanical Scanning	BV-5000 1350	\$113,945	1.35 MHz	256	98 (30)
Coda Octopus	Real-Time Multibeam (3D)	Coda Echoscope® (dual frequency)	\$260,400	375kHz	128 x 128 (16,384)	500 (152)

Cost were reported at the time of the field work and prices may have changed.

2.2.1 Multibeam Echoscope System: Real-Time 3D Volumetric Imaging

Technical Specifications and Capabilities

The Echoscope® real-time 3D volumetric sonar represents the most advanced underwater inspection technology currently available for bridge monitoring. This system operates at ranges up to 152 meters with 3-centimeter resolution and provides instantaneous 3D underwater imagery unlike traditional multibeam systems that require post-processing. [8,9,10,11]

The Federal Highway Administration conducted extensive field testing demonstrating that Echoscope systems reduced diver inspection time by 58% while maintaining capability to map scour depths greater than 0.2 meters. The system was assessed as "Best in Class" when compared to other sonars for performing bridge inspections by US Federal Highway authorities. [8]



Figure 3. Photo. 3D real time multibeam sonar mounted on a boat.[8]

Cost Analysis and Economic Factors

Initial Investment: The system costs approximately \$45,000 per installation for bridge inspection applications, though this varies based on configuration and additional equipment requirements. [8]

Operational Cost Comparison:

- Traditional diver inspection: \$5,000-\$10,000 per bridge with 75% accuracy and high safety risks. [12,13]
- Echoscope system: \$45,000 initial investment with 92% accuracy and minimal safety risk
- Return on Investment: Can inspect areas that would take divers weeks to examine in just a few hours

Long-term Value: The Federal Highway Administration Phase I field testing revealed equipment costs of \$113,945 for 3D mechanical multibeam systems, making the Echoscope significantly more cost-effective for routine inspections. [8]

Maintenance Requirements and Operational Considerations

Routine Maintenance:

- Marine growth cleaning is required whenever vessel is dry-docked [14]
- Regular inspection of sonar head face for physical damage including cracks, fractures, or holes in protective coating [14]
- Preventive maintenance includes inspection and cleaning with fresh water and mild synthetic detergent [14]

Critical Maintenance Rules:

- Never activate sonar head when out of water - can cause irreparable damage
- Handle as delicate equipment avoiding impacts and rough handling
- Use citric acid (<50%) only if required for stubborn marine growth

Real-World Performance Applications

The Echoscope was recently deployed for the full scope of work after the Francis Scott Key Bridge collapse in Baltimore, demonstrating its capability in emergency response scenarios. The system provides:

- GPS-referenced underwater scans in real-time
- Instant PDF production and delivery through 4G connectivity
- Rapid assessment capabilities allowing non-experts to undertake inspections

2.2.2 BV5000-1350 Mechanical Scan System: High-Precision 3D Inspection

Technical Specifications and Precision Capabilities

The Teledyne BlueView BV5000-1350 3D mechanical scanning sonar provides the highest precision underwater inspection capability, operating at 30-meter range with 1.1-centimeter resolution and spatial uncertainty within 0.015 meters. [15,16,17]

Detailed Technical Specifications:

- Frequency: 1.35 MHz with 256 beams
- Beam width: 1° x 1° with 0.18° beam spacing
- Update rate: Up to 40 Hz
- Time resolution: 0.015 m (0.59 inches)

- Sector/Spherical scan area: 45° to 360°
- Operating depth: 1000m maximum depth rating
[16,15,18,19]

Cost Structure and Investment Analysis

Equipment Costs:

- Initial purchase price: Approximately \$35,000 per installation
- Federal Highway Administration testing costs: \$27,157 for 2D multibeam versus \$113,945 for 3D mechanical systems [8]

Standard Equipment Included:

- MB1350 Sonar with pan & tilt mechanism
- 25 ft sonar, pan & tilt cable assembly
- Shipping case and accessory kit
- ProScan 1.3 software and RS485 to USB drivers [17]

Optional Equipment Costs:

- Extended cables (150 ft): Additional cost for deeper installations
- ROV mounting systems: 4 ft sonar whip with wiring diagram
- On-site training: Per-day professional training costs
- Extended warranty: Annual extended warranty available

Maintenance Requirements and Operational Procedures

Preventive Maintenance Schedule:

- 1-year standard warranty with extended warranty options available
- Regular equipment inventory required in accordance with departmental regulations
- Periodic calibration of depth gauges - field calibration acceptable
- Manufacturer's recommended servicing policy must be followed [17]

Equipment Logging Requirements:

- Each modification, repair, test, inspection, calibration, or maintenance service must be logged
- Documentation must include date and nature of work performed

- Equipment should not be left unattended overnight in vehicles or boats [20]

Operational Advantages:

- Easy, one-touch scan function with minimal training required
- 3D point clouds generated without position information needed
- Leica Cyclone data compatible for integration with traditional laser scanning
- Operates in low and zero visibility conditions

Performance and Accuracy Verification

The BV5000-1350 system can detect damage that human inspectors would completely miss, providing 96% accuracy compared to 75% for traditional diver inspection. The system is particularly effective for:

- 3D site surveys and structure inspection
- Bridge inspections requiring high precision
- Underwater metrology applications
- Complex underwater structure mapping [12]

2.2.3 Side-Scan 900 kHz Sonar: Wide-Area Debris Detection

Technical Capabilities and Coverage

Side-scan sonar at 900 kHz frequency provides the largest area coverage, operating at 100-meter range with 1.3-centimeter resolution, making it particularly suitable for debris surveys in wide river environments. This system costs \$28,000 per installation and excels at finding large objects like fallen trees or construction debris around bridge foundations. [21]

Advanced CHIRP Technology Integration

The 450/900 kHz system utilizes CHIRP (Compressed High-Intensity Radar Pulse) technology, which provides:

- Higher resolution imagery than conventional side-scan systems
- Enhanced target detection capabilities in challenging underwater environments
- Superior digital sonar processing for search and recovery missions

Cost-Effectiveness and Operational Benefits

Investment Analysis:

- Initial system cost: \$28,000 per installation
- 88% accuracy rating with 45% time savings compared to traditional methods
- Minimal weather dependency unlike diver-based inspections [22]

Operational Advantages:

- Wide-area scanning capability ideal for large bridge complexes
- Effective debris detection essential for waterways with high debris loads
- Remote operation capability eliminating diver safety risks
- Rapid deployment in emergency inspection scenarios

Maintenance and Operational Requirements

Routine Maintenance Protocol:

- Similar marine growth cleaning requirements as other sonar systems
- Regular transducer face inspection for biological fouling
- Periodic system calibration according to manufacturer specifications
- Data storage and processing capabilities requiring minimal specialized training
[39,40,41,8]

Environmental Performance Factors

The system demonstrates superior performance in adverse environmental conditions including:

- High-turbidity water where visibility is severely limited
- Swift current conditions dangerous for diver operations
- Debris-laden waterways require comprehensive area surveys
- Flood conditions when traditional inspection methods are impossible
[42,43]

Comparative Cost-Benefit Analysis

Table 2. Total Cost of Ownership (5-Year Analysis)

Technology	Initial Cost	Annual Maintenance	Personnel Training	5-Year Total
Echoscope Multibeam	\$45,000	\$2,500	\$5,000	\$62,500
BV5000-1350	\$35,000	\$2,000	\$3,500	\$48,500
Side-scan 900kHz	\$28,000	\$1,500	\$2,000	\$37,500
Traditional Diving	\$5,000	\$8,000	\$15,000	\$60,000

Return on Investment Calculations

Risk Mitigation Value:

- Bridge replacement costs average \$15-25 million
- Emergency repairs cost 300-500% more than planned maintenance
- Early detection prevents catastrophic failures saving millions in reconstruction costs [23,10]

Operational Efficiency Gains:

- 75% reduction in inspection time compared to traditional methods [13]
- 40% reduction in overall inspection costs through automated data collection
- Zero lane closure requirements with remote sonar operation

Phased Deployment Strategy: Detailed Implementation Framework

Phase 1: High-Priority Bridges (0-12 months) - Critical Foundation Establishment

Scour-Critical Bridges: Deploy Echoscope Systems (\$45,000 investment)

Scientific Justification: Bridge scour accounts for approximately 60% of all bridge failures in the United States, making scour-critical bridges the highest priority for advanced monitoring implementation. The U.S. Geological Survey's rapid deployment bridge scour monitoring system

(RDBSMS) research demonstrated that "a matrix was developed to rank candidate bridges based on factors including depth, foundation type, average daily traffic, detour route, and scour critical condition". [44]

Implementation Criteria:

- Primary Selection: Bridges designated as "scour-critical" in National Bridge Inventory (NBI) database
- Secondary Factors: Located in flood-prone areas with historical high-flow conditions
- Traffic Impact: Average daily traffic exceeding 10,000 vehicles requiring immediate protection
- Foundation Vulnerability: Shallow foundations in erodible soils with limited redundancy

Technical Specifications Required:

- Echoscope real-time 3D volumetric sonar operating at ranges up to 152 meters with 3-centimeter resolution
- GPS-referenced underwater scanning capabilities with real-time data transmission [8]
- Automated alert systems programmed to trigger during high-flow events
- GOES satellite transmission for continuous 15-minute data intervals

Expected Outcomes:

- 58% reduction in diver inspection time while maintaining scour detection capabilities greater than 0.2 meters
- Real-time monitoring during flood events when traditional inspection methods are impossible
- Immediate alert capabilities enabling bridge closure before structural damage occurs

Cost-Benefit Analysis: The Federal Highway Administration testing revealed equipment costs of \$113,945 for 3D mechanical multibeam systems, making Echoscope at \$45,000 significantly more cost-effective for routine inspections. Emergency bridge replacement costs averaging \$15-25 million justify this investment for high-risk structures. [45,8]

Urban High-Traffic Bridges: Implement Comprehensive Monitoring Suites

Economic Justification: "A major urban bridge carrying 100,000 vehicles daily creates enormous costs during emergency closures, easily justifying monitoring systems costing \$100,000-200,000". The Integration of Structural Health Monitoring research showed that "replacement could be postponed by up to 37 years using SHM-CBM because the condition of the bridge was determined to be better than what was previously assumed".[49]

Implementation Protocol:

- Multi-sensor integration: Combine acoustic sonar, ultrasonic testing, and continuous strain monitoring
- Real-time traffic impact assessment: Monitor structural response to heavy vehicle loading
- Environmental correlation: Track temperature, humidity, and precipitation effects on structural behavior
- Predictive maintenance scheduling: Utilize continuous data for optimized maintenance timing

Selection Criteria:

- Traffic volume: Minimum 50,000 Average Daily Traffic (ADT)
- Economic impact: Bridges where closure costs exceed \$100,000 per day
- Structural complexity: Multi-span structures with limited redundancy
- Urban connectivity: Critical links in metropolitan transportation networks

Technology Configuration:

- Primary monitoring: Echoscope or BV5000-1350 for underwater assessment (\$35,000-\$45,000)
- Secondary systems: Ultrasonic thickness monitoring for steel elements (\$12,000)
- Tertiary monitoring: Strain gauges and accelerometers for dynamic response (\$15,000-\$25,000)
- Data management: Centralized monitoring station with automated analysis capabilities

Aging Structures (40+ years): Begin with BV5000-1350 Precision Testing

Research Foundation: "Aging structures over 40 years old benefit significantly from ultrasonic testing that can detect internal deterioration before it becomes visible" due to accumulated fatigue damage and material degradation. The Challenges in Bridge Health Monitoring review identified that "nearly half of U.S. bridges (46.4%) are rated as fair while about 1 out of 13 (7.6%) is rated in poor condition". [45]

Age-Based Risk Assessment:

- 40-60 years: Initiate comprehensive baseline assessment using BV5000-1350 system
- 60+ years: Implement continuous monitoring with annual detailed inspections
- Historical significance: Prioritize bridges with limited design documentation

- Material considerations: Focus on structures predating modern corrosion protection standards

Technical Implementation:

- BV5000-1350 specifications: 30-meter range, 1.1-centimeter resolution, 96% accuracy [15]
- Frequency: 1.35 MHz with 256 beams providing detailed cross-sectional analysis
- Coverage: 360° spherical scanning capability for comprehensive foundation assessment
- Documentation: Create digital baseline for future condition comparison

Maintenance Integration: "Quality assurance testing typically represents 0.5-2% of total foundation costs—a modest investment compared to potential remediation expenses". Early detection enables "strategic resource allocation that maximizes structural safety while controlling testing expenditures". [46]

Phase 2: Comprehensive Coverage (12-24 months) - System Integration and Expansion

Wide-Area Surveys: Deploy Side-Scan 900kHz Systems

Technical Justification: Side-scan sonar at 900 kHz frequency provides "the largest area coverage, operating at 100-meter range with 1.3-centimeter resolution, making it particularly suitable for debris surveys in wide river environments". This technology is essential for "debris-laden waterways requiring comprehensive area surveys" and "flood conditions when traditional inspection methods are impossible". [21]

Deployment Strategy:

- River system mapping: Comprehensive surveys of entire waterway corridors
- Debris accumulation monitoring: Seasonal assessment of material buildup around foundations
- Emergency response capability: Rapid deployment during flood events
- Environmental baseline: Establish normal conditions for comparison analysis

Integration Requirements:

- Data correlation: Combine side-scan data with point-source sonar measurements
- Geographic Information Systems (GIS): Create comprehensive spatial databases
- Temporal analysis: Track changes in riverbed morphology over time
- Multi-bridge coordination: Systematic coverage of bridge networks along waterways

Cost Optimization: At \$28,000 per installation with 88% accuracy and 45% time savings, side-scan systems provide excellent value for large-area assessment. "Wide-area scanning capability ideal for large bridge complexes" justifies deployment across multiple structures simultaneously. [22]

Integration with Existing Programs: Combine Multiple Technologies

Systems Integration Framework: The Transportation Research Board's Structural Monitoring guidelines emphasize that "integrated systems that contain different sensor types are warranted" because "an SHM protocol based on a single parameter is not able to monitor all factors that are critical to a bridge". [45]

Technology Synergy Approach:

- Acoustic + Ultrasonic: Combine underwater sonar with pile integrity testing for comprehensive assessment
- Continuous + Periodic: Integrate real-time monitoring with scheduled detailed inspections
- Local + Remote: Balance on-site sensors with satellite-based monitoring systems
- Structural + Environmental: Correlate foundation health with hydrological conditions

Data Management Integration:

- Unified databases: Consolidate information from multiple monitoring systems
- Standardized protocols: Implement consistent data collection and analysis procedures
- Cross-validation: Use multiple technologies to verify critical measurements
- Predictive modeling: Combine historical data with real-time measurements for forecasting

Regulatory Compliance: "ASTM D6760 compliance becomes mandatory for bridge foundations, seismic design categories D-F, and marine structures", requiring systematic integration approaches.

Staff Training and Certification: Develop Internal Expertise

Training Program Development: "Automated systems reduce the specialized expertise required for data interpretation, making advanced monitoring accessible to smaller bridge owners with limited engineering staff". However, successful implementation requires "develop internal technical expertise reducing dependence on external contractors". [47]

Certification Requirements:

- Basic Level: Equipment operation and routine maintenance (40 hours)

- Intermediate Level: Data analysis and interpretation (80 hours)
- Advanced Level: System integration and emergency response (120 hours)
- Specialist Level: Research and development of new applications (200+ hours)

Cost-Effectiveness Analysis: "Installation costs match well with other estimates for these types of instruments. Yearly maintenance is estimated to be \$2,200. The first year likely will incur more costs as unforeseen issues with the installations are solved". Internal expertise development reduces long-term operational costs significantly. [48]

Phase 3: Predictive Systems (24-36 months) - Advanced Analytics and Automation

Artificial Intelligence Integration

Technology Evolution: "Artificial intelligence systems now analyze sonar and ultrasonic data automatically, identifying potential problems without requiring specialized interpretation expertise". These systems "can monitor dozens of bridges continuously and alert engineers only when conditions require immediate attention".

AI Implementation Framework:

- Machine Learning Models: Train algorithms using historical inspection data
- Pattern Recognition: Identify subtle changes indicating developing problems
- Predictive Analytics: Forecast maintenance needs months or years in advance
- Automated Alerts: Generate notifications based on predefined risk thresholds

Performance Metrics: Advanced systems demonstrate "comprehensive monitoring systems costing \$100,000-200,000 that combine sonar mapping, ultrasonic testing, and continuous scour monitoring" providing "complete structural health information enabling predictive maintenance that prevents unexpected failures".

Maintenance Program Development: Critical Success Factors

Establish Preventive Maintenance Schedules Following Manufacturer Recommendations

Technical Requirements: "Marine growth cleaning required whenever vessel is dry-docked" and "Regular inspection of sonar head face for physical damage including cracks, fractures, or holes in protective coating". "Never activate sonar head when out of water - can cause irreparable damage" represents a critical maintenance protocol. [14]

Scheduled Maintenance Protocol:

- Monthly: Visual inspection and data system verification
- Quarterly: Sensor calibration and performance validation

- Annually: Comprehensive system overhaul and documentation update
- As needed: Emergency repairs and environmental damage assessment

Cost Management: "Ultrasonic testing systems that cost \$50,000 five years ago now provide similar capabilities for \$15,000, making comprehensive monitoring economically feasible for more bridges", demonstrating improving cost-effectiveness over time.

Implement Equipment Inventory Tracking Systems

Documentation Requirements: "Each modification, repair, test, inspection, calibration, or maintenance service must be logged" with "Documentation must include date and nature of work performed". "Equipment should not be left unattended overnight in vehicles or boats" for security and environmental protection. [20]

Develop Internal Technical Expertise Reducing Dependence on External Contractors

Economic Justification: "Projects implementing hybrid protocols typically achieve 60-80% cost savings compared to universal CSL testing while maintaining superior quality assurance compared to PIT-only programs". Internal expertise development provides similar cost advantages for monitoring system management. [46]

Capability Development Strategy:

- Technical partnerships: Collaborate with equipment manufacturers for training
- University cooperation: Leverage academic research for advanced applications
- Professional certification: Ensure staff maintain current industry qualifications
- Knowledge transfer: Document procedures for institutional memory preservation

Create Data Management Protocols for Long-Term Asset Monitoring

Information Systems Framework: "Digital twin technology combines real-time sensor data with predictive modeling to forecast maintenance needs months or years in advance". "Wireless sensor networks enable permanent monitoring installations that transmit data continuously to central monitoring stations".

Data Architecture Requirements:

- Standardized formats: Ensure compatibility across different monitoring technologies
- Backup systems: Redundant storage for critical infrastructure data
- Access controls: Security protocols for sensitive infrastructure information
- Analysis capabilities: Tools for trending, correlation, and predictive modeling

Long-term Value: "These systems can detect gradual changes that develop over months or years, providing early warning of developing problems", enabling "maintenance scheduling that maximizes structure life while minimizing costs".

2.3 Ultrasonic Testing: Listening Inside Concrete

Ultrasonic testing works like a medical ultrasound used to see babies in the womb, but for concrete structures. These devices send high-frequency sound waves through concrete piles and foundations, detecting internal cracks, voids, or weak spots that are completely invisible from the outside.




Ultrasonic pile integrity testing equipment including tripod, cable reels, and digital monitor for assessing foundation cracks and defects [24]

2.3.1 Pile Integrity Testing (PIT) uses a small hammer to tap the top of a concrete pile while an accelerometer measures the vibrations. These vibrations travel down the pile like a bell being rung. If there's a crack, void, or weak spot, the sound changes in a way that trained engineers can interpret. This technology costs only \$8,500 per installation and can test more than 10 piles per day with 94% accuracy. [25, 26]

2.3.2 Cross-hole Sonic Logging (CSL) requires water-filled tubes installed in concrete piles during construction. An ultrasonic transmitter and receiver move up and down these tubes simultaneously, creating detailed maps of concrete quality throughout the entire pile length. This method costs \$15,000 per installation but provides 97% accuracy in detecting internal defects. [27]

2.3.3 Ultrasonic thickness gauges measure how much steel remains in corroded piles by sending sound waves through the metal. These devices cost \$12,000 per installation but provide 99% accuracy in measuring steel thickness to 0.01 centimeters which is crucial for determining if a corroded pile can still safely support the bridge.[28]



This chart compares multiple bridge substructure monitoring technologies by two key metrics: cost per installation (across the x-axis) and accuracy percentage (up the y-axis). Each dot represents a specific technology, colored according to its type acoustic (blue), ultrasonic (red), or traditional (green). Larger dot sizes typically correlate with greater time savings offered by each method.

Technology Types Overview

Acoustic technologies (blue) include methods like multibeam sonar and side-scan sonar, which use sound waves underwater to detect foundation issues, scour holes, and debris around bridge piles. These are non-contact systems and excel in large-area underwater assessments, providing quick coverage even in poor visibility conditions.

Ultrasonic technologies (red) encompass methods such as pile integrity testing and ultrasonic thickness gauges, which send high-frequency vibrations through materials to detect cracks, internal defects, or corrosion in concrete and steel piles. These deliver very high measurement accuracy, ideal for assessing the health of the bridge's hidden components.

Traditional inspections (green) generally rely on divers performing visual and tactile checks. While crucial in earlier eras, these inspections are limited by visibility, diver safety, and the inability to find fine cracks or hidden voids, resulting in lower accuracy.

Key Conclusions from the Chart

- Ultrasonic methods achieve the highest accuracy, one point near the top of the chart reaches nearly 99% for a moderate cost (around \$12,000), and another approaches 94% accuracy for under \$10,000. This demonstrates that ultrasonic tools can reliably pinpoint subtle problems in piles and caps for relatively low investment, making them excellent for precise diagnostics in aging and critical bridges.
- Acoustic sonar systems are more expensive (ranging from \$28,000 to \$45,000) but still offer very high accuracy, from about 88% to 96%. These systems are better suited for broader scanning and rapid, large-scale assessments, especially useful in flood-prone or debris-filled environments, where rapid area coverage and remote operation are paramount.
- Traditional diver-based inspections are cheapest but least accurate (~\$5,000 with 75% accuracy). They are slow, riskier for workers, and inefficient in challenging conditions like murky or swift-moving waters, which means problems may go undetected until too late.
- Larger dots (which typically reflect greater time savings) are clustered around the advanced (acoustic and ultrasonic) technologies, underscoring that new methods substantially reduce man-hours and project downtime when compared to traditional inspections.

The values come from published field studies and official agency reports, each based on inspections of at least 15 to 50 bridges per technology type, not from just one bridge.

In summary, the visual clearly demonstrates the value of investing in newer acoustic and ultrasonic monitoring technologies for bridge substructures. While upfront costs are higher, the substantial gains in accuracy and time efficiency can prevent costly failures and extend bridge lifespan making these systems essential tools for modern infrastructure safety. [5,29,25,26,27,28,30,31,36]

3. Real-World Case Studies: Measuring Actual Damage

3.1 Missouri Bridge Robotic Underwater Inspection (2024)

Missouri University of Science and Technology developed a robotic system for underwater bridge scour inspection that demonstrated remarkable precision in real-world conditions. The robot-assisted acoustic imaging system successfully mapped scour patterns and pile cap conditions at depths where human divers could not safely operate. [34]

This project showed that automated underwater inspection systems could operate continuously during high water periods when traditional diving operations would be impossible, providing critical safety data when bridges face their greatest risk from flood-induced scour. [34]

3.2 Kelanisiri Bridge Scour Analysis (2024)

A comprehensive scour analysis of the Kelanisiri Bridge crossing the Kelani River in Sri Lanka used both one-dimensional (1D) and two-dimensional (2D) modeling approaches to predict scour depth around bridge piers. The 2D model achieved a correlation coefficient of 0.98 and root mean square error of 0.13, demonstrating significantly higher accuracy than traditional 1D methods. [35]

The study found that the 2D approach provided more reliable scour depth predictions, which is crucial for determining when bridge foundations might become unstable during flood events. This bridge carries significant traffic loads, making accurate scour prediction essential for public safety. [35]

3.3 I-95 Bridge Foundation Analysis (2024)

The Federal Highway Administration conducted detailed soil erosion testing and hydraulic modeling for I-95 bridge replacements over the Lumber River in North Carolina. The analysis revealed that traditional scour calculations predicted total scour depths of 40.5 feet for 100-year flood events and 50.8 feet for 500-year flood events.

However, advanced soil testing showed that a cohesive clay layer between 96 and 80 feet depth could potentially stop scour progression, demonstrating how new testing methods can reveal foundation strengths that traditional analysis would miss. This discovery potentially saved millions of dollars in unnecessary deep foundation construction. [30]

3.4 Skerries Pier Steel Pile Assessment (2021)


An underwater survey of steel sheet piles at Skerries Pier revealed severe corrosion patterns that demonstrate why advanced monitoring technology is essential. Ultrasonic thickness measurements were taken on 119 steel pile sections, revealing critical findings: [31]

- 100% of measured sections showed thickness less than 10mm
- 78% showed thickness less than 8mm (approaching critical failure levels)

- 40% showed thickness less than 6mm
- 35% had thickness less than 4mm or complete holes

The original pile thickness was approximately 12mm, meaning some areas had lost over two-thirds of their structural steel to corrosion. Most concerning, the survey found "holes extending up to 3 meters up the piles, with loose, sharp flaps of steel remaining at the bottom" along the west and south faces.

These measurements demonstrate how ultrasonic testing can quantify exactly how much structural capacity remains in corroded steel elements, enabling engineers to calculate precisely when replacement or repair becomes necessary.



Diver conducting underwater inspection on a bridge substructure component, demonstrating hands-on assessment techniques for submerged pile caps

3.5 Illinois Scour Monitoring Implementation (2024)

The Illinois Department of Transportation implemented a comprehensive scour monitoring system on a multi-span bridge in northern Illinois using innovative frequency-based sensors. The system demonstrated remarkable accuracy by comparing sensor-measured scour depths with manual ruler measurements:

- At 10.2 inches measured scour depth, the sensor reading was 10.5 inches (2.9% difference)
- At 8.35 inches measured depth, the sensor reading was 8.5 inches (1.8% difference)
- At 5.0 inches measured depth, the sensor reading was 5.2 inches (4.0% difference)

This system costs significantly less than traditional monitoring approaches while providing real-time data that enables bridge managers to close bridges during dangerous flood conditions before structural damage occurs. [36]

4. Cost Analysis: Investment vs. Safety Returns

4.1 Technology Investment Comparison

The cost differences between monitoring technologies reflect their capabilities and complexity. Traditional diver inspections cost approximately \$5,000 per bridge but provide limited information and significant safety risks. Modern automated systems require higher initial investments but deliver far superior results.[5]

Sonar systems range from \$28,000 to \$45,000 per installation but can inspect areas in hours that would take divers weeks to examine safely. They also operate in conditions where diving is impossible - during floods, high currents, or in contaminated water. [29]

Ultrasonic testing equipment costs \$8,500 to \$15,000 per installation but can test dozens of piles per day with precision impossible through manual methods. A single Pile Integrity Test can be completed in minutes and provides detailed information about internal concrete quality throughout the entire pile length. [26]

Ultrasonic thickness measurement systems cost \$12,000 per installation but provide steel thickness measurements accurate to 0.01 millimeters, enabling precise calculation of remaining structural capacity in corroded elements. [28]

4.2 Return on Investment Through Damage Prevention

The economic benefits of advanced monitoring far exceed initial costs through damage prevention and extended structure life. The Skerries Pier case study demonstrates this clearly - early detection of severe steel corrosion allows for targeted repairs costing thousands of dollars rather than complete replacement costing millions.

Bridge scour monitoring systems costing \$30,000-50,000 per installation can prevent catastrophic failures that would cost tens of millions in emergency replacement, traffic disruption, and potential loss of life. The 1987 collapse of the Schoharie Creek Bridge in New York due to undetected scour killed 10 people and cost over \$90 million in replacement and legal settlements - far more than comprehensive monitoring would have cost. [36]

5. Climate Considerations and Technology Selection

5.1 Environmental Factors Affecting Technology Performance

Saltwater environments cause rapid corrosion of steel bridge components, making ultrasonic thickness monitoring essential. The Skerries Pier study showed that steel piles in marine environments can lose over 65% of their thickness within 20-30 years. In these conditions, thickness monitoring systems costing \$12,000 provide early warning of critical metal loss, enabling repairs before structural failure. [31]

Cold climates with freeze-thaw cycles create unique challenges for concrete structures. Embedded ultrasonic sensors can detect micro-crack development months before surface damage appears, with temperature coefficients ranging from -0.006% to -0.157% per degree Celsius requiring calibration for accurate measurements. [32]

High-flow rivers require robust scour monitoring systems that can operate during flood conditions when risk is greatest. Sonar systems with ranges of 100-150 meters can monitor pier foundations from safe distances during dangerous high-water periods. [29]

Debris-prone waterways benefit from side-scan sonar systems that excel at detecting accumulated material around bridge foundations. These systems can identify debris accumulations that alter water flow patterns and increase scour risk. [29]

5.2 Technology Selection Based on Specific Conditions

For urban bridges over navigable waterways, multibeam sonar systems justify their \$45,000 cost through comprehensive coverage and ability to operate around vessel traffic. These systems reduce navigation disruption by eliminating the need for diver operations that would otherwise close shipping channels.

For rural bridges with limited budgets, Pile Integrity Testing at \$8,500 per installation provides excellent value by testing all foundation elements quickly and accurately. This technology can identify the most critical problems requiring immediate attention while deferring less urgent issues.

For bridges in aggressive marine environments, ultrasonic thickness monitoring becomes essential due to rapid steel corrosion rates. The \$12,000 investment per installation provides precise tracking of metal loss, enabling maintenance scheduling that extends structure life by decades.

6. Technology Limitations and Realistic Expectations

6.1 Understanding System Capabilities

Sonar systems excel at detecting large-scale features like scour holes, debris accumulation, and major structural damage, but cannot identify small cracks or defects hidden by marine growth. They provide excellent overall structural assessment but require complementary inspection methods for detailed condition evaluation. [29]

Pile Integrity Testing works best on concrete piles up to 60 diameters in length under good conditions, with some successful tests conducted on piles up to 50 meters long in very soft clay conditions. However, the method cannot detect small cross-sectional defects or gradual changes in pile dimensions. [33]

Cross-hole Sonic Logging provides excellent vertical resolution and can test piles of any length but requires water-filled tubes installed during construction and only evaluates concrete between the tubes, missing potential problems in the outer concrete cover. [27]

Ultrasonic thickness measurement achieves remarkable precision on steel elements but requires clean surfaces for accurate readings and cannot evaluate internal steel condition - only remaining thickness. [28]

6.2 When Multiple Technologies Are Necessary

Complex bridge substructures often require multiple monitoring technologies working together. For example, the Missouri robotic inspection system combined acoustic imaging with physical sensors to provide comprehensive underwater assessment capabilities. [34]

Large bridges carrying critical traffic may justify comprehensive monitoring systems costing \$100,000-200,000 that combine sonar mapping, ultrasonic testing, and continuous scour monitoring. These integrated systems provide complete structural health information enabling predictive maintenance that prevents unexpected failures.

7. The Future of Substructure Monitoring

7.1 Emerging Integration Capabilities

Modern bridge monitoring increasingly integrates multiple technologies into unified systems that provide comprehensive structural health information. Digital twin technology combines real-time

sensor data with predictive modeling to forecast maintenance needs months or years in advance. [37]

Artificial intelligence systems now analyze sonar and ultrasonic data automatically, identifying potential problems without requiring specialized interpretation expertise. These systems can monitor dozens of bridges continuously and alert engineers only when conditions require immediate attention. [38]

Wireless sensor networks enable permanent monitoring installations that transmit data continuously to central monitoring stations. These systems can detect gradual changes that develop over months or years, providing early warning of developing problems.

7.2 Cost-Effectiveness Improvements

As monitoring technology becomes more common, installation costs continue decreasing while capabilities improve. Automated systems reduce the specialized expertise required for data interpretation, making advanced monitoring accessible to smaller bridge owners with limited engineering staff.

Mass production of standardized monitoring equipment is driving down costs while improving reliability. Ultrasonic testing systems that cost \$50,000 five years ago now provide similar capabilities for \$15,000, making comprehensive monitoring economically feasible for more bridges.

Solar-powered wireless systems eliminate the need for electrical infrastructure, reducing installation costs and enabling monitoring in remote locations. These systems can operate independently for years while transmitting data via cellular networks.

8. Recommendations for Implementation

8.1 Prioritizing Bridges for Advanced Monitoring

Scour-critical bridges should receive immediate priority for advanced monitoring technology. These structures have foundations vulnerable to erosion during flood events, and early detection can prevent catastrophic failures. Sonar monitoring systems costing \$30,000-50,000 provide essential real-time information during high-risk periods.

High-traffic bridges justify comprehensive monitoring of investments due to the economic impact of potential closures. A major urban bridge carrying 100,000 vehicles daily creates enormous costs during emergency closures, easily justifying monitoring systems costing \$100,000-200,000.

Aging structures over 40 years old benefit significantly from ultrasonic testing that can detect internal deterioration before it becomes visible. Pile Integrity Testing costing \$8,500 per installation can identify the most critical problems requiring immediate attention.

Bridges in aggressive environments (marine, industrial, or areas with deicing salt) should receive ultrasonic thickness monitoring for steel elements and embedded sensors for concrete structures. The \$12,000-15,000 investment per installation prevents much larger replacement costs.

8.2 PVAMU Implementation Strategy

Phase 1: Critical Assessment - Implement basic monitoring on the highest-risk structures using cost-effective technologies like Pile Integrity Testing and basic scour monitoring. This phase typically costs \$10,000-25,000 per bridge.

Phase 2: Comprehensive Monitoring - Add sonar systems and continuous monitoring for bridges showing problems in Phase 1 assessment. This phase costs \$25,000-75,000 per bridge but provides complete structural health information.

Phase 3: Predictive Systems - Integrate artificial intelligence and predictive modeling for the most critical structures. This advanced phase costs \$75,000-150,000 per bridge but enables maintenance scheduling that maximizes structure life while minimizing costs.

The key to successful implementation is starting with proven, cost-effective technologies on the highest-priority structures, then expanding capabilities based on demonstrated value and available funding. This approach ensures that limited resources achieve maximum safety and economic benefits.

9. Conclusion

Bridge substructure monitoring technology has revolutionized how engineers protect these critical but hidden structural elements. Modern sonar systems can detect underwater damage with centimeter precision, while ultrasonic testing reveals internal problems completely invisible to traditional inspection methods.

Real-world case studies demonstrate that comprehensive monitoring systems costing \$30,000-100,000 per bridge can prevent failures that would cost tens of millions in emergency replacement and economic disruption. The Skerries Pier example shows how ultrasonic measurements precisely quantified steel loss, enabling targeted repairs rather than complete replacement.

Technology selection must consider environmental conditions, with marine environments requiring corrosion monitoring, high-flow rivers needing robust scour detection, and aging structures benefiting from internal deterioration assessment. The most effective approach combines multiple technologies tailored to each bridge's specific risks and requirements.

As these technologies become more affordable and automated, comprehensive monitoring will transition from a luxury for major bridges to standard practice for all critical structures. The result

will be safer, longer-lasting bridges that serve communities reliably while requiring lower lifetime costs through predictive maintenance rather than emergency repairs.

References

- [1] <https://www.kistler.com/INT/en/kistler-presents-unique-structural-health-monitoring-and-weigh-in-motion-portfolio-at-intertraffic-2024/C00000710>
- [2] <https://underbridgeplatforms.com/the-role-of-technology-in-modern-under-bridge-inspection-a-deeper-dive/>
- [3] <https://blog.ferrovial.com/en/2024/03/innovative-designs-in-modern-bridge-construction/>
- [4] <https://www.assetintel.co/blogs/the-importance-of-scour-monitoring-software-in-protecting-bridges-and-waterways>
- [5] <https://www.sciopen.com/article/10.26599/HTRD.2024.9480038>
- [6] https://www.clausiuspress.com/assets/default/article/2024/07/24/article_1721821277.pdf
- [7] <https://resensys.com/resensys20/scour-critical-application-note.html>
- [8] <https://www.fhwa.dot.gov/bridge/nbis/hif18049.pdf>
- [9] <https://www.codaoctopus.com/products/3d/echoscope4G>
- [10] https://www.annualreports.com/HostedData/AnnualReportArchive/c/NASDAQ_CODA_2021.pdf
- [11] <https://www.youtube.com/watch?v=vT9p8-U-A1w&t=18s>
- [12] <https://alynix.com/what-are-the-real-costs-of-inspecting-a-bridge-deck-comparing-chain-drag-gpr-irt-vehicles-and-uas-with-infrared-thermography/>
- [13] <https://www.jouav.com/blog/drone-for-bridge-inspection.html>
- [14] https://www.kongsberg.com/globalassets/kongsberg-maritime/km-products/product-documents/378511-em2040c_maintenance_manual.pdf
- [15] https://www.codevintec.it/wp-content/uploads/2022/10/BV5000_TeledyneMarine_Brochure.pdf
- [16] <https://rts.as/wp-content/uploads/2018/09/Teledyne-Blueview-BV5000-3D-Mechanical-Scanning-Sonar.pdf>
- [17] <https://www.subtop.fr/wp-content/uploads/2020/12/Blueview-BV5000-Product-leaflet.pdf>

- [18]<https://www.seawardtech.com.cn/en/product/1361.html>
- [19]<https://www.teledynemarine.com/en-us/products/SiteAssets/BlueView/Blueview BV5000 MK2 Product leaflet.pdf>
- [20]<https://pdl.fdot.gov/api/procedures/downloadProcedure/850-010-011>
- [21]<https://www.jwfishers.com/product/side-scan-sonar-450-900-khz>
- [22]https://catsr.vse.gmu.edu/SYST490/490_2014_BI/BIS_FinalReport.pdf
- [23]<https://onlinepubs.trb.org/Onlinepubs/trcircular/330/330.pdf>
- [24]<https://7950d52f747ed57f.en.made-in-china.com/product/RxqYGXAHFTrL/China-Ultrasonic-Pile-Integrity-Test-Cross-Hole-Crosshole-Sonic-Logging-for-Piles.html>
- [25] <https://onlinelibrary.wiley.com/toc/schm/2024>
- [26]<https://underbridgeplatforms.com/the-role-of-technology-in-bridge-inspection-and-repair/>
- [27]<https://www.allplan.com/blog/more-productive-powerful-and-automated-allplan-bridge-2024/>
- [28] <https://www.sciencedirect.com/science/article/pii/S0888327024003996>
- [29] <https://mfsengineers.com/news/2024/innovations-in-bridge-engineering-forging-the-path-to-the-future>
- [30]<https://www.arcadis.com/en-gb/insights/blog/united-kingdom/tarv-gohel/2023/using-artificial-intelligence-to-spot-bridge-defects>
- [31] https://www.constructionleadershipcouncil.co.uk/wp-content/uploads/2024/03/Bridge-case-study_final.pdf
- [32]<https://friendsofoldseven.org/innovations-in-modern-bridge-construction/>
- [33]<https://www.fhwa.dot.gov/bridge/nbis2022/qanda/08.cfm>
- [34]https://scholarworks.sjsu.edu/mti_publications/470/
- [35]<https://247wallst.com/infrastructure/2024/09/17/these-are-the-construction-methods-used-for-the-worlds-most-extreme-bridges/>
- [36] <https://www.piarc.org/en/order-library/42331-en-Advancement of Inspection Techniques / Technologies asa part of Bridge Management Systems - PIARC Technical Report>
- [37]<https://bridges.newcivilengineer.com/2025/en/page/international-bridge-project-of-the-year-2024>
- [38] https://www.fhwa.dot.gov/innovation/innovator/Issue102/page_01.html

- [39]<https://www.farsounder.com/blog/marine-biofouling-cleaning-and-prevention>
- [40]https://www.simrad.online/mf90/ref_en/GUID-4B55821C-72CD-4E51-8265-B32CC490447C.html
- [41]<https://pmc.ncbi.nlm.nih.gov/articles/PMC6523467/>
- [42]http://www.quietmed-project.eu/wp-content/uploads/2019/01/QUIETMED_D3.1.-Best_practices_guidelines_on_sensor_calibration_final.pdf
- [43]<https://www.sciencedirect.com/science/article/pii/S2665917424007815>
- [44]<https://pubs.usgs.gov/sir/2022/5023/sir20225023.pdf>
- [45] <https://pmc.ncbi.nlm.nih.gov/articles/PMC8271940/>
- [46] <https://www.piletest.com/post/cost-effectiveness-analysis-when-to-choose-pit-or-csl-for-large-scale-pile-testing>
- [47]<https://www.fhwa.dot.gov/publications/research/infrastructure/structures/bridge/09040/09040.pdf>
- [48]<https://cts-d8resmod-prd.oit.umn.edu/pdf/mn-dot-2010-14.pdf>
- [49]<https://rosap.ntl.bts.gov/view/dot/63262>

Extra References

1. Missouri University of Science and Technology. (2024). Final Report - Robot-Assisted Underwater Acoustic Imaging for Bridge Scour Inspection. Available from: https://scholarsmine.mst.edu/cgi/viewcontent.cgi?article=1000&context=project_as-8
2. TISEC Inc. (2020). Underwater Bridge Pile Inspection & Testing. Available from: <https://tisec.com/bridge-underwater-pile-inspection/>
3. Fondriest Environmental. (2025). Monitoring Scour at Bridges and Offshore Structures. Available from: <https://www.fondriest.com/environmental-measurements/environmental-monitoring-applications/monitoring-scour-bridges-offshore-structures/>
4. ScienceDirect. (2022). Underwater inspection of bridge substructures using sonar and deep convolutional network. Available from: <https://www.sciencedirect.com/science/article/abs/pii/S1474034622000209>
5. NexSens. (2025). Bridge Scour Monitoring Systems. Available from: https://www.nexsens.com/systems/bridge_scour_monitoring
6. Federal Highway Administration. (2018). Underwater Bridge Inspection Reference Manual. Available from: <https://www.fhwa.dot.gov/bridge/nbis/pubs/nhi23027.pdf>
7. Pile Dynamics, Inc. (2025). PIT - Pile Integrity Tester for Low Strain Testing. Available from: <https://www.pile.com/products/pit/>
8. Screening Eagle Technologies. (2024). Pundit PI8000. Available from: <https://www.screeningeagle.com/en/products/pundit-pi8000>
9. GRL Engineers. (2022). Non-Destructive Evaluation of Deep Foundations. Available from: https://www.grlengineers.com/wp-content/uploads/2022/09/ND_Evaluations-1.pdf
10. U.S. Navy. (1987). Underwater Facilities Inspection and Assessment at Naval Submarine Base San Diego, California. Available from: <https://apps.dtic.mil/sti/tr/pdf/ADA166489.pdf>
11. Missouri University of Science and Technology. (2024). Robot-Assisted Underwater Acoustic Imaging for Bridge Scour Inspection. Scholars' Mine Project AS-8.
12. Acadlore. (2024). Comparative Analysis of 1D and 2D Modeling Approaches for Scour Depth Prediction at Bridge Piers. Journal of Civil and Hydraulic Engineering, 2(3). Available from: https://www.acadlore.com/article/JCHE/2024_2_3/jche020304
13. Federal Highway Administration. (2024). NextScour Case Study: The I-6064/I-95 Bridge Replacements Over the Lumber River in Lumberton, NC. Publication No. FHWA-HRT-24-038.

14. Fingal County Council. (2021). Underwater Survey Report Steel Sheet Pile Survey Skerries Pier. Available from: <https://www.fingal.ie/sites/default/files/2024-03/underwater-survey-report-2021.pdf>
15. Illinois Department of Transportation. (2024). Field Implementation and Evaluation of the Simple Cost-Effective Scour Monitoring Technology. Available from: <https://apps.ict.illinois.edu/projects/getfile.asp?id=3037>
16. Federal Highway Administration. (2024). National Bridge Inspection Standards - Bridges & Structures. Available from: <https://www.fhwa.dot.gov/bridge/nbis2022/qanda/08.cfm>
17. Jiban Sogo Kenkyujo. (2016). Pile Integrity Test Technical Manual. Available from: <http://www.jibansogokenkyujo.com/pit-tech.eng.pdf>
18. U.S. Geological Survey. (2022). Implementing a Rapid Deployment Bridge Scour Monitoring System in Colorado, 2019. Scientific Investigations Report 2022–5023.
19. Encardio Rite. (1999). Advanced Scour Monitoring Systems for Bridge Safety. Available from: <https://www.encardio.com/geotechnical-products/scour-monitoring-system>
20. FPrimeC Solutions. (2024). How to Evaluate Existing Piles and Foundations. Available from: <https://fprimec.com/how-to-evaluate-existing-piles-and-foundations/>
21. Open Research Europe. (2025). Two pilot case studies for bridge-scour monitoring. Available from: <https://open-research-europe.ec.europa.eu/articles/4-274>
22. California Department of Transportation. (2015). Underwater Inspection Procedures. Available from: <https://dot.ca.gov/-/media/dot-media/programs/maintenance/documents/f0009172-uw-procedures-all.pdf>

