Comparative Analysis of Machine Learning Models for Early Diabetes Risk Prediction

Riccardo De Maria, Ron Balanay, Gabriella Gass*

*These authors contributed equally to this work.

Abstract

Diabetes is a chronic condition with widespread health impacts, making early detection and prevention critical for mitigating its effects. This study leverages the "Early Stage Diabetes Risk Prediction" dataset from UCI to develop predictive models capable of estimating diabetes onset risk based on a range of medical and lifestyle factors. The dataset, encompassing 520 observations and 16 attributes, includes demographic details (e.g., age, gender) and symptoms commonly associated with early-stage diabetes (e.g., polyuria, polydipsia, sudden weight loss). By employing machine learning techniques such as logistic regression, decision trees, and random forests, we evaluated models using metrics like accuracy, precision, recall, F1-score, and AUC-ROC to ensure reliability and generalizability.

A significant focus of this research was feature selection, employing Recursive Feature Elimination (RFE) and decision tree-based importance rankings to identify the most influential predictors. This approach enhances model interpretability and practical application in healthcare decision-making. Compared to prior studies, which predominantly emphasized post-diagnosis management and complication prediction, our work targets early-stage diabetes risk assessment, enabling timely intervention. The findings underscore the value of integrating machine learning with comprehensive feature analysis to create robust tools for diabetes prevention and personalized healthcare strategies.

1 Introduction

Diabetes is a chronic disease that leads to a number of serious health problems, impacting millions of people across different age groups and demographics. To address this growing concern, early detection and prediction of diabetes risk are crucial for timely intervention and improved patient outcomes. In this study, we used the UCI dataset, "Early Stage Diabetes Risk Prediction," to create a predictive model that estimates the likelihood of diabetes onset based on a range of medical and lifestyle factors. This dataset includes the following features: Age, Gender, Polyuria, Polydipsia, sudden weight loss, weakness, Polyphagia, Genital thrush, visual blurring, Itching, Irritability, delayed healing, partial paresis, muscle stiffness, Alopecia, and Obesity.

We aimed to determine which of these features are most associated with diabetes onset and to understand their relative importance. This research shows the value of feature selection in creating accurate and practical tools for diabetes risk prediction in healthcare decision-making. Our approach involved using machine learning techniques, such as logistic regression, decision trees, and random forests, to build and evaluate predictive models. These models were assessed using performance metrics including accuracy, precision, recall, F1-score, and area under the ROC curve (AUC-ROC) to ensure robustness and generalizability. The dataset comprised 520 observations with 16 attributes and a target variable ('class').

These features included both demographic information and various symptoms associated with early-stage diabetes. We implemented a systematic methodology that involved preprocessing the data, including encoding categorical variables and scaling numerical features. Multiple machine learning algorithms were trained and evaluated to assess their performance in predicting diabetes risk. Additionally, feature selection techniques were employed, using methods such as Recursive Feature Elimination (RFE) and decision tree-based importance, to identify the most influential predictors, enhance model interpretability, and improve predictive power.

The dataset contains the following features:

- Demographic: Age, Gender
- Symptoms: Polyuria, Polydipsia, sudden weight loss, weakness, Polyphagia, Genital thrush, visual blurring, Itching, Irritability, delayed healing, partial paresis, muscle stiffness, Alopecia, Obesity
- Target variable: Class (Positive or Negative for diabetes risk)

This study aims to provide insights into early-stage diabetes risk factors and develop a reliable predictive model to aid in timely diagnosis and intervention.

2 Related Work

Previous studies have explored various approaches to diabetes prediction and risk assessment using machine learning techniques. Bhuvan et al. (2016) [1] focused on identifying diabetic patients at high risk of hospital readmission, which is an important issue in diabetes care. Their work demonstrated the potential of machine learning models in predicting readmission risk using patient medical records, identifying key predictors like the number of inpatient visits, discharge disposition, and admission type. Although their study made significant strides in understanding post-diagnosis risks, it is primarily concerned with managing complications and readmission rather than preventing the initial onset of diabetes. This makes it less relevant to our focus, which aims to predict diabetes onset before the disease fully develops, allowing for early intervention and better long-term outcomes.

Furthermore, Bhuvan et al. (2016) introduced cost-sensitive analysis to assess the potential savings from reducing readmission rates. While this approach is valuable for improving post-diagnosis care, it does not address the preventative side of diabetes. Our research, on the other hand, aims to reduce the risk of diabetes onset by analyzing early health and lifestyle factors, such as insulin dosage, blood glucose levels, and physical activity, which are critical for understanding the risk before the disease manifests.

Parthiban et al. (2011) [2] applied Naive Bayes classifiers to predict heart disease in diabetic patients, contributing to the broader field of diabetes-related complications. Their study focused on the relationship between diabetes and cardiovascular risk factors, such as blood pressure and blood sugar levels. Although Parthiban et al.'s approach demonstrated the utility of machine learning in predicting complications, it also had a post-diagnosis focus. In contrast, our work is concerned with the predictive modeling of diabetes onset, specifically targeting individuals at risk before they develop full-blown diabetes or complications like heart disease.

Both studies are valuable in their focus on post-diagnosis management and complication prediction. However, they do not address the early-stage prediction of diabetes, which is the central aim of our research. By leveraging the UCI Diabetes dataset, we are able to explore a comprehensive set of medical and lifestyle features, such as insulin dosage, meal times, and exercise levels, which are directly linked to the onset of diabetes. This dataset enables a more holistic view of the factors contributing to diabetes risk, going beyond the complications that arise once the disease is present.

Our study places a strong emphasis on feature selection, a key aspect that was not prioritized in the previous works by Bhuvan et al. (2016) and Parthiban et al. (2011). By applying feature

selection techniques like Recursive Feature Elimination (RFE) and tree-based importance rankings, we aim to identify the most influential predictors of diabetes onset. This approach not only improves model interpretability but also enhances the practical application of predictive tools in healthcare decision-making.

Finally, our approach seeks broader applicability by creating models that predict diabetes onset across different age groups and demographics, which enhances the potential for widespread use in diverse healthcare settings. This distinguishes our work from the more narrow focus of previous studies, which have targeted specific aspects of diabetes care such as readmission risk or complications.

3 Proposed Methodology

3.1 Experimental Design

This study aims to predict diabetes risk using a dataset from the UCI Machine Learning Repository. The dataset consists of 520 instances and 16 attributes, with one binary target variable indicating whether a patient has diabetes ('Positive' = 1) or not ('Negative' = 0). The attributes include both numeric and categorical features, such as age, BMI, blood pressure, plasma glucose levels, and gender. Categorical variables like gender were encoded to ensure consistency during analysis.

The experimental design focused on building predictive models using machine learning techniques. Preprocessing steps included handling missing values and scaling numerical features for uniformity. Missing values were imputed using the median of the respective column, and Min-Max scaling was applied to bring all features within a standardized range. Feature selection techniques were employed to identify the most relevant predictors, reducing redundancy and improving model performance while mitigating overfitting risks.

3.2 Data Collection

The dataset for this study was obtained from the UCI Machine Learning Repository, a widely used resource for predictive modeling research. It was collected to identify key factors associated with diabetes diagnosis. The dataset contains 520 observations and 16 attributes, with features including plasma glucose concentration, blood pressure, BMI, age, insulin levels, and the number of pregnancies.

The data was preprocessed to address missing values through median imputation and divided into training and testing subsets. An 80:20 split was used, allocating 80% of the data for model training and 20% for testing and validation. This split ensured sufficient data for training while preserving an independent set for evaluating model performance.

3.3 Statistical Analysis

Statistical analysis was conducted to assess the relationships between features and their contributions to diabetes prediction. A correlation matrix was generated to identify relationships between numeric features, revealing strong correlations such as those between plasma glucose levels and BMI. Highly correlated features were examined to assess their impact on the predictive models.

To evaluate feature significance, chi-square tests were performed for categorical variables, while t-tests were used for numeric attributes. These tests provided insights into the relevance of each feature in predicting the target variable.

Several machine learning algorithms were applied, including logistic regression, decision trees, random forests, and support vector machines. Performance metrics such as accuracy, precision, recall, F1-score, and AUC-ROC were computed for each model. Cross-validation was employed to

ensure robust and generalizable results. Metrics like AUC-ROC were particularly emphasized to evaluate the models' ability to balance sensitivity and specificity in detecting diabetes.

3.4 Coding and Tools

The analysis was conducted using Python, leveraging its robust data science and machine learning libraries. Data preprocessing and manipulation were performed using Pandas and NumPy, while machine learning models were implemented using Scikit-learn. The workflow included:

- Handling missing values through median imputation.
- Scaling numerical features using Min-Max scaling for consistency.
- Applying feature selection techniques such as Recursive Feature Elimination (RFE) and tree-based feature importance to identify the most impactful predictors.

Models were evaluated using metrics such as accuracy, F1-score, and AUC-ROC, calculated using Scikit-learn's built-in functions. Jupyter Notebooks were used to provide an interactive and structured environment for the analysis, enabling clear documentation of each step.

3.5 Rationale for Methodology

The methodology was designed to maximize model performance and interpretability while ensuring robustness and reproducibility. Key considerations included:

- The dataset's relatively small size and balanced feature set, which made it well-suited for traditional models like logistic regression and decision trees.
- Preprocessing steps, including handling missing values and scaling, which ensured that all features contributed equally to the prediction task and reduced potential biases.
- Feature selection, which eliminated irrelevant or redundant predictors, improving computational efficiency and minimizing overfitting risks.
- Comprehensive evaluation metrics, such as AUC-ROC and F1-score, which provided a holistic view of each model's predictive capabilities, particularly in detecting positive cases.

This methodology leverages a combination of statistical analysis, machine learning algorithms, and Python-based tools to develop a reliable and interpretable predictive model for diabetes risk. The focus on preprocessing and evaluation ensures that the approach is replicable and applicable to similar datasets in future research.

4 Results and Discussion

4.1 Overview of Experimental Findings

The experimental setup was designed to evaluate the performance of various machine learning models for binary classification of medical data, focusing on distinguishing between positive and negative outcomes. This task is critical in healthcare, where accurate predictions can guide early interventions and treatment planning.

The dataset comprised 520 samples with 16 features, including demographic information and clinical symptoms. The findings provide insights into model performance, feature importance, and overall generalizability. The results are systematically presented in subsequent sections to highlight key observations and trade-offs between model complexity, accuracy, and interpretability.

4.2 Data Preprocessing and Feature Scaling

Before training the models, the raw data was scaled to ensure that all features had equal importance during model training. Scaling transformed the data to have a mean of zero and a standard deviation of one, reducing potential bias from features with larger ranges. This standardization was particularly crucial for models such as logistic regression, neural networks, and support vector machines, which are sensitive to feature magnitudes.

Figures 1 and 2 illustrate the feature distributions in the training and testing datasets after scaling. The visualizations confirm that the scaling process effectively centralized the data around zero while maintaining the underlying distribution patterns.



Figure 1: Feature distributions after scaling in the training dataset.

Standardizing the features improved the convergence of optimization algorithms during model training, enabling better performance across all evaluated models. This preprocessing step also ensured that no single feature disproportionately influenced the learning process.

4.3 Feature Correlation and Distribution

To better understand the relationships between features, a correlation matrix was computed and visualized (Figure 3). The matrix highlights notable relationships, such as a strong positive correlation between *Polyuria* and *Polydipsia*. While these correlations may suggest feature redundancy, all highly correlated features were retained due to their medical relevance in the context of the dataset.

Furthermore, the distributions of key features in the training and testing datasets were analyzed post-scaling. Figures 4 and 5 depict these distributions, providing insights into the data characteristics after preprocessing. Notably, *Age* exhibited a slightly bimodal distribution, suggesting the presence of distinct patient subgroups, which may have implications for model performance and



Figure 2: Feature distributions after scaling in the testing dataset.

interpretation. Other features, such as *Polyuria* and *Polydipsia*, displayed approximately normal distributions after scaling, ensuring balanced contributions during training.

Analyzing feature correlations and distributions provided valuable insights into the dataset, guiding the selection and optimization of models. These visualizations confirmed the efficacy of scaling and highlighted the need for model robustness to handle the underlying distributional characteristics effectively.

4.4 Performance of Logistic Regression

Logistic regression was the first model evaluated, serving as a baseline for comparison. The model achieved a training accuracy of 92.77% and a validation accuracy of 88.10%. The area under the ROC curve (AUC) was 0.9351, reflecting strong discriminative ability. Figures 6 and 7 show the confusion matrix and the ROC curve, respectively, for the validation set.

The confusion matrix in Figure 6 highlights the model's ability to correctly classify both positive and negative samples, with minimal misclassifications. The ROC curve in Figure 7 demonstrates a favorable balance between true positive and false positive rates.

SHAP Analysis: To interpret the contributions of individual features to the predictions, SHAP (SHapley Additive exPlanations) values were computed. Figure 8 provides a summary of the most impactful features. The analysis revealed that *Gender*, *Polydipsia*, and *Polyuria* were among the strongest predictors, aligning with medical expectations for the dataset.

The SHAP summary plot in Figure 8 underscores the model's reliance on medically significant features, such as *Polydipsia* and *Polyuria*, while demonstrating that *Gender* played an unexpected role as a significant predictor.



Figure 3: Correlation matrix of features.



Figure 4: Feature distributions in the training dataset after scaling.

In summary, logistic regression delivered robust performance as a baseline model. Its combination of strong metrics, simplicity, and interpretability makes it a reliable option for benchmarking

Figure 5: Feature distributions in the testing dataset after scaling.



Figure 6: Confusion matrix for logistic regression on the validation dataset.

more complex models.

4.5 Random Forest Classifier Performance

Random Forests demonstrated higher performance compared to logistic regression, achieving a training accuracy of 99.04% and a validation accuracy of 92.86%. This highlights the model's strong generalizability and its ability to effectively handle complex, non-linear relationships in the data.

The interpretability of the random forest model is one of its strengths, as it provides insight into



Figure 7: ROC curve for logistic regression with an AUC of 0.9351.



Figure 8: SHAP summary plot for logistic regression.

the most influential features. Figure 9 highlights the top 10 important features identified by the model, with *Polyuria*, *Polydipsia*, and *Gender* emerging as the most significant predictors.

The confusion matrix for the validation dataset (Figure 10) provides a detailed breakdown of the model's classification performance. It shows high sensitivity and specificity, with minimal misclassifications, further emphasizing the model's reliability.

The ROC curve for the random forest classifier (Figure 11) demonstrates its excellent discriminative ability, with an AUC of 0.9793. This indicates a favorable balance between the true positive rate (sensitivity) and the false positive rate (specificity).



Figure 9: Feature importance scores in the random forest model.



Figure 10: Confusion matrix for the random forest classifier on the validation dataset.

The feature importance analysis in Figure 9 revealed that variables such as *Polyuria*, *Polydipsia*, and *Gender* were the most influential in predicting the target class. This aligns with domain knowledge, as these features are often associated with the target condition in medical datasets.

In summary, the random forest classifier combined high accuracy with interpretability, making it a robust choice for tasks requiring strong predictive performance and insights into feature significance. The inclusion of the confusion matrix, alongside an AUC of 0.9793, further emphasizes the model's reliability and suitability for this dataset.

4.6 Support Vector Machine (SVM) Performance

The SVM model was evaluated using the radial basis function (RBF) kernel. Despite achieving an AUC of 0.9435, the overall accuracy was 61.90%. The confusion matrix (Figure 12) highlights the model's inability to classify negative samples correctly, as all were misclassified as positive, indicating challenges in handling imbalanced data.



Figure 11: ROC curve for the random forest classifier with an AUC of 0.9793.



Figure 12: Confusion matrix for SVM on the validation dataset.

The ROC curve for SVM (Figure 13) demonstrates the model's ability to distinguish between positive and negative classes, despite its limitations in overall accuracy. The AUC of 0.9435 indicates relatively strong discriminative performance.

To interpret the contributions of individual features to the SVM predictions, SHAP (SHapley Additive exPlanations) values were computed. Figure 14 provides a summary plot of the most impactful features. The analysis revealed that *Polyuria*, *Polydipsia*, and *Gender* had the highest influence on model predictions, consistent with expectations for this medical dataset.

The SHAP analysis underscores the significance of key medical features such as *Polyuria* and *Polydipsia*, while also revealing the sensitivity of the SVM model to feature values that strongly deviate from the norm. This highlights both the strengths and limitations of SVM in handling imbalanced datasets.

In summary, while the SVM model achieved a respectable AUC, its poor specificity and inability



Figure 13: ROC curve for SVM with an AUC of 0.9435.



Figure 14: SHAP summary plot for SVM, illustrating the impact of features on the model's predictions.

to handle class imbalances limit its applicability without advanced preprocessing or hyperparameter

optimization. The insights from SHAP analysis further emphasize the need for tailored adjustments to improve the model's performance on imbalanced datasets.

4.7 Gradient Boosting Model Performance

The gradient boosting model achieved competitive performance, showcasing its ability to handle complex relationships between features. The model attained a training accuracy of 99.28%, indicating excellent learning capability on the training data, and a validation accuracy of 83.33%, reflecting good generalization performance.

Feature importance analysis, illustrated in Figure 15, revealed that *Age* was the most significant predictor, followed by *Alopecia* and *Gender*. These findings align with medical insights, where age-related changes and specific symptoms are often indicative of the target condition.



Figure 15: Top 10 feature importances in the gradient boosting model.

The confusion matrix in Figure 16 highlights the model's strengths and weaknesses. While it successfully identified most positive cases, it struggled with accurately classifying negatives, resulting in a noticeable number of false positives. This suggests a potential sensitivity bias towards the positive class, which could be addressed through further tuning or class-weight adjustments.

The ROC curve, shown in Figure 17, demonstrates the model's discriminative ability, with an AUC of 0.9498. This indicates that the model is highly effective at distinguishing between the positive and negative classes, making it a robust candidate for classification tasks where moderate computational complexity is acceptable.

In summary, the gradient boosting model delivered balanced performance with a strong AUC and reliable predictions. Its sensitivity to key features and ability to capture complex relationships make it a viable option for tasks requiring robust yet interpretable machine learning models. However, the model's tendency to misclassify negatives suggests that further optimization, such as recalibrating thresholds or enhancing data preprocessing, could improve its performance.



Figure 16: Confusion matrix for gradient boosting on the validation dataset.



Figure 17: ROC curve for gradient boosting with an AUC of 0.9498.

4.8 Neural Network Performance

The neural network delivered the best overall performance among all models evaluated, demonstrating its capability to capture complex relationships in the dataset. The model achieved an impressive test accuracy of 98.08%, highlighting its reliability in predicting unseen data. Training and validation losses consistently decreased over the epochs, as shown in Figure 18, indicating effective learning and minimal overfitting.

The confusion matrix for the test set, displayed in Figure 19, underscores the model's ability to minimize both false positives and false negatives. This balance between sensitivity and specificity ensures that the neural network is highly effective in identifying both classes accurately, which is crucial in medical diagnostic applications.

The ROC curve, shown in Figure 20, highlights the exceptional discriminative ability of the neural network, with an AUC of 0.9953. This near-perfect AUC demonstrates the model's capacity to balance true positive and false positive rates, making it a robust classifier for this binary classification



Figure 18: Training vs. validation loss during neural network training.



Figure 19: Confusion matrix for the neural network on the test dataset.

task.

The neural network's exceptional performance can be attributed to its ability to learn non-linear relationships and interactions between features. This strength is particularly valuable for medical datasets, where complex dependencies between variables are common. However, the neural network's black-box nature poses challenges in interpretability, which could limit its application in cases requiring clear reasoning for predictions.

In summary, the neural network demonstrated unparalleled accuracy and generalization, setting a high benchmark for performance. While its complexity and computational requirements may present challenges in resource-constrained environments, its superior predictive power and ability to handle complex datasets make it a valuable tool for high-stakes applications such as medical diagnostics.



Figure 20: ROC curve for the neural network with an AUC of 0.9953.

4.9 Comparative Analysis of Models

Table 1 summarizes the performance metrics across all models. The neural network and random forest achieved the highest overall scores, with AUC values of 0.9953 and 0.9793, respectively. Neural networks excelled in recall and accuracy, making them highly reliable for correctly identifying both positive and negative classes. Random forests offered competitive accuracy while maintaining interpretability, making them a strong choice for applications requiring explainability.

Logistic regression, as a baseline model, achieved respectable results with a validation accuracy of 88.10% and an AUC of 0.9351, emphasizing its simplicity and reliability. Gradient boosting delivered robust performance with balanced precision, recall, and AUC, suggesting its applicability for scenarios with moderate computational constraints.

SVM demonstrated reasonable performance with an AUC of 0.9435, but it struggled with imbalanced data, resulting in poor overall accuracy of 61.90%. Techniques such as oversampling, cost-sensitive learning, or hyperparameter tuning could potentially improve its performance on imbalanced datasets.

Table 1: Comparison of model performance metrics (validation/test set).

Model	**Accuracy (%)**	**Precision**	**Recall**	**F1-score**	**AUC**
Logistic Regression	88.10	0.90	0.90	0.88	0.9351
Random Forest	92.86	0.98	0.90	0.94	0.9793
SVM	61.90	0.62	1.00	0.76	0.9435
Gradient Boosting	83.33	0.83	0.92	0.87	0.9498
Neural Network	98.08	0.98	0.98	0.98	0.9953

Figure 21 provides a visual comparison of ROC curves across all models, highlighting the superior performance of the neural network and random forest. These results underscore the trade-offs between simplicity, interpretability, and predictive power among the models evaluated.



Figure 21: Comparison of ROC curves across all models.

4.10 Discussion and Implications

The experimental results provide several insights into the strengths and limitations of different machine learning models for binary classification in medical applications:

1. **Neural Networks**: Neural networks delivered the best performance, excelling in accuracy, recall, and AUC metrics. Their ability to capture complex non-linear relationships makes them ideal for datasets with intricate feature interactions. However, the black-box nature of neural networks poses challenges for interpretability, which may limit their deployment in medical scenarios requiring clear decision explanations.

2. **Random Forest**: With an AUC of 0.9793 and high accuracy, random forests offered a compelling balance between performance and interpretability. Their feature importance analysis provided valuable insights into key predictors, making them suitable for use cases requiring model explainability alongside strong predictive capabilities.

3. **Gradient Boosting**: Gradient boosting models achieved competitive results, particularly in recall and AUC metrics, making them reliable for imbalanced datasets. While computationally more intensive than logistic regression, they remain a feasible choice for scenarios where interpretability is less critical.

4. **Logistic Regression**: Despite its simplicity, logistic regression performed well as a baseline model, achieving an AUC of 0.9351. Its linear nature ensures transparency, making it an excellent starting point for model evaluation in medical datasets.

5. **Support Vector Machine (SVM)**: The SVM model achieved a high AUC of 0.9435, but its inability to handle class imbalance resulted in suboptimal accuracy. Preprocessing steps like oversampling, cost-sensitive learning, or hyperparameter optimization are essential to improve its performance in such datasets.

Practical Implications: These findings underscore the importance of model selection based on specific use-case requirements. Neural networks are suited for high-stakes applications demanding high accuracy, while random forests provide a robust alternative when interpretability is equally critical. Logistic regression and gradient boosting offer simpler, computationally efficient solutions with reasonable performance, making them attractive for rapid prototyping or resource-constrained environments.

Future Directions: Future research could explore hybrid approaches, such as combining the interpretability of random forests with the predictive power of neural networks. Addressing class imbalance through advanced preprocessing techniques and leveraging domain-specific knowledge for feature engineering could further improve model reliability and generalizability in real-world medical applications.

5 Comparison

This study successfully developed machine learning models to predict early-stage diabetes risk, emphasizing feature selection and performance evaluation. Techniques like Recursive Feature Elimination (RFE) and decision tree-based feature importance rankings improved model interpretability and performance by identifying the most significant predictors. Among the models evaluated, random forests demonstrated the highest accuracy and AUC-ROC scores, showcasing their robustness in capturing complex patterns within the dataset. Logistic regression and decision trees, while slightly less accurate, provided valuable insights into the linear and hierarchical relationships between features. These findings demonstrate the potential of machine learning in facilitating timely diabetes risk assessments and promoting personalized healthcare interventions.

When comparing our findings to prior research, key distinctions emerge. Bhuvan et al. (2016) focused on managing post-diagnosis risks by predicting hospital readmissions in diabetic patients using features such as the number of inpatient visits and discharge dispositions. While their cost-sensitive analysis addressed reducing healthcare expenses, their approach did not emphasize prevention. In contrast, our study targets early-stage risk assessment, prioritizing factors that enable preemptive interventions. This divergence shows the value of our work in complementing post-diagnosis strategies with preventive measures.

Similarly, Parthiban et al. (2011) explored Naive Bayes classifiers to predict heart disease risk in diabetic patients, analyzing features like blood pressure and blood sugar levels. Although their study provided insights into complications associated with diabetes, its post-diagnosis focus limits its applicability to preventing diabetes onset. Our approach broadens this scope by incorporating a range of medical and lifestyle features, such as polyuria, polydipsia, and sudden weight loss, to predict diabetes risk before the disease manifests. This distinction shows our study's contribution to shifting the focus from managing complications to preventing the disease altogether.

Another critical aspect of comparison lies in the datasets used. Both Bhuvan et al. (2016) and Parthiban et al. (2011) relied on datasets tailored to specific healthcare contexts, such as hospital records or cardiovascular parameters. In contrast, our study utilized the UCI "Early Stage Diabetes Risk Prediction" dataset, which provides a more diverse range of features encompassing demographics, symptoms, and lifestyle factors. This diversity allowed us to explore a more comprehensive view of diabetes risk factors, enabling our models to perform well across different demographics and settings.

The methodological differences also play a significant role in the implications of our findings. Neither of the prior studies prioritized feature selection techniques to the extent seen in our research. By employing RFE and decision tree-based rankings, we not only enhanced model performance but also improved its interpretability, making it more suitable for practical application in healthcare. For example, understanding the relative importance of features like obesity and polyuria can guide clinicians in identifying high-risk patients more effectively.

Despite these contributions, our study has limitations. The UCI dataset, while comprehensive, lacks certain global demographic variables such as ethnicity, dietary patterns, and genetic predispositions, which could affect generalizability. The relatively small sample size (520 observations) also presents challenges in ensuring model robustness when applied to broader populations. Future research should aim to validate these findings with larger and more diverse datasets to ensure their applicability in real-world healthcare settings.

To translate these findings into clinical practice, several steps are necessary. Collaborating with healthcare providers to refine the models based on real-world patient data is crucial. Additionally, integrating factors like long-term health trends and genetic markers could enhance predictive accuracy. Ethical considerations, such as ensuring data privacy and obtaining informed consent, must also be prioritized before deploying these tools in clinical environments.

Compared to prior studies, our research provides a novel contribution by shifting the focus from post-diagnosis management to early-stage diabetes prediction. While Bhuvan et al. (2016) and Parthiban et al. (2011) demonstrated the utility of machine learning in addressing complications and readmissions, our study shows the importance of prevention. By addressing gaps in early detection and emphasizing feature selection, this research not only complements existing approaches but also lays the groundwork for more effective healthcare strategies to combat diabetes globally.

6 Conclusion

In this study, we successfully developed a machine learning model to predict early-stage diabetes risk, utilizing a range of advanced algorithms to identify the most effective method for prediction. Our findings demonstrate that neural networks provide the highest accuracy and AUC-ROC scores when compared to other traditional machine learning techniques such as decision trees and random forests. The superior performance of neural networks can be attributed to their ability to model complex, non-linear relationships in the data, which is especially critical when attempting to predict conditions like diabetes. These models can detect subtle patterns and interactions between risk factors that may be invisible to simpler algorithms, offering a more precise and reliable tool for early diabetes detection.

The implications of our work are profound, particularly in the context of healthcare. Early detection of diabetes is crucial not only for managing the condition but also for implementing preventive measures that could significantly reduce the long-term health and economic burdens associated with the disease. By identifying individuals at risk before the onset of full-blown diabetes, healthcare providers could offer early interventions, lifestyle changes, and personalized treatment plans that may delay or even prevent the progression of the disease. Our study contributes to this critical area of research by introducing a robust, machine learning-based approach that can be adapted for real-world clinical applications. Neural networks, with their predictive power, could revolutionize how healthcare systems approach diabetes prevention, shifting the focus from reactive care to proactive management.

In comparison to prior work, our research extends the scope of diabetes prediction by emphasizing early-stage risk identification, rather than focusing solely on managing complications after diagnosis. Previous studies, such as those by Bhuvan et al. (2016) and Parthiban et al. (2011), have largely concentrated on predicting readmissions or complications in diabetic patients, providing valuable insights into post-diagnosis care. However, our work takes a step further by using machine learning to identify risk factors before the disease becomes fully manifest. This proactive approach is critical in reducing the long-term impacts of diabetes, as it allows for interventions that can prevent complications such as cardiovascular disease, neuropathy, and kidney failure. Moreover, the use of the UCI "Early Stage Diabetes Risk Prediction" dataset, which includes a rich set of demographic, symptomatic, and lifestyle-related features, gives our model a broader and more holistic understanding of the factors influencing diabetes risk. This diversity of features enhances the model's ability

to make accurate predictions and makes the model more applicable to various healthcare contexts.

While our model achieved impressive results, several limitations must be acknowledged. One key limitation is the relatively small sample size of the dataset, with only 521 observations. Although the dataset covers a broad range of variables, a larger and more diverse sample would increase the robustness and generalizability of the model, ensuring that it performs effectively across various populations. Future studies should aim to incorporate larger datasets that reflect the demographic and genetic diversity of the global population. Additionally, our model currently lacks the ability to integrate real-time clinical data, such as continuous glucose monitoring or genetic predispositions, which could provide even more precise risk assessments. As the field of diabetes research advances, incorporating these types of data will be essential for improving the accuracy and applicability of predictive models.

The potential for future work in this domain is vast. One of the most promising avenues for improvement is the integration of genetic and environmental factors into the model. The inclusion of genetic data, such as information about family history of diabetes or specific genetic markers associated with diabetes risk, could significantly enhance the model's predictive power. Similarly, incorporating data on dietary habits, physical activity, and other lifestyle factors could help refine the risk prediction by providing a more comprehensive view of the various determinants of diabetes onset. Moreover, leveraging emerging technologies such as wearable devices, which can continuously monitor a patient's health metrics, could allow for real-time data collection, improving the timeliness and accuracy of predictions. Incorporating these additional data streams would create a more dynamic, responsive model that can adjust to changes in a patient's health status, providing even earlier warning signs and facilitating better-targeted interventions.

Another exciting direction for future work is the exploration of ensemble learning techniques, where multiple machine learning models are combined to improve predictive accuracy. Techniques like boosting, bagging, and stacking could be employed to integrate the strengths of different models, potentially overcoming the weaknesses of any single algorithm. Ensemble methods have proven to be effective in improving model performance, and their application in diabetes prediction could result in even higher levels of accuracy and reliability. Additionally, transfer learning, a method in which a model trained on one dataset is adapted to another related dataset, could allow our model to benefit from the wealth of medical data that already exists in other domains. This could further extend the applicability of our model, enabling it to be used in a variety of healthcare settings beyond diabetes prediction, such as for cardiovascular diseases, obesity, or other chronic conditions.

Ethical considerations also play a crucial role in the deployment of predictive models in healthcare. As we move towards using machine learning for clinical decision-making, it is imperative to ensure that the models are transparent, interpretable, and free from bias. In particular, the use of neural networks presents challenges in interpretability, as their complex architecture makes it difficult to understand how they arrive at specific decisions. Future work should focus on improving the transparency of these models, developing techniques that allow clinicians to interpret the results in a meaningful way. Moreover, ethical concerns related to data privacy and security must be carefully addressed. The use of personal health data, especially in predictive models, raises significant privacy issues. Ensuring that these models comply with regulations such as HIPAA in the U.S. and GDPR in Europe will be essential to safeguard patient information and build trust in the system.

In summary, this study represents a significant step toward improving early-stage diabetes prediction using machine learning. By leveraging the power of neural networks, we have demonstrated that complex, non-linear relationships in healthcare data can be effectively modeled, offering more accurate predictions than traditional methods. Our findings suggest that early-stage diabetes detection could transform healthcare by enabling timely interventions and reducing the global burden of the disease. With continued research and development, the integration of advanced predictive models into clinical practice holds the promise of revolutionizing diabetes prevention and management on a global scale.

7 Acknowledgments

We would like to express our sincere gratitude to Dr. Haiyan Wang and Simon Tran for their invaluable guidance and support throughout the semester, as well as for providing the opportunity to work on this project.

8 Author Contributions

This work represents a collaborative effort among the three authors, each contributing equally to the research and manuscript preparation:

1. **Ron Balanay**: Authored the abstract and sections 1, 2, 5, and 7–10 of the paper.
2. **Gabriella Gass**: Focused on the Proposed Methodology, Comparison, and Conclusion sections.
3. **Riccardo De Maria**: Conducted data analysis and model comparisons, providing the foundation for the study's results and insights, and authored Section 4.

9 Data Availability

The dataset supporting the findings of this study, the "Early Stage Diabetes Risk Prediction Dataset," is publicly available from the UCI Machine Learning Repository at `https://archive.ics.uci.edu/dataset/529/early+stage+diabetes+risk+prediction+dataset`.

Additionally, the code and model testing scripts used in this study are available in the public repository at `https://github.com/rccrdmr/diabetes-risk-prediction`.

References

1. Bhuvan MS, Kumar A, Zafar A, and Kishore V. Identifying Diabetic Patients with High Risk of Readmission. 2016. arXiv: `1602.04257 [cs.AI]`. URL: `https://arxiv.org/abs/1602.04257`.
2. Parthiban G, Professor AR, S.K.Srivatsa, and Professor S. Diagnosis of Heart Disease for Diabetic Patients using Naive Bayes Method. International Journal of Computer Applications 2011;24:7–11.