NexoTech · UX Content Strategy

RAMÓN A. CURBALÁN VEGA · ENGLISH EDITION

NEXOTECH / UX RESEARCH AND CONTENT STRATEGY Visual report · July 12, 2026 | 1 NEXO / UX UX strategy to reactivate content technological Research, information architecture and testing prototype CHALLENGE Recover visibility, participation and recurrence in the blog, social networks and newsletter through a more findable, relevant and actionable experience.

CASE STUDY Organization Audience Centerpiece NexoTech (fictional case) Digital professionals and students Article: “How to get started with AI generative safely” Academic deliverable · version 1.0

NEXOTECH / UX RESEARCH AND CONTENT STRATEGY Visual report · July 12, 2026 | 2

1. Executive summary Engagement drop is interpreted as an entire experience issue, not just volume editorial. The proposal connects research, content organization, design of the piece and measurement.

Finding/hypothesis Design decision Indicator Overload and Level Mixing Paths by Objective and Level Task Success/Depth Correct headlines but little utility-oriented Promise + time + level + CTR result and useful reading Little continuity between channels Save, follow topic and newsletter contextual Return and subscription Generic or late CTAs Micro-CTAs after the first value Engagement and conversion 90-DAY GOAL Increase CTR towards content by 20%, interaction by 15% significant and 10% recurrence. They are project goals, not already obtained results.

Proposed process Benchmark interviews and analytics card sorting architecture prioritization prototype Figma → → → → → → moderated test iteration A/B experiment.→ →

2. Success Reference: HubSpot Blog HubSpot Blog is selected as a functional benchmark due to its status as an editorial hub technological/commercial, your navigation through blogs and topics, visible search, content in various formats, explicit updating, contextual newsletter and calls to action connected to the topic.

Observed Practice UX Value Adaptation to NexoTech Architecture by areas and themes Reduces the uncertainty of navigation AI, Cybersecurity, Programming and Digital transformation Accessible search Solve specific needs Predictive search with filters level and format Visible metadata Helps decide before clicking Time, level, date, author and update Mix article + video Support consumer preferences Text, summary, short video and resource downloadable Contextual subscription Converts specific interest into a relationship Follow topic and choose frequency High contrast Broad WCAG AA accessibility, visible focus and controls clear What not to copy literally • Commercial density and extensive menus: NexoTech must prioritize learning and clarity. • The number of categories: the main navigation will be limited to six options. • Repetitive conversion patterns: each CTA must correspond to the moment and the content. CRITERION Benchmarking does not mean visual imitation; means detecting transferable principles and validate them with your own audience.

3. Research and design requirements Research plan Method Sample/Source Answering Question Analytics and funnels 90 days, by channel/device Where do they abandon and what content returns?

Semi-structured interviews 8 users: 4 students, 4 What do professionals consider useful and credible? Hybrid card sorting 15–20 participants How do you group and name the contents? Tree testing 20 participants. Do they find what they are looking for in AI?

proposal? Prototype testing 5–8 users per round Do they understand, find and Do they interact?

Derived requirements (hypotheses) • R1. Show level, duration, format and date before opening a piece. • R2. Allow exploration by objective (“learn”, “solve”, “upgrade”) and by topic. • R3. Include initial summary, anchored index, and scannable examples. • R4. Offer to save, share with context and follow a topic without interrupting reading. • R5. Maintain responsive experience, keyboard navigation, AA contrast and resizable text. • R6. Instrument events: impression, open, 50/90% scroll, save, share, CTA and return.

4. Card sorting: preferences and perception A hybrid card sorting is proposed: four initial categories and freedom to create or rename groups. The figures below are a simulated pilot exercise to show how the data would be analyzed; they must be replaced by real results.

Cards Expected Group Content Cards AI and data First prompt; Automation; AI Ethics; Analysis of data Cybersecurity Phishing; Passwords; Privacy; Incident response Basic Python Programming; APIs; Git; Web development digital work tools; Productivity; Tendencies; Success stories Simulated pilot: patterns Grouping Consistency Reading Python + Git + APIs + Web 88% “Programming” is a label stable Phishing + Passwords + Privacy 84% “Security” is more natural than “Cyber defense” Prompts + Automation + AI 76% “Practical AI” outperforms “Innovation” Productivity + Tools 72% Perceived as work utility Trends + Success stories 48% Ambiguous: it is advisable to separate them by intention RESULTING AI Learn · Solve · News · Resources, with transversal Topic filters, Level, Format and Duration.

5. Information architecture proposal Level 1 Level 2 / behavior Learn Guided Routes · Short courses · Basic concepts Solve Tutorials · Templates · Bug Fixes Current News Explained · Trends · Analysis Resources Guides · Checklists · Tools Topics AI and data · Security · Programming · Digital work My space Saved · Followed topics · Preferences Labeling principles • User words before internal taxonomy. • Mutually understandable categories; overlaps are resolved with filters and labels. • The same piece has a primary location and can appear in secondary collections. • The architecture must be validated with tree testing; card sorting generates hypotheses, not navigation definitive.

Search and filters The search will suggest queries and display results with level, format, duration and date chips. The Filters will be persistent throughout the session and will have a clear reset option.

NEXOTECH / UX RESEARCH AND CONTENT STRATEGY Visual report · July 12, 2026 | 7

6. Empathy map Analyzed piece: “How to get started with generative AI safely.” Provisional person: Lucía, 29 years, administrative who wants to incorporate AI without advanced technical knowledge.

SAY THINK “I want examples that I can apply today.” “I need to know what data I should not share.” “I don't want to be left behind.” “Can I trust this tool?” IT MAKES YOU FEEL Search Google, scan subtitles, save guides and contrast two sources. Drop if the text starts with extensive theory.

Curiosity and urgency; certain technical insecurity; relief when you find clear steps and limits.

Pains Expected earnings Jargon, lack of time, fear of mistakes, few examples realistic.

Secure checklist, replicable example, credibility and feeling of progress. DESIGN OPPORTUNITY Open with a 60 second summary, indicate “initial level · 7 min”, show a privacy alert before the example and close with a saveable template.

7. Content prioritization MoSCoW matrix Content/function priority MUST Task-oriented title; summary; index; level/time; sources; examples; accessibility; CTA save/follow topic; measurement.

SHOULD Short video; content related by intent; contextual newsletter; author profile; review date.

COULD Advanced customization; progress; comments moderate; audio mode; light gamification.

WON'T (now) Open forum, social wall, AI opaque recommendations and native app.

Impact/effort matrix Initiative Impact (1–5) Effort (1–5) Decision Metadata + summary 5 1 Do now New AI + filters 5 3 Priority Save/follow topic 4 2 Priority Video in each article 3 4 Selective Personalization with AI 3 5 After Social forum 2 5 Not now RULE Findability and clarity are corrected first; then personalization is added.

Automating chaos only produces chaos faster.

8. Visual prototype for Figma The prototype should be of medium-high fidelity and focus on an evaluable flow. No need to do entire web clickable; yes each task-relevant decision.

Frame Key Content Interaction

1. Home / Search hub, routes by intent, topics and featured piece Search or choose “Learn”

2. Results Filters, chips, order and cards with metadata Filter: AI + initial + <10 min

3. Article summary, index, alert privacy, example, progress Save and advance by anchors

4. Downloadable and upcoming Checklist resource steps Open template

5. Subscription Topic, Frequency and Preview Confirm “Practical/Weekly AI” visual system Item Specification Color Blue #176B87; turquoise #64CCC5; background #EDF6F8; orange #F59E0B for emphasis only Typography Inter or Aptos; 16px base; line 1.5; reading width 65–75 characters Components Cards, chips, search engine, sticky index, progress, CTA primary/secondary, alerts Accessibility Contrast AA; visible focus; targets 44px; labels; not ≥ depend only on the color

9. Usability test script Participants and protocol First round: 5–8 participants, balancing students and digitally competent professionals basic/intermediate. 30-minute moderated sessions, consent, think aloud, and closure with abbreviated SUS or UMUX-Lite.

Task Success Criterion Metric Find an AI starter guide from less than 10 minutes Get to the article without help Success, time, route and errors Identify what data should not be share Locate and understand the alert Correct answer + confidence Save the guide to review it later Press “Save” and understand the status Success + perception Only subscribe to AI frequently weekly Select topic and frequency Success + abandonment Explain what you would do next Recognize checklist or piece related Understanding and intention Decision thresholds • Success per task 80%.≥ • Median time to find a piece 60 s.≤ • Critical errors 10% of sessions.≤ • Understanding the 90% privacy alert.≥ • UMUX-Lite 70/100 as internal reference.≥ MODERATION Do not explain the interface or confirm that an action is correct. Ask: “What “Did you expect it to happen?” and record behavior before opinion.

10. Measurement, roadmap and closure Phase Weeks Exit Discover 1–2 Analytics, interviews, inventory and benchmark Structure 3–4 Card sorting, AI, tree testing and MoSCoW Prototype 5–6 Figma, components and content realistic Validate 7 Tests, severity and second iteration Experiment 8–12 controlled A/B and tracking cohorts Dashboard Target Main Guardrail Indicator Findability Search/task success Reformulations and zero results Helpful interaction Save, share, open resource Don't bloat with accidental clicks Depth 90% scroll + interaction Active time, not tab time Recurrence Return within 7/30 days Cancellations and newsletter fatigue Conversion Subscription by topic Confirmation and unsubscription rate Conclusion The strategy shifts the focus from “publishing more” to “helping better.” The priority is that each user understands what they will find, arrives without friction, obtains value in the first seconds and has of a relevant next action. The attached infographic summarizes this logic to reconstruct it as board or prototype in Figma.

Sources consulted • HubSpot Blog — https://blog.hubspot.com/ • Nielsen Norman Group, Card Sorting — https://www.nngroup.com/articles/card-sorting-definition/ • Nielsen Norman Group, Empathy Mapping — https://www.nngroup.com/articles/empathy-mapping/ • Nielsen Norman Group, Card Sorting vs. Tree Testing — https://www.nngroup.com/articles/card-sorting-tree-testing-differences/ • Figma, AI Usability Testing Guide — https://www.figma.com/resource-library/ai-usability-testing/