

# Algorithms for Interviews

Raymond Xu

[raymond@adicu.com](mailto:raymond@adicu.com)

[raymondxu.io](http://raymondxu.io)



# This Talk

---

Sequel to [Data Structures for Interviews](#)

- This talk is more challenging
- Assumes data structures proficiency

*for each:*

- Basic Principles
- Example Problems
- Study Guide

# Outline

---

Sorting

Recursion

Greedy

Dynamic Programming

# Outline

---

Sorting

Recursion

Greedy

Dynamic Programming

# Sorting

---

Given a **collection** of comparable elements, sort them.

Collection: Array, ArrayList, LinkedList, Stack, Queue

# (Relevant) Sorting Algorithms

---

Slowest

$O(n^2)$

Selection Sort, Insertion Sort

$O(n \log n)$

Quicksort, Mergesort, Heapsort

$O(n)$

Bucket Sort, Radix Sort

Fastest

# Lightning Review of Sorts!

# Selection Sort

---

Repeatedly select the smallest unsorted element and place it right after the sorted elements.



# Insertion Sort

---

Repeatedly slide each element left until it is in the proper relative place.

# Bucket Sort

---

Scatter elements into buckets, sort within each bucket, and combine the buckets.

# Radix Sort

---

Sort within significant positions for all significant positions.

# Heapsort

---

**Build a heap and repeatedly extract the root.**

$O(n \log n)$

# Mergesort

---

Repeatedly divide lists into two sublists, repeatedly merge the sublists together in sorted order.

> Recursion Tree Breakdown

# Quicksort

---

Sort elements only with respect to a pivot such that the pivot is in its final location,  
Recur on left and right sublists.

> Recursion Tree Breakdown

# Study Guide

---

Implement the  $n \log n$  sorts.

What are the best and worst case inputs for each sort?

- Runtimes?

How do you sort a Linked List? How about a stack or queue?

- Runtimes?

- Space complexities?

# Outline

---

Sorting

Recursion

Greedy

Dynamic Programming



# Recursion

---

Use recursion when the solution to the problem depends on solutions to smaller instances of the same problem.

## > Fibonacci Recursion Tree Breakdown

$$\text{fib}(0) = 1$$

$$\text{fib}(1) = 1$$

$$\text{fib}(n) = \text{fib}(n-2) + \text{fib}(n-1) \quad \text{for } n > 1$$

# Divide and Conquer

---

**Dividing a problem into subproblems that are solved recursively and then combined to solve the original problem.**

# Divide and Conquer

---

Dividing a problem into subproblems that are solved recursively and then combined to solve the original problem.

Examples:

- Binary search

- Quicksort

- Mergesort

- Fast Integer Multiplication

# Recursion

---

## BST Sum

- Find the sum of a BST where each node has an integer


## Linked List Merge

- Merge two sorted Linked Lists in place

# BST Sum

---


**Problem:** Find the sum of all the nodes in a BST where each node has an integer.



# BST Sum

---

**Solution:** Pass the values of the each node from the leaves to the root and sum them off of the recursive stack.



# BST Sum

---

```
int bstSum(Node n) {  
    if (n == null)  
        return 0;  
    return n.value + bstSum(n.left) +  
           bstSum(n.right);  
}
```

# Linked List Merge

---

**Problem:** Merge two sorted Linked Lists in place.



# Linked List Merge

---

**Problem:** Merge two sorted Linked Lists in place.

**Solution:** Use recursion to pass back the appropriate “next” node to the previous nodes.

# Linked List Merge

---

```
Node merge(Node list1, Node list2) {  
    if (list1 == null) { return list2; }  
    if (list2 == null) { return list1; }  
  
    if (list1.val < list2.val) {  
        list1.next = merge(list1.next, list2);  
        return list1;  
    }  
    else {  
        list2.next = merge(list1, list2.next);  
        return list2;  
    }  
}
```

# Study Guide

---

**Practice a lot of recursion problems:**

- Develop base case instinct**
- Learn data passing themes**
- Analyze runtime**

**Trees, sorting, searching**

# Outline

---

Sorting

Recursion

Greedy

Dynamic Programming

# Greedy

---

**Greedy algorithms take the optimal choice at each local step, which produces an optimal/almost-optimal global result.**

# Greedy

---

## Coin change

- Minimum number of coins needed to represent  $n$  cents

## Kruskal's Algorithm

- Minimum Spanning Tree

# Coin Change

---

**Problem:** Find the minimum number of coins needed to represent  $n$  cents.

# Coin Change

---

**Problem:** Find the minimum number of coins needed to represent  $n$  cents.

**Solution:** Starting from the largest denomination, use as many coins as you can until you have to move to a smaller denomination.



# Coin Change

---

```
int coinChange(int n) {  
    int numCoins = 0;  
  
    while (n >= 25) {  
        n -= 25;  
        numCoins++;  
    }  
    while (n >= 10) {  
        n -= 10;  
        numCoins++;  
    }  
    ...  
    return numCoins;  
}
```

# Kruskal's Algorithm

---

**Problem:** Find a Minimum Spanning Tree of a graph.

# Kruskal's Algorithm

---

**Problem:** Find a Minimum Spanning Tree of a graph.

**Solution:** Repeatedly select the smallest edge that does not form a cycle with the selected edges.

# Kruskal's Algorithm

---

```
function kruskal(set of edges) {  
  -init a set of edges to represent the MST edges  
  -init a set for each vertex (to detect cycles)  
  -init a min heap and add all graph edges into it  
  -while heap is not empty:  
    -pop the min edge  
    -if the min edge does not form a cycle with the  
      MST edges:  
      -add the edge to the MST edges set  
      -union the vertex sets  
  -return the MST edges set  
}
```

# Study Guide

---

**Study common greedy problems:**

- Activity Scheduling**
- Coin Change**
- MST**
- Graph Bipartition**

**Build intuition on whether a greedy strategy could be applicable to a problem**

# Outline

---

Sorting

Recursion

Greedy

Dynamic Programming

# Dynamic Programming

---

**Building up to an optimal solution to a problem using the optimal solutions to subproblems.**

# DP

---

## DP

- bottom-up
- optimal substructure
- overlapping, repeating subproblems
- tabulation vs memoization



# DP vs Recursion

---

## DP

- bottom-up
- optimal substructure
- overlapping, repeating subproblems
- tabulation vs memoization

## Recursion

- top-down
- distinct subproblems

# Dynamic Programming

---

## Rod Cutting

- Cut a rod into discrete pieces, each length has a value, maximize value

## Longest Increasing Subsequence

- Find the length of the longest subsequence in an array of integers

# Rod Cutting

---

**Problem:** Given a rod of length  $n$ , a table of lengths and values, and unlimited cuts, determine the maximum value obtainable.

# Rod Cutting

---

**Problem:** Given a rod of length  $n$ , a table of lengths and values, and unlimited cuts, determine the maximum value obtainable.

value	1	5	8	9	10	17	18	20
length	1	2	3	4	5	6	7	8

For  $n = 8$ , the maximum value is 22 by cutting the rod into two rods of lengths 2 and 6.

# Rod Cutting

---

## Solution:

$dp[i]$  stores the optimal value attainable from a rod of length  $i$

Compute  $dp[i]$  by considering all indices  $j$  less than  $i$   
find the maximum  $(value[i] + dp[j - 1])$  and set  $dp[i]$  to this value

The solution is in  $dp[n]$

# Rod Cutting

---

```
int cutRod(int[] value, int n) {  
    int[] dp = new int[n + 1];  
  
    for (int i = 1; i <= n; i++) {  
        int max = Integer.MIN_VALUE;  
        for (int j = 1; j < i; j++) {  
            max = Math.max(max, value[j]  
                           + dp[i - j]);  
        }  
        dp[i] = max;  
    }  
    return dp[n];  
}
```

# Rod Cutting

---

**Time Complexity:  $O(n^2)$**

**Space Complexity:  $O(n)$**

**Classic recursive solution has a time complexity of  $O(2^N)$**

# Longest Increasing Subsequence

---

**Problem:** Find the length of the longest increasing subsequence in an array of integers.



# Longest Increasing Subsequence

---

**Problem:** Find the length of the longest increasing subsequence in an array of integers.

```
arr = [8, 2, 5, 3, 10, 1, 30, 76]  
lis = [2, 5, 10, 30, 76]
```

# Longest Increasing Subsequence

---

## Solution:

$dp[i]$  stores the length of the LIS that ends at the element at index  $i$

Compute  $dp[i]$  by considering all indices  $j$  less than  $i$   
if  $(dp[j] + 1 > dp[i])$  and  $(arr[j] < arr[i])$   
then we can update  $dp[i]$

The solution is the maximum value in the  $dp$  array

# Longest Increasing Subsequence

---

```
int lis(int[] arr) {  
    // Initialize dp array and set all entries to 1  
    int dp[] = new int[arr.length];  
    for (int x = 0; x < n; x++) dp[x] = 1;  
  
    // Fill in dp array  
    for (int i = 0; i < n; i++)  
        for (int j = 0; j < i; j++)  
            if (arr[j] < arr[i] && dp[j] + 1 > dp[i])  
                dp[i] = dp[j] + 1;  
  
    // Find lis length  
    int max = 0;  
    for (x = 0; x < n; x++)  
        max = Math.max(max, dp[x]);  
  
    return max;  
}
```

# Longest Increasing Subsequence

---

Time Complexity:  $O(n^2)$

Space Complexity:  $O(n)$

There exist more efficient algorithms for LIS: [O\(nlogn\) solution](#)

# Study Guide

---

**Focus on 1D DP problems:**

- Base case (initialize array)**
- Recurrence (build the array)**
- Solution (where in the array is it?)**

**The hardest part is figuring out how to build the recurrence**

**Extra-credit: Practice some 2D DP problems**

# Outline

---

Sorting

Recursion

Greedy

Dynamic Programming

# Definitely know

---

Sorting

Recursion

# Good-to-know

---

Greedy

Dynamic Programming



# Outline

---

Sorting

Recursion

Greedy

Dynamic Programming

# Resources

---

Most interviews don't demand much formal algorithms knowledge.

## Problems

- HackerRank
- GeeksForGeeks
- Leetcode
- CTCI

## Theory

- Analysis of Algorithms (CSOR 4231)
- CLRS

# Algorithms for Interviews

Raymond Xu

[raymond@adicu.com](mailto:raymond@adicu.com)

[raymondxu.io](http://raymondxu.io)

