



Circular Queue is a linear data structure in which the operations are performed based on FIFO (First In First Out) principle and the last position is connected back to the first position to make a circle. It is also called '**Ring Buffer**'.



a normal Queue, we can insert elements until queue becomes full. But once queue becomes full, we can not insert the next element even if there is a space in front of queue.



Operations on Circular Queue:

- **Front:** Get the front item from queue.
- **Rear:** Get the last item from queue.
- **enQueue(value)** This function is used to insert an element into the circular queue. In a circular queue, the new element is always inserted at Rear position.
 1. **Steps:** Check whether queue is Full – Check $((\text{rear} == \text{SIZE}-1 \ \&\& \ \text{front} == 0) \ || \ (\text{rear} == \text{front}-1))$.
 2. If it is full then display Queue is full. If queue is not full then, check if $(\text{rear} == \text{SIZE} - 1 \ \&\& \ \text{front} != 0)$ if it is true then set $\text{rear}=0$ and insert element.

- **deQueue()** This function is used to delete an element from the circular queue. In a circular queue, the element is always deleted from front position.
 1. **Steps:** Check whether queue is Empty means check (front==-1).
 2. If it is empty then display Queue is empty. If queue is not empty then step 3
 3. Check if (front==rear) if it is true then set front=rear= -1 else check if (front==size-1), if it is true then set front=0 and return the element.

References

Carrano, F. M., & Henry, T. (2019). *Data structures and abstractions with Java*. Pearson Education.

Goodrich, M. T., Goldwasser, M. H., & Tamassia, R. (2013). *Data structures and algorithms in Python*. Wiley.