

LAB # 2

DATASET PREPARATION WITH EXCEL SPREADSHEET AND DATASET PREPROCESSING AND SCALING TECHNIQUES

Lab Tasks:-

1. Write a python code to load an excel spreadsheet containing two different sheets and print both of them.

Code:-

```
import pandas as pd

excel_file = 'Example.xlsx'

sheet1 = pd.read_excel(excel_file, sheet_name=0) # First sheet
sheet2 = pd.read_excel(excel_file, sheet_name=1) # Second sheet

print("----- Sheet 1 -----")
print(sheet1)
print("\n----- Sheet 2 -----")
print(sheet2)
```

Output:-

```
----- Sheet 1 -----
   Name  Age  Stream  Percentage
0   Ali   30   Math         65
1 Faizan   39  Science         90
2  Abrar   44 Commerce         75
3 Hareem   23   Math         85
4 Kashif   21  Science         70

----- Sheet 2 -----
   Name  Age  Stream  Percentage
0  Amina   28  Science         88
1  Bilal   35 Commerce         78
2  Dania   42   Math         92
3 Hassan   25  Science         80
4  Iqra    22 Commerce         67
```

2. Write a python code to generate a pandas data frame having 4 columns and 5 rows. Column 1 must contain the index values like Ali, Amir, Kamran, etc and Row 1 must contain the subject names.

Code:-

```
import pandas as pd

data = {
    'Math': [85, 78, 92, 88, 76],
    'English': [79, 85, 90, 82, 88],
    'Science': [91, 80, 87, 89, 84],
    'History': [76, 89, 84, 90, 82]
}

index = ['Ali', 'Amir', 'Kamran', 'Sara', 'Hina']

df = pd.DataFrame(data, index=index)

print(df)
```

Output:-

	Math	English	Science	History
Ali	85	79	91	76
Amir	78	85	80	89
Kamran	92	90	87	84
Sara	88	82	89	90
Hina	76	88	84	82

3. Write a python code to read an excel spreadsheet and only print first two columns using pandas data frame.

Code:-

```
import pandas as pd

df = pd.read_excel('Example.xlsx')

print(df.iloc[:, :2])
```

Output:-

	Name	Age
0	Ali	30
1	Faizan	39
2	Abrar	44
3	Hareem	23
4	Kashif	21

4. Write a python code to skip the first two rows of excel spreadsheet and print the output using pandas data frame.

Code:-

```
import pandas as pd

df = pd.read_excel('Example.xlsx', skiprows=2)

print(df)
```

Output:-

	Faizan	39	Science	90
0	Abrar	44	Commerce	75
1	Hareem	23	Math	85
2	Kashif	21	Science	70

5. Write a python code to fill all the null values in Gender column of employees.csv with “No Gender”. Print the first 10 to 30 rows of the data frame for visualization.

Code:-

```
import pandas as pd

df = pd.read_csv('employees.csv')

df['Gender'] = df['Gender'].fillna('No Gender')

print(df)
```

Output:-

	EmployeeID	Name	Age	Gender	Department	Salary
0	101	Ali	28	Male	Finance	55000
1	102	Amir	32	No Gender	IT	50000
2	103	Sarah	26	Female	HR	60000
3	104	Kamran	29	Male	Marketing	50000
4	105	Hina	31	No Gender	Finance	60000

6. Write a python code to scale the values of features (Age and Salary) using Min-Max Normalization technique. Verify your answers by applying the formula mentioned above.

Code:-

```
import pandas as pd

df = pd.read_csv('employees.csv')

cols_to_scale = ['Age', 'Salary']

df_scaled = df.copy()
for col in cols_to_scale:
    min_val = df[col].min()
    max_val = df[col].max()
    df_scaled[col] = (df[col] - min_val) / (max_val - min_val)

print("Original Data:")
print(df[['Name', 'Age', 'Salary']])
print("\nNormalized Data (Min-Max Scaled):")
print(df_scaled[['Name', 'Age', 'Salary']])
```

Output:-

Original Data:

	Name	Age	Salary
0	Ali	28	55000
1	Amir	32	50000
2	Sarah	26	60000
3	Kamran	29	50000
4	Hina	31	60000

Normalized Data (Min-Max Scaled):

	Name	Age	Salary
0	Ali	0.333333	0.5
1	Amir	1.000000	0.0
2	Sarah	0.000000	1.0
3	Kamran	0.500000	0.0
4	Hina	0.833333	1.0

7. Write a python code to scale the values of features (Age and Salary) using Standardization technique. Verify your answers by applying the formula mentioned above.

Age	Salary
25	42000
36	50000
30	45000
27	43000
38	51000
42	62000
34	48000

Code:-

```
import pandas as pd
data = {
    'Name': ['Ali', 'Amir', 'Sarah', 'Kamran', 'Hina', 'Rayyan', 'Wania'],
    'Age': [25, 36, 30, 27, 38, 42, 34],
    'Salary': [42000, 50000, 45000, 43000, 51000, 62000, 48000]
}

df = pd.DataFrame(data)

features = ['Age', 'Salary']

df_standardized = df.copy()

for feature in features:
    mean = df[feature].mean()
    std = df[feature].std()
    df_standardized[feature] = (df[feature] - mean) / std
    print(f"\nStandardizing {feature}:")
    print(f"Mean = {mean}, Std Dev = {std}")
    print(df_standardized[[feature]])

# Display
print("\nOriginal Data:")
print(df)
print("\nStandardized Data:")
print(df_standardized)
```

Output:-

```
Standardizing Age:
Mean = 33.142857142857146, Std Dev = 6.12178000880385
   Age
0 -1.330145
1  0.466718
2 -0.513389
3 -1.003443
4  0.793420
5  1.446825
6  0.140015

Standardizing Salary:
Mean = 48714.28571428572, Std Dev = 6775.305299745681
   Salary
0 -0.990994
1  0.189765
2 -0.548209
3 -0.843399
4  0.337360
5  1.960903
6 -0.105425

Original Data:
   Name  Age  Salary
0   Ali   25   42000
1  Amir   36   50000
2  Sarah   30   45000
3 Kamran   27   43000
4   Hina   38   51000
5 Rayyan   42   62000
6  Wania   34   48000

Standardized Data:
   Name  Age  Salary
0   Ali -1.330145 -0.990994
1  Amir  0.466718  0.189765
2  Sarah -0.513389 -0.548209
3 Kamran -1.003443 -0.843399
4   Hina  0.793420  0.337360
5 Rayyan  1.446825  1.960903
6  Wania  0.140015 -0.105425
```

8. Given this dictionary, create a dataframe from dictionary and interpolate the missing values using backward interpolation. Hint: use interpolate().

```
dict = {'First Score': [100, 90, np.nan, 95],  
        'Second Score': [30, 45, 56, np.nan],  
        'Third Score': [np.nan, 40, 80, 98]}
```

Code:-

```
import pandas as pd  
import numpy as np  
  
# Given dictionary  
data = {  
    'First Score': [100, 90, np.nan, 95],  
    'Second Score': [30, 45, 56, np.nan],  
    'Third Score': [np.nan, 40, 80, 98]  
}  
  
# Create DataFrame  
df = pd.DataFrame(data)  
  
# Interpolate missing values using backward interpolation  
df_interpolated = df.interpolate(method='linear', limit_direction='backward')  
  
print("Original DataFrame:\n", df)  
print("\nBackward Interpolated DataFrame:\n", df_interpolated)
```

Output:-

```
Original DataFrame:  
   First Score  Second Score  Third Score  
0         100.0           30.0          NaN  
1          90.0           45.0          40.0  
2          NaN           56.0          80.0  
3          95.0           NaN          98.0  
  
Backward Interpolated DataFrame:  
   First Score  Second Score  Third Score  
0         100.0           30.0          40.0  
1          90.0           45.0          40.0  
2          92.5           56.0          80.0  
3          95.0           NaN          98.0
```