Feedback — Week 1 Exercise

Help Center

Answer the following questions. Some of the questions will require you to run code in IDLE's Python shell. (You should do this anyway to get used to using IDLE.)

Question 1

Select the function call(s) that run without error. Determine the answer using the description given by `help(round)`, not by running the code.

Your Answer		Score	Explanation
☐ `round(45.345, 2, 5)`	✔	0.20	
☑ `round(45.8)`	✔	0.20	
☑ `round(45.345, 2)`	✔	0.20	

☐ `round()`	✔	0.20
☑ `round(45)`	✔	0.20
Total		1.00 / 1.00

Question Explanation

The function `round` takes one argument, as well as a second optional argument.

```
Help on built-in function round in module builtins:

round(...)
    round(number[, ndigits]) -> number

    Round a number to a given precision in decimal digits (default 0 digits).
    This returns an int when called with one argument, otherwise the
    same type as the number. ndigits may be negative.
```

Question 2

What type of value does built-in function `id` return? Determine the answer using the description given by `help(id)`.

Your Answer		Score	Explanation
○ `float`			
◉ `int`	✔	1.00	

Total	1.00 / 1.00

Question Explanation

Here is the output of `help(id)`. The return type is to the right of the arrow:

```
id(...)
    id(object) -> integer

    Return the identity of an object.  This is guaranteed to be unique among
    simultaneously existing objects.  (Hint: it's the object's memory address.)
```

Question 3

Consider this code:

```
x = 12 / 3
```

What value does `x` refer to?

You entered:

4.0

Your Answer		Score	Explanation
4.0	✔	1.00	
Total		1.00 / 1.00	

Question Explanation

The division operation (`/`) produces a `float`. Note that the question just asks for a value, so don't include any other information other than the value.

Question 4

Consider this code:

```
x = 12 // 3
```

What value does `x` refer to?

You entered:

4

Your Answer		Score	Explanation
4	✔	1.00	
Total		1.00 / 1.00	

Question Explanation

The integer division operation (`//`) produces an `int`. Note that the question just asks for a value, so don't include any other information other than the value.

Question 5

Consider this code:

```
x = 12 / 5
```

What value does `x` refer to?

You entered:

2.4

Your Answer		Score	Explanation
2.4	✔	1.00	
Total		1.00 / 1.00	

Question Explanation

The division operation (`/`) produces a `float`. Note that the question just asks for a value, so don't include any other information other than the value.

Question 6

Consider this code:

```
x = 13 / 7
```

What value does `x` refer to?

You entered:

1.8571428571428572

Your Answer		Score	Explanation
1.8571428571428572	✔	1.00	
Total		1.00 / 1.00	

Question Explanation

The division operation (`/`) evaluates to a `float`. Note that the question just asks for a value, so don't include any other information other than the value.

Question 7

Consider this code:

```
x = 3
y = 5
x = y
```

After the code above has executed, what value does `x` refer?

You entered:

5

Your Answer		Score	Explanation
5	✔	1.00	
Total		1.00 / 1.00	

Question Explanation

Note that the question just asks for a value, so don't include any other information other than the value.

Question 8

Consider this code:

```
x = 3
y = 5
x = y
```

After the code above has executed, what value does `y` refer?

You entered:

5

Your Answer		Score	Explanation
5	✔	1.00	

Total	1.00 / 1.00

Question 9

Consider this code:

```
apple = banana
```

When the code above is executed, what type of error occurs?

Your Answer		Score	Explanation
◉ `NameError`	✔	1.00	
○ `SyntaxError`			
Total		1.00 / 1.00	

Question Explanation

The name `banana` does not exist, so a `NameError` occurs.

Question 10

Select the legal Python name(s) below.

Your Answer		Score	Explanation
☑ `haPpyDAY`	✔	0.25	
☑ `_happy`	✔	0.25	
☐ `18happy_day`	✔	0.25	
☑ `happy_day`	✔	0.25	
Total		1.00 / 1.00	

Question Explanation

1. Names must start with a letter or `_`.
2. Names must contain only letters, digits, and `_`.

Question 11

Consider this code:

```
def greater(one, two):
    return one > two
```

Select the phrase that describes `two`.

Your Answer		Score	Explanation
◉ a parameter	✔	1.00	

○ a function name	
○ an argument	
Total	1.00 / 1.00

Question Explanation

Review this terminology in the "Defining Functions" video and lecture summary.

Question 12

Consider this code:

```
def example(a, b, c):
    d = a + b - c
    return d
```

How many parameters does function `example` have?

Your Answer		Score	Explanation
○ 2			
○ 1			
◉ 3	✔	1.00	
○ 0			
Total		1.00 / 1.00	

Question Explanation

The parameters are `a`, `b` and `c`. Review this terminology in the "Defining Functions" video and lecture summary.

Question 13

Consider this code:

```
value = 8.564
result = round(value)
```

Select the phrase that describes `value` in the **second** line.

Your Answer		Score	Explanation
○ a parameter			
○ a function name			
◉ an argument	✔	1.00	
Total		1.00 / 1.00	

Question Explanation

The value of `value` is passed as an argument to function `round`.

Question 14

Consider this code:

```
round(45.342, 2)
```

What value does the expression above produce?

You entered:

45.34

Your Answer		Score	Explanation
45.34	✔	1.00	
Total		1.00 / 1.00	

Question Explanation

Note that the question just asks for a value, so don't include any other information other than the value.

Question 15

Consider this code:

```
def bigger(x):
    return x ** x

bigger(12)
```

Which value does `bigger(12)` produce?

Your Answer		Score	Explanation
○ 285311670611			
○ 302875106592253			
◉ 8916100448256	✔	1.00	
○ 11112006825558016			
Total		1.00 / 1.00	