RNA-Seq Gene Expression for Cancer-Type Prediction

Department of Computer Science and Engineering

Goal	Dataset Scale	Best Result
Cancer-type prediction Use gene-expression patterns to classify cancer types and cluster low-confidence samples.	**20,531 features** Each patient record contains 20,531 gene-expression values before dimensionality reduction.	**92.5% cluster accuracy** Top hierarchical settings (ward / average) outperformed most alternatives, while K-Means reached 91.6%.

Overview

This project investigated cancer type prediction using RNA-Seq gene expression data, with a particular focus on identifying samples that could not be confidently assigned to known classes. The approach combined ***SVM classification*** with ***K-Means*** and ***Hierarchical Clustering***, allowing low-confidence samples to be further analysed rather than being forced into known categories. The workflow also included ***KNN imputation***, ***PCA-based dimensionality reduction***, and class rebalancing with ***KMeans-SMOTE*** and ***ADASYN***. Results showed that the proposed hybrid approach improved class separability, with the best clustering configuration achieving ***92.5%*** cluster accuracy.

Methodological Pipeline



Figure 1. Proposed analytical pipeline for cancer type prediction: preprocessing and rebalancing were followed by SVM classification, while low-confidence samples (confidence < 0.95) were further analyzed using clustering.

1. Data cleaning: The dataset originally contained ***20,531 gene-expression features,*** with a missing rate of ***14.1%***. By removing features with more than ***90% missing values***, the missing rate was reduced to ***0.4%***, while feature dimensionality decreased by ***22.6%***.

2. Imputation & Dimensionality reduction: The remaining missing values were imputed using ***KNNImputer***. To address the curse of dimensionality, ***PCA*** was then applied to reduce the feature space to ***292 principal components*** while retaining ***95%*** of the total variance, yielding an overall dimensionality reduction of approximately ***98.6%*** relative to the original feature space.

3. Class balancing (Figure 2): Because the dataset was highly imbalanced across cancer types, a hybrid oversampling strategy was adopted using ***KMeans-SMOTE (90%)*** and ***ADASYN (10%)***. This combination improved class balance while also reinforcing sample representation near difficult decision boundaries.

4. SVM-based classification: ***SVM*** was selected as the primary classifier due to its strong performance on high-dimensional data. In internal validation on known classes, the model demonstrated very strong classification performance, and a confidence threshold of ***0.95*** was applied to identify uncertain predictions.

5. Unknown class discovery: Samples with confidence scores below ***0.95*** were routed to unsupervised clustering for further analysis instead of being directly assigned to known categories. This design allowed potentially unseen or ambiguous samples outside the training set to be examined more cautiously.

6. Clustering and Evaluation: Two clustering methods were compared: ***K-Means*** and ***Hierarchical Clustering***. The results showed that ***K-Means reached 91.6% accuracy***, while ***Hierarchical Clustering achieved up to 92.5%***, although performance varied significantly across linkage strategies.

Post-PCA Class Distribution After Rebalancing

PCA and rebalancing improved class separability. Figure 2 shows clearer class structure after dimensionality reduction and hybrid oversampling, indicating that the preprocessing pipeline enhanced the quality of the feature space.

Hybrid rebalancing strengthened performance. The combination of ***KMeans-SMOTE (90%)*** and ***ADASYN (10%)*** improved class balance while preserving harder-to-learn samples near decision boundaries.

Cluster selection was not based on a single metric. Both ***Silhouette Analysis*** and the ***Elbow Method*** were used to determine cluster counts before comparing clustering results across settings.

Figure 2. Post-PCA class distribution after hybrid rebalancing with KMeans_SMOTE (90%) + ADASYN (10%).

Clustering Performance by Method and Cluster Selection Criteria

Method	Clusters (Silhouette)	Accuracy	Clusters (Elbow)	Accuracy
K-Means	2	91.6%	2	91.6%
Hierarchical - single	2	53.3%	9	53.3%
Hierarchical - complete	2	92.2%	2	92.2%
Hierarchical - average	10	90.4%	6	92.5%
Hierarchical - ward	2	92.5%	2	92.5%

Table 1. Most hierarchical-linkage settings exceeded 90% accuracy, whereas single-linkage performed substantially worse. For single linkage, varying the selected number of clusters did not improve clustering accuracy. K-Means achieved 91.6% accuracy.

Technical Takeaways

Key Insight	Analytical Significance
High-dimensional, ***incomplete***, and ***imbalance*** data required careful preprocessing, including imputation, dimensionality reduction, and hybrid resampling, before reliable modeling could be achieved.	This project refined my ability to design robust data pipelines for complex datasets, with an emphasis on stability, reliability, and well-structured downstream analysis.
Low-confidence samples were not forced into predefined classes, but were instead examined through unsupervised clustering.	This reflects an uncertainty-aware modelling approach, where ambiguous cases are handled cautiously rather than being overconfidently classified, supporting more reliable and nuanced decision-making.