

4. Implement AO* Search algorithm

```
# Cost to find the AND and OR path
# Cost to find the AND and OR path
def Cost(H, condition, weight = 1):
    cost = {}
    if 'AND' in condition:
        AND_nodes = condition['AND']
        Path_A = ' AND '.join(AND_nodes)
        PathA = sum(H[node]+weight for node in AND_nodes)
        cost[Path_A] = PathA

    if 'OR' in condition:
        OR_nodes = condition['OR']
        Path_B = ' OR '.join(OR_nodes)
        PathB = min(H[node]+weight for node in OR_nodes)
        cost[Path_B] = PathB
    return cost

# Update the cost
def update_cost(H, Conditions, weight=1):
    Main_nodes = list(Conditions.keys())
    Main_nodes.reverse()
    least_cost = {}
    for key in Main_nodes:
        condition = Conditions[key]
        print(key, ':', Conditions[key], '>>>', Cost(H, condition, weight))
        c = Cost(H, condition, weight)
        H[key] = min(c.values())
        least_cost[key] = Cost(H, condition, weight)
    return least_cost

# Print the shortest path
def shortest_path(Start, Updated_cost, H):
    Path = Start
    if Start in Updated_cost.keys():
        Min_cost = min(Updated_cost[Start].values())
        key = list(Updated_cost[Start].keys())
        values = list(Updated_cost[Start].values())
        Index = values.index(Min_cost)

        # FIND MINIMUM PATH KEY
        Next = key[Index].split()
        # ADD TO PATH FOR OR PATH
        if len(Next) == 1:
            Start = Next[0]
            Path += '<--' + shortest_path(Start, Updated_cost, H)
        # ADD TO PATH FOR AND PATH
        else:
            Path += '<--(' + key[Index] + ') '

            Start = Next[0]
            Path += '[' + shortest_path(Start, Updated_cost, H) + ' + ' + '

            Start = Next[-1]
            Path += shortest_path(Start, Updated_cost, H) + ']'

    return Path
```

```

H = {'A': -1, 'B': 5, 'C': 2, 'D': 4, 'E': 7, 'F': 9, 'G': 3, 'H': 0, 'I':0, 'J':0}

Conditions = {
'A': {'OR': ['B'], 'AND': ['C', 'D']},
'B': {'OR': ['E', 'F']},
'C': {'OR': ['G'], 'AND': ['H', 'I']},
'D': {'OR': ['J']}}
}
# weight
weight = 1
# Updated cost
print('Updated Cost :')
Updated_cost = update_cost(H, Conditions, weight=1)
print('*'*75)
print('Shortest Path :\n',shortest_path('A', Updated_cost,H))

```

Output

```

Updated Cost :
D : {'OR': ['J']} >>> {'J': 1}
C : {'OR': ['G'], 'AND': ['H', 'I']} >>> {'H AND I': 2, 'G': 4}
B : {'OR': ['E', 'F']} >>> {'E OR F': 8}
A : {'OR': ['B'], 'AND': ['C', 'D']} >>> {'C AND D': 5, 'B': 9}
*****
Shortest Path :
A<--(C AND D) [C<--(H AND I) [H + I] + D<--J]

```