

# Automating Agisoft Metashape Model Building

This is a tutorial for setting up and running multiple models in sequence on the command line through Agisoft Metashape. In essence, this creates separate scripts for each model that will be built, and these scripts will be run through Metashape one after another. We have created this method as a work-around for the various intricacies of Metashape. Metashape requires a connection to a local display. This connection is reinitiated when each model finishes so if the program is running on a detached screen, Metashape cannot reestablish the connection and the job will stop. As such, we recommend using a desktop or laptop with an ethernet connection to maintain a constant link from the server to a display.

Access your remote computer using the -XY flags for ssh in terminal. This allows for a safe, forwarded connection from the server to your local display. Metashape requires this connection to a display in order to function on a remote server.

## Setting up photos for automated model building

1. Ensure all photos for a single model has been put into its own subdirectory. I do this before transferring photos to the remote system, still it helps to check that photos uploaded properly.

```
Main/Photo_Set1  
Main/Photo_Set2  
Main/Photo_Set3
```

2. Create a list of absolute file paths to each of the subdirectories in the Main directory

```
ls -d -1 $PWD/** > FragDirs.txt
```

- a. Check that FragDirs.txt is in Main/ and that it contains absolute file paths to subdirectories

## Creating unique Python scripts to run each group of photos

3. Change working directory to location of Metashape software
  - a. This is the directory created when you unzipped Metashape during installation i.e. metashape-pro\_1\_5\_4
4. Create a base script that will run Metashape with given settings for each of your groups of photos.
  - a. This script will act as a template with place holders that will be filled using the absolute file paths from FragDirs.txt. You can change model building settings in this base script that you want all models to run on.

- b. See metashapeBase.py and metashapeBaseDepthMaps.py as examples
- 5. Generate unique python scripts that will run Metashape for each group of photos included in FragDirs.txt
  - a. Change line 33 of Meta\_expand.sh to include the name of the base script that you would like to use as a template

```
./Meta_expand.sh ~/Main/FragDirs.txt
```

- b. Check to see if new .py scripts were created in metashape-pro\_1\_5\_4 directory
- c. Make new scripts executable

```
chmod +x *.py
```

You can also change Metashape settings on each of these new scripts manually. This is useful when you know one or two models will require higher quality camera alignment or depth mapping.

## Build multiple models in Metashape with single command

- 6. Use a bash script to call photosets to be automatically submitted in sequence to Metashape
  - a. Edit line 3 of metashapeLoop.sh with wildcards to specify which groups of photos will be run with each job
  - b. e.g. scripts='ls Photo\_Set\*.py' to build models from scripts with Photo\_Set in the name
  - c. Send output to a text file to check progress and diagnosis errors

```
metashapeLoop.sh > output.txt
```