

# Lecture 17

## 6.2.3 Language classes with respect to time and space complexity

187

# Language classes with respect to time and space complexity

# Language classes with respect to time and space complexity

- **Nondeterministic TM**

## Language classes with respect to time and space complexity

- **Nondeterministic TM**
  - **space complexity  $S(n)$**

## Language classes with respect to time and space complexity

- **Nondeterministic TM**
  - **space complexity  $S(n)$**   
—for any string of length  $n$

# Language classes with respect to time and space complexity

- **Nondeterministic TM**
  - **space complexity  $S(n)$** 
    - for any string of length  $n$
    - any sequence of moves

# Language classes with respect to time and space complexity

- **Nondeterministic TM**
  - **space complexity  $S(n)$** 
    - for any string of length  $n$
    - any sequence of moves
    - on any work tape

# Language classes with respect to time and space complexity

- **Nondeterministic TM**
  - **space complexity  $S(n)$** 
    - for any string of length  $n$
    - any sequence of moves
    - on any work tape
    - uses at most  $S(n)$  cells



# Language classes with respect to time and space complexity

- **Nondeterministic TM**
  - **space complexity  $S(n)$** 
    - for any string of length  $n$
    - any sequence of moves
    - on any work tape
    - uses at most  $S(n)$  cells
- **Language  $L$**

# Language classes with respect to time and space complexity

- **Nondeterministic TM**
  - **space complexity  $S(n)$** 
    - for any string of length  $n$
    - any sequence of moves
    - on any work tape
    - uses at most  $S(n)$  cells
- **Language  $L$** 
  - **nondeterministic space complexity  $S(n)$**

# Language classes with respect to time and space complexity

- **Nondeterministic TM**
  - **space complexity  $S(n)$** 
    - for any string of length  $n$
    - any sequence of moves
    - on any work tape
    - uses at most  $S(n)$  cells
- **Language  $L$** 
  - **nondeterministic space complexity  $S(n)$** 
    - if and only if there is a nondeterministic TM  $M$  with space complexity  $S(n)$  that accepts the language  $L(M) = L$

# Language classes with respect to time and space complexity

# Language classes with respect to time and space complexity

- **Nondeterministic TM**

## Language classes with respect to time and space complexity

- **Nondeterministic TM**
  - time complexity  $T(n)$

## Language classes with respect to time and space complexity

- **Nondeterministic TM**
  - **time complexity  $T(n)$**   
—for any string of length  $n$

# Language classes with respect to time and space complexity

- **Nondeterministic TM**
  - **time complexity  $T(n)$** 
    - for any string of length  $n$
    - any sequence of moves



# Language classes with respect to time and space complexity

- **Nondeterministic TM**
  - **time complexity  $T(n)$** 
    - for any string of length  $n$
    - any sequence of moves
    - moves the head at most  $T(n)$  times

# Language classes with respect to time and space complexity

- **Nondeterministic TM**
  - **time complexity  $T(n)$** 
    - for any string of length  $n$
    - any sequence of moves
    - moves the head at most  $T(n)$  times
- **Language  $L$**

# Language classes with respect to time and space complexity

- **Nondeterministic TM**
  - **time complexity  $T(n)$** 
    - for any string of length  $n$
    - any sequence of moves
    - moves the head at most  $T(n)$  times
- **Language  $L$** 
  - **nondeterministic time complexity  $T(n)$**

# Language classes with respect to time and space complexity

- **Nondeterministic TM**
  - **time complexity  $T(n)$** 
    - for any string of length  $n$
    - any sequence of moves
    - moves the head at most  $T(n)$  times
- **Language  $L$** 
  - **nondeterministic time complexity  $T(n)$** 
    - if and only if there is a nondeterministic TM  $M$  with time complexity  $T(n)$  that accepts the language  $L(M) = L$

# Language classes with respect to time and space complexity

## Language classes with respect to time and space complexity

- **Four main classes of languages:**

## Language classes with respect to time and space complexity

- **Four main classes of languages:**
  - **DSPACE( $S(n)$ )**
    - a set of languages with deterministic space complexity  $S(n)$

# Language classes with respect to time and space complexity

- **Four main classes of languages:**
  - **DSPACE( $S(n)$ )**
    - a set of languages with deterministic space complexity  $S(n)$
  - **NSPACE( $S(n)$ )**
    - a set of languages with nondeterministic space complexity  $S(n)$



## Language classes with respect to time and space complexity

- **Four main classes of languages:**
  - **DSPACE( $S(n)$ )**
    - a set of languages with deterministic space complexity  $S(n)$
  - **NSPACE( $S(n)$ )**
    - a set of languages with nondeterministic space complexity  $S(n)$
  - **DTIME( $T(n)$ )**
    - a set of languages with deterministic time complexity  $T(n)$

## Language classes with respect to time and space complexity

- **Four main classes of languages:**
  - **DSPACE( $S(n)$ )**
    - a set of languages with deterministic space complexity  $S(n)$
  - **NSPACE( $S(n)$ )**
    - a set of languages with nondeterministic space complexity  $S(n)$
  - **DTIME( $T(n)$ )**
    - a set of languages with deterministic time complexity  $T(n)$
  - **NTIME( $T(n)$ )**
    - a set of languages with nondeterministic time complexity  $T(n)$

# Relations between language classes

# Relations between language classes

- If  $L \in \text{DTIME}(f(n)) \Rightarrow L \in \text{DSPACE}(f(n))$

# Relations between language classes

- If  $L \in \text{DTIME}(f(n)) \Rightarrow L \in \text{DSPACE}(f(n))$ 
  - Deterministic TM  $M$  with time complexity  $f(n)$

# Relations between language classes

- If  $L \in \text{DTIME}(f(n)) \Rightarrow L \in \text{DSPACE}(f(n))$
- **Deterministic TM  $M$  with time complexity  $f(n)$** 
  - Using  $f(n)$  head moves, TM  $M$  cannot pass more than  $f(n)+1$  cells

# Relations between language classes

- If  $L \in \text{DTIME}(f(n)) \Rightarrow L \in \text{DSPACE}(f(n))$ 
  - **Deterministic TM  $M$  with time complexity  $f(n)$** 
    - Using  $f(n)$  head moves, TM  $M$  cannot pass more than  $f(n)+1$  cells
  - **Merging two cells into one**

# Relations between language classes

- If  $L \in \text{DTIME}(f(n)) \Rightarrow L \in \text{DSPACE}(f(n))$ 
  - **Deterministic TM  $M$  with time complexity  $f(n)$** 
    - Using  $f(n)$  head moves, TM  $M$  cannot pass more than  $f(n)+1$  cells
  - **Merging two cells into one**
    - we can build TM that does not use more than  $\lceil (f(n)+1)/2 \rceil$  cells



# Relations between language classes

- If  $L \in \text{DTIME}(f(n)) \Rightarrow L \in \text{DSPACE}(f(n))$ 
  - **Deterministic TM  $M$  with time complexity  $f(n)$** 
    - Using  $f(n)$  head moves, TM  $M$  cannot pass more than  $f(n)+1$  cells
  - **Merging two cells into one**
    - we can build TM that does not use more than  $\lceil (f(n)+1)/2 \rceil$  cells
  - $(\lceil (f(n)+1)/2 \rceil < f(n)) \Rightarrow L \in \text{DSPACE}(f(n))$

# Relations between language classes

# Relations between language classes

- (If  $L \in \text{DSPACE}(f(n)) \wedge f(n) \geq \log_2 n \Rightarrow L \in \text{DTIME}(c^{f(n)})$ )

# Relations between language classes


- (If  $L \in \text{DSPACE}(f(n)) \wedge f(n) \geq \log_2 n \Rightarrow L \in \text{DTIME}(c^{f(n)})$ )
  - Deterministic TM  $M_1$  with space complexity  $f(n)$

# Relations between language classes

- (If  $L \in \text{DSPACE}(f(n)) \wedge f(n) \geq \log_2 n \Rightarrow L \in \text{DTIME}(c^{f(n)})$ )
- **Deterministic TM  $M_1$  with space complexity  $f(n)$**   
—one input tape and one work tape

# Relations between language classes


Maximal number of different configurations of TM  $M_1$



# Relations between language classes

Maximal number of different configurations of TM  $M_1$

- $s(n+2) f(n) t^{f(n)}$




# Relations between language classes

## Maximal number of different configurations of TM $M_1$

- $s(n+2) f(n) t^{f(n)}$

—  $s$       - number of states in  $Q$






# Relations between language classes

## Maximal number of different configurations of TM $M_1$

- $s(n+2) f(n) t^{f(n)}$

- $s$  - number of states in  $Q$
- $n+2$  - number of different head positions on the input tape




# Relations between language classes

## Maximal number of different configurations of TM $M_1$

- $s(n+2) f(n) t^{f(n)}$

- $s$  - number of states in  $Q$
- $n+2$  - number of different head positions on the input tape
  - $n$  - length of string  $w$




# Relations between language classes

## Maximal number of different configurations of TM $M_1$

- $s(n+2) f(n) t^{f(n)}$

- $s$  - number of states in  $Q$
- $n+2$  - number of different head positions on the input tape
  - $n$  - length of string  $w$
- $f(n)$  - number of different head positions on the work tape




# Relations between language classes

## Maximal number of different configurations of TM $M_1$

- $s(n+2) f(n) t^{f(n)}$

- $s$  - number of states in  $Q$
- $n+2$  - number of different head positions on the input tape
  - $n$  - length of string  $w$
- $f(n)$  - number of different head positions on the work tape
- $t^{f(n)}$  - number of different work tape contents




# Relations between language classes

## Maximal number of different configurations of TM $M_1$

- $s(n+2) f(n) t^{f(n)}$

- $s$  - number of states in  $Q$
- $n+2$  - number of different head positions on the input tape
  - $n$  - length of string  $w$
- $f(n)$  - number of different head positions on the work tape
- $t^{f(n)}$  - number of different work tape contents
  - $t$  - cardinal number of the symbol set  $\Gamma$




# Relations between language classes

## Maximal number of different configurations of TM $M_1$

- $s(n+2) f(n) t^{f(n)}$

- $s$  - number of states in  $Q$
- $n+2$  - number of different head positions on the input tape
  - $n$  - length of string  $w$
- $f(n)$  - number of different head positions on the work tape
- $t^{f(n)}$  - number of different work tape contents
  - $t$  - cardinal number of the symbol set  $\Gamma$
  - $f(n)$  – maximal number of cells used by TM  $M_1$




# Relations between language classes

## Maximal number of different configurations of TM $M_1$

- $s(n+2) f(n) t^{f(n)}$

- $s$  - number of states in  $Q$
- $n+2$  - number of different head positions on the input tape
  - $n$  - length of string  $w$
- $f(n)$  - number of different head positions on the work tape
- $t^{f(n)}$  - number of different work tape contents
  - $t$  - cardinal number of the symbol set  $\Gamma$
  - $f(n)$  - maximal number of cells used by TM  $M_1$



$$f(n) \geq \log_2 n \Rightarrow (c^{f(n)} \geq s(n+2) f(n) t^{f(n)}) \Rightarrow L \in \text{DTIME}(c^{f(n)})$$


# Relations between language classes




# Relations between language classes

TM  $M'$  that uses less than  $c^{f(n)}$  head moves

# Relations between language classes




# Relations between language classes




# Relations between language classes

$C^{f(n)}$




# Relations between language classes

$C^{f(n)}$




# Relations between language classes

$C^{f(n)}$




# Relations between language classes

$C^{f(n)}$



# Relations between language classes


$C^{f(n)}$






# Relations between language classes

$C^{f(n)}$




# Relations between language classes

$C^{f(n)}$




# Relations between language classes

$C^{f(n)}$




# Relations between language classes

$C^{f(n)}$




# Relations between language classes

$C^{f(n)}$



# Relations between language classes

$C^{f(n)}$



# Relations between language classes

# Relations between language classes

- (If  $L \in \text{NTIME}(f(n)) \wedge f(n) \geq \log_2 n$  )  $\Rightarrow L \in \text{DTIME}(c^{f(n)})$  )



# Relations between language classes

- (If  $L \in \text{NTIME}(f(n)) \wedge f(n) \geq \log_2 n$  )  $\Rightarrow L \in \text{DTIME}(c^{f(n)})$ 
  - Nondeterministic TM  $M_1$  with time complexity  $f(n)$

# Relations between language classes


- (If  $L \in \text{NTIME}(f(n)) \wedge f(n) \geq \log_2 n \Rightarrow L \in \text{DTIME}(c^{f(n)})$ )
- Nondeterministic TM  $M_1$  with time complexity  $f(n)$   
—  $k$  work tapes

# Relations between language classes

- (If  $L \in \text{NTIME}(f(n)) \wedge f(n) \geq \log_2 n$ )  $\Rightarrow L \in \text{DTIME}(c^{f(n)})$
- **Nondeterministic TM  $M_1$  with time complexity  $f(n)$** 
  - $k$  work tapes
  - by applying  $f(n)$  moves, the head cannot pass more than  $f(n)+1$  cells

# Relations between language classes


**Maximal number of  
different configurations  
of TM  $M_1$**



# Relations between language classes


Maximal number of  
different configurations  
of TM  $M_1$

- $s(f(n)+1)^k t^{kf(n)}$



# Relations between language classes


Maximal number of  
different configurations  
of TM  $M_1$



- $s (f(n)+1)^k t^{k f(n)}$   
 —  $s$  - number of states in  $Q$

# Relations between language classes


Maximal number of  
different configurations  
of TM  $M_1$



- $s (f(n)+1)^k t^{k f(n)}$ 
  - $s$  - number of states in  $Q$
  - $(f(n)+1)^k$  - number of head positions on  $k$  work tapes

# Relations between language classes

Maximal number of  
different configurations  
of TM  $M_1$



- $s (f(n)+1)^k t^{k f(n)}$

—  $s$

- number of states in  $Q$

—  $(f(n)+1)^k$


- number of head positions on  $k$  work tapes

-  $f(n)+1$  - number of head positions on one work tape



# Relations between language classes


Maximal number of different configurations of TM  $M_1$



- $s (f(n)+1)^k t^{k f(n)}$ 
  - $s$  - number of states in  $Q$
  - $(f(n)+1)^k$  - number of head positions on  $k$  work tapes
    - $f(n)+1$  - number of head positions on one work tape
    - $k$  – number of work tapes

# Relations between language classes

Maximal number of different configurations of TM  $M_1$



- $s (f(n)+1)^k t^{k f(n)}$

—  $s$

- number of states in  $Q$

—  $(f(n)+1)^k$

- number of head positions on  $k$  work tapes


-  $f(n)+1$  - number of head positions on one work tape

-  $k$  – number of work tapes

-  $n$  - length of string  $w$

# Relations between language classes


Maximal number of different configurations of TM  $M_1$



- $s (f(n)+1)^k t^{k f(n)}$ 
  - $s$  - number of states in  $Q$
  - $(f(n)+1)^k$  - number of head positions on  $k$  work tapes
    - $f(n)+1$  - number of head positions on one work tape
    - $k$  – number of work tapes
    - $n$  - length of string  $w$
  - $t^{k f(n)}$  - number of different contents of  $k$  work tapes

# Relations between language classes


Maximal number of different configurations of TM  $M_1$



- $s (f(n)+1)^k t^{k f(n)}$ 
  - $s$  - number of states in  $Q$
  - $(f(n)+1)^k$  - number of head positions on  $k$  work tapes
    - $f(n)+1$  - number of head positions on one work tape
    - $k$  – number of work tapes
    - $n$  - length of string  $w$
  - $t^{k f(n)}$  - number of different contents of  $k$  work tapes
    - $t^{f(n)}$  - number of different contents of one work tape

# Relations between language classes

Maximal number of different configurations of TM  $M_1$



- $s (f(n)+1)^k t^{k f(n)}$ 
  - $s$  - number of states in  $Q$
  - $(f(n)+1)^k$  - number of head positions on  $k$  work tapes
    - $f(n)+1$  - number of head positions on one work tape
    - $k$  – number of work tapes
    - $n$  - length of string  $w$
  - $t^{k f(n)}$  - number of different contents of  $k$  work tapes
    - $t^{f(n)}$  - number of different contents of one work tape
    - $t$  – number of tape symbols in  $\Gamma$


# Relations between language classes

# Relations between language classes

## Nondeterministic TM

# Relations between language classes


## Nondeterministic TM






# Relations between language classes

## Nondeterministic TM




# Relations between language classes

## Nondeterministic TM




# Relations between language classes

## Nondeterministic TM




# Relations between language classes

## Nondeterministic TM




# Relations between language classes

## Nondeterministic TM




# Relations between language classes

## Nondeterministic TM




# Relations between language classes

# Deterministic TM



# Relations between language classes


## Deterministic TM






# Relations between language classes

## Deterministic TM




# Relations between language classes

## Deterministic TM




# Relations between language classes

## Deterministic TM




# Relations between language classes

# Deterministic TM



# Relations between language classes

# Deterministic TM



# Relations between language classes

# Relations between language classes

- A deterministic TM simulates  $M_1$  by constructing a list of all configurations reachable from the initial configuration

# Relations between language classes

- A deterministic TM simulates  $M_1$  by constructing a list of all configurations reachable from the initial configuration
- Maximal number of cells needed to store a list of configurations



# Relations between language classes

- A deterministic TM simulates  $M_1$  by constructing a list of all configurations reachable from the initial configuration
- Maximal number of cells needed to store a list of configurations
  - Maximal number of configurations

# Relations between language classes

- A deterministic TM simulates  $M_1$  by constructing a list of all configurations reachable from the initial configuration
- Maximal number of cells needed to store a list of configurations
  - Maximal number of configurations
    - $V = s(f(n)+1)^k t^{k f(n)}$

# Relations between language classes

- A deterministic TM simulates  $M_1$  by constructing a list of all configurations reachable from the initial configuration
- Maximal number of cells needed to store a list of configurations
  - Maximal number of configurations
    - $V = s(f(n)+1)^k t^{k f(n)}$
  - number of cells needed to store one configuration

# Relations between language classes

- A deterministic TM simulates  $M_1$  by constructing a list of all configurations reachable from the initial configuration
- Maximal number of cells needed to store a list of configurations
  - Maximal number of configurations
    - $V = s(f(n)+1)^k t^k f(n)$
  - number of cells needed to store one configuration
    - $W = k(f(n)+1)+1$

# Relations between language classes

- A deterministic TM simulates  $M_1$  by constructing a list of all configurations reachable from the initial configuration
- Maximal number of cells needed to store a list of configurations
  - Maximal number of configurations
    - $V = s(f(n)+1)^k t^k f(n)$
  - number of cells needed to store one configuration
    - $W = k(f(n)+1)+1$
  - $B = V W$

# Relations between language classes

- A deterministic TM simulates  $M_1$  by constructing a list of all configurations reachable from the initial configuration
- Maximal number of cells needed to store a list of configurations
  - Maximal number of configurations
    - $V = s(f(n)+1)^k t^k f(n)$
  - number of cells needed to store one configuration
    - $W = k(f(n)+1)+1$
  - $B = V W$
- Head moves between list beginning and list end

# Relations between language classes

- A deterministic TM simulates  $M_1$  by constructing a list of all configurations reachable from the initial configuration
- Maximal number of cells needed to store a list of configurations
  - Maximal number of configurations
    - $V = s(f(n)+1)^k t^k f(n)$
  - number of cells needed to store one configuration
    - $W = k(f(n)+1)+1$
  - $B = V W$
- Head moves between list beginning and list end
  - number of head moves =  $B^2$

# Relations between language classes

- A deterministic TM simulates  $M_1$  by constructing a list of all configurations reachable from the initial configuration
- Maximal number of cells needed to store a list of configurations
  - Maximal number of configurations
    - $V = s(f(n)+1)^k t^k f(n)$
  - number of cells needed to store one configuration
    - $W = k(f(n)+1)+1$
  - $B = V W$
- Head moves between list beginning and list end
  - number of head moves =  $B^2$
  - $f(n) \geq \log_2 n \Rightarrow (c^{f(n)} \geq B^2) \Rightarrow L \in \text{DTIME}(c^{f(n)})$



# Relations between language classes

# Relations between language classes

- **Space-constructible functions**

# Relations between language classes

- **Space-constructible functions**
  - **Function  $S(n)$  is *space-constructible***
    - for each  $n > n_0$
    - there is a TM  $M$  that computes  $S(n)$  using exactly  $S(n)$  cells

# Relations between language classes

- **Space-constructible functions**
  - **Function  $S(n)$  is *space-constructible***
    - for each  $n > n_0$
    - there is a TM  $M$  that computes  $S(n)$  using exactly  $S(n)$  cells
  - **Function  $S(n)$  is *fully space-constructible***
    - the above definition holds for each  $n$
- **Time-constructible functions**

# Relations between language classes

- **Space-constructible functions**
  - **Function  $S(n)$  is *space-constructible***
    - for each  $n > n_0$
    - there is a TM  $M$  that computes  $S(n)$  using exactly  $S(n)$  cells
  - **Function  $S(n)$  is *fully space-constructible***
    - the above definition holds for each  $n$
- **Time-constructible functions**
  - **Function  $T(n)$  is *time-constructible***
    - for each  $n > n_0$
    - there is a TM  $M$  that computes  $T(n)$  in exactly  $T(n)$  steps (halts after  $T(n)$  steps)

# Relations between language classes

- **Space-constructible functions**
  - **Function  $S(n)$  is *space-constructible***
    - for each  $n > n_0$
    - there is a TM  $M$  that computes  $S(n)$  using exactly  $S(n)$  cells
  - **Function  $S(n)$  is *fully space-constructible***
    - the above definition holds for each  $n$
- **Time-constructible functions**
  - **Function  $T(n)$  is *time-constructible***
    - for each  $n > n_0$
    - there is a TM  $M$  that computes  $T(n)$  in exactly  $T(n)$  steps (halts after  $T(n)$  steps)
  - **Function  $T(n)$  is *fully time-constructible***
    - the above definition holds for each  $n$

# Relations between language classes

# Relations between language classes

- **Function  $f(n)$**



# Relations between language classes

- **Function  $f(n)$** 
  - $f(n) \geq \log_2 n$ , fully space-constructible

# Relations between language classes

- **Function  $f(n)$** 
  - $f(n) \geq \log_2 n$ , fully space-constructible
- **If  $L \in \text{NSPACE}(f(n)) \Rightarrow L \in \text{DSPACE}(f^2(n))$**

# Relations between language classes

- **Function  $f(n)$** 
  - $f(n) \geq \log_2 n$ , fully space-constructible
- **If  $L \in \text{NSPACE}(f(n)) \Rightarrow L \in \text{DSPACE}(f^2(n))$** 
  - Off-line nondeterministic TM  $M_1$  with space complexity  $f(n)$

# Relations between language classes

- **Function  $f(n)$** 
  - $f(n) \geq \log_2 n$ , fully space-constructible
- **If  $L \in \text{NSPACE}(f(n)) \Rightarrow L \in \text{DSPACE}(f^2(n))$** 
  - **Off-line nondeterministic TM  $M_1$  with space complexity  $f(n)$** 
    - one input tape and one work tape

# Relations between language classes

- **Function  $f(n)$** 
  - $f(n) \geq \log_2 n$ , fully space-constructible
- **If  $L \in \text{NSPACE}(f(n)) \Rightarrow L \in \text{DSPACE}(f^2(n))$** 
  - **Off-line nondeterministic TM  $M_1$  with space complexity  $f(n)$** 
    - one input tape and one work tape
  - **Maximal number of different configurations of TM  $M_1$**

# Relations between language classes

- **Function  $f(n)$** 
  - $f(n) \geq \log_2 n$ , fully space-constructible
- **If  $L \in \text{NSPACE}(f(n)) \Rightarrow L \in \text{DSPACE}(f^2(n))$** 
  - **Off-line nondeterministic TM  $M_1$  with space complexity  $f(n)$** 
    - one input tape and one work tape
  - **Maximal number of different configurations of TM  $M_1$**
  - $s(n+2) f(n) t^{f(n)} \leq c^{f(n)}$

# Relations between language classes

- **Function  $f(n)$** 
  - $f(n) \geq \log_2 n$ , fully space-constructible
- **If  $L \in \text{NSPACE}(f(n)) \Rightarrow L \in \text{DSPACE}(f^2(n))$** 
  - **Off-line nondeterministic TM  $M_1$  with space complexity  $f(n)$** 
    - one input tape and one work tape
  - **Maximal number of different configurations of TM  $M_1$**
  - $s(n+2) f(n) t^{f(n)} \leq c^{f(n)}$ 
    - $s$  - number of states in  $Q$

# Relations between language classes

- **Function  $f(n)$** 
  - $f(n) \geq \log_2 n$ , fully space-constructible
- **If  $L \in \text{NSPACE}(f(n)) \Rightarrow L \in \text{DSPACE}(f^2(n))$** 
  - **Off-line nondeterministic TM  $M_1$  with space complexity  $f(n)$** 
    - one input tape and one work tape
  - **Maximal number of different configurations of TM  $M_1$**
  - $s(n+2) f(n) t^{f(n)} \leq c^{f(n)}$ 
    - $s$  - number of states in  $Q$
    - $(n+2)$  - number of different head positions on the input tape



# Relations between language classes

- **Function  $f(n)$** 
  - $f(n) \geq \log_2 n$ , fully space-constructible
- **If  $L \in \text{NSPACE}(f(n)) \Rightarrow L \in \text{DSPACE}(f^2(n))$** 
  - **Off-line nondeterministic TM  $M_1$  with space complexity  $f(n)$** 
    - one input tape and one work tape
  - **Maximal number of different configurations of TM  $M_1$**
  - $s(n+2) f(n) t^{f(n)} \leq c^{f(n)}$ 
    - $s$  - number of states in  $Q$
    - $(n+2)$  - number of different head positions on the input tape
    - $n$  - length of string  $w$

# Relations between language classes

- **Function  $f(n)$** 
  - $f(n) \geq \log_2 n$ , fully space-constructible
- **If  $L \in \text{NSPACE}(f(n)) \Rightarrow L \in \text{DSPACE}(f^2(n))$** 
  - **Off-line nondeterministic TM  $M_1$  with space complexity  $f(n)$** 
    - one input tape and one work tape
  - **Maximal number of different configurations of TM  $M_1$**
  - $s(n+2) f(n) t^{f(n)} \leq c^{f(n)}$ 
    - $s$  - number of states in  $Q$
    - $(n+2)$  - number of different head positions on the input tape
      - $n$  - length of string  $w$
    - $f(n)$  - number of different head positions on the work tape

# Relations between language classes

- **Function  $f(n)$** 
  - $f(n) \geq \log_2 n$ , fully space-constructible
- **If  $L \in \text{NSPACE}(f(n)) \Rightarrow L \in \text{DSPACE}(f^2(n))$** 
  - **Off-line nondeterministic TM  $M_1$  with space complexity  $f(n)$** 
    - one input tape and one work tape
  - **Maximal number of different configurations of TM  $M_1$**
  - **$s(n+2) f(n) t^{f(n)} \leq c^{f(n)}$** 
    - $s$  - number of states in  $Q$
    - $(n+2)$  - number of different head positions on the input tape
      - $n$  - length of string  $w$
    - $f(n)$  - number of different head positions on the work tape
    - $t^{f(n)}$  - number of different work tape contents

# Relations between language classes

- **Function  $f(n)$** 
  - $f(n) \geq \log_2 n$ , fully space-constructible
- **If  $L \in \text{NSPACE}(f(n)) \Rightarrow L \in \text{DSPACE}(f^2(n))$** 
  - **Off-line nondeterministic TM  $M_1$  with space complexity  $f(n)$** 
    - one input tape and one work tape
  - **Maximal number of different configurations of TM  $M_1$**
  - **$s(n+2) f(n) t^{f(n)} \leq c^{f(n)}$** 
    - $s$  - number of states in  $Q$
    - $(n+2)$  - number of different head positions on the input tape
      - $n$  - length of string  $w$
    - $f(n)$  - number of different head positions on the work tape
    - $t^{f(n)}$  - number of different work tape contents
      - $t$  - number of tape symbols in  $\Gamma$

# Relations between language classes

- **Function  $f(n)$** 
  - $f(n) \geq \log_2 n$ , fully space-constructible
- **If  $L \in \text{NSPACE}(f(n)) \Rightarrow L \in \text{DSPACE}(f^2(n))$** 
  - **Off-line nondeterministic TM  $M_1$  with space complexity  $f(n)$** 
    - one input tape and one work tape
  - **Maximal number of different configurations of TM  $M_1$**
  - $s(n+2) f(n) t^{f(n)} \leq c^{f(n)}$ 
    - $s$  - number of states in  $Q$
    - $(n+2)$  - number of different head positions on the input tape
      - $n$  - length of string  $w$
    - $f(n)$  - number of different head positions on the work tape
    - $t^{f(n)}$  - number of different work tape contents
      - $t$  – number of tape symbols in  $\Gamma$
    - Content of the input tape does not change and does not affect the total number of configurations

# Relations between language classes

# Relations between language classes

$$I_1 \stackrel{i}{\sim} I_2$$

# Relations between language classes

$$I_1 \stackrel{i}{\sim} I_2$$

- TM  $M_1$



# Relations between language classes

$$I_1 \stackrel{i}{\sim} I_2$$

- **TM  $M_1$** 
  - **from configuration  $I_1$**

# Relations between language classes

$$I_1 \stackrel{i}{\sim} I_2$$

- **TM  $M_1$** 
  - from configuration  $I_1$
  - moves into configuration  $I_2$

# Relations between language classes

$$I_1 \stackrel{i}{\succ} I_2$$

- **TM  $M_1$** 
  - from configuration  $I_1$
  - moves into configuration  $I_2$
  - using at most  $2^i$  moves

# Relations between language classes

$$L_1 \stackrel{i}{\sim} L_2$$

# Relations between language classes

*Test*( $l_1, l_2, i$ )

$l_1 \gamma^i l_2$

# Relations between language classes

$\text{Test}(l_1, l_2, i)$   
{

$l_1 \cap l_2$

# Relations between language classes

$Test(l_1, l_2, i)$   
{  
    if ( $i == 0$ ) && (( $l_1 == l_2$ ) || ( $l_1 \succ l_2$ ))

# Relations between language classes

$Test(l_1, l_2, i)$   
{  
    if ( $i == 0$ ) && (( $l_1 == l_2$ ) || ( $l_1 \succ l_2$ ))  
        return *TRUE*;



# Relations between language classes

$Test(l_1, l_2, i)$   
{  
    if ( $i == 0$ ) && (( $l_1 == l_2$ ) || ( $l_1 \succ l_2$ ))  
        return *TRUE*;

# Relations between language classes

$Test(l_1, l_2, i)$

$\{$

if ( $i == 0$ ) && (( $l_1 == l_2$ ) || ( $l_1 \succ l_2$ ))

return *TRUE*;

if ( $i \geq 1$ )

# Relations between language classes

$Test(l_1, l_2, i)$

$\{$

if ( $i == 0$ ) && (( $l_1 == l_2$ ) || ( $l_1 \succ l_2$ ))

return *TRUE*;

if ( $i \geq 1$ )

for each (configuration  $l'$  of length  $< f(n)$ )

# Relations between language classes

$$l_1 \succ^i l_2$$

```

Test( $l_1, l_2, i$ )
{
    if ( $i == 0$ ) && (( $l_1 == l_2$ ) || ( $l_1 \succ l_2$ ))
        return TRUE;

    if ( $i \geq 1$ )
        for each (configuration  $l'$  of length  $< f(n)$ )
            if ((Test( $l_1, l', i-1$ ) == TRUE) &&

```

# Relations between language classes

$$l_1 \succ^i l_2$$

```
Test( $l_1, l_2, i$ )
{
    if ( $i == 0$ ) && (( $l_1 == l_2$ ) || ( $l_1 \succ l_2$ ))
        return TRUE;

    if ( $i \geq 1$ )
        for each (configuration  $l'$  of length  $< f(n)$ )
            if ((Test( $l_1, l', i-1$ ) == TRUE) &&
                (Test( $l', l_2, i-1$ ) == TRUE))
```

# Relations between language classes

$Test(l_1, l_2, i)$

$l_1 \succ^i l_2$

```
{  
  if ( $i == 0$ ) && (( $l_1 == l_2$ ) || ( $l_1 \succ l_2$ ))  
    return TRUE;  
  
  if ( $i \geq 1$ )  
    for each (configuration  $l'$  of length  $< f(n)$ )  
      if (( $Test(l_1, l', i-1) == TRUE$ ) &&  
        ( $Test(l', l_2, i-1) == TRUE$ ))  
        return TRUE;
```

# Relations between language classes

$$l_1 \succ^i l_2$$

```
Test( $l_1, l_2, i$ )
{
    if ( $i == 0$ ) && (( $l_1 == l_2$ ) || ( $l_1 \succ l_2$ ))
        return TRUE;

    if ( $i \geq 1$ )
        for each (configuration  $l'$  of length  $< f(n)$ )
            if ((Test( $l_1, l', i-1$ ) == TRUE) &&
                (Test( $l', l_2, i-1$ ) == TRUE))
                return TRUE;
```

# Relations between language classes

$$l_1 \succ^i l_2$$

```
Test( $l_1, l_2, i$ )
{
    if ( $i == 0$ ) && (( $l_1 == l_2$ ) || ( $l_1 \succ l_2$ ))
        return TRUE;

    if ( $i \geq 1$ )
        for each (configuration  $l'$  of length  $< f(n)$ )
            if ((Test( $l_1, l', i-1$ ) == TRUE) &&
                (Test( $l', l_2, i-1$ ) == TRUE))
                return TRUE;

    return FALSE;
```



# Relations between language classes

$$l_1 \succ^i l_2$$

```
Test( $l_1, l_2, i$ )
{
    if ( $i == 0$ ) && (( $l_1 == l_2$ ) || ( $l_1 \succ l_2$ ))
        return TRUE;

    if ( $i \geq 1$ )
        for each (configuration  $l'$  of length  $< f(n)$ )
            if ((Test( $l_1, l', i-1$ ) == TRUE) &&
                (Test( $l', l_2, i-1$ ) == TRUE))
                return TRUE;

    return FALSE;
}
```

# Relations between language classes

$$I_1 \stackrel{i}{\sim} I_2$$

# Relations between language classes

$$L_1 \stackrel{i}{\sim} L_2$$

- TM  $M_2$  simulates a nondeterministic TM  $M_1$

# Relations between language classes

$$L_1 \stackrel{i}{\sim} L_2$$

- **TM  $M_2$  simulates a nondeterministic TM  $M_1$** 
  - **Testing a string  $w$  of length  $n$**

# Relations between language classes

$$I_1 \stackrel{i}{\sim} I_2$$

- TM  $M_2$  simulates a nondeterministic TM  $M_1$ 
  - Testing a string  $w$  of length  $n$
  - TM  $M_2$  calls  $\text{Test}(I_1, I_2, i)$

# Relations between language classes

$$I_1 \stackrel{i}{\sim} I_2$$

- **TM  $M_2$  simulates a nondeterministic TM  $M_1$** 
  - **Testing a string  $w$  of length  $n$**
  - **TM  $M_2$  calls  $\text{Test}(I_1, I_2, i)$** 
    1. Based on the length  $n$  it calculates  $f(n)$

# Relations between language classes

$$l_1 \stackrel{i}{\sim} l_2$$

- **TM  $M_2$  simulates a nondeterministic TM  $M_1$** 
  - **Testing a string  $w$  of length  $n$**
  - **TM  $M_2$  calls  $\text{Test}(l_1, l_2, i)$** 
    1. Based on the length  $n$  it calculates  $f(n)$
    2. Configurations  $l_1$  is the initial configuration

# Relations between language classes

$$l_1 \stackrel{i}{\succ} l_2$$

- **TM  $M_2$  simulates a nondeterministic TM  $M_1$** 
  - **Testing a string  $w$  of length  $n$**
  - **TM  $M_2$  calls  $\text{Test}(l_1, l_2, i)$** 
    1. Based on the length  $n$  it calculates  $f(n)$
    2. Configurations  $l_1$  is the initial configuration
    3. Configurations  $l_2$  is one of the configurations of TM  $M_1$  which accept the string



# Relations between language classes

$$l_1 \xrightarrow{i} l_2$$

- **TM  $M_2$  simulates a nondeterministic TM  $M_1$** 
  - **Testing a string  $w$  of length  $n$**
  - **TM  $M_2$  calls  $\text{Test}(l_1, l_2, i)$** 
    1. Based on the length  $n$  it calculates  $f(n)$
    2. Configurations  $l_1$  is the initial configuration
    3. Configurations  $l_2$  is one of the configurations of TM  $M_1$  which accept the string
    4. Maximal number of configurations from initial configuration to the configuration that accepts the string  $\leq c^{f(n)} \Rightarrow$

# Relations between language classes

$$l_1 \xrightarrow{i} l_2$$

- **TM  $M_2$  simulates a nondeterministic TM  $M_1$** 
  - **Testing a string  $w$  of length  $n$**
  - **TM  $M_2$  calls  $\text{Test}(l_1, l_2, i)$** 
    1. Based on the length  $n$  it calculates  $f(n)$
    2. Configurations  $l_1$  is the initial configuration
    3. Configurations  $l_2$  is one of the configurations of TM  $M_1$  which accept the string
    4. Maximal number of configurations from initial configuration to the configuration that accepts the string  $\leq c^{f(n)} \Rightarrow$

$$i = \log_2( c^{f(n)} ) = f(n) \log_2 c$$

# Relations between language classes

# Relations between language classes

*LIFO stack*




# Relations between language classes




# Relations between language classes



# Relations between language classes




# Relations between language classes







# Relations between language classes




# Relations between language classes




# Relations between language classes




# Relations between language classes




# Relations between language classes



# Relations between language classes



# Relations between language classes



$$f(n)+1 \approx f(n) \wedge$$


$$(\log_2(n+2) \leq f(n)) \wedge$$

$$(\log_2 c \text{ is constant})$$

$$\Rightarrow 3(f(n)+1) + 3 \log_2(n+2) + f(n) \log_2 c \approx$$


$$3f(n) + 3f(n) + \log_2 c f(n) \approx f(n)$$

# Relations between language classes







# Relations between language classes




# Relations between language classes




# Relations between language classes




# Relations between language classes



# Relations between language classes



# Relations between language classes



# Relations between language classes

