

Lecture 10

3.2.3 PA and Context-free Grammar

3.3 PROPERTIES OF CONTEXT-FREE LANGUAGES

3.3.1 Closure Properties of Context-Free Languages

3.3.2 Pumping Lemma

Lecture 10

3.2.3 PA and Context-free Grammar

3.3 PROPERTIES OF CONTEXT-FREE LANGUAGES

3.3.1 Closure Properties of Context-Free Languages

3.3.2 Pumping Lemma

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

$$G = (V, T, P, S)$$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

$$G = (V, T, P, S)$$

Greibach normal form:

$$\begin{aligned} A &\rightarrow a\beta \\ A \in V, a \in T, \beta &\in V^* \end{aligned}$$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

PA $M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$

$G = (V, T, P, S)$

Greibach normal form:

$$A \rightarrow a\beta \\ A \in V, a \in T, \beta \in V^*$$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

PA $M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$

$G = (V, T, P, S)$

Greibach normal form:

$$A \rightarrow a\beta \\ A \in V, a \in T, \beta \in V^*$$

a) PA M has only one state q which is also its start state

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

PA $M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$

$G = (V, T, P, S)$

Greibach normal form:

$$A \rightarrow a\beta \\ A \in V, a \in T, \beta \in V^*$$

- a) PA M has only one state q which is also its start state
- b) $\Sigma = T$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

PA $M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$

$G = (V, T, P, S)$

Greibach normal form:

$$A \rightarrow a\beta \\ A \in V, a \in T, \beta \in V^*$$

- a) PA M has only one state q which is also its start state
- b) $\Sigma = T$
- c) $\Gamma = V$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

PA $M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$

$G = (V, T, P, S)$

Greibach normal form:

$$A \rightarrow a\beta \\ A \in V, a \in T, \beta \in V^*$$

- a) PA M has only one state q which is also its start state
- b) $\Sigma = T$
- c) $\Gamma = V$
- d) **Start stack symbol = S**

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

PA $M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$

$G = (V, T, P, S)$

Greibach normal form:

$$A \rightarrow a\beta \\ A \in V, a \in T, \beta \in V^*$$

- a) PA M has only one state q which is also its start state
- b) $\Sigma = T$
- c) $\Gamma = V$
- d) Start stack symbol = S
- e) $F = \emptyset$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

PA $M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$

$G = (V, T, P, S)$

Greibach normal form:

$$A \rightarrow a\beta \\ A \in V, a \in T, \beta \in V^*$$

- a) PA M has only one state q which is also its start state
- b) $\Sigma = T$
- c) $\Gamma = V$
- d) Start stack symbol = S
- e) $F = \emptyset$
- f) PA M accepts by empty stack

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

PA $M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$

$G = (V, T, P, S)$

Greibach normal form:

$$A \rightarrow a\beta \\ A \in V, a \in T, \beta \in V^*$$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

PA $M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$

$G = (V, T, P, S)$

Greibach normal form:

$$A \rightarrow a\beta \\ A \in V, a \in T, \beta \in V^*$$

Transition function:

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

PA $M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$

$G = (V, T, P, S)$

Greibach normal form:

$$A \rightarrow a\beta \\ A \in V, a \in T, \beta \in V^*$$

Transition function:

$$(q, \gamma) \in \delta(q, a, A) \quad \text{if and only if} \quad A \rightarrow a\gamma$$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

PA $M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$

$G = (V, T, P, S)$

Greibach normal form:

$$A \rightarrow a\beta \\ A \in V, a \in T, \beta \in V^*$$

Transition function:

$$(q, \gamma) \in \delta(q, a, A) \quad \text{if and only if} \quad A \rightarrow a\gamma$$



Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

PA $M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$

$G = (V, T, P, S)$


Greibach normal form:

$$A \rightarrow a\beta \\ A \in V, a \in T, \beta \in V^*$$

Transition function:

$$(q, \gamma) \in \delta(q, a, A) \quad \text{if and only if} \quad A \rightarrow a\gamma$$

Input tape



Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

$$\text{PA } M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$$


$$G = (V, T, P, S)$$

Greibach normal form:

$$\begin{aligned} A &\rightarrow a\beta \\ A \in V, a \in T, \beta &\in V^* \end{aligned}$$

Transition function:

$$(q, \gamma) \in \delta(q, a, A) \quad \text{if and only if} \quad A \rightarrow a\gamma$$



Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

$$\text{PA } M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$$


$$G = (V, T, P, S)$$

Greibach normal form:

$$\begin{aligned} A &\rightarrow a\beta \\ A \in V, a \in T, \beta &\in V^* \end{aligned}$$

Transition function:

$$(q, \gamma) \in \delta(q, a, A) \quad \text{if and only if} \quad A \rightarrow a\gamma$$



Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

$$\text{PA } M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$$


$$G = (V, T, P, S)$$

Greibach normal form:

$$\begin{aligned} A &\rightarrow a\beta \\ A \in V, a \in T, \beta &\in V^* \end{aligned}$$

Transition function:

$$(q, \gamma) \in \delta(q, a, A) \quad \text{if and only if} \quad A \rightarrow a\gamma$$



Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

$$\text{PA } M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$$


$$G = (V, T, P, S)$$

Greibach normal form:

$$\begin{aligned} A &\rightarrow a\beta \\ A \in V, a \in T, \beta &\in V^* \end{aligned}$$

Transition function:

$$(q, \gamma) \in \delta(q, a, A) \quad \text{if and only if} \quad A \rightarrow a\gamma$$



Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

PA $M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$

$G = (V, T, P, S)$

Greibach normal form:

$$A \rightarrow a\beta \\ A \in V, a \in T, \beta \in V^*$$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

PA $M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$

$G = (V, T, P, S)$

Greibach normal form:

$$A \rightarrow a\beta \\ A \in V, a \in T, \beta \in V^*$$

(q, x, S)

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

PA $M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$

$G = (V, T, P, S)$

Greibach normal form:

$$A \rightarrow a\beta \\ A \in V, a \in T, \beta \in V^*$$

$(q, x, S) \succ_M$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

PA $M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$

$G = (V, T, P, S)$

Greibach normal form:

$$A \rightarrow a\beta \\ A \in V, a \in T, \beta \in V^*$$

$$(q, x, S) \xrightarrow{M} (q, \varepsilon, \alpha)$$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

PA $M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$

$G = (V, T, P, S)$

Greibach normal form:

$$A \rightarrow a\beta \\ A \in V, a \in T, \beta \in V^*$$

$$(q, x, S) \xrightarrow{M} (q, \varepsilon, \alpha)$$

S

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

PA $M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$

$G = (V, T, P, S)$

Greibach normal form:

$$A \rightarrow a\beta \\ A \in V, a \in T, \beta \in V^*$$

$(q, x, S) \xrightarrow{M} (q, \varepsilon, \alpha)$

$S \xrightarrow{G}$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

PA $M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$

$G = (V, T, P, S)$

Greibach normal form:

$$A \rightarrow a\beta \\ A \in V, a \in T, \beta \in V^*$$

$$(q, x, S) \xrightarrow{M} (q, \varepsilon, \alpha)$$

$$S \xrightarrow[G]{} x\alpha$$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

PA $M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$

$G = (V, T, P, S)$

Greibach normal form:

$$A \rightarrow a\beta \\ A \in V, a \in T, \beta \in V^*$$

$$(q, x, S) \xrightarrow[M]{} (q, \varepsilon, \varepsilon)$$

$$S \xrightarrow[G]{} x\alpha$$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

PA $M = (\{q\}, \Sigma, \Gamma, \delta, q, S, \emptyset)$

$G = (V, T, P, S)$

Greibach normal form:

$$A \rightarrow a\beta \\ A \in V, a \in T, \beta \in V^*$$

$$(q, x, S) \xrightarrow[M]{} (q, \varepsilon, \varepsilon)$$

$$S \xrightarrow[G]{} x$$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

$$G = (\{S, A\}, \{a, b\}, \\ \{S \rightarrow aAA, A \rightarrow aS \mid bS \mid a\}, S)$$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

$M = (\{q\}, \{a, b\}, \{S, A\}, \delta, q, S, \emptyset)$

$G = (\{S, A\}, \{a, b\},$
 $\{S \rightarrow aAA, A \rightarrow aS \mid bS \mid a\}, S)$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

$M = (\{q\}, \{a, b\}, \{S, A\}, \delta, q, S, \emptyset)$

$G = (\{S, A\}, \{a, b\},$
 $\{S \rightarrow aAA, A \rightarrow aS \mid bS \mid a\}, S)$

$S \rightarrow aAA$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

$M = (\{q\}, \{a, b\}, \{S, A\}, \delta, q, S, \emptyset)$

$G = (\{S, A\}, \{a, b\},$
 $\{S \rightarrow aAA, A \rightarrow aS \mid bS \mid a\}, S)$

$\delta(q, a, S) = \{(q, AA)\}$

$S \rightarrow aAA$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

$M = (\{q\}, \{a, b\}, \{S, A\}, \delta, q, S, \emptyset)$

$G = (\{S, A\}, \{a, b\},$
 $\{S \rightarrow aAA, A \rightarrow aS \mid bS \mid a\}, S)$

$\delta(q, a, S) = \{(q, AA)\}$

$S \rightarrow aAA$

$A \rightarrow aS, A \rightarrow a$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

$M = (\{q\}, \{a, b\}, \{S, A\}, \delta, q, S, \emptyset)$

$G = (\{S, A\}, \{a, b\},$
 $\{S \rightarrow aAA, A \rightarrow aS \mid bS \mid a\}, S)$

$$\delta(q, a, S) = \{(q, AA)\}$$

$$S \rightarrow aAA$$

$$\delta(q, a, A) = \{(q, S), (q, \epsilon)\}$$

$$A \rightarrow aS, A \rightarrow a$$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

$M = (\{q\}, \{a, b\}, \{S, A\}, \delta, q, S, \emptyset)$

$G = (\{S, A\}, \{a, b\},$
 $\{S \rightarrow aAA, A \rightarrow aS \mid bS \mid a\}, S)$

$$\delta(q, a, S) = \{(q, AA)\}$$

$$S \rightarrow aAA$$

$$\delta(q, a, A) = \{(q, S), (q, \epsilon)\}$$

$$A \rightarrow aS, A \rightarrow a$$

$$A \rightarrow bS$$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

$M = (\{q\}, \{a, b\}, \{S, A\}, \delta, q, S, \emptyset)$

$G = (\{S, A\}, \{a, b\},$
 $\{S \rightarrow aAA, A \rightarrow aS \mid bS \mid a\}, S)$

$$\delta(q, a, S) = \{(q, AA)\}$$

$$S \rightarrow aAA$$

$$\delta(q, a, A) = \{(q, S), (q, \epsilon)\}$$

$$A \rightarrow aS, A \rightarrow a$$

$$\delta(q, b, A) = \{(q, S)\}$$

$$A \rightarrow bS$$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

$$M = (\{q\}, \{a, b\}, \{S, A\}, \delta, q, S, \emptyset)$$

$$G = (\{S, A\}, \{a, b\}, \\ \{S \rightarrow aAA, A \rightarrow aS \mid bS \mid a\}, S)$$

$$\delta(q, a, S) = \{(q, AA)\}$$

$$S \rightarrow aAA$$

$$\delta(q, a, A) = \{(q, S), (q, \epsilon)\}$$

$$A \rightarrow aS, A \rightarrow a$$

$$\delta(q, b, A) = \{(q, S)\}$$

$$A \rightarrow bS$$

$S \Rightarrow aAA \Rightarrow abSA \Rightarrow abaAAA \Rightarrow$
 $abaaAA \Rightarrow abaaaA \Rightarrow abaaaa$

Constructing a PA That Accepts By Empty Stack Given a Context-Free Grammar

$$M = (\{q\}, \{a, b\}, \{S, A\}, \delta, q, S, \emptyset)$$

$$G = (\{S, A\}, \{a, b\}, \\ \{S \rightarrow aAA, A \rightarrow aS \mid bS \mid a\}, S)$$

$$\delta(q, a, S) = \{(q, AA)\}$$

$$S \rightarrow aAA$$

$$\delta(q, a, A) = \{(q, S), (q, \epsilon)\}$$

$$A \rightarrow aS, A \rightarrow a$$

$$\delta(q, b, A) = \{(q, S)\}$$

$$A \rightarrow bS$$

$S \Rightarrow aAA \Rightarrow abSA \Rightarrow abaAAA \Rightarrow$
 $abaaAA \Rightarrow abaaaA \Rightarrow abaaaa$

$(q, abaaaa, S) \succ (q, baaaa, AA) \succ (q, aaaa, SA) \succ (q, aaa, AAA) \succ$
 $(q, aa, AA) \succ (q, a, A) \succ (q, \epsilon, \epsilon)$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$[q, A, p] \in V$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$[q, A, p] \in V$

$q \in Q$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$[q, A, p] \in V$

$p \in Q$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$[q, A, p] \in V$

$A \in \Gamma$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$


$[q, A, p] \in V$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$

$$[q, A, p] \in V$$




Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$[q, A, p] \in V$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$




Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$[q, A, p] \in V$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$




Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$

$$[q, A, p] \in V$$




Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$[q, A, p] \in V$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$




Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$[q, A, p] \in V$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$




Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$

$$[q, A, p] \in V$$




Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$

$$[q, A, p] \in V$$




Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$

$$[q, A, p] \in V$$




Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$[q, A, p] \in V$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$




Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$

$$[q, A, p] \in V$$




Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$

$$[q, A, p] \in V$$




Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$

$$[q, A, p] \in V$$




Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$

$$[q, A, p] \in V$$




Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$

$$[q, A, p] \in V$$




Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$

$$[q, A, p] \in V$$



Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$[q, A, p] \in V$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$[q, A, p] \in V$

$$q_0 \xrightarrow[M]{*} q_0$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$[q, A, p] \in V$

$$q_0 \xrightarrow[M]{\gamma^*} q_0$$
$$q_0 \xrightarrow[M]{\gamma^*} q_1$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$

$$[q, A, p] \in V$$

$$\begin{array}{c} q_0 \xrightarrow[M]{\gamma^*} q_0 \\ q_0 \xrightarrow[M]{\gamma^*} q_1 \\ q_0 \xrightarrow[M]{\gamma^*} q_2 \end{array}$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$

$$[q, A, p] \in V$$

$$q_0 \xrightarrow[M]{*} q_0$$

$$q_0 \xrightarrow[M]{*} q_1$$

$$q_0 \xrightarrow[M]{*} q_2$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$

$$[q, A, p] \in V$$

$$\begin{array}{c} q_0 \xrightarrow[M]{*} q_0 \\ q_0 \xrightarrow[M]{*} q_1 \\ q_0 \xrightarrow[M]{*} q_2 \\ \cdots \\ q_0 \xrightarrow[M]{*} q_n \end{array}$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$

$$[q, A, p] \in V$$

$$\begin{array}{ccc} q_0 & \succ^* & q_0 \\ & M & \\ q_0 & \succ^* & q_1 \\ & M & \\ q_0 & \succ^* & q_2 \\ & M & \\ \cdots & & \\ q_0 & \succ^* & q_n \\ & M & \end{array}$$

$$S \rightarrow [q_0, Z_0, q_0]$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$

$$[q, A, p] \in V$$

$$\begin{array}{ccc} q_0 & \succ^* & q_0 \\ & M & \\ q_0 & \succ^* & q_1 \\ & M & \\ q_0 & \succ^* & q_2 \\ & M & \\ \cdots & & \\ q_0 & \succ^* & q_n \\ & M & \end{array}$$

$$S \rightarrow [q_0, Z_0, q_0]$$

$$S \rightarrow [q_0, Z_0, q_1]$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$

$$[q, A, p] \in V$$

$$q_0 \xrightarrow[M]{*} q_0$$

$$S \rightarrow [q_0, Z_0, q_0]$$

$$q_0 \xrightarrow[M]{*} q_1$$

$$S \rightarrow [q_0, Z_0, q_1]$$

$$q_0 \xrightarrow[M]{*} q_2$$

$$S \rightarrow [q_0, Z_0, q_2]$$

$$q_0 \xrightarrow[M]{*} q_n$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$

$$[q, A, p] \in V$$

$$q_0 \xrightarrow[M]{*} q_0$$
$$q_0 \xrightarrow[M]{*} q_1$$
$$q_0 \xrightarrow[M]{*} q_2$$

- - -

$$q_0 \xrightarrow[M]{*} q_n$$

$$S \rightarrow [q_0, Z_0, q_0]$$

$$S \rightarrow [q_0, Z_0, q_1]$$

$$S \rightarrow [q_0, Z_0, q_2]$$

- - -

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$

$$[q, A, p] \in V$$

$$q_0 \xrightarrow[M]{*} q_0$$

$$S \rightarrow [q_0, Z_0, q_0]$$

$$q_0 \xrightarrow[M]{*} q_1$$

$$S \rightarrow [q_0, Z_0, q_1]$$

$$q_0 \xrightarrow[M]{*} q_2$$

$$S \rightarrow [q_0, Z_0, q_2]$$

$$q_0 \xrightarrow[M]{*} q_n$$

$$S \rightarrow [q_0, Z_0, q_n]$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1B_2 \dots B_m) \in \delta(q, a, A)$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$q \xrightarrow{M} q_1 \xrightarrow{M} q_1 \xrightarrow{M} q_1 \xrightarrow{M} q_1 \xrightarrow{*}{M} q_1 \xrightarrow{M} q_1 \xrightarrow{M} q_1$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$\begin{array}{ccc} q \succ_M q_1 \succ_M q_1 \succ_M q_1 & \succ_M^* & q_1 \succ_M q_1 \succ_M q_1 \\ q \succ_M q_1 \succ_M q_1 \succ_M q_1 & \succ_M^* & q_1 \succ_M q_1 \succ_M q_2 \end{array}$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$\begin{array}{ll} q \succ_M q_1 \succ_M q_1 \succ_M q_1 & \succ_M^* \\ & q_1 \succ_M q_1 \succ_M q_1 \\ q \succ_M q_1 \succ_M q_1 \succ_M q_1 & \succ_M^* \\ & q_1 \succ_M q_1 \succ_M q_2 \\ q \succ_M q_1 \succ_M q_1 \succ_M q_1 & \succ_M^* \\ & q_1 \succ_M q_2 \succ_M q_1 \end{array}$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$q \xrightarrow{M} q_1 \xrightarrow{M} q_1 \xrightarrow{M} q_1 \xrightarrow{M} q_1 \xrightarrow{M} \dots$$

$$q \xrightarrow{M} q_1 \xrightarrow{M} q_1 \xrightarrow{M} q_1 \xrightarrow{M} q_1 \xrightarrow{M} \dots$$


$$q \xrightarrow{M} q_1 \xrightarrow{M} q_1 \xrightarrow{M} q_1 \xrightarrow{M} q_1 \xrightarrow{M} \dots$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$



Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$q \xrightarrow{M} q_1 \xrightarrow{M} q_1 \xrightarrow{M} q_1 \xrightarrow{M} q_1 \xrightarrow{M} \dots \xrightarrow{M} q_1$$

$$q \xrightarrow{M} q_1 \xrightarrow{M} q_1 \xrightarrow{M} q_1 \xrightarrow{M} q_1 \xrightarrow{M} \dots \xrightarrow{M} q_1$$

$$q \xrightarrow{M} q_1 \xrightarrow{M} q_1 \xrightarrow{M} q_1 \xrightarrow{M} q_1 \xrightarrow{M} \dots \xrightarrow{M} q_1$$

$$q \xrightarrow{M} q_1 \xrightarrow{M} q_n \xrightarrow{M} q_n \xrightarrow{M} \dots \xrightarrow{M} q_n$$

$$q \xrightarrow{M} q_1 \xrightarrow{M} q_n \xrightarrow{M} q_n \xrightarrow{M} \dots \xrightarrow{M} q_n$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$q \xrightarrow[M]{} q_1 \xrightarrow[M]{} q_1 \xrightarrow[M]{} q_1 \quad \xrightarrow[M]^* \quad q_1 \xrightarrow[M]{} q_1 \xrightarrow[M]{} q_1$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$q \xrightarrow[M]{} q_1 \xrightarrow[M]{} q_1 \xrightarrow[M]{} q_1 \xrightarrow[M]^* q_1 \xrightarrow[M]{} q_1 \xrightarrow[M]{} q_1$$

$$[q, A, q_1] \rightarrow a [q_1, B_1, q_1] [q_1, B_2, q_1] \dots [q_1, B_{m-1}, q_1] [q_1, B_m, q_1]$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$q \xrightarrow[M]{} q_1 \xrightarrow[M]{} q_1 \xrightarrow[M]{} q_1 \xrightarrow[M]{} \cdots \xrightarrow[M]^* q_1 \xrightarrow[M]{} q_1 \xrightarrow[M]{} q_1$$

$$[q, A, q_1] \rightarrow a [q_1, B_1, q_1] [q_1, B_2, q_1] \dots [q_1, B_{m-1}, q_1] [q_1, B_m, q_1]$$

$$q \xrightarrow[M]{} q_1 \xrightarrow[M]{} q_1 \xrightarrow[M]{} q_1 \xrightarrow[M]{} \cdots \xrightarrow[M]^* q_1 \xrightarrow[M]{} q_2$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$$G = (V, T, P, S)$$

$$\text{PA } M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$q \xrightarrow[M]{} q_1 \xrightarrow[M]{} q_1 \xrightarrow[M]{} q_1 \xrightarrow[M]{} \cdots \xrightarrow[M]^* q_1 \xrightarrow[M]{} q_1 \xrightarrow[M]{} q_1$$

$$[q, A, q_1] \rightarrow a [q_1, B_1, q_1] [q_1, B_2, q_1] \dots [q_1, B_{m-1}, q_1] [q_1, B_m, q_1]$$

$$q \xrightarrow[M]{} q_1 \xrightarrow[M]{} q_1 \xrightarrow[M]{} q_1 \xrightarrow[M]{} \cdots \xrightarrow[M]^* q_1 \xrightarrow[M]{} q_2$$

$$[q, A, q_2] \rightarrow a [q_1, B_1, q_1] [q_1, B_2, q_1] \dots [q_1, B_{m-1}, q_1] [q_1, B_m, q_2]$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$[q, A, q_{m+1}] \rightarrow a [q_1, B_1, q_2] [q_2, B_2, q_3] \dots [q_{m-1}, B_{m-1}, q_m] [q_m, B_m, q_{m+1}]$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$[q, A, q_{m+1}] \rightarrow a [q_1, B_1, q_2] [q_2, B_2, q_3] \dots [q_{m-1}, B_{m-1}, q_m] [q_m, B_m, q_{m+1}]$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$[q, A, q_{m+1}] \rightarrow a [q_1, B_1, q_2] [q_2, B_2, q_3] \dots [q_{m-1}, B_{m-1}, q_m] [q_m, B_m, q_{m+1}]$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$[q, A, q_{m+1}] \rightarrow a [q_1, B_1, q_2] [q_2, B_2, q_3] \dots [q_{m-1}, B_{m-1}, q_m] [q_m, B_m, q_{m+1}]$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$[q, A, q_{m+1}] \rightarrow a [q_1, B_1, q_2] [q_2, B_2, q_3] \dots [q_{m-1}, B_{m-1}, q_m] [q_m, B_m, q_{m+1}]$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$[q, A, q_{m+1}] \rightarrow a [q_1, B_1, q_2] [q_2, B_2, q_3] \dots [q_{m-1}, B_{m-1}, q_m] [q_m, B_m, q_{m+1}]$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$[q, A, q_{m+1}] \rightarrow a [q_1, B_1, q_2] [q_2, B_2, q_3] \dots [q_{m-1}, B_{m-1}, q_m] [q_m, B_m, q_{m+1}]$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$[q, A, q_{m+1}] \rightarrow a [q_1, B_1, q_2] [q_2, B_2, q_3] \dots [q_{m-1}, B_{m-1}, q_m] [q_m, B_m, q_{m+1}]$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$[q, A, q_{m+1}] \rightarrow a [q_1, B_1, q_2] [q_2, B_2, q_3] \dots [q_{m-1}, B_{m-1}, q_m] [q_m, B_m, q_{m+1}]$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$[q, A, q_{m+1}] \rightarrow a [q_1, B_1, q_2] [q_2, B_2, q_3] \dots [q_{m-1}, B_{m-1}, q_m] [q_m, B_m, q_{m+1}]$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$[q, A, q_{m+1}] \rightarrow a [q_1, B_1, q_2] [q_2, B_2, q_3] \dots [q_{m-1}, B_{m-1}, q_m] [q_m, B_m, q_{m+1}]$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$[q, A, q_{m+1}] \rightarrow a [q_1, B_1, q_2] [q_2, B_2, q_3] \dots [q_{m-1}, B_{m-1}, q_m] [q_m, B_m, q_{m+1}]$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$[q, A, q_{m+1}] \rightarrow a [q_1, B_1, q_2] [q_2, B_2, q_3] \dots [q_{m-1}, B_{m-1}, q_m] [q_m, B_m, q_{m+1}]$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$[q, A, q_{m+1}] \rightarrow a [q_1, B_1, q_2] [q_2, B_2, q_3] \dots [q_{m-1}, B_{m-1}, q_m] [q_m, B_m, q_{m+1}]$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$[q, A, q_{m+1}] \rightarrow a [q_1, B_1, q_2] [q_2, B_2, q_3] \dots [q_{m-1}, B_{m-1}, q_m] [q_m, B_m, q_{m+1}]$$

$$(q_1, \varepsilon) \in \delta(q, a, A)$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$[q, A, q_{m+1}] \rightarrow a [q_1, B_1, q_2] [q_2, B_2, q_3] \dots [q_{m-1}, B_{m-1}, q_m] [q_m, B_m, q_{m+1}]$$

$$(q_1, \varepsilon) \in \delta(q, a, A)$$

$$[q, A, q_1] \rightarrow a$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$[q, A, q_{m+1}] \rightarrow a [q_1, B_1, q_2] [q_2, B_2, q_3] \dots [q_{m-1}, B_{m-1}, q_m] [q_m, B_m, q_{m+1}]$$

$$(q_1, \varepsilon) \in \delta(q, a, A)$$

$$[q, A, q_1] \rightarrow a$$

$$(q, x, A)$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$[q, A, q_{m+1}] \rightarrow a [q_1, B_1, q_2] [q_2, B_2, q_3] \dots [q_{m-1}, B_{m-1}, q_m] [q_m, B_m, q_{m+1}]$$

$$(q_1, \varepsilon) \in \delta(q, a, A)$$

$$[q, A, q_1] \rightarrow a$$

$$(q, x, A) \xrightarrow[M]{*}$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$[q, A, q_{m+1}] \rightarrow a [q_1, B_1, q_2] [q_2, B_2, q_3] \dots [q_{m-1}, B_{m-1}, q_m] [q_m, B_m, q_{m+1}]$$

$$(q_1, \varepsilon) \in \delta(q, a, A)$$

$$[q, A, q_1] \rightarrow a$$

$$(q, x, A) \xrightarrow[M]{*} (p, \varepsilon, \varepsilon)$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$[q, A, q_{m+1}] \rightarrow a [q_1, B_1, q_2] [q_2, B_2, q_3] \dots [q_{m-1}, B_{m-1}, q_m] [q_m, B_m, q_{m+1}]$$

$$(q_1, \varepsilon) \in \delta(q, a, A)$$

$$[q, A, q_1] \rightarrow a$$

$$[q, A, p]$$

$$(q, x, A) \xrightarrow[M]{*} (p, \varepsilon, \varepsilon)$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$[q, A, q_{m+1}] \rightarrow a [q_1, B_1, q_2] [q_2, B_2, q_3] \dots [q_{m-1}, B_{m-1}, q_m] [q_m, B_m, q_{m+1}]$$

$$(q_1, \varepsilon) \in \delta(q, a, A)$$

$$[q, A, q_1] \rightarrow a$$

$$[q, A, p] \xrightarrow[G]{*}$$

$$(q, x, A) \xrightarrow[M]{*} (p, \varepsilon, \varepsilon)$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, T, P, S)$

PA $M = (Q, \Sigma, \Gamma, \delta, q_0, Z_0, F)$

$$(q_1, B_1 B_2 \dots B_m) \in \delta(q, a, A)$$

$$[q, A, q_{m+1}] \rightarrow a [q_1, B_1, q_2] [q_2, B_2, q_3] \dots [q_{m-1}, B_{m-1}, q_m] [q_m, B_m, q_{m+1}]$$

$$(q_1, \varepsilon) \in \delta(q, a, A)$$

$$[q, A, q_1] \rightarrow a$$

$$[q, A, p] \xrightarrow[G]{*} x$$

$$(q, x, A) \xrightarrow[M]{*} (p, \varepsilon, \varepsilon)$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

- 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
- 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
- 3) $\delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

- | | |
|---|---|
| 1) $\delta(q_1, 0, N) = \{(q_1, NK)\}$ | 4) $\delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$ |
| 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$ | 5) $\delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$ |
| 3) $\delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$ | 6) $\delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$ |

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

$$1) \quad \delta(q_1, 0, K) = \{(q_1, NK)\}$$

$$2) \quad \delta(q_1, 0, N) = \{(q_1, NN)\}$$

$$3) \quad \delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$4) \quad \delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$5) \quad \delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$$

$$6) \quad \delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

$$1) \quad \delta(q_1, 0, N) = \{(q_1, NK)\}$$

$$2) \quad \delta(q_1, 0, N) = \{(q_1, NN)\}$$

$$3) \quad \delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$4) \quad \delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$5) \quad \delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$$

$$6) \quad \delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$$

$V = \{ S, [q_1, N, q_1], [q_1, N, q_2], [q_2, N, q_1], [q_2, N, q_2],$
 $[q_1, K, q_1], [q_1, K, q_2], [q_2, K, q_1], [q_2, K, q_2] \}$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

$$1) \quad \delta(q_1, 0, K) = \{(q_1, NK)\}$$

$$2) \quad \delta(q_1, 0, N) = \{(q_1, NN)\}$$

$$3) \quad \delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$4) \quad \delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$5) \quad \delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$$

$$6) \quad \delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

$$1) \quad \delta(q_1, 0, K) = \{(q_1, NK)\}$$

$$2) \quad \delta(q_1, 0, N) = \{(q_1, NN)\}$$

$$3) \quad \delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$4) \quad \delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$5) \quad \delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$$

$$6) \quad \delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$$

i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$

2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$

3) $\delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$

4) $\delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$

5) $\delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$

6) $\delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$

i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$

2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$

3) $\delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$

4) $\delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$

5) $\delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$

6) $\delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$

i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$

2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$

3) $\delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$

4) $\delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$

5) $\delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$

6) $\delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$

i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$

ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_1] \mid 0 [q_1, N, q_2] [q_2, K, q_1]$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$

2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$

3) $\delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$

4) $\delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$

5) $\delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$

6) $\delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$

i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$

ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_1] \mid 0 [q_1, N, q_2] [q_2, K, q_1]$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$

2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$

3) $\delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$

4) $\delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$

5) $\delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$

6) $\delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$

i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$

ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_1] \mid 0 [q_1, N, q_2] [q_2, K, q_1]$

iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$

2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$

3) $\delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$

4) $\delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$

5) $\delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$

6) $\delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$

i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$

ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_1] \mid 0 [q_1, N, q_2] [q_2, K, q_1]$

iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$

2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$

3) $\delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$

4) $\delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$

5) $\delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$

6) $\delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$

i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$

ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_1] \mid 0 [q_1, N, q_2] [q_2, K, q_1]$

iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$

2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$

3) $\delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$

4) $\delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$

5) $\delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$

6) $\delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$

i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$

ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_1] \mid 0 [q_1, N, q_2] [q_2, K, q_1]$

iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

$$1) \quad \delta(q_1, 0, K) = \{(q_1, NK)\}$$

$$2) \quad \delta(q_1, 0, N) = \{(q_1, NN)\}$$

$$3) \quad \delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$4) \quad \delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$5) \quad \delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$$

$$6) \quad \delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$$

i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$

ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_1] \mid 0 [q_1, N, q_2] [q_2, K, q_1]$

iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$

iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_1] \mid 0 [q_1, N, q_2] [q_2, N, q_1]$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

$$1) \quad \delta(q_1, 0, K) = \{(q_1, NK)\}$$

$$2) \quad \delta(q_1, 0, N) = \{(q_1, NN)\}$$

$$3) \quad \delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$4) \quad \delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$5) \quad \delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$$

$$6) \quad \delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$$

i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$

ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_1] \mid 0 [q_1, N, q_2] [q_2, K, q_1]$

iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$

iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_1] \mid 0 [q_1, N, q_2] [q_2, N, q_1]$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

$$1) \quad \delta(q_1, 0, K) = \{(q_1, NK)\}$$

$$2) \quad \delta(q_1, 0, N) = \{(q_1, NN)\}$$

$$3) \quad \delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$4) \quad \delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$5) \quad \delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$$

$$6) \quad \delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$$

i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$

ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_1] \mid 0 [q_1, N, q_2] [q_2, K, q_1]$

iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$

iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_1] \mid 0 [q_1, N, q_2] [q_2, N, q_1]$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

$$1) \quad \delta(q_1, 0, K) = \{(q_1, NK)\}$$

$$2) \quad \delta(q_1, 0, N) = \{(q_1, NN)\}$$

$$3) \quad \delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$4) \quad \delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$5) \quad \delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$$

$$6) \quad \delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$$

$$i) \quad S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$$

$$ii) \quad [q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_1] \mid 0 [q_1, N, q_2] [q_2, K, q_1]$$

$$iii) \quad [q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$$

$$iv) \quad [q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_1] \mid 0 [q_1, N, q_2] [q_2, N, q_1]$$

$$[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_2] \mid 0 [q_1, N, q_2] [q_2, N, q_2]$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

- 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
- 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
- 3) $\delta(q_1, 1, N) = \{(q_2, \epsilon)\}$

- 4) $\delta(q_2, 1, N) = \{(q_2, \epsilon)\}$
- 5) $\delta(q_2, \epsilon, N) = \{(q_2, \epsilon)\}$
- 6) $\delta(q_2, \epsilon, K) = \{(q_2, \epsilon)\}$

- i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$
- ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_1] \mid 0 [q_1, N, q_2] [q_2, K, q_1]$
- iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$
- iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_1] \mid 0 [q_1, N, q_2] [q_2, N, q_1]$
 $[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_2] \mid 0 [q_1, N, q_2] [q_2, N, q_2]$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

- 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
- 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
- 3) $\delta(q_1, 1, N) = \{(q_2, \epsilon)\}$

- 4) $\delta(q_2, 1, N) = \{(q_2, \epsilon)\}$
- 5) $\delta(q_2, \epsilon, N) = \{(q_2, \epsilon)\}$
- 6) $\delta(q_2, \epsilon, K) = \{(q_2, \epsilon)\}$

- i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$
- ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_1] \mid 0 [q_1, N, q_2] [q_2, K, q_1]$
- iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$
- iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_1] \mid 0 [q_1, N, q_2] [q_2, N, q_1]$
 $[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_2] \mid 0 [q_1, N, q_2] [q_2, N, q_2]$
- v) $[q_1, N, q_2] \rightarrow 1$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{\})$

- 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
- 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
- 3) $\delta(q_1, 1, N) = \{(q_2, \epsilon)\}$

- 4) $\delta(q_2, 1, N) = \{(q_2, \epsilon)\}$
- 5) $\delta(q_2, \epsilon, N) = \{(q_2, \epsilon)\}$
- 6) $\delta(q_2, \epsilon, K) = \{(q_2, \epsilon)\}$

- i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$
- ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_1] \mid 0 [q_1, N, q_2] [q_2, K, q_1]$
- iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$
- iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_1] \mid 0 [q_1, N, q_2] [q_2, N, q_1]$
 $[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_2] \mid 0 [q_1, N, q_2] [q_2, N, q_2]$
- v) $[q_1, N, q_2] \rightarrow 1$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G=(V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

- | | |
|--|--|
| 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
3) $\delta(q_1, 1, N) = \{(q_2, \epsilon)\}$ | 4) $\delta(q_2, 1, N) = \{(q_2, \epsilon)\}$
5) $\delta(q_2, \epsilon, N) = \{(q_2, \epsilon)\}$
6) $\delta(q_2, \epsilon, K) = \{(q_2, \epsilon)\}$ |
|--|--|

- i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$
- ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_1] \mid 0 [q_1, N, q_2] [q_2, K, q_1]$
- iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$
- iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_1] \mid 0 [q_1, N, q_2] [q_2, N, q_1]$
 $[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_2] \mid 0 [q_1, N, q_2] [q_2, N, q_2]$
- v) $[q_1, N, q_2] \rightarrow 1$
 $[q_2, K, q_2] \rightarrow \epsilon$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

- | | |
|---|---|
| 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$ | 4) $\delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$ |
| 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$ | 5) $\delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$ |
| 3) $\delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$ | 6) $\delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$ |

- i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$
- ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_1] \mid 0 [q_1, N, q_2] [q_2, K, q_1]$
- iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$
- iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_1] \mid 0 [q_1, N, q_2] [q_2, N, q_1]$
 $[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_2] \mid 0 [q_1, N, q_2] [q_2, N, q_2]$
- v) $[q_1, N, q_2] \rightarrow 1$
 $[q_2, K, q_2] \rightarrow \varepsilon$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

- | | |
|---|---|
| 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$ | 4) $\delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$ |
| 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$ | 5) $\delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$ |
| 3) $\delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$ | 6) $\delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$ |

- i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$
- ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_1] \mid 0 [q_1, N, q_2] [q_2, K, q_1]$
- iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$
- iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_1] \mid 0 [q_1, N, q_2] [q_2, N, q_1]$
 $[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_2] \mid 0 [q_1, N, q_2] [q_2, N, q_2]$
- v) $[q_1, N, q_2] \rightarrow 1$
 $[q_2, K, q_2] \rightarrow \varepsilon$
 $[q_2, N, q_2] \rightarrow \varepsilon$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

- 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
- 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
- 3) $\delta(q_1, 1, N) = \{(q_2, \epsilon)\}$

- 4) $\delta(q_2, 1, N) = \{(q_2, \epsilon)\}$
- 5) $\delta(q_2, \epsilon, N) = \{(q_2, \epsilon)\}$
- 6) $\delta(q_2, \epsilon, K) = \{(q_2, \epsilon)\}$

- i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$
- ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_1] \mid 0 [q_1, N, q_2] [q_2, K, q_1]$
- iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$
- iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_1] \mid 0 [q_1, N, q_2] [q_2, N, q_1]$
 $[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_2] \mid 0 [q_1, N, q_2] [q_2, N, q_2]$
- v) $[q_1, N, q_2] \rightarrow 1$
 $[q_2, K, q_2] \rightarrow \epsilon$
 $[q_2, N, q_2] \rightarrow \epsilon$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

- 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
- 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
- 3) $\delta(q_1, 1, N) = \{(q_2, \epsilon)\}$

- 4) $\delta(q_2, 1, N) = \{(q_2, \epsilon)\}$
- 5) $\delta(q_2, \epsilon, N) = \{(q_2, \epsilon)\}$
- 6) $\delta(q_2, \epsilon, K) = \{(q_2, \epsilon)\}$

- i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$
- ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_1] \mid 0 [q_1, N, q_2] [q_2, K, q_1]$
- iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$
- iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_1] \mid 0 [q_1, N, q_2] [q_2, N, q_1]$
 $[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_2] \mid 0 [q_1, N, q_2] [q_2, N, q_2]$
- v) $[q_1, N, q_2] \rightarrow 1$
 $[q_2, K, q_2] \rightarrow \epsilon$
 $[q_2, N, q_2] \rightarrow \epsilon$
 $[q_2, N, q_2] \rightarrow 1$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

- 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
- 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
- 3) $\delta(q_1, 1, N) = \{(q_2, \epsilon)\}$

- 4) $\delta(q_2, 1, N) = \{(q_2, \epsilon)\}$
- 5) $\delta(q_2, \epsilon, N) = \{(q_2, \epsilon)\}$
- 6) $\delta(q_2, \epsilon, K) = \{(q_2, \epsilon)\}$

- i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$
- ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] \mid [q_1, K, q_1] \mid 0 [q_1, N, q_2] \mid [q_2, K, q_1]$
- iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] \mid [q_1, K, q_2] \mid 0 [q_1, N, q_2] \mid [q_2, K, q_2]$
- iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] \mid [q_1, N, q_1] \mid 0 [q_1, N, q_2] \mid [q_2, N, q_1]$
 $[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] \mid [q_1, N, q_2] \mid 0 [q_1, N, q_2] \mid [q_2, N, q_2]$
- v) $[q_1, N, q_2] \rightarrow 1$
 $[q_2, K, q_2] \rightarrow \epsilon$
 $[q_2, N, q_2] \rightarrow \epsilon$
 $[q_2, N, q_2] \rightarrow 1$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{\})$

- 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
- 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
- 3) $\delta(q_1, 1, N) = \{(q_2, \epsilon)\}$

- 4) $\delta(q_2, 1, N) = \{(q_2, \epsilon)\}$
- 5) $\delta(q_2, \epsilon, N) = \{(q_2, \epsilon)\}$
- 6) $\delta(q_2, \epsilon, K) = \{(q_2, \epsilon)\}$

- i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$
- ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] \mid [q_1, K, q_1] \mid 0 [q_1, N, q_2] \mid [q_2, K, q_1]$
- iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] \mid [q_1, K, q_2] \mid 0 [q_1, N, q_2] \mid [q_2, K, q_2]$
- iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] \mid [q_1, N, q_1] \mid 0 [q_1, N, q_2] \mid [q_2, N, q_1]$
 $[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] \mid [q_1, N, q_2] \mid 0 [q_1, N, q_2] \mid [q_2, N, q_2]$
- v) $[q_1, N, q_2] \rightarrow 1$
 $[q_2, K, q_2] \rightarrow \epsilon$
 $[q_2, N, q_2] \rightarrow \epsilon$
 $[q_2, N, q_2] \rightarrow 1$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{\})$

- 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
- 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
- 3) $\delta(q_1, 1, N) = \{(q_2, \epsilon)\}$

- 4) $\delta(q_2, 1, N) = \{(q_2, \epsilon)\}$
- 5) $\delta(q_2, \epsilon, N) = \{(q_2, \epsilon)\}$
- 6) $\delta(q_2, \epsilon, K) = \{(q_2, \epsilon)\}$

- i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$
- ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] \mid [q_1, K, q_1] \mid 0 [q_1, N, q_2] \mid [q_2, K, q_1]$
- iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] \mid [q_1, K, q_2] \mid 0 [q_1, N, q_2] \mid [q_2, K, q_2]$
- iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] \mid [q_1, N, q_1] \mid 0 [q_1, N, q_2] \mid [q_2, N, q_1]$
 $[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] \mid [q_1, N, q_2] \mid 0 [q_1, N, q_2] \mid [q_2, N, q_2]$
- v) $[q_1, N, q_2] \rightarrow 1$
 $[q_2, K, q_2] \rightarrow \epsilon$
 $[q_2, N, q_2] \rightarrow \epsilon$
 $[q_2, N, q_2] \rightarrow 1$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

- 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
- 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
- 3) $\delta(q_1, 1, N) = \{(q_2, \epsilon)\}$

- 4) $\delta(q_2, 1, N) = \{(q_2, \epsilon)\}$
- 5) $\delta(q_2, \epsilon, N) = \{(q_2, \epsilon)\}$
- 6) $\delta(q_2, \epsilon, K) = \{(q_2, \epsilon)\}$

- i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$
- ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] \mid [q_1, K, q_1] \mid 0 [q_1, N, q_2] \mid [q_2, K, q_1]$
- iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] \mid [q_1, K, q_2] \mid 0 [q_1, N, q_2] \mid [q_2, K, q_2]$
- iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] \mid [q_1, N, q_1] \mid 0 [q_1, N, q_2] \mid [q_2, N, q_1]$
 $[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] \mid [q_1, N, q_2] \mid 0 [q_1, N, q_2] \mid [q_2, N, q_2]$
- v) $[q_1, N, q_2] \rightarrow 1$
 $[q_2, K, q_2] \rightarrow \epsilon$
 $[q_2, N, q_2] \rightarrow \epsilon$
 $[q_2, N, q_2] \rightarrow 1$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{\})$

- 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
- 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
- 3) $\delta(q_1, 1, N) = \{(q_2, \epsilon)\}$

- 4) $\delta(q_2, 1, N) = \{(q_2, \epsilon)\}$
- 5) $\delta(q_2, \epsilon, N) = \{(q_2, \epsilon)\}$
- 6) $\delta(q_2, \epsilon, K) = \{(q_2, \epsilon)\}$

- i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$
- ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] \mid [q_1, K, q_1] \mid 0 [q_1, N, q_2] \mid [q_2, K, q_1]$
- iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] \mid [q_1, K, q_2] \mid 0 [q_1, N, q_2] \mid [q_2, K, q_2]$
- iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] \mid [q_1, N, q_1] \mid 0 [q_1, N, q_2] \mid [q_2, N, q_1]$
 $[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] \mid [q_1, N, q_2] \mid 0 [q_1, N, q_2] \mid [q_2, N, q_2]$
- v) $[q_1, N, q_2] \rightarrow 1$
 $[q_2, K, q_2] \rightarrow \epsilon$
 $[q_2, N, q_2] \rightarrow \epsilon$
 $[q_2, N, q_2] \rightarrow 1$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{\})$

- 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
- 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
- 3) $\delta(q_1, 1, N) = \{(q_2, \epsilon)\}$

- 4) $\delta(q_2, 1, N) = \{(q_2, \epsilon)\}$
- 5) $\delta(q_2, \epsilon, N) = \{(q_2, \epsilon)\}$
- 6) $\delta(q_2, \epsilon, K) = \{(q_2, \epsilon)\}$

- i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$
- ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] \mid [q_1, K, q_1] \mid 0 [q_1, N, q_2] \mid [q_2, K, q_1]$
- iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] \mid [q_1, K, q_2] \mid 0 [q_1, N, q_2] \mid [q_2, K, q_2]$
- iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] \mid [q_1, N, q_1] \mid 0 [q_1, N, q_2] \mid [q_2, N, q_1]$
 $[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] \mid [q_1, N, q_2] \mid 0 [q_1, N, q_2] \mid [q_2, N, q_2]$
- v) $[q_1, N, q_2] \rightarrow 1$
 $[q_2, K, q_2] \rightarrow \epsilon$
 $[q_2, N, q_2] \rightarrow \epsilon$
 $[q_2, N, q_2] \rightarrow 1$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{\})$

- 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
- 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
- 3) $\delta(q_1, 1, N) = \{(q_2, \epsilon)\}$

- 4) $\delta(q_2, 1, N) = \{(q_2, \epsilon)\}$
- 5) $\delta(q_2, \epsilon, N) = \{(q_2, \epsilon)\}$
- 6) $\delta(q_2, \epsilon, K) = \{(q_2, \epsilon)\}$

- i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$
- ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] \mid [q_1, K, q_1] \mid 0 [q_1, N, q_2] \mid [q_2, K, q_1]$
- iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] \mid [q_1, K, q_2] \mid 0 [q_1, N, q_2] \mid [q_2, K, q_2]$
- iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] \mid [q_1, N, q_2] \mid 0 [q_1, N, q_2] \mid [q_2, N, q_1]$
 $[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] \mid [q_1, N, q_2] \mid 0 [q_1, N, q_2] \mid [q_2, N, q_2]$
- v) $[q_1, N, q_2] \rightarrow 1$
 $[q_2, K, q_2] \rightarrow \epsilon$
 $[q_2, N, q_2] \rightarrow \epsilon$
 $[q_2, N, q_2] \rightarrow 1$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

- 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
- 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
- 3) $\delta(q_1, 1, N) = \{(q_2, \epsilon)\}$

- 4) $\delta(q_2, 1, N) = \{(q_2, \epsilon)\}$
- 5) $\delta(q_2, \epsilon, N) = \{(q_2, \epsilon)\}$
- 6) $\delta(q_2, \epsilon, K) = \{(q_2, \epsilon)\}$

- i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$
- ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] \mid [q_1, K, q_1] \mid 0 [q_1, N, q_2] \mid [q_2, K, q_1]$
- iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] \mid [q_1, K, q_2] \mid 0 [q_1, N, q_2] \mid [q_2, K, q_2]$
- iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] \mid [q_1, N, q_2] \mid 0 [q_1, N, q_2] \mid [q_2, N, q_1]$
 $[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] \mid [q_1, N, q_2] \mid 0 [q_1, N, q_2] \mid [q_2, N, q_2]$
- v) $[q_1, N, q_2] \rightarrow 1$
 $[q_2, K, q_2] \rightarrow \epsilon$
 $[q_2, N, q_2] \rightarrow \epsilon$
 $[q_2, N, q_2] \rightarrow 1$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

- 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
- 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
- 3) $\delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$

- 4) $\delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$
- 5) $\delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$
- 6) $\delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$

- i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$
- ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_1]$
- iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$
- iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_1]$
 $[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_2] \mid 0 [q_1, N, q_2] [q_2, N, q_2]$
- v) $[q_1, N, q_2] \rightarrow 1$
 $[q_2, K, q_2] \rightarrow \varepsilon$
 $[q_2, N, q_2] \rightarrow \varepsilon$
 $[q_2, N, q_2] \rightarrow 1$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

- 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
- 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
- 3) $\delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$

- 4) $\delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$
- 5) $\delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$
- 6) $\delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$

- i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$
- ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_1]$
- iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$
- iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_1]$
 $[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_2] \mid 0 [q_1, N, q_2] [q_2, N, q_2]$
- v) $[q_1, N, q_2] \rightarrow 1$
 $[q_2, K, q_2] \rightarrow \varepsilon$
 $[q_2, N, q_2] \rightarrow \varepsilon$
 $[q_2, N, q_2] \rightarrow 1$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

- 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
- 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
- 3) $\delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$

- 4) $\delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$
- 5) $\delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$
- 6) $\delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$

- i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$
- ii) $[q_1, K, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_1]$
- iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$
- iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_1]$
 $[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_2] \mid 0 [q_1, N, q_2] [q_2, N, q_2]$
- v) $[q_1, N, q_2] \rightarrow 1$
 $[q_2, K, q_2] \rightarrow \varepsilon$
 $[q_2, N, q_2] \rightarrow \varepsilon$
 $[q_2, N, q_2] \rightarrow 1$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

- | | |
|---|---|
| 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$ | 4) $\delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$ |
| 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$ | 5) $\delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$ |
| 3) $\delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$ | 6) $\delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$ |

i) $S \rightarrow [q_1, K, q_1] \mid [q_1, K, q_2]$

iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$

iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_1]$

$[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_2] \mid 0 [q_1, N, q_2] [q_2, N, q_2]$

v) $[q_1, N, q_2] \rightarrow 1$

$[q_2, K, q_2] \rightarrow \varepsilon$

$[q_2, N, q_2] \rightarrow \varepsilon$

$[q_2, N, q_2] \rightarrow 1$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

- 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
- 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
- 3) $\delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$

- 4) $\delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$
- 5) $\delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$
- 6) $\delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$

i) $S \rightarrow [q_1, K, q_2]$

iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$

iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_1]$

$[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_2] \mid 0 [q_1, N, q_2] [q_2, N, q_2]$

v) $[q_1, N, q_2] \rightarrow 1$

$[q_2, K, q_2] \rightarrow \varepsilon$

$[q_2, N, q_2] \rightarrow \varepsilon$

$[q_2, N, q_2] \rightarrow 1$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

- 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
- 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
- 3) $\delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$

- 4) $\delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$
- 5) $\delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$
- 6) $\delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$

i) $S \rightarrow [q_1, K, q_2]$

iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$

iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_1]$

$[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_2] \mid 0 [q_1, N, q_2] [q_2, N, q_2]$

v) $[q_1, N, q_2] \rightarrow 1$

$[q_2, K, q_2] \rightarrow \varepsilon$

$[q_2, N, q_2] \rightarrow \varepsilon$

$[q_2, N, q_2] \rightarrow 1$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

- 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
- 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
- 3) $\delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$

- 4) $\delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$
- 5) $\delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$
- 6) $\delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$

i) $S \rightarrow [q_1, K, q_2]$

iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$

iv) $[q_1, N, q_1] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_1]$

$[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_2] \mid 0 [q_1, N, q_2] [q_2, N, q_2]$

v) $[q_1, N, q_2] \rightarrow 1$

$[q_2, K, q_2] \rightarrow \varepsilon$

$[q_2, N, q_2] \rightarrow \varepsilon$

$[q_2, N, q_2] \rightarrow 1$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

- 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
- 2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
- 3) $\delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$

- 4) $\delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$
- 5) $\delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$
- 6) $\delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$

i) $S \rightarrow [q_1, K, q_2]$

iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, K, q_2] \mid 0 [q_1, N, q_2] [q_2, K, q_2]$

$[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_2] \mid 0 [q_1, N, q_2] [q_2, N, q_2]$

v) $[q_1, N, q_2] \rightarrow 1$

$[q_2, K, q_2] \rightarrow \varepsilon$

$[q_2, N, q_2] \rightarrow \varepsilon$

$[q_2, N, q_2] \rightarrow 1$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

- | | |
|---|---|
| 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
3) $\delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$ | 4) $\delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$
5) $\delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$
6) $\delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$ |
|---|---|

i) $S \rightarrow [q_1, K, q_2]$

iii) $[q_1, K, q_2] \rightarrow 0 [q_1, N, q_2] [q_2, K, q_2]$

$[q_1, N, q_2] \rightarrow 0 [q_1, N, q_1] [q_1, N, q_2] \mid 0 [q_1, N, q_2] [q_2, N, q_2]$

v) $[q_1, N, q_2] \rightarrow 1$

$[q_2, K, q_2] \rightarrow \varepsilon$

$[q_2, N, q_2] \rightarrow \varepsilon$

$[q_2, N, q_2] \rightarrow 1$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

- | | |
|---|---|
| 1) $\delta(q_1, 0, K) = \{(q_1, NK)\}$
2) $\delta(q_1, 0, N) = \{(q_1, NN)\}$
3) $\delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$ | 4) $\delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$
5) $\delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$
6) $\delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$ |
|---|---|

i) $S \rightarrow$

$[q_1, K, q_2]$

iii) $[q_1, K, q_2] \rightarrow$

0 $[q_1, N, q_2] [q_2, K, q_2]$

$[q_1, N, q_2] \rightarrow$

0 $[q_1, N, q_2] [q_2, N, q_2]$

v) $[q_1, N, q_2] \rightarrow 1$

$[q_2, K, q_2] \rightarrow \varepsilon$

$[q_2, N, q_2] \rightarrow \varepsilon$

$[q_2, N, q_2] \rightarrow 1$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

$$1) \quad \delta(q_1, 0, K) = \{(q_1, NK)\}$$

$$2) \quad \delta(q_1, 0, N) = \{(q_1, NN)\}$$

$$3) \quad \delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$4) \quad \delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$5) \quad \delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$$

$$6) \quad \delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$$

$$S \rightarrow [q_1, K, q_2]$$

$$[q_1, K, q_2] \rightarrow 0 [q_1, N, q_2] [q_2, K, q_2]$$

$$[q_1, N, q_2] \rightarrow 0 [q_1, N, q_2] [q_2, N, q_2]$$

$$[q_1, N, q_2] \rightarrow 1$$

$$[q_2, K, q_2] \rightarrow \varepsilon$$

$$[q_2, N, q_2] \rightarrow \varepsilon$$

$$[q_2, N, q_2] \rightarrow 1$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{ \})$

$$1) \quad \delta(q_1, 0, K) = \{(q_1, NK)\}$$

$$2) \quad \delta(q_1, 0, N) = \{(q_1, NN)\}$$

$$3) \quad \delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$4) \quad \delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$5) \quad \delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$$

$$6) \quad \delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$$

$$S \rightarrow [q_1, K, q_2]$$

$$[q_1, K, q_2] \rightarrow 0 [q_1, N, q_2] [q_2, K, q_2]$$

$$[q_1, N, q_2] \rightarrow 0 [q_1, N, q_2] [q_2, N, q_2]$$

$$[q_1, N, q_2] \rightarrow 1$$

$$[q_2, K, q_2] \rightarrow \varepsilon$$

$$[q_2, N, q_2] \rightarrow \varepsilon$$

$$[q_2, N, q_2] \rightarrow 1$$

$$(q_1, 00011, K) \succ (q_1, 0011, NK) \succ (q_1, 011, NNK) \succ (q_1, 11, NNNK) \succ$$

$$(q_2, 1, NNNK) \succ (q_2, \varepsilon, NK) \succ (q_2, \varepsilon, K) \succ (q_2, \varepsilon, \varepsilon)$$

Constructing a Context-Free Grammar Given a PA That Accepts By Empty Stack

$G = (V, \{0, 1\}, P, S)$

PA $M = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta, q_1, K, \{\})$

$$1) \quad \delta(q_1, 0, K) = \{(q_1, NK)\}$$

$$2) \quad \delta(q_1, 0, N) = \{(q_1, NN)\}$$

$$3) \quad \delta(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$4) \quad \delta(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$5) \quad \delta(q_2, \varepsilon, N) = \{(q_2, \varepsilon)\}$$

$$6) \quad \delta(q_2, \varepsilon, K) = \{(q_2, \varepsilon)\}$$

$$S \rightarrow [q_1, K, q_2]$$

$$[q_1, K, q_2] \rightarrow 0 [q_1, N, q_2] [q_2, K, q_2]$$

$$[q_1, N, q_2] \rightarrow 0 [q_1, N, q_2] [q_2, N, q_2]$$

$$[q_1, N, q_2] \rightarrow 1$$

$$[q_2, K, q_2] \rightarrow \varepsilon$$

$$[q_2, N, q_2] \rightarrow \varepsilon$$

$$[q_2, N, q_2] \rightarrow 1$$

$$(q_1, 00011, K) \succ (q_1, 0011, NK) \succ (q_1, 011, NNK) \succ (q_1, 11, NNNK) \succ$$

$$(q_2, 1, NNNK) \succ (q_2, \varepsilon, NK) \succ (q_2, \varepsilon, K) \succ (q_2, \varepsilon, \varepsilon)$$

$$S \Rightarrow [q_1, K, q_2] \Rightarrow 0[q_1, N, q_2][q_2, K, q_2] \Rightarrow 00[q_1, N, q_2][q_2, N, q_2][q_2, K, q_2] \Rightarrow$$

$$000[q_1, N, q_2][q_2, N, q_2][q_2, N, q_2][q_2, K, q_2] \Rightarrow 0001[q_2, N, q_2][q_2, N, q_2][q_2, K, q_2] \Rightarrow$$

$$00011[q_2, N, q_2][q_2, K, q_2] \Rightarrow 00011\varepsilon[q_2, K, q_2] \Rightarrow 00011\varepsilon\varepsilon \Rightarrow 00011$$

Lecture 10

3.2.3 PA and Context-free Grammar

3.3 PROPERTIES OF CONTEXT-FREE LANGUAGES

3.3.1 Closure Properties of Context-Free Languages

3.3.2 Pumping Lemma

Properties of Context-Free Languages

Properties of Context-Free Languages

Languages that are not context-free

Properties of Context-Free Languages

Languages that are not context-free

It is not possible to define them using a context-free grammar

Properties of Context-Free Languages

Languages that are not context-free

It is not possible to define them using a context-free grammar

$$L = \{ a^i b^i c^i \mid i \geq 1 \}$$

Properties of Context-Free Languages

Languages that are not context-free

It is not possible to define them using a context-free grammar

$$L = \{ a^i b^i c^i \mid i \geq 1 \}$$

2^{Σ^*} set of all languages
given an input symbol set Σ

Properties of Context-Free Languages

Languages that are not context-free

It is not possible to define them using a context-free grammar

$$L = \{ a^i b^i c^i \mid i \geq 1 \}$$

2^{Σ^*} set of all languages
given an input symbol set Σ

Context-free languages
 $KNJ \subset 2^{\Sigma^*}$

Properties of Context-Free Languages

Languages that are not context-free

It is not possible to define them using a context-free grammar

$$L = \{ a^i b^i c^i \mid i \geq 1 \}$$

2^{Σ^*} set of all languages
given an input symbol set Σ

Context-free languages
 $KNJ \subset 2^{\Sigma^*}$

$G = (V, T, P, S)$

Properties of Context-Free Languages

Properties of Context-Free Languages

Finite automata

Properties of Context-Free Languages

Finite automata

Regular languages: REG

Properties of Context-Free Languages

Deterministic pushdown automata

Finite automata

Regular languages: REG

Properties of Context-Free Languages

Deterministic pushdown automata

Finite automata

Deterministic context-free languages : DCFL

Language $L_3: \{ w2w^R \mid w \in (0+1)^* \text{ i } |w| > 1 \}$
 $L_3 \in DKNJ \text{ i } L_3 \notin REG$

Regular languages: REG

Properties of Context-Free Languages

Nondeterministic pushdown automata

Deterministic pushdown automata

Finite automata

Deterministic context-free languages : DCFL

Language $L_3: \{ w2w^R \mid w \in (0+1)^* \text{ i } |w| > 1 \}$
 $L_3 \in DKNJ \text{ i } L_3 \notin REG$

Regular languages: REG

Properties of Context-Free Languages

Nondeterministic pushdown automata

Deterministic pushdown automata

Finite automata

Nondeterministic context-free languages: NCFL

Language $L_2: \{ ww^R \mid w \in (0+1)^* \text{ i } |w| > 1 \}$
 $L_2 \in NKNJ \text{ i } L_2 \notin DKNJ$

Deterministic context-free languages : DCFL

Language $L_3: \{ w2w^R \mid w \in (0+1)^* \text{ i } |w| > 1 \}$
 $L_3 \in DKNJ \text{ i } L_3 \notin REG$

Regular languages: REG

Properties of Context-Free Languages

Properties of Context-Free Languages

- Union

Properties of Context-Free Languages

- **Union**

- $G_1 = (V_1, T_1, P_1, S_1)$, $G_2 = (V_2, T_2, P_2, S_2)$

Properties of Context-Free Languages

- **Union**

- $G_1 = (V_1, T_1, P_1, S_1)$, $G_2 = (V_2, T_2, P_2, S_2)$
- $V_1 \cap V_2 = \emptyset$

Properties of Context-Free Languages

- Union
 - $G_1 = (V_1, T_1, P_1, S_1)$, $G_2 = (V_2, T_2, P_2, S_2)$
 - $V_1 \cap V_2 = \emptyset$
- $L(G_3) = L(G_1) \cup L(G_2)$

Properties of Context-Free Languages

- **Union**
 - $G_1 = (V_1, T_1, P_1, S_1)$, $G_2 = (V_2, T_2, P_2, S_2)$
 - $V_1 \cap V_2 = \emptyset$
 - $L(G_3) = L(G_1) \cup L(G_2)$
 - $G_3 = (V_3, T_3, P_3, S_3)$
-

Properties of Context-Free Languages

- Union
 - $G_1 = (V_1, T_1, P_1, S_1)$, $G_2 = (V_2, T_2, P_2, S_2)$
 - $V_1 \cap V_2 = \emptyset$
 - $L(G_3) = L(G_1) \cup L(G_2)$
 - $G_3 = (V_3, T_3, P_3, S_3)$
-

Constructing the grammar G_3

Properties of Context-Free Languages

- **Union**

- $G_1 = (V_1, T_1, P_1, S_1)$, $G_2 = (V_2, T_2, P_2, S_2)$
 - $V_1 \cap V_2 = \emptyset$
 - $L(G_3) = L(G_1) \cup L(G_2)$
 - $G_3 = (V_3, T_3, P_3, S_3)$
-

Constructing the grammar G_3

$$1) \quad V_3 = V_1 \cup V_2 \cup \{S_3\}, \quad S_3 \notin V_1 \text{ i } S_3 \notin V_2$$

Properties of Context-Free Languages

- Union
 - $G_1 = (V_1, T_1, P_1, S_1)$, $G_2 = (V_2, T_2, P_2, S_2)$
 - $V_1 \cap V_2 = \emptyset$
 - $L(G_3) = L(G_1) \cup L(G_2)$
 - $G_3 = (V_3, T_3, P_3, S_3)$
-

Constructing the grammar G_3

- 1) $V_3 = V_1 \cup V_2 \cup \{S_3\}$, $S_3 \notin V_1 \cup V_2$
- 2) $T_3 = T_1 \cup T_2$

Properties of Context-Free Languages

- **Union**

- $G_1 = (V_1, T_1, P_1, S_1)$, $G_2 = (V_2, T_2, P_2, S_2)$
 - $V_1 \cap V_2 = \emptyset$
 - $L(G_3) = L(G_1) \cup L(G_2)$
 - $G_3 = (V_3, T_3, P_3, S_3)$
-

Constructing the grammar G_3

- 1) $V_3 = V_1 \cup V_2 \cup \{S_3\}$, $S_3 \notin V_1 \cup V_2$
- 2) $T_3 = T_1 \cup T_2$
- 3) $P_3 = P_1 \cup P_2 \cup \{S_3 \rightarrow S_1 \mid S_2\}$

Properties of Context-Free Languages

Properties of Context-Free Languages

Proof $L(G_3) = L(G_1) \cup L(G_2)$

Properties of Context-Free Languages

Proof $L(G_3) = L(G_1) \cup L(G_2)$

1) **Proof** $(L(G_1) \cup L(G_2)) \subseteq L(G_3)$

Properties of Context-Free Languages

Proof $L(G_3) = L(G_1) \cup L(G_2)$

1) **Proof** $(L(G_1) \cup L(G_2)) \subseteq L(G_3)$

2) **Proof** $L(G_3) \subseteq (L(G_1) \cup L(G_2))$

Properties of Context-Free Languages

Proof $L(G_3) = L(G_1) \cup L(G_2)$

1) **Proof** $(L(G_1) \cup L(G_2)) \subseteq L(G_3)$

(a)

2) **Proof** $L(G_3) \subseteq (L(G_1) \cup L(G_2))$

Properties of Context-Free Languages

Proof $L(G_3) = L(G_1) \cup L(G_2)$

1) **Proof** $(L(G_1) \cup L(G_2)) \subseteq L(G_3)$

(a) S_3

2) **Proof** $L(G_3) \subseteq (L(G_1) \cup L(G_2))$

Properties of Context-Free Languages

Proof $L(G_3) = L(G_1) \cup L(G_2)$

1) **Proof** $(L(G_1) \cup L(G_2)) \subseteq L(G_3)$

$$(a) \quad S_3 \Rightarrow G_3$$

2) **Proof** $L(G_3) \subseteq (L(G_1) \cup L(G_2))$

Properties of Context-Free Languages

Proof $L(G_3) = L(G_1) \cup L(G_2)$

1) **Proof** $(L(G_1) \cup L(G_2)) \subseteq L(G_3)$

$$(a) \quad S_3 \xrightarrow[G_3]{} S_1$$

2) **Proof** $L(G_3) \subseteq (L(G_1) \cup L(G_2))$

Properties of Context-Free Languages

Proof $L(G_3) = L(G_1) \cup L(G_2)$

1) **Proof** $(L(G_1) \cup L(G_2)) \subseteq L(G_3)$

$$(a) \quad S_3 \xrightarrow[G_3]{} S_1 \xrightarrow[G_1]{*} \quad$$

2) **Proof** $L(G_3) \subseteq (L(G_1) \cup L(G_2))$

Properties of Context-Free Languages

Proof $L(G_3) = L(G_1) \cup L(G_2)$

1) **Proof** $(L(G_1) \cup L(G_2)) \subseteq L(G_3)$

$$(a) \quad S_3 \xrightarrow[G_3]{} S_1 \xrightarrow[G_1]^* w$$

2) **Proof** $L(G_3) \subseteq (L(G_1) \cup L(G_2))$

Properties of Context-Free Languages

Proof $L(G_3) = L(G_1) \cup L(G_2)$

1) **Proof** $(L(G_1) \cup L(G_2)) \subseteq L(G_3)$

$$(a) \quad S_3 \xrightarrow[G_3]{} S_1 \xrightarrow[G_1]^* w$$

(b)

2) **Proof** $L(G_3) \subseteq (L(G_1) \cup L(G_2))$

Properties of Context-Free Languages

Proof $L(G_3) = L(G_1) \cup L(G_2)$

1) **Proof** $(L(G_1) \cup L(G_2)) \subseteq L(G_3)$

$$(a) \quad S_3 \xrightarrow[G_3]{} S_1 \xrightarrow[G_1]^* w$$

$$(b) \quad S_3$$

2) **Proof** $L(G_3) \subseteq (L(G_1) \cup L(G_2))$

Properties of Context-Free Languages

Proof $L(G_3) = L(G_1) \cup L(G_2)$

1) **Proof** $(L(G_1) \cup L(G_2)) \subseteq L(G_3)$

$$(a) \quad S_3 \xrightarrow[G_3]{} S_1 \xrightarrow[G_1]^* w$$

$$(b) \quad S_3 \xrightarrow[G_3]{} \quad$$

2) **Proof** $L(G_3) \subseteq (L(G_1) \cup L(G_2))$

Properties of Context-Free Languages

Proof $L(G_3) = L(G_1) \cup L(G_2)$

1) **Proof** $(L(G_1) \cup L(G_2)) \subseteq L(G_3)$

$$(a) \quad S_3 \xrightarrow[G_3]{} S_1 \xrightarrow[G_1]^* w$$

$$(b) \quad S_3 \xrightarrow[G_3]{} S_2$$

2) **Proof** $L(G_3) \subseteq (L(G_1) \cup L(G_2))$

Properties of Context-Free Languages

Proof $L(G_3) = L(G_1) \cup L(G_2)$

1) **Proof** $(L(G_1) \cup L(G_2)) \subseteq L(G_3)$

$$(a) \quad S_3 \xrightarrow[G_3]{} S_1 \xrightarrow[G_1]^* w$$

$$(b) \quad S_3 \xrightarrow[G_3]{} S_2 \xrightarrow[G_2]^*$$

2) **Proof** $L(G_3) \subseteq (L(G_1) \cup L(G_2))$

Properties of Context-Free Languages

Proof $L(G_3) = L(G_1) \cup L(G_2)$

1) **Proof** $(L(G_1) \cup L(G_2)) \subseteq L(G_3)$

$$(a) \quad S_3 \xrightarrow[G_3]{} S_1 \xrightarrow[G_1]{*} w$$

$$(b) \quad S_3 \xrightarrow[G_3]{} S_2 \xrightarrow[G_2]{*} w$$

2) **Proof** $L(G_3) \subseteq (L(G_1) \cup L(G_2))$

Properties of Context-Free Languages

Proof $L(G_3) = L(G_1) \cup L(G_2)$

1) **Proof** $(L(G_1) \cup L(G_2)) \subseteq L(G_3)$

$$(a) \quad S_3 \xrightarrow[G_3]{} S_1 \xrightarrow[G_1]^* w$$

$$(b) \quad S_3 \xrightarrow[G_3]{} S_2 \xrightarrow[G_2]^* w$$

2) **Proof** $L(G_3) \subseteq (L(G_1) \cup L(G_2))$

$$V_1 \cap V_2 = \emptyset$$

Properties of Context-Free Languages

Proof $L(G_3) = L(G_1) \cup L(G_2)$

1) **Proof** $(L(G_1) \cup L(G_2)) \subseteq L(G_3)$

$$(a) \quad S_3 \xrightarrow[G_3]{} S_1 \xrightarrow[G_1]^* w$$

$$(b) \quad S_3 \xrightarrow[G_3]{} S_2 \xrightarrow[G_2]^* w$$

2) **Proof** $L(G_3) \subseteq (L(G_1) \cup L(G_2))$

$$V_1 \cap V_2 = \emptyset$$

In step (a) only the productions of grammar G_1 are used

Properties of Context-Free Languages

Proof $L(G_3) = L(G_1) \cup L(G_2)$

1) **Proof** $(L(G_1) \cup L(G_2)) \subseteq L(G_3)$

$$(a) \quad S_3 \xrightarrow[G_3]{} S_1 \xrightarrow[G_1]{*} w$$

$$(b) \quad S_3 \xrightarrow[G_3]{} S_2 \xrightarrow[G_2]{*} w$$

2) **Proof** $L(G_3) \subseteq (L(G_1) \cup L(G_2))$

$$V_1 \cap V_2 = \emptyset$$

In step (a) only the productions of grammar G_1 are used

In step (b) only the productions of grammar G_2 are used

Properties of Context-Free Languages

Properties of Context-Free Languages

- Concatenation

Properties of Context-Free Languages

- **Concatenation**

- $G_1 = (V_1, T_1, P_1, S_1)$, $G_2 = (V_2, T_2, P_2, S_2)$

Properties of Context-Free Languages

- **Concatenation**

- $G_1 = (V_1, T_1, P_1, S_1)$, $G_2 = (V_2, T_2, P_2, S_2)$
- $V_1 \cap V_2 = \emptyset$

Properties of Context-Free Languages

- **Concatenation**
 - $G_1 = (V_1, T_1, P_1, S_1)$, $G_2 = (V_2, T_2, P_2, S_2)$
 - $V_1 \cap V_2 = \emptyset$
- $L(G_4) = L(G_1) L(G_2)$

Properties of Context-Free Languages

- **Concatenation**
 - $G_1 = (V_1, T_1, P_1, S_1)$, $G_2 = (V_2, T_2, P_2, S_2)$
 - $V_1 \cap V_2 = \emptyset$
- $L(G_4) = L(G_1) L(G_2)$
 - $G_4 = (V_4, T_4, P_4, S_4)$

Properties of Context-Free Languages

- **Concatenation**

- $G_1 = (V_1, T_1, P_1, S_1)$, $G_2 = (V_2, T_2, P_2, S_2)$
- $V_1 \cap V_2 = \emptyset$
- $L(G_4) = L(G_1) L(G_2)$
- $G_4 = (V_4, T_4, P_4, S_4)$

$$1) \quad V_4 = V_1 \cup V_2 \cup \{S_4\}, S_4 \notin V_1 \text{ i } S_4 \notin V_2$$

Properties of Context-Free Languages

- **Concatenation**

- $G_1 = (V_1, T_1, P_1, S_1)$, $G_2 = (V_2, T_2, P_2, S_2)$
- $V_1 \cap V_2 = \emptyset$
- $L(G_4) = L(G_1) L(G_2)$
- $G_4 = (V_4, T_4, P_4, S_4)$

$$1) \quad V_4 = V_1 \cup V_2 \cup \{S_4\}, S_4 \notin V_1 \text{ i } S_4 \notin V_2$$

$$2) \quad T_4 = T_1 \cup T_2$$

Properties of Context-Free Languages

- **Concatenation**

- $G_1 = (V_1, T_1, P_1, S_1)$, $G_2 = (V_2, T_2, P_2, S_2)$
- $V_1 \cap V_2 = \emptyset$
- $L(G_4) = L(G_1) L(G_2)$
- $G_4 = (V_4, T_4, P_4, S_4)$

$$1) \quad V_4 = V_1 \cup V_2 \cup \{S_4\}, S_4 \notin V_1 \text{ i } S_4 \notin V_2$$

$$2) \quad T_4 = T_1 \cup T_2$$

$$3) \quad P_4 = P_1 \cup P_2 \cup \{S_4 \rightarrow S_1 S_2\}$$

Properties of Context-Free Languages

- **Concatenation**

- $G_1 = (V_1, T_1, P_1, S_1)$, $G_2 = (V_2, T_2, P_2, S_2)$
- $V_1 \cap V_2 = \emptyset$
- $L(G_4) = L(G_1) L(G_2)$
- $G_4 = (V_4, T_4, P_4, S_4)$

$$1) \quad V_4 = V_1 \cup V_2 \cup \{S_4\}, S_4 \notin V_1 \text{ i } S_4 \notin V_2$$

$$2) \quad T_4 = T_1 \cup T_2$$

$$3) \quad P_4 = P_1 \cup P_2 \cup \{S_4 \rightarrow S_1 S_2\}$$

S_4

Properties of Context-Free Languages

- **Concatenation**

- $G_1 = (V_1, T_1, P_1, S_1)$, $G_2 = (V_2, T_2, P_2, S_2)$
- $V_1 \cap V_2 = \emptyset$
- $L(G_4) = L(G_1) L(G_2)$
- $G_4 = (V_4, T_4, P_4, S_4)$

$$1) \quad V_4 = V_1 \cup V_2 \cup \{S_4\}, S_4 \notin V_1 \text{ i } S_4 \notin V_2$$

$$2) \quad T_4 = T_1 \cup T_2$$

$$3) \quad P_4 = P_1 \cup P_2 \cup \{S_4 \rightarrow S_1 S_2\}$$

$$\begin{matrix} S_4 \\ \Rightarrow \\ G_4 \end{matrix}$$

Properties of Context-Free Languages

- **Concatenation**

- $G_1 = (V_1, T_1, P_1, S_1)$, $G_2 = (V_2, T_2, P_2, S_2)$
- $V_1 \cap V_2 = \emptyset$
- $L(G_4) = L(G_1) L(G_2)$
- $G_4 = (V_4, T_4, P_4, S_4)$

$$1) \quad V_4 = V_1 \cup V_2 \cup \{S_4\}, S_4 \notin V_1 \text{ i } S_4 \notin V_2$$

$$2) \quad T_4 = T_1 \cup T_2$$

$$3) \quad P_4 = P_1 \cup P_2 \cup \{S_4 \rightarrow S_1 S_2\}$$

$$S_4 \xrightarrow[G_4]{} S_1 S_2$$

Properties of Context-Free Languages

- **Concatenation**

- $G_1 = (V_1, T_1, P_1, S_1)$, $G_2 = (V_2, T_2, P_2, S_2)$
- $V_1 \cap V_2 = \emptyset$
- $L(G_4) = L(G_1) L(G_2)$
- $G_4 = (V_4, T_4, P_4, S_4)$

$$1) \quad V_4 = V_1 \cup V_2 \cup \{S_4\}, S_4 \notin V_1 \text{ i } S_4 \notin V_2$$

$$2) \quad T_4 = T_1 \cup T_2$$

$$3) \quad P_4 = P_1 \cup P_2 \cup \{S_4 \rightarrow S_1 S_2\}$$

$$S_4 \xrightarrow[G_4]{} S_1 S_2 \xrightarrow[G_1]{*}$$

Properties of Context-Free Languages

- **Concatenation**

- $G_1 = (V_1, T_1, P_1, S_1)$, $G_2 = (V_2, T_2, P_2, S_2)$
- $V_1 \cap V_2 = \emptyset$
- $L(G_4) = L(G_1) L(G_2)$
- $G_4 = (V_4, T_4, P_4, S_4)$

$$1) \quad V_4 = V_1 \cup V_2 \cup \{S_4\}, S_4 \notin V_1 \text{ i } S_4 \notin V_2$$

$$2) \quad T_4 = T_1 \cup T_2$$

$$3) \quad P_4 = P_1 \cup P_2 \cup \{S_4 \rightarrow S_1 S_2\}$$

$$S_4 \xrightarrow[G_4]{} S_1 S_2 \xrightarrow[G_1]{} w_1 S_2$$

Properties of Context-Free Languages

- **Concatenation**

- $G_1 = (V_1, T_1, P_1, S_1)$, $G_2 = (V_2, T_2, P_2, S_2)$
- $V_1 \cap V_2 = \emptyset$
- $L(G_4) = L(G_1) L(G_2)$
- $G_4 = (V_4, T_4, P_4, S_4)$

$$1) \quad V_4 = V_1 \cup V_2 \cup \{S_4\}, S_4 \notin V_1 \text{ i } S_4 \notin V_2$$

$$2) \quad T_4 = T_1 \cup T_2$$

$$3) \quad P_4 = P_1 \cup P_2 \cup \{S_4 \rightarrow S_1 S_2\}$$

$$S_4 \xrightarrow[G_4]{} S_1 S_2 \xrightarrow[G_1]{*} w_1 S_2 \xrightarrow[G_2]{*}$$

Properties of Context-Free Languages

- **Concatenation**

- $G_1 = (V_1, T_1, P_1, S_1)$, $G_2 = (V_2, T_2, P_2, S_2)$
- $V_1 \cap V_2 = \emptyset$
- $L(G_4) = L(G_1) L(G_2)$
- $G_4 = (V_4, T_4, P_4, S_4)$

$$1) \quad V_4 = V_1 \cup V_2 \cup \{S_4\}, S_4 \notin V_1 \text{ i } S_4 \notin V_2$$

$$2) \quad T_4 = T_1 \cup T_2$$

$$3) \quad P_4 = P_1 \cup P_2 \cup \{S_4 \rightarrow S_1 S_2\}$$

$$S_4 \xrightarrow[G_4]{} S_1 S_2 \xrightarrow[G_1]{}^* w_1 S_2 \xrightarrow[G_2]{}^* w_1 w_2$$

Properties of Context-Free Languages

Properties of Context-Free Languages

- Kleen operator (closure) L^*

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$
 - $G_5 = (V_5, T_5, P_5, S_5)$

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$
 - $G_5 = (V_5, T_5, P_5, S_5)$

1) $V_5 = V_1 \cup \{S_5\}, \quad S_5 \notin V_1$

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$
 - $G_5 = (V_5, T_5, P_5, S_5)$

-
- 1) $V_5 = V_1 \cup \{S_5\}, S_5 \notin V_1$
 - 2) $T_5 = T_1$

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$
 - $G_5 = (V_5, T_5, P_5, S_5)$

-
- 1) $V_5 = V_1 \cup \{S_5\}, S_5 \notin V_1$
 - 2) $T_5 = T_1$
 - 3) $P_4 = P_1 \cup \{S_5 \rightarrow S_1 \mid \epsilon\}$

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$
 - $G_5 = (V_5, T_5, P_5, S_5)$

-
- 1) $V_5 = V_1 \cup \{S_5\}, S_5 \notin V_1$
 - 2) $T_5 = T_1$
 - 3) $P_4 = P_1 \cup \{S_5 \rightarrow S_1 S_5 \mid \varepsilon\}$

S_5

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$
 - $G_5 = (V_5, T_5, P_5, S_5)$

-
- 1) $V_5 = V_1 \cup \{S_5\}, S_5 \notin V_1$
 - 2) $T_5 = T_1$
 - 3) $P_4 = P_1 \cup \{S_5 \rightarrow S_1 S_5 \mid \varepsilon\}$

$S_5 \Rightarrow G_5$

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$
 - $G_5 = (V_5, T_5, P_5, S_5)$

-
- 1) $V_5 = V_1 \cup \{S_5\}, S_5 \notin V_1$
 - 2) $T_5 = T_1$
 - 3) $P_4 = P_1 \cup \{S_5 \rightarrow S_1 S_5 \mid \varepsilon\}$

$$S_5 \xrightarrow[G_5]{} S_1 S_5$$

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$
 - $G_5 = (V_5, T_5, P_5, S_5)$

1) $V_5 = V_1 \cup \{S_5\}, \quad S_5 \notin V_1$

2) $T_5 = T_1$

3) $P_5 = P_1 \cup \{S_5 \rightarrow S_1 \ S_5 \mid \epsilon\}$

$$S_5 \underset{G_5}{\Rightarrow} S_1 \ S_5 \underset{G_1}{\stackrel{*}{\Rightarrow}}$$

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$
 - $G_5 = (V_5, T_5, P_5, S_5)$

-
- 1) $V_5 = V_1 \cup \{S_5\}, S_5 \notin V_1$
 - 2) $T_5 = T_1$
 - 3) $P_4 = P_1 \cup \{S_5 \rightarrow S_1 S_5 \mid \varepsilon\}$

$$S_5 \underset{G_5}{\Rightarrow} S_1 S_5 \underset{G_1}{\stackrel{*}{\Rightarrow}} w S_5$$

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$
 - $G_5 = (V_5, T_5, P_5, S_5)$

-
- 1) $V_5 = V_1 \cup \{S_5\}, S_5 \notin V_1$
 - 2) $T_5 = T_1$
 - 3) $P_4 = P_1 \cup \{S_5 \rightarrow S_1 S_5 \mid \varepsilon\}$

$$S_5 \underset{G_5}{\Rightarrow} S_1 S_5 \underset{G_1}{\stackrel{*}{\Rightarrow}} w S_5 \underset{G_5}{\Rightarrow}$$

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$
 - $G_5 = (V_5, T_5, P_5, S_5)$

-
- 1) $V_5 = V_1 \cup \{S_5\}, S_5 \notin V_1$
 - 2) $T_5 = T_1$
 - 3) $P_4 = P_1 \cup \{S_5 \rightarrow S_1 S_5 \mid \epsilon\}$

$$S_5 \underset{G_5}{\Rightarrow} S_1 S_5 \underset{G_1}{\stackrel{*}{\Rightarrow}} w S_5 \underset{G_5}{\Rightarrow} w S_1 S_5$$

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$
 - $G_5 = (V_5, T_5, P_5, S_5)$

1) $V_5 = V_1 \cup \{S_5\}, S_5 \notin V_1$

2) $T_5 = T_1$

3) $P_4 = P_1 \cup \{S_5 \rightarrow S_1 S_5 \mid \epsilon\}$

$$S_5 \underset{G_5}{\Rightarrow} S_1 S_5 \underset{G_1}{\stackrel{*}{\Rightarrow}} w S_5 \underset{G_5}{\Rightarrow} w S_1 S_5 \underset{G_1}{\stackrel{*}{\Rightarrow}}$$

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$
 - $G_5 = (V_5, T_5, P_5, S_5)$

1) $V_5 = V_1 \cup \{S_5\}, S_5 \notin V_1$

2) $T_5 = T_1$

3) $P_4 = P_1 \cup \{S_5 \rightarrow S_1 S_5 \mid \varepsilon\}$

$$S_5 \underset{G_5}{\Rightarrow} S_1 S_5 \underset{G_1}{\stackrel{*}{\Rightarrow}} w S_5 \underset{G_5}{\Rightarrow} w S_1 S_5 \underset{G_1}{\stackrel{*}{\Rightarrow}} w w S_5$$

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$
 - $G_5 = (V_5, T_5, P_5, S_5)$

1) $V_5 = V_1 \cup \{S_5\}, S_5 \notin V_1$

2) $T_5 = T_1$

3) $P_4 = P_1 \cup \{S_5 \rightarrow S_1 S_5 \mid \epsilon\}$

$$S_5 \underset{G_5}{\Rightarrow} S_1 S_5 \underset{G_1}{\stackrel{*}{\Rightarrow}} w S_5 \underset{G_5}{\Rightarrow} w S_1 S_5 \underset{G_1}{\stackrel{*}{\Rightarrow}} w w S_5 \underset{G_5}{\Rightarrow}$$

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$
 - $G_5 = (V_5, T_5, P_5, S_5)$

1) $V_5 = V_1 \cup \{S_5\}, S_5 \notin V_1$

2) $T_5 = T_1$

3) $P_4 = P_1 \cup \{S_5 \rightarrow S_1 S_5 \mid \epsilon\}$

$$S_5 \underset{G_5}{\Rightarrow} S_1 S_5 \underset{G_1}{\stackrel{*}{\Rightarrow}} w S_5 \underset{G_5}{\Rightarrow} w S_1 S_5 \underset{G_1}{\stackrel{*}{\Rightarrow}} w w S_5 \underset{G_5}{\Rightarrow} \dots$$

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$
 - $G_5 = (V_5, T_5, P_5, S_5)$

1) $V_5 = V_1 \cup \{S_5\}, \quad S_5 \notin V_1$

2) $T_5 = T_1$

3) $P_4 = P_1 \cup \{S_5 \rightarrow S_1 \ S_5 \mid \epsilon\}$

$$S_5 \xrightarrow[G_5]{} S_1 \ S_5 \xrightarrow[G_1]{*} w \ S_5 \xrightarrow[G_5]{} w \ S_1 \ S_5 \xrightarrow[G_1]{*} w \ w \ S_5 \xrightarrow[G_5]{} \dots$$

$\xrightarrow{*}$
 \Rightarrow
 G_1

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$
 - $G_5 = (V_5, T_5, P_5, S_5)$

1) $V_5 = V_1 \cup \{S_5\}, \quad S_5 \notin V_1$

2) $T_5 = T_1$

3) $P_4 = P_1 \cup \{S_5 \rightarrow S_1 \ S_5 \mid \epsilon\}$

$$\begin{array}{ccccccccc} S_5 & \xrightarrow[G_5]{} & S_1 \ S_5 & \xrightarrow[G_1]{*} & w \ S_5 & \xrightarrow[G_5]{} & w \ S_1 \ S_5 & \xrightarrow[G_1]{*} & w \ w \ S_5 \xrightarrow[G_5]{} \dots \\ & \xrightarrow[G_1]{*} & & & & & & & \end{array}$$

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$
 - $G_5 = (V_5, T_5, P_5, S_5)$

1) $V_5 = V_1 \cup \{S_5\}, S_5 \notin V_1$

2) $T_5 = T_1$

3) $P_4 = P_1 \cup \{S_5 \rightarrow S_1 S_5 \mid \varepsilon\}$

$$\begin{array}{ccccccccc} S_5 & \xrightarrow[G_5]{} & S_1 & S_5 & \xrightarrow[G_1]{*} & w & S_5 & \xrightarrow[G_5]{} & w S_1 & S_5 & \xrightarrow[G_1]{*} & w w & S_5 & \xrightarrow[G_5]{} & \dots \\ & & & & & & & & & & & & & & & & \end{array}$$
$$\begin{array}{c} * \\ \xrightarrow[G_1]{*} \\ \xrightarrow[G_5]{} \end{array}$$
$$w^+ S_5$$

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$
 - $G_5 = (V_5, T_5, P_5, S_5)$

1) $V_5 = V_1 \cup \{S_5\}, S_5 \notin V_1$

2) $T_5 = T_1$

3) $P_4 = P_1 \cup \{S_5 \rightarrow S_1 S_5 \mid \varepsilon\}$

$$\begin{array}{ccccccccc} S_5 & \xrightarrow[G_5]{} & S_1 & S_5 & \xrightarrow[G_1]{*} & w & S_5 & \xrightarrow[G_5]{} & w S_1 & S_5 & \xrightarrow[G_1]{*} & w & w & S_5 & \xrightarrow[G_5]{} & \dots \\ & & & & & & & & & & & & & & & & & \\ & \xrightarrow[G_1]{*} & w^+ & S_5 & \xrightarrow[G_5]{} & w^+ & & & & & & & & & & & & \end{array}$$

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$
 - $G_5 = (V_5, T_5, P_5, S_5)$

1) $V_5 = V_1 \cup \{S_5\}, \quad S_5 \notin V_1$

2) $T_5 = T_1$

3) $P_4 = P_1 \cup \{S_5 \rightarrow S_1 \ S_5 \mid \varepsilon\}$

$$\begin{array}{ccccccccc} S_5 & \xrightarrow[G_5]{} & S_1 \ S_5 & \xrightarrow[G_1]{*} & w \ S_5 & \xrightarrow[G_5]{} & w \ S_1 \ S_5 & \xrightarrow[G_1]{*} & w \ w \ S_5 \xrightarrow[G_5]{} \dots \\ & & & & & & & & \\ & \xrightarrow[G_1]{*} & w^+ \ S_5 & \xrightarrow[G_5]{} & w^+ \\ & & & & & & & & \\ & & S_5 & & & & & & \end{array}$$

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$
 - $G_5 = (V_5, T_5, P_5, S_5)$

1) $V_5 = V_1 \cup \{S_5\}, S_5 \notin V_1$

2) $T_5 = T_1$

3) $P_4 = P_1 \cup \{S_5 \rightarrow S_1 S_5 \mid \epsilon\}$

$$\begin{array}{ccccccccc} S_5 & \xrightarrow[G_5]{} & S_1 & S_5 & \xrightarrow[G_1]{*} & w & S_5 & \xrightarrow[G_5]{} & w S_1 & S_5 & \xrightarrow[G_1]{*} & w w & S_5 & \xrightarrow[G_5]{} & \dots \\ & & & & & & & & & & & & & & & & \\ & \xrightarrow[G_1]{*} & w^+ & S_5 & \xrightarrow[G_5]{} & w^+ & & & & & & & & & & & \\ & & & & & & & & & & & & & & & & & \\ S_5 & \xrightarrow[G_5]{} & & & & & & & & & & & & & & & & \end{array}$$

Properties of Context-Free Languages

- Kleen operator (closure) L^*
 - $G_1 = (V_1, T_1, P_1, S_1)$
 - $L(G_5) = L(G_1)^*$
 - $G_5 = (V_5, T_5, P_5, S_5)$

1) $V_5 = V_1 \cup \{S_5\}, \quad S_5 \notin V_1$

2) $T_5 = T_1$

3) $P_4 = P_1 \cup \{S_5 \rightarrow S_1 \ S_5 \mid \epsilon\}$

$$\begin{array}{ccccccccc} S_5 & \xrightarrow[G_5]{} & S_1 \ S_5 & \xrightarrow[G_1]{*} & w \ S_5 & \xrightarrow[G_5]{} & w \ S_1 \ S_5 & \xrightarrow[G_1]{*} & w \ w \ S_5 \xrightarrow[G_5]{} \dots \\ & & & & & & & & \\ & \xrightarrow[G_1]{*} & w^+ \ S_5 & \xrightarrow[G_5]{} & w^+ & & & & \\ & & & & & & & & \\ S_5 & \xrightarrow[G_5]{} & \epsilon & & & & & & \end{array}$$

Properties of Context-Free Languages

Properties of Context-Free Languages

- **Substitution**

Properties of Context-Free Languages

- **Substitution**
 - $G = (V, T, P, S)$

Properties of Context-Free Languages

- **Substitution**
 - $G = (V, T, P, S)$
 - $a_i \in L(G)$ are substituted by strings in $L(G_i)$

Properties of Context-Free Languages

- **Substitution**
 - $G = (V, T, P, S)$
 - $a_i \in L(G)$ are substituted by strings in $L(G_i)$
 - $G_i = (V_i, T_i, P_i, S_i)$

Properties of Context-Free Languages

- **Substitution**
 - $G = (V, T, P, S)$
 - $a_i \in L(G)$ are substituted by strings in $L(G_i)$
 - $G_i = (V_i, T_i, P_i, S_i)$
 - $1 \leq i \leq k$, k – cardinal number of set T

Properties of Context-Free Languages

- **Substitution**
 - $G = (V, T, P, S)$
 - $a_i \in L(G)$ are substituted by strings in $L(G_i)$
 - $G_i = (V_i, T_i, P_i, S_i)$
 - $1 \leq i \leq k$, k – cardinal number of set T
 - $G' = (V', T', P', S')$
-

Properties of Context-Free Languages

- **Substitution**
 - $G = (V, T, P, S)$
 - $a_i \in L(G)$ are substituted by strings in $L(G_i)$
 - $G_i = (V_i, T_i, P_i, S_i)$
 - $1 \leq i \leq k$, k – cardinal number of set T
- $G' = (V', T', P', S')$

$$1) \quad V' = V \cup V_1 \cup V_2 \cup \dots \cup V_k, \quad V \cap V_i = \emptyset, \quad V_i \cap V_j = \emptyset, \quad 1 \leq i \leq k, \quad 1 \leq j \leq k, \quad i \neq j$$

Properties of Context-Free Languages

- **Substitution**
 - $G = (V, T, P, S)$
 - $a_i \in L(G)$ are substituted by strings in $L(G_i)$
 - $G_i = (V_i, T_i, P_i, S_i)$
 - $1 \leq i \leq k$, k – cardinal number of set T
- $G' = (V', T', P', S')$

1) $V' = V \cup V_1 \cup V_2 \cup \dots \cup V_k$, $V \cap V_i = \emptyset$, $V_i \cap V_j = \emptyset$, $1 \leq i \leq k$, $1 \leq j \leq k$, $i \neq j$

2) $T' = T_1 \cup T_2 \cup \dots \cup T_k$

Properties of Context-Free Languages

- **Substitution**
 - $G = (V, T, P, S)$
 - $a_i \in L(G)$ are substituted by strings in $L(G_i)$
 - $G_i = (V_i, T_i, P_i, S_i)$
 - $1 \leq i \leq k$, k – cardinal number of set T
- $G' = (V', T', P', S')$

-
- 1) $V' = V \cup V_1 \cup V_2 \cup \dots \cup V_k$, $V \cap V_i = \emptyset$, $V_i \cap V_j = \emptyset$, $1 \leq i \leq k$, $1 \leq j \leq k$, $i \neq j$
 - 2) $T' = T_1 \cup T_2 \cup \dots \cup T_k$
 - 3) $S' = S$

Properties of Context-Free Languages

- **Substitution**
 - $G = (V, T, P, S)$
 - $a_i \in L(G)$ are substituted by strings in $L(G_i)$
 - $G_i = (V_i, T_i, P_i, S_i)$
 - $1 \leq i \leq k$, k – cardinal number of set T
- $G' = (V', T', P', S')$

-
- 1) $V' = V \cup V_1 \cup V_2 \dots V_k$, $V \cap V_i = \emptyset$, $V_i \cap V_j = \emptyset$, $1 \leq i \leq k$, $1 \leq j \leq k$, $i \neq j$
 - 2) $T' = T_1 \cup T_2 \dots T_k$
 - 3) $S' = S$
 - 4) Set of productions $P' = P_1 \cup P_2 \dots P_k$

Properties of Context-Free Languages

- **Substitution**
 - $G = (V, T, P, S)$
 - $a_i \in L(G)$ are substituted by strings in $L(G_i)$
 - $G_i = (V_i, T_i, P_i, S_i)$
 - $1 \leq i \leq k$, k – cardinal number of set T
- $G' = (V', T', P', S')$

1) $V' = V \cup V_1 \cup V_2 \dots V_k$, $V \cap V_i = \emptyset$, $V_i \cap V_j = \emptyset$, $1 \leq i \leq k$, $1 \leq j \leq k$, $i \neq j$

2) $T' = T_1 \cup T_2 \dots T_k$

3) $S' = S$

4) Set of productions $P' = P_1 \cup P_2 \dots P_k$

modified productions of grammar G are added:

Properties of Context-Free Languages

- **Substitution**
 - $G = (V, T, P, S)$
 - $a_i \in L(G)$ are substituted by strings in $L(G_i)$
 - $G_i = (V_i, T_i, P_i, S_i)$
 - $1 \leq i \leq k$, k – cardinal number of set T
- $G' = (V', T', P', S')$

1) $V' = V \cup V_1 \cup V_2 \dots V_k$, $V \cap V_i = \emptyset$, $V_i \cap V_j = \emptyset$, $1 \leq i \leq k$, $1 \leq j \leq k$, $i \neq j$

2) $T' = T_1 \cup T_2 \dots T_k$

3) $S' = S$

4) Set of productions $P' = P_1 \cup P_2 \dots P_k$

modified productions of grammar G are added:

a_i is replaced by S_i

Properties of Context-Free Languages

1) $V' = V \cup V_1 \cup V_2 \cup \dots \cup V_k, \quad V \cap V_i = \emptyset, \quad V_i \cap V_j = \emptyset, \quad 1 \leq i \leq k, \quad 1 \leq j \leq k, \quad i \neq j$

2) $T' = T_1 \cup T_2 \cup \dots \cup T_k$

3) $S' = S$

4) Set of productions $P' = P_1 \cup P_2 \cup \dots \cup P_k$

modified productions of grammar G are added:

a_i is replaced by S_i

Properties of Context-Free Languages

- $S \rightarrow aSbS \mid bSaS \mid \epsilon$

1) $V' = V \cup V_1 \cup V_2 \cup \dots \cup V_k, \quad V \cap V_i = \emptyset, \quad V_i \cap V_j = \emptyset, \quad 1 \leq i \leq k, \quad 1 \leq j \leq k, \quad i \neq j$

2) $T' = T_1 \cup T_2 \cup \dots \cup T_k$

3) $S' = S$

4) Set of productions $P' = P_1 \cup P_2 \cup \dots \cup P_k$

modified productions of grammar G are added:

a_i is replaced by S_i

Properties of Context-Free Languages

- $S \rightarrow aSbS \mid bSaS \mid \epsilon$
 - $a \in L(G)$ are replaced by strings in $L_1 = \{ 0^n 1^n \mid n \geq 1 \}$

1) $V' = V \cup V_1 \cup V_2 \cup \dots \cup V_k, \quad V \cap V_i = \emptyset, \quad V_i \cap V_j = \emptyset, \quad 1 \leq i \leq k, \quad 1 \leq j \leq k, \quad i \neq j$

2) $T' = T_1 \cup T_2 \cup \dots \cup T_k$

3) $S' = S$

4) Set of productions $P' = P_1 \cup P_2 \cup \dots \cup P_k$

modified productions of grammar G are added:

a_i is replaced by S_i

Properties of Context-Free Languages

- $S \rightarrow aSbS \mid bSaS \mid \epsilon$
 - $a \in L(G)$ are replaced by strings in $L_1 = \{ 0^n 1^n \mid n \geq 1\}$
 - $S_1 \rightarrow 0 S_1 1 \mid 0 1$

1) $V' = V \cup V_1 \cup V_2 \cup \dots \cup V_k, \quad V \cap V_i = \emptyset, \quad V_i \cap V_j = \emptyset, \quad 1 \leq i \leq k, \quad 1 \leq j \leq k, \quad i \neq j$

2) $T' = T_1 \cup T_2 \cup \dots \cup T_k$

3) $S' = S$

4) Set of productions $P' = P_1 \cup P_2 \cup \dots \cup P_k$

modified productions of grammar G are added:

a_i is replaced by S_i

Properties of Context-Free Languages

- $S \rightarrow aSbS \mid bSaS \mid \epsilon$

- $a \in L(G)$ are replaced by strings in $L_1 = \{ 0^n 1^n \mid n \geq 1\}$
- $S_1 \rightarrow 0 S_1 1 \mid 0 1$
- $b \in L(G)$ are replaced by strings in $L_2 = \{ ww^R \mid w \text{ is } (0+2)^*\}$

1) $V' = V \cup V_1 \cup V_2 \cup \dots \cup V_k, \quad V \cap V_i = \emptyset, \quad V_i \cap V_j = \emptyset, \quad 1 \leq i \leq k, \quad 1 \leq j \leq k, \quad i \neq j$

2) $T' = T_1 \cup T_2 \cup \dots \cup T_k$

3) $S' = S$

4) Set of productions $P' = P_1 \cup P_2 \cup \dots \cup P_k$

modified productions of grammar G are added:

a_i is replaced by S_i

Properties of Context-Free Languages

- $S \rightarrow aSbS \mid bSaS \mid \epsilon$

- $a \in L(G)$ are replaced by strings in $L_1 = \{ 0^n 1^n \mid n \geq 1\}$
- $S_1 \rightarrow 0 S_1 1 \mid 0 1$
- $b \in L(G)$ are replaced by strings in $L_2 = \{ ww^R \mid w \text{ is } (0+2)^*\}$
- $S_2 \rightarrow 0 S_2 0 \mid 2 S_2 2 \mid \epsilon$

1) $V' = V \cup V_1 \cup V_2 \cup \dots \cup V_k, \quad V \cap V_i = \emptyset, \quad V_i \cap V_j = \emptyset, \quad 1 \leq i \leq k, \quad 1 \leq j \leq k, \quad i \neq j$

2) $T' = T_1 \cup T_2 \cup \dots \cup T_k$

3) $S' = S$

4) Set of productions $P' = P_1 \cup P_2 \cup \dots \cup P_k$

modified productions of grammar G are added:

a_i is replaced by S_i

Properties of Context-Free Languages

- $S \rightarrow aSbS \mid bSaS \mid \epsilon$
 - $a \in L(G)$ are replaced by strings in $L_1 = \{ 0^n 1^n \mid n \geq 1\}$
 - $S_1 \rightarrow 0 S_1 1 \mid 0 1$
- $b \in L(G)$ are replaced by strings in $L_2 = \{ ww^R \mid w \text{ is } (0+2)^*\}$
- $S_2 \rightarrow 0 S_2 0 \mid 2 S_2 2 \mid \epsilon$

1) $V' = \{S\} \cup \{S_1\} \cup \{S_2\} = \{S, S_1, S_2\}$

2) $T' = T_1 \cup T_2 \cup \dots \cup T_k$

3) $S' = S$

4) Set of productions $P' = P_1 \cup P_2 \cup \dots \cup P_k$

modified productions of grammar G are added:

a_i is replaced by S_i

Properties of Context-Free Languages

- $S \rightarrow aSbS \mid bSaS \mid \epsilon$
 - $a \in L(G)$ are replaced by strings in $L_1 = \{ 0^n 1^n \mid n \geq 1\}$
 - $S_1 \rightarrow 0 S_1 1 \mid 0 1$
- $b \in L(G)$ are replaced by strings in $L_2 = \{ ww^R \mid w \text{ is } (0+2)^*\}$
- $S_2 \rightarrow 0 S_2 0 \mid 2 S_2 2 \mid \epsilon$

1) $V' = \{S\} \cup \{S_1\} \cup \{S_2\} = \{S, S_1, S_2\}$

2) $T' = \{0, 1\} \cup \{0, 2\} = \{0, 1, 2\}$

3) $S' = S$

4) Set of productions $P' = P_1 \cup P_2 \dots P_k$

modified productions of grammar G are added:

a_i is replaced by S_i

Properties of Context-Free Languages

- $S \rightarrow aSbS \mid bSaS \mid \epsilon$
 - $a \in L(G)$ are replaced by strings in $L_1 = \{ 0^n 1^n \mid n \geq 1\}$
 - $S_1 \rightarrow 0 S_1 1 \mid 0 1$
- $b \in L(G)$ are replaced by strings in $L_2 = \{ ww^R \mid w \text{ is } (0+2)^*\}$
- $S_2 \rightarrow 0 S_2 0 \mid 2 S_2 2 \mid \epsilon$

-
- 1) $V' = \{S\} \cup \{S_1\} \cup \{S_2\} = \{S, S_1, S_2\}$
 - 2) $T' = \{0, 1\} \cup \{0, 2\} = \{0, 1, 2\}$
 - 3) $S' = S$
 - 4) Set of productions $P' = \{S_1 \rightarrow 0S_11 \mid 01\} \cup \{S_2 \rightarrow 0S_20 \mid 2S_22 \mid \epsilon\}$
modified productions of grammar G are added:
 a_i is replaced by S_i

Properties of Context-Free Languages

- $S \rightarrow aSbS \mid bSaS \mid \epsilon$
 - $a \in L(G)$ are replaced by strings in $L_1 = \{ 0^n 1^n \mid n \geq 1\}$
 - $S_1 \rightarrow 0 S_1 1 \mid 0 1$
- $b \in L(G)$ are replaced by strings in $L_2 = \{ ww^R \mid w \text{ is } (0+2)^*\}$
- $S_2 \rightarrow 0 S_2 0 \mid 2 S_2 2 \mid \epsilon$

1) $V' = \{S\} \cup \{S_1\} \cup \{S_2\} = \{S, S_1, S_2\}$

2) $T' = \{0, 1\} \cup \{0, 2\} = \{0, 1, 2\}$

3) $S' = S$

4) Set of productions $P' = \{S_1 \rightarrow 0S_11 \mid 01\} \cup \{S_2 \rightarrow 0S_20 \mid 2S_22 \mid \epsilon\}$
modified productions of grammar G are added:

$$S \rightarrow a S b S \mid b S a S \mid \epsilon$$

Properties of Context-Free Languages

- $S \rightarrow aSbS \mid bSaS \mid \epsilon$
 - $a \in L(G)$ are replaced by strings in $L_1 = \{ 0^n 1^n \mid n \geq 1\}$
 - $S_1 \rightarrow 0 S_1 1 \mid 0 1$
- $b \in L(G)$ are replaced by strings in $L_2 = \{ ww^R \mid w \text{ is } (0+2)^*\}$
- $S_2 \rightarrow 0 S_2 0 \mid 2 S_2 2 \mid \epsilon$

1) $V' = \{S\} \cup \{S_1\} \cup \{S_2\} = \{S, S_1, S_2\}$

2) $T' = \{0, 1\} \cup \{0, 2\} = \{0, 1, 2\}$

3) $S' = S$

4) Set of productions $P' = \{S_1 \rightarrow 0S_11 \mid 01\} \cup \{S_2 \rightarrow 0S_20 \mid 2S_22 \mid \epsilon\}$
modified productions of grammar G are added:

$$S \rightarrow S_1 S \quad b \quad S \mid \quad b \quad S \quad S_1 \quad S \mid \epsilon$$

Properties of Context-Free Languages

- $S \rightarrow aSbS \mid bSaS \mid \epsilon$
 - $a \in L(G)$ are replaced by strings in $L_1 = \{ 0^n 1^n \mid n \geq 1\}$
 - $S_1 \rightarrow 0 S_1 1 \mid 0 1$
- $b \in L(G)$ are replaced by strings in $L_2 = \{ ww^R \mid w \text{ is } (0+2)^*\}$
- $S_2 \rightarrow 0 S_2 0 \mid 2 S_2 2 \mid \epsilon$

1) $V' = \{S\} \cup \{S_1\} \cup \{S_2\} = \{S, S_1, S_2\}$

2) $T' = \{0, 1\} \cup \{0, 2\} = \{0, 1, 2\}$

3) $S' = S$

4) Set of productions $P' = \{S_1 \rightarrow 0S_11 \mid 01\} \cup \{S_2 \rightarrow 0S_20 \mid 2S_22 \mid \epsilon\}$
modified productions of grammar G are added:

$$S \rightarrow S_1 S \ S_2 S \mid S_2 S \ S_1 S \mid \epsilon$$

Properties of Context-Free Languages

Properties of Context-Free Languages

$$L_1 = \{ a^i b^i c^j \mid i \geq 1 \text{ and } j \geq 1 \}$$

Properties of Context-Free Languages

$$L_1 = \{ a^i b^i c^j \mid i \geq 1 \text{ and } j \geq 1 \}$$

$$L_2 = \{ a^j b^i c^i \mid i \geq 1 \text{ and } j \geq 1 \}$$

Properties of Context-Free Languages

$$L_1 = \{ a^i b^i c^j \mid i \geq 1 \text{ and } j \geq 1 \}$$

$$S \rightarrow A C$$

$$L_2 = \{ a^j b^i c^i \mid i \geq 1 \text{ and } j \geq 1 \}$$

Properties of Context-Free Languages

$$L_1 = \{ a^i b^i c^j \mid i \geq 1 \text{ and } j \geq 1 \}$$

$$\begin{array}{ll} S & \rightarrow A C \\ A & \rightarrow a A b \mid a \\ b & \end{array}$$

$$L_2 = \{ a^j b^i c^i \mid i \geq 1 \text{ and } j \geq 1 \}$$

Properties of Context-Free Languages

$$L_1 = \{ a^i b^i c^j \mid i \geq 1 \text{ and } j \geq 1 \}$$

S → A C
A → a A b | a
b
C → c C | c

$$L_2 = \{ a^j b^i c^i \mid i \geq 1 \text{ and } j \geq 1 \}$$

Properties of Context-Free Languages

$$L_1 = \{ a^i b^i c^j \mid i \geq 1 \text{ and } j \geq 1 \}$$

$$\begin{array}{ll} S & \rightarrow A C \\ A & \rightarrow a A b \mid a \\ b & \\ C & \rightarrow c C \mid c \end{array}$$

$$L_2 = \{ a^j b^i c^i \mid i \geq 1 \text{ and } j \geq 1 \}$$

$$S \rightarrow A B$$

Properties of Context-Free Languages

$$L_1 = \{ a^i b^i c^j \mid i \geq 1 \text{ and } j \geq 1 \}$$

$$\begin{array}{ll} S & \rightarrow A C \\ A & \rightarrow a A b \mid a \\ b & \\ C & \rightarrow c C \mid c \end{array}$$

$$L_2 = \{ a^j b^i c^i \mid i \geq 1 \text{ and } j \geq 1 \}$$

$$\begin{array}{ll} S & \rightarrow A B \\ A & \rightarrow a A \mid a \end{array}$$

Properties of Context-Free Languages

$$L_1 = \{ a^i b^i c^j \mid i \geq 1 \text{ and } j \geq 1 \}$$

$$\begin{array}{ll} S & \rightarrow A C \\ A & \rightarrow a A b \mid a \\ b & \\ C & \rightarrow c C \mid c \end{array}$$

$$L_2 = \{ a^j b^i c^i \mid i \geq 1 \text{ and } j \geq 1 \}$$

$$\begin{array}{ll} S & \rightarrow A B \\ A & \rightarrow a A \mid a \\ B & \rightarrow b B c \mid b \\ C & \end{array}$$

Properties of Context-Free Languages

$$L_1 = \{ a^i b^i c^j \mid i \geq 1 \text{ and } j \geq 1 \}$$

$$L_2 = \{ a^j b^i c^i \mid i \geq 1 \text{ and } j \geq 1 \}$$

$$\begin{array}{ll} S & \rightarrow A C \\ A & \rightarrow a A b \mid a \\ b & \\ C & \rightarrow c C \mid c \end{array}$$

$$\begin{array}{ll} S & \rightarrow A B \\ A & \rightarrow a A \mid a \\ B & \rightarrow b B c \mid b \\ C & \end{array}$$

Properties of Context-Free Languages


$L_1 = \{ a^i b^i c^j \mid i \geq 1 \text{ i } j \geq 1 \}$

$L_2 = \{ a^j b^i c^i \mid i \geq 1 \text{ i } j \geq 1 \}$

$S \rightarrow A C$
 $A \rightarrow a A b \mid a b$
 $C \rightarrow c C \mid c$

$S \rightarrow A B$
 $A \rightarrow a A \mid a$
 $B \rightarrow b B c \mid b c$


Properties of Context-Free Languages



$S \rightarrow A C$
 $A \rightarrow a A b \mid a b$
 $C \rightarrow c C \mid c$

$S \rightarrow A B$
 $A \rightarrow a A \mid a$
 $B \rightarrow b B c \mid b c$

Properties of Context-Free Languages




$$\begin{aligned} S &\rightarrow A C \\ A &\rightarrow a A b \mid a b \\ C &\rightarrow c C \mid c \end{aligned}$$

$$L = \{ a^i b^i c^i \mid i \geq 1 \}$$

$$\begin{aligned} S &\rightarrow A B \\ A &\rightarrow a A \mid a \\ B &\rightarrow b B c \mid b c \end{aligned}$$

Properties of Context-Free Languages



$S \rightarrow A C$
 $A \rightarrow a A b \mid a b$
 $C \rightarrow c C \mid c$

$$L = \{ a^i b^i c^i \mid i \geq 1 \}$$

Intersection of CFLs is *not* a CFL

$S \rightarrow A B$
 $A \rightarrow a A \mid a$
 $B \rightarrow b B c \mid b c$

Properties of Context-Free Languages

Properties of Context-Free Languages

- ***Complement of CFL is not necessarily a CFL***

Properties of Context-Free Languages

- ***Complement of CFL is not necessarily a CFL***
- **De Morgan's Laws**

Properties of Context-Free Languages

- ***Complement of CFL is not necessarily a CFL***
- **De Morgan's Laws**
 - $L_1 \cap L_2 = (L_1^c \cup L_2^c)^c$

Properties of Context-Free Languages

- **Complement of CFL is not necessarily a CFL**
- **De Morgan's Laws**
 - $L_1 \cap L_2 = (L_1^c \cup L_2^c)^c$
 - **Assumption – complement of context-free language is a context-free language**

Properties of Context-Free Languages

- **Complement of CFL is not necessarily a CFL**
- **De Morgan's Laws**
 - $L_1 \cap L_2 = (L_1^c \cup L_2^c)^c$
 - **Assumption – complement of context-free language is a context-free language**
 - **Based on De Morgan's laws**

Properties of Context-Free Languages

- **Complement of CFL is not necessarily a CFL**
- **De Morgan's Laws**
 - $L_1 \cap L_2 = (L_1^c \cup L_2^c)^c$
 - **Assumption – complement of context-free language is a context-free language**
 - **Based on De Morgan's laws**
 - intersection of CFL's appears to be a CFL

Properties of Context-Free Languages

- **Complement of CFL is not necessarily a CFL**
- **De Morgan's Laws**
 - $L_1 \cap L_2 = (L_1^c \cup L_2^c)^c$
 - **Assumption – complement of context-free language is a context-free language**
 - **Based on De Morgan's laws**
 - intersection of CFL's appears to be a CFL
 - this contradicts the previously shown fact regarding intersection of CFLs

Properties of Context-Free Languages

- **Complement of CFL is not necessarily a CFL**
- **De Morgan's Laws**
 - $L_1 \cap L_2 = (L_1^c \cup L_2^c)^c$
 - **Assumption – complement of context-free language is a context-free language**
 - **Based on De Morgan's laws**
 - intersection of CFL's appears to be a CFL
 - this contradicts the previously shown fact regarding intersection of CFLs
 - **Conclusion:**

Properties of Context-Free Languages

- **Complement of CFL is not necessarily a CFL**
- **De Morgan's Laws**
 - $L_1 \cap L_2 = (L_1^c \cup L_2^c)^c$
 - **Assumption – complement of context-free language is a context-free language**
 - **Based on De Morgan's laws**
 - intersection of CFL's appears to be a CFL
 - this contradicts the previously shown fact regarding intersection of CFLs
 - **Conclusion:**
 - complement of a context-free language is **not** a context free language

Properties of Context-Free Languages

Properties of Context-Free Languages

- Intersection of CFL with a regular language

Properties of Context-Free Languages

- Intersection of CFL with a regular language
 - L_1 accepts PA $M_1 = (Q_1, \Sigma, \Gamma, \delta_1, q_0, Z_1, F_1)$

Properties of Context-Free Languages

- Intersection of CFL with a regular language
 - L_1 accepts PA $M_1 = (Q_1, \Sigma, \Gamma, \delta_1, q_0, Z_1, F_1)$
 - L_2 accepts DKA $M_2 = (Q_2, \Sigma, \delta_2, p_0, F_2)$

Properties of Context-Free Languages

- Intersection of CFL with a regular language
 - L_1 accepts PA $M_1 = (Q_1, \Sigma, \Gamma, \delta_1, q_0, Z_1, F_1)$
 - L_2 accepts DKA $M_2 = (Q_2, \Sigma, \delta_2, p_0, F_2)$
- $L = L_1 \cap L_2$

Properties of Context-Free Languages

- Intersection of CFL with a regular language

- L_1 accepts PA M_1 = $(Q_1, \Sigma, \Gamma, \delta_1, q_0, Z_1, F_1)$
 - L_2 accepts DKA M_2 = $(Q_2, \Sigma, \delta_2, p_0, F_2)$

- $L = L_1 \cap L_2$

- L accepts PA M' = $(Q', \Sigma, \Gamma, \delta', q'_0, Z_0, F')$

Properties of Context-Free Languages

- Intersection of CFL with a regular language

- L_1 accepts PA M_1 = $(Q_1, \Sigma, \Gamma, \delta_1, q_0, Z_1, F_1)$
 - L_2 accepts DKA M_2 = $(Q_2, \Sigma, \delta_2, p_0, F_2)$

- $L = L_1 \cap L_2$

- L accepts PA M' = $(Q', \Sigma, \Gamma, \delta', q'_0, Z_0, F')$

1) $Q' = Q_2 \times Q_1$

Properties of Context-Free Languages

- Intersection of CFL with a regular language

- L_1 accepts PA M_1 = $(Q_1, \Sigma, \Gamma, \delta_1, q_0, Z_1, F_1)$
 - L_2 accepts DKA M_2 = $(Q_2, \Sigma, \delta_2, p_0, F_2)$

- $L = L_1 \cap L_2$

- L accepts PA M' = $(Q', \Sigma, \Gamma, \delta', q'_0, Z_0, F')$

1) $Q' = Q_2 \times Q_1$

2) $q'_0 = [p_0, q_0]$

Properties of Context-Free Languages

- Intersection of CFL with a regular language

- L_1 accepts PA $M_1 = (Q_1, \Sigma, \Gamma, \delta_1, q_0, Z_1, F_1)$
 - L_2 accepts DKA $M_2 = (Q_2, \Sigma, \delta_2, p_0, F_2)$

- $L = L_1 \cap L_2$

- L accepts PA $M' = (Q', \Sigma, \Gamma, \delta', q'_0, Z_0, F')$

1) $Q' = Q_2 \times Q_1$

2) $q'_0 = [p_0, q_0]$

3) $F' = F_2 \times F_1$

Properties of Context-Free Languages

- Intersection of CFL with a regular language
 - L_1 accepts PA $M_1 = (Q_1, \Sigma, \Gamma, \delta_1, q_0, Z_1, F_1)$
 - L_2 accepts DKA $M_2 = (Q_2, \Sigma, \delta_2, p_0, F_2)$
 - $L = L_1 \cap L_2$
 - L accepts PA $M' = (Q', \Sigma, \Gamma, \delta', q'_0, Z_0, F')$
-
- 1) $Q' = Q_2 \times Q_1$
 - 2) $q'_0 = [p_0, q_0]$
 - 3) $F' = F_2 \times F_1$
 - 4) $([p', q'], \gamma) \in \delta'([p, q], a, X)$

Properties of Context-Free Languages

- Intersection of CFL with a regular language
 - L_1 accepts PA $M_1 = (Q_1, \Sigma, \Gamma, \delta_1, q_0, Z_1, F_1)$
 - L_2 accepts DKA $M_2 = (Q_2, \Sigma, \delta_2, p_0, F_2)$
- $L = L_1 \cap L_2$
 - L accepts PA $M' = (Q', \Sigma, \Gamma, \delta', q'_0, Z_0, F')$

$$1) \quad Q' = Q_2 \times Q_1$$

$$2) \quad q'_0 = [p_0, q_0]$$

$$3) \quad F' = F_2 \times F_1$$

$$4) \quad ([p', q'], \gamma) \in \delta'([p, q], a, X)$$

$$\text{DKA } M_2 \quad - \delta_2(p, a) = p'$$

Properties of Context-Free Languages

- Intersection of CFL with a regular language
 - L_1 accepts PA $M_1 = (Q_1, \Sigma, \Gamma, \delta_1, q_0, Z_1, F_1)$
 - L_2 accepts DKA $M_2 = (Q_2, \Sigma, \delta_2, p_0, F_2)$
- $L = L_1 \cap L_2$
 - L accepts PA $M' = (Q', \Sigma, \Gamma, \delta', q'_0, Z_0, F')$

$$1) \quad Q' = Q_2 \times Q_1$$

$$2) \quad q'_0 = [p_0, q_0]$$

$$3) \quad F' = F_2 \times F_1$$

$$4) \quad ([p', q'], \gamma) \in \delta'([p, q], a, X)$$

$$\text{DKA } M_2 - \delta_2(p, a) = p'$$

$$\text{PA } M_1 - (q', \gamma) \in \delta_1(q, a, X)$$

Properties of Context-Free Languages

- Intersection of CFL with a regular language
 - L_1 accepts PA M_1 = $(Q_1, \Sigma, \Gamma, \delta_1, q_0, Z_1, F_1)$
 - L_2 accepts DKA M_2 = $(Q_2, \Sigma, \delta_2, p_0, F_2)$
- $L = L_1 \cap L_2$
 - L accepts PA M' = $(Q', \Sigma, \Gamma, \delta', q'_0, Z_0, F')$

$$1) \quad Q' = Q_2 \times Q_1$$

$$2) \quad q'_0 = [p_0, q_0]$$

$$3) \quad F' = F_2 \times F_1$$

$$4) \quad ([p', q'], \gamma) \in \delta'([p, q], a, X)$$

$$\text{DKA } M_2 - \delta_2(p, a) = p'$$

$$\text{PA } M_1 - (q', \gamma) \in \delta_1(q, a, X)$$

If a is ϵ , then $p' = p$

Properties of Context-Free Languages

Properties of Context-Free Languages

PA M'

Properties of Context-Free Languages

PA M'

([p_0 , q_0], w , Z_0)

Properties of Context-Free Languages

PA M'

$$([p_0, q_0], w, Z_0) \xrightarrow[M']{\gamma^*}$$

Properties of Context-Free Languages

PA M'

$$([p_0, q_0], w, Z_0) \xrightarrow[M']{*} ([p, q], \varepsilon, \gamma)$$

Properties of Context-Free Languages

PA M'

$$([p_0, q_0], w, Z_0) \xrightarrow[M']{*} ([p, q], \varepsilon, \gamma)$$

PA M_1

Properties of Context-Free Languages

PA M'

$$([p_0, q_0], w, Z_0) \xrightarrow[M']{*} ([p, q], \varepsilon, \gamma)$$

PA M_1

$$(q_0, w, Z_0)$$

Properties of Context-Free Languages

PA M'

$$([p_0, q_0], w, Z_0) \xrightarrow[M']{*} ([p, q], \varepsilon, \gamma)$$

PA M_1

$$(q_0, w, Z_0) \xrightarrow[M_1]{*}$$

Properties of Context-Free Languages

PA M'

$$([p_0, q_0], w, Z_0) \xrightarrow[M']{*} ([p, q], \varepsilon, \gamma)$$

PA M_1

$$(q_0, w, Z_0) \xrightarrow[M_1]{*} (q, \varepsilon, \gamma)$$

Properties of Context-Free Languages

PA M'

$$([p_0, q_0], w, Z_0) \xrightarrow[M']{*} ([p, q], \varepsilon, \gamma)$$

PA M_1

$$(q_0, w, Z_0) \xrightarrow[M_1]{*} (q, \varepsilon, \gamma)$$

DKA M_2

Properties of Context-Free Languages

PA M'

$$([p_0, q_0], w, Z_0) \xrightarrow[M']{*} ([p, q], \varepsilon, \gamma)$$

PA M_1

$$(q_0, w, Z_0) \xrightarrow[M_1]{*} (q, \varepsilon, \gamma)$$

DKA M_2

$$\delta_2(p_0, w) = p$$

Properties of Context-Free Languages

-
- 1) $Q' = Q_2 \times Q_1$
 - 2) $q'_0 = [p_0, q_0]$
 - 3) $F' = F_2 \times F_1$

Properties of Context-Free Languages

- PA $M_1 = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta_1, q_1, K, \{q_2\})$

-
- 1) $Q' = Q_2 \times Q_1$
 - 2) $q'_0 = [p_0, q_0]$
 - 3) $F' = F_2 \times F_1$

Properties of Context-Free Languages

- PA $M_1 = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta_1, q_1, K, \{q_2\})$
 - accepts language $L(M_1) = \{ 0^n 1^m \mid n \geq 1, m \geq 1, m \leq n \}$

-
- 1) $Q' = Q_2 \times Q_1$
 - 2) $q'_0 = [p_0, q_0]$
 - 3) $F' = F_2 \times F_1$

Properties of Context-Free Languages

- PA $M_1 = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta_1, q_1, K, \{q_2\})$
 - accepts language $L(M_1) = \{0^n 1^m \mid n \geq 1, m \geq 1, m \leq n\}$

$$\delta_1(q_1, 0, N) = \{(q_1, NK)\}$$

$$\delta_1(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_1(q_1, 0, N) = \{(q_1, NN)\}$$

$$\delta_1(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

- 1) $Q' = Q_2 \times Q_1$
- 2) $q'_0 = [p_0, q_0]$
- 3) $F' = F_2 \times F_1$

Properties of Context-Free Languages

- PA $M_1 = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta_1, q_1, K, \{q_2\})$
 - accepts language $L(M_1) = \{ 0^n 1^m \mid n \geq 1, m \geq 1, m \leq n \}$

$$\begin{aligned}\delta_1(q_1, 0, N) &= \{(q_1, NK)\} \\ \delta_1(q_1, 1, N) &= \{(q_2, \varepsilon)\}\end{aligned}$$

$$\begin{aligned}\delta_1(q_1, 0, N) &= \{(q_1, NN)\} \\ \delta_1(q_2, 1, N) &= \{(q_2, \varepsilon)\}\end{aligned}$$

- DKA $M_2 = (\{p_1, p_2, p_3\}, \{0, 1\}, \delta_2, p_1, \{p_3\})$

-
- 1) $Q' = Q_2 \times Q_1$
 - 2) $q'_0 = [p_0, q_0]$
 - 3) $F' = F_2 \times F_1$

Properties of Context-Free Languages

- PA $M_1 = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta_1, q_1, K, \{q_2\})$
 - accepts language $L(M_1) = \{ 0^n 1^m \mid n \geq 1, m \geq 1, m \leq n \}$

$$\begin{aligned}\delta_1(q_1, 0, N) &= \{(q_1, NK)\} \\ \delta_1(q_1, 1, N) &= \{(q_2, \epsilon)\}\end{aligned}$$

$$\begin{aligned}\delta_1(q_1, 0, N) &= \{(q_1, NN)\} \\ \delta_1(q_2, 1, N) &= \{(q_2, \epsilon)\}\end{aligned}$$

- DKA $M_2 = (\{p_1, p_2, p_3\}, \{0, 1\}, \delta_2, p_1, \{p_3\})$
 - strings of language $L(M_2)$ contain at least two symbols 1

-
- 1) $Q' = Q_2 \times Q_1$
 - 2) $q'_0 = [p_0, q_0]$
 - 3) $F' = F_2 \times F_1$

Properties of Context-Free Languages

- PA $M_1 = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta_1, q_1, K, \{q_2\})$
 - accepts language $L(M_1) = \{0^n 1^m \mid n \geq 1, m \geq 1, m \leq n\}$

$$\begin{aligned}\delta_1(q_1, 0, N) &= \{(q_1, NK)\} \\ \delta_1(q_1, 1, N) &= \{(q_2, \varepsilon)\}\end{aligned}$$

$$\begin{aligned}\delta_1(q_1, 0, N) &= \{(q_1, NN)\} \\ \delta_1(q_2, 1, N) &= \{(q_2, \varepsilon)\}\end{aligned}$$

- DKA $M_2 = (\{p_1, p_2, p_3\}, \{0, 1\}, \delta_2, p_1, \{p_3\})$
 - strings of language $L(M_2)$ contain at least two symbols 1

$$\begin{aligned}\delta_2(p_1, 0) &= p_1 \\ \delta_2(p_2, 0) &= p_2 \\ \delta_2(p_3, 0) &= p_3\end{aligned}$$

$$\begin{aligned}\delta_2(p_1, 1) &= p_2 \\ \delta_2(p_2, 1) &= p_3 \\ \delta_2(p_3, 1) &= p_3\end{aligned}$$

-
- 1) $Q' = Q_2 \times Q_1$
 - 2) $q'_0 = [p_0, q_0]$
 - 3) $F' = F_2 \times F_1$

Properties of Context-Free Languages

- PA $M_1 = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta_1, q_1, K, \{q_2\})$
 - accepts language $L(M_1) = \{0^n 1^m \mid n \geq 1, m \geq 1, m \leq n\}$

$$\begin{aligned}\delta_1(q_1, 0, N) &= \{(q_1, NK)\} \\ \delta_1(q_1, 1, N) &= \{(q_2, \varepsilon)\}\end{aligned}$$

$$\begin{aligned}\delta_1(q_1, 0, N) &= \{(q_1, NN)\} \\ \delta_1(q_2, 1, N) &= \{(q_2, \varepsilon)\}\end{aligned}$$

- DKA $M_2 = (\{p_1, p_2, p_3\}, \{0, 1\}, \delta_2, p_1, \{p_3\})$
 - strings of language $L(M_2)$ contain at least two symbols 1

$$\begin{aligned}\delta_2(p_1, 0) &= p_1 \\ \delta_2(p_2, 0) &= p_2 \\ \delta_2(p_3, 0) &= p_3\end{aligned}$$

$$\begin{aligned}\delta_2(p_1, 1) &= p_2 \\ \delta_2(p_2, 1) &= p_3 \\ \delta_2(p_3, 1) &= p_3\end{aligned}$$

-
- 1) $Q' = \{[p_1, q_1], [p_1, q_2], [p_2, q_1], [p_2, q_2], [p_3, q_1], [p_3, q_2]\}$
 - 2) $q'_0 = [p_0, q_0]$
 - 3) $F' = F_2 \times F_1$

Properties of Context-Free Languages

- PA $M_1 = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta_1, q_1, K, \{q_2\})$
 - accepts language $L(M_1) = \{0^n 1^m \mid n \geq 1, m \geq 1, m \leq n\}$

$$\begin{aligned}\delta_1(q_1, 0, N) &= \{(q_1, NK)\} \\ \delta_1(q_1, 1, N) &= \{(q_2, \varepsilon)\}\end{aligned}$$

$$\begin{aligned}\delta_1(q_1, 0, N) &= \{(q_1, NN)\} \\ \delta_1(q_2, 1, N) &= \{(q_2, \varepsilon)\}\end{aligned}$$

- DKA $M_2 = (\{p_1, p_2, p_3\}, \{0, 1\}, \delta_2, p_1, \{p_3\})$
 - strings of language $L(M_2)$ contain at least two symbols 1

$$\begin{aligned}\delta_2(p_1, 0) &= p_1 \\ \delta_2(p_2, 0) &= p_2 \\ \delta_2(p_3, 0) &= p_3\end{aligned}$$

$$\begin{aligned}\delta_2(p_1, 1) &= p_2 \\ \delta_2(p_2, 1) &= p_3 \\ \delta_2(p_3, 1) &= p_3\end{aligned}$$

-
- 1) $Q' = \{[p_1, q_1], [p_1, q_2], [p_2, q_1], [p_2, q_2], [p_3, q_1], [p_3, q_2]\}$
 - 2) $q'_0 = [p_1, q_1]$
 - 3) $F' = F_2 \times F_1$

Properties of Context-Free Languages

- PA $M_1 = (\{q_1, q_2\}, \{0, 1\}, \{N, K\}, \delta_1, q_1, K, \{q_2\})$
 - accepts language $L(M_1) = \{ 0^n 1^m \mid n \geq 1, m \geq 1, m \leq n \}$

$$\begin{aligned}\delta_1(q_1, 0, N) &= \{(q_1, NK)\} \\ \delta_1(q_1, 1, N) &= \{(q_2, \varepsilon)\}\end{aligned}$$

$$\begin{aligned}\delta_1(q_1, 0, N) &= \{(q_1, NN)\} \\ \delta_1(q_2, 1, N) &= \{(q_2, \varepsilon)\}\end{aligned}$$

- DKA $M_2 = (\{p_1, p_2, p_3\}, \{0, 1\}, \delta_2, p_1, \{p_3\})$
 - strings of language $L(M_2)$ contain at least two symbols 1

$$\begin{aligned}\delta_2(p_1, 0) &= p_1 \\ \delta_2(p_2, 0) &= p_2 \\ \delta_2(p_3, 0) &= p_3\end{aligned}$$

$$\begin{aligned}\delta_2(p_1, 1) &= p_2 \\ \delta_2(p_2, 1) &= p_3 \\ \delta_2(p_3, 1) &= p_3\end{aligned}$$

-
- 1) $Q' = \{[p_1, q_1], [p_1, q_2], [p_2, q_1], [p_2, q_2], [p_3, q_1], [p_3, q_2]\}$
 - 2) $q'_0 = [p_1, q_1]$
 - 3) $F' = \{ [p_3, q_2] \}$

Properties of Context-Free Languages

$$\delta_1(q_1, 0, K) = \{(q_1, NK)\}$$

$$\delta_1(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_1(q_1, 0, N) = \{(q_1, NN)\}$$

$$\delta_1(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_2(p_1, 0) = p_1$$

$$\delta_2(p_2, 0) = p_2$$

$$\delta_2(p_3, 0) = p_3$$

$$\delta_2(p_1, 1) = p_2$$

$$\delta_2(p_2, 1) = p_3$$

$$\delta_2(p_3, 1) = p_3$$

Properties of Context-Free Languages

$$\delta_1(q_1, 0, K) = \{(q_1, NK)\}$$

$$\delta_1(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_1(q_1, 0, N) = \{(q_1, NN)\}$$

$$\delta_1(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_2(p_1, 0) = p_1$$

$$\delta_2(p_2, 0) = p_2$$

$$\delta_2(p_3, 0) = p_3$$

$$\delta_2(p_1, 1) = p_2$$

$$\delta_2(p_2, 1) = p_3$$

$$\delta_2(p_3, 1) = p_3$$

Properties of Context-Free Languages

$$\delta_1(q_1, 0, K) = \{(q_1, NK)\}$$

$$\delta_1(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_1(q_1, 0, N) = \{(q_1, NN)\}$$

$$\delta_1(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_2(p_1, 0) = p_1$$

$$\delta_2(p_2, 0) = p_2$$

$$\delta_2(p_3, 0) = p_3$$

$$\delta_2(p_1, 1) = p_2$$

$$\delta_2(p_2, 1) = p_3$$

$$\delta_2(p_3, 1) = p_3$$

Properties of Context-Free Languages

$$\delta_1(q_1, 0, K) = \{(q_1, NK)\}$$

$$\delta_1(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_1(q_1, 0, N) = \{(q_1, NN)\}$$

$$\delta_1(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_2(p_1, 0) = p_1$$

$$\delta_2(p_2, 0) = p_2$$

$$\delta_2(p_3, 0) = p_3$$

$$\delta_2(p_1, 1) = p_2$$

$$\delta_2(p_2, 1) = p_3$$

$$\delta_2(p_3, 1) = p_3$$

$$\delta'([p_1, q_1], 0, K) = \{([p_1, q_1], NK)\}$$

Properties of Context-Free Languages

$$\delta_1(q_1, 0, K) = \{(q_1, NK)\}$$

$$\delta_1(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_2(p_1, 0) = p_1$$

$$\delta_2(p_2, 0) = p_2$$

$$\delta_2(p_3, 0) = p_3$$

$$\delta_1(q_1, 0, N) = \{(q_1, NN)\}$$

$$\delta_1(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_2(p_1, 1) = p_2$$

$$\delta_2(p_2, 1) = p_3$$

$$\delta_2(p_3, 1) = p_3$$

$$\delta'([p_1, q_1], 0, K) = \{([p_1, q_1], NK)\}$$

Properties of Context-Free Languages

$$\delta_1(q_1, 0, K) = \{(q_1, NK)\}$$

$$\delta_1(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_1(q_1, 0, N) = \{(q_1, NN)\}$$

$$\delta_1(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_2(p_1, 0) = p_1$$

$$\delta_2(p_2, 0) = p_2$$

$$\delta_2(p_3, 0) = p_3$$

$$\delta_2(p_1, 1) = p_2$$

$$\delta_2(p_2, 1) = p_3$$

$$\delta_2(p_3, 1) = p_3$$

$$\delta'([p_1, q_1], 0, K) = \{([p_1, q_1], NK)\}$$

Properties of Context-Free Languages

$$\delta_1(q_1, 0, K) = \{(q_1, NK)\}$$

$$\delta_1(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_1(q_1, 0, N) = \{(q_1, NN)\}$$

$$\delta_1(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_2(p_1, 0) = p_1$$

$$\delta_2(p_2, 0) = p_2$$

$$\delta_2(p_3, 0) = p_3$$

$$\delta_2(p_1, 1) = p_2$$

$$\delta_2(p_2, 1) = p_3$$

$$\delta_2(p_3, 1) = p_3$$

$$\delta'([p_1, q_1], 0, K) = \{([p_1, q_1], NK)\}$$

$$\delta'([p_1, q_1], 0, N) = \{([p_1, q_1], NN)\}$$

Properties of Context-Free Languages

$$\delta_1(a_1, 0, K) = \{(a_1, NK)\}$$

$$\delta_1(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_1(q_1, 0, N) = \{(q_1, NN)\}$$

$$\delta_1(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_2(p_1, 0) = p_1$$

$$\delta_2(p_2, 0) = p_2$$

$$\delta_2(p_3, 0) = p_3$$

$$\delta_2(p_1, 1) = p_2$$

$$\delta_2(p_2, 1) = p_3$$

$$\delta_2(p_3, 1) = p_3$$

$$\delta'([p_1, q_1], 0, K) = \{([p_1, q_1], NK)\}$$

$$\delta'([p_1, q_1], 0, N) = \{([p_1, q_1], NN)\}$$

Properties of Context-Free Languages

$$\delta_1(q_1, 0, K) = \{(q_1, NK)\}$$

$$\delta_1(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_1(q_1, 0, N) = \{(q_1, NN)\}$$

$$\delta_1(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_2(p_1, 0) = p_1$$

$$\delta_2(p_2, 0) = p_2$$

$$\delta_2(p_3, 0) = p_3$$

$$\delta_2(p_1, 1) = p_2$$

$$\delta_2(p_2, 1) = p_3$$

$$\delta_2(p_3, 1) = p_3$$

$$\delta'([p_1, q_1], 0, K) = \{([p_1, q_1], NK)\}$$

$$\delta'([p_1, q_1], 0, N) = \{([p_1, q_1], NN)\}$$

Properties of Context-Free Languages

$$\delta_1(q_1, 0, K) = \{(q_1, NK)\}$$

$$\delta_1(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_1(q_1, 0, N) = \{(q_1, NN)\}$$

$$\delta_1(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_2(p_1, 0) = p_1$$

$$\delta_2(p_2, 0) = p_2$$

$$\delta_2(p_3, 0) = p_3$$

$$\delta_2(p_1, 1) = p_2$$

$$\delta_2(p_2, 1) = p_3$$

$$\delta_2(p_3, 1) = p_3$$

$$\delta'([p_1, q_1], 0, K) = \{([p_1, q_1], NK)\}$$

$$\delta'([p_1, q_1], 0, N) = \{([p_1, q_1], NN)\}$$

$$\delta'([p_1, q_1], 1, N) = \{([p_2, q_2], \varepsilon)\}$$

Properties of Context-Free Languages

$$\delta_1(q_1, 0, K) = \{(q_1, NK)\}$$

$$\delta_1(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_1(a_1, 0, N) = \{(a_1, NN)\}$$

$$\delta_1(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_2(p_1, 0) = p_1$$

$$\delta_2(p_2, 0) = p_2$$

$$\delta_2(p_3, 0) = p_3$$

$$\delta_2(p_1, 1) = p_2$$

$$\delta_2(p_2, 1) = p_3$$

$$\delta_2(p_3, 1) = p_3$$

$$\delta'([p_1, q_1], 0, K) = \{([p_1, q_1], NK)\}$$

$$\delta'([p_1, q_1], 0, N) = \{([p_1, q_1], NN)\}$$

$$\delta'([p_1, q_1], 1, N) = \{([p_2, q_2], \varepsilon)\}$$

Properties of Context-Free Languages

$$\delta_1(q_1, 0, K) = \{(q_1, NK)\}$$

$$\delta_1(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_1(q_1, 0, N) = \{(q_1, NN)\}$$

$$\delta_1(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_2(p_1, 0) = p_1$$

$$\delta_2(p_2, 0) = p_2$$

$$\delta_2(p_3, 0) = p_3$$

$$\delta_2(p_1, 1) = p_2$$

$$\delta_2(p_2, 1) = p_3$$

$$\delta_2(p_3, 1) = p_3$$

$$\delta'([p_1, q_1], 0, K) = \{([p_1, q_1], NK)\}$$

$$\delta'([p_1, q_1], 0, N) = \{([p_1, q_1], NN)\}$$

$$\delta'([p_1, q_1], 1, N) = \{([p_2, q_2], \varepsilon)\}$$

Properties of Context-Free Languages

$$\delta_1(q_1, 0, K) = \{(q_1, NK)\}$$

$$\delta_1(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_1(q_1, 0, N) = \{(q_1, NN)\}$$

$$\delta_1(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_2(p_1, 0) = p_1$$

$$\delta_2(p_2, 0) = p_2$$

$$\delta_2(p_3, 0) = p_3$$

$$\delta_2(p_1, 1) = p_2$$

$$\delta_2(p_2, 1) = p_3$$

$$\delta_2(p_3, 1) = p_3$$

$$\delta'([p_1, q_1], 0, K) = \{([p_1, q_1], NK)\}$$

$$\delta'([p_1, q_1], 0, N) = \{([p_1, q_1], NN)\}$$

$$\delta'([p_1, q_1], 1, N) = \{([p_2, q_2], \varepsilon)\}$$

$$\delta'([p_2, q_2], 1, N) = \{([p_3, q_2], \varepsilon)\}$$

Properties of Context-Free Languages

$$\delta_1(q_1, 0, K) = \{(q_1, NK)\}$$

$$\delta_1(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_1(a_1, 0, N) = \{(a_1, NN)\}$$

$$\delta_1(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_2(p_1, 0) = p_1$$

$$\delta_2(p_2, 0) = p_2$$

$$\delta_2(p_3, 0) = p_3$$

$$\delta_2(p_1, 1) = p_2$$

$$\delta_2(p_2, 1) = p_3$$

$$\delta_2(p_3, 1) = p_3$$

$$\delta'([p_1, q_1], 0, K) = \{([p_1, q_1], NK)\}$$

$$\delta'([p_1, q_1], 0, N) = \{([p_1, q_1], NN)\}$$

$$\delta'([p_1, q_1], 1, N) = \{([p_2, q_2], \varepsilon)\}$$

$$\delta'([p_2, q_2], 1, N) = \{([p_3, q_2], \varepsilon)\}$$

Properties of Context-Free Languages

$$\delta_1(q_1, 0, K) = \{(q_1, NK)\}$$

$$\delta_1(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_1(q_1, 0, N) = \{(q_1, NN)\}$$

$$\delta_1(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_2(p_1, 0) = p_1$$

$$\delta_2(p_2, 0) = p_2$$

$$\delta_2(p_3, 0) = p_3$$

$$\delta_2(p_1, 1) = p_2$$

$$\delta_2(p_2, 1) = p_3$$

$$\delta_2(p_3, 1) = p_3$$

$$\delta'([p_1, q_1], 0, K) = \{([p_1, q_1], NK)\}$$

$$\delta'([p_1, q_1], 0, N) = \{([p_1, q_1], NN)\}$$

$$\delta'([p_1, q_1], 1, N) = \{([p_2, q_2], \varepsilon)\}$$

$$\delta'([p_2, q_2], 1, N) = \{([p_3, q_2], \varepsilon)\}$$

Properties of Context-Free Languages

$$\delta_1(q_1, 0, K) = \{(q_1, NK)\}$$

$$\delta_1(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_1(q_1, 0, N) = \{(q_1, NN)\}$$

$$\delta_1(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_2(p_1, 0) = p_1$$

$$\delta_2(p_2, 0) = p_2$$

$$\delta_2(p_3, 0) = p_3$$

$$\delta_2(p_1, 1) = p_2$$

$$\delta_2(p_2, 1) = p_3$$

$$\delta_2(p_3, 1) = p_3$$

$$\delta'([p_1, q_1], 0, K) = \{([p_1, q_1], NK)\}$$

$$\delta'([p_1, q_1], 0, N) = \{([p_1, q_1], NN)\}$$

$$\delta'([p_1, q_1], 1, N) = \{([p_2, q_2], \varepsilon)\}$$

$$\delta'([p_2, q_2], 1, N) = \{([p_3, q_2], \varepsilon)\}$$

$$\delta'([p_3, q_2], 1, N) = \{([p_3, q_2], \varepsilon)\}$$

Properties of Context-Free Languages

$$\delta_1(q_1, 0, K) = \{(q_1, NK)\}$$

$$\delta_1(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_1(q_1, 0, N) = \{(q_1, NN)\}$$

$$\delta_1(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_2(p_1, 0) = p_1$$

$$\delta_2(p_2, 0) = p_2$$

$$\delta_2(p_3, 0) = p_3$$

$$\delta_2(p_1, 1) = p_2$$

$$\delta_2(p_2, 1) = p_3$$

$$\delta_2(p_3, 1) = p_3$$

$$\delta'([p_1, q_1], 0, K) = \{([p_1, q_1], NK)\}$$

$$\delta'([p_1, q_1], 0, N) = \{([p_1, q_1], NN)\}$$

$$\delta'([p_1, q_1], 1, N) = \{([p_2, q_2], \varepsilon)\}$$

$$\delta'([p_2, q_2], 1, N) = \{([p_3, q_2], \varepsilon)\}$$

$$\delta'([p_3, q_2], 1, N) = \{([p_3, q_2], \varepsilon)\}$$

- PA M'

Properties of Context-Free Languages

$$\delta_1(q_1, 0, K) = \{(q_1, NK)\}$$

$$\delta_1(q_1, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_1(q_1, 0, N) = \{(q_1, NN)\}$$

$$\delta_1(q_2, 1, N) = \{(q_2, \varepsilon)\}$$

$$\delta_2(p_1, 0) = p_1$$

$$\delta_2(p_2, 0) = p_2$$

$$\delta_2(p_3, 0) = p_3$$

$$\delta_2(p_1, 1) = p_2$$

$$\delta_2(p_2, 1) = p_3$$

$$\delta_2(p_3, 1) = p_3$$

$$\delta'([p_1, q_1], 0, K) = \{([p_1, q_1], NK)\}$$

$$\delta'([p_1, q_1], 0, N) = \{([p_1, q_1], NN)\}$$

$$\delta'([p_1, q_1], 1, N) = \{([p_2, q_2], \varepsilon)\}$$

$$\delta'([p_2, q_2], 1, N) = \{([p_3, q_2], \varepsilon)\}$$

$$\delta'([p_3, q_2], 1, N) = \{([p_3, q_2], \varepsilon)\}$$

- PA M'

- accepts language $L_3 = L(M_1) \cap L(M_2) = \{0^n 1^m \mid n \geq 2, m \geq 2, m \leq n\}$

Properties of Context-Free Languages

Properties of Context-Free Languages

String 00011

Properties of Context-Free Languages

String 00011

DKA M_2

Properties of Context-Free Languages

String 00011

DKA M_2

$$\begin{aligned}\delta(p_1, 00011) &= \delta(p_1, 0011) = \delta(p_1, 011) = \delta(p_1, 11) = \\ \delta(p_2, 1) &= p_3 \text{ i } p_3 \in F_2\end{aligned}$$

Properties of Context-Free Languages

String 00011

DKA M_2

$$\begin{aligned}\delta(p_1, 00011) &= \delta(p_1, 0011) = \delta(p_1, 011) = \delta(p_1, 11) = \\ \delta(p_2, 1) &= p_3 \text{ i } p_3 \in F_2\end{aligned}$$

PA M_1

Properties of Context-Free Languages

String 00011

DKA M_2

$$\begin{aligned}\delta(p_1, 00011) &= \delta(p_1, 0011) = \delta(p_1, 011) = \delta(p_1, 11) = \\ \delta(p_2, 1) &= p_3 \text{ i } p_3 \in F_2\end{aligned}$$

PA M_1

$$\begin{aligned}(q_1, 00011, K) \succ (q_1, 0011, NK) \succ (q_1, 011, NNK) \succ \\ (q_1, 11, NNNK) \succ (q_2, 1, NNK) \succ (q_2, \varepsilon, NKX_0) \text{ i } q_2 \in F_1\end{aligned}$$

Properties of Context-Free Languages

String 00011

DKA M_2

$$\begin{aligned}\delta(p_1, 00011) &= \delta(p_1, 0011) = \delta(p_1, 011) = \delta(p_1, 11) = \\ \delta(p_2, 1) &= p_3 \text{ i } p_3 \in F_2\end{aligned}$$

PA M_1

$$\begin{aligned}(q_1, 00011, K) \succ (q_1, 0011, NK) \succ (q_1, 011, NNK) \succ \\ (q_1, 11, NNNK) \succ (q_2, 1, NNK) \succ (q_2, \varepsilon, NKX_0) \text{ i } q_2 \in F_1\end{aligned}$$

PA M'

Properties of Context-Free Languages

String 00011

DKA M_2

$$\begin{aligned}\delta(p_1, 00011) &= \delta(p_1, 0011) = \delta(p_1, 011) = \delta(p_1, 11) = \\ \delta(p_2, 1) &= p_3 \text{ i } p_3 \in F_2\end{aligned}$$

PA M_1

$$\begin{aligned}(q_1, 00011, K) &\succ (q_1, 0011, NK) \succ (q_1, 011, NNK) \succ \\ (q_1, 11, NNNK) &\succ (q_2, 1, NNK) \succ (q_2, \varepsilon, NKX_0) \text{ i } q_2 \in F_1\end{aligned}$$

PA M'

$$\begin{aligned}([p_1, q_1], 00011, K) &\succ ([p_1, q_1], 0011, NK) \succ ([p_1, q_1], 011, NNK) \succ \\ ([p_1, q_1], 11, NNNK) &\succ ([p_2, q_2], 1, NNK) \succ \\ ([p_3, q_2], \varepsilon, NK) &\text{ i } [p_3, q_2] \in F'\end{aligned}$$

Lecture 10

3.2.3 PA and Context-free Grammar

3.3 PROPERTIES OF CONTEXT-FREE LANGUAGES

3.3.1 Closure Properties of Context-Free Languages


3.3.2 Pumping Lemma

Pumping Lemma


Pumping Lemma

s


Pumping Lemma




Pumping Lemma




Pumping Lemma



Pumping Lemma




Pumping Lemma




Pumping Lemma

Number of parse tree inner nodes > Number of grammar variables




Pumping Lemma

Number of parse tree inner nodes > Number of grammar variables




Pumping Lemma

Number of parse tree inner nodes > Number of grammar variables




Pumping Lemma

Number of parse tree inner nodes > Number of grammar variables




Pumping Lemma

Number of parse tree inner nodes > Number of grammar variables




Pumping Lemma

Number of parse tree inner nodes > Number of grammar variables




Pumping Lemma

Number of parse tree inner nodes > Number of grammar variables



Pumping Lemma

Number of parse tree inner nodes > Number of grammar variables



Pumping Lemma

Pumping Lemma

$$A \xrightarrow[G]{*} w$$

$$A \xrightarrow[G]{*} v \underline{A} x$$

Pumping Lemma

$$A \xrightarrow[G]{*} w$$

$$A \xrightarrow[G]{*} v \underline{A} x$$

s

Pumping Lemma

$$A \xrightarrow[G]{*} w$$

$$A \xrightarrow[G]{*} v \underline{A} x$$

$$S \xrightarrow{*} G$$

Pumping Lemma

$$A \xrightarrow[G]{*} w$$

$$A \xrightarrow[G]{*} v \underline{A} x$$

$$S \xrightarrow[G]{*} u \underline{A} y$$

Pumping Lemma

$$A \xrightarrow[G]{*} w$$

$$A \xrightarrow[G]{*} v \underline{A} x$$

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*}$$

Pumping Lemma

$$A \xrightarrow[G]{*} w$$

$$A \xrightarrow[G]{*} v \underline{A} x$$

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*}$$

u w y

Pumping Lemma

$$A \xrightarrow[G]{*} w$$

$$A \xrightarrow[G]{*} v \underline{A} x$$

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*}$$

u w y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*}$$

Pumping Lemma

$$A \xrightarrow[G]{*} w$$

$$A \xrightarrow[G]{*} v \underline{A} x$$

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*}$$

u w y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u \underline{v} \underline{A} x y$$

Pumping Lemma

$$A \xrightarrow[G]{*} w$$

$$A \xrightarrow[G]{*} v \underline{A} x$$

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*}$$

u w y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u \underline{v} \underline{A} x y \xrightarrow[G]{*}$$

Pumping Lemma

$$A \xrightarrow[G]{*} w$$

$$A \xrightarrow[G]{*} v \underline{A} x$$

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*}$$

u w y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u \underline{v} \underline{A} x y \xrightarrow[G]{*}$$

u v w x y

Pumping Lemma

$$A \xrightarrow[G]{*} w$$

$$A \xrightarrow[G]{*} v \underline{A} x$$

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*}$$

u w y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u \underline{v} \underline{A} x y \xrightarrow[G]{*}$$

u v w x y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u \underline{v} \underline{A} x y \xrightarrow[G]{*}$$

Pumping Lemma

$$A \xrightarrow[G]{*} w$$

$$A \xrightarrow[G]{*} v \underline{A} x$$

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*}$$

u w y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u \underline{v} \underline{A} x y \xrightarrow[G]{*}$$

u v w x y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u \underline{v} \underline{A} x y \xrightarrow[G]{*} u \underline{v} \underline{v} \underline{A} x x y$$

Pumping Lemma

$$A \xrightarrow[G]{*} w$$

$$A \xrightarrow[G]{*} v \underline{A} x$$

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*}$$

u w y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u \underline{v} \underline{A} x y \xrightarrow[G]{*}$$

u v w x y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u \underline{v} \underline{A} x y \xrightarrow[G]{*} u \underline{v} \underline{v} \underline{A} x x y \xrightarrow[G]{*}$$

Pumping Lemma

$$A \xrightarrow[G]{*} w$$

$$A \xrightarrow[G]{*} v \underline{A} x$$

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*}$$

u w y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u v \underline{A} x y \xrightarrow[G]{*}$$

u v w x y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u v \underline{A} x y \xrightarrow[G]{*} u v v \underline{A} x x y \xrightarrow[G]{*}$$

u v v w x x y

Pumping Lemma

$$A \xrightarrow[G]{*} w$$

$$A \xrightarrow[G]{*} v \underline{A} x$$

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*}$$

u w y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u v \underline{A} x y \xrightarrow[G]{*}$$

u v w x y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u v \underline{A} x y \xrightarrow[G]{*} u v v \underline{A} x x y \xrightarrow[G]{*} \boxed{u v v w x x y}$$

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u v \underline{A} x y \xrightarrow[G]{*}$$

Pumping Lemma

$$A \xrightarrow[G]{*} w$$

$$A \xrightarrow[G]{*} v \underline{A} x$$

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*}$$

u w y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u \underline{v} \underline{A} x y \xrightarrow[G]{*}$$

u v w x y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u \underline{v} \underline{A} x y \xrightarrow[G]{*} u \underline{v} \underline{v} \underline{A} x x y \xrightarrow[G]{*}$$

u v v w x x y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u \underline{v} \underline{A} x y \xrightarrow[G]{*} u \underline{v}^i \underline{A} x^i y$$

Pumping Lemma

$$A \xrightarrow[G]{*} w$$

$$A \xrightarrow[G]{*} v \underline{A} x$$

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*}$$

u w y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u \underline{v} \underline{A} x y \xrightarrow[G]{*}$$

u v w x y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u \underline{v} \underline{A} x y \xrightarrow[G]{*} u \underline{v} \underline{v} \underline{A} x x y \xrightarrow[G]{*}$$

u v v w x x y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u \underline{v} \underline{A} x y \xrightarrow[G]{*} u \underline{v}^i \underline{A} x^i y \xrightarrow[G]{*}$$

Pumping Lemma

$$A \xrightarrow[G]{*} w$$

$$A \xrightarrow[G]{*} v \underline{A} x$$

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*}$$

u w y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u \underline{v} \underline{A} x y \xrightarrow[G]{*}$$

u v w x y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u \underline{v} \underline{A} x y \xrightarrow[G]{*} u \underline{v} \underline{v} \underline{A} x x y \xrightarrow[G]{*}$$

u v v w x x y

$$S \xrightarrow[G]{*} u \underline{A} y \xrightarrow[G]{*} u \underline{v} \underline{A} x y \xrightarrow[G]{*} u \underline{v}^i \underline{A} x^i y \xrightarrow[G]{*}$$

u vⁱ w xⁱ y

Pumping Lemma

Pumping Lemma

Proof goal:

Language $L = \{ a^i b^i c^i \mid i \geq 1\}$ – **is not a CFL**

Pumping Lemma

Proof goal:

Language $L = \{ a^i b^i c^i \mid i \geq 1\}$ – ***is not a CFL***

Assumption:

L is a context-free language

Pumping Lemma

Proof goal:

Language $L = \{ a^i b^i c^i \mid i \geq 1\}$ – **is not a CFL**

Assumption:

L is a context-free language

Constant:

n

Pumping Lemma

Proof goal:

Language $L = \{ a^i b^i c^i \mid i \geq 1\}$ – **is not a CFL**

Assumption:

L is a context-free language

Constant:

n

String:

$z = a^n b^n c^n, \quad |z| \geq n$

Pumping Lemma

Proof goal:

Language $L = \{ a^i b^i c^i \mid i \geq 1\}$ – **is not a CFL**

Assumption:

L is a context-free language

Constant:

n

String:

$z = a^n b^n c^n, \quad |z| \geq n$

z is broken into:

$u v w x y$

Pumping Lemma

Proof goal:

Language $L = \{ a^i b^i c^i \mid i \geq 1\}$ – **is not a CFL**

Assumption:

L is a context-free language

Constant:

n

String:

$z = a^n b^n c^n, \quad |z| \geq n$

z is broken into:

$u v w x y$

It is necessary to determine: substrings v and x

Pumping Lemma

Proof goal:

Language $L = \{ a^i b^i c^i \mid i \geq 1\}$ – **is not a CFL**

Assumption:

L is a context-free language

Constant:

n

String:

$z = a^n b^n c^n, \quad |z| \geq n$

z is broken into:

$u v w x y$

It is necessary to determine: substrings v and x

in the string $a^n b^n c^n$

Pumping Lemma

- Proof goal:** Language $L = \{ a^i b^i c^i \mid i \geq 1\}$ – **is not a CFL**
- Assumption:** L is a context-free language
- Constant:** n
- String:** $z = a^n b^n c^n, \quad |z| \geq n$
- z is broken into:** $u v w x y$
- It is necessary to determine:** substrings v and x
in the string $a^n b^n c^n$
that can be repeated (pumped) any number of times

Pumping Lemma

Pumping Lemma

a^n

b^n

c^n

Pumping Lemma

a^n

b^n

c^n

u

v

w

x

y

Pumping Lemma

$$|vwx| \leq n$$

aⁿ

bⁿ

cⁿ

u

v


w

x

y


Pumping Lemma

$$|vwx| \leq n$$



Pumping Lemma


$$|vwx| \leq n$$



Strings v i x contain exclusively symbols b

Pumping Lemma

$$|vwx| \leq n$$




Strings v i x contain exclusively symbols b

String uwy

Pumping Lemma

$$|vwx| \leq n$$




Strings v i x contain exclusively symbols b

String uwy

Pumping Lemma

$$|vwx| \leq n$$




Strings v i x contain exclusively symbols b

String uwy

Pumping Lemma

$$|vwx| \leq n$$




Strings v i x contain exclusively symbols b

String uwy

n symbols a

Pumping Lemma

$$|vwx| \leq n$$



Strings v i x contain exclusively symbols b


String uwy

n symbols a

n symbols c

Pumping Lemma

$$|vwx| \leq n$$



Strings v i x contain exclusively symbols b

String uwy


n symbols a

n symbols c

less then n symbols b , because $|vx| \geq 1$

Pumping Lemma

$$|vwx| \leq n$$



Strings v i x contain exclusively symbols b

String uwy

n symbols a

n symbols c

less then n symbols b , because $|vx| \geq 1$

String uwy does not have form $a^j b^j c^j$

Pumping Lemma

$$|vwx| \leq n$$

aⁿ

bⁿ

cⁿ

u

v



w

x

y


Pumping Lemma

$$|vwx| \leq n$$




Pumping Lemma

$$|vwx| \leq n$$




Pumping Lemma

$$|vwx| \leq n$$



Pumping Lemma

$$|vwx| \leq n$$



Pumping Lemma

$$|vwx| \leq n$$

aⁿ

bⁿ

cⁿ

u

v

w

x

y