



Search

☒ Repository ☐ Web

[Google](#)

[View ALL Data Sets](#)

# Human Activity Recognition Using Smartphones Data Set

Download: [Data Folder](#), [Data Set Description](#)

**Abstract:** Human Activity Recognition database built from the recordings of 30 subjects performing activities of daily living (ADL) while carrying a waist-mounted smartphone with embedded inertial sensors.

Data Set Characteristics:	Multivariate, Time-Series	Number of Instances:	10299	Area:	Computer
Attribute Characteristics:	N/A	Number of Attributes:	561	Date Donated	2012-12-10
Associated Tasks:	Classification, Clustering	Missing Values?	N/A	Number of Web Hits:	117608

## Source:

Jorge L. Reyes-Ortiz, Davide Anguita, Alessandro Ghio, Luca Oneto.  
Smartlab - Non Linear Complex Systems Laboratory  
DITEN - Università degli Studi di Genova, Genoa I-16145, Italy.  
[activityrecognition '@' smartlab.ws](mailto:activityrecognition '@' smartlab.ws)  
[www.smartlab.ws](http://www.smartlab.ws)

## Data Set Information:

The experiments have been carried out with a group of 30 volunteers within an age bracket of 19-48 years. Each person performed six activities (WALKING, WALKING\_UPSTAIRS, WALKING\_DOWNSTAIRS, SITTING, STANDING, LAYING) wearing a smartphone (Samsung Galaxy S II) on the waist. Using its embedded accelerometer and gyroscope, we captured 3-axial linear acceleration and 3-axial angular velocity at a constant rate of 50Hz. The experiments have been video-recorded to label the data manually. The obtained dataset has been randomly partitioned into two sets, where 70% of the volunteers was selected for generating the training data and 30% the test data.

The sensor signals (accelerometer and gyroscope) were pre-processed by applying noise filters and then sampled in fixed-width sliding windows of 2.56 sec and 50% overlap (128 readings/window). The sensor acceleration signal, which has gravitational and body motion components, was separated using a Butterworth low-pass filter into body acceleration and gravity. The gravitational force is assumed to have only low frequency components, therefore a filter with 0.3 Hz cutoff frequency was used. From each window, a vector of features was obtained by calculating variables from the time and frequency domain.

Check the README.txt file for further details about this dataset.

## Attribute Information:

- For each record in the dataset it is provided:
- Triaxial acceleration from the accelerometer (total acceleration) and the estimated body acceleration.
  - Triaxial Angular velocity from the gyroscope.
  - A 561-feature vector with time and frequency domain variables.
  - Its activity label.
  - An identifier of the subject who carried out the experiment.

## Relevant Papers:

N/A

## Citation Request:

[1] Davide Anguita, Alessandro Ghio, Luca Oneto, Xavier Parra and Jorge L. Reyes-Ortiz. Human Activity Recognition on Smartphones using a Multiclass Hardware-Friendly Support Vector Machine. International Workshop of Ambient Assisted Living (IWAAL 2012). Vitoria-Gasteiz, Spain. Dec 2012

Supported By:



In Collaboration With:

