# FemboyEngine2D Complete Reference Manual

Architecture, rendering, ECS, the animation/AI canvases with blend-cycle and PIE contracts, DOD pipelines and production distribution

Version 0.3.0-alpha.1 (Alpha) - 2026-11-05 - English

## Contents


- 1. Scope, conformance and engine rules
- 2. Building, targets and compiler flags
- 3. Core value types, FORCEINLINE and the cast family
- 4. FrameArena: the only frame allocator
- 5. JobSystem and per-thread diagnostics
- 6. ECS, scheduling and snapshots
- 7. RHI, render items and frame statistics
- 8. Materials: cooked graphs, the pipeline cache and the shipped path
- 9. Physics: Box2D v3, joints, cloth and SdfCollisionSystem
- 10. NetRollbackSession: deterministic rollback
- 11. Audio: mixer, DSP graph, limiter
- 12. PinkUI and WidgetCanvasSystem
- 13. Accessibility kernel (BlindMode, DeafMode, FlashGuard)
- 14. Asset pipeline, VFS and localization
- 15. Platform services: Steam, Epic Games Store, GOG
- 16. Editor: dashboard, fonts, LogBoy, Scene Diagnostics
- 17. Step-by-step: a game from an empty folder
- 18. Testing, style gate and release checklist
- 19. Open work
- 20. GOG Galaxy: provider, shim ABI and PostUpdate systems
- 21. Font pipeline: fby_fontc, .fbyfont and the stable buffer
- 22. Cloth render path: from Verlet vertices to one indirect draw
- 23. Atmosphere: weather context, fBm wind and GPU rain with SDF splashes
- 24. ECS by composition: a 2D shooter without inheritance
- 25. Multi-Draw Indirect and Texture Cooking in production
- 26. Repository layout, CMake targets and the gates
- 27. Threading contract: RHI, the OS main loop and TTS
- 28. The 32-bit DrawBatch pipeline: end of the 65,536-texture ceiling
- 29. Atomic VFS font hot reload and the strict MountFonts contract
- 30. TTS: the main-thread contract and localized voice fallback
- 31. State-Driven Gameplay: AnimGraph, StateTree AI and the Animation Graph Canvas
- 32. Advanced AAA DOD Pipelines: Virtual Texturing, Component Change Masks, Relevance Grids, and Audio Buses
- 33. Production Distribution: Encryption, LZMA Compression, and the Steam/EGS/GOG Release Checklist

- 34. SystemGraph: the parallel scheduling contract, then the blend-cycle contract
- 35. Box2D rollback teardown, then the PIE animation hand-off
- 36. Release gate
- 37. Profiling cache misses and vectorisation toward 8000+ FPS
- 38. Materials in the engine: cook, cache and the frame
- 39. Appendix A - generated symbol index
- 40. Appendix B - macros and platform defines

## 1. Scope, conformance and engine rules

This manual specifies the public surface of FemboyEngine2D: every header under Source/Engine and the editor infrastructure that a host links against. It is written against the release-candidate tree, so a symbol described here exists in the headers that ship with that tree, and the appendix index is generated from those headers on every run.

The engine targets C++26 with GCC 16 or newer and Clang 19 or newer; the Windows release candidate is built with clang-cl against the MSVC standard library. Four rules are load bearing and every public API is designed around them:

- Simulation state is plain, trivially copyable data. No virtual calls, no owning pointers and no std::string belong in a component, snapshot or network payload.
- Hot paths do not allocate. Frame scratch memory comes from FrameArena, logs go through fixed char buffers, and callbacks are function pointers plus void*, never std::function.
- Determinism is a property of the data, not of the scheduler. Every subsystem exposes a checksummed image, and NetRollbackSession can only replay what it can reproduce byte for byte.
- No RTTI in engine code: dynamic_cast and typeid are rejected by the style gate. Cast<> walks stable type ids instead (see section 3).

*The style gate (Source/Tools/Dev/CheckStyle.py) enforces the naming and structure rules: PascalCase file stems, Allman braces, braced control bodies, In-prefixed parameters, Scoped-prefixed locals, no trailing line comments and no Cyrillic in engine sources.*

## 2. Building, targets and compiler flags

One CMake tree produces three kinds of artefact: the engine static library (FemboyEngine2D::Engine), the editor library and application (FemboyEngine2D::Editor), and the offline tools. A shipped game links the engine only; Dear ImGui, ImGuizmo, ImPlot and the TOML writer never enter a shipping target.

| CMake option | Default | Effect |
|---|---|---|
| **FBY_BUILD_EDITOR** | ON | Builds fby_editor, the editor app and the panel plugins. |
| **FBY_BUILD_TESTS** | OFF | Builds the ctest suite under Source/Tests. |
| **FBY_BUILD_TOOLS** | ON | FempakCooker, LocTool, SceneTool, ShaderCompiler, AotCompiler. |
| **FBY_BUILD_PLATFORM_PROVIDERS** | ON | Steam and Epic Games Store provider plugins. |
| **FBY_RHI_BACKEND** | auto | auto, vulkan, metal or null. auto selects per platform. |

```
cmake -S . -B build -G Ninja -DCMAKE_BUILD_TYPE=RelWithDebInfo \
      -DFBY_BUILD_TESTS=ON -DFBY_BUILD_EDITOR=ON
```

```
cmake --build build --target fby_editor
ctest --test-dir build --output-on-failure
python Source/Tools/Dev/CheckStyle.py
```

The compiler wrapper (cmake/FbyCompiler.cmake) owns the C++26 flag, the warning set and the sanitizer switches. Do not add flags per target: a target that needs a different dialect is a target that should not exist.

## 3. Core value types, FORCEINLINE and the cast family

Definitions.hpp is the contract header of the engine. It supplies the export macros, the assertion macros (FBY_ASSERT, FBY_VERIFY, FBY_UNREACHABLE), the stable TypeId machinery, the cast family and the component registration macros. Every other header includes it, directly or transitively.

```
#if defined(_MSC_VER)
#define FORCEINLINE __forceinline
#elif defined(__GNUC__) || defined(__clang__)
#define FORCEINLINE inline __attribute__((always_inline))
#else
#define FORCEINLINE inline
#endif
```

FORCEINLINE is the only inlining spelling in public headers. It is used for accessors, hot arithmetic and template casts; it never replaces a measured optimisation. The three families are:

| Symbol | Contract |
|---|---|
| **FemCast<To>(value)** | Unchecked static_cast with reference collapsing. Use when the concrete type is proven by construction (factory output, storage tag). No runtime cost. |
| **Cast<To>(object)** | Checked cast. Upcast is a compile-time static_cast; downcast compares the object's GetTypeId() against StableTypeId<To>() and its registered parent chain; unrelated types fail to compile. Returns nullptr on a mismatch, never throws, never uses RTTI. |
| **CastComponent<To>(registry, entity)** | ECS spelling of Cast<>: EnTT proves the component type at compile time and the registry validates the entity. Returns nullptr when the entity lacks the component. |

```
// Downcast through the stable type table, not through RTTI.
Fby::TypeObject* base = factory.Create("Sprite");
if (Fby::Sprite* sprite = Fby::Cast<Fby::Sprite>(base))
{
    sprite->Animate(dt);
}
```

```
// Registration binds Sprite to TypeObject and derives its stable id.
FBY_REGISTER_TYPE(Fby::Sprite, Fby::TypeObject);
```

StableTypeId<T>() is a consteval FNV-1a of the type's registered name (or the compiler signature when no name is pinned). A type that changes its registered name changes its id, which is why component names are part of the serialized schema and why Snapshot v4 stores a LayoutHash next to the name.

## 4. FrameArena: the only frame allocator

FrameArena is a bump pointer over caller-owned storage. It is reset at the start of a frame and never frees individual allocations. Systems that need transient arrays take it from SystemContext::frameArena; a system that calls operator new in its frame path is a defect, not a style preference.

```
Fby::FrameArena arena(storage);          // caller owns storage
arena.Reset();                           // once per frame
auto* items = arena.AllocateArray<MeshRenderItem>(count);
if (items == nullptr)
{
    // Arena exhausted: degrade, never allocate on the heap.
    return;
}
const std::size_t used = arena.Used();
const std::size_t capacity = arena.Capacity();
```

- Allocate() returns nullptr instead of throwing when the arena is exhausted; callers must handle the failure.
- AllocateArray<T>() static_asserts std::is_trivially_copyable_v<T>: the arena stores POD payloads only.
- Over-aligned types must pass their alignment explicitly; the default is alignof(std::max_align_t).

## 5. JobSystem and per-thread diagnostics

JobSystem owns a pool of std::jthread workers. Tasks are function pointers plus a context pointer plus a half-open range, so submitting a task never allocates. ParallelFor splits a range into chunks, lets every participant pull the next chunk from an atomic counter, and always runs at least one chunk on the caller, which keeps single-core machines correct and worker re-entry safe.

```
jobs.ParallelFor(entityCount, 4096, [&](std::uint32_t begin, std::uint32_t end)
{
    for (std::uint32_t i = begin; i < end; ++i)
    {
        Integrate(entities[i], dt);
    }
});
jobs.WaitIdle();
```

```
// Diagnostics: one row per thread, slot 0 is the main thread.
std::array<Fby::JobSystem::ThreadLoad, Fby::JobSystem::kMaxThreadSlots> loads{};
const std::uint32_t slots = jobs.SampleThreadLoad(loads);
```

ThreadLoad carries busyNanoseconds (wall time inside engine work), taskCount and a 16-byte name. The counters are one cache line per thread, so two workers finishing at the same time do not contend. SceneDiagnosticsPanel turns two samples into a per-thread occupancy percentage.

*ThreadSlotCount() is ThreadCount() + 1 and is clamped by the fixed MCounters array; a device with more than 64 workers reports the first 64 slots.*

## 6. ECS, scheduling and snapshots

The registry is EnTT. Systems are registered on a SystemGraph in one of five phases (PreUpdate, FixedUpdate, Update, PostUpdate, Render). SystemContext is the only parameter a system receives; it carries the registry, JobSystem, frame arena, renderer, window, VFS, AssetDatabase, audio, physics, joints, cloth, fluid, camera stack, accessibility kernel and font atlases.

```
Fby::Ecs::Schedule schedule;
schedule.Add(Fby::Ecs::Phase::FixedUpdate, "physics", &PhysicsStepSystem,
&physics);
schedule.Add(Fby::Ecs::Phase::Update, "movement", &MovementSystem, nullptr);
schedule.Add(Fby::Ecs::Phase::PostUpdate, "platform", &GogAchievementSystem,
&gog);

Fby::Ecs::SystemContext context{registry, jobs};
context.physics = &physics;
context.window = &window;
schedule.Run(Fby::Ecs::Phase::FixedUpdate, context);
```

Snapshot v4 is a canonical, checksummed byte image of the registry. Components are written by hand-written codecs when they contain runtime handles (b2BodyId, b2ShapeId); the snapshot never serializes those handles, and the restore path recreates bodies from the component fields. The schema stores the Mirror name and LayoutHash of every component, so a field change is rejected instead of silently misread.

| API | Contract |
|---|---|
| **GetOrAdd<T>(registry, entity)** | Adds the component when missing and returns a stable reference. |
| **ecs::SnapshotWriter / SnapshotReader** | Writes and validates the canonical image; checksum is FNV-1a over the payload. |
| **Fby::Net::NetRollbackSession** | Consumes snapshot v4 and replays ticks on late input (section 10). |

## 7. RHI, render items and frame statistics

The RHI is a hand-written Vulkan/Metal layer. Frames are recorded into persistent ring buffers; sprite items are 48-byte PODs; meshes are drawn through one indirect call per material/layer; linear-blend skinning is one compute dispatch. FrameStats exposes what the pass actually submitted, which is what SceneDiagnosticsPanel plots.

| FrameStats field | Meaning |
|---|---|
| **items / batches / drawCalls** | Sprite items, batches and submitted draws. |
| **meshItems / meshIndirectCalls** | MeshRenderItem count and indirect draws. |
| **skinDispatches / skinRanges** | Skinning compute dispatches and ranges. |
| **uploadedBytes** | Bytes uploaded this frame. |

*The editor's Viewport renders into an offscreen target, not into the swapchain. EnsureViewportTarget() sizes that target in physical pixels; a target sized in points is the usual cause of a blurry Viewport on a HiDPI monitor.*

## 8. Materials: cooked graphs, the pipeline cache and the shipped path

Material authoring and material compilation live on opposite sides of the engine boundary. `Render::MaterialGraph` is the authoring DAG: fixed capacities (128 nodes, 384 pins, 64 parameters), trivially copyable, and hashed without the editor positions. `Render::MaterialGraphCompiler` turns a validated graph into GLSL 450 text. `fby_matc` runs that compiler and glslang at build time and writes a `.femmat` payload, so a shipped game never links glslang and never parses GLSL. The full rationale is in [ADR 0002](../../adr/0002-materials-in-engine.md).

| Piece | Header | Contract |
|---|---|---|
| **`Render::MaterialGraph`** | `Engine/RHI/MaterialGraph.hpp` | Authoring DAG; `Hash()` is the pipeline identity and excludes UI positions |
| **`MaterialGraphCompiler`** | `Engine/RHI/MaterialGraphCompiler.hpp` | DAG to GLSL 450 and the shader contract flags |
| **`EncodeMaterialGraph` / `DecodeMaterialGraph`** | `Engine/RHI/MaterialAsset.hpp` | `.fgraph` wire format: explicit little-endian fields, no struct memcpy |
| **`EncodeCookedMaterial` / `DecodeCookedMaterial`** | `Engine/RHI/MaterialAsset.hpp` | `.femmat` payload: 32-byte header, vertex and fragment SPIR-V, zero-copy decoding |
| **`Render::MaterialPipelineCache`** | `Engine/RHI/MaterialPipelineCache.hpp` | 128 pipelines keyed by graph hash, reference counted, LRU eviction, no heap use |
| **`Rhi::RHI::SupportsRuntimeShaderPipelines`** | `Engine/RHI/RHI.hpp` | Capability query: Vulkan returns true, Null and Metal return false |

```
# Author the graph once, cook it in the build step
build/bin/fby_matc assets/materials/tinted.fgraph -o
assets/materials/tinted.femmat
```

```
// `InBytes` is the .femmat payload from the VFS or a package entry.
Render::CookedMaterialView ScopedMaterial;
if (!Render::DecodeCookedMaterial(InBytes, &ScopedMaterial))
{
    return false;
}

// One cache per device: acquire at load time, release at shutdown.
const Rhi::ShaderPipelineHandle ScopedPipeline = InMaterials.Acquire(InRhi,
ScopedMaterial);

Rhi::MeshRenderItem ScopedItem;
ScopedItem.materialPipeline =
    ScopedPipeline.IsValid() ? ScopedPipeline.id :
Rhi::kDefaultMaterialPipeline;
```

- The graph hash is the pipeline identity. Editing a graph produces a new hash, so the old pipeline becomes an unreferenced cache entry instead of being mutated in place.
- The contract mask travels with the payload: generated vertex stage, fragment view projection, material push constants, world and vertex position varyings. A live entry whose hash arrives with another contract is refused, because that is a different shader.
- `Acquire()` adds a reference and `Release()` drops one. A pipeline at zero references stays resident, so a material acquired once per frame never recreates a pipeline; it is destroyed by LRU eviction, `ReleaseAll()` or `Shutdown()`.
- The cache never allocates and never formats text on the frame path; `LastError()` returns the fixed error buffer.
- Backends without runtime shader pipelines keep the engine shaders. Query `SupportsRuntimeShaderPipelines()` instead of probing for an invalid handle.

| Payload | Fields | Validated on load |
|---|---|---|
| **`.fgraph`** | magic `FBYG`, version, node/pin/param counts, nodes, pins, params | magic, version, counts against capacity, exact size, node kinds, pin and param indices |
| **`.femmat`** | magic `FBYM`, version, contract mask, graph hash, vertex and fragment byte lengths | magic, version, size against the lengths, both SPIR-V modules, contract consistency |

The editor keeps live editing on top of the same cache: `Fby::Editor::MaterialGraphRuntime` recompiles a graph when its hash changes, reports per-tab errors and delegates pipeline ownership to `MaterialPipelineCache`. `MaterialGraphRuntime::SetDomain` switches the live compile between the mesh and the sprite contract, and the panel's `SaveGraph`/`LoadGraph` write and read the

`.fgraph` payload the cooker consumes. A shipped build skips glslang entirely and only calls `DecodeCookedMaterial` and `Acquire`.

Sprites take materials through the third artefact: `MaterialCompileOptions::domain` selects the sprite domain, where the generated fragment stage matches the `quad.vert` varyings (`vUv`, `vColor`, `vLayer`, and `vWorld` when a node needs it) and samples the item's atlas slice through `vLayer`. `Time` is available: the sprite push block carries a material clock at offset 80, so the generated stage reads `pc.materialParams.x` exactly like a mesh shader. `fby_matc --sprite` cooks that variant. `DrawOrder::MaterialBucket` places the sprite in a bucket, `ChangeMaskRenderExtract::SetMaterialPipelines` maps buckets to cached pipeline ids, and the extractor emits one `DrawBatch` per bucket with `DrawBatch::pipeline` already resolved. The 64-bit render key carries the bucket (16 layer, 8 material, 32 depth, 8 sequence), so a material batch is never split by depth. Nodes that need the mesh view-projection (`Fresnel`, `VertexPosition`) are refused in the sprite domain with a readable reason.

## 9. Physics: Box2D v3, joints, cloth and SdfCollisionSystem

PhysicsSystem owns one b2WorldId and exposes it to extension modules as a packed uint32, so box2d.h never leaks into a public header. Bodies are mirrored from RigidBody2D/Collider2D components into Box2D, stepped at the fixed rate, and read back before interpolation. PhysicsJointSystem builds a fixed-capacity joint graph: chain, rope and spring connections with break limits, damage accumulation, gameplay cuts, repair, in-place rebuild and ties. ClothSystem integrates a Verlet grid and projects it against the same Box2D colliders.

SdfCollisionSystem contract:

| Member | Contract |
|---|---|
| **SetField(const SdfField&)** | Installs a non-owning mdspan over a row-major grid. Negative values are solid; the field's memory is owned by the renderer/terrain, not by the system. |
| **Step(registry, physics, fixedDt)** | Samples the grid at body corners and centre, converts the gradient to a normal, applies a mass-scaled push impulse, reflects inward velocity and writes the corrected state back. Returns the number of corrected bodies. |
| **Update(SystemContext&)** | ECS convenience wrapper around Step(); a headless call without physics is a no-op. |
| **Contacts()** | Fixed array of SdfContact {entity, point, normal, penetration, impulse, sequence}. |
| **SdfCollisionDesc** | pushOut, restitution, maxImpulse, subSamples, dynamicOnly. |

```
Fby::SdfCollisionDesc desc;
desc.pushOut = 0.65f;
desc.restitution = 0.05f;
desc.subSamples = 2;
```

```
sdf.Initialize(desc);
sdf.SetField(terrain.Field());
sdf.Register(graph);                    // Phase::FixedUpdate

// Viewport overlay: red vectors whose length is the penetration.
debug.Build(context, Fby::Editor::PhysicsDebugSdf, &sdf);
```

*SdfCollisionSystem is not part of SystemContext. A host that wants SDF physics registers the system explicitly through Register(graph) and keeps the instance alive; the Viewport debug pass takes the same pointer.*

## 10. NetRollbackSession: deterministic rollback

A session binds snapshot v4, CommandLog, Pcg32 and the gameplay components (tags, attributes, effects and skills) into one fixed-capacity rollback loop. Everything after Initialize() is allocation-free: one snapshot ring, one input ring per player, a fixed entity map and fixed frame metadata. The simulation callback is a function pointer plus void*.

| Method | Contract |
|---|---|
| **Initialize(registry, schema, config, arena)** | Allocation-free setup with a caller-owned snapshot arena. |
| **Initialize(registry, schema, config)** | Convenience overload; allocates one arena (the only allocation the session makes). |
| **SetSimulation(fn, user) / SetCommandLog(log)** | Binds the pure simulation function and the structural command log. |
| **Start(rng)** | Captures the base tick and stores the session RNG. Required before Step(). |
| **Step(localInput)** | Simulates exactly one tick with prediction for missing remote inputs and captures the snapshot. |
| **SubmitRemoteInput(player, frame)** | Stores a late or current input; a frame for an already simulated tick marks a pending rollback. |
| **ReplayPending(report)** | Restores the snapshot before the earliest corrected tick, restores RNG and CommandLog cursor, re-simulates, captures new snapshots and reports changed ticks. |
| **CompareChecksums(tick, snap, state, out)** | Compares a remote report with the stored frame; the two checksums isolate a byte-level desync from a gameplay-state desync. |

```
Fby::Net::NetRollbackSession::Config cfg;
cfg.playerCount = 2;
cfg.localPlayer = 0;
cfg.rollbackTicks = 64;
session.Initialize(registry, schema, cfg, arena);
```

```
session.SetSimulation(&SimulateTick, &game);
session.Start(pcg);

while (running)
{
    session.SubmitRemoteInput(remote, received);
    session.Step(localInput);
    if (session.RollbackPending())
    {
        Fby::Net::RollbackReport report;
        session.ReplayPending(&report);
        if (report.changedTicks > 0)
        {
            LogBoy().Log(Fby::Editor::LogBoySeverity::Desync, "net",
                         "rollback {}..{} changed {}", report.fromTick,
report.toTick,
                         report.changedTicks);
        }
    }
}
```

- NetInputFrame is 24 bytes of integer axes (int16 fixed point). Floats are not allowed: a float bit pattern is not guaranteed to survive a different compiler.
- Result enumerates every failure mode (NotInitialized, BufferFull, RollbackTooOld, ChecksumMismatch, ...); ResultName() is the log spelling.
- A session is non-copyable and owns its arena when the convenience overload is used.

## 11. Audio: mixer, DSP graph, limiter

AudioSystem owns the miniaudio device and a fixed mixer. DspGraph routes nodes into buses, supports ducking and reverb, and receives commands through a lock-free ring so the game thread never blocks the audio callback. Limiter.hpp is the final true-peak stage.

- DeafMode mutes the graph at the Master root and turns sound triggers into subtitle lines; it is a policy of the audio system, not a post-effect.
- Ogg/Opus is decoded off the audio thread; the mixer only sees cooked .fpcm buffers.

## 12. PinkUI and WidgetCanvasSystem

PinkUI is the in-game UI: a fixed-capacity canvas, mdspan grid layout, anchor resolution, hit testing and one-batch packing. WidgetCanvasSystem turns a WidgetCanvas into FrameOutput (draw items) without allocating; font glyphs come from a .fbyfont atlas mapped through the VFS, so the shipping runtime carries no TTF rasterizer. Glyphs are atlas-only: there is no embedded 8x8 bitmap fallback, and a text frame without a mounted font array is refused instead of drawn with the wrong layer.

| Member | Contract |
|---|---|
| **WidgetCanvasSystem::MountFonts(RHI&)** | Mandatory cold-start stage on the main thread. Builds the GPU texture array from the |

| | |
|---|---|
| | VFS .fbyfont set; a failure is a PANIC log plus FBY_ASSERT_MSG, never a fallback. |
| **BuildFrame(context, canvas, output)** | Lays out and culls one canvas, returning BuildStatus and filling FrameOutput. A text canvas without a current mounted atlas returns FontsNotMounted and writes nothing. Allocation-free; safe to call from Phase::Render. |
| **Update(context, canvases, output)** | Builds every active canvas into one output; the host submits the result as one batch. A font-contract violation stops the pass and sets fontContractViolated. |
| **WidgetCanvas::SetDisplayScale** | Density from CameraStackSystem::DisplayScale; font sizes are rounded to whole physical pixels. |
| **OledShiftState** | Integer 2 px orbit for OLED safety; ApplyOledShift() binds it to a canvas pool. |

WidgetCanvasSystem is also the accessibility surface: BlindMode reads widget labels for the narrative log, DeafMode receives subtitle widgets, and colour-vision matrices plus FlashGuard are applied to the canvas colours before packing.

## 13. Accessibility kernel (BlindMode, DeafMode, FlashGuard)

Accessibility is a frame policy, not an overlay. BlindMode skips the game pass, indirect draws and the skinning dispatch, then publishes a bounded narrative log. DeafMode mutes the Master bus and routes sound triggers into SubtitleLines. FlashGuard compresses sudden luminance changes. Colour-vision correction uses the published Machado 2009 matrices, and SrgbRelativeLuminance()/ContrastRatio() implement WCAG 2.2 for authoring-time validation.

| Item | Contract |
|---|---|
| **NarrativeEvent** | 128-slot SPSC ring of 160-byte text payloads; the simulation thread pushes, the speech thread pops. |
| **ColorVisionMatrix(deficiency)** | Returns the 3x3 matrix for protanopia, deuteranopia or tritanopia. |
| **ApplyColorVision(color, matrix, strength)** | Applies the matrix in linear light to an sRGB Color32. |
| **FlashGuard::Evaluate(luminance, dt)** | Returns the gain for the current frame; a large delta is compressed to the threshold. |
| **EditorSettings::ide*** | The same policies applied to the editor window itself: Machado correction, WCAG high-contrast, FlashGuard, keyboard navigation and LogBoy as the narration sink. |

## 14. Asset pipeline, VFS and localization

Assets are addressed by relative path inside the VFS. A .fempak archive is mounted with a priority; a directory mount can shadow it, which is how the editor writes a loose file before the cooker folds it back in. Read() returns a span into an mmap that stays valid until the mount is dropped or the file is hot-reloaded.

| Format | Owner | Purpose |
|---|---|---|
| **.fempak** | FempakCooker | Immutable shipped archive with an index and optional encryption. |
| **.fbyfont** | FontAtlas (PinkUI) | Baked glyph atlas: [header] [glyph records][pixels]; no runtime TTF rasterizer. |
| **.femeta** | AssetDatabase | Typed metadata, import settings and stable AssetId. |
| **.fbin** | LocTool | Compiled localization table; the editor UI itself is English-only. |

*The editor UI is not localizable by design: menus, panel titles, errors and the inspector are English-only. Localization applies to game content and documentation, where a .fbin table and the EN/RU manual cover the shipped languages.*

## 15. Platform services: Steam, Epic Games Store, GOG

PlatformService is the engine-side bridge; PlatformAPI.h is a flat pure-C ABI that a store SDK plugin implements. The provider is loaded dynamically, resolves only documented entry points and converts every store-specific type at the boundary, so a game never includes steam_api.h, EOSSDK or Galaxy headers.

| Provider | Status in this tree | Notes |
|---|---|---|
| **SteamProvider.cpp** | Implemented | Steamworks flat API through a function table. |
| **EgsProvider.cpp** | Implemented | Epic Online Services provider through the same C ABI. |
| **GogProvider.cpp** | Implemented (shim) | Loads galaxy64.dll / libgalaxy64.so / libgalaxy64.dylib at runtime and resolves the flat fby_gog_* shim ABI; the game ships the shim built against its SDK revision. Galaxy is a C++ interface library, so a shim is mandatory. GogAchievementSystem and GogStorageSystem write the |

| | | |
|---|---|---|
| | | binary PlatformCommandLog in Phase::PostUpdate. |
| **fby_fontc** | Implemented | Offline TTF -> .fbyfont cooker (stb_truetype, RGBA8 atlas, verified header). |

```
// Pure C ABI: the provider is a shared library, not a C++ dependency.
typedef struct FbyPlatformApi {
    uint32_t version;
    void* user;
    bool (*init)(void* user);
    void (*shutdown)(void* user);
    void (*unlockAchievement)(void* user, const char* id);
    bool (*writeCloudFile)(void* user, const char* name, const uint8_t* data,
uint32_t size);
} FbyPlatformApi;
```

## 16. Editor: dashboard, fonts, LogBoy, Scene Diagnostics

The dashboard is the only editor surface that exists before a project is open. It installs the editor font set before the first frame, so the first window is already Inter at the physical DPI. A new project starts in Projects/ under the engine root, resolved by DefaultProjectsRoot() - never in the process working directory and never in the install directory.

| Component | Contract |
|---|---|
| **EditorFonts** | Loads Inter and JetBrains Mono from the VFS mmap. Subpixel advances (PixelSnapH=false), auto oversampling, no bitmap fallback, dynamic atlas baked at the viewport pixel density. Legacy backends get RasterizerDensity + inverse FontGlobalScale. |
| **ProjectDashboard** | Initialize(paths, config, visible, window, vfs, fonts, uiScale): installs typography, resolves the default Projects/ location and creates it. |
| **LogBoySystem / LogBoyPanel** | Fixed 4096-record ring of 192-byte text payloads with severity Trace/Info/Warning/Critical/Desync, FNV-1a system hashes and colour+hash filtering. |
| **SceneDiagnosticsPanel** | Per-thread occupancy bars and heatmap, FrameArena bytes, MeshRenderItem count, indirect draws, draw calls and exact simulation microseconds with avg/p99/peak. |
| **PhysicsDebugVisualizer** | Fixed-buffer line/point geometry for Box2D bodies, ropes, cloth and SDF normals, drawn over the Viewport through a caller-supplied world-to-screen map. |

*The .fbyfont atlas is a baked PinkUI asset and cannot feed ImGui's vector rasterizer. The editor therefore loads the Inter TTF from the same VFS mount; the atlas header is still validated on startup, so a corrupt game-UI atlas is reported by the editor, not by the player.*

## 17. Step-by-step: a game from an empty folder

This walkthrough produces a playable project with a sprite, physics, keyboard input, a PinkUI HUD and a deterministic rollback session. Every step maps to a real header from the index.

- 1. Launch the editor and create a project with New Project. The dashboard creates <engineRoot>/Projects/<name> with assets/{textures,audio,scenes}, configs/ and project.femproj.
- 2. Import a sprite into assets/textures. The watcher imports it, writes a .femeta and cooks a .ftex texture array layer.
- 3. Create assets/scenes/main.toml with one SpriteRenderer, one Transform2D and one RigidBody2D + Collider2D.
- 4. Register the systems: input in PreUpdate, physics in FixedUpdate, movement in Update, PinkUI in Render.
- 5. Give the camera a CameraStackSystem and call SetDisplayScale() from SDL_GetWindowDisplayScale so UI glyphs are crisp on HiDPI.
- 6. Add an AccessibilityKernel from project settings; BlindMode and DeafMode are read from project.femproj, not hard-coded.
- 7. Create a NetRollbackSession per match, bind a pure SimulateTick callback and feed NetInputFrame values.
- 8. Log through LogBoy: severity + system hash + fixed-format message. Open the LogBoy panel and filter by Desync while testing netcode.
- 9. Enable Physics Debug Draw in the Viewport while tuning colliders and cloth.
- 10. Cook with FempakCooker, run the suite with ctest and the style gate, then ship the engine-only target.

```
// 4-7 in code: systems, accessibility and rollback for one match.
Fby::Ecs::Schedule schedule;
schedule.Add(Fby::Ecs::Phase::PreUpdate, "input", &InputSystem);
schedule.Add(Fby::Ecs::Phase::FixedUpdate, "physics", &PhysicsStepSystem,
&physics);
schedule.Add(Fby::Ecs::Phase::Update, "movement", &MovementSystem);
schedule.Add(Fby::Ecs::Phase::Render, "ui", &UiSystem, &ui);

Fby::AccessibilityKernel kernel;
kernel.Configure(settings);              // blind/deaf/colour/flash

Fby::Net::NetRollbackSession session;
if (session.Initialize(registry, schema, cfg, arena) !=
Fby::Net::NetRollbackSession::Result::Ok)
{
    LogBoy().Log(Fby::Editor::LogBoySeverity::Critical, "net", "rollback init
failed");
```

```
}
```

## 18. Testing, style gate and release checklist

The suite is deliberately framework-free: every test is an executable with a main() that returns non-zero on failure, so it runs on a headless CI agent, a console devkit and a developer workstation with the same command. The full suite passes at Release.

```
ctest --test-dir build --output-on-failure          # the full suite
python Source/Tools/Dev/CheckStyle.py               # style gate
python Documentation/Tools/GenerateAPIReference.py  # this manual
python Documentation/Tools/GenerateDocumentation.py
python Documentation/Tools/GenerateApplicationGuide.py
```

- A release build enables asserts and runs the whole suite once with FBY_ENABLE_ASSERTS=1, because two latent debug-only compile errors existed in JobSystem at RC.
- The POSIX branch of WriteFileAtomically() and LogLine() must be compiled on Linux/macOS in CI; the Windows-only build never saw them.
- The style gate must report zero failures before a commit is eligible for release.

## 19. Open work

Open work is tracked in Documentation/ROADMAP.md.

## 20. GOG Galaxy: provider, shim ABI and PostUpdate systems

GOG Galaxy ships a C++ interface library, not a flat C API. The engine therefore keeps the same architecture it uses for Steam and Epic: a provider shared object speaks only PlatformAPI.h, and a thin Galaxy shim (built by the game against the exact SDK revision it ships) exposes a flat C surface that the provider resolves with dlopen/LoadLibrary at runtime. No Galaxy header enters the engine, and an SDK upgrade replaces the shim without recompiling the game.

| Flat shim export | Maps to |
|---|---|
| **fby_gog_initialize(clientId, clientSecret)** | Galaxy::Init with a User/Listener registration. |
| **fby_gog_process_data()** | Galaxy::ProcessData, called once per Pump(). |
| **fby_gog_unlock_achievement(name)** | IAchievements::SetAchievement + StoreAchievements. |
| **fby_gog_write_cloud/read_cloud/ delete_cloud** | IStorage file API; BufferTooSmall reports the required size. |
| **fby_gog_pending_cloud_writes()** | Outstanding Galaxy write listeners. |

```
// The provider resolves the shim once, then every call is a pointer hop.
bool EnsureLibrary() noexcept
```

```
{
    GState.library = OpenGalaxyLibrary();          //
galaxy64.dll / .so / .dylib
    if (GState.library == nullptr)
    {
        return false;                              // honest NotAvailable
    }
    return ResolveFlat(GState.library, "fby_gog_unlock_achievement",
                       GState.api.unlockAchievement);
}

// Game side: PostUpdate turns components into logged commands.
Fby::Platform::GogAchievementSystem achievements;
achievements.Initialize(platform, commandLog, 1);
Fby::Platform::GogAchievementSystem::Register(graph, achievements);

Fby::Platform::GogStorageSystem storage;
storage.Initialize(platform, commandLog, 1);
std::span<const std::byte> save = SerializeSlot(slot);
storage.StageWrite(0x51u, "slot0.sav", save);
Fby::Platform::GogStorageSystem::Register(graph, storage);
```

Both systems run in Phase::PostUpdate. They iterate a bounded view (64 entities), sort deterministically by id and entity, append one byte-exact record to PlatformCommandLog and queue one fixed-size PlatformCommand. PlatformService::Pump() is the only caller of the shim, so a Galaxy callback can never run on a simulation thread. When the shim is absent the provider returns NotAvailable and the log keeps the intent instead of pretending the achievement unlocked.

## 21. Font pipeline: fby_fontc, .fbyfont and the stable buffer

Pink UI never rasterizes a TTF at runtime. fby_fontc bakes the vector outlines into the engine's atlas format, the cooker packs the blob into .fempak, and the VFS maps it on demand. The tool is the only target that links stb_truetype.

```
fby_fontc --input assets/fonts/Inter-Regular.ttf \
          --output assets/fonts/Inter.fbyfont \
          --size 32 --font-id 0 --ranges latin,cyrillic --verify

fby_fempak --input assets --output assets.fempak
```

| Region | Contents |
|---|---|
| **Header** | 48 bytes: magic FBYFNT01, version, glyph count, atlas size, format, offsets, line height, ascent/descent, font id. |
| **Glyph table** | 40 bytes per glyph: codepoint, normalized UVs, advance, bearings, quad size. Sorted ascending for the binary search in FontAtlas::Glyph(). |

| | |
|---|---|
| **Pixels** | RGBA8: white RGB with the coverage mask in A, so a label tint multiplies correctly. |

*Editor typography is a different consumer: ImGui needs vector outlines to bake glyphs at arbitrary DPI and cannot read .fbyfont. EditorFonts copies the TTF bytes from the VFS into an EditorFonts-owned buffer before handing the pointer to ImGui, so a hot reload that unmaps the file can never leave the atlas pointing at freed pages. The atlas header is still validated on startup, which is how a broken game-UI font is caught by the editor.*

## 22. Cloth render path: from Verlet vertices to one indirect draw

ClothSystem integrates a Verlet grid and writes MeshVertex positions that are already final. The renderer must not skin them: with boneCount == 0 a skinning dispatch would multiply every vertex by an identity-stack default and collapse the cloth to a point. The engine therefore has exactly one classification helper and one producer:

```
// Mesh.hpp: one predicate, used by VulkanRHI and any future backend.
inline bool IsUnskinnedMeshItem(const MeshRenderItem& item) noexcept
{
    return (item.Flags & MeshItemUnskinned) != 0 || item.boneCount == 0;
}

// VulkanRHI: unskinned vertices bypass the compute dispatch entirely.
const bool unskinned = !isStatic && IsUnskinnedMeshItem(item);
memcpy(targetVertexRing + totalSkinned + unskinnedCursor,
item.vertices.data(), ...);
record.unskinned = true;   // mesh.vert reads binding 3, not the skinned SSBO

// App: ClothRenderSystem is the producer the path was missing.
Fby::ClothRenderSystem clothRender;
clothRender.Initialize(&clothSystem);
Fby::ClothRenderSystem::Register(graph, clothRender);   // Phase::PostUpdate
extract.Build(registry, camera, clear, textureArray, clothRender.Items());
```

The bridge fills a fixed 64-item array, forces MeshItemUnskinned and sorts by (sortLayer, depth, ClothId), so draw order is deterministic without an allocation. The regression test checks the mesh still spans the authored 64x64 pixels - the exact symptom of a collapsed cloth - and that a zero-bone item is classified as unskinned even when its flag is missing.

## 23. Atmosphere: weather context, fBm wind and GPU rain with SDF splashes

WeatherContextComponent is the single authored source of atmosphere constants and wind. WeatherSystem resolves one gust-modulated vector per frame with fBm noise and writes it back into the component and into the std140-friendly WeatherWindField block. Cloth, plant vertices and rain all read that same vector, so nothing disagrees about where the wind blows.

```
Fby::Weather::WeatherContextComponent weather;
weather.atmosphereDensity = 1.35f;   // denser alien air
weather.airViscosity = 1.1e-5f;
```

```
weather.gravityScale = 0.82f;
weather.windSpeed = 26.0f;
weather.windDirectionX = 0.8f;
weather.windDirectionY = -0.6f;
weather.turbulence = 0.55f;
weather.rainIntensity = 0.85f;
weather.Flags |= Fby::Weather::WeatherRain | Fby::Weather::WeatherWind;

// WeatherSystem -> ClothSystem -> shader block, one resolved vector.
cloth.SetAmbientWind({weather.resolvedWindX, weather.resolvedWindY});
shaders.SetWeatherBlock(WeatherWindFieldFrom(weather));
```

WeatherPreconciliatedSystem owns no particles on the CPU. It uploads one WeatherGpuConstants block per frame and records four graph passes: integrate droplets (weather_rain.comp), age splashes (weather_rain_splash.comp), draw line segments (weather_rain.vert/frag) and draw splash sprites. The rain compute shader integrates wind, samples the global terrain SDF and appends a splash with atomicAdd when a droplet crosses the implicit surface.

```
// weather_rain.comp: one invocation per droplet, 262144 drops per dispatch.
const vec2 previous = particle.state0.xy;
particle.state0.xy += velocity * dt;

const vec2 uv = (particle.state0.xy - weather.fieldTransform.xy) / fieldSize;
const float surface = texture(uSdf, uv).r;          // negative = solid
if (surface <= 0.0 && previousSurface > 0.0)
{
    const uint slot = atomicAdd(splashBuffer.splashCount, 1u);
    splashBuffer.splashes[slot].state0 = vec4(particle.state0.xy, 0.0, 1.0);
    splashBuffer.splashes[slot].color = particle.color;
    spawnParticle(particle, randomState);              // respawn at the top
}
particleBuffer.particles[particleIndex] = particle;
```

*The Metal mirror embeds the same constants and the same splash arithmetic; the MSL source is compiled into the engine at build time. The CPU cost of a storm is one constant upload plus the graph records, independent of the drop count.*

## 24. ECS by composition: a 2D shooter without inheritance

A Player and an Enemy are not classes. They are the same entity type with different component sets, and the systems that run are selected by data. This section builds the canonical shooter from four components and three systems; adding a boss means adding components and a spawn row, not a new subclass.

```
struct HealthComponent   { float health = 100.0f; float maxHealth = 100.0f;
float invuln = 0.0f; };
struct WeaponComponent   { float damage = 10.0f; float cooldown = 0.0f; float
interval = 0.12f;
                           float projectileSpeed = 900.0f; std::uint32_t
archetype = 0; };
```

```
struct InputComponent    { std::int16_t moveX = 0; std::int16_t moveY = 0;
std::uint32_t buttons = 0; };
struct AIBehaviorComponent { std::uint32_t behaviour = 0; float aggroRadius =
400.0f;
                             float fireRange = 320.0f; std::uint32_t targetNetId
= 0; };

// Player: Transform + PhysicsBodyDesc + Health + Weapon + Input
// Enemy : Transform + PhysicsBodyDesc + Health + Weapon + AIBehavior
// Boss  : same as Enemy + phases[] + WeaponArray; no new class.
```

| System | Phase | Reads / writes |
|---|---|---|
| **InputSystem** | PreUpdate | Reads InputComponent, writes it from the tick input packet. |
| **AISystem** | Update | Reads AIBehavior + Health, writes InputComponent (AI produces input, not velocity). |
| **WeaponSystem** | FixedUpdate | Reads Weapon + Input, spawns projectiles through CommandBuffer. |
| **DamageSystem** | PostUpdate | Reads collision events, decrements Health, queues despawn. |

```
void SpawnEnemy(Fby::Ecs::Registry& registry, const Fby::CharacterDesc& desc,
                const Fby::PhysicsBodyDesc& body, Fby::Vector2D at)
{
    const Fby::Entity enemy = registry.create();
    registry.emplace<Fby::Transform2D>(enemy, Fby::Transform2D{at, {}, {1.0f,
1.0f}, 0.0f});
    registry.emplace<Fby::RigidBody2D>(enemy, Fby::RigidBody2D{.Position = at});
    registry.emplace<Fby::Collider2D>(enemy, Fby::Collider2D{body.halfExtents});
    registry.emplace<HealthComponent>(enemy, HealthComponent{desc.maxHealth,
desc.maxHealth, 0.0f});
    registry.emplace<WeaponComponent>(enemy,
        WeaponComponent{desc.damage, 0.0f, desc.fireInterval,
desc.projectileSpeed, desc.weaponArchetype});
    registry.emplace<AIBehaviorComponent>(enemy, AIBehaviorComponent{0, 420.0f,
300.0f, 0});
}
```

Determinism follows from the component set: the same seed, the same integer inputs and the same systems produce the same snapshot checksum. A boss that needs a phase machine adds a PhaseComponent and a system in the same phase; it does not change Player, Enemy, the weapon code or the netcode.

## 25. Multi-Draw Indirect and Texture Cooking in production

Sprites and meshes take two different paths through the same FramePacket. Sprites are 48-byte RenderItems sorted into batches; meshes are MeshRenderItems that become one MeshDrawData record and one indirect command each, grouped by (textureArray, layer, materialPipeline). The GPU never sees a per-object descriptor bind on this path.

```
Fby::Rhi::MeshRenderItem item;
item.vertices   = skinVertices;              // or MeshSystem::WriteMesh()
item.indices    = skinIndices;
item.boneOffset = paletteOffset;
item.boneCount  = paletteSize;               // 0 => unskinned bind pose
item.textureArray = atlas.Handle().id;       // one binding for the scene
item.Layer        = sprite.Layer;
item.model        = Fby::Mat4::Identity();

packet.meshItems = renderExtract.MeshItems();
packet.boneMatrices = renderExtract.BonePalette();
rhi.Submit(packet);                                // one indirect call per group
```

| Budget | What to measure |
|---|---|
| **MeshDrawData** | 80 bytes per draw, uploaded once per frame; firstInstance selects it. |
| **Bone palette** | One contiguous Mat4 block per frame; never per draw. |
| **Texture array** | One sampler2DArray binding for the whole scene; cooking picks BC7 (desktop) or ASTC (mobile). |
| **SceneDiagnostics** | Watch MeshRenderItem, indirect calls, draw calls and the frame arena in one panel. |

```
# Texture cooking: source PNG -> .ftex (BC7/ASTC mips) -> .fempak
fby_fempak --input assets --output assets.fempak --format bc7-srgb
fby_fontc --input assets/fonts/Inter-Regular.ttf --output
assets/fonts/Inter.fbyfont

# Verify the shipping pack through the same VFS the game uses
ctest --test-dir build -R data_driven --output-on-failure
```

*The editor's Project Settings panel edits the cook format and the collision matrix transactionally; both persist into project.femproj and are applied to live b2Shape filters on commit. A project that changes its target from desktop to mobile keeps the same scene and re-cooks the atlas.*

## 26. Repository layout, CMake targets and the gates

The tree is part of the contract. CheckStyle.py now fails when a translation unit appears directly under Source/Engine or Source/Editor, when an unexpected module directory exists, or when a

build log, object file, screenshot or Python cache is committed outside the disposable build tree. The module set is fixed: Core, RHI, ECS, Physics, Audio, Network, Assets, Script, UI, Video, plus the first-class Weather and Platform modules.

| Target | Kind | Purpose |
|---|---|---|
| **fby_engine** | static library | Runtime; no ImGui, no TOML writer, no storefront SDK. |
| **fby_editor / fby_editor_app** | library + executable | ImGui/ImPlot panels and the IDE. |
| **fby_fontc** | tool | TTF -> .fbyfont atlas; the only stb_truetype consumer. |
| **fby_fempak** | tool | Asset cooker and archive writer. |
| **fby_platform_steam/egs/gog** | shared libraries | Storefront providers behind the C ABI. |

```
python Source/Tools/Dev/CheckStyle.py                # style + layout + hygiene
cmake --build build --target fby_editor fby_fontc fby_platform_gog
ctest --test-dir build --output-on-failure        # the full suite
python Documentation/Tools/GenerateCompleteReference.py
```

*Shaders still live under Source/Engine/RHI/Shaders because the engine embeds their SPIR-V at configure time; the directory is the shader module, not a loose asset folder. Moving it to a top-level Shaders/ would require changing the embed step and every shader path for no packaging benefit.*

## 27. Threading contract: RHI, the OS main loop and TTS

Three subsystems have non-negotiable thread affinity: the RHI command stream, the window/ImGui loop and OS speech. Simulation systems may run on JobSystem workers, but workers never call the RHI, never touch the window and never create an AVSpeechSynthesizer or an ISpVoice. They only append to lock-free queues and fixed-size logs.

| Entry point | Affinity | Rule |
|---|---|---|
| **VulkanRHI::DrawPacket** | main render thread | Records vkCmdBindDescriptorSets inside the batch loop; the batch carries full 32-bit pipeline and texture-array ids, 0 inherits the packet array. |
| **WidgetCanvasSystem::MountFonts** | cold path, main thread | Mandatory UI host stage. Creates the GPU texture array and may WaitIdle. A missing set, an empty set or a failed mount logs PANIC and trips FBY_ASSERT_MSG: there is no fallback. |

| | | |
|---|---|---|
| **WidgetCanvasSystem::BuildFrame** | main render thread | Reads FontAtlasSet::IsCurrent() and the 32-bit array id. Text without a mounted array returns BuildStatus::FontsNotMounted and writes nothing; no GPU creation, no WaitIdle, no VFS remap, no allocation after Add(). |
| **FontAtlasSet::MountToTextureArray** | cold path | Validates the device maxTextureLayers before touching GPU memory, publishes the new array only after every layer is built, and calls WaitIdle before destroying the previous array (no GPU use-after-free). |
| **EditorFonts hot reload** | main thread, before NewFrame | DetectFontChanges() -> RHI::WaitIdle() -> ReloadFonts(). PollForFontChanges() was removed: the combined helper destroyed the atlas without the barrier. |
| **AccessibilityKernel::Update** | simulation / worker | Builds the Narrative Tree and pushes NarrativeEvents. It never calls SAPI or AVSpeech. |
| **AccessibilityKernel::SetBlindMode / SetTtsBackend** | OS main thread (asserted) | RequireMainThread() first: a worker call is logged, dropped and trips FBY_ASSERT_MSG in an assert build. Enabling BlindMode may attach the native backend and select a voice. |
| **AccessibilityKernel::SetNarrativeLocale** | any thread | Changes the narrative tree language. A worker call only records a pending TTS language; the setVoice() is applied by FlushSpeech() on the owner thread. |
| **AccessibilityKernel::FlushSpeech** | OS main thread | Called from EditorSystem::Tick() / the SDL main loop. Applies a deferred locale, then drains the log and calls the backend speak callback. A worker call returns before the log is touched. |
| **SAPI 5 (Windows)** | STA main thread | CoInitializeEx(COINIT_APARTMENTTHREADED) is paired |

| | | |
|---|---|---|
| | | with CoUninitialize. SetVoice enumerates every installed token and scores it against the BCP-47 tag; no match falls back to the system default voice. |
| **AVSpeechSynthesizer (macOS)** | main run loop | Initialize/Speak/SetVoice assert [NSThread isMainThread]. SetVoice resolves the best installed voice language and falls back to the system default. |
| **JobSystem workers** | any worker | May run ECS systems and append to lock-free rings; may not call RHI, window, VFS remap or TTS. |

```
// Cold path: app init / scene load, OS main thread. Creates the GPU array once.
ui::WidgetCanvasSystem scopedUi{&fonts};
if (!scopedUi.MountFonts(*gpu))
{
    // Panic already logged; an assert build never reaches this line.
    return Shutdown(ExitCode::UiFontsUnavailable);
}

// Hot path: Render phase, main thread. No GPU creation, no WaitIdle.
ui::FrameOutput out;
const ui::BuildStatus status = ui::WidgetCanvasSystem::BuildFrame(ctx, canvas,
out);
if (status == ui::BuildStatus::FontsNotMounted) { /* refuse the whole UI pass */
}
// out.batches[0].textureArray is the 32-bit font array id and out.items carry
the
// real layer (0 = white, 1..N = fonts); DrawPacket rebinds per batch.

// Font hot reload: the barrier is deliberate and one-shot.
if (fonts.DetectFontChanges())
{
    gpu->WaitIdle();
    fonts.ReloadFonts(ImGui::GetIO());
}

// Speech: Simulation never flushes. The editor/Main loop owns it.
void EditorSystem::Tick(ecs::SystemContext& ctx)
{
    if (ctx.accessibility) { ctx.accessibility->FlushSpeech(); }  // main thread
only
    // ... ImGui frame ...
}
```

*Rule of thumb: if an operation can wait on the GPU, allocate a VkImage, close a VFS mapping or talk to a COM/Objective-C UI object, it belongs to the cold path or the OS main thread. The render and simulation hot paths only read immutable state and append to queues. A debug build turns every one of those boundaries into an FBY_ASSERT_MSG; a release build logs and drops the unsafe call instead of issuing it.*

## 28. The 32-bit DrawBatch pipeline: end of the 65,536-texture ceiling

DrawBatch is the only place where a texture-array id and a shader-pipeline id cross the render-extract boundary. Both fields were std::uint16_t, while every RHI handle (TextureArrayHandle, ShaderPipelineHandle) is std::uint32_t. The result was a silent alias: the 65,537th texture array or pipeline was truncated to an unrelated low id and the batch sampled the wrong resource - with no error, no assert and no way to see it in a log. Both fields are std::uint32_t and ordered so the struct remains exactly 16 bytes.

| Offset | Field | Type | Contract |
|---|---|---|---|
| **0** | firstItem | uint32_t | First RenderItem of the run; an index into the frame's item span. |
| **4** | itemCount | uint32_t | Number of contiguous items in the run. |
| **8** | pipeline | uint32_t | ShaderPipelineHandle::id, 0 = the quad pipeline. No uint16 narrowing. |
| **12** | textureArray | uint32_t | TextureArrayHandle::id, 0 = inherit FramePacket::textureArray (id 0 is the backend's built-in atlas by contract). |

```
// RenderItem.hpp - 16 bytes, no padding, four batches per 64-byte cache line.
struct DrawBatch
{
    std::uint32_t firstItem = 0;
    std::uint32_t itemCount = 0;
    std::uint32_t pipeline = 0;      // ShaderPipelineHandle::id
    std::uint32_t textureArray = 0;  // TextureArrayHandle::id, 0 = inherit
};
static_assert(sizeof(DrawBatch) == 16);
static_assert(alignof(DrawBatch) == 4);
static_assert(offsetof(DrawBatch, textureArray) == 12);
static_assert(std::is_trivially_copyable_v<DrawBatch>);

// VulkanRHI::DrawPacket - the id is consumed at full width.
const std::uint32_t requested =
    batch.textureArray != 0 ? batch.textureArray : packet.textureArray;
```

```
if (requested != boundArray) { BindDescriptorFor(requested); boundArray =
requested; }

// Pink UI writes the same 32-bit id: the old "<= 0xFFFF" clamp is gone.
Output.batches[0] = rhi::DrawBatch{start, count, canvas.pipeline, fontArray.id};
```

- No narrowing cast survives on the path: a grep for 0xFFFF in the batch, WidgetCanvas and Vulkan batch loop returns nothing.
- WidgetCanvas::textureArray and WidgetCanvas::pipeline are also 32-bit; SetTextureArray and SetPipeline take std::uint32_t.
- MeshRenderItem::textureArray was already std::uint32_t; static_asserts now pin its width so a future tightening cannot re-introduce the ceiling on the mesh path.
- A host that indexes its own descriptor table from a batch id must validate it: the engine forwards the id, the backend logs and falls back to the built-in atlas for an unknown id instead of dereferencing it.

*Why the struct did not grow: the two former uint16_t fields plus the 4-byte pad became two uint32_t fields. The batch is still 16 bytes, the sorted batch array keeps its density, and four consecutive batches share one cache line. Widening a resource id must never cost a cache miss in the per-frame batch loop.*

## 29. Atomic VFS font hot reload and the strict MountFonts contract

Pink UI text is atlas-only. The VFS mmap supplies cooked .fbyfont blobs, the cold path packs them into one GPU texture array (white layer 0, font atlases 1..N), and the hot path only reads that array. Two failure modes are excluded by contract: a lazy mount cannot leave the first frame on an 8x8 bitmap layer, and a remount cannot destroy an array that a frame may still sample.

| Stage | Thread / timing | Rule |
|---|---|---|
| **FontAtlasSet::Add / LoadFromVfs** | cold path | Validates the .fbyfont header and the shared pixel size immediately, grows the mount scratch outside the frame, and bumps the set Generation. |
| **WidgetCanvasSystem::MountFonts** | cold start, main thread | Mandatory. Empty/null/failed mount -> PANIC in LogBoy + FBY_ASSERT_MSG (debug). Remounts when the set is not current. |
| **FontAtlasSet::MountToTextureArray** | cold path | Checks maxTextureLayers before allocating, builds every layer, publishes atomically, and calls WaitIdle before releasing the previous array. |
| **FontAtlasSet::IsCurrent** | read from the hot path | MountedGeneration == Generation. Adding an atlas invalidates the mount; the next frame is refused until |

| | | |
|---|---|---|
| | | MountFonts() runs again. |
| **WidgetCanvasSystem::BuildFrame** | main render thread | Text with a missing/stale/non-current set, an invalid atlas index or a foreign image array returns FontsNotMounted and writes nothing. No mounting, no WaitIdle, no allocation. |
| **EditorFonts::DetectFontChanges** | main thread, between frames | Detection only. The host then calls RHI::WaitIdle() and ReloadFonts(). PollForFontChanges() was deleted because it skipped the barrier. |

```
// 1. Cold start: load -> mount -> build. Order is mandatory.
ui::FontAtlasSet fonts;
if (!fonts.LoadFromVfs(vfs, "fonts/Inter.fbyfont")) { return Fail("atlas"); }
ui::WidgetCanvasSystem ui{&fonts};
if (!ui.MountFonts(*gpu)) { return Fail("font array"); }  // PANIC + assert in
debug

// 2. Hot frame: atlas-only text, full 32-bit array id.
ui::FrameOutput out{items, keys, batches, 0};
if (ui::WidgetCanvasSystem::BuildFrame(ctx, canvas, out) ==
ui::BuildStatus::FontsNotMounted)
{
    frame.fontContractViolated = true;  // release: draw no text, never a bitmap
}

// 3. Adding a locale atlas at runtime invalidates the mount.
fonts.LoadFromVfs(vfs, "fonts/NotoSansJP.fbyfont");
if (!fonts.IsCurrent()) { (void)ui.MountFonts(*gpu); }  // remount, old array
waits idle

// 4. Editor ImGui typography: the only supported hot-reload chain.
if (editorFonts.DetectFontChanges())
{
    gpu->WaitIdle();
    editorFonts.ReloadFonts(ImGui::GetIO());  // between frames, before
NewFrame()
}
```

- VFS ownership: EditorFonts copies each TTF into stable storage before ImGui sees it, so a VFS remap can never leave the atlas pointing into an unmapped page.
- GPU ownership: FontAtlasSet waits for the device before destroying a texture array, because the previous frame may still be sampling its descriptor set.
- Failure policy: a missing atlas is loud. There is no 8x8 fallback in any build; a release build refuses the text frame and sets FrameOutput::fontContractViolated.

*A canvas that mixes text with its own image texture array cannot be one batch, because one batch samples exactly one array. BuildFrame rejects it with FontsNotMounted. A per-array batch split requires a multi-batch FrameOutput contract.*

## 30. TTS: the main-thread contract and localized voice fallback

Speech is the one accessibility surface that cannot be simulated on a worker. SAPI 5 creates an apartment-threaded COM object, AVSpeechSynthesizer owns a main-run-loop object, and neither tolerates being built or driven from a JobSystem thread. The kernel now enforces that in three layers: RequireMainThread() on every entry point, FBY_ASSERT_MSG in an assert build, and a release fallback that logs and drops the unsafe call. A simulation worker can still change the narrative locale; it only records the pending language, which FlushSpeech() applies on the owner thread before the next utterance.

| Entry point | Affinity | Worker call |
|---|---|---|
| **SapiTts::Initialize / AvSpeechTts::Initialize** | OS main thread / main run loop | Returns false after RequireMainThread(); assert build aborts. |
| **SapiTts::SetVoice / AvSpeechTts::SetVoice** | OS main thread / main run loop | Dropped with a log line; no COM/Objective-C call is issued. |
| **SapiTts::Speak / Stop / SetRate** | OS main thread | Dropped; SAPI stays usable for the owner thread. |
| **AccessibilityKernel::SetBlindMode** | OS main thread | Returned before touching settings or attaching the backend. |
| **AccessibilityKernel::SetTtsBackend** | OS main thread | Returned; the previous backend stays installed. |
| **AccessibilityKernel::SetNarrativeLocale** | any thread | Records a pending language; setVoice() runs later in FlushSpeech(). |
| **AccessibilityKernel::FlushSpeech** | OS main thread | Returns before the narrative log is touched, so no event is stolen. |
| **NativeTtsBackend** | OS main thread | Returns nullptr; COM/AVFoundation is never initialized on the worker. |

Voice selection is a locale search, not a token filter. The old implementation mapped only the first letter of the tag to Language=409/419 and returned silently for everything else, so a Russian narrative on an English OS kept an English voice (or, after a failed filter, kept whatever was already installed). SetVoice() now parses the BCP-47 primary language, resolves the full tag through LocaleNameToLCID, enumerates every installed SAPI token and scores it.

| Score | Meaning | Example |
|---|---|---|

| | | |
|---|---|---|
| **4** | Exact LCID match | requested ru-RU, installed ru-RU |
| **3** | Same language and same sublanguage/region | requested ru-RU, installed ru (0x0419) |
| **2** | Same primary language, different region | requested en-GB, installed en-US |
| **0** | No shared language -> system default voice | requested ru-RU on an English-only OS |

```
// AccessibilityKernel::SetBlindMode - main thread only.
if (!RequireMainThread("AccessibilityKernel::SetBlindMode")) { return; }
MTtsBackend = NativeTtsBackend();   // SAPI COM / AVSpeech created here
ApplyTtsLanguage();                // setVoice on the owner thread

// A worker that changes the locale never reaches the backend.
void AccessibilityKernel::SetNarrativeLocale(std::string_view locale) noexcept
{
    // ... update MTtsLanguage ...
    if (IsMainThread()) { ApplyTtsLanguage(); } else { MPendingVoiceLanguage =
true; }
}

// The owner thread applies it before draining the log.
void AccessibilityKernel::FlushSpeech() noexcept
{
    if (std::this_thread::get_id() != MMainThread) { return; }  // drop, do not
steal
    if (MPendingVoiceLanguage) { ApplyTtsLanguage(); }
    // ... speak NarrativeEvents ...
}

// SAPI fallback: score 4/3/2, else the system default. Never silent.
LogWarn("tts", "no installed voice matches '{}'; falling back to LCID 0x{:04X}",
        tag, defaultLcid);
```

- The SAPI implementation no longer includes sphelper.h: it uses ISpObjectTokenCategory directly, so the engine build does not depend on the ATL component (a machine without atlbase.h still builds).
- AVSpeech enumerates [AVSpeechSynthesisVoice speechVoices], scores the language prefix and stores the best installed language; the system default is the fallback.
- Every decision is logged once with the requested tag, the selected LCID/language and whether it was a fallback, so a support ticket can say what the player actually heard.

*Debug builds compile FBY_ASSERT_MSG into every guard listed above. A call from the wrong thread stops in the debugger with the exact function name instead of producing an intermittent COM failure or a silent run loop corruption. Release builds keep the guard semantics but not the abort: they log and refuse the call.*

## 31. State-Driven Gameplay: AnimGraph, StateTree AI and the Animation Graph Canvas

The high-level gameplay layer follows the same rule as the renderer: behaviour is a function over plain data, not a graph of objects. AnimGraph is a flat animation state machine and StateTree is a flat AI state tree. Neither one has a base class, a virtual Evaluate(), a per-node heap allocation or a std::function callback. An entity owns a fixed-size POD component; the system owns the shared tables (the animation clips and the AI node/transition arrays) and walks only the active path.

Why not a Behaviour Tree: a BT re-walks its hierarchy from the root every tick, so the cost of an idle NPC is proportional to the size of its tree. A State Tree stores the active path once and re-evaluates one guard; transitions are a flat, trigger-indexed array. The same reasoning applies to AnimGraph: transition conditions are state-time, tag and float comparisons on the component, and the expensive part - the bone pose - is blended once per tick, never per graph node.

Project Settings owns one Gameplay Tags database. Tags are authored as paths, stored in project.femproj and copied into GameplayTagRegistry on Apply. Definitions are project-global; values stay on the entity in GameplayTagsComponent, GameplayAttributesComponent, GameplayEffectsComponent and GameplaySkillsComponent. That split keeps ECS iteration packed and keeps SDF/world data separate from gameplay.

The AI runtime is perception -> StateTree -> buffered AICommand -> AIController -> navigation and GameplaySkillSystem. The controller never moves an entity, applies damage or emits a combat event: it writes NavAgentSettings, activates skills, and routes ActionId as data for a game-owned ECS system. All combat rules live in game effects and that system. Navigation offers a cost-grid NavMap, a paged flow field for large worlds and a convex NavMesh with a portal funnel. Per-agent NavAgentPathSettings select raw, line-of-sight, Chaikin or Catmull-Rom paths, deterministic route noise and waypoint jitter; every generated segment is validated against the walkable grid.

| AnimStateComponent field | Type | Role |
|---|---|---|
| **CurrentState** | uint64_t | Opaque logical state id. 0 = rest pose; gameplay owns the numbering. |
| **PreviousState** | uint64_t | Source pose of the active cross-fade. |
| **StateTime** | float | Seconds in the current state; reset on every fired transition. |
| **TransitionCount** | uint32_t | Diagnostics. Placed at offset 20 to fill the pad before the 8-byte-aligned transition array. |
| **Transitions[8]** | AnimTransition | Authored transitions, evaluated in array order; first match wins. Inert when Conditions == AnimConditionNone. |
| **Clips[8] / ClipCount** | AnimClip | Per-entity clip table: bone keys plus the SpriteAnimation frame range for the same state. |

| | | |
|---|---|---|
| **Floats[8]** | float | Float parameters (speed, health, aim) read by the transition conditions. |
| **RestPose[128]** | AnimRestBone | Captured once from the skeleton; a clip only authors the bones it moves. |
| **BlendDuration / BlendTime / BlendWeight** | float | Cross-fade timing and the eased weight the SkeletalAnimation bridge applies. |

| Condition flag | Evaluator |
|---|---|
| **AnimConditionStateTimeAtLeast** | StateTime >= StateTimeThreshold |
| **AnimConditionStateTimeAtMost** | StateTime <= StateTimeThreshold |
| **AnimConditionTagsAny** | Any of TagsAny[0..TagsAnyCount) is present in GameplayTagsComponent.Tags |
| **AnimConditionTagsAll** | All of TagsAll[0..TagsAllCount) are present |
| **AnimConditionTagsNone** | None of TagsAny[0..TagsAnyCount) is present |
| **AnimConditionFloatAtLeast / AtMost** | Floats[FloatParam] compared with FloatThreshold; a non-finite value fails closed. |

```
// AnimGraph.hpp - the component prefix is stable and visible in an inspector.
struct AnimStateComponent
{
    std::uint64_t CurrentState = 0;   // 0  logical state, 0 = rest
    std::uint64_t PreviousState = 0;  // 8  cross-fade source
    float StateTime = 0.0f;           // 16 seconds in state
    std::uint32_t TransitionCount = 0;// 20 diagnostics / pad
    std::array<AnimTransition, 8> Transitions{};  // 24
    std::array<AnimClip, 8> Clips{};
    std::array<float, 8> Floats{};
    std::array<AnimRestBone, kMaxBones> RestPose{};
    float BlendDuration = 0.0f, BlendTime = 0.0f, BlendWeight = 1.0f;
    // ...
};

// Once per fixed tick: conditions -> state -> two bridges.
for (auto [entity, state] : registry.view<AnimStateComponent>().each())
{
    state.StateTime += dt;
    const std::uint64_t tags = gameplayBits(registry, entity);
    for (auto& t : state.Transitions)
    {
        if (t.FromState != kAnimAnyState && t.FromState != state.CurrentState)
continue;
        if (!AnimTransitionMatches(t, state, tags)) continue;
```

```
        state.PreviousState = state.CurrentState;
        state.CurrentState = t.ToState;
        state.StateTime = 0.0f;
        state.BlendDuration = t.BlendDuration;
        break;   // first match wins, at most 8 comparisons
    }
    // SkeletalAnimation: blend local TRS, then one hierarchy pass.
    if (auto* skeleton = registry.try_get<SkeletonComponent>(entity))
        AnimGraphApplySkeletal(state, *skeleton);
    // SpriteAnimation: only on a state change, so the frame advance is not
fought.
    if (changed) AnimGraphApplySpriteClip(state, spriteAnimation, grid,
spritePtr);
}
```

The SkeletalAnimation bridge blends in local TRS space - shortest-arc rotation, linear position and scale - and then calls SkeletalAnimation::Evaluate() exactly once. That single hierarchy pass rebuilds globalMatrices and the Mat4 skinningMatrices palette that the GPU consumes. Lerping two composed Mat4 palettes would be cheaper by one pass but produces shear on a rotating parent/child chain and is not a rigid transform; the local blend keeps every bone rigid. The SpriteAnimation bridge is the opposite trade-off: it is instantaneous by design (startFrame, frameCount, duration, currentFrame = 0, UV applied in the same tick), because a flipbook has no interpolatable pose.

| StateTreeComponent field | Type | Role |
|---|---|---|
| **ActiveStates[4]** | uint16_t | Dense root-first path: [0] root, last = active leaf, unused = kStateTreeNone. A State Tree never stores the whole node list per entity. |
| **CurrentLeaf** | uint32_t | Node index of the active leaf (also ActiveStates[ActiveDepth - 1]). |
| **ActiveDepth** | uint32_t | 1..4; validated by StateTreeAddNode so BuildPath cannot overrun. |
| **Triggers** | uint64_t | Pending change triggers. 0 -> the transition table is not touched at all this tick. Bit 63 is reserved for the internal leaf-guard-failed event. |
| **Target / TargetPosition** | Entity / Vector2D | Blackboard: a live entity target, with a cached position fallback for patrol points. |
| **Floats[4]** | float | Float blackboard read by FloatBelow / FloatAbove (health, threat, ...). |

| | | |
|---|---|---|
| **StateTime / Ticks** | float / uint32_t | Time in the current leaf and fixed ticks since entry; reset by BuildPath. |
| **TreeId** | uint32_t | Selects a StateTreeDefinition owned by the system; many entities share one tree. |

| Flat table | Contents | Cost per tick |
|---|---|---|
| **StateTreeDefinition::Nodes[64]** | Root/Selector/Leaf kind, parent, intrusive child list, depth, evaluator, task. | Not walked in steady state. |
| **StateTreeDefinition::Transitions[32]** | FromLeaf, ToNode, TriggerMask, ConsumeMask, RequireTags, ForbidTags. | Scanned only when Triggers != 0. |
| **StateTreeEvaluator** | Flat enum + uint64 tag mask + float threshold + float index, switched in one function. | One call for the active leaf. |
| **StateTreeTask** | None / MoveToTarget / Stop / SetTag / ClearTag / ActivateSkill / Action. | Movement and skills are built in; Action routes ActionId to the developer registry. |

```
// Authoring: a fixed table, no allocations, depth enforced at AddNode().
StateTreeDefinition tree; tree.TreeId = 7;
const auto root  = StateTreeAddNode(tree, StateTreeNodeKind::Root);
const auto group = StateTreeAddNode(tree, StateTreeNodeKind::Selector, root);
const auto action = StateTreeAddNode(tree, StateTreeNodeKind::Leaf, group);
const auto move   = StateTreeAddNode(tree, StateTreeNodeKind::Leaf, group);
StateTreeTask actionTask; actionTask.Kind = StateTreeTaskKind::Action;
actionTask.ActionId = 1;   // game-registered callback
StateTreeSetLeaf(tree, action,
                 StateTreeEvaluator{StateTreeEvaluatorKind::TargetWithinRadius,
0, 64.0f, 0},
                 actionTask);
StateTreeSetLeaf(tree, move,
                 StateTreeEvaluator{StateTreeEvaluatorKind::AlwaysTrue, 0, 0.0f,
0},
                 StateTreeTask{StateTreeTaskKind::MoveToTarget, 0, 120.0f, 0});
StateTreeTransition spotted{};
spotted.FromLeaf = move;
spotted.ToNode = action;
spotted.TriggerMask = 1ull << 0;   // "player spotted"
spotted.ConsumeMask = 1ull << 0;
StateTreeAddTransition(tree, spotted);

// Runtime: the path is data, the transition table is consulted only on a
trigger.
void StateTreeSystem::Run(ecs::SystemContext& ctx) const noexcept
```

```
{
    for (auto [entity, state] : ctx.registry.view<StateTreeComponent>().each())
    {
        const auto* tree = Tree(state.TreeId);
        if (!state.Active || tree == nullptr) continue;
        state.Tags = gameplayBits(ctx.registry, entity);
        ++state.Ticks; state.StateTime += ctx.dt;
        if (!state.Initialized) { BuildPath(*tree, SelectLeaf(...), state); }
        else if (!GuardPasses(state, *tree)) state.Triggers |=
kStateTreeTriggerLeafFailed;
        if (state.Triggers != 0) TryTransitions(*tree, state);  // flat, <= 32
entries
        RunTask(ctx, entity, state, *tree);  // emits AICommandComponent
    }
}
```

- No inheritance, no virtual dispatch: StateTreeNodeKind, StateTreeEvaluatorKind and StateTreeTaskKind are enums switched in one translation unit. A plugin adds a new evaluator by extending the enum and the switch, not by subclassing a node.
- No per-frame tree walk: with no pending trigger the system reads one guard and runs one task. A Behaviour Tree tick would touch every branch of the hierarchy.
- No runtime allocation: nodes, transitions, the active path and the command payloads are fixed arrays; CommandBuffer copies the tiny AICommandComponent into the frame arena and Play() applies it after the fixed steps.
- Determinism: Phase::FixedUpdate + fixed dt + insertion-order command replay. Network rollback can reproduce the same ActiveStates path from the same triggers.

The runtime tables above are authored by AnimationGraphCanvasPanel, the ImNodes editor in Source/Editor/Panels. The panel is intentionally not a second runtime model: its document is a trivially copyable AnimationGraphDocument registered as one CommandStack external buffer. A clip node compiles to AnimClip, a float-parameter node compiles to AnimStateComponent::Floats, a direct clip-to-clip link compiles to AnimTransition, and a blend node compiles to the AnimTransition of the Idle -> Attack style cross-fade. The runtime never sees ImNodes, positions, names or the editor's blend topology.

| Editor node | Pins | Compiles to |
|---|---|---|
| **Clip** | In, Out | AnimClip (State, Keys[8], SpriteAnimation start/count/duration/loop/play). |
| **Float Parameter** | Float out | AnimStateComponent::Floats[ ParameterIndex] = ParameterValue; the index is also used by AnimConditionFloatAtLeast/At Most. |
| **Blend** | Src, Mod, Out | One AnimTransition from the source clip to the target clip; BlendDuration and the condition bitmask live on the |

| | | |
|---|---|---|
| | | blend node, the optional Mod binding supplies FloatParam. |

| AnimationGraphDocument field | Type / capacity | Role |
|---|---|---|
| **GraphId** | uint32_t | Identity used by the scene TOML block and by the PIE binding. |
| **NodeCount / Nodes[24]** | uint16_t / AnimationGraphNode | Fixed union-like POD node: kind, enabled, name[32], position, AnimClip, AnimTransition blend payload, parameter index/value. |
| **LinkCount / Links[32]** | uint16_t / AnimationGraphLink | Kind, endpoints, pins and the direct AnimTransition payload. The four link kinds are Transition, BlendSource, BlendParameter and BlendTarget. |

```
// CompileGraph(): fixed storage, one flat AnimStateComponent, no allocation.
AnimStateComponent out;
std::array<bool, kMaxAnimParams> paramUsed{};
std::array<std::uint64_t, kMaxAnimClips> stateIds{};
std::uint16_t clipCount = 0, transitionCount = 0;
for (node : document.Nodes)
    if (node.Kind == Clip)
    {
        if (node.Clip.State == 0 || duplicate(stateIds, node.Clip.State))
reject();
        stateIds[clipCount] = node.Clip.State;
        out.Clips[clipCount++] = node.Clip;
    }
    else if (node.Kind == FloatParameter)
        out.Floats[node.ParameterIndex] = node.ParameterValue;
// Isolated-node check: every node needs at least one incident link.
for (node : document.Nodes) if (degree[node] == 0) reject("isolated");
// Direct links become transitions; each Blend needs one source, one target
// and at most one parameter binding.
for (link : document.Links)
    if (link.Kind == Transition && conditionsValid(link.Transition))
        out.Transitions[transitionCount++] = link.Transition;
for (blend : document.Nodes)
    if (blend.Kind == Blend)
        out.Transitions[transitionCount++] = makeTransition(blend, source,
target);
for (i = transitionCount; i < 8; ++i)
    out.Transitions[i].Enabled = false;   // inert slots, not garbage
```

```
out.ClipCount = clipCount;
out.TransitionCount = 0;                    // runtime diagnostic, not an authored
count
```

Every gesture is one CommandStack transaction. The document is a single external buffer, so a node drag records only the changed position bytes and a condition toggle records only the changed condition word. The ImNodes callbacks never call Record() directly: DrawCanvas reports a state change, ProcessCanvasEvents opens BeginEdit(), the edit method mutates the document, RecordEdit() captures the new bytes, and CommitEdit() commits one undo group. Ctrl+Z/Ctrl+Y are handled by EditorSystem, which first commits any open canvas transaction and then asks CommandStack to apply the inverse delta. Inspector edits use the Mirror-backed AnimationGraphTransitionFieldsEqual()/_ClipFieldsEqual() helpers; both compare only the FieldDesc byte ranges through reflect::FieldBytesEqual(), so padding bytes cannot create an empty undo command.

| Condition bit | Inspector control | Runtime evaluator |
|---|---|---|
| **AnimConditionStateTimeAtLeast** | StateTimeAtLeast checkbox + StateTimeThreshold | StateTime >= threshold |
| **AnimConditionTagsAll** | TagsAll checkbox + TagsAll mask | (tags & TagsAll) == TagsAll; empty mask fails closed |
| **AnimConditionFloatAtMost** | FloatAtMost checkbox + FloatParam + FloatThreshold | Floats[FloatParam] <= FloatThreshold |

```
# Appended by "Compile Animations"; EditorSystem re-appends it after Ctrl+S.
[anim_graph]
version = 1
graph_id = 12
node_count = 4
link_count = 4

[[anim_graph.node]]
kind = 0                        # Clip
name = "Idle"
position = [-260.0, 40.0]
clip_state = "0x0000000000000001"
clip_key_count = 1
clip_sprite_count = 4
[[anim_graph.node.key]]
bone = 1
rotation = 0.5
position = [0.0, 0.0]
scale = 1.0

[[anim_graph.node]]
kind = 2                        # Blend
blend_duration = 0.2
blend_conditions = 64           # FloatAtMost/AtLeast family
blend_float_param = 0
```

```
[[anim_graph.link]]
kind = 0                        # Transition
from = 1
to = 0
t_conditions = 1                # StateTimeAtLeast
t_state_time = 1.0
t_duration = 0.15
```

PIE debugging is a read-only projection of the live component back onto the authored document. RefreshPIEState() finds the selected entity (EditorSelected), reads AnimStateComponent::CurrentState/PreviousState and maps those 64-bit ids to Clip nodes; LastTransition maps through the compiler's transition-to-link table to the exact authored link. The current node is drawn with a pulsing neon outline and a ProgressBar for BlendWeight, the PreviousState is drawn in the cross-fade source colour, and BlendTime/BlendWeight are shown both on the canvas and in the Mirror inspector. No debug draw allocates; it only reads the component and writes ImGui draw commands.

*Both systems are render-agnostic: AnimStateComponent writes only skeleton/SpriteAnimation data and StateTreeComponent writes only AI intent. The Metal backend now consumes the same 32-bit DrawBatch contract as Vulkan - per-batch setFragmentTexture: and a vertex-buffer offset instead of baseInstance - so the batch a State Tree or AnimGraph frame produces looks identical on both APIs.*

## 32. Advanced AAA DOD Pipelines: Virtual Texturing, Component Change Masks, Relevance Grids, and Audio Buses

Chapter 32 documents the four pipelines added to the Release build. They share one constraint: a frame may not allocate, may not walk a scene graph and may not upload a resource that did not change. VirtualTextureSystem turns the world into VFS-mapped chunk files and a fixed 2048 texture array; ChangeMaskRenderExtract turns a 64-bit per-entity word into coalesced SSBO ranges; RelevanceGrid turns a spatial mdspan into a per-player snapshot filter; AudioZoneSystem turns a Box2D sensor volume into a lock-free bus filter ramp. Each subsystem has a fixed-capacity data layout and a headless acceptance test.

| Pipeline | Mutable state | Bounded by | Per-frame allocation |
|---|---|---|---|
| **VirtualTextureSystem** | Page residency table + VFS mappings | layerCount x 32 x 32 pages | 0 |
| **ChangeMaskRenderExtract** | Stable entity slots + sorted output cache | Capacity template parameter | 0 |
| **RelevanceGrid** | mdspan cells + one 64-bit bitset per plan | cellsX x cellsY <= 4096 | 0 |
| **AudioZoneSystem** | One context record per listener | kMaxZones = 64 authored zones | 0 |

31.1 Virtual texturing. The world address space is split into 64x64 tiles. Four tiles per axis form one 256x256 RGBA8 chunk file, so a single VFS mapping supplies sixteen tile uploads. The GPU owns a fixed 2048x2048 texture array with N layers; a layer is a 32x32 page pool and every page is one tile. The resident bytes are therefore exactly

```
// Constant VRAM, independent of the camera path or the world size.
constexpr std::uint64_t kPageBytes = 2048ull * 2048ull * 4ull;
const std::uint64_t Budget = layerCount * kPageBytes;

// Residency is a two-pass clock over a fixed page table.
void VirtualTextureSystem::Update(const VirtualTextureCamera& InCamera) noexcept
{
    ++MFrame;
    const float HalfX = InCamera.ViewSize.X * 0.5f / InCamera.Zoom;
    const float HalfY = InCamera.ViewSize.Y * 0.5f / InCamera.Zoom;
    const float X = std::fabs(std::cos(InCamera.Rotation));
    const float Y = std::fabs(std::sin(InCamera.Rotation));
    const float ExtentX = HalfX * X + HalfY * Y;   // rotated AABB
    const float ExtentY = HalfX * Y + HalfY * X;
    for (std::int64_t Ty = MinY; Ty <= MaxY; ++Ty)
        for (std::int64_t Tx = MinX; Tx <= MaxX; ++Tx)
        {
            const std::uint32_t Layer = LayerForTile(Tx, Ty);
            const std::uint32_t Hash = FindHash(Tx, Ty);
            if (Hash != kHashCapacity)
            {
                MSlots[Layer * 1024u + MHash[Hash].slot].lastUsedFrame = MFrame;
                continue;
            }
            std::uint32_t Slot = 0;
            if (LoadTile(Tx, Ty, Layer, &Slot))   // mmap chunk, upload one
64x64 tile
            {
                MSlots[Layer * 1024u + Slot].lastUsedFrame = MFrame;
                ++MStats.uploads;               // one vkCmdCopyBufferToImage
            }
        }
}
```

| Chunk header field | Offset | Value | Validation |
|---|---|---|---|
| **magic** | 0 | FBYVTC01 | Rejected before the mapping is indexed |
| **version** | 8 | 1 | A future format fails closed |
| **tileSize** | 12 | 64 | Must equal the descriptor |
| **chunkTiles** | 16 | 4 | Must equal the descriptor |
| **format** | 20 | 0 = RGBA8 | No runtime decode |

| | | | |
|---|---|---|---|
| **pixels** | 32 | 256 x 256 x 4 | Exact size check before subspan |

- Eviction is a per-layer clock. A page whose lastUsedFrame is the current frame is visible and is never a victim; if all 1024 pages of a pool are visible the request is counted as a spill instead of corrupting a tile that is on screen.
- The resident lookup is open addressing with tombstones. A hit costs one hash probe and a store into lastUsedFrame; a chunk mapping is never re-read for a resident tile.
- VirtualTextureSystem itself is about 2 MiB (page table plus the 65536-entry hash). It is a startup object, allocated once on the heap, not a stack local in a frame function.

31.2 Component change masks. A render-visible entity carries ComponentChangeMask next to Transform2D/Sprite2D. A mutating system calls change::MarkTransform(), MarkSprite() or MarkDrawOrder(); the mark is one atomic fetch_or on the 64-bit word. The extract peeks the word, consumes it with fetch_and(0), and recomputes a RenderItem only when one of the three render bits was present. An entity with a zero mask reaches one pointer lookup and one relaxed load - no Transform read, no Sprite copy, no RenderKey arithmetic.

| Bit | Name | Consumer | Effect |
|---|---|---|---|
| **0** | Transform2D | ChangeMaskRenderExtract | Rebuild position/scale/rotation; key unchanged |
| **1** | Sprite2D | ChangeMaskRenderExtract | Rebuild UV/size/colour/layer |
| **2** | DrawOrder | ChangeMaskRenderExtract | RenderKey may move: structural rebuild |
| **3-9** | Velocity/ GameplayTags/ Animation/Audio/ Physics/Lifetime/ Custom | Gameplay systems | Consumed by the owner; the GPU sees nothing |
| **16-63** | GameBitBase + n | Game code | Reserved for project aliases |

```
struct ComponentChangeMask          // 16 bytes, align 8
{
    ChangeMask   Bits      = 0;     // offset 0, atomic_ref target
    std::uint32_t LastFrame = 0;    // offset 8, diagnostic only
    std::uint32_t Reserved  = 0;    // offset 12, zero
};
static_assert(sizeof(ComponentChangeMask) == 16);

// A system marks after the write, not before: the extract must never see a bit
// for a value it has not finished writing.
```

```
transform.Position = NewPosition;
Fby::Change::MarkTransform(registry, entity, frameIndex);

// Extract: static items fall through after one relaxed load.
for (auto [e, mask, transform, sprite] : view.each()) {
    const ChangeMask Bits = change::Peek(mask);
    if (Bits == 0 && SlotKnown(e)) { ++stats.skippedStatic; continue; }
    const ChangeMask Hit = change::Consume(mask);
    if ((Hit & kRenderBits) == 0) { continue; }
    BuildItem(registry, e, &items[slot], &keys[slot]);
}
```

```
// Output-relative dirty ranges coalesced in one sorted pass.
struct DirtyRange { std::uint32_t first; std::uint32_t count; };
static_assert(sizeof(DirtyRange) == 8);

// Transform-only edit: key unchanged, order unchanged, patch one output item.
MOutputItems[MOutputIndex[slot]] = MItems[slot];
MChangedScratch[MChangedCount++] = MOutputIndex[slot];
// ... sort + coalesce into 1..N ranges; the backend uploads only those bytes.

// DrawOrder edit: the item can move in the sort. The safe upload is the whole
// sorted range, because firstItem in every DrawBatch may have shifted.
if (OldKey != NewKey) { RebuildOutput(); return DirtyRange{0, MOutputCount}; }
```

FillPacket() publishes the same ranges as FramePacket::instanceRanges and sets instanceRangesAreDeltas. VulkanRHI copies only those ranges into its persistent per-frame instance slice once that slice has received one full image; a first use, a resize or a structural rebuild falls back to the full copy. MetalRHI keeps the full-copy fallback, so the packet contract is portable while the optimisation is explicit.

- No allocation: every slot, key, batch, dirty range and lookup bucket lives inside the Capacity-templated object. The default 4096 covers a large 2D scene; a streaming world instantiates ChangeMaskRenderExtract<1u << 18> without changing a line of API.
- The extract exposes both arrays: Items()/Keys()/Batches() fill the existing FramePacket, while DirtyRanges() is the upload plan for a backend that owns a persistent instance SSBO. A zero-mask frame with no structural change produces an empty range list.
- A layer change is deliberately treated as structural even when the float depth did not move: batching groups by the top 16 RenderKey bits, so a stable order is a correctness condition, not an optimisation.

31.3 Network relevance grid. NetRollbackSession owns the stable NetEntityId map; RelevanceGrid owns an mdspan of cells. The grid is rebuilt once per tick: entities are sorted by NetEntityId, their Transform2D position selects a cell, and each cell appends a fixed number of ids. The plan for one player walks only the square of cells inside farRadius. Current and neighbouring cells are immediate; the near ring is gated by nearInterval; the far ring by farInterval. The phase is NetEntityId::value % interval, so distant objects do not all update on the same tick.

| Band | Chebyshev distance | Cadence | Typical payload |
|---|---|---|---|

| | | | |
|---|---|---|---|
| **Immediate** | 0..neighborRadius (default 1) | every tick | player, nearby actors, doors |
| **Near** | neighborRadius+1..nearRadius | every nearInterval ticks | mid-distance props |
| **Far** | nearRadius+1..farRadius | every farInterval ticks | ambient movers, VFX anchors |
| **Outer** | > farRadius | never | not in the plan |

```
// The cell grid is an mdspan over one flat vector<RelevanceCell>.
std::mdspan<RelevanceCell, std::dextents<std::size_t, 2>>
    Grid(MCells.data(), MConfig.cellsY, MConfig.cellsX);

// Rebuild once per tick, deterministically sorted by NetEntityId.
InEntities.ForEach([&](NetEntityId Net, Entity Local) noexcept {
    MSortScratch[Count++] = SortableEntity{Net.Value, Local};
});
std::sort(MSortScratch.begin(), MSortScratch.begin() + Count,
          [](const auto& A, const auto& B) { return A.id < B.id; });
for (const SortableEntity& E : span(MSortScratch.data(), Count)) {
    const Transform2D& T = InRegistry.get<Transform2D>(E.local);
    Grid[CellY(T.Position), CellX(T.Position)].Append(NetEntityId{E.id});
}

// Plan: walk only cells inside farRadius; the bitset is O(1) membership.
const RelevanceBand Band = BandFor(std::abs(Cx - PlayerCx), std::abs(Cy -
PlayerCy));
const std::uint32_t Interval = Band == RelevanceBand::Immediate ? 1u
    : (Band == RelevanceBand::Near ? Config.nearInterval : Config.farInterval);
if (!IsDue(Interval, Id, Tick)) { continue; }
OutPlan.items[OutPlan.count++] = RelevanceEntity{Id, Cx, Cy, Band};
OutPlan.Set(Id);
```

```
// Filtering is a record copy, not a registry walk. The output is a valid
// Snapshot v4 delta against the same base: checksum and counts are rebuilt.
for (std::uint32_t R = 0; R < View.header.entityCount; ++R) {
    const FilteredRecordHeader& Rec = ReadRecord(View.payload, Offset);
    const bool Removed = (Rec.Flags & SnapshotEntityRemoved) != 0;
    const NetEntityId Net = MEntities.IdOf(Rec.entity);
    const bool Keep = Removed ? InKeepRemovals : InPlan.Contains(Net);
    if (Keep) { CopyRecord(Rec, Out); ++Out.header.entityCount; }
}
Out.header.checksum = Fnv1a(OutPayload);
// Client: RestoreDelta(base, filtered) - each record still restores the
// component bytes that the server captured for that tick.
```

| RelevancePlan field | Size | Purpose |
|---|---|---|
| **player, tick** | 16 B | Identifies the wire view |

| | | |
|---|---|---|
| **items[4096]** | 64 KiB | Sorted RelevanceEntity records |
| **bits[64]** | 512 B | One bit per NetEntityId for O(1) delta filtering |
| **immediate/near/far counts** | 12 B | Diagnostics and bandwidth budgeting |

31.4 Hierarchical audio buses. AudioZoneComponent is the authored Box2D sensor volume: an AABB copied from the shape, a stable zoneId, a priority, a bus mask and the two target parameters ReverbGain and LowPassHz. AudioContextComponent is the listener's resolved state. AudioZoneSystem picks the highest-priority containing zone, interpolates the context in game time with a one-pole ramp and emits at most three fixed commands (Master, SFX, Music). The audio thread then ramps the actual coefficient per sample inside ApplyFilter and the reverb return gain inside ApplyReverb; neither function allocates, locks or calls into ECS.

| Bus | Flag | Zone parameter | Audio-thread stage |
|---|---|---|---|
| **Master** | bit 0 | ReverbGain, LowPassHz | ApplyFilter -> ApplyReverb -> ApplyBusGain |
| **SFX** | bit 1 | ReverbGain, LowPassHz | Same chain, independently |
| **Music** | bit 2 | ReverbGain, LowPassHz | Same chain, independently |
| **Cave (example)** | Master+SFX | 0.45, 900 Hz | A 0.1 s context fade, then a sample ramp |
| **Underwater (example)** | All | 0.20, 450 Hz | Priority 9 wins over Cave |

```
struct AudioZoneComponent                  // authored, trivially copyable
{
    Vector2D min, max;                    // Box2D sensor AABB, world units
    std::uint32_t zoneId, kind, priority, busMask, flags;
    float reverbGain;                     // 0..4, return gain
    float lowPassHz;                      // 20..20000 one-pole cutoff
    float fadeSeconds;                    // context cross-fade time
};

struct AudioContextComponent              // resolved per listener
{
    std::uint32_t activeZoneId, previousZoneId, activeKind, flags;
    float blend, reverbGain, lowPassHz;
    float targetReverbGain, targetLowPassHz, fadeSeconds;
    Vector2D listenerPosition;
    float lastSentReverbGain, lastSentLowPassHz;
    std::uint32_t lastBusMask;
};
```

```
// Zone system: retarget and ramp the game-side context.
const float Alpha = 1.0f - std::exp(-dt / Fade);
Context.reverbGain += (Context.targetReverbGain - Context.reverbGain) * Alpha;
Context.lowPassHz  += (Context.targetLowPassHz  - Context.lowPassHz)  * Alpha;
Context.blend = Saturate(Context.blend + dt / Fade);
Audio.SetBusZoneParameters(AudioBus::Sfx, Context.reverbGain, Context.lowPassHz,
Fade);
```

```
// Audio thread: coefficient and reverb gain are ramped per sample.
const float Start = ScopedCoefficient(CurrentCutoff);
const float End   = ScopedCoefficient(TargetCutoff);
for (std::uint32_t F = 0; F < Frames; ++F) {
    const float C = Start + (End - Start) * T(F);
    State[0] += C * (Buffer[F * 2 + 0] - State[0]);
    State[1] += C * (Buffer[F * 2 + 1] - State[1]);
    Buffer[F * 2 + 0] = State[0];
    Buffer[F * 2 + 1] = State[1];
}
// Reverb return: value = wet * wetParams * zoneGainRamp(F).
// Command ring: SetBusFilter, fixed size, no lock on the producer side.
```

*The four pipelines are covered by the headless advanced_pipelines test. It mounts a real directory, writes real .fvtc chunks and verifies that a second view produces zero uploads; it checks that a static entity produces an empty dirty range; it builds a real Snapshot v4 delta and verifies that FilterDeltaForPlayer keeps one of two records; and it drives a priority-9 underwater zone to 450 Hz and back to open. No GPU or audio device is opened, so the test runs on a headless CI agent.*

## 33. Production Distribution: Encryption, LZMA Compression, and the Steam/EGS/GOG Release Checklist

Chapter 33 closes the distribution gap between the isolated console tools and the editor. Before this chapter the tree had fby_fempak (cook, secure, list, extract), FemArchiver (LZMA/FbyLZ plus ChaCha20-Poly1305/AES-256-GCM), FemCrypto, AotBuilder and the per-panel 'Cook AOT' action, but no single operation that ran them as one release. The ReleaseCooker class now owns that operation: one Build & Pack Game button starts the native logic plugin, the ordered asset cook, the deterministic .fempak writer and the encrypted .femarc wrapper, then publishes progress to SceneDiagnosticsPanel.

| Stage | Command / class | Writes | Failure contract |
|---|---|---|---|
| **Key** | ReleaseCooker::PrepareKey | .fbyrelease.seed, release.key.tmp, ReleaseKey.generated.hpp | No plaintext key in project.femproj or editor.ini |
| **AOT** | script::AotBuilder + forceIncludeHeader | logic_graph.cpp / .dll | Skipped when no LogicGraph is bound, never faked |

| | | | |
|---|---|---|---|
| **Cook** | fby_fempak cook --progress | assets.fempak + cook.progress | Non-zero child exit fails the build |
| **Secure** | fby_fempak secure --key-file --progress | game.femarc | AEAD tag failure or missing key fails closed |
| **Progress** | CookProgressRecord -> ReleaseCookProgress | cook.progress / secure.progress | Torn record rejected by double-read sequence check |

31.1 ReleaseCooker. The class lives in Source/Editor/Infrastructure/ReleaseCooker.hpp and links only the editor's existing services. Start() validates paths, creates the release tree, copies the LogicGraph POD and starts one std::jthread. The worker calls AotBuilder, then the cooker and the secure step, while the editor thread calls Progress() once per frame. The UI copy is a fixed POD under a short mutex; the worker never calls ImGui and the editor never blocks on the compiler or the compressor.

```
// One click from the toolbar: Build menu or the Viewport button.
ReleaseCookConfig Config = ReleaseCooker::FromProject(
    projectConfig.Paths(), projectConfig.Project(), EngineRoot, FempakPath);
Config.compileAot = visualScript.Initialized() && visualScript.Graph().nodeCount
!= 0;
char Error[256]{};
if (!releaseCooker.Start(Config, Graph, Error, sizeof(Error)))
{
    SetStatus(Error);
}

// SceneDiagnosticsPanel every frame. No allocation while drawing.
releaseCooker.Poll();
sceneDiagnostics.SetReleaseProgress(releaseCooker.Progress());

// The worker owns the sequence, in this order:
//   PrepareKey -> AotBuilder -> fby_fempak cook -> fby_fempak secure
```

32.2 Key baking. The earlier secure command required --key or --key-env and the editor had no caller. ReleaseCooker now reads a project-local 32-byte seed from .fbyrelease.seed (created with SecureRng when absent), writes a build-scoped binary key file for fby_fempak, and force-includes a generated header into the AOT translation unit. The header exports a C ABI function that reconstructs the key from two XOR arrays; the plugin carries the key, while the project file carries no password. The seed is the only persistent secret, and deleting it rotates the release key on the next build.

```
// Generated into build/release/ReleaseKey.generated.hpp and force-included
// into the AOT plugin (clang-cl /FI, clang/g++ -include).
FBY_RELEASE_KEY_EXPORT bool fby_release_archive_key(std::uint8_t* OutKey,
                                                    std::uint32_t InCapacity)
noexcept
{
    if (OutKey == nullptr || InCapacity < 32u) return false;
```

```
    constexpr std::uint8_t kMasked[32] = { /* key ^ mask */ };
    constexpr std::uint8_t kMask[32]   = { /* build mask */ };
    for (std::uint32_t i = 0; i < 32u; ++i)
        OutKey[i] = static_cast<std::uint8_t>(kMasked[i] ^ kMask[i]);
    return true;
}

// A launcher can resolve the same plugin and call the export before
// opening game.femarc. No password is read from ini or the environment.
```

| File | Lifetime | Contains | On success |
|---|---|---|---|
| **.fbyrelease.seed** | Persistent project secret | 32 random bytes | Kept, mode-restricted by the host |
| **release.key.tmp** | One build only | Plaintext AEAD key for fby_fempak | Overwritten with zeroes and deleted |
| **ReleaseKey.generated.hpp** | Compile only | Masked key + C ABI export | Deleted |
| **archives/ game.femarc** | Shipped artifact | LZMA/FbyLZ + ChaCha20/AES body | Kept |

32.2a Project-local output tree. A project created by the dashboard owns every artifact it produces: build intermediates and the release key live in <root>/build/release, the canonical archive is <root>/archives/game.femarc, and the per-store stages are <root>/stores/{steam,epic,gog}. ReleaseCooker copies the archive and the AOT plugin into each store directory after a successful build and writes a store.txt manifest (project, archive, plugin, cipher, key_baked). Moving or deleting the project directory therefore moves the build, the archive and all store copies together; nothing is written into the engine tree or the process working directory.

32.3 Progress protocol. fby_fempak writes a 424-byte CookProgressRecord to --progress. The record is a POD: stage, completed/total, current asset, raw and stored bytes, elapsed microseconds, bytes/second, cipher and flags. The writer seeks to zero, writes the whole record and flushes after every update; ReleaseCooker reads it twice and accepts only a matching sequence, so a partially written record can never produce a false 90% bar. ArchiveBuildOptions carries a plain function-pointer progress callback, not std::function, so FemArchiver can report per-entry compressed bytes inside its noexcept build.

```
struct CookProgressRecord                       // 424 bytes, ABI-stable
{
    char magic[8];                              // FBYCOOK1
    std::uint32_t version, sequence;
    std::uint32_t stage, completed, total, bytesPerSecond;
    std::uint32_t cipher, flags, reserved;
    std::uint64_t rawBytes, storedBytes, elapsedMicroseconds;
    char asset[192];
    char message[160];
};

// SceneDiagnosticsPanel: the only UI work per frame.
```

```
ImGui::ProgressBar(Progress.Fraction(), ImVec2(-1.0f, 0.0f), Overlay);
ImGui::Text("asset: %s", Progress.asset);
ImGui::Text("LZMA %.2f MB/s", Progress.bytesPerSecond / (1024.0 * 1024.0));
ImGui::Text("encrypted: %s", CookCipherName(Progress.cipher));
```

- The current asset is exact: fby_fempak updates the record before and after every cooked file, so the bar shows the texture, audio or localization file being processed, not a generic 'cooking' label.
- Encryption state is exact: cipher 1/2 and the encrypted flag are copied from the secure build; a missing key or a rejected AEAD tag ends the stage as Failed, never Succeeded.
- LZMA throughput is measured from the archiver's progress bytes and elapsed time. Because the 7-Zip SDK call compresses one .fempak entry as a single operation, the rate is sampled at the entry boundary rather than every 64 KiB; the UI labels the value as measured, not predicted.

32.4 Release checklist. The same artifacts feed Steam, Epic Games Store and GOG. The cook tree is per-project and reproducible: a fixed seed and the deterministic .fempak writer make the archive hash a build stamp; the .femarc keeps LZMA and AEAD settings in its header; the AOT plugin records graph and component layout hashes. A store submission should attach the hash of game.femarc, the plugin, the seed identifier (not the seed itself) and the BuildProfile snapshot.

| Store | Required artifact | ReleaseCooker check | Manual follow-up |
|---|---|---|---|
| **Steam** | game.femarc + plugin + depot VDF | LZMA/AEAD header, archive hash | SteamPipe upload, build id |
| **Epic Games Store** | game.femarc + plugin + EOS manifest | same bytes, EOS artifact hash | EOS BuildPatch, sandbox |
| **GOG Galaxy** | game.femarc + plugin + Galaxy shim | same bytes, shim ABI | Galaxy build, cloud saves |
| **All stores** | Seed identity, BuildProfile | Graph hash + component LayoutHash | Keep seed offline, rotate on leak |

*The build orchestrator needs the fby_fempak executable in build/bin. If the editor was built with FBY_BUILD_TOOLS=OFF, Start() fails before spawning anything and the status bar names the missing packer. The AOT stage is optional by construction: a project with no bound LogicGraph still cooks and secures its assets, and the result reports keyBaked=false.*

## 34. SystemGraph: the parallel scheduling contract, then the blend-cycle contract

G8 changes SystemGraph::Run from a registration-order walk into a dependency-aware dispatcher. Build() already folds every before edge into an after mask; it now also computes a longest-path level per node. Two nodes on the same level cannot depend on each other, so a level is a safe parallel wave. Run(phase) launches every enabled node of one wave through JobSystem, leaves one node for the caller, and joins the wave through a counting_semaphore that lives on the caller's stack. There is no std::function, no allocation and no shared per-system semaphore; a 24-worker pool therefore executes 24 independent systems in the same wave instead of 24 sequential calls.

```
// Build(): longest-path level, same-phase edges only.
for (Position in TopologicalOrder) {
    Node = Order[Position];
    Level = 0;
    for (Dep in DependencyMask(Node))
        if (Phase(Dep) == Phase(Node)) Level = max(Level, MLevels[Dep] + 1);
    MLevels[Node] = Level;
}

// Run(Phase): one wave, one per-call semaphore.
std::counting_semaphore<kMaxGraphSystems> Done{0};
for (I = 1; I < WaveSize; ++I) {
    Wave[I].completed = &Done;
    Jobs.Submit(&InvokeGraphNode, &Wave[I], 0, 0);   // no allocation
}
Wave[0].run(Context, Wave[0].user);                    // caller keeps one node
for (I = 1; I < WaveSize; ++I) Done.acquire();          // join before next
level
```

| Guarantee | Why it is enforced |
|---|---|
| **A node never starts before every after/before dependency completed** | Level = max(dep level) + 1; Run joins a wave before opening the next one |
| **Nodes in one wave never depend on each other** | A dependency edge always raises the dependent's level |
| **No worker thread is leaked or waited on twice** | One release per submitted thunk, one acquire per submission, semaphore is stack-local |
| **Render stays on the render thread** | Run(Render) takes the sequential path: the RHI command stream is single-threaded |
| **A mutation invalidates the schedule** | Add/RemoveUser/Clear set MBuilt = false; Run does nothing until Build() succeeds |

*The dependency mask is the whole data-race contract. Two systems that write the same component pool must have an edge; 'they happened to be registered in this order' is not a dependency. The editor's FixedUpdate chain (events_clear -> movement -> physics -> contacts -> spriteAnimation -> skeletalAnimation_animate) therefore declares five after bits, while independent PostUpdate nodes (skeletalAnimation_evaluate, physics_interpolate, cloth collect) form one wave. JobSystem follows the same contract: MPending and MRunning occupy separate 64-byte lines, so submit/completion traffic from different cores does not bounce one cache line, and ParallelFor uses a per-call semaphore instead of a shared member.*

CompileGraph() is not a serializer: it is the last place where an authored graph can be rejected before AnimStateComponent becomes runtime state. The contract has two layers. The first is local: a Clip node owns one non-zero state id, a Float node owns one unique parameter index, a Blend node owns exactly one source link, exactly one target link and at most one parameter link, and the source and target states must differ. The second is global: the compiled transition graph must have no cycle that can fire forever without an exit.

| Rule | Compiler result | Authoring action |
| --- | --- | --- |
| **Clip state is 0 or kAnimAnyState** | Rejected: needs a non-zero state id | Assign a unique 64-bit gameplay id |
| **Blend source state == target state** | Rejected: cross-fades a state into itself | Pick two different clips |
| **Blend has 0 or 2 source/target links** | Rejected: exactly one source, one target | Delete the extra link |
| **Cycle of hot transitions with no exit** | Rejected: dead blend cycle without an exit | Add a gated exit or remove the loop |
| **Cycle with any enabled exit** | Accepted | Keep the exit before the hot edge in array order |

A transition is 'hot' when it is Enabled, has no tag/float condition, and its state-time predicate is already true at StateTime == 0: StateTimeAtLeast with threshold <= 0, and/or StateTimeAtMost with threshold >= 0. AnimGraphSystem resets StateTime to zero on every fired transition and adds dt before evaluating the next tick, so a hot edge fires on every entry. A hot cycle is a dead loop only when no enabled transition leaves the set of states in that cycle; a gated exit keeps the graph legal even if the loop itself is hot.

```
// Iterative three-colour DFS. Bounded by kMaxAnimClips == 8; no recursion.
std::array<std::uint8_t, kMaxAnimClips> Color{};   // 0 white, 1 gray, 2 black
std::array<std::uint16_t, kMaxAnimClips> Stack{};
for (std::uint16_t Start = 0; Start < N; ++Start) {
    if (Color[Start] != 0) continue;
    std::int32_t Top = 0;
    Stack[0] = Start; Color[Start] = 1;
    while (Top >= 0) {
        const std::uint16_t V = Stack[Top];
        std::uint32_t& Edges = HotEdges[V];
        if (Edges == 0) { Color[V] = 2; --Top; continue; }
        std::uint16_t W = 0;
        while (((Edges >> W) & 1u) == 0) ++W;
        Edges &= ~(1u << W);
        if (Color[W] == 0) { Color[W] = 1; Stack[++Top] = W; continue; }
        if (Color[W] == 1) {
            // W is on the gray stack: reconstruct the cycle, test for an exit.
            if (!HasEnabledExit(Stack, Top, W)) {
                SetStatus("Anim compile: dead blend cycle without an exit: %s",
Path);
                LogLine(LogLevel::Warn, "AnimGraph", MStatus);
                return false;
            }
        }
    }
}
```

*The validator runs on the compiled edge set, not on the ImNodes document, so it sees exactly what the runtime will evaluate: disabled links are already filtered by AnimTransitionMatches, and state ids have been resolved from the links. The warning goes through LogLine (not std::format), so the error path stays noexcept and LogBoy still receives the record. A fully cyclic document is at most 8 vertices: the explicit stack cannot overflow, and the worst case is 64 edge visits.*

## 35. Box2D rollback teardown, then the PIE animation hand-off

R1 is an ownership bug, not a Box2D bug. Registry::clear() destroys ECS objects; it cannot know that RigidBody2D::body is a native b2BodyId, so the old bodies stay in the world while the restored snapshot rows all carry body == 0. The next EnsureBodies()/Step() then creates a second body for every entity. The teardown order is: (1) ask PhysicsSystem to destroy every tracked live body and sweep the registry for joint-link bodies it did not create; (2) clear and restore the snapshot; (3) recreate bodies from the restored bytes. A body is destroyed only after b2Body_IsValid, so a joint system that already tore its anchors down is safe.

```
NetRollbackSession::Result NetRollbackSession::RestoreSnapshot(
    std::span<const std::byte> InSnapshot) noexcept
{
    if (!MInitialized || MRegistry == nullptr || MSchema == nullptr)
        return Result::NotInitialized;

    // R1: native bodies die BEFORE Registry::clear().
    if (MPhysics != nullptr)
        (void)MPhysics->DestroyAllBodies(MRegistry);

    if (!ecs::RestoreSnapshot(*MRegistry, *MSchema, InSnapshot, &MRng))
        return Result::RestoreFailed;

    // Snapshot bytes never carry a b2 handle: rebuild from the restored rows.
    if (MPhysics != nullptr)
        MPhysics->EnsureBodies(*MRegistry);
    return Result::Ok;
}

// PhysicsSystem::DestroyAllBodies: tracked pass + registry sweep.
for (Record : MBodies)
    if (b2Body_IsValid(Load(Record.body)))
        { b2DestroyBody(Load(Record.body)); ++Destroyed; }
MBodies.clear();
for (Body : Registry.view<RigidBody2D>())
    if (Body.body != 0) {
        if (b2Body_IsValid(Load(Body.body))) { b2DestroyBody(Load(Body.body)); +
+Destroyed; }
        Body.body = 0;                       // no stale handle survives
    }
for (Collider : Registry.view<Collider2D>()) Collider.shape = 0;
```

| Restore phase | Native state | Invariant after the phase |
|---|---|---|
| **DestroyAllBodies(registry)** | Every valid tracked body + | World contains no body owned |

| | every registry body destroyed | by the old frame |
|---|---|---|
| **Registry::clear() + snapshot decode** | No native object is touched | Restored RigidBody2D rows have body == 0 |
| **EnsureBodies(registry)** | One b2Body/b2Shape per restored row | Body count equals the pre-rollback count, never twice it |
| **Replay to the current tick** | Step() finds body != 0 and skips creation | No duplicate physics on any replayed tick |

*Play-In-Editor uses the same rule at a larger granularity. The clone owns a separate PhysicsSystem, so Play never inserts clone bodies into the editor world. Stop calls DestroyAllBodies(clone) and then shuts that world down; the authoring scene was never mutated, so Stop is a constant-time rollback with no orphan body. The same path is what makes the toolbar Play/Pause/Stop honest: the buttons drive a real simulation, not a preview flag.*

The canvas needs six scalars per frame: CurrentState, PreviousState, BlendWeight, BlendTime, StateTime and LastTransition. Reading them from a live AnimStateComponent on the ImGui thread is not a benign race: SystemGraph workers may be inside AnimGraphSystem::Run, and the EnTT lookup itself is unsafe while component pools are created or destroyed. Atomic reads of the six fields would not fix the registry/lifetime part. The panel therefore owns a 64-byte POD and a two-slot seqlock: the simulation thread publishes, the editor thread consumes, and the live component is never dereferenced from Draw().

```
struct PIEAnimFrame {                          // exactly 64 bytes
    std::uint64_t CurrentState = 0;
    std::uint64_t PreviousState = 0;
    float BlendWeight = 0.0f, BlendTime = 0.0f, StateTime = 0.0f;
    std::uint16_t LastTransition = kNoAnimTransition;
    std::array<std::byte, 34> Reserved{};
};

// Producer (simulation thread, after the FixedUpdate join):
void PublishPIEState(const AnimStateComponent& S) noexcept {
    const std::uint32_t Write = MPieWriteSlot.load(std::memory_order_relaxed);
    PIEFrameSlot& Slot = MPieSlots[Write ^ 1u];
    const std::uint64_t Seq = Slot.Sequence.load(std::memory_order_relaxed);
    Slot.Sequence.store(Seq + 1u, std::memory_order_relaxed);
    std::atomic_thread_fence(std::memory_order_release);
    StoreRelaxed(Slot.Frame.CurrentState, S.CurrentState);
    StoreRelaxed(Slot.Frame.PreviousState, S.PreviousState);
    StoreRelaxed(Slot.Frame.BlendWeight, S.BlendWeight);
    StoreRelaxed(Slot.Frame.BlendTime, S.BlendTime);
    StoreRelaxed(Slot.Frame.StateTime, S.StateTime);
    StoreRelaxed(Slot.Frame.LastTransition, S.LastTransition);
    std::atomic_thread_fence(std::memory_order_release);
    Slot.Sequence.store(Seq + 2u, std::memory_order_release);
    MPieWriteSlot.store(Write ^ 1u, std::memory_order_release);
    MPiePublished.store(1u, std::memory_order_release);
}
```

```
// Consumer (ImGui/Render thread): retry only if the sequence changed.
const std::uint64_t Before = Slot.Sequence.load(std::memory_order_acquire);
if ((Before & 1u) == 0) {
    ReadRelaxed(Frame.CurrentState, Slot.Frame.CurrentState);
    /* ... five more ... */
    std::atomic_thread_fence(std::memory_order_acquire);
    if (Before == Slot.Sequence.load(std::memory_order_relaxed)) return true;
}
```

| Operation | Ordering | Why |
|---|---|---|
| **sequence increment (odd)** | relaxed + release fence | Marks the slot as being written; the fence prevents payload stores from moving before it |
| **payload stores** | relaxed atomic_ref | No data race; ordering is supplied by the sequence brackets |
| **sequence increment (even)** | release store | Publishes the payload before the reader can accept it |
| **writer slot publish** | release store | Reader takes the slot index with acquire and sees a complete frame |
| **reader retry** | acquire + relaxed re-check | Rejects a torn read after the writer lapped the reader |

- BindRuntimeWorld() only invalidates the buffer when the world pointers or the PIE flag actually change; EditorSystem calls it every frame, so an unconditional invalidate would erase the sample before Draw().
- PublishPIEStateFromWorlds() is the convenience producer: it resolves EditorSelected, looks up AnimStateComponent in the runtime world and publishes. It must run on the simulation thread, never from Draw().
- RefreshPIEState() and DrawPIEInspector() read only the seqlock slot. The inspector no longer walks the Mirror table over a live pointer; it prints the published scalar fields.
- The hand-off adds exactly one frame of latency and one 64-byte copy per published frame. It allocates nothing and never takes a mutex.

*If PIE is later stepped on a worker pool, the host must publish after joining the pool and before the editor draws. Do not call PublishPIEState() from the render thread while workers still run: the producer side touches the registry and a live component, which are not protected by the seqlock. The seqlock protects the hand-off, not the capture.*

## 36. Release gate

The release gate is the full CTest suite, the C++ style gate and the documentation checks. Run them from the repository root before publishing a build.

## 37. Profiling cache misses and vectorisation toward 8000+ FPS

8000 FPS is 125 microseconds per frame. That number is meaningful only together with the scene, resolution and hardware: a 2D batch of a few thousand sprites at 1080p is a different problem from a 4K frame with post-processing. Treat 8000 FPS as a target for the engine's own frame cost (simulation + extract + submission) on a Zen 5 machine with a warm cache, and always report the 99th percentile frame time, not just the average FPS. A stable 8000+ means p99 <= 125 us, not one lucky frame.

- Step 1 — baseline. Record CPU and GPU frame time separately. On Windows use WPA/ETW or AMD uProf; on Linux use perf stat with cache-references, cache-misses, L1-dcache-load-misses, LLC-load-misses and stalled-cycles-frontend. Store the numbers in the repository so a regression is visible.
- Step 2 — find the hot array. The animation tick walks AnimStateComponent per entity (4 KB stride); the extract walks RenderItem; the job pool touches one shared cache line. A 4 KB stride with 8 transitions and 8 clips per component thrashes L1 and L2 before any math runs.
- Step 3 — split hot/cold. Keep a 64-byte AnimHot per entity (states, StateTime, Blend*) and move Transitions/Clips/RestPose into a shared graph object or a cold side table. The system then streams a dense array; the shared tables stay L1-resident.
- Step 4 — vectorise the presentation blend, not the deterministic simulation. Use __restrict, SoA float arrays (X[], Y[], Rotation[], Scale[]) and check the vectoriser report. Do not reorder floating-point reductions used by rollback or physics.
- Step 5 — reduce RHI binds. Sort draws by (pipeline, material, texture array), use push constants for the draw id, keep one bindless set, and record one indirect draw per batch. Descriptor-set churn is usually more expensive than the draw itself at 8k FPS.
- Step 6 — parallelise phases, not just entities. SystemGraph::Build() computes dependency levels once; Run() launches each level as one wave through JobSystem and joins it with a per-call semaphore before Render. MPending and MRunning sit on separate 64-byte lines, so submit/completion traffic does not bounce a shared line between 24 workers. Keep the main thread for submission and reserve one physical core for render/UI; 23 SMT workers on 12 physical cores often lose to 11-12 dedicated workers on cache-bound work.

```
// SoA blend: one AVX-512 iteration covers 16 bones on Zen 5.
void BlendBones(float* __restrict OutX, float* __restrict OutY,
                const float* __restrict AX, const float* __restrict AY,
                const float* __restrict BX, const float* __restrict BY,
                std::size_t Count, float Weight) noexcept
{
    for (std::size_t I = 0; I < Count; ++I)
    {
        OutX[I] = AX[I] + (BX[I] - AX[I]) * Weight;
        OutY[I] = AY[I] + (BY[I] - AY[I]) * Weight;
    }
}

// Verify the vectoriser actually fired:
// clang-cl /O2 /Rpass=loop-vectorize /Rpass-missed=loop-vectorize
// clang++  -O2 -Rpass=loop-vectorize -Rpass-missed=loop-vectorize
```

| Counter | Healthy range | If it is worse |
|---|---|---|
| **L1d load misses** | < 2% of loads | Hot/cold split, prefetch, reduce stride |
| **LLC load misses** | < 1-2% | Shrink working set, huge pages, reorder loops |
| **stalled-cycles-frontend** | < 10% | Branch layout, inline hot paths, avoid i-cache thrash |
| **IPC** | > 2.5 | Check dependency chains, false sharing, lock contention |
| **p99 frame time** | <= 125 us for 8000 FPS | Cap fixed steps, remove WaitIdle from the frame, budget submissions |

*Use RenderDoc or PIX to separate CPU from GPU: an 8k FPS CPU frame with a 2 ms GPU frame is still 500 FPS on screen. Do not chase the CPU target by removing correctness work (validation, barriers, checksums) — move it to a background job or a less frequent pass. And keep a rollback-determinism test green after every SIMD change: vectorised float order is a classic source of 'works on my machine' desync.*

## 38. Materials in the engine: cook, cache and the frame

The material system was the last subsystem whose runtime still lived on the editor side. The graph model and the GLSL emitter shipped in `fby_engine`, but the driver that turned a graph into a pipeline - glslang, SPIR-V, `CreateShaderPipeline` and a private 128-entry table - shipped only in `fby_editor`. A game links `FemboyEngine2D::Engine` alone, so it could validate a material and had no way to draw with it. [ADR 0002](../../adr/0002-materials-in-engine.md) moves the missing half into the engine and leaves the editor with a thin live-recompile adapter.

| Stage | Owner | What it validates |
|---|---|---|
| **Author: `MaterialGraph`** | Editor panel, or a tool that writes `.fgraph` | One output node, connected required pins, type compatibility, acyclicity, capacity limits |
| **Cook: `fby_matc`** | Build step, links glslang | The whole graph, then each generated GLSL stage through glslang, then the payload encoder |
| **Load: `DecodeCookedMaterial`** | Shipped runtime, no allocation | Magic, version, size against the stage lengths, both SPIR-V modules, contract consistency |
| **Acquire: `MaterialPipelineCache`** | Shipped runtime, one cache per device | Hash and contract against the resident entries, reference count, LRU eviction, backend capability |

| | | |
|---|---|---|
| **Frame: `MeshRenderItem::materialPipeline`** | Render extract and the backend | Vulkan groups mesh records by the id and binds one material pipeline per group; other backends keep the engine shader |

Cooking a material is one command, and the output travels like any other cooked asset:

```
# fby_matc <graph.fgraph> [-o <cooked.femmat>]
build/bin/fby_matc assets/materials/tinted.fgraph -o
assets/materials/tinted.femmat

# The tool refuses a graph that does not validate, prints the hash and the SPIR-
V word
# counts, and never writes a payload the runtime would reject.
```

```
// One cache per device, owned by the game. Acquire at load time.
Render::MaterialPipelineCache ScopedMaterials;

// `InBytes` comes from the VFS or a package entry.
Render::CookedMaterialView ScopedTinted;
if (!Render::DecodeCookedMaterial(InBytes, &ScopedTinted))
{
    LogError("materials", "tinted.femmat is not a cooked material");
    return false;
}

const Rhi::ShaderPipelineHandle ScopedTintedPipeline =
    ScopedMaterials.Acquire(InRhi, ScopedTinted);

// A missing pipeline is not a crash: the item falls back to the engine shader.
ScopedItem.materialPipeline = ScopedTintedPipeline.IsValid()
    ? ScopedTintedPipeline.id
    : Rhi::kDefaultMaterialPipeline;

// At shutdown, while the device is still alive.
ScopedMaterials.Shutdown(InRhi);
```

- Retention over churn: a pipeline at zero references stays resident, because a game that acquires a material every frame and releases it at the end of the frame would otherwise rebuild the pipeline sixty times per second. The 128-entry cap and LRU eviction bound the cost instead.
- The contract mask is part of the identity check. A graph hash that arrives with a different contract while the entry is live is refused; the same hash with a different contract and no references is replaced in place, which is what the editor does when push-constant support changes.
- The backend says whether it can build a runtime pipeline. Vulkan returns true; Null and Metal return false and keep the engine shaders, so a game targeting them fails at load with a readable error instead of drawing with an unbound pipeline.

- Nothing on this path allocates or formats text per frame: the cache is a fixed array, the decode is a view, and the error is a fixed buffer.

The editor keeps its live experience through the same cache. `MaterialGraphRuntime` stores one graph pointer per tab, recompiles when `Hash()` changes, keeps the last good pipeline while an edit is invalid, and reports the failure per tab. It no longer owns a pipeline table: `Pipeline()` returns the handle the engine cache handed out, so an editor session and a game share one budget.

| Test | Covers |
|---|---|
| **`material_graph`** | DAG validation, deterministic GLSL, glslang acceptance |
| **`material_asset`** | Graph round trip, payload corruption, contract flags |
| **`material_cook`** | End-to-end: the tool cooks, an Engine-only binary decodes and checks the hash |
| **`material_pipeline_cache`** | Sharing, reference counts, eviction, exhaustion, refusal paths |
| **`material_mesh_path`** | Two meshes share one cached pipeline, a third keeps the engine shader |

The sprite path is now part of the same system. A sprite material is a second shader contract, not a second compiler: `MaterialCompileOptions::domain` switches the fragment interface to the `quad.vert` varyings, `vLayer` supplies the item's atlas slice, and the sprite push block carries a material clock at offset 80, so `Time` works in both domains; only `Fresnel` and `VertexPosition` are refused because they need a view-projection. The 64-bit render key carries the material bucket (16 bits layer, 8 bits material, 32 bits depth, 8 bits sequence), so `DrawOrder::MaterialBucket` both sorts a sprite into its material run and, through `ChangeMaskRenderExtract::SetMaterialPipelines`, resolves the run to one `DrawBatch` with the cached pipeline id. The Vulkan sprite loop binds that pipeline per batch and restores the engine quad pipeline for the next run; a backend without runtime shader pipelines keeps the quad pipeline and draws the sprite unshaded by the graph, never with an unbound handle. Compile-time layer composition, if it is ever added, becomes node kinds in the same graph, never a variable-length closure buffer.

## 39. Appendix A - generated symbol index

Generated from the headers on every run. Header and line are the authoritative location.

### Editor/Infrastructure (115)

| Symbol | Kind | Header | Line |
|---|---|---|---|
| **AIStateTreeCanvasPanel** | Infrastructure | Source/Editor/Infrastructure/EditorSystem.hpp | 44 |
| **AnimationGraphCanvasPanel** | Infrastructure | Source/Editor/Infrastructure/EditorSystem.hpp | 45 |
| **AnimationTimelinePanel** | Infrastructure | Source/Editor/Infrastructure/EditorSystem.hpp | 46 |
| **AssetDatabaseWatchSystem** | Infrastructure | Source/Editor/Infrastructure/AssetDatabaseWatchSystem.hpp | 20 |
| **AssetDatabaseWatchSystem** | Infrastructure | Source/Editor/Infrastructure/EditorSystem.hpp | 47 |
| **AssetImportService** | Infrastructure | Source/Editor/Infrastructure/AssetImportService.hpp | 30 |
| **AssetImportService** | Infrastructure | Source/Editor/Infrastructure/EditorSystem.hpp | 48 |
| **Callbacks** | Infrastructure | Source/Editor/Infrastructure/AssetDatabaseWatchSystem.hpp | 38 |
| **Change** | Infrastructure | Source/Editor/Infrastructure/AssetDatabaseWatchSystem.hpp | 102 |
| **Codec** | Infrastructure | Source/Editor/Infrastructure/CommandStack.hpp | 220 |
| **Command** | Infrastructure | Source/Editor/Infrastructure/CommandStack.hpp | 234 |
| **CommandKind** | Infrastructure | Source/Editor/Infrastructure/CommandStack.hpp | 33 |

| | | | |
|---|---|---|---|
| **CommandStack** | Infrastructure | Source/Editor/ Infrastructure/ CommandStack.hpp | 30 |
| **CommandStack** | Infrastructure | Source/Editor/ Infrastructure/ EditorSystem.hpp | 49 |
| **Config** | Infrastructure | Source/Editor/ Infrastructure/ AssetDatabaseWatch System.hpp | 27 |
| **Config** | Infrastructure | Source/Editor/ Infrastructure/ AssetImportService.hp p | 39 |
| **Config** | Infrastructure | Source/Editor/ Infrastructure/ CommandStack.hpp | 88 |
| **ContentBrowserPan el** | Infrastructure | Source/Editor/ Infrastructure/ EditorSystem.hpp | 50 |
| **CookRequest** | Infrastructure | Source/Editor/ Infrastructure/ AssetImportService.hp p | 115 |
| **CookResult** | Infrastructure | Source/Editor/ Infrastructure/ AssetImportService.hp p | 126 |
| **EditorCamera** | Infrastructure | Source/Editor/ Infrastructure/ EditorSystem.hpp | 91 |
| **EditorDesc** | Infrastructure | Source/Editor/ Infrastructure/ EditorSystem.hpp | 62 |
| **EditorFontRole** | Infrastructure | Source/Editor/ Infrastructure/ EditorFonts.hpp | 22 |
| **EditorFonts** | Infrastructure | Source/Editor/ Infrastructure/ EditorFonts.hpp | 84 |
| **EditorFonts** | Infrastructure | Source/Editor/ Infrastructure/ EditorTypography.hpp | 7 |
| **EditorFontSpec** | Infrastructure | Source/Editor/ Infrastructure/ | 38 |

| | | | |
|---|---|---|---|
| | | EditorFonts.hpp | |
| **EditorFontStatus** | Infrastructure | Source/Editor/ Infrastructure/ EditorFonts.hpp | 67 |
| **EditorSettings** | Infrastructure | Source/Editor/ Infrastructure/ EditorSettings.hpp | 19 |
| **EditorSettingsPanel** | Infrastructure | Source/Editor/ Infrastructure/ EditorSystem.hpp | 51 |
| **EditorSystem** | Infrastructure | Source/Editor/ Infrastructure/ EditorSystem.hpp | 100 |
| **Entry** | Infrastructure | Source/Editor/ Infrastructure/ TextureThumbnails.hpp | 52 |
| **ExternalClientDesc** | Infrastructure | Source/Editor/ Infrastructure/ PlayInEditor.hpp | 37 |
| **FrameComposer** | Infrastructure | Source/Editor/ Infrastructure/ FrameComposer.hpp | 64 |
| **FrameComposerStats** | Infrastructure | Source/Editor/ Infrastructure/ FrameComposer.hpp | 45 |
| **FrameGenerationMode** | Infrastructure | Source/Editor/ Infrastructure/ ProjectConfig.hpp | 138 |
| **FrameGenerationPolicySetting** | Infrastructure | Source/Editor/ Infrastructure/ ProjectConfig.hpp | 131 |
| **HudTargetMode** | Infrastructure | Source/Editor/ Infrastructure/ ProjectConfig.hpp | 147 |
| **ImFont** | Infrastructure | Source/Editor/ Infrastructure/ EditorFonts.hpp | 10 |
| **ImGuiIO** | Infrastructure | Source/Editor/ Infrastructure/ EditorFonts.hpp | 11 |
| **Impl** | Infrastructure | Source/Editor/ Infrastructure/ EditorSystem.hpp | 221 |
| **InteractionTransacti** | Infrastructure | Source/Editor/ | 16 |

| | | | |
|---|---|---|---|
| **on** | | Infrastructure/ EditTransactions.hpp | |
| **LoadedSource** | Infrastructure | Source/Editor/ Infrastructure/ EditorFonts.hpp | 138 |
| **MaterialGraphPanel** | Infrastructure | Source/Editor/ Infrastructure/ EditorSystem.hpp | 52 |
| **MaterialGraphRuntime** | Infrastructure | Source/Editor/ Infrastructure/ MaterialGraphRuntime.hpp | 41 |
| **MaterialRuntimeStats** | Infrastructure | Source/Editor/ Infrastructure/ MaterialGraphRuntime.hpp | 25 |
| **MotionHistory2D** | Infrastructure | Source/Editor/ Infrastructure/ FrameComposer.hpp | 30 |
| **NetSession** | Infrastructure | Source/Editor/ Infrastructure/ EditorSystem.hpp | 32 |
| **NetworkDiagnosticsPanel** | Infrastructure | Source/Editor/ Infrastructure/ EditorSystem.hpp | 53 |
| **OitMode** | Infrastructure | Source/Editor/ Infrastructure/ ProjectConfig.hpp | 98 |
| **OpaqueRenderMode** | Infrastructure | Source/Editor/ Infrastructure/ ProjectConfig.hpp | 91 |
| **PendingEdit** | Infrastructure | Source/Editor/ Infrastructure/ CommandStack.hpp | 255 |
| **PendingSpawn** | Infrastructure | Source/Editor/ Infrastructure/ CommandStack.hpp | 264 |
| **PhysicsDebugFlags** | Infrastructure | Source/Editor/ Infrastructure/ PhysicsDebugDraw.hpp | 19 |
| **PhysicsDebugFrame** | Infrastructure | Source/Editor/ Infrastructure/ PhysicsDebugDraw.hpp | 47 |

| | | | |
|---|---|---|---|
| **PhysicsDebugLine** | Infrastructure | Source/Editor/ Infrastructure/ PhysicsDebugDraw.hpp | 32 |
| **PhysicsDebugPoint** | Infrastructure | Source/Editor/ Infrastructure/ PhysicsDebugDraw.hpp | 40 |
| **PhysicsDebugVisualizer** | Infrastructure | Source/Editor/ Infrastructure/ PhysicsDebugDraw.hpp | 58 |
| **PiePlayerInput** | Infrastructure | Source/Editor/ Infrastructure/ PlayInEditor.hpp | 27 |
| **PlaybackIcon** | Infrastructure | Source/Editor/ Infrastructure/ EditorWidgets.hpp | 12 |
| **PlayInEditor** | Infrastructure | Source/Editor/ Infrastructure/ PlayInEditor.hpp | 44 |
| **Profiler** | Infrastructure | Source/Editor/ Infrastructure/ EditorSystem.hpp | 27 |
| **ProjectConfig** | Infrastructure | Source/Editor/ Infrastructure/ EditorSystem.hpp | 57 |
| **ProjectConfig** | Infrastructure | Source/Editor/ Infrastructure/ ProjectConfig.hpp | 254 |
| **ProjectConfigStore** | Infrastructure | Source/Editor/ Infrastructure/ EditorSystem.hpp | 54 |
| **ProjectConfigStore** | Infrastructure | Source/Editor/ Infrastructure/ ProjectConfig.hpp | 314 |
| **ProjectDashboard** | Infrastructure | Source/Editor/ Infrastructure/ EditorSystem.hpp | 55 |
| **ProjectPaths** | Infrastructure | Source/Editor/ Infrastructure/ EditorSystem.hpp | 58 |
| **ProjectPaths** | Infrastructure | Source/Editor/ Infrastructure/ ProjectConfig.hpp | 276 |

| | | | |
|---|---|---|---|
| **ProjectPaths** | Infrastructure | Source/Editor/ Infrastructure/ ReleaseCooker.hpp | 21 |
| **ProjectSettings** | Infrastructure | Source/Editor/ Infrastructure/ ProjectConfig.hpp | 162 |
| **ProjectSettings** | Infrastructure | Source/Editor/ Infrastructure/ ReleaseCooker.hpp | 22 |
| **ProjectSettingsPanel** | Infrastructure | Source/Editor/ Infrastructure/ EditorSystem.hpp | 56 |
| **Range** | Infrastructure | Source/Editor/ Infrastructure/ CommandStack.hpp | 249 |
| **ReleaseCookConfig** | Infrastructure | Source/Editor/ Infrastructure/ ReleaseCooker.hpp | 70 |
| **ReleaseCooker** | Infrastructure | Source/Editor/ Infrastructure/ ReleaseCooker.hpp | 154 |
| **ReleaseCookProgress** | Infrastructure | Source/Editor/ Infrastructure/ ReleaseCooker.hpp | 117 |
| **ReleaseCookResult** | Infrastructure | Source/Editor/ Infrastructure/ ReleaseCooker.hpp | 138 |
| **ReleaseCookStage** | Infrastructure | Source/Editor/ Infrastructure/ ReleaseCooker.hpp | 28 |
| **ResolvedHudSettings** | Infrastructure | Source/Editor/ Infrastructure/ ResolvedRenderSettings.hpp | 35 |
| **ResolvedRenderSettings** | Infrastructure | Source/Editor/ Infrastructure/ ResolvedRenderSettings.hpp | 14 |
| **Result** | Infrastructure | Source/Editor/ Infrastructure/ CommandStack.hpp | 43 |
| **Result** | Infrastructure | Source/Editor/ Infrastructure/ PlayInEditor.hpp | 47 |
| **SdfCollisionSystem** | Infrastructure | Source/Editor/ | 13 |

| | | | |
|---|---|---|---|
| | | Infrastructure/ PhysicsDebugDraw.hpp | |
| **SdfField** | Infrastructure | Source/Editor/ Infrastructure/ FrameComposer.hpp | 20 |
| **SdfGiVolume** | Infrastructure | Source/Editor/ Infrastructure/ FrameComposer.hpp | 21 |
| **Services** | Infrastructure | Source/Editor/ Infrastructure/ PlayInEditor.hpp | 220 |
| **SettingDesc** | Infrastructure | Source/Editor/ Infrastructure/ SettingsSchema.hpp | 28 |
| **SettingKind** | Infrastructure | Source/Editor/ Infrastructure/ SettingsSchema.hpp | 20 |
| **SettingScope** | Infrastructure | Source/Editor/ Infrastructure/ SettingsSchema.hpp | 11 |
| **Slot** | Infrastructure | Source/Editor/ Infrastructure/ MaterialGraphRuntime.hpp | 118 |
| **Source** | Infrastructure | Source/Editor/ Infrastructure/ EditTransactions.hpp | 19 |
| **SpawnComponent** | Infrastructure | Source/Editor/ Infrastructure/ CommandStack.hpp | 278 |
| **SpawnHeader** | Infrastructure | Source/Editor/ Infrastructure/ CommandStack.hpp | 271 |
| **SpawnTransaction** | Infrastructure | Source/Editor/ Infrastructure/ EditTransactions.hpp | 190 |
| **StableSource** | Infrastructure | Source/Editor/ Infrastructure/ EditorFonts.hpp | 145 |
| **Stats** | Infrastructure | Source/Editor/ Infrastructure/ AssetDatabaseWatchSystem.hpp | 88 |
| **Stats** | Infrastructure | Source/Editor/ | 55 |

| | | | |
|---|---|---|---|
| | | Infrastructure/ AssetImportService.hpp | |
| **Stats** | Infrastructure | Source/Editor/ Infrastructure/ CommandStack.hpp | 95 |
| **TemporalUpscaleMode** | Infrastructure | Source/Editor/ Infrastructure/ ProjectConfig.hpp | 154 |
| **TextureArrayAsset** | Infrastructure | Source/Editor/ Infrastructure/ AssetImportService.hpp | 23 |
| **TextureBinding** | Infrastructure | Source/Editor/ Infrastructure/ AssetImportService.hpp | 142 |
| **TextureThumbnailCache** | Infrastructure | Source/Editor/ Infrastructure/ TextureThumbnails.hpp | 17 |
| **UpscaleMode** | Infrastructure | Source/Editor/ Infrastructure/ ProjectConfig.hpp | 105 |
| **UpscalePolicy** | Infrastructure | Source/Editor/ Infrastructure/ ProjectConfig.hpp | 114 |
| **UpscalerBackendSetting** | Infrastructure | Source/Editor/ Infrastructure/ ProjectConfig.hpp | 121 |
| **UserSettings** | Infrastructure | Source/Editor/ Infrastructure/ EditorSystem.hpp | 59 |
| **UserSettings** | Infrastructure | Source/Editor/ Infrastructure/ UserSettings.hpp | 16 |
| **VirtualFileSystem** | Infrastructure | Source/Editor/ Infrastructure/ AssetImportService.hpp | 20 |
| **VirtualFileSystem** | Infrastructure | Source/Editor/ Infrastructure/ EditorFonts.hpp | 15 |
| **VirtualFileSystem** | Infrastructure | Source/Editor/ Infrastructure/ | 18 |

| | | | |
|---|---|---|---|
| | | EditorSystem.hpp | |
| **VirtualTextureSettings** | Infrastructure | Source/Editor/Infrastructure/EditorSystem.hpp | 37 |
| **VirtualTextureSettings** | Infrastructure | Source/Editor/Infrastructure/ProjectConfig.hpp | 31 |
| **VirtualTextureSystem** | Infrastructure | Source/Editor/Infrastructure/EditorSystem.hpp | 22 |
| **VisualScriptPanel** | Infrastructure | Source/Editor/Infrastructure/EditorSystem.hpp | 60 |
| **WindowManager** | Infrastructure | Source/Editor/Infrastructure/EditorFonts.hpp | 16 |

### Editor/Panels (79)

| Symbol | Kind | Header | Line |
|---|---|---|---|
| **Action** | Panels | Source/Editor/Panels/ProjectDashboard.hpp | 25 |
| **AIStateTreeCanvasPanel** | Panels | Source/Editor/Panels/AIStateTreeCanvasPanel.hpp | 55 |
| **AIStateTreeCompiled** | Panels | Source/Editor/Panels/AIStateTreeCanvasPanel.hpp | 35 |
| **AIStateTreeDocument** | Panels | Source/Editor/Panels/AIStateTreeCanvasPanel.hpp | 24 |
| **AnimationGraphCanvasPanel** | Panels | Source/Editor/Panels/AnimationGraphCanvasPanel.hpp | 116 |
| **AnimationGraphDocument** | Panels | Source/Editor/Panels/AnimationGraphCanvasPanel.hpp | 79 |
| **AnimationGraphLink** | Panels | Source/Editor/Panels/ | 65 |

| | | | |
|---|---|---|---|
| | | AnimationGraphCanvasPanel.hpp | |
| **AnimationGraphLinkKind** | Panels | Source/Editor/Panels/AnimationGraphCanvasPanel.hpp | 33 |
| **AnimationGraphNode** | Panels | Source/Editor/Panels/AnimationGraphCanvasPanel.hpp | 45 |
| **AnimationGraphNodeKind** | Panels | Source/Editor/Panels/AnimationGraphCanvasPanel.hpp | 26 |
| **AnimationTimelinePanel** | Panels | Source/Editor/Panels/AnimationTimelinePanel.hpp | 34 |
| **AssetImportService** | Panels | Source/Editor/Panels/ContentBrowserPanel.hpp | 24 |
| **AudioSystem** | Panels | Source/Editor/Panels/AnimationTimelinePanel.hpp | 15 |
| **AudioSystem** | Panels | Source/Editor/Panels/VoiceDevicePanel.hpp | 11 |
| **CanvasModelOps** | Panels | Source/Editor/Panels/NodeCanvasPanel.hpp | 21 |
| **CommandStack** | Panels | Source/Editor/Panels/ContentBrowserPanel.hpp | 25 |
| **CommandStack** | Panels | Source/Editor/Panels/SettingsPanels.hpp | 30 |
| **ComponentRegistry** | Panels | Source/Editor/Panels/ScriptDebuggerPanel.hpp | 18 |
| **Config** | Panels | Source/Editor/Panels/ | 35 |

| | | | |
|---|---|---|---|
| | | ContentBrowserPanel.hpp | |
| **ContentBrowserPanel** | Panels | Source/Editor/Panels/ContentBrowserPanel.hpp | 27 |
| **DragPayload** | Panels | Source/Editor/Panels/ContentBrowserPanel.hpp | 60 |
| **EditorFonts** | Panels | Source/Editor/Panels/ProjectDashboard.hpp | 20 |
| **EditorFonts** | Panels | Source/Editor/Panels/VisualScriptPanel.hpp | 20 |
| **EditorSettingsPanel** | Panels | Source/Editor/Panels/SettingsPanels.hpp | 91 |
| **EditSource** | Panels | Source/Editor/Panels/AIStateTreeCanvasPanel.hpp | 58 |
| **EditSource** | Panels | Source/Editor/Panels/AnimationGraphCanvasPanel.hpp | 119 |
| **Entry** | Panels | Source/Editor/Panels/ContentBrowserPanel.hpp | 43 |
| **FileDialog** | Panels | Source/Editor/Panels/ContentBrowserPanel.hpp | 140 |
| **ImNodesContext** | Panels | Source/Editor/Panels/AIStateTreeCanvasPanel.hpp | 13 |
| **ImNodesContext** | Panels | Source/Editor/Panels/AnimationGraphCanvasPanel.hpp | 15 |
| **LevelSettingsPanel** | Panels | Source/Editor/Panels/LevelSettingsPanel.hp | 12 |

| | | | |
|---|---|---|---|
| | | p | |
| **LicensesPanel** | Panels | Source/Editor/ Panels/ LicensesPanel.hpp | 11 |
| **LogBoyPanel** | Panels | Source/Editor/ Panels/ LogBoyPanel.hpp | 394 |
| **LogBoyRecord** | Panels | Source/Editor/ Panels/ LogBoyPanel.hpp | 105 |
| **LogBoyRing** | Panels | Source/Editor/ Panels/ LogBoyPanel.hpp | 121 |
| **LogBoySeverity** | Panels | Source/Editor/ Panels/ LogBoyPanel.hpp | 33 |
| **LogBoySystem** | Panels | Source/Editor/ Panels/ LogBoyPanel.hpp | 186 |
| **LogicGraphDocument** | Panels | Source/Editor/ Panels/ VisualScriptPanel.hpp | 23 |
| **MaterialGraphPanel** | Panels | Source/Editor/ Panels/ MaterialGraphPanel.hpp | 20 |
| **Mode** | Panels | Source/Editor/ Panels/ ProjectDashboard.hpp | 84 |
| **NetSession** | Panels | Source/Editor/ Panels/ NetworkDiagnosticsPanel.hpp | 6 |
| **NetworkDiagnosticsPanel** | Panels | Source/Editor/ Panels/ NetworkDiagnosticsPanel.hpp | 15 |
| **NodeCanvasPanel** | Panels | Source/Editor/ Panels/ NodeCanvasPanel.hpp | 54 |
| **PIEAnimFrame** | Panels | Source/Editor/ Panels/ AnimationGraphCanvasPanel.hpp | 101 |

| | | | |
|---|---|---|---|
| **PieClientViewport** | Panels | Source/Editor/ Panels/ PieClientViewport.hpp | 15 |
| **PIEFrameSlot** | Panels | Source/Editor/ Panels/ AnimationGraphCanvasPanel.hpp | 289 |
| **ProjectConfigStore** | Panels | Source/Editor/ Panels/ SettingsPanels.hpp | 31 |
| **ProjectConfigStore** | Panels | Source/Editor/ Panels/ VoiceDevicePanel.hpp | 17 |
| **ProjectDashboard** | Panels | Source/Editor/ Panels/ ProjectDashboard.hpp | 22 |
| **ProjectSettingsPanel** | Panels | Source/Editor/ Panels/ SettingsPanels.hpp | 33 |
| **QueryKind** | Panels | Source/Editor/ Panels/ LogBoyPanel.hpp | 430 |
| **SceneDiagnosticsPanel** | Panels | Source/Editor/ Panels/ SceneDiagnosticsPanel.hpp | 56 |
| **SceneDiagnosticsSample** | Panels | Source/Editor/ Panels/ SceneDiagnosticsPanel.hpp | 15 |
| **ScriptDebuggerPanel** | Panels | Source/Editor/ Panels/ ScriptDebuggerPanel.hpp | 28 |
| **ScriptRuntime** | Panels | Source/Editor/ Panels/ AnimationTimelinePanel.hpp | 16 |
| **SinkUser** | Panels | Source/Editor/ Panels/ AnimationTimelinePanel.hpp | 88 |
| **SkeletonInspectorState** | Panels | Source/Editor/ Panels/ SkeletonAssetPanel.hpp | 19 |

| | | | |
|---|---|---|---|
| **SpawnContext** | Panels | Source/Editor/ Panels/ ContentBrowserPanel. hpp | 68 |
| **SpriteAnimationInsp ectorState** | Panels | Source/Editor/ Panels/ SpriteAnimationPanel. hpp | 21 |
| **SystemContext** | Panels | Source/Editor/ Panels/ SettingsPanels.hpp | 24 |
| **SystemContext** | Panels | Source/Editor/ Panels/ SkeletonAssetPanel.h pp | 13 |
| **SystemContext** | Panels | Source/Editor/ Panels/ SpriteAnimationPanel. hpp | 13 |
| **SystemName** | Panels | Source/Editor/ Panels/ LogBoyPanel.hpp | 189 |
| **TextPreviewPanel** | Panels | Source/Editor/ Panels/ TextPreviewPanel.hpp | 24 |
| **TextureThumbnailCa che** | Panels | Source/Editor/ Panels/ SpriteAnimationPanel. hpp | 19 |
| **TilemapEditorPanel** | Panels | Source/Editor/ Panels/ TilemapEditorPanel.h pp | 20 |
| **TimelinePanelConte xt** | Panels | Source/Editor/ Panels/ AnimationTimelinePan el.hpp | 22 |
| **TransportGroupPane l** | Panels | Source/Editor/ Panels/ TransportGroupPanel. hpp | 14 |
| **UserSettingsPanel** | Panels | Source/Editor/ Panels/ UserSettingsPanel.hp p | 16 |
| **VirtualFileSystem** | Panels | Source/Editor/ | 18 |

| | | | |
|---|---|---|---|
| | | Panels/ ContentBrowserPanel. hpp | |
| **VirtualFileSystem** | Panels | Source/Editor/ Panels/ ProjectDashboard.hpp | 13 |
| **VirtualFileSystem** | Panels | Source/Editor/ Panels/ TextPreviewPanel.hpp | 15 |
| **VirtualTexturePanel** | Panels | Source/Editor/ Panels/ VirtualTexturePanel.h pp | 18 |
| **VirtualTextureSyste m** | Panels | Source/Editor/ Panels/ VirtualTexturePanel.h pp | 10 |
| **VisualScriptPanel** | Panels | Source/Editor/ Panels/ ScriptDebuggerPanel. hpp | 24 |
| **VisualScriptPanel** | Panels | Source/Editor/ Panels/ VisualScriptPanel.hpp | 32 |
| **VoiceDevicePanel** | Panels | Source/Editor/ Panels/ VoiceDevicePanel.hpp | 19 |
| **WidgetCanvas** | Panels | Source/Editor/ Panels/ SettingsPanels.hpp | 18 |
| **WindowManager** | Panels | Source/Editor/ Panels/ ProjectDashboard.hpp | 14 |

### Engine/AI (6)

| Symbol | Kind | Header | Line |
|---|---|---|---|
| **AIAgentSettings** | AI | Source/Engine/AI/ AIController.hpp | 16 |
| **AIControllerCompon ent** | AI | Source/Engine/AI/ AIController.hpp | 31 |
| **AIControllerSystem** | AI | Source/Engine/AI/ AIController.hpp | 84 |

| | | | |
|---|---|---|---|
| **AIPerceptionComponent** | AI | Source/Engine/AI/AIController.hpp | 59 |
| **AIPerceptionSettings** | AI | Source/Engine/AI/AIController.hpp | 48 |
| **AIPerceptionSystem** | AI | Source/Engine/AI/AIController.hpp | 67 |

## Engine/Assets (58)

| Symbol | Kind | Header | Line |
|---|---|---|---|
| **AeadAlgorithm** | Assets | Source/Engine/Assets/FemCrypto.hpp | 18 |
| **AeadKey** | Assets | Source/Engine/Assets/FemCrypto.hpp | 39 |
| **AeadNonce** | Assets | Source/Engine/Assets/FemCrypto.hpp | 46 |
| **AeadTag** | Assets | Source/Engine/Assets/FemCrypto.hpp | 54 |
| **ArchiveBuildOptions** | Assets | Source/Engine/Assets/FemArchiver.hpp | 99 |
| **ArchiveCipher** | Assets | Source/Engine/Assets/FemArchiver.hpp | 29 |
| **ArchiveCodec** | Assets | Source/Engine/Assets/FemArchiver.hpp | 22 |
| **ArchiveEntryView** | Assets | Source/Engine/Assets/FemArchiver.hpp | 115 |
| **ArchiveInput** | Assets | Source/Engine/Assets/FemArchiver.hpp | 72 |
| **ArchiveProgress** | Assets | Source/Engine/Assets/FemArchiver.hpp | 85 |
| **ArchiveProgressStage** | Assets | Source/Engine/Assets/FemArchiver.hpp | 78 |
| **ArchiveReader** | Assets | Source/Engine/ | 126 |

| | | | |
|---|---|---|---|
| | | Assets/ FemArchiver.hpp | |
| **ArchiveReader** | Assets | Source/Engine/ Assets/ FemArchiver.hpp | 145 |
| **ArchiveStatus** | Assets | Source/Engine/ Assets/ FemArchiver.hpp | 36 |
| **AssetDatabase** | Assets | Source/Engine/ Assets/ AssetDatabase.hpp | 28 |
| **AssetDependency** | Assets | Source/Engine/ Assets/AssetMeta.hpp | 83 |
| **AssetHandle** | Assets | Source/Engine/ Assets/AssetMeta.hpp | 22 |
| **AssetImportSettings** | Assets | Source/Engine/ Assets/AssetMeta.hpp | 45 |
| **AssetMeta** | Assets | Source/Engine/ Assets/AssetMeta.hpp | 61 |
| **AssetRecord** | Assets | Source/Engine/ Assets/ AssetDatabase.hpp | 19 |
| **AstcBlock** | Assets | Source/Engine/ Assets/ TextureCook.hpp | 25 |
| **AtlasDesc** | Assets | Source/Engine/ Assets/ TextureArray.hpp | 31 |
| **AtlasLayer** | Assets | Source/Engine/ Assets/ TextureArray.hpp | 21 |
| **AudioClipHeader** | Assets | Source/Engine/ Assets/ AudioClipFormat.hpp | 87 |
| **BlockExtent** | Assets | Source/Engine/ Assets/ TextureFormat.hpp | 103 |
| **CleanRenderExtract** | Assets | Source/Engine/ Assets/ ProjectScaffold.hpp | 127 |
| **CookedAudioView** | Assets | Source/Engine/ Assets/ AudioClipFormat.hpp | 116 |
| **CookedTexture** | Assets | Source/Engine/ | 41 |

| | | | |
|---|---|---|---|
| | | Assets/ TextureCook.hpp | |
| **CookedTextureView** | Assets | Source/Engine/ Assets/ TextureFormat.hpp | 203 |
| **CookProgressFlags** | Assets | Source/Engine/ Assets/ CookProgress.hpp | 31 |
| **CookProgressRecord** | Assets | Source/Engine/ Assets/ CookProgress.hpp | 38 |
| **CookProgressStage** | Assets | Source/Engine/ Assets/ CookProgress.hpp | 18 |
| **CookTarget** | Assets | Source/Engine/ Assets/ TextureCook.hpp | 17 |
| **FanmHeader** | Assets | Source/Engine/ Assets/ AnimationClipAsset.hpp | 22 |
| **FemArchiver** | Assets | Source/Engine/ Assets/ FemArchiver.hpp | 128 |
| **FempakInput** | Assets | Source/Engine/ Assets/ FempakWriter.hpp | 15 |
| **FempakWriter** | Assets | Source/Engine/ Assets/ FempakWriter.hpp | 22 |
| **LocaleTable** | Assets | Source/Engine/ Assets/ Localization.hpp | 14 |
| **LocalizationGender** | Assets | Source/Engine/ Assets/ Localization.hpp | 21 |
| **LocalizationPack** | Assets | Source/Engine/ Assets/ Localization.hpp | 13 |
| **LocalizationTable** | Assets | Source/Engine/ Assets/ Localization.hpp | 28 |
| **MappedFile** | Assets | Source/Engine/ Assets/VFS.hpp | 19 |
| **MountRecord** | Assets | Source/Engine/ | 128 |

| | | | |
|---|---|---|---|
| | | Assets/VFS.hpp | |
| **PakEntry** | Assets | Source/Engine/ Assets/ PakFormat.hpp | 26 |
| **PakHeader** | Assets | Source/Engine/ Assets/ PakFormat.hpp | 16 |
| **PcmFormat** | Assets | Source/Engine/ Assets/ AudioClipFormat.hpp | 21 |
| **PinnedFile** | Assets | Source/Engine/ Assets/VFS.hpp | 63 |
| **ReloadNotice** | Assets | Source/Engine/ Assets/ AssetDatabase.hpp | 86 |
| **StagedRow** | Assets | Source/Engine/ Assets/ AssetDatabase.hpp | 108 |
| **StringEntry** | Assets | Source/Engine/ Assets/ Localization.hpp | 15 |
| **TextureAlphaMode** | Assets | Source/Engine/ Assets/ TextureFormat.hpp | 43 |
| **TextureArrayAsset** | Assets | Source/Engine/ Assets/ TextureArray.hpp | 51 |
| **TextureCookOptions** | Assets | Source/Engine/ Assets/ TextureCook.hpp | 31 |
| **TextureFormat** | Assets | Source/Engine/ Assets/ TextureFormat.hpp | 22 |
| **TextureHeader** | Assets | Source/Engine/ Assets/ TextureFormat.hpp | 184 |
| **VfsEntry** | Assets | Source/Engine/ Assets/VFS.hpp | 55 |
| **VirtualFileSystem** | Assets | Source/Engine/ Assets/ TextureArray.hpp | 16 |
| **VirtualFileSystem** | Assets | Source/Engine/ Assets/VFS.hpp | 69 |

## Engine/Audio (101)

| Symbol | Kind | Header | Line |
|---|---|---|---|
| **AudioBus** | Audio | Source/Engine/Audio/Audio.hpp | 26 |
| **AudioBusComponent** | Audio | Source/Engine/Audio/Audio.hpp | 40 |
| **AudioCaptureMonitor** | Audio | Source/Engine/Audio/AudioDevices.hpp | 144 |
| **AudioClip** | Audio | Source/Engine/Audio/Audio.hpp | 69 |
| **AudioCommand** | Audio | Source/Engine/Audio/DspGraph.hpp | 138 |
| **AudioCommandType** | Audio | Source/Engine/Audio/DspGraph.hpp | 121 |
| **AudioContextComponent** | Audio | Source/Engine/Audio/AudioZones.hpp | 67 |
| **AudioDeviceEnumerator** | Audio | Source/Engine/Audio/AudioDevices.hpp | 93 |
| **AudioDeviceInfo** | Audio | Source/Engine/Audio/AudioDevices.hpp | 54 |
| **AudioDeviceKind** | Audio | Source/Engine/Audio/AudioDevices.hpp | 15 |
| **AudioDeviceList** | Audio | Source/Engine/Audio/AudioDevices.hpp | 66 |
| **AudioDevicePreferences** | Audio | Source/Engine/Audio/AudioDevices.hpp | 73 |
| **AudioDeviceStatus** | Audio | Source/Engine/Audio/AudioDevices.hpp | 21 |
| **AudioLimiter** | Audio | Source/Engine/Audio/Limiter.hpp | 23 |
| **AudioListener** | Audio | Source/Engine/Audio/Audio.hpp | 94 |
| **AudioSource** | Audio | Source/Engine/Audio/Audio.hpp | 79 |
| **AudioSourceCompo** | Audio | Source/Engine/ | 53 |

| | | | |
|---|---|---|---|
| **nent** | | Audio/Audio.hpp | |
| **AudioSystem** | Audio | Source/Engine/ Audio/Audio.hpp | 100 |
| **AudioZoneComponent** | Audio | Source/Engine/ Audio/ AudioZones.hpp | 32 |
| **AudioZoneKind** | Audio | Source/Engine/ Audio/ AudioZones.hpp | 14 |
| **AudioZoneSystem** | Audio | Source/Engine/ Audio/ AudioZones.hpp | 91 |
| **BiquadState** | Audio | Source/Engine/ Audio/ VoiceEffects.hpp | 369 |
| **BusAtomics** | Audio | Source/Engine/ Audio/DspGraph.hpp | 370 |
| **BusFilterParams** | Audio | Source/Engine/ Audio/DspGraph.hpp | 108 |
| **BusRuntime** | Audio | Source/Engine/ Audio/Audio.hpp | 212 |
| **BusShadow** | Audio | Source/Engine/ Audio/DspGraph.hpp | 291 |
| **BusState** | Audio | Source/Engine/ Audio/DspGraph.hpp | 338 |
| **CommandQueue** | Audio | Source/Engine/ Audio/DspGraph.hpp | 170 |
| **CookedClipRecord** | Audio | Source/Engine/ Audio/Audio.hpp | 187 |
| **DspClipView** | Audio | Source/Engine/ Audio/DspGraph.hpp | 205 |
| **DspGraph** | Audio | Source/Engine/ Audio/DspGraph.hpp | 216 |
| **DspGraph** | Audio | Source/Engine/ Audio/ VoiceChannel.hpp | 16 |
| **DspResult** | Audio | Source/Engine/ Audio/DspGraph.hpp | 34 |
| **DspResult** | Audio | Source/Engine/ Audio/ VoiceChannel.hpp | 19 |
| **DuckingParams** | Audio | Source/Engine/ Audio/DspGraph.hpp | 80 |

| | | | |
|---|---|---|---|
| **DuckingState** | Audio | Source/Engine/ Audio/DspGraph.hpp | 298 |
| **FilterState** | Audio | Source/Engine/ Audio/DspGraph.hpp | 327 |
| **FloatRing** | Audio | Source/Engine/ Audio/Audio.hpp | 24 |
| **FloatRing** | Audio | Source/Engine/ Audio/ AudioStream.hpp | 16 |
| **FloatRing** | Audio | Source/Engine/ Audio/DspGraph.hpp | 32 |
| **JitterSlot** | Audio | Source/Engine/ Audio/ VoiceChannel.hpp | 119 |
| **LimiterDesc** | Audio | Source/Engine/ Audio/Limiter.hpp | 11 |
| **OggOpusStream** | Audio | Source/Engine/ Audio/OggOpus.hpp | 131 |
| **OggPacket** | Audio | Source/Engine/ Audio/OggOpus.hpp | 76 |
| **OggPacketReader** | Audio | Source/Engine/ Audio/OggOpus.hpp | 86 |
| **OggPage** | Audio | Source/Engine/ Audio/OggOpus.hpp | 36 |
| **OggPageReader** | Audio | Source/Engine/ Audio/OggOpus.hpp | 57 |
| **OpusHeadInfo** | Audio | Source/Engine/ Audio/OggOpus.hpp | 106 |
| **OwnedPcmRecord** | Audio | Source/Engine/ Audio/Audio.hpp | 194 |
| **Peer** | Audio | Source/Engine/ Audio/ VoiceChannel.hpp | 129 |
| **RateBucket** | Audio | Source/Engine/ Audio/ VoiceNetworkBridge.hpp | 62 |
| **ResolvedZone** | Audio | Source/Engine/ Audio/ AudioZones.hpp | 113 |
| **ReverbParams** | Audio | Source/Engine/ Audio/DspGraph.hpp | 96 |
| **ReverbState** | Audio | Source/Engine/ | 311 |

| | | | |
|---|---|---|---|
| | | Audio/DspGraph.hpp | |
| **SlotRuntime** | Audio | Source/Engine/ Audio/ VoiceEffects.hpp | 385 |
| **SourceRuntime** | Audio | Source/Engine/ Audio/Audio.hpp | 204 |
| **State** | Audio | Source/Engine/ Audio/ AudioDevices.hpp | 164 |
| **Stats** | Audio | Source/Engine/ Audio/ AudioZones.hpp | 94 |
| **VoiceAec** | Audio | Source/Engine/ Audio/VoiceAec.hpp | 44 |
| **VoiceAecSettings** | Audio | Source/Engine/ Audio/VoiceAec.hpp | 22 |
| **VoiceCapture** | Audio | Source/Engine/ Audio/ AudioStream.hpp | 64 |
| **VoiceChannel** | Audio | Source/Engine/ Audio/ VoiceChannel.hpp | 65 |
| **VoiceChannelConfig** | Audio | Source/Engine/ Audio/ VoiceChannel.hpp | 36 |
| **VoiceChannelStats** | Audio | Source/Engine/ Audio/ VoiceChannel.hpp | 46 |
| **VoiceCodecConfig** | Audio | Source/Engine/ Audio/ VoiceCodec.hpp | 15 |
| **VoiceConditionOutput** | Audio | Source/Engine/ Audio/ VoiceEffects.hpp | 333 |
| **VoiceConditionSettings** | Audio | Source/Engine/ Audio/ VoiceEffects.hpp | 284 |
| **VoiceConditionState** | Audio | Source/Engine/ Audio/ VoiceEffects.hpp | 324 |
| **VoiceDecoder** | Audio | Source/Engine/ Audio/ VoiceCodec.hpp | 51 |
| **VoiceDenoiseTier** | Audio | Source/Engine/ | 10 |

| | | | |
|---|---|---|---|
| | | Audio/VoiceDsp.hpp | |
| **VoiceDistortionSettings** | Audio | Source/Engine/Audio/VoiceEffects.hpp | 157 |
| **VoiceDspChain** | Audio | Source/Engine/Audio/VoiceDsp.hpp | 99 |
| **VoiceDspSettings** | Audio | Source/Engine/Audio/VoiceDsp.hpp | 43 |
| **VoiceEffectChain** | Audio | Source/Engine/Audio/VoiceEffects.hpp | 345 |
| **VoiceEffectChainSettings** | Audio | Source/Engine/Audio/VoiceEffects.hpp | 221 |
| **VoiceEffectKind** | Audio | Source/Engine/Audio/VoiceEffects.hpp | 20 |
| **VoiceEffectPresetKind** | Audio | Source/Engine/Audio/VoiceEffects.hpp | 235 |
| **VoiceEffectProfile** | Audio | Source/Engine/Audio/VoiceEffects.hpp | 310 |
| **VoiceEffectRack** | Audio | Source/Engine/Audio/VoiceEffects.hpp | 433 |
| **VoiceEffectSlot** | Audio | Source/Engine/Audio/VoiceEffects.hpp | 200 |
| **VoiceEncoder** | Audio | Source/Engine/Audio/VoiceCodec.hpp | 27 |
| **VoiceFormantSettings** | Audio | Source/Engine/Audio/VoiceEffects.hpp | 146 |
| **VoiceMuffleSettings** | Audio | Source/Engine/Audio/VoiceEffects.hpp | 80 |
| **VoiceMuteSettings** | Audio | Source/Engine/Audio/VoiceEffects.hpp | 67 |
| **VoiceNetworkBridge** | Audio | Source/Engine/Audio/VoiceNetworkBridge.h | 18 |

| | | | |
|---|---|---|---|
| | | pp | |
| **VoiceParticipant** | Audio | Source/Engine/Audio/VoiceSession.hpp | 46 |
| **VoicePitchSettings** | Audio | Source/Engine/Audio/VoiceEffects.hpp | 133 |
| **VoicePresetKind** | Audio | Source/Engine/Audio/VoiceDsp.hpp | 68 |
| **VoiceRadioSettings** | Audio | Source/Engine/Audio/VoiceEffects.hpp | 115 |
| **VoiceRingModulationSettings** | Audio | Source/Engine/Audio/VoiceEffects.hpp | 171 |
| **VoiceRouting** | Audio | Source/Engine/Audio/VoiceChannel.hpp | 30 |
| **VoiceSession** | Audio | Source/Engine/Audio/VoiceChannel.hpp | 15 |
| **VoiceSession** | Audio | Source/Engine/Audio/VoiceSession.hpp | 65 |
| **VoiceSpatialPosition** | Audio | Source/Engine/Audio/VoiceSession.hpp | 37 |
| **VoiceSpatialSettings** | Audio | Source/Engine/Audio/VoiceSession.hpp | 22 |
| **VoiceState** | Audio | Source/Engine/Audio/DspGraph.hpp | 350 |
| **VoiceSystem** | Audio | Source/Engine/Audio/VoiceSystem.hpp | 39 |
| **VoiceSystemConfig** | Audio | Source/Engine/Audio/VoiceSystem.hpp | 22 |
| **VoiceUnderwaterSettings** | Audio | Source/Engine/Audio/VoiceEffects.hpp | 98 |
| **VoiceWhisperSettings** | Audio | Source/Engine/Audio/VoiceEffects.hpp | 185 |

| | | | |
|---|---|---|---|
| **VorbisIdentInfo** | Audio | Source/Engine/Audio/OggOpus.hpp | 121 |

## Engine/Core (103)

| Symbol | Kind | Header | Line |
|---|---|---|---|
| **AssetId** | Core | Source/Engine/Core/AssetId.hpp | 43 |
| **AssetKind** | Core | Source/Engine/Core/AssetId.hpp | 15 |
| **BigIntT** | Core | Source/Engine/Core/BigInt.hpp | 179 |
| **BigNumberStore** | Core | Source/Engine/Core/BigNumberStore.hpp | 41 |
| **BinaryKind** | Core | Source/Engine/Core/BigNumberStore.hpp | 259 |
| **BinaryKind** | Core | Source/Engine/Core/DecimalStore.hpp | 206 |
| **BufferTag** | Core | Source/Engine/Core/Types.hpp | 301 |
| **BuildInfo** | Core | Source/Engine/Core/BuildInfo.hpp | 12 |
| **BuildProfile** | Core | Source/Engine/Core/BuildProfile.hpp | 135 |
| **CameraView** | Core | Source/Engine/Core/Grid.hpp | 337 |
| **Cell** | Core | Source/Engine/Core/Grid.hpp | 74 |
| **CivilDate** | Core | Source/Engine/Core/Calendar.hpp | 21 |
| **Clock** | Core | Source/Engine/Core/Time.hpp | 28 |
| **ClockTime** | Core | Source/Engine/Core/Calendar.hpp | 32 |
| **Color32** | Core | Source/Engine/Core/Types.hpp | 203 |
| **ComponentDesc** | Core | Source/Engine/Core/Mirror.hpp | 48 |
| **ComponentRegistry** | Core | Source/Engine/Core/PluginHost.hpp | 27 |
| **ComponentType** | Core | Source/Engine/Core/ | 18 |

| | | | |
|---|---|---|---|
| | | PluginHost.hpp | |
| **DateTime** | Core | Source/Engine/Core/Calendar.hpp | 44 |
| **DecimalStore** | Core | Source/Engine/Core/DecimalStore.hpp | 17 |
| **DecimalT** | Core | Source/Engine/Core/Decimal.hpp | 34 |
| **DurationStyle** | Core | Source/Engine/Core/Time.hpp | 571 |
| **EddsaKeyPair** | Core | Source/Engine/Core/CryptoAsymmetric.hpp | 31 |
| **FieldDesc** | Core | Source/Engine/Core/Mirror.hpp | 37 |
| **FieldKind** | Core | Source/Engine/Core/Mirror.hpp | 17 |
| **FileFilter** | Core | Source/Engine/Core/WindowManager.hpp | 183 |
| **FormatSpec** | Core | Source/Engine/Core/BigInt.hpp | 36 |
| **FrameArena** | Core | Source/Engine/Core/FrameArena.hpp | 12 |
| **FrameTimer** | Core | Source/Engine/Core/Time.hpp | 501 |
| **GamepadState** | Core | Source/Engine/Core/WindowManager.hpp | 26 |
| **GridDesc** | Core | Source/Engine/Core/Grid.hpp | 91 |
| **Handle** | Core | Source/Engine/Core/BigNumberStore.hpp | 20 |
| **Handle** | Core | Source/Engine/Core/Types.hpp | 275 |
| **Handle** | Core | Source/Engine/Core/WindowHost.hpp | 20 |
| **Host** | Core | Source/Engine/Core/Plugin.hpp | 20 |
| **InputState** | Core | Source/Engine/Core/WindowManager.hpp | 114 |
| **JobSystem** | Core | Source/Engine/Core/ | 25 |

| | | | |
|---|---|---|---|
| | | JobSystem.hpp | |
| **Key** | Core | Source/Engine/ Core/ WindowManager.hpp | 46 |
| **KeyLess** | Core | Source/Engine/Core/ FlatMap.hpp | 203 |
| **LoadedPlugin** | Core | Source/Engine/Core/ PluginHost.hpp | 64 |
| **LogLevel** | Core | Source/Engine/Core/ Log.hpp | 13 |
| **LogRetention** | Core | Source/Engine/Core/ Log.hpp | 31 |
| **Mat4** | Core | Source/Engine/ Core/Mat4.hpp | 14 |
| **NoiseGenerator** | Core | Source/Engine/Core/ NoiseGenerator.hpp | 10 |
| **Notation** | Core | Source/Engine/Core/ BigInt.hpp | 30 |
| **NoticeEntry** | Core | Source/Engine/Core/ ThirdPartyNotices.hpp | 12 |
| **OptimizationAdvice** | Core | Source/Engine/Core/ BuildProfile.hpp | 154 |
| **OptimizationLevel** | Core | Source/Engine/Core/ BuildProfile.hpp | 10 |
| **Pcg32** | Core | Source/Engine/Core/ Pcg32.hpp | 20 |
| **PipelineTag** | Core | Source/Engine/Core/ Types.hpp | 303 |
| **PluginHost** | Core | Source/Engine/Core/ PluginHost.hpp | 76 |
| **PluginSystem** | Core | Source/Engine/Core/ PluginHost.hpp | 54 |
| **Profiler** | Core | Source/Engine/Core/ Profiler.hpp | 43 |
| **ProfileRow** | Core | Source/Engine/Core/ ProfilerPanel.hpp | 26 |
| **ProfilerPanel** | Core | Source/Engine/Core/ ProfilerPanel.hpp | 39 |
| **ProfileSample** | Core | Source/Engine/Core/ Profiler.hpp | 28 |
| **ProfileSortMode** | Core | Source/Engine/Core/ | 16 |

| | | | |
|---|---|---|---|
| | | ProfilerPanel.hpp | |
| **ProfileStats** | Core | Source/Engine/Core/Profiler.hpp | 16 |
| **ProjectionMode** | Core | Source/Engine/Core/Grid.hpp | 17 |
| **Rect** | Core | Source/Engine/Core/Types.hpp | 173 |
| **Reflection** | Core | Source/Engine/Core/Mirror.hpp | 66 |
| **Reflection** | Core | Source/Engine/Core/Mirror.hpp | 294 |
| **Reflection** | Core | Source/Engine/Core/Mirror.hpp | 306 |
| **ReplayFrame** | Core | Source/Engine/Core/Replay.hpp | 238 |
| **ReplayKeyframe** | Core | Source/Engine/Core/Replay.hpp | 16 |
| **ReplaySession** | Core | Source/Engine/Core/Replay.hpp | 25 |
| **RngState** | Core | Source/Engine/Core/Pcg32.hpp | 11 |
| **RoundingMode** | Core | Source/Engine/Core/Decimal.hpp | 22 |
| **SamplerTag** | Core | Source/Engine/Core/Types.hpp | 304 |
| **Scope** | Core | Source/Engine/Core/Profiler.hpp | 141 |
| **SecureRng** | Core | Source/Engine/Core/SecureRng.hpp | 11 |
| **Sha256Context** | Core | Source/Engine/Core/Sha256.hpp | 17 |
| **Slot** | Core | Source/Engine/Core/BigNumberStore.hpp | 252 |
| **Slot** | Core | Source/Engine/Core/DecimalStore.hpp | 199 |
| **SplashClock** | Core | Source/Engine/Core/Splash.hpp | 10 |
| **Status** | Core | Source/Engine/Core/BigInt.hpp | 18 |
| **Stopwatch** | Core | Source/Engine/Core/Time.hpp | 209 |

| | | | |
|---|---|---|---|
| **Task** | Core | Source/Engine/Core/JobSystem.hpp | 96 |
| **TextureTag** | Core | Source/Engine/Core/Types.hpp | 302 |
| **TextWriter** | Core | Source/Engine/Core/Calendar.hpp | 189 |
| **ThreadCounter** | Core | Source/Engine/Core/JobSystem.hpp | 109 |
| **ThreadLoad** | Core | Source/Engine/Core/JobSystem.hpp | 31 |
| **TimerFired** | Core | Source/Engine/Core/Time.hpp | 255 |
| **TimerHandle** | Core | Source/Engine/Core/Time.hpp | 240 |
| **TimerPool** | Core | Source/Engine/Core/Time.hpp | 266 |
| **TypeNameOverride** | Core | Source/Engine/Core/Definitions.hpp | 40 |
| **TypeNameOverride** | Core | Source/Engine/Core/Definitions.hpp | 283 |
| **TypeObject** | Core | Source/Engine/Core/Definitions.hpp | 185 |
| **TypeRecord** | Core | Source/Engine/Core/Definitions.hpp | 85 |
| **TypeTable** | Core | Source/Engine/Core/Definitions.hpp | 93 |
| **TypeTraits** | Core | Source/Engine/Core/Definitions.hpp | 170 |
| **TypeTraits** | Core | Source/Engine/Core/Definitions.hpp | 267 |
| **Unregistered** | Core | Source/Engine/Core/Mirror.hpp | 59 |
| **Vector2D** | Core | Source/Engine/Core/Types.hpp | 13 |
| **Vector3D** | Core | Source/Engine/Core/Types.hpp | 90 |
| **Vector4D** | Core | Source/Engine/Core/Types.hpp | 139 |
| **WindowDesc** | Core | Source/Engine/Core/WindowManager.hpp | 204 |
| **WindowExtent** | Core | Source/Engine/ | 37 |

| | | | |
|---|---|---|---|
| | | Core/ WindowManager.hpp | |
| **WindowHost** | Core | Source/Engine/ Core/WindowHost.hpp | 17 |
| **WindowManager** | Core | Source/Engine/ Core/ WindowManager.hpp | 215 |
| **WindowMode** | Core | Source/Engine/ Core/ WindowManager.hpp | 195 |
| **WindowRecord** | Core | Source/Engine/ Core/WindowHost.hpp | 30 |
| **X25519KeyPair** | Core | Source/Engine/Core/ CryptoAsymmetric.hp p | 20 |

### Engine/ECS (211)

| Symbol | Kind | Header | Line |
|---|---|---|---|
| **AccessibilityKernel** | ECS | Source/Engine/ECS/ Schedule.hpp | 21 |
| **AICommandCompon ent** | ECS | Source/Engine/ECS/ StateTree.hpp | 175 |
| **AICommandKind** | ECS | Source/Engine/ECS/ StateTree.hpp | 163 |
| **AnimationTimeline** | ECS | Source/Engine/ECS/ AnimationTimeline.hp p | 90 |
| **AnimBoneKey** | ECS | Source/Engine/ECS/ AnimGraph.hpp | 74 |
| **AnimClip** | ECS | Source/Engine/ECS/ AnimGraph.hpp | 86 |
| **AnimConditionFlags** | ECS | Source/Engine/ECS/ AnimGraph.hpp | 28 |
| **AnimGraphSystem** | ECS | Source/Engine/ECS/ AnimGraph.hpp | 180 |
| **AnimRestBone** | ECS | Source/Engine/ECS/ AnimGraph.hpp | 104 |
| **AnimStateCompone nt** | ECS | Source/Engine/ECS/ AnimGraph.hpp | 114 |
| **AnimTransition** | ECS | Source/Engine/ECS/ AnimGraph.hpp | 48 |

| | | | |
|---|---|---|---|
| **AssetDatabase** | ECS | Source/Engine/ECS/Scene.hpp | 21 |
| **AssetDatabase** | ECS | Source/Engine/ECS/Schedule.hpp | 33 |
| **AudioSystem** | ECS | Source/Engine/ECS/Schedule.hpp | 16 |
| **BigIntComponent** | ECS | Source/Engine/ECS/Components.hpp | 265 |
| **CachedTarget** | ECS | Source/Engine/ECS/LightSource.hpp | 229 |
| **Camera2D** | ECS | Source/Engine/ECS/Components.hpp | 218 |
| **CameraStackSystem** | ECS | Source/Engine/ECS/Schedule.hpp | 26 |
| **CarrierMemberComponent** | ECS | Source/Engine/ECS/Components.hpp | 168 |
| **ChainIdTag** | ECS | Source/Engine/ECS/StableIds.hpp | 12 |
| **ChainSaveV3** | ECS | Source/Engine/ECS/SnapshotWorld.hpp | 28 |
| **ChangeMaskBit** | ECS | Source/Engine/ECS/ChangeMask.hpp | 19 |
| **CharacterDesc** | ECS | Source/Engine/ECS/Descriptors.hpp | 51 |
| **ChunkCopyRange** | ECS | Source/Engine/ECS/RenderEcs.hpp | 90 |
| **ChunkHeader** | ECS | Source/Engine/ECS/RenderEcs.hpp | 45 |
| **ClothIdTag** | ECS | Source/Engine/ECS/StableIds.hpp | 13 |
| **ClothSaveV3** | ECS | Source/Engine/ECS/SnapshotWorld.hpp | 59 |
| **ClothSystem** | ECS | Source/Engine/ECS/Schedule.hpp | 23 |
| **ColliderSnapshot** | ECS | Source/Engine/ECS/Snapshot.hpp | 181 |
| **CollisionMode** | ECS | Source/Engine/ECS/Presentation.hpp | 21 |
| **CollisionPolicyComponent** | ECS | Source/Engine/ECS/Presentation.hpp | 101 |
| **Command** | ECS | Source/Engine/ECS/ | 29 |

| | | | |
|---|---|---|---|
| | | CommandBuffer.hpp | |
| **CommandBuffer** | ECS | Source/Engine/ECS/ CommandBuffer.hpp | 37 |
| **CommandBuffer** | ECS | Source/Engine/ECS/ Schedule.hpp | 54 |
| **CommandCutChain** | ECS | Source/Engine/ECS/ CommandLog.hpp | 42 |
| **CommandKind** | ECS | Source/Engine/ECS/ CommandBuffer.hpp | 19 |
| **CommandLog** | ECS | Source/Engine/ECS/ CommandLog.hpp | 92 |
| **CommandLogHeader** | ECS | Source/Engine/ECS/ CommandLog.hpp | 66 |
| **CommandRecord** | ECS | Source/Engine/ECS/ CommandLog.hpp | 78 |
| **CommandType** | ECS | Source/Engine/ECS/ CommandLog.hpp | 22 |
| **CommandWorldCallbacks** | ECS | Source/Engine/ECS/ CommandLog.hpp | 52 |
| **ComponentChangeMask** | ECS | Source/Engine/ECS/ ChangeMask.hpp | 52 |
| **ComponentOps** | ECS | Source/Engine/ECS/ ComponentRegistry.hpp | 30 |
| **ComponentOpsFor** | ECS | Source/Engine/ECS/ ComponentRegistry.hpp | 55 |
| **ComponentRegistry** | ECS | Source/Engine/ECS/ ComponentRegistry.hpp | 116 |
| **CompressedClip** | ECS | Source/Engine/ECS/ AnimationCompression.hpp | 47 |
| **CompressedKey** | ECS | Source/Engine/ECS/ AnimationCompression.hpp | 19 |
| **CompressedTrack** | ECS | Source/Engine/ECS/ AnimationCompression.hpp | 31 |
| **CompressionReport** | ECS | Source/Engine/ECS/ AnimationCompression.hpp | 63 |
| **Cursor** | ECS | Source/Engine/ECS/ | 177 |

| | | | |
|---|---|---|---|
| | | CommandLog.hpp | |
| **DecimalComponent** | ECS | Source/Engine/ECS/ Components.hpp | 276 |
| **DrawOrder** | ECS | Source/Engine/ECS/ Components.hpp | 207 |
| **EditorSelected** | ECS | Source/Engine/ECS/ Components.hpp | 232 |
| **EmitterIdTag** | ECS | Source/Engine/ECS/ StableIds.hpp | 14 |
| **EmitterSaveV3** | ECS | Source/Engine/ECS/ SnapshotWorld.hpp | 79 |
| **EntityRemap** | ECS | Source/Engine/ECS/ Scene.hpp | 59 |
| **Entry** | ECS | Source/Engine/ECS/ Schedule.hpp | 130 |
| **FeskIHeader** | ECS | Source/Engine/ECS/ SkeletonAsset.hpp | 37 |
| **FeskINameRef** | ECS | Source/Engine/ECS/ SkeletonAsset.hpp | 87 |
| **FeskISprite** | ECS | Source/Engine/ECS/ SkeletonAsset.hpp | 97 |
| **FluidSaveV3** | ECS | Source/Engine/ECS/ SnapshotWorld.hpp | 71 |
| **FluidWaveSystem** | ECS | Source/Engine/ECS/ Schedule.hpp | 24 |
| **FontAtlasSet** | ECS | Source/Engine/ECS/ Schedule.hpp | 41 |
| **FrameArena** | ECS | Source/Engine/ECS/ Schedule.hpp | 17 |
| **GameplayAttributeRegistry** | ECS | Source/Engine/ECS/ Schedule.hpp | 28 |
| **GameplayEffectSystem** | ECS | Source/Engine/ECS/ Schedule.hpp | 29 |
| **GameplaySkillSystem** | ECS | Source/Engine/ECS/ Schedule.hpp | 30 |
| **GameplayTagRegistry** | ECS | Source/Engine/ECS/ Schedule.hpp | 27 |
| **GpuEntity** | ECS | Source/Engine/ECS/ RenderEcs.hpp | 31 |
| **GpuSpriteInstance** | ECS | Source/Engine/ECS/ RenderEcs.hpp | 245 |

| | | | |
|---|---|---|---|
| **GraphSystem** | ECS | Source/Engine/ECS/SystemGraph.hpp | 17 |
| **Hidden** | ECS | Source/Engine/ECS/Components.hpp | 237 |
| **IkChain** | ECS | Source/Engine/ECS/SkeletonIk.hpp | 43 |
| **IkComponent** | ECS | Source/Engine/ECS/SkeletonIk.hpp | 64 |
| **IkGoalComponent** | ECS | Source/Engine/ECS/SkeletonIk.hpp | 77 |
| **IkSolver** | ECS | Source/Engine/ECS/SkeletonIk.hpp | 19 |
| **InputUserComponent** | ECS | Source/Engine/ECS/Components.hpp | 65 |
| **Interpolation** | ECS | Source/Engine/ECS/AnimationTimeline.hpp | 29 |
| **ITextShaper** | ECS | Source/Engine/ECS/Schedule.hpp | 47 |
| **Lifetime** | ECS | Source/Engine/ECS/Components.hpp | 226 |
| **Light2DComponent** | ECS | Source/Engine/ECS/Lighting.hpp | 37 |
| **Light2DOccluderComponent** | ECS | Source/Engine/ECS/Lighting.hpp | 106 |
| **Light2DResultComponent** | ECS | Source/Engine/ECS/Lighting.hpp | 69 |
| **Light2DTargetComponent** | ECS | Source/Engine/ECS/Lighting.hpp | 53 |
| **LightGrid2D** | ECS | Source/Engine/ECS/LightGrid.hpp | 26 |
| **LightGridInput** | ECS | Source/Engine/ECS/LightGrid.hpp | 16 |
| **LightingSettings** | ECS | Source/Engine/ECS/Lighting.hpp | 117 |
| **LightingSystem** | ECS | Source/Engine/ECS/Lighting.hpp | 144 |
| **LightSourceComponent** | ECS | Source/Engine/ECS/LightSource.hpp | 48 |
| **LightSourceFlags** | ECS | Source/Engine/ECS/LightSource.hpp | 32 |
| **LightSourceSettings** | ECS | Source/Engine/ECS/ | 149 |

| | | | |
|---|---|---|---|
| | | LightSource.hpp | |
| **LightSourceSystem** | ECS | Source/Engine/ECS/ LightSource.hpp | 168 |
| **LightSourceType** | ECS | Source/Engine/ECS/ LightSource.hpp | 22 |
| **LocalizationTable** | ECS | Source/Engine/ECS/ Schedule.hpp | 22 |
| **LocalizedTextCompo nent** | ECS | Source/Engine/ECS/ Components.hpp | 323 |
| **LocalTransform2D** | ECS | Source/Engine/ECS/ Components.hpp | 34 |
| **Mat3** | ECS | Source/Engine/ECS/ Skeleton.hpp | 31 |
| **NameComponent** | ECS | Source/Engine/ECS/ Components.hpp | 244 |
| **NarrativeLabelComp onent** | ECS | Source/Engine/ECS/ Components.hpp | 254 |
| **NativeCleanupHook** | ECS | Source/Engine/ECS/ RegistryOps.hpp | 12 |
| **PackedTransform2D** | ECS | Source/Engine/ECS/ RenderEcs.hpp | 229 |
| **Parent2D** | ECS | Source/Engine/ECS/ Components.hpp | 42 |
| **Phase** | ECS | Source/Engine/ECS/ Schedule.hpp | 59 |
| **PhysicsBodyDesc** | ECS | Source/Engine/ECS/ Descriptors.hpp | 22 |
| **PhysicsJointSystem** | ECS | Source/Engine/ECS/ Schedule.hpp | 25 |
| **PhysicsShapeKind** | ECS | Source/Engine/ECS/ Descriptors.hpp | 15 |
| **PhysicsSystem** | ECS | Source/Engine/ECS/ Schedule.hpp | 18 |
| **PrefabAsset** | ECS | Source/Engine/ECS/ Descriptors.hpp | 88 |
| **PrefabEntityDesc** | ECS | Source/Engine/ECS/ Descriptors.hpp | 76 |
| **PrefabEntityFlags** | ECS | Source/Engine/ECS/ Descriptors.hpp | 98 |
| **PrefabEntityOverride** | ECS | Source/Engine/ECS/ PrefabSystem.hpp | 18 |

| | | | |
|---|---|---|---|
| **PrefabOverrides** | ECS | Source/Engine/ECS/PrefabSystem.hpp | 31 |
| **PrefabSystem** | ECS | Source/Engine/ECS/PrefabSystem.hpp | 36 |
| **QuantizedPose** | ECS | Source/Engine/ECS/SkeletonIk.hpp | 165 |
| **RenderChunk** | ECS | Source/Engine/ECS/RenderEcs.hpp | 62 |
| **RenderChunkArena** | ECS | Source/Engine/ECS/RenderEcs.hpp | 304 |
| **RenderEcs** | ECS | Source/Engine/ECS/RenderEcs.hpp | 456 |
| **RenderMaskComponent** | ECS | Source/Engine/ECS/Presentation.hpp | 139 |
| **RenderPassMask** | ECS | Source/Engine/ECS/Presentation.hpp | 126 |
| **ReplayPlayback** | ECS | Source/Engine/ECS/ReplayRecorder.hpp | 103 |
| **ReplayRecorder** | ECS | Source/Engine/ECS/ReplayRecorder.hpp | 32 |
| **RetargetMap** | ECS | Source/Engine/ECS/SkeletonIk.hpp | 131 |
| **RetargetPair** | ECS | Source/Engine/ECS/SkeletonIk.hpp | 118 |
| **RHI** | ECS | Source/Engine/ECS/Schedule.hpp | 37 |
| **RigidBodySnapshot** | ECS | Source/Engine/ECS/Snapshot.hpp | 167 |
| **SceneComponent** | ECS | Source/Engine/ECS/Scene.hpp | 38 |
| **SceneData** | ECS | Source/Engine/ECS/Scene.hpp | 52 |
| **SceneEntity** | ECS | Source/Engine/ECS/Scene.hpp | 45 |
| **SceneLoadOptions** | ECS | Source/Engine/ECS/Scene.hpp | 76 |
| **SceneMeta** | ECS | Source/Engine/ECS/Scene.hpp | 31 |
| **Schedule** | ECS | Source/Engine/ECS/Schedule.hpp | 125 |
| **SdfBrickMap** | ECS | Source/Engine/ECS/ | 17 |

| | | | |
|---|---|---|---|
| | | Lighting.hpp | |
| **SdfGiVolume** | ECS | Source/Engine/ECS/ Lighting.hpp | 18 |
| **SdfLightingFrame** | ECS | Source/Engine/ECS/ Lighting.hpp | 22 |
| **SdfSunComponent** | ECS | Source/Engine/ECS/ Lighting.hpp | 81 |
| **SkeletonAssetRef** | ECS | Source/Engine/ECS/ SkeletonAssetRef.hpp | 20 |
| **SkeletonAssetSource** | ECS | Source/Engine/ECS/ SkeletonAsset.hpp | 189 |
| **SkeletonAssetView** | ECS | Source/Engine/ECS/ SkeletonAsset.hpp | 121 |
| **SkeletonBoneName** | ECS | Source/Engine/ECS/ SkeletonAsset.hpp | 168 |
| **SkeletonComponent** | ECS | Source/Engine/ECS/ Skeleton.hpp | 121 |
| **SkeletonNameTable** | ECS | Source/Engine/ECS/ SkeletonAsset.hpp | 175 |
| **SkeletonSystem** | ECS | Source/Engine/ECS/ Skeleton.hpp | 198 |
| **SkinComponent** | ECS | Source/Engine/ECS/ Skeleton.hpp | 136 |
| **SkinnedSprite** | ECS | Source/Engine/ECS/ Skeleton.hpp | 147 |
| **SleepingStaticComponent** | ECS | Source/Engine/ECS/ Presentation.hpp | 202 |
| **SnapshotBaseline** | ECS | Source/Engine/ECS/ Snapshot.hpp | 314 |
| **SnapshotComponent** | ECS | Source/Engine/ECS/ Snapshot.hpp | 76 |
| **SnapshotComponentOp** | ECS | Source/Engine/ECS/ Snapshot.hpp | 41 |
| **SnapshotExtras** | ECS | Source/Engine/ECS/ Snapshot.hpp | 265 |
| **SnapshotFlags** | ECS | Source/Engine/ECS/ Snapshot.hpp | 29 |
| **SnapshotHeader** | ECS | Source/Engine/ECS/ Snapshot.hpp | 47 |
| **SnapshotRecordFlags** | ECS | Source/Engine/ECS/ Snapshot.hpp | 35 |

| | | | |
|---|---|---|---|
| **SnapshotRestoreExtras** | ECS | Source/Engine/ECS/Snapshot.hpp | 270 |
| **SnapshotSchema** | ECS | Source/Engine/ECS/Snapshot.hpp | 91 |
| **SnapshotSchema** | ECS | Source/Engine/ECS/Snapshot.hpp | 206 |
| **SnapshotView** | ECS | Source/Engine/ECS/Snapshot.hpp | 255 |
| **Sprite2D** | ECS | Source/Engine/ECS/Components.hpp | 192 |
| **SpriteAnimationComponent** | ECS | Source/Engine/ECS/SpriteAnimation.hpp | 21 |
| **SpriteAnimationEventQueue** | ECS | Source/Engine/ECS/SpriteAnimation.hpp | 74 |
| **SpriteAnimationSystem** | ECS | Source/Engine/ECS/SpriteAnimation.hpp | 118 |
| **SpriteFrameEvent** | ECS | Source/Engine/ECS/SpriteAnimation.hpp | 66 |
| **SpriteFrameRect** | ECS | Source/Engine/ECS/SpriteAnimation.hpp | 55 |
| **SpriteSheetComponent** | ECS | Source/Engine/ECS/SpriteAnimation.hpp | 40 |
| **StableIdAllocator** | ECS | Source/Engine/ECS/StableIds.hpp | 25 |
| **StateTreeComponent** | ECS | Source/Engine/ECS/StateTree.hpp | 192 |
| **StateTreeDefinition** | ECS | Source/Engine/ECS/StateTree.hpp | 152 |
| **StateTreeEvaluator** | ECS | Source/Engine/ECS/StateTree.hpp | 55 |
| **StateTreeEvaluatorKind** | ECS | Source/Engine/ECS/StateTree.hpp | 28 |
| **StateTreeNode** | ECS | Source/Engine/ECS/StateTree.hpp | 115 |
| **StateTreeNodeKind** | ECS | Source/Engine/ECS/StateTree.hpp | 105 |
| **StateTreeSystem** | ECS | Source/Engine/ECS/StateTree.hpp | 237 |
| **StateTreeTask** | ECS | Source/Engine/ECS/StateTree.hpp | 87 |
| **StateTreeTaskKind** | ECS | Source/Engine/ECS/ | 73 |

| | | | |
|---|---|---|---|
| | | StateTree.hpp | |
| **StateTreeTransition** | ECS | Source/Engine/ECS/StateTree.hpp | 134 |
| **SystemContext** | ECS | Source/Engine/ECS/Schedule.hpp | 87 |
| **SystemGraph** | ECS | Source/Engine/ECS/Schedule.hpp | 55 |
| **SystemGraph** | ECS | Source/Engine/ECS/SystemGraph.hpp | 29 |
| **TextComponent** | ECS | Source/Engine/ECS/Components.hpp | 295 |
| **TextConditionComponent** | ECS | Source/Engine/ECS/Components.hpp | 379 |
| **TextEffectComponent** | ECS | Source/Engine/ECS/Components.hpp | 349 |
| **TextFormatComponent** | ECS | Source/Engine/ECS/Components.hpp | 361 |
| **TextService** | ECS | Source/Engine/ECS/Schedule.hpp | 45 |
| **TextShapeCache** | ECS | Source/Engine/ECS/Schedule.hpp | 46 |
| **TextShapeComponent** | ECS | Source/Engine/ECS/Components.hpp | 338 |
| **TilemapAssetRefComponent** | ECS | Source/Engine/ECS/Tilemap.hpp | 130 |
| **TilemapComponent** | ECS | Source/Engine/ECS/Tilemap.hpp | 63 |
| **TilemapRenderSystem** | ECS | Source/Engine/ECS/Tilemap.hpp | 150 |
| **TileQuad** | ECS | Source/Engine/ECS/Tilemap.hpp | 142 |
| **TimelineEvent** | ECS | Source/Engine/ECS/AnimationTimeline.hpp | 67 |
| **TimelineEventKind** | ECS | Source/Engine/ECS/AnimationTimeline.hpp | 36 |
| **TimelineKey** | ECS | Source/Engine/ECS/AnimationTimeline.hpp | 43 |
| **TimelineTrack** | ECS | Source/Engine/ECS/AnimationTimeline.hp | 56 |

| | | | |
|---|---|---|---|
| | | p | |
| **TimelineTriggerSink** | ECS | Source/Engine/ECS/AnimationTimeline.hpp | 83 |
| **TimeScaleComponent** | ECS | Source/Engine/ECS/Presentation.hpp | 168 |
| **TrackKind** | ECS | Source/Engine/ECS/AnimationTimeline.hpp | 20 |
| **Transform2D** | ECS | Source/Engine/ECS/Components.hpp | 23 |
| **TransportGroupComponent** | ECS | Source/Engine/ECS/Components.hpp | 152 |
| **TransportMotion** | ECS | Source/Engine/ECS/Components.hpp | 138 |
| **TransportPath** | ECS | Source/Engine/ECS/Components.hpp | 129 |
| **TransportSurface** | ECS | Source/Engine/ECS/Components.hpp | 119 |
| **Vehicle2D** | ECS | Source/Engine/ECS/Components.hpp | 83 |
| **VehicleFlags** | ECS | Source/Engine/ECS/Components.hpp | 75 |
| **Velocity** | ECS | Source/Engine/ECS/Components.hpp | 186 |
| **View** | ECS | Source/Engine/ECS/CommandLog.hpp | 187 |
| **VirtualFileSystem** | ECS | Source/Engine/ECS/Scene.hpp | 18 |
| **VirtualFileSystem** | ECS | Source/Engine/ECS/Schedule.hpp | 20 |
| **VirtualFileSystem** | ECS | Source/Engine/ECS/SkeletonAsset.hpp | 18 |
| **VirtualFileSystem** | ECS | Source/Engine/ECS/Tilemap.hpp | 20 |
| **Wheel2D** | ECS | Source/Engine/ECS/Components.hpp | 99 |
| **WindowManager** | ECS | Source/Engine/ECS/Schedule.hpp | 19 |
| **WorldSnapshotV3** | ECS | Source/Engine/ECS/SnapshotWorld.hpp | 86 |

## Engine/Gameplay (31)

| Symbol | Kind | Header | Line |
|---|---|---|---|
| **ActiveGameplayEffect** | Gameplay | Source/Engine/Gameplay/GameplayEffects.hpp | 66 |
| **Entry** | Gameplay | Source/Engine/Gameplay/GameplayAttributes.hpp | 50 |
| **Entry** | Gameplay | Source/Engine/Gameplay/GameplayTags.hpp | 152 |
| **GameplayAttribute** | Gameplay | Source/Engine/Gameplay/GameplayAttributes.hpp | 21 |
| **GameplayAttributeModifier** | Gameplay | Source/Engine/Gameplay/GameplayAttributes.hpp | 82 |
| **GameplayAttributeRegistry** | Gameplay | Source/Engine/Gameplay/GameplayAttributes.hpp | 35 |
| **GameplayAttributesComponent** | Gameplay | Source/Engine/Gameplay/GameplayAttributes.hpp | 66 |
| **GameplayAttributeValues** | Gameplay | Source/Engine/Gameplay/GameplayAttributes.hpp | 60 |
| **GameplayEffectDef** | Gameplay | Source/Engine/Gameplay/GameplayEffects.hpp | 45 |
| **GameplayEffectEvent** | Gameplay | Source/Engine/Gameplay/GameplayEffects.hpp | 95 |
| **GameplayEffectEventType** | Gameplay | Source/Engine/Gameplay/GameplayEffects.hpp | 88 |
| **GameplayEffectFlags** | Gameplay | Source/Engine/Gameplay/GameplayEffects.hpp | 32 |
| **GameplayEffectsCo** | Gameplay | Source/Engine/ | 78 |

| | | | |
|---|---|---|---|
| **mponent** | | Gameplay/ GameplayEffects.hpp | |
| **GameplayEffectStackPolicy** | Gameplay | Source/Engine/ Gameplay/ GameplayEffects.hpp | 22 |
| **GameplayEffectSystem** | Gameplay | Source/Engine/ Gameplay/ GameplayEffects.hpp | 107 |
| **GameplayModifierOp** | Gameplay | Source/Engine/ Gameplay/ GameplayAttributes.hpp | 75 |
| **GameplaySkillDef** | Gameplay | Source/Engine/ Gameplay/ GameplaySkills.hpp | 55 |
| **GameplaySkillEvent** | Gameplay | Source/Engine/ Gameplay/ GameplaySkills.hpp | 98 |
| **GameplaySkillEventType** | Gameplay | Source/Engine/ Gameplay/ GameplaySkills.hpp | 33 |
| **GameplaySkillFailReason** | Gameplay | Source/Engine/ Gameplay/ GameplaySkills.hpp | 41 |
| **GameplaySkillsComponent** | Gameplay | Source/Engine/ Gameplay/ GameplaySkills.hpp | 89 |
| **GameplaySkillSlot** | Gameplay | Source/Engine/ Gameplay/ GameplaySkills.hpp | 77 |
| **GameplaySkillState** | Gameplay | Source/Engine/ Gameplay/ GameplaySkills.hpp | 27 |
| **GameplaySkillSystem** | Gameplay | Source/Engine/ Gameplay/ GameplaySkills.hpp | 110 |
| **GameplaySkillTargetKind** | Gameplay | Source/Engine/ Gameplay/ GameplaySkills.hpp | 19 |
| **GameplayTag** | Gameplay | Source/Engine/ Gameplay/ GameplayTags.hpp | 22 |
| **GameplayTagContainer** | Gameplay | Source/Engine/ Gameplay/ GameplayTags.hpp | 170 |

| | | | |
|---|---|---|---|
| **GameplayTagDatabase** | Gameplay | Source/Engine/Gameplay/GameplayTagDatabase.hpp | 18 |
| **GameplayTagMask** | Gameplay | Source/Engine/Gameplay/GameplayTags.hpp | 38 |
| **GameplayTagRegistry** | Gameplay | Source/Engine/Gameplay/GameplayTags.hpp | 132 |
| **GameplayTagsComponent** | Gameplay | Source/Engine/Gameplay/GameplayTags.hpp | 211 |

## Engine/Input (14)

| Symbol | Kind | Header | Line |
|---|---|---|---|
| **InputActionDesc** | Input | Source/Engine/Input/InputSystem.hpp | 81 |
| **InputActionState** | Input | Source/Engine/Input/InputSystem.hpp | 108 |
| **InputActionType** | Input | Source/Engine/Input/InputSystem.hpp | 23 |
| **InputContextDesc** | Input | Source/Engine/Input/InputSystem.hpp | 87 |
| **InputEvent** | Input | Source/Engine/Input/InputSystem.hpp | 120 |
| **InputEventType** | Input | Source/Engine/Input/InputSystem.hpp | 60 |
| **InputMappingDesc** | Input | Source/Engine/Input/InputSystem.hpp | 94 |
| **InputModifier** | Input | Source/Engine/Input/InputSystem.hpp | 74 |
| **InputModifierKind** | Input | Source/Engine/Input/InputSystem.hpp | 39 |
| **InputSource** | Input | Source/Engine/Input/InputSystem.hpp | 68 |
| **InputSourceKind** | Input | Source/Engine/Input/InputSystem.hpp | 30 |
| **InputSystem** | Input | Source/Engine/Input/InputSystem.hpp | 132 |
| **InputTriggerKind** | Input | Source/Engine/Input/InputSystem.hpp | 50 |

| | | | |
|---|---|---|---|
| **UserSlot** | Input | Source/Engine/Input/ InputSystem.hpp | 175 |

## Engine/Navigation (25)

| Symbol | Kind | Header | Line |
|---|---|---|---|
| **CrowdAgent** | Navigation | Source/Engine/ Navigation/ CrowdPool.hpp | 16 |
| **CrowdPool** | Navigation | Source/Engine/ Navigation/ CrowdPool.hpp | 46 |
| **CrowdRenderSettings** | Navigation | Source/Engine/ Navigation/ CrowdRender.hpp | 14 |
| **CrowdSettings** | Navigation | Source/Engine/ Navigation/ CrowdPool.hpp | 27 |
| **Entry** | Navigation | Source/Engine/ Navigation/ FlowField.hpp | 79 |
| **FlowField** | Navigation | Source/Engine/ Navigation/ FlowField.hpp | 33 |
| **FlowFieldDesc** | Navigation | Source/Engine/ Navigation/ FlowField.hpp | 22 |
| **NavAgentComponent** | Navigation | Source/Engine/ Navigation/ Navigation.hpp | 242 |
| **NavAgentPathSettings** | Navigation | Source/Engine/ Navigation/ Navigation.hpp | 206 |
| **NavAgentSettings** | Navigation | Source/Engine/ Navigation/ Navigation.hpp | 184 |
| **NavigationSystem** | Navigation | Source/Engine/ Navigation/ Navigation.hpp | 265 |
| **NavMap** | Navigation | Source/Engine/ Navigation/ Navigation.hpp | 27 |
| **NavMesh** | Navigation | Source/Engine/ Navigation/ | 49 |

| | | | |
|---|---|---|---|
| | | NavMesh.hpp | |
| **NavMesh** | Navigation | Source/Engine/ Navigation/ Navigation.hpp | 18 |
| **NavMeshPortal** | Navigation | Source/Engine/ Navigation/ NavMesh.hpp | 39 |
| **NavMeshRect** | Navigation | Source/Engine/ Navigation/ NavMesh.hpp | 19 |
| **NavPath** | Navigation | Source/Engine/ Navigation/ Navigation.hpp | 99 |
| **NavPathOptions** | Navigation | Source/Engine/ Navigation/ Navigation.hpp | 80 |
| **NavSmoothingMode** | Navigation | Source/Engine/ Navigation/ Navigation.hpp | 72 |
| **Page** | Navigation | Source/Engine/ Navigation/ PagedNavGrid.hpp | 105 |
| **PagedNavGrid** | Navigation | Source/Engine/ Navigation/ PagedNavGrid.hpp | 32 |
| **PagedNavGridDesc** | Navigation | Source/Engine/ Navigation/ PagedNavGrid.hpp | 23 |
| **PathFinder** | Navigation | Source/Engine/ Navigation/ Navigation.hpp | 127 |
| **PathStats** | Navigation | Source/Engine/ Navigation/ Navigation.hpp | 116 |
| **TilemapComponent** | Navigation | Source/Engine/ Navigation/ PagedNavGrid.hpp | 14 |

## Engine/Network (89)

| Symbol | Kind | Header | Line |
|---|---|---|---|
| **CellCoordinate** | Network | Source/Engine/ Network/ RelevanceGrid.hpp | 168 |

| | | | |
|---|---|---|---|
| **ChecksumComparison** | Network | Source/Engine/Network/NetRollback.hpp | 457 |
| **Config** | Network | Source/Engine/Network/NetRollback.hpp | 316 |
| **DatagramSocket** | Network | Source/Engine/Network/Transport.hpp | 32 |
| **Endpoint** | Network | Source/Engine/Network/NetLink.hpp | 92 |
| **Frame** | Network | Source/Engine/Network/NetLink.hpp | 84 |
| **FrameInfo** | Network | Source/Engine/Network/NetRollback.hpp | 221 |
| **FrameMeta** | Network | Source/Engine/Network/NetRollback.hpp | 473 |
| **InputChannel** | Network | Source/Engine/Network/NetProtocol.hpp | 56 |
| **InputChannelStats** | Network | Source/Engine/Network/NetProtocol.hpp | 44 |
| **InputPacket** | Network | Source/Engine/Network/NetProtocol.hpp | 24 |
| **InputRingBuffer** | Network | Source/Engine/Network/NetRollback.hpp | 123 |
| **LobbyError** | Network | Source/Engine/Network/Lobby.hpp | 37 |
| **LobbyMessageType** | Network | Source/Engine/Network/Lobby.hpp | 25 |
| **LobbyRoomInfo** | Network | Source/Engine/Network/Lobby.hpp | 73 |
| **LobbyServer** | Network | Source/Engine/Network/Lobby.hpp | 93 |
| **LobbyServerConfig** | Network | Source/Engine/Network/Lobby.hpp | 82 |
| **LocalEntry** | Network | Source/Engine/Network/NetRollback.hpp | 205 |

| | | | |
|---|---|---|---|
| **Member** | Network | Source/Engine/ Network/Lobby.hpp | 126 |
| **MemoryEndpoint** | Network | Source/Engine/ Network/NetLink.hpp | 46 |
| **MemoryEndpoint** | Network | Source/Engine/ Network/NetLink.hpp | 113 |
| **MemoryNetwork** | Network | Source/Engine/ Network/NetLink.hpp | 53 |
| **NetAddress** | Network | Source/Engine/ Network/ Transport.hpp | 19 |
| **NetDiagnosticsSnapshot** | Network | Source/Engine/ Network/ Diagnostics.hpp | 12 |
| **NetDisconnectReason** | Network | Source/Engine/ Network/Session.hpp | 65 |
| **NetEntityId** | Network | Source/Engine/ Network/ NetRollback.hpp | 39 |
| **NetEntityMap** | Network | Source/Engine/ Network/ NetRollback.hpp | 167 |
| **NetEntry** | Network | Source/Engine/ Network/ NetRollback.hpp | 200 |
| **NetIdentity** | Network | Source/Engine/ Network/Identity.hpp | 32 |
| **NetInputFrame** | Network | Source/Engine/ Network/ NetRollback.hpp | 70 |
| **NetInputStatus** | Network | Source/Engine/ Network/ NetRollback.hpp | 99 |
| **NetLink** | Network | Source/Engine/ Network/NetLink.hpp | 19 |
| **NetLobbyClient** | Network | Source/Engine/ Network/Lobby.hpp | 160 |
| **NetLobbyClientConfig** | Network | Source/Engine/ Network/Lobby.hpp | 151 |
| **NetPlayerId** | Network | Source/Engine/ Network/ NetRollback.hpp | 59 |
| **NetPlayerSlot** | Network | Source/Engine/ | 134 |

| | | | |
|---|---|---|---|
| | | Network/Session.hpp | |
| **NetRole** | Network | Source/Engine/ Network/Session.hpp | 32 |
| **NetRollbackSession** | Network | Source/Engine/ Network/ NetRollback.hpp | 240 |
| **NetSession** | Network | Source/Engine/ Network/Session.hpp | 189 |
| **NetSessionCallbacks** | Network | Source/Engine/ Network/Session.hpp | 178 |
| **NetSessionConfig** | Network | Source/Engine/ Network/Lobby.hpp | 15 |
| **NetSessionConfig** | Network | Source/Engine/ Network/Session.hpp | 149 |
| **NetSessionMode** | Network | Source/Engine/ Network/Session.hpp | 22 |
| **NetSessionStatus** | Network | Source/Engine/ Network/Session.hpp | 46 |
| **NetSlotState** | Network | Source/Engine/ Network/Session.hpp | 58 |
| **NetTicket** | Network | Source/Engine/ Network/Ticket.hpp | 35 |
| **NetTickInputs** | Network | Source/Engine/ Network/ NetRollback.hpp | 110 |
| **NetTickMode** | Network | Source/Engine/ Network/Session.hpp | 40 |
| **NetTransport** | Network | Source/Engine/ Network/ Transport.hpp | 127 |
| **Outstanding** | Network | Source/Engine/ Network/ Transport.hpp | 100 |
| **Peer** | Network | Source/Engine/ Network/ SecureSessionTransport.hpp | 87 |
| **PendingEvent** | Network | Source/Engine/ Network/Session.hpp | 279 |
| **PendingState** | Network | Source/Engine/ Network/ Replication.hpp | 129 |
| **Phase** | Network | Source/Engine/ | 256 |

| | | | |
|---|---|---|---|
| | | Network/ SecureChannel.hpp | |
| **PhysicsSystem** | Network | Source/Engine/ Network/ NetRollback.hpp | 20 |
| **RateEntry** | Network | Source/Engine/ Network/ SecureSessionTransport.hpp | 120 |
| **Reassembly** | Network | Source/Engine/ Network/ Transport.hpp | 112 |
| **RelevanceBand** | Network | Source/Engine/ Network/ RelevanceGrid.hpp | 32 |
| **RelevanceCell** | Network | Source/Engine/ Network/ RelevanceGrid.hpp | 71 |
| **RelevanceConfig** | Network | Source/Engine/ Network/ NetRollback.hpp | 34 |
| **RelevanceConfig** | Network | Source/Engine/ Network/ RelevanceGrid.hpp | 56 |
| **RelevanceEntity** | Network | Source/Engine/ Network/ RelevanceGrid.hpp | 81 |
| **RelevanceGrid** | Network | Source/Engine/ Network/ NetRollback.hpp | 36 |
| **RelevanceGrid** | Network | Source/Engine/ Network/ RelevanceGrid.hpp | 131 |
| **RelevanceGridStats** | Network | Source/Engine/ Network/ RelevanceGrid.hpp | 121 |
| **RelevancePlan** | Network | Source/Engine/ Network/ NetRollback.hpp | 35 |
| **RelevancePlan** | Network | Source/Engine/ Network/ RelevanceGrid.hpp | 93 |
| **ReplicationStatus** | Network | Source/Engine/ Network/ Replication.hpp | 28 |

| | | | |
|---|---|---|---|
| **Result** | Network | Source/Engine/ Network/ NetRollback.hpp | 243 |
| **RollbackReport** | Network | Source/Engine/ Network/ NetRollback.hpp | 229 |
| **Room** | Network | Source/Engine/ Network/Lobby.hpp | 132 |
| **SecureChannel** | Network | Source/Engine/ Network/ SecureChannel.hpp | 198 |
| **SecureChannelConfig** | Network | Source/Engine/ Network/ SecureChannel.hpp | 151 |
| **SecureCookieIssuer** | Network | Source/Engine/ Network/ SecureChannel.hpp | 131 |
| **SecureEndpoint** | Network | Source/Engine/ Network/ SecureEndpoint.hpp | 16 |
| **SecureSessionAuthConfig** | Network | Source/Engine/ Network/ SecureSessionTransport.hpp | 24 |
| **SecureSessionTransport** | Network | Source/Engine/ Network/ SecureSessionTransport.hpp | 38 |
| **SecureStatus** | Network | Source/Engine/ Network/ SecureChannel.hpp | 65 |
| **Slot** | Network | Source/Engine/ Network/ NetRollback.hpp | 155 |
| **SnapshotReceiver** | Network | Source/Engine/ Network/ Replication.hpp | 177 |
| **SnapshotReceiverConfig** | Network | Source/Engine/ Network/ Replication.hpp | 166 |
| **SnapshotSender** | Network | Source/Engine/ Network/ Replication.hpp | 94 |
| **SnapshotSenderConfig** | Network | Source/Engine/ Network/ | 70 |

| | | | |
|---|---|---|---|
| | | Replication.hpp | |
| **SnapshotSenderStats** | Network | Source/Engine/Network/Replication.hpp | 80 |
| **SortableEntity** | Network | Source/Engine/Network/RelevanceGrid.hpp | 195 |
| **TicketStatus** | Network | Source/Engine/Network/Ticket.hpp | 54 |
| **TransportChannel** | Network | Source/Engine/Network/Transport.hpp | 63 |
| **TransportPeer** | Network | Source/Engine/Network/Transport.hpp | 85 |
| **TransportStats** | Network | Source/Engine/Network/Transport.hpp | 69 |

### Engine/Physics (134)

| Symbol | Kind | Header | Line |
|---|---|---|---|
| **Body** | Physics | Source/Engine/Physics/DodPhysicsBackend.hpp | 57 |
| **BodyRecord** | Physics | Source/Engine/Physics/Physics.hpp | 284 |
| **BodyType** | Physics | Source/Engine/Physics/Physics.hpp | 44 |
| **ChainBreakEvent** | Physics | Source/Engine/Physics/PhysicsJoints.hpp | 314 |
| **ChainError** | Physics | Source/Engine/Physics/PhysicsJoints.hpp | 146 |
| **ChainRuntime** | Physics | Source/Engine/Physics/PhysicsJoints.hpp | 618 |
| **ClothComponent** | Physics | Source/Engine/Physics/Cloth.hpp | 31 |
| **ClothDesc** | Physics | Source/Engine/Physics/Cloth.hpp | 63 |
| **ClothFlags** | Physics | Source/Engine/ | 20 |

| | | | |
|---|---|---|---|
| | | Physics/Cloth.hpp | |
| **ClothHandle** | Physics | Source/Engine/ Physics/Cloth.hpp | 46 |
| **ClothInfo** | Physics | Source/Engine/ Physics/Cloth.hpp | 99 |
| **ClothRenderSystem** | Physics | Source/Engine/ Physics/ ClothRenderSystem.hpp | 15 |
| **ClothSystem** | Physics | Source/Engine/ Physics/Cloth.hpp | 110 |
| **Collider2D** | Physics | Source/Engine/ Physics/Physics.hpp | 81 |
| **CollisionFilterMatrix** | Physics | Source/Engine/ Physics/ CollisionFilter.hpp | 48 |
| **CollisionLayer** | Physics | Source/Engine/ Physics/ CollisionFilter.hpp | 15 |
| **ConnectionRuntime** | Physics | Source/Engine/ Physics/ PhysicsJoints.hpp | 590 |
| **DodPhysicsBackend** | Physics | Source/Engine/ Physics/ DodPhysicsBackend.hpp | 17 |
| **DodPhysicsBackend** | Physics | Source/Engine/ Physics/Physics.hpp | 20 |
| **FluidDesc** | Physics | Source/Engine/ Physics/Fluid.hpp | 114 |
| **FluidInteractorComponent** | Physics | Source/Engine/ Physics/Fluid.hpp | 208 |
| **FluidWaveSystem** | Physics | Source/Engine/ Physics/Fluid.hpp | 219 |
| **GerstnerField** | Physics | Source/Engine/ Physics/Fluid.hpp | 49 |
| **GerstnerSample** | Physics | Source/Engine/ Physics/Fluid.hpp | 39 |
| **GerstnerWave** | Physics | Source/Engine/ Physics/Fluid.hpp | 25 |
| **GravityBodyComponent** | Physics | Source/Engine/ Physics/Gravity.hpp | 77 |
| **GravityBodyMode** | Physics | Source/Engine/ | 33 |

| | | | |
|---|---|---|---|
| | | Physics/Gravity.hpp | |
| **GravityBodyShape** | Physics | Source/Engine/ Physics/Gravity.hpp | 39 |
| **GravityDirection** | Physics | Source/Engine/ Physics/Gravity.hpp | 15 |
| **GravityFalloff** | Physics | Source/Engine/ Physics/Gravity.hpp | 25 |
| **GravitySystem** | Physics | Source/Engine/ Physics/Gravity.hpp | 120 |
| **GridEntry** | Physics | Source/Engine/ Physics/ DodPhysicsBackend.hpp | 90 |
| **JointBreakReason** | Physics | Source/Engine/ Physics/ PhysicsJoints.hpp | 72 |
| **JointChainComponent** | Physics | Source/Engine/ Physics/ PhysicsJoints.hpp | 378 |
| **JointChainDesc** | Physics | Source/Engine/ Physics/ PhysicsJoints.hpp | 187 |
| **JointChainFlags** | Physics | Source/Engine/ Physics/ PhysicsJoints.hpp | 91 |
| **JointChainHandle** | Physics | Source/Engine/ Physics/ PhysicsJoints.hpp | 250 |
| **JointChainInfo** | Physics | Source/Engine/ Physics/ PhysicsJoints.hpp | 429 |
| **JointChainKind** | Physics | Source/Engine/ Physics/ PhysicsJoints.hpp | 54 |
| **JointChainSection** | Physics | Source/Engine/ Physics/ PhysicsJoints.hpp | 119 |
| **JointConnectionFlags** | Physics | Source/Engine/ Physics/ PhysicsJoints.hpp | 80 |
| **JointConnectionHandle** | Physics | Source/Engine/ Physics/ PhysicsJoints.hpp | 268 |
| **JointConnectionInfo** | Physics | Source/Engine/ | 287 |

| | | | |
|---|---|---|---|
| | | Physics/ PhysicsJoints.hpp | |
| **JointConnectionKind** | Physics | Source/Engine/ Physics/ PhysicsJoints.hpp | 64 |
| **JointConnectionParams** | Physics | Source/Engine/ Physics/ PhysicsJoints.hpp | 559 |
| **JointLinkComponent** | Physics | Source/Engine/ Physics/ PhysicsJoints.hpp | 33 |
| **JointLinkFlags** | Physics | Source/Engine/ Physics/ PhysicsJoints.hpp | 22 |
| **JointTieDesc** | Physics | Source/Engine/ Physics/ PhysicsJoints.hpp | 328 |
| **JointTieSave** | Physics | Source/Engine/ Physics/ PhysicsJoints.hpp | 351 |
| **LevelGravityComponent** | Physics | Source/Engine/ Physics/Gravity.hpp | 53 |
| **ParticleEmitterComponent** | Physics | Source/Engine/ Physics/Particles.hpp | 30 |
| **ParticleEmitterFlags** | Physics | Source/Engine/ Physics/Particles.hpp | 14 |
| **ParticleEmitterGpu** | Physics | Source/Engine/ Physics/Particles.hpp | 65 |
| **ParticleSeedPush** | Physics | Source/Engine/ Physics/Particles.hpp | 88 |
| **ParticleStateGpu** | Physics | Source/Engine/ Physics/Particles.hpp | 96 |
| **PhysicsBackendKind** | Physics | Source/Engine/ Physics/Physics.hpp | 27 |
| **PhysicsBodyRemapEntry** | Physics | Source/Engine/ Physics/ SnapshotRemap.hpp | 17 |
| **PhysicsBodyRemapTable** | Physics | Source/Engine/ Physics/ SnapshotRemap.hpp | 24 |
| **PhysicsCapabilities** | Physics | Source/Engine/ Physics/Physics.hpp | 34 |

| | | | |
|---|---|---|---|
| **PhysicsContactEvent** | Physics | Source/Engine/ Physics/Physics.hpp | 109 |
| **PhysicsDesc** | Physics | Source/Engine/ Physics/Physics.hpp | 145 |
| **PhysicsEventType** | Physics | Source/Engine/ Physics/Physics.hpp | 102 |
| **PhysicsJointSystem** | Physics | Source/Engine/ Physics/ PhysicsJoints.hpp | 444 |
| **PhysicsRayHit** | Physics | Source/Engine/ Physics/Physics.hpp | 120 |
| **PhysicsSystem** | Physics | Source/Engine/ Physics/Physics.hpp | 159 |
| **PhysicsSystem** | Physics | Source/Engine/ Physics/ TransportGroups.hpp | 13 |
| **Projectile2D** | Physics | Source/Engine/ Physics/Physics.hpp | 134 |
| **ProjectileHitEvent** | Physics | Source/Engine/ Physics/ ProjectileSystem.hpp | 12 |
| **ProjectileSystem** | Physics | Source/Engine/ Physics/ ProjectileSystem.hpp | 24 |
| **RigidBody2D** | Physics | Source/Engine/ Physics/Physics.hpp | 64 |
| **RigidBodyFlags** | Physics | Source/Engine/ Physics/Physics.hpp | 51 |
| **Runtime** | Physics | Source/Engine/ Physics/Cloth.hpp | 156 |
| **SdfAtlasImage** | Physics | Source/Engine/ Physics/SdfAtlas.hpp | 18 |
| **SdfBrickGpu** | Physics | Source/Engine/ Physics/ SdfBrickMap.hpp | 48 |
| **SdfBrickHeader** | Physics | Source/Engine/ Physics/ SdfBrickMap.hpp | 32 |
| **SdfBrickHeader** | Physics | Source/Engine/ Physics/ SdfCollision.hpp | 103 |
| **SdfBrickMap** | Physics | Source/Engine/ Physics/ | 79 |

| | | | |
|---|---|---|---|
| | | SdfBrickMap.hpp | |
| **SdfBrickMap** | Physics | Source/Engine/ Physics/ SdfCollision.hpp | 102 |
| **SdfBrickMapDesc** | Physics | Source/Engine/ Physics/ SdfBrickMap.hpp | 63 |
| **SdfBrickState** | Physics | Source/Engine/ Physics/ SdfBrickMap.hpp | 24 |
| **SdfCarveOp** | Physics | Source/Engine/ Physics/ SdfDestructible.hpp | 25 |
| **SdfCarveReplayContext** | Physics | Source/Engine/ Physics/ SdfDestructionCommands.hpp | 37 |
| **SdfCarveShape** | Physics | Source/Engine/ Physics/ SdfDestructible.hpp | 17 |
| **SdfCollisionDesc** | Physics | Source/Engine/ Physics/ SdfCollision.hpp | 45 |
| **SdfCollisionSystem** | Physics | Source/Engine/ Physics/ SdfCollision.hpp | 105 |
| **SdfComposeLayer** | Physics | Source/Engine/ Physics/ SdfComposer.hpp | 25 |
| **SdfComposeOp** | Physics | Source/Engine/ Physics/ SdfComposer.hpp | 16 |
| **SdfComposer** | Physics | Source/Engine/ Physics/ SdfComposer.hpp | 37 |
| **SdfComposerSession** | Physics | Source/Engine/ Physics/ SdfComposerSession.hpp | 15 |
| **SdfConnection** | Physics | Source/Engine/ Physics/ SdfDamage.hpp | 66 |
| **SdfContact** | Physics | Source/Engine/ Physics/ SdfCollision.hpp | 62 |

| | | | |
|---|---|---|---|
| **SdfContactManifold** | Physics | Source/Engine/ Physics/ SdfCollision.hpp | 93 |
| **SdfContactPoint** | Physics | Source/Engine/ Physics/ SdfCollision.hpp | 82 |
| **SdfDamageModel** | Physics | Source/Engine/ Physics/ SdfDamage.hpp | 188 |
| **SdfDebrisPiece** | Physics | Source/Engine/ Physics/SdfDebris.hpp | 19 |
| **SdfDebrisSettings** | Physics | Source/Engine/ Physics/SdfDebris.hpp | 30 |
| **SdfDestructible** | Physics | Source/Engine/ Physics/ SdfDestructible.hpp | 56 |
| **SdfDestructible** | Physics | Source/Engine/ Physics/SdfWorld.hpp | 16 |
| **SdfDestructibleDesc** | Physics | Source/Engine/ Physics/ SdfDestructible.hpp | 36 |
| **SdfField** | Physics | Source/Engine/ Physics/ SdfCollision.hpp | 19 |
| **SdfGiAsset** | Physics | Source/Engine/ Physics/ SdfGiAsset.hpp | 65 |
| **SdfGiAssetHeader** | Physics | Source/Engine/ Physics/ SdfGiAsset.hpp | 45 |
| **SdfGiBaked** | Physics | Source/Engine/ Physics/ SdfGiBake.hpp | 44 |
| **SdfGiBakedProbe** | Physics | Source/Engine/ Physics/ SdfGiBake.hpp | 32 |
| **SdfGiBakeSettings** | Physics | Source/Engine/ Physics/ SdfGiBake.hpp | 16 |
| **SdfGiProbe** | Physics | Source/Engine/ Physics/SdfGi.hpp | 21 |
| **SdfGiVolume** | Physics | Source/Engine/ Physics/SdfGi.hpp | 40 |
| **SdfImpact** | Physics | Source/Engine/ | 85 |

| | | | |
|---|---|---|---|
| | | Physics/ SdfDamage.hpp | |
| **SdfImpactResult** | Physics | Source/Engine/ Physics/ SdfDamage.hpp | 100 |
| **SdfMaterialProfile** | Physics | Source/Engine/ Physics/ SdfDamage.hpp | 25 |
| **SdfPart** | Physics | Source/Engine/ Physics/ SdfDamage.hpp | 47 |
| **SdfPrimitiveInfo** | Physics | Source/Engine/ Physics/ SdfPrimitives.hpp | 137 |
| **SdfShape** | Physics | Source/Engine/ Physics/ SdfPrimitives.hpp | 82 |
| **SdfShapeComponent** | Physics | Source/Engine/ Physics/ SdfPrimitives.hpp | 127 |
| **SdfShapeType** | Physics | Source/Engine/ Physics/ SdfPrimitives.hpp | 16 |
| **SdfSmokeDesc** | Physics | Source/Engine/ Physics/ SdfSmoke.hpp | 15 |
| **SdfSmokeField** | Physics | Source/Engine/ Physics/ SdfSmoke.hpp | 32 |
| **SdfVolumeAsset** | Physics | Source/Engine/ Physics/ SdfVolumeAsset.hpp | 52 |
| **SdfVolumeHeader** | Physics | Source/Engine/ Physics/ SdfVolumeAsset.hpp | 26 |
| **SdfWorld** | Physics | Source/Engine/ Physics/SdfWorld.hpp | 60 |
| **SdfWorldBox** | Physics | Source/Engine/ Physics/SdfWorld.hpp | 45 |
| **SdfWorldCircle** | Physics | Source/Engine/ Physics/SdfWorld.hpp | 51 |
| **SdfWorldDesc** | Physics | Source/Engine/ Physics/SdfWorld.hpp | 31 |
| **SdfWorldImprint** | Physics | Source/Engine/ | 20 |

| | | | |
|---|---|---|---|
| | | Physics/SdfWorld.hpp | |
| **ShallowWaterGrid** | Physics | Source/Engine/ Physics/Fluid.hpp | 134 |
| **Storage** | Physics | Source/Engine/ Physics/Cloth.hpp | 155 |
| **Storage** | Physics | Source/Engine/ Physics/ PhysicsJoints.hpp | 642 |
| **TilemapComponent** | Physics | Source/Engine/ Physics/SdfWorld.hpp | 15 |
| **Tracked** | Physics | Source/Engine/ Physics/Fluid.hpp | 248 |
| **TransportCapabilities** | Physics | Source/Engine/ Physics/ TransportGroups.hpp | 31 |
| **TransportGroupState** | Physics | Source/Engine/ Physics/ TransportGroups.hpp | 41 |
| **TransportGroupSystem** | Physics | Source/Engine/ Physics/ TransportGroups.hpp | 63 |
| **WaterView** | Physics | Source/Engine/ Physics/Fluid.hpp | 85 |
| **WheelSystem** | Physics | Source/Engine/ Physics/ VehicleWheels.hpp | 16 |

### Engine/Platform (21)

| Symbol | Kind | Header | Line |
|---|---|---|---|
| **AchievementFlags** | Platform | Source/Engine/ Platform/ PlatformSystems.hpp | 95 |
| **AchievementRequest** | Platform | Source/Engine/ Platform/ PlatformSystems.hpp | 104 |
| **CloudSaveComponent** | Platform | Source/Engine/ Platform/ PlatformSystems.hpp | 124 |
| **CloudSaveFlags** | Platform | Source/Engine/ Platform/ PlatformSystems.hpp | 115 |
| **EgsStoreSystem** | Platform | Source/Engine/ Platform/ | 178 |

| | | | |
|---|---|---|---|
| | | PlatformSystems.hpp | |
| **GogAchievementSystem** | Platform | Source/Engine/ Platform/ PlatformSystems.hpp | 224 |
| **GogStorageSystem** | Platform | Source/Engine/ Platform/ PlatformSystems.hpp | 258 |
| **PlatformAccountComponent** | Platform | Source/Engine/ Platform/ PlatformSystems.hpp | 137 |
| **PlatformCommand** | Platform | Source/Engine/ Platform/ PlatformService.hpp | 35 |
| **PlatformCommandLog** | Platform | Source/Engine/ Platform/ PlatformSystems.hpp | 46 |
| **PlatformCommandType** | Platform | Source/Engine/ Platform/ PlatformService.hpp | 24 |
| **PlatformLogEvent** | Platform | Source/Engine/ Platform/ PlatformSystems.hpp | 35 |
| **PlatformLogType** | Platform | Source/Engine/ Platform/ PlatformSystems.hpp | 26 |
| **PlatformService** | Platform | Source/Engine/ Platform/ PlatformService.hpp | 76 |
| **PlatformServiceCallbacks** | Platform | Source/Engine/ Platform/ PlatformService.hpp | 51 |
| **PlatformServiceDesc** | Platform | Source/Engine/ Platform/ PlatformService.hpp | 71 |
| **PlatformServiceStats** | Platform | Source/Engine/ Platform/ PlatformService.hpp | 59 |
| **PlatformState** | Platform | Source/Engine/ Platform/ PlatformService.hpp | 132 |
| **StagedSave** | Platform | Source/Engine/ Platform/ PlatformSystems.hpp | 204 |
| **StagedSave** | Platform | Source/Engine/ Platform/ | 291 |

| | | | |
|---|---|---|---|
| | | PlatformSystems.hpp | |
| **SteamAchievementSystem** | Platform | Source/Engine/ Platform/ PlatformSystems.hpp | 148 |

### Engine/RHI (161)

| Symbol | Kind | Header | Line |
|---|---|---|---|
| **Api** | RHI | Source/Engine/RHI/ Vulkan/ VulkanLoader.hpp | 122 |
| **Backend** | RHI | Source/Engine/RHI/ RHI.hpp | 19 |
| **BackendCapabilities** | RHI | Source/Engine/RHI/ UpscalerCapabilities.hpp | 28 |
| **BackendSelection** | RHI | Source/Engine/RHI/ UpscalerBackend.hpp | 28 |
| **CameraData** | RHI | Source/Engine/RHI/ RenderItem.hpp | 240 |
| **CameraDistortionFlags** | RHI | Source/Engine/RHI/ CameraStack.hpp | 30 |
| **CameraDistortionSettings** | RHI | Source/Engine/RHI/ CameraStack.hpp | 40 |
| **CameraStackDesc** | RHI | Source/Engine/RHI/ CameraStack.hpp | 56 |
| **CameraStackFlags** | RHI | Source/Engine/RHI/ CameraStack.hpp | 17 |
| **CameraStackSystem** | RHI | Source/Engine/RHI/ CameraStack.hpp | 81 |
| **CameraStackSystem** | RHI | Source/Engine/RHI/ RenderGraph.hpp | 16 |
| **CameraStackSystem** | RHI | Source/Engine/RHI/ RenderPasses.hpp | 12 |
| **ChangeMaskRenderExtract** | RHI | Source/Engine/RHI/ ChangeMaskExtract.hpp | 33 |
| **ClusterGridConstants** | RHI | Source/Engine/RHI/ GpuLighting.hpp | 46 |
| **ClusterHeader** | RHI | Source/Engine/RHI/ GpuLighting.hpp | 36 |
| **ColorGradingConsta** | RHI | Source/Engine/RHI/ | 128 |

| | | | |
|---|---|---|---|
| **nts** | | RenderPasses.hpp | |
| **ColorGradingPass** | RHI | Source/Engine/RHI/RenderPasses.hpp | 136 |
| **ColorGradingSettings** | RHI | Source/Engine/RHI/RenderPasses.hpp | 116 |
| **CookedMaterialView** | RHI | Source/Engine/RHI/MaterialAsset.hpp | 152 |
| **CustomFrameGenerator** | RHI | Source/Engine/RHI/CustomFrameGenerator.hpp | 10 |
| **DeviceDesc** | RHI | Source/Engine/RHI/RHI.hpp | 49 |
| **DeviceInfo** | RHI | Source/Engine/RHI/RHI.hpp | 112 |
| **DirtyRange** | RHI | Source/Engine/RHI/RenderItem.hpp | 221 |
| **DlssAdapter** | RHI | Source/Engine/RHI/DlssAdapter.hpp | 33 |
| **DlssQualityMode** | RHI | Source/Engine/RHI/DlssAdapter.hpp | 9 |
| **DlssRuntimeAvailability** | RHI | Source/Engine/RHI/DlssRuntime.hpp | 9 |
| **DlssRuntimeProbe** | RHI | Source/Engine/RHI/DlssRuntimeProbe.hpp | 14 |
| **DrawBatch** | RHI | Source/Engine/RHI/RenderItem.hpp | 201 |
| **DrawIndexedIndirectCommand** | RHI | Source/Engine/RHI/GpuVisibility.hpp | 15 |
| **DynamicResolution** | RHI | Source/Engine/RHI/DynamicResolution.hpp | 19 |
| **DynamicResolutionSettings** | RHI | Source/Engine/RHI/DynamicResolution.hpp | 9 |
| **Entry** | RHI | Source/Engine/RHI/MaterialPipelineCache.hpp | 74 |
| **ExportStatus** | RHI | Source/Engine/RHI/FrameExporter.hpp | 100 |
| **Extent2D** | RHI | Source/Engine/RHI/RHI.hpp | 40 |

| | | | |
|---|---|---|---|
| **ExtractStats** | RHI | Source/Engine/RHI/ChangeMaskExtract.hpp | 21 |
| **FidelityFxRuntimeAvailability** | RHI | Source/Engine/RHI/FidelityFxRuntime.hpp | 25 |
| **FrameAccessibility** | RHI | Source/Engine/RHI/RenderItem.hpp | 262 |
| **FrameAccessibilityFlags** | RHI | Source/Engine/RHI/RenderItem.hpp | 249 |
| **FrameExportDesc** | RHI | Source/Engine/RHI/FrameExporter.hpp | 53 |
| **FrameExporter** | RHI | Source/Engine/RHI/FrameExporter.hpp | 112 |
| **FrameGenBackend** | RHI | Source/Engine/RHI/UpscalerBackend.hpp | 19 |
| **FrameGenerationInput** | RHI | Source/Engine/RHI/FrameGeneration.hpp | 10 |
| **FrameGenerationPolicy** | RHI | Source/Engine/RHI/FrameGenerationPolicy.hpp | 19 |
| **FrameGenerationStatus** | RHI | Source/Engine/RHI/FrameGenerationPolicy.hpp | 9 |
| **FramePacingConfig** | RHI | Source/Engine/RHI/FramePacing.hpp | 10 |
| **FramePacingState** | RHI | Source/Engine/RHI/FramePacing.hpp | 17 |
| **FramePacket** | RHI | Source/Engine/RHI/RenderItem.hpp | 372 |
| **FrameSink** | RHI | Source/Engine/RHI/FrameExporter.hpp | 85 |
| **FrameStats** | RHI | Source/Engine/RHI/RHI.hpp | 257 |
| **Fsr2Adapter** | RHI | Source/Engine/RHI/Fsr2Adapter.hpp | 33 |
| **Fsr2Pass** | RHI | Source/Engine/RHI/Fsr2Pass.hpp | 10 |
| **Fsr2QualityMode** | RHI | Source/Engine/RHI/Fsr2Adapter.hpp | 9 |
| **Fsr3FrameGenerator** | RHI | Source/Engine/RHI/Fsr3FrameGenerator.hpp | 10 |

| | | | |
|---|---|---|---|
| **GpuCullingConstants** | RHI | Source/Engine/RHI/GpuVisibility.hpp | 28 |
| **GpuGiProbe** | RHI | Source/Engine/RHI/GpuLighting.hpp | 67 |
| **GpuGiVolumeHeader** | RHI | Source/Engine/RHI/GpuLighting.hpp | 57 |
| **GpuLight** | RHI | Source/Engine/RHI/GpuLighting.hpp | 18 |
| **GpuVendor** | RHI | Source/Engine/RHI/UpscalerCapabilities.hpp | 19 |
| **HashEntry** | RHI | Source/Engine/RHI/VirtualTextureSystem.hpp | 197 |
| **IFrameGenerator** | RHI | Source/Engine/RHI/FrameGeneration.hpp | 27 |
| **ImageLayout** | RHI | Source/Engine/RHI/RHI.hpp | 218 |
| **ITemporalUpscaler** | RHI | Source/Engine/RHI/TemporalUpscaler.hpp | 28 |
| **KeySorter** | RHI | Source/Engine/RHI/Sort.hpp | 14 |
| **LookupEntry** | RHI | Source/Engine/RHI/ChangeMaskExtract.hpp | 255 |
| **MaterialAssetError** | RHI | Source/Engine/RHI/MaterialAsset.hpp | 42 |
| **MaterialCompileOptions** | RHI | Source/Engine/RHI/MaterialGraphCompiler.hpp | 27 |
| **MaterialContract** | RHI | Source/Engine/RHI/MaterialAsset.hpp | 83 |
| **MaterialDomain** | RHI | Source/Engine/RHI/MaterialGraphCompiler.hpp | 21 |
| **MaterialGraph** | RHI | Source/Engine/RHI/MaterialGraph.hpp | 555 |
| **MaterialGraphCompiler** | RHI | Source/Engine/RHI/MaterialGraphCompiler.hpp | 58 |
| **MaterialGraphRequirements** | RHI | Source/Engine/RHI/MaterialGraph.hpp | 542 |

| | | | |
|---|---|---|---|
| **MaterialNode** | RHI | Source/Engine/RHI/MaterialGraph.hpp | 117 |
| **MaterialNodeFlags** | RHI | Source/Engine/RHI/MaterialGraph.hpp | 111 |
| **MaterialNodeKind** | RHI | Source/Engine/RHI/MaterialGraph.hpp | 29 |
| **MaterialParam** | RHI | Source/Engine/RHI/MaterialGraph.hpp | 99 |
| **MaterialParamKind** | RHI | Source/Engine/RHI/MaterialGraph.hpp | 88 |
| **MaterialPin** | RHI | Source/Engine/RHI/MaterialGraph.hpp | 129 |
| **MaterialPipelineCache** | RHI | Source/Engine/RHI/MaterialPipelineCache.hpp | 38 |
| **MaterialPipelineCacheStats** | RHI | Source/Engine/RHI/MaterialPipelineCache.hpp | 18 |
| **MaterialShaderProgram** | RHI | Source/Engine/RHI/MaterialGraphCompiler.hpp | 39 |
| **MaterialValueType** | RHI | Source/Engine/RHI/MaterialGraph.hpp | 78 |
| **MeshDesc** | RHI | Source/Engine/RHI/Mesh.hpp | 102 |
| **MeshDrawData** | RHI | Source/Engine/RHI/Mesh.hpp | 70 |
| **MeshDrawFlags** | RHI | Source/Engine/RHI/Mesh.hpp | 54 |
| **MeshHandle** | RHI | Source/Engine/RHI/Mesh.hpp | 87 |
| **MeshItemFlags** | RHI | Source/Engine/RHI/Mesh.hpp | 62 |
| **MeshRenderItem** | RHI | Source/Engine/RHI/Mesh.hpp | 114 |
| **MeshSkinRange** | RHI | Source/Engine/RHI/Mesh.hpp | 46 |
| **MeshVertex** | RHI | Source/Engine/RHI/Mesh.hpp | 17 |
| **MotionVectorItem** | RHI | Source/Engine/RHI/RenderItem.hpp | 354 |
| **NativeDeviceHandle** | RHI | Source/Engine/RHI/ | 708 |

| | | | |
|---|---|---|---|
| **s** | | RHI.hpp | |
| **NativeTextureView** | RHI | Source/Engine/RHI/RHI.hpp | 224 |
| **OitPass** | RHI | Source/Engine/RHI/OitPass.hpp | 11 |
| **PageSlot** | RHI | Source/Engine/RHI/VirtualTextureSystem.hpp | 188 |
| **PlatformKind** | RHI | Source/Engine/RHI/UpscalerCapabilities.hpp | 11 |
| **PostFxConstants** | RHI | Source/Engine/RHI/RenderPasses.hpp | 97 |
| **PostFxFlags** | RHI | Source/Engine/RHI/PostProcess.hpp | 10 |
| **PostFxPass** | RHI | Source/Engine/RHI/RenderPasses.hpp | 157 |
| **PostFxSettings** | RHI | Source/Engine/RHI/PostProcess.hpp | 30 |
| **RenderBlendMode** | RHI | Source/Engine/RHI/RHI.hpp | 190 |
| **RenderCommandRecord** | RHI | Source/Engine/RHI/RenderGraph.hpp | 52 |
| **RenderFlags** | RHI | Source/Engine/RHI/RenderItem.hpp | 42 |
| **RenderGraph** | RHI | Source/Engine/RHI/RenderGraph.hpp | 119 |
| **RenderGraphContext** | RHI | Source/Engine/RHI/RenderGraph.hpp | 69 |
| **RenderGraphPass** | RHI | Source/Engine/RHI/RenderGraph.hpp | 106 |
| **RenderItem** | RHI | Source/Engine/RHI/RenderItem.hpp | 90 |
| **RenderPassDesc** | RHI | Source/Engine/RHI/RenderGraph.hpp | 94 |
| **RenderPassKind** | RHI | Source/Engine/RHI/RenderGraph.hpp | 26 |
| **RenderResourceKind** | RHI | Source/Engine/RHI/RenderGraph.hpp | 33 |
| **RenderTargetDesc** | RHI | Source/Engine/RHI/RHI.hpp | 197 |
| **RenderTargetHandle** | RHI | Source/Engine/RHI/ | 207 |

| | | | |
|---|---|---|---|
| | | RHI.hpp | |
| **RHI** | RHI | Source/Engine/RHI/RHI.hpp | 328 |
| **SdfLightingFrame** | RHI | Source/Engine/RHI/RenderItem.hpp | 310 |
| **SdfLightingOccluder** | RHI | Source/Engine/RHI/RenderItem.hpp | 302 |
| **SdfShadowConstants** | RHI | Source/Engine/RHI/RenderPasses.hpp | 37 |
| **SdfShadowDesc** | RHI | Source/Engine/RHI/RenderPasses.hpp | 18 |
| **SdfShadowPass** | RHI | Source/Engine/RHI/RenderPasses.hpp | 66 |
| **SequenceFooter** | RHI | Source/Engine/RHI/FrameExporter.hpp | 42 |
| **SequenceHeader** | RHI | Source/Engine/RHI/FrameExporter.hpp | 31 |
| **ShaderPipelineDesc** | RHI | Source/Engine/RHI/RHI.hpp | 167 |
| **ShaderPipelineDomain** | RHI | Source/Engine/RHI/RHI.hpp | 161 |
| **ShaderPipelineHandle** | RHI | Source/Engine/RHI/RHI.hpp | 178 |
| **SkinnedVertex** | RHI | Source/Engine/RHI/Mesh.hpp | 30 |
| **Slot** | RHI | Source/Engine/RHI/CameraStack.hpp | 142 |
| **SpatialUpscaleMode** | RHI | Source/Engine/RHI/RHI.hpp | 90 |
| **StaticBakeCache** | RHI | Source/Engine/RHI/StaticBake.hpp | 58 |
| **StaticBakeRenderer** | RHI | Source/Engine/RHI/StaticBakeRenderer.hpp | 14 |
| **StaticBakeSettings** | RHI | Source/Engine/RHI/StaticBake.hpp | 10 |
| **StaticBakeStats** | RHI | Source/Engine/RHI/StaticBake.hpp | 47 |
| **StaticBakeTileKey** | RHI | Source/Engine/RHI/StaticBake.hpp | 17 |
| **TemporalResolvePass** | RHI | Source/Engine/RHI/TemporalResolvePass | 11 |

| | | | |
|---|---|---|---|
| | | .hpp | |
| **TemporalUpscaleInput** | RHI | Source/Engine/RHI/TemporalUpscaler.hpp | 11 |
| **TextureArrayDesc** | RHI | Source/Engine/RHI/RHI.hpp | 146 |
| **TextureArrayHandle** | RHI | Source/Engine/RHI/RHI.hpp | 304 |
| **Tile** | RHI | Source/Engine/RHI/StaticBake.hpp | 90 |
| **TintEntry** | RHI | Source/Engine/RHI/ViewportPresenter.hpp | 81 |
| **TransientRing** | RHI | Source/Engine/RHI/RingBuffer.hpp | 15 |
| **UiBackendInfo** | RHI | Source/Engine/RHI/RHI.hpp | 234 |
| **UpscalerBackend** | RHI | Source/Engine/RHI/UpscalerBackend.hpp | 9 |
| **UpscalerCaps** | RHI | Source/Engine/RHI/RHI.hpp | 98 |
| **ViewportMode** | RHI | Source/Engine/RHI/ViewportModes.hpp | 15 |
| **ViewportModeDescriptor** | RHI | Source/Engine/RHI/ViewportModes.hpp | 46 |
| **ViewportModeLegend** | RHI | Source/Engine/RHI/ViewportModes.hpp | 37 |
| **ViewportPresenter** | RHI | Source/Engine/RHI/ViewportPresenter.hpp | 29 |
| **ViewportPresenterStats** | RHI | Source/Engine/RHI/ViewportPresenter.hpp | 17 |
| **VirtualFileSystem** | RHI | Source/Engine/RHI/FrameExporter.hpp | 15 |
| **VirtualFileSystem** | RHI | Source/Engine/RHI/VirtualTextureSystem.hpp | 16 |
| **VirtualTextureAddress** | RHI | Source/Engine/RHI/VirtualTextureSystem.hpp | 68 |
| **VirtualTextureCamera** | RHI | Source/Engine/RHI/VirtualTextureSystem. | 59 |

| | | | |
|---|---|---|---|
| | | hpp | |
| **VirtualTextureDesc** | RHI | Source/Engine/RHI/VirtualTextureSystem.hpp | 33 |
| **VirtualTextureHandle** | RHI | Source/Engine/RHI/RenderItem.hpp | 279 |
| **VirtualTexturePageLocation** | RHI | Source/Engine/RHI/VirtualTextureGpu.hpp | 11 |
| **VirtualTextureResourceDesc** | RHI | Source/Engine/RHI/RHI.hpp | 316 |
| **VirtualTextureRhiTarget** | RHI | Source/Engine/RHI/VirtualTextureGpu.hpp | 118 |
| **VirtualTextureSample** | RHI | Source/Engine/RHI/VirtualTextureGpu.hpp | 58 |
| **VirtualTextureStats** | RHI | Source/Engine/RHI/VirtualTextureSystem.hpp | 45 |
| **VirtualTextureSystem** | RHI | Source/Engine/RHI/VirtualTextureSystem.hpp | 111 |
| **VirtualTextureTableUpdate** | RHI | Source/Engine/RHI/VirtualTextureSystem.hpp | 101 |
| **VirtualTextureTileId** | RHI | Source/Engine/RHI/VirtualTextureSystem.hpp | 92 |
| **VirtualTextureTileUpload** | RHI | Source/Engine/RHI/VirtualTextureSystem.hpp | 77 |
| **VisibleSprite** | RHI | Source/Engine/RHI/ViewportPresenter.hpp | 87 |

### Engine/Script (67)

| Symbol | Kind | Header | Line |
|---|---|---|---|
| **AotBuilder** | Script | Source/Engine/Script/AotBuilder.hpp | 71 |
| **AotBuildOptions** | Script | Source/Engine/Script/AotBuilder.hpp | 43 |
| **AotBuildResult** | Script | Source/Engine/Script/AotBuilder.hpp | 60 |
| **AotBuildState** | Script | Source/Engine/ | 19 |

| | | | |
|---|---|---|---|
| | | Script/AotBuilder.hpp | |
| **AotGraphTranspileOptions** | Script | Source/Engine/Script/AotGraphCompiler.hpp | 13 |
| **AotHost** | Script | Source/Engine/Script/AotHost.hpp | 32 |
| **AotHost** | Script | Source/Engine/Script/ScriptSystem.hpp | 23 |
| **AotModule** | Script | Source/Engine/Script/AotModule.hpp | 22 |
| **AotProgramRef** | Script | Source/Engine/Script/AotHost.hpp | 22 |
| **AotTranspileOptions** | Script | Source/Engine/Script/AotTranspiler.hpp | 12 |
| **BoundProgram** | Script | Source/Engine/Script/EcsBridge.hpp | 101 |
| **CameraStackSystem** | Script | Source/Engine/Script/ScriptSystem.hpp | 18 |
| **CameraStackSystem** | Script | Source/Engine/Script/Vm.hpp | 18 |
| **Code** | Script | Source/Engine/Script/Vm.hpp | 32 |
| **CompiledDebug** | Script | Source/Engine/Script/Bytecode.hpp | 488 |
| **CompiledProgram** | Script | Source/Engine/Script/Bytecode.hpp | 503 |
| **ComponentAccessor** | Script | Source/Engine/Script/EcsBridge.hpp | 17 |
| **ComponentBinding** | Script | Source/Engine/Script/Bytecode.hpp | 432 |
| **Context** | Script | Source/Engine/Script/AotAbi.hpp | 112 |
| **DebugField** | Script | Source/Engine/Script/ScriptDebug.hpp | 123 |
| **DebugFrame** | Script | Source/Engine/Script/ScriptDebug.hpp | 103 |
| **DebugSectionHeade** | Script | Source/Engine/ | 181 |

| | | | |
|---|---|---|---|
| **r** | | Script/Bytecode.hpp | |
| **DebugSpan** | Script | Source/Engine/ Script/Bytecode.hpp | 159 |
| **DebugSpanFlags** | Script | Source/Engine/ Script/Bytecode.hpp | 150 |
| **DebugVariable** | Script | Source/Engine/ Script/Bytecode.hpp | 172 |
| **EcsBridge** | Script | Source/Engine/ Script/EcsBridge.hpp | 26 |
| **FieldBinding** | Script | Source/Engine/ Script/Bytecode.hpp | 442 |
| **FunctionEntry** | Script | Source/Engine/ Script/Bytecode.hpp | 455 |
| **HostApi** | Script | Source/Engine/ Script/AotAbi.hpp | 54 |
| **Instruction** | Script | Source/Engine/ Script/Bytecode.hpp | 412 |
| **LogicCompareOp** | Script | Source/Engine/ Script/ GraphCompiler.hpp | 22 |
| **LogicCompileOptions** | Script | Source/Engine/ Script/ GraphCompiler.hpp | 741 |
| **LogicCompileResult** | Script | Source/Engine/ Script/ GraphCompiler.hpp | 748 |
| **LogicFieldBinding** | Script | Source/Engine/ Script/ GraphCompiler.hpp | 90 |
| **LogicGraph** | Script | Source/Engine/ Script/ GraphCompiler.hpp | 350 |
| **LogicLink** | Script | Source/Engine/ Script/ GraphCompiler.hpp | 339 |
| **LogicMathOp** | Script | Source/Engine/ Script/ GraphCompiler.hpp | 56 |
| **LogicNode** | Script | Source/Engine/ Script/ GraphCompiler.hpp | 321 |
| **LogicNodeKind** | Script | Source/Engine/ Script/ | 111 |

| | | | |
|---|---|---|---|
| | | GraphCompiler.hpp | |
| **Module** | Script | Source/Engine/ Script/AotAbi.hpp | 379 |
| **NativeId** | Script | Source/Engine/ Script/Bytecode.hpp | 18 |
| **OpCode** | Script | Source/Engine/ Script/Bytecode.hpp | 230 |
| **PendingField** | Script | Source/Engine/ Script/Bytecode.hpp | 569 |
| **PhysicsSystem** | Script | Source/Engine/ Script/ ScriptSystem.hpp | 17 |
| **PhysicsSystem** | Script | Source/Engine/ Script/Vm.hpp | 17 |
| **PinType** | Script | Source/Engine/ Script/ GraphCompiler.hpp | 306 |
| **ProgramBuilder** | Script | Source/Engine/ Script/Bytecode.hpp | 534 |
| **ProgramHeader** | Script | Source/Engine/ Script/Bytecode.hpp | 465 |
| **ResolvedComponent** | Script | Source/Engine/ Script/EcsBridge.hpp | 93 |
| **ScriptComponent** | Script | Source/Engine/ Script/ ScriptComponent.hpp | 16 |
| **ScriptEvent** | Script | Source/Engine/ Script/Bytecode.hpp | 205 |
| **ScriptRuntime** | Script | Source/Engine/ Script/ ScriptSystem.hpp | 22 |
| **ScriptRuntime** | Script | Source/Engine/ Script/ ScriptSystem.hpp | 26 |
| **ScriptVm** | Script | Source/Engine/ Script/Vm.hpp | 115 |
| **ScriptVm** | Script | Source/Engine/ Script/Vm.hpp | 229 |
| **Slot** | Script | Source/Engine/ Script/AotHost.hpp | 94 |
| **Slot** | Script | Source/Engine/ Script/ ScriptSystem.hpp | 140 |

| | | | |
|---|---|---|---|
| **SourceLocation** | Script | Source/Engine/ Script/ ScriptDebug.hpp | 17 |
| **TextCompileOptions** | Script | Source/Engine/ Script/TextScript.hpp | 14 |
| **TransportGroupSyst em** | Script | Source/Engine/ Script/Vm.hpp | 16 |
| **Vector2D** | Script | Source/Engine/ Script/AotAbi.hpp | 28 |
| **VmContext** | Script | Source/Engine/ Script/Vm.hpp | 94 |
| **VmDebugState** | Script | Source/Engine/ Script/Vm.hpp | 154 |
| **VmFault** | Script | Source/Engine/ Script/Vm.hpp | 30 |
| **VmHalt** | Script | Source/Engine/ Script/Vm.hpp | 127 |
| **VmPauseReason** | Script | Source/Engine/ Script/Vm.hpp | 118 |
| **VmStopInfo** | Script | Source/Engine/ Script/Vm.hpp | 134 |

## Engine/Text (68)

| Symbol | Kind | Header | Line |
|---|---|---|---|
| **AssetSlot** | Text | Source/Engine/Text/ TextStore.hpp | 218 |
| **ChainedShaper** | Text | Source/Engine/Text/ TextShaper.hpp | 133 |
| **CodepointShaper** | Text | Source/Engine/Text/ TextShaper.hpp | 99 |
| **Entry** | Text | Source/Engine/Text/ TextShaper.hpp | 247 |
| **FontCandidate** | Text | Source/Engine/Text/ TextFontStack.hpp | 24 |
| **FontSlot** | Text | Source/Engine/Text/ TextFontStack.hpp | 59 |
| **FormatEntry** | Text | Source/Engine/Text/ TextService.hpp | 583 |
| **FormattedLayoutEnt ry** | Text | Source/Engine/Text/ TextService.hpp | 566 |
| **FormattedLayoutKey** | Text | Source/Engine/Text/ | 556 |

| | | | |
|---|---|---|---|
| | | TextService.hpp | |
| **HarfBuzzShaper** | Text | Source/Engine/Text/TextShaper.hpp | 110 |
| **Impl** | Text | Source/Engine/Text/TextShaper.hpp | 128 |
| **ITextShaper** | Text | Source/Engine/Text/TextShaper.hpp | 89 |
| **LayoutEntry** | Text | Source/Engine/Text/TextService.hpp | 548 |
| **LayoutKey** | Text | Source/Engine/Text/TextService.hpp | 528 |
| **MappedTextAsset** | Text | Source/Engine/Text/TextAssetFile.hpp | 17 |
| **MarkupStackEntry** | Text | Source/Engine/Text/TextMarkup.hpp | 71 |
| **MarkupVariantEntry** | Text | Source/Engine/Text/TextService.hpp | 574 |
| **ScriptBackend** | Text | Source/Engine/Text/TextShapeSystem.hpp | 111 |
| **ScriptShaper** | Text | Source/Engine/Text/TextShaper.hpp | 207 |
| **ShapedGlyph** | Text | Source/Engine/Text/TextShaper.hpp | 56 |
| **ShapedGlyphHit** | Text | Source/Engine/Text/TextShapedLayout.hpp | 153 |
| **ShapedLayoutResult** | Text | Source/Engine/Text/TextShapedLayout.hpp | 26 |
| **ShapedLine** | Text | Source/Engine/Text/TextShapedLayout.hpp | 18 |
| **StyledAsset** | Text | Source/Engine/Text/TextService.hpp | 595 |
| **TextAction** | Text | Source/Engine/Text/TextStyle.hpp | 61 |
| **TextActionKind** | Text | Source/Engine/Text/TextStyle.hpp | 51 |
| **TextAnimationParams** | Text | Source/Engine/Text/TextRender.hpp | 29 |
| **TextAssetBlock** | Text | Source/Engine/Text/ | 34 |

| | | | |
|---|---|---|---|
| | | TextAssetFormat.hpp | |
| **TextAssetHeader** | Text | Source/Engine/Text/ TextAssetFormat.hpp | 20 |
| **TextAssetRef** | Text | Source/Engine/Text/ TextAsset.hpp | 14 |
| **TextAssetStatus** | Text | Source/Engine/Text/ TextAssetFormat.hpp | 63 |
| **TextAssetView** | Text | Source/Engine/Text/ TextAssetFormat.hpp | 42 |
| **TextBlock** | Text | Source/Engine/Text/ TextAsset.hpp | 37 |
| **TextDirection** | Text | Source/Engine/Text/ TextShaper.hpp | 21 |
| **TextFontStack** | Text | Source/Engine/Text/ TextFontStack.hpp | 54 |
| **TextFormatArg** | Text | Source/Engine/Text/ TextFormat.hpp | 45 |
| **TextFormatStatus** | Text | Source/Engine/Text/ TextFormat.hpp | 33 |
| **TextGradientParams** | Text | Source/Engine/Text/ TextRender.hpp | 22 |
| **TextInlineHit** | Text | Source/Engine/Text/ TextLayout.hpp | 204 |
| **TextInlineKind** | Text | Source/Engine/Text/ TextStyle.hpp | 73 |
| **TextInlineObject** | Text | Source/Engine/Text/ TextStyle.hpp | 83 |
| **TextInlineSprite** | Text | Source/Engine/Text/ TextStyle.hpp | 99 |
| **TextLayoutParams** | Text | Source/Engine/Text/ TextLayout.hpp | 54 |
| **TextLayoutResult** | Text | Source/Engine/Text/ TextLayout.hpp | 72 |
| **TextLine** | Text | Source/Engine/Text/ TextLayout.hpp | 22 |
| **TextMarkupStatus** | Text | Source/Engine/Text/ TextMarkup.hpp | 16 |
| **TextRenderEffects** | Text | Source/Engine/Text/ TextRender.hpp | 44 |
| **TextRenderParams** | Text | Source/Engine/Text/ TextRender.hpp | 57 |

| | | | |
|---|---|---|---|
| **TextRenderStats** | Text | Source/Engine/Text/TextRender.hpp | 76 |
| **TextRenderSystemStats** | Text | Source/Engine/Text/TextRenderSystem.hpp | 19 |
| **TextRun** | Text | Source/Engine/Text/TextShaper.hpp | 47 |
| **TextRuntime** | Text | Source/Engine/Text/TextRuntime.hpp | 17 |
| **TextScript** | Text | Source/Engine/Text/TextShaper.hpp | 30 |
| **TextService** | Text | Source/Engine/Text/TextService.hpp | 18 |
| **TextShapeCache** | Text | Source/Engine/Text/TextShapeCache.hpp | 59 |
| **TextShapeHandle** | Text | Source/Engine/Text/TextShapeCache.hpp | 19 |
| **TextShapeKey** | Text | Source/Engine/Text/TextShapeCache.hpp | 32 |
| **TextShapeParams** | Text | Source/Engine/Text/TextShaper.hpp | 71 |
| **TextShapeResult** | Text | Source/Engine/Text/TextShaper.hpp | 82 |
| **TextShapeSystemStats** | Text | Source/Engine/Text/TextShapeSystem.hpp | 16 |
| **TextShapeView** | Text | Source/Engine/Text/TextShapeCache.hpp | 50 |
| **TextSpan** | Text | Source/Engine/Text/TextStyle.hpp | 40 |
| **TextStore** | Text | Source/Engine/Text/TextStore.hpp | 19 |
| **TextStyle** | Text | Source/Engine/Text/TextStyle.hpp | 27 |
| **TextStyledBlock** | Text | Source/Engine/Text/TextMarkup.hpp | 30 |
| **TextStyleFlags** | Text | Source/Engine/Text/TextStyle.hpp | 12 |
| **UnicodeBoundary** | Text | Source/Engine/Text/UnicodeBreak.hpp | 13 |
| **VerticalFormEntry** | Text | Source/Engine/Text/TextVertical.hpp | 16 |

## Engine/UI (101)

| Symbol | Kind | Header | Line |
|---|---|---|---|
| **AccessibilityEditorSettings** | UI | Source/Engine/UI/Accessibility.hpp | 250 |
| **AccessibilityFlags** | UI | Source/Engine/UI/Accessibility.hpp | 208 |
| **AccessibilityKernel** | UI | Source/Engine/UI/Accessibility.hpp | 304 |
| **AccessibilityOverlay** | UI | Source/Engine/UI/AccessibilityOverlay.hpp | 30 |
| **AccessibilityPresentationSettings** | UI | Source/Engine/UI/Accessibility.hpp | 233 |
| **AccessibilityProfile** | UI | Source/Engine/UI/Accessibility.hpp | 272 |
| **AccessibilitySettings** | UI | Source/Engine/UI/Accessibility.hpp | 217 |
| **AudioSystem** | UI | Source/Engine/UI/Accessibility.hpp | 26 |
| **AvSpeechTts** | UI | Source/Engine/UI/Tts.hpp | 60 |
| **BuildStatus** | UI | Source/Engine/UI/PinkUI.hpp | 1440 |
| **CardBoardComponent** | UI | Source/Engine/UI/CardBoard.hpp | 49 |
| **CardBoardSystem** | UI | Source/Engine/UI/CardBoard.hpp | 74 |
| **ColorMatrix3** | UI | Source/Engine/UI/Accessibility.hpp | 42 |
| **ColorVisionDeficiency** | UI | Source/Engine/UI/Accessibility.hpp | 34 |
| **Dropdown** | UI | Source/Engine/UI/PinkUI.hpp | 534 |
| **FlashGuard** | UI | Source/Engine/UI/Accessibility.hpp | 59 |
| **FocusDirection** | UI | Source/Engine/UI/PinkUI.hpp | 211 |
| **FocusPolicy** | UI | Source/Engine/UI/PinkUI.hpp | 187 |
| **FontAtlas** | UI | Source/Engine/UI/ | 101 |

| | | | |
|---|---|---|---|
| | | FontAtlas.hpp | |
| **FontAtlasHeader** | UI | Source/Engine/UI/ FontAtlas.hpp | 45 |
| **FontAtlasSet** | UI | Source/Engine/UI/ FontAtlas.hpp | 167 |
| **FontBuildOptions** | UI | Source/Engine/UI/ FontAtlas.hpp | 25 |
| **FontBuildOptions** | UI | Source/Engine/UI/ FontBuilder.hpp | 15 |
| **FontCoverage** | UI | Source/Engine/UI/ FontCoverage.hpp | 21 |
| **FontFamilyFile** | UI | Source/Engine/UI/ FontAtlas.hpp | 74 |
| **FontFamilyManifest** | UI | Source/Engine/UI/ FontFamilyAsset.hpp | 17 |
| **FontPixelFormat** | UI | Source/Engine/UI/ FontAtlas.hpp | 37 |
| **FontStyle** | UI | Source/Engine/UI/ FontAtlas.hpp | 65 |
| **FrameOutput** | UI | Source/Engine/UI/ PinkUI.hpp | 1418 |
| **GlyphRecord** | UI | Source/Engine/UI/ FontAtlas.hpp | 80 |
| **GridView** | UI | Source/Engine/UI/ PinkUI.hpp | 424 |
| **HyperlinkRange** | UI | Source/Engine/UI/ Hypertext.hpp | 51 |
| **HypertextComponent** | UI | Source/Engine/UI/ Hypertext.hpp | 32 |
| **HypertextFlags** | UI | Source/Engine/UI/ Hypertext.hpp | 21 |
| **HypertextPool** | UI | Source/Engine/UI/ Hypertext.hpp | 74 |
| **HypertextView** | UI | Source/Engine/UI/ Hypertext.hpp | 67 |
| **ITextShaper** | UI | Source/Engine/UI/ PinkUI.hpp | 33 |
| **LayoutCache** | UI | Source/Engine/UI/ PinkUI.hpp | 736 |
| **LazyFontFamily** | UI | Source/Engine/UI/ FontFamilyAsset.hpp | 101 |

| | | | |
|---|---|---|---|
| **ListView** | UI | Source/Engine/UI/ PinkUI.hpp | 560 |
| **LocalizationTable** | UI | Source/Engine/UI/ Accessibility.hpp | 24 |
| **LocalizationTable** | UI | Source/Engine/UI/ Hypertext.hpp | 16 |
| **LocalizationTable** | UI | Source/Engine/UI/ PinkUI.hpp | 39 |
| **NarrativeArchetype** | UI | Source/Engine/UI/ NarrativeTree.hpp | 23 |
| **NarrativeEvent** | UI | Source/Engine/UI/ Accessibility.hpp | 83 |
| **NarrativeGroup** | UI | Source/Engine/UI/ NarrativeTree.hpp | 37 |
| **NarrativeLocale** | UI | Source/Engine/UI/ NarrativeTree.hpp | 17 |
| **NarrativeLog** | UI | Source/Engine/UI/ Accessibility.hpp | 99 |
| **NarrativeNode** | UI | Source/Engine/UI/ NarrativeTree.hpp | 47 |
| **NarrativeTree** | UI | Source/Engine/UI/ NarrativeTree.hpp | 55 |
| **OledShiftState** | UI | Source/Engine/UI/ PinkUI.hpp | 463 |
| **PinkSdfDraw** | UI | Source/Engine/UI/ PinkSdf.hpp | 74 |
| **PinkSdfFlags** | UI | Source/Engine/UI/ PinkSdf.hpp | 24 |
| **PinkSdfGpuPrimitive** | UI | Source/Engine/UI/ PinkSdf.hpp | 51 |
| **PinkSdfPrimitive** | UI | Source/Engine/UI/ PinkSdf.hpp | 33 |
| **PinkSdfShape** | UI | Source/Engine/UI/ PinkSdf.hpp | 15 |
| **RadialProgress** | UI | Source/Engine/UI/ PinkUI.hpp | 584 |
| **RetainedFont** | UI | Source/Engine/UI/ FontAtlas.hpp | 293 |
| **SapiTts** | UI | Source/Engine/UI/ Tts.hpp | 30 |
| **ScrollView** | UI | Source/Engine/UI/ | 491 |

| | | | |
|---|---|---|---|
| | | PinkUI.hpp | |
| **SlotComponent** | UI | Source/Engine/UI/CardBoard.hpp | 27 |
| **SlotFlags** | UI | Source/Engine/UI/CardBoard.hpp | 15 |
| **SlotLayout** | UI | Source/Engine/UI/CardBoard.hpp | 65 |
| **SoundCueCategory** | UI | Source/Engine/UI/SoundCues.hpp | 26 |
| **SoundCueDef** | UI | Source/Engine/UI/SoundCues.hpp | 62 |
| **SoundCueRegistry** | UI | Source/Engine/UI/SoundCues.hpp | 71 |
| **SoundTrigger** | UI | Source/Engine/UI/Accessibility.hpp | 128 |
| **StateTrack** | UI | Source/Engine/UI/Accessibility.hpp | 417 |
| **SubtitleLine** | UI | Source/Engine/UI/Accessibility.hpp | 139 |
| **SubtitleQueue** | UI | Source/Engine/UI/Accessibility.hpp | 163 |
| **SystemContext** | UI | Source/Engine/UI/PinkUI.hpp | 28 |
| **TabBar** | UI | Source/Engine/UI/PinkUI.hpp | 515 |
| **TextAlign** | UI | Source/Engine/UI/PinkUI.hpp | 222 |
| **TextShapeParams** | UI | Source/Engine/UI/PinkUI.hpp | 34 |
| **TextVerticalAlign** | UI | Source/Engine/UI/PinkUI.hpp | 229 |
| **TimedSoundCue** | UI | Source/Engine/UI/Accessibility.hpp | 152 |
| **TooltipPlacer** | UI | Source/Engine/UI/PinkUI.hpp | 595 |
| **TtsBackend** | UI | Source/Engine/UI/Accessibility.hpp | 27 |
| **TtsBackend** | UI | Source/Engine/UI/Tts.hpp | 19 |
| **TtsPriority** | UI | Source/Engine/UI/Tts.hpp | 11 |

| | | | |
|---|---|---|---|
| **UiPalette** | UI | Source/Engine/UI/UiTheme.hpp | 41 |
| **UiPaletteSlot** | UI | Source/Engine/UI/UiTheme.hpp | 18 |
| **UiThemeAsset** | UI | Source/Engine/UI/UiTheme.hpp | 46 |
| **VirtualFileSystem** | UI | Source/Engine/UI/FontAtlas.hpp | 19 |
| **VoiceCaptionEvent** | UI | Source/Engine/UI/Accessibility.hpp | 193 |
| **VoiceCaptionProvider** | UI | Source/Engine/UI/Accessibility.hpp | 201 |
| **WidgetCanvas** | UI | Source/Engine/UI/Accessibility.hpp | 30 |
| **WidgetCanvas** | UI | Source/Engine/UI/PinkUI.hpp | 290 |
| **WidgetCanvas** | UI | Source/Engine/UI/PinkUI.hpp | 483 |
| **WidgetCanvas** | UI | Source/Engine/UI/PinkUI.hpp | 607 |
| **WidgetCanvasSystem** | UI | Source/Engine/UI/PinkUI.hpp | 1453 |
| **WidgetComponent** | UI | Source/Engine/UI/PinkUI.hpp | 251 |
| **WidgetComponentFlags** | UI | Source/Engine/UI/PinkUI.hpp | 263 |
| **WidgetDesc** | UI | Source/Engine/UI/PinkUI.hpp | 309 |
| **WidgetFlags** | UI | Source/Engine/UI/PinkUI.hpp | 145 |
| **WidgetHandle** | UI | Source/Engine/UI/PinkUI.hpp | 80 |
| **WidgetHyperlink** | UI | Source/Engine/UI/PinkUI.hpp | 300 |
| **WidgetKind** | UI | Source/Engine/UI/PinkUI.hpp | 99 |
| **WidgetLayoutAsset** | UI | Source/Engine/UI/WidgetLayoutAsset.hpp | 15 |
| **WidgetPaintContext** | UI | Source/Engine/UI/PinkUI.hpp | 291 |
| **WidgetPaintContext** | UI | Source/Engine/UI/ | 391 |

| | | | |
|---|---|---|---|
| | | PinkUI.hpp | |

### Engine/Video (20)

| Symbol | Kind | Header | Line |
|---|---|---|---|
| **AssetDatabase** | Video | Source/Engine/Video/VideoStream.hpp | 23 |
| **ClusterScan** | Video | Source/Engine/Video/WebmDemuxer.hpp | 108 |
| **ContainerKind** | Video | Source/Engine/Video/WebmDemuxer.hpp | 150 |
| **DecodeStatus** | Video | Source/Engine/Video/VideoTypes.hpp | 29 |
| **DemuxStatus** | Video | Source/Engine/Video/WebmDemuxer.hpp | 52 |
| **Element** | Video | Source/Engine/Video/WebmDemuxer.hpp | 85 |
| **FrameBuffer** | Video | Source/Engine/Video/VideoPlayer.hpp | 118 |
| **FrameSlot** | Video | Source/Engine/Video/VideoPlayer.hpp | 125 |
| **MappedFile** | Video | Source/Engine/Video/VideoPlayer.hpp | 22 |
| **RHI** | Video | Source/Engine/Video/VideoPlayer.hpp | 27 |
| **VideoPlayer** | Video | Source/Engine/Video/VideoPlayer.hpp | 33 |
| **VideoStreamComponent** | Video | Source/Engine/Video/VideoStream.hpp | 31 |
| **VideoStreamFlags** | Video | Source/Engine/Video/VideoTypes.hpp | 20 |
| **VideoSystem** | Video | Source/Engine/Video/ | 49 |

| | | | |
|---|---|---|---|
| | | VideoStream.hpp | |
| **VirtualFileSystem** | Video | Source/Engine/ Video/ VideoStream.hpp | 20 |
| **Vp9Backend** | Video | Source/Engine/ Video/ Vp9Backend.hpp | 30 |
| **WebmDemuxer** | Video | Source/Engine/ Video/ WebmDemuxer.hpp | 60 |
| **WebmFrame** | Video | Source/Engine/ Video/ WebmDemuxer.hpp | 38 |
| **WebmTrackInfo** | Video | Source/Engine/ Video/ WebmDemuxer.hpp | 14 |
| **YuvFrameView** | Video | Source/Engine/ Video/ Vp9Backend.hpp | 12 |

### Engine/Weather (12)

| Symbol | Kind | Header | Line |
|---|---|---|---|
| **ClothSystem** | Weather | Source/Engine/ Weather/Weather.hpp | 13 |
| **WeatherAtmosphere Pass** | Weather | Source/Engine/ Weather/ WeatherPreconciliated .hpp | 128 |
| **WeatherContextCom ponent** | Weather | Source/Engine/ Weather/Weather.hpp | 32 |
| **WeatherDesc** | Weather | Source/Engine/ Weather/Weather.hpp | 91 |
| **WeatherFlags** | Weather | Source/Engine/ Weather/Weather.hpp | 19 |
| **WeatherGpuConstan ts** | Weather | Source/Engine/ Weather/ WeatherPreconciliated .hpp | 46 |
| **WeatherGpuResourc es** | Weather | Source/Engine/ Weather/ WeatherPreconciliated .hpp | 18 |
| **WeatherGpuStats** | Weather | Source/Engine/ | 68 |

| | | | |
|---|---|---|---|
| | | Weather/ WeatherPreconciliated .hpp | |
| **WeatherPreconciliatedDesc** | Weather | Source/Engine/ Weather/ WeatherPreconciliated .hpp | 32 |
| **WeatherPreconciliatedSystem** | Weather | Source/Engine/ Weather/ WeatherPreconciliated .hpp | 78 |
| **WeatherSystem** | Weather | Source/Engine/ Weather/Weather.hpp | 99 |
| **WeatherWindField** | Weather | Source/Engine/ Weather/Weather.hpp | 75 |

## 40. Appendix B - macros and platform defines

| Macro | Header | Line |
|---|---|---|
| **FBY_AOT_EXPORT** | Source/Engine/Script/ AotAbi.hpp | 396 |
| **FBY_AOT_EXPORT** | Source/Engine/Script/ AotAbi.hpp | 398 |
| **FBY_ASSERT** | Source/Engine/Core/ Assert.hpp | 13 |
| **FBY_ASSERT** | Source/Engine/Core/ Assert.hpp | 31 |
| **FBY_ASSERT_MSG** | Source/Engine/Core/ Assert.hpp | 22 |
| **FBY_ASSERT_MSG** | Source/Engine/Core/ Assert.hpp | 32 |
| **FBY_DEFINE_PLUGIN** | Source/Engine/Core/ Plugin.hpp | 56 |
| **FBY_DETAIL_CONCAT** | Source/Engine/Core/ Definitions.hpp | 261 |
| **FBY_DETAIL_CONCAT_INNER** | Source/Engine/Core/ Definitions.hpp | 260 |
| **FBY_FIELD** | Source/Engine/Core/ Mirror.hpp | 284 |
| **FBY_FLUID_HAS_MDSPAN** | Source/Engine/Physics/ Fluid.hpp | 16 |
| **FBY_FLUID_HAS_MDSPAN** | Source/Engine/Physics/ | 18 |

| | | |
|---|---|---|
| | Fluid.hpp | |
| **FBY_HAS_MDSPAN** | Source/Engine/ECS/ Skeleton.hpp | 17 |
| **FBY_HAS_MDSPAN** | Source/Engine/ECS/ Skeleton.hpp | 19 |
| **FBY_HAS_STATIC_REFLECTION** | Source/Engine/Core/ Mirror.hpp | 102 |
| **FBY_HAS_STATIC_REFLECTION** | Source/Engine/Core/ Mirror.hpp | 105 |
| **FBY_HAS_STATIC_REFLECTION** | Source/Engine/Core/ Mirror.hpp | 109 |
| **FBY_HAS_STD_FLAT_MAP** | Source/Engine/Core/ FlatMap.hpp | 19 |
| **FBY_HAS_STD_FLAT_MAP** | Source/Engine/Core/ FlatMap.hpp | 21 |
| **FBY_HAS_STD_FLAT_MAP** | Source/Engine/Core/ FlatMap.hpp | 24 |
| **FBY_PLATFORM_ABI_VERSION** | Source/Plugins/ PlatformService/PlatformAPI.h | 11 |
| **FBY_PLATFORM_CALL** | Source/Plugins/ PlatformService/PlatformAPI.h | 15 |
| **FBY_PLATFORM_CALL** | Source/Plugins/ PlatformService/PlatformAPI.h | 18 |
| **FBY_PLATFORM_EXPORT** | Source/Plugins/ PlatformService/PlatformAPI.h | 14 |
| **FBY_PLATFORM_EXPORT** | Source/Plugins/ PlatformService/PlatformAPI.h | 17 |
| **FBY_PLUGIN_ABI_VERSION** | Source/Engine/Core/ PluginAPI.h | 28 |
| **FBY_PLUGIN_API_H** | Source/Engine/Core/ PluginAPI.h | 18 |
| **FBY_PLUGIN_COMPONENT** | Source/Engine/Core/ Plugin.hpp | 53 |
| **FBY_PLUGIN_ENTRY** | Source/Engine/Core/ PluginAPI.h | 115 |
| **FBY_PLUGIN_EXPORT** | Source/Engine/Core/ PluginAPI.h | 31 |
| **FBY_PLUGIN_EXPORT** | Source/Engine/Core/ PluginAPI.h | 33 |
| **FBY_PLUGIN_EXPORT** | Source/Engine/Core/ PluginAPI.h | 35 |

| | | |
|---|---|---|
| **FBY_PLUGIN_EXPORT** | Source/Engine/Core/ PluginApi.hpp | 11 |
| **FBY_PLUGIN_EXPORT** | Source/Engine/Core/ PluginApi.hpp | 13 |
| **FBY_PLUGIN_INFO_SYMBOL** | Source/Engine/Core/ PluginAPI.h | 107 |
| **FBY_PLUGIN_LOAD_SYMBOL** | Source/Engine/Core/ PluginAPI.h | 108 |
| **FBY_PLUGIN_UNLOAD_SYMBOL** | Source/Engine/Core/ PluginAPI.h | 109 |
| **FBY_PROJECT_ASSETS** | Source/Engine/Assets/ ProjectScaffold.hpp | 123 |
| **FBY_REFLECT_COMPONENT** | Source/Engine/Core/ Mirror.hpp | 291 |
| **FBY_REFLECT_COMPONENT_EMPTY** | Source/Engine/Core/ Mirror.hpp | 303 |
| **FBY_REGISTER_TYPE** | Source/Engine/Core/ Definitions.hpp | 264 |
| **FBY_RELEVANCE_HAS_MDSPAN** | Source/Engine/Network/ RelevanceGrid.hpp | 19 |
| **FBY_RELEVANCE_HAS_MDSPAN** | Source/Engine/Network/ RelevanceGrid.hpp | 21 |
| **FBY_RESTRICT** | Source/Engine/Core/ Definitions.hpp | 26 |
| **FBY_RESTRICT** | Source/Engine/Core/ Definitions.hpp | 28 |
| **FBY_SDF_SHAPE_FIELD** | Source/Engine/Physics/ SdfPrimitives.hpp | 172 |
| **FBY_TYPE_NAME** | Source/Engine/Core/ Definitions.hpp | 280 |
| **FBY_UI_HAS_MDSPAN** | Source/Engine/UI/PinkUI.hpp | 21 |
| **FBY_UI_HAS_MDSPAN** | Source/Engine/UI/PinkUI.hpp | 23 |
| **FBY_UNREACHABLE** | Source/Engine/Core/ Assert.hpp | 45 |
| **FBY_VERIFY** | Source/Engine/Core/ Assert.hpp | 36 |
| **FBY_VK_DECLARE** | Source/Engine/RHI/Vulkan/ VulkanLoader.hpp | 126 |
| **FBY_VK_DEVICE_FUNCTIONS** | Source/Engine/RHI/Vulkan/ VulkanLoader.hpp | 36 |
| **FBY_VK_GLOBAL_FUNCTIO** | Source/Engine/RHI/Vulkan/ | 15 |

| | | |
|---|---|---|
| **NS** | VulkanLoader.hpp | |
| **FBY_VK_INSTANCE_FUNCTIONS** | Source/Engine/RHI/Vulkan/VulkanLoader.hpp | 20 |
| **FORCEINLINE** | Source/Engine/Core/Definitions.hpp | 17 |
| **FORCEINLINE** | Source/Engine/Core/Definitions.hpp | 19 |
| **FORCEINLINE** | Source/Engine/Core/Definitions.hpp | 21 |