

AGREGATE FRIGORIFICE PENTRU ECHIPARE AUTOUTILITARE TRANSPORT MARFĂ – KONVEKTA

Autoutilitare tip VAN – refrigerare & congelare

Modele - TK 2920 & TK 4020

The distinctive character and design of these innovative, powerful roof-top units will enhance every cooling van. The new transport refrigeration units do not only captivate with their design, they also demonstrate a strong and powerful cooling system.

The units provide a cooling capacity for panel vans with a storage room up to 17 m³ and can be used for the transportation of perishable goods. When transporting perishable goods at -20°C with R404A the use of panel vans with a cold storage room up to 10 m³ is possible.

The new Konvekta units also excel in the refrigeration of two separate temperature zones in dual-chamber vehicles as well as in the heating of the cabin during winter months.

For the use of the cooling vehicle as a storage room or for the selling on weekly markets four models of these extremely noiseless but powerful standby units are available. They meet the needs in almost all installation situations.

Due to a low weight the loading capacity of the vehicle is increased and the energy consumption is reduced.

Compact roof unit



Technical Data – TK 2920

Cooling capacity driving cooling (+6°C*/+30°C**) [W]:	3.400
Cooling capacity driving cooling (+0°C*/+30°C**) [W]:	2.900
Cooling capacity standby option(-20°C*/+30°C**) [W]:	1.900
Evaporator-Air flow rate[m ³ /h]:	1.150
Power consumption 12V/24V [A]:	33/17
Weight mobile cooling [kg]:	45
Weight standby cooling [kg]:	76
Evaporator L/B/H [mm]:	VD 3013/585x827x197
Condenser L/B/H [mm]:	DKD 327/1420x910x189
Standby :	1.800/2.800

*Insidetemperature **Outsidetemperature

Technical Data – TK 4020

Cooling capacity driving cooling (+6°C*/+30°C**) [W]:	4.450
Cooling capacity driving cooling (+0°C*/+30°C**) [W]:	3.850
Cooling capacity standby option(-20°C*/+30°C**) [W]:	2.150
Evaporator-Air flow rate[m ³ /h]:	2.450
Power consumption 12V/24V [A]:	30/20
Weight mobile cooling [kg]:	67
Weight standby cooling [kg]:	98
Evaporator L/B/H [mm]:	VD 4015/738x1120x185
Condenser L/B/H [mm]:	DKD 327/1420x910x189
standby:	2.200/2.800

*Insidetemperature **Outsidetemperature

Options

- Oil separator
- Available also with electronic engine-independent cooling system 230 V or 400 V

Your Advantages:

- Fully-developed Longlife-technique
- High cooling capacity
- Constant temperature and air circulation at different speed ranges
- Hot gas defrosting as standard feature
- No loss of loading space due to external evaporator
- Easy to maintain – all components easy to access
- Remote control of cooling unit from driver's cab
- Aerodynamic design
- Easy to install
- Eco-friendly
- Low noise level