

AGREGATE FRIGORIFICE PENTRU ECHIPARE AUTOUTILITARE TRANSPORT MARFĂ – KONVEKTA

Autoutilitare tip VAN – refrigerare & congelare

Model - TK 3650 - efficient and reliable



Roof mounted condenser



Evaporator



The Konvekta product ranges FK 2950 and TK 3650 are powerful refrigeration units for the delivery of perishable goods and deep-freeze transport. For panel vans the condenser is mounted on the roof-top, for refrigeration truck containers a front wall condenser is used. This makes these units suitable for the largest possible range of refrigerated containers.

Both lines of products are extremely well suited for the transport of perishable goods and frozen foods. Their high cooling capacity and fast achievement of setpoint are especially beneficial for the distribution trade. With its capacity of over 2000 Watts at 30°C ambient and -20°C inside temperature, the TK 3650 provides the ideal solution for deep-freeze transport.

Available as mobile cooling unit or as a mobile / standby cooling unit, the units FK 2950 and TK 3650 are suitable for the use on all common types of panel vans and refrigeration truck containers.

Technical Data

Type:	TK 3650
Cooling capacity driving cooling (+0°C*/+30°C**) [W]:	3.600
Cooling capacity driving cooling (-20°C*/+30°C**) [W]:	2.050
Cooling capacity standby option (+0°C*/+30°C**) [W]:	2.400
Evaporator-Air flow rate [m³/h]:	2.450
Current intake at 12V/24V [A]:	25
Weight frontwall unit mobile cooling/standby cooling[kg]:	58/107
Weight roof-top unit mobile cooling/standby cooling [kg]:	63/111
Evaporator L/B/H [mm]:	738/1.120/185
Condenser roof mounted unit/driving cooling L/B/H [mm]:	1.141/990/275
Condenser frontwallunit/driving cooling L/B/H [mm]:	700/884/350
Options:	see right
*Insidetemperature **Outsidetemperature	

Your Advantages:

- Units for refrigerating vans
- Units for box-type delivery vans
- Deep-freezing unit down to -20°C
- Powered by vehicle's engine
- High cooling capacity / High chilling capacity
- Constant temperature and air circulation even at different speed ranges
- Remote control of refrigerator from driver's cabin
- Hot gas defrosting as standard feature
- Low fuel consumption
- Durable – unit corrosion-resistant
- Eco-friendly
- Unit completely re-usable
- Service-friendly – all components easy to access

Options:

- Electrical heating
- Available in 12 Volt / 24 Volt
- Hot water heating
- Electric engine-independent cooling system available of 400 Volt