

AGREGATE FRIGORIFICE PENTRU ECHIPARE AUTOUTILITARE TRANSPORT MARFĂ – KONVEKTA

Autoutilitare tip VAN - refrigerare

Model - FK 1500 - the small cool ones



o
f-top Condenser



Evaporator

The different options of split units of this series developed by Konvekta for small delivery vans and vehicles with cooling boxes meet all client requirements. Whether with elegant roof-mounted condenser (FK 1520), condenser mounted ahead of cooler (FK 1500) or designed as discrete underfloor unit (FK 1510), FK 1500 is the perfect refrigerating unit for transportation of fresh foods. Also available with additional engine-independent cooling system.

Technical Data

Type:	FK 1500
Cooling capacity mobile cool. (+6°C*/+30°C**) [W]:	1.810
Cooling capacity mobile cool. (+0°C*/+30°C**) [W]:	1.510
Cooling capacity standby cool (-20°C*/+30°C**) [W]:	900
Evaporator air capacity [m³/h]:	800
Current draw at 12V/24V [A]:	7,5
Weight mobile cooling [kg]:	23
Weight standby cooling [kg]:	-
Refrigerant	R134a
Dimensions evaporator L/W/H [mm]:	586/592/187
special options:	-
*Insidetemperature **Outsidetemperature	

Technical Data

Type:	FK 1510
Cooling capacity mobile cool. (+6°C*/+30°C**) [W]:	1.810
Cooling capacity mobile cool. (+0°C*/+30°C**) [W]:	1.510
Cooling capacity standby cool. (+0°C*/+30°C**) [W]:	900
Evaporator air capacity [m³/h]:	800
Current draw at 12V [A]:	15
Weight mobile cooling [kg]:	26
Weight standby cooling [kg]:	66
Refrigerant	R134a
Dimensions evaporator L/W/H [mm]:	586/592/187
special options:	standby cooling
*Insidetemperature **Outsidetemperature	

Technical Data

Type:	FK 1520
Cooling capacity mobile cool. (+6°C*/+30°C**) [W]:	1.810
Cooling capacity mobile cool. (+0°C*/+30°C**) [W]:	1.510
Cooling capacity standby cool. (+0°C*/+30°C**) [W]:	900
Evaporator air capacity [m³/h]:	800
Current draw at 12V/24V [A]:	15
Refrigerant	R134a
Weight mobile cooling [kg]:	32
Weight standby cooling [kg]:	72
Dimensions evaporator L/W/H [mm]:	586/592/187
special options:	standby cooling
*Insidetemperature **Outsidetemperature	

Model - FK 2000 - One size more

A fully-developed, easy to maintain Split-unit for vans and small and middle-sized delivery vehicles, guaranteeing a constant temperature due to the high cooling capacity even at different engine speeds. Easy to install and to operate (remote control from driver's cabin) there are three models available, roof-mounted condenser (FK 2020), underfloor unit (FK 1010) and condenser ahead of cooler (FK 2000). All models are available also with hot gas defrosting and additional engine-independent refrigeration system.

Technical Data

Type:	FK 2000
Cooling capacity mobile cool. (+6°C*/+30°C**) [W]:	2.350
Cooling capacity mobile cool. (+0°C*/+30°C**) [W]:	2000
Cooling capacity standby cool. (-20°C*/+30°C**) [W]:	1.000
Evaporator air capacity [m³/h]:	800
Current draw at 12V/24V [A]:	7,5
Weight mobile cooling [kg]:	25
Weight standby cooling [kg]:	-
Refrigerant	R134a
Dimensions evaporator L/W/H [mm]:	586/592/187
special options:	-
*Insidetemperature **Outsidetemperature	

Technical Data

Type:	FK 2010
Cooling capacity mobile cool. (+6°C*/+30°C**) [W]:	2.350
Cooling capacity mobile cool. (+0°C*/+30°C**) [W]:	2000
Cooling capacity standby cool. (-20°C*/+30°C**) [W]:	1.000
Evaporator air capacity [m³/h]:	800
Current draw at 12V [A]:	15
Weight mobile cooling [kg]:	28
Weight standby cooling [kg]:	76
Refrigerant	R134a
Dimensions seaporator L/W/H [mm]:	586/592/187
special options:	standby cooling
*Insidetemperature **Outsidetemperature	

Technical Data

Type:	FK 2020
Cooling capacity mobile cool. (+6°C*/+30°C**) [W]:	2.350
Cooling capacity mobile cool. (+0°C*/+30°C**) [W]:	2000
Cooling capacity standby cool. (+0°C*/+30°C**) [W]:	1.000
Evaporator air capacity [m³/h]:	800
Current draw at 12V [A]:	15
Weight mobile cooling [kg]:	34
Weight standby cooling [kg]:	82
Refrigerant	R134a
Dimensions evaporator L/W/H [mm]:	586/592/187
Condenser L/W/H [mm]:(DKD 112)	827/600/172
special options:	standby cooling

*Insidetemperature **Outsidetemperature

Model - FK 2500 - The great under the small-sized

Dimensioned for insulating vehicles with boxes and large delivery vans this fully-developed Split unit makes it possible to upgrade your vehicle to a fail-safe refrigerating vehicle and that at low cost. Available with roof-mounted as well as with underfloor condenser (FK 2520, FK 2510) this efficient and handsome unit ensures a constant temperature and consistent air circulation even at different speed ranges. Also available with hot gas defrosting and additional electric engine-independent refrigeration system.

Technical Data

Type:	FK 2510
Cooling capacity mobile cool. (+6°C*/+30°C**) [W]:	3.100
Cooling capacity mobile cool. (+0°C*/+30°C**) [W]:	2.690
Cooling capacity standby cool. (-20°C*/+30°C**) [W]:	1.650
Evaporator air capacity [m³/h]:	1.150
Current draw at 12V/24V [A]:	22
Weight mobile cooling [kg]:	31
Weight standby cooling [kg]:	71
Refrigerant	R134a
Dimensions evaporator L/W/H [mm]:	581/825/172
special options:	standby cooling

*Insidetemperature **Outsidetemperature

Technical Data

Type:	FK 2520
Cooling capacity mobile cool. (+6°C*/+30°C**) [W]:	3.100
Cooling capacity mobile cool. (+0°C*/+30°C**) [W]:	2.690
Cooling capacity standby cool. (-20°C*/+30°C**) [W]:	1.650
Evaporator air capacity [m³/h]:	1.150
Current intake at 12V/24V [A]:	22/-
Weight mobile cooling [kg]:	37
Weight standby cooling [kg]:	81
Refrigerant	R134a
Dimensions evaporator L/W/H [mm]:	581/825/172
special options:	standby cooling
*Insidetemperature **Outsidetemperature	

Your Advantages:

- Fully-developed Longlife-technique
- ATP certified (FK 2500)
- High cooling capacity
- Powered by vehicle's engine
- Constant temperature
- Air circulation at different speed ranges
- Remote control of refrigerating unit from driver's cab
- Safe to operate and reliable
- Easy to install
- Easy to maintain
- Low fuel consumption
- Corrosion-resistant and of low noise level
- High operator convenience

Options Series FK 1500, FK 2000, FK 2500

- Hot gas defrosting
- Hot gas heating
- Electric engine-independent cooling system (FK 2500)