

AGREGATE FRIGORIFICE PENTRU ECHIPARE AUTOUTILITARE TRANSPORT MARFĂ – KONVEKTA

Autoutilitare tip VAN - refrigerare

Model - FK 2650 - high performance, compact design



Compact roof unit



No loading space is lost with this easy to install and to maintain unit applicable for all common box-type delivery vans. Only the air diffuser board guaranteeing optimal air circulation is located inside the vehicle. All other components of this high-performance unit with minimum space requirements are integrated into the attractive aerodynamically flat roof-mounted cover. Perfect design and a high-quality technical equipment with hot gas defrosting and Thermotronic remote control from driver's cab as standard features make FK 2650 to the most efficient unit of its grade.

Technical Data

Type:	FK 2650
Cooling capacity driving cooling (+6°C*/+30°C**) [W]:	3.040
Cooling capacity driving cooling (+0°C*/+30°C**) [W]:	2.670
Cooling capacity standby option(+0°C*/+30°C**) [W]:	1.580
Evaporator-Air flow rate[m³/h]:	1.140
Current intake at 12V/24V [A]:	34
Weight driving cooling [kg]:	47
Weight driving-/standing cooling [kg]:	100
Evaporator L/B/H [mm]:	-
Condenser driving cooling L/B/H [mm]:(compact)	1.141/990/275
Condenser standing cooling L/B/H [mm]:(compact)	1.571/990/275
options :	see down

*Insidetemperature **Outsidetemperature

Options

- Oil separator
- Available also with electronic engine-independent cooling system 230 V or 400 V

Your Advantages:

- Fully-developed Longlife-technique
- High cooling capacity
- Constant temperature and air circulation at different speed ranges
- Hot gas defrosting as standard feature
- No loss of loading space due to external evaporator
- Easy to maintain – all components easy to access
- Remote control of cooling unit from driver's cab
- Aerodynamic design
- Easy to install
- Eco-friendly
- Low noise level