

UMA-MT

R404A-R507

range evap. T° -5/-15 °C

indoor

Model	Compressor - Compressor			Set di progetto - Design data				Dati tecnici - Technical data				Accessories						
	N°	Power kW	Type	Q	Power	T max	U _{ts}	A	B	H	Weight	Liquid receiver	Connections			RSD Category	Sound Power	Sound Pressure
				-15/+5 °C									D	L	D			
SYNHERMETIC RECPs																		
				kW	kW	°C	kPa	mm	mm	mm	kg	l	mm	mm	mm		dB(A)	dB(A)
UMA 200 MT	1	20	SE	28,4	12,5	30,5	160,0	2.200	1.100	1.380	410	15	35	28	22	II	28,0	50,0
UMA 250 MT	1	25	SE	34,5	16,4	40,1	192,0	2.200	1.100	1.380	430	25	42	28	22	II	29,0	51,0
UMA 300 MT	1	30	SE	42,5	19,8	42,7	218,0	2.200	1.100	1.380	460	25	54	35	22	II	28,0	50,0
UMA 350 MT	1	35	SE	51,0	25,5	62,4	264,0	2.200	1.100	1.380	480	25	54	35	28	II	35,0	57,0
UMA 400 MT	1	40	SE	59,5	27,1	71,8	247,0	2.200	1.100	1.380	520	25	54	35	28	II	32,0	54,0
UMA 500 MT	1	50	SE	72,5	34,1	94,7	415,0	2.200	1.100	1.380	580	50	64	42	28	III	39,0	58,0
UMA 600 MT	1	60	SE	87,5	38,4	107,0	544,0	2.200	1.100	1.380	680	50	64	42	35	III	34,0	56,0
SYNHERMETIC TWO STAGE																		
UMA 2x100 MTSR	2	10	HS	34,4	16,1	38,4	146,2	2.200	1.100	1.380	400	15	35	22	16	II	33,0	55,0
UMA 2x130 MTSR	2	13	HS	48,8	20,5	51,2	192,6	2.200	1.100	1.380	450	15	35	22	16	II	33,0	55,0
UMA 2x150 MTSR	2	15	HS	52,5	24,8	55,6	225,8	2.200	1.100	1.380	510	15	35	28	22	II	33,0	55,0
UMA 2x150 MT	2	15	SE	48,4	20,8	62,0	163,0	2.110	1.100	1.980	670	15	42	28	22	II	29,5	51,5
UMA 2x200 MT	2	20	SE	56,8	25,2	61,0	196,4	2.110	1.100	1.980	770	15	42	28	22	II	31,0	53,0
UMA 2x250 MT	2	25	SE	69,0	32,8	80,2	232,1	2.110	1.300	1.980	810	25	42	28	22	II	32,0	54,0
UMA 2x300 MT	2	30	SE	85,0	38,5	95,4	265,7	2.110	1.300	1.980	870	25	54	35	22	II	31,0	53,0
UMA 2x350 MT	2	35	SE	102,0	51,0	124,8	346,4	2.110	1.300	1.980	910	25	54	35	28	II	38,0	60,0
UMA 2x400 MT	2	40	SE	119,0	42,2	143,6	418,8	2.110	1.300	1.980	950	25	54	35	28	II	35,0	57,0
UMA 2x500 MT	2	50	SE	145,0	68,2	189,4	505,7	2.110	1.300	1.980	1.110	50	64	42	28	III	39,0	61,0

UMA-BT

R404A-R507

range evap. T° -25/-35 °C

indoor

Model	Compressor - Compressor			Set di progetto - Design data				Dati tecnici - Technical data				Accessories						RSD Category	Sound Power	Sound Pressure
	N°	Power kW	Type	Q -15/+5 °C	Power	T max	U _{ts}	A	B	H	Weight	Liquid receiver	S	Connections D	L					
SYNHERMETIC RECPs																				
UMA 150 BT	1	15	SE	13,3	10,9	31,0	132,0	2.200	1.100	1.380	420	15	42	28	16	II	31,0	53,0		
UMA 200 BT	1	20	SE	15,5	12,5	32,0	158,0	2.200	1.100	1.380	430	25	42	28	16	II	36,5	58,5		
UMA 250 BT	1	25	SE	19,9	16,2	45,0	193,0	2.200	1.100	1.380	480	25	54	35	16	II	30,5	62,5		
UMA 300 BT	1	30	SE	22,5	18,3	53,0	226,0	2.200	1.100	1.380	450	25	54	35	22	II	30,5	62,5		
UMA 400 BT	1	40	SE	26,2	21,4	78,0	223,0	2.200	1.100	1.380	510	25	54	42	22	II	31,5	63,5		
SYNHERMETIC TWO STAGE																				
UMA 2x100 BTSR	2	10	HS	15,0	14,4	44,6	149,3	2.200	1.100	1.380	450	15	35	16	12	II	33,0	55,0		
UMA 2x130 BTSR	2	13	HS	18,9	17,0	50,2	192,1	2.200	1.100	1.380	480	15	35	16	12	II	33,0	55,0		
UMA 2x150 BTSR	2	15	HS	21,5	20,6	61,2	212,6	2.200	1.100	1.380	510	15	42	22	16	II	33,0	55,0		
UMA 2x150 BT	2	15	SE	20,6	21,7	62,0	163,0	2.110	1.100	1.980	770	15	42	28	16	II	34,0	56,0		
UMA 2x200 BT	2	20	SE	31,0	25,1	74,0	195,0	2.110	1.100	1.980	800	25	42	28	16	II	39,5	61,5		
UMA 2x250 BT	2	25	SE	39,8	32,3	90,0	238,0	2.110	1.300	1.980	920	25	54	35	16	II	33,5	65,5		
UMA 2x300 BT	2	30	SE	45,0	36,5	106,0	273,0	2.110	1.300	1.980	930	25	54	35	22	II	33,5	65,5		
UMA 2x400 BT	2	40	SE	52,4	42,8	156,0	401,0	2.110	1.300	1.980	970	25	54	42	22	II	34,5	66,5		

UMA-BSBT

R404A-R507

range evap. T° -30/-40 °C

indoor

SYNHERMETIC TWO STAGE													-15/+5 °C											
UMA 150 BSBT	1	15	BS	10,9	14,0	31,0	132,0	2.200	1.100	1.380	400	15	42	28	16	II	30,0	52,0						
UMA 200 BSBT	1	20	BS	21,0	16,2	32,0	158,0	2.200	1.100	1.380	480	25	42	28	16	II	32,0	54,0						
UMA 250 BSBT	1	25	BS	24,9	18,6	45,0	193,0	2.200	1.100	1.380	500	25	54	35	22	II	33,5	55,5						
UMA 300 BSBT	1	30	BS	29,5	22,2	53,0	226,0	2.300	1.100	1.380	510	25	54	35	22	II	33,0	55,0						
SYNHERMETIC TWO STAGE																								
UMA 2x150 BSBT	2	15	BS	37,8	28,0	62,0	163,0	2.110	1.100	1.980	880	15	42	28	16	II	33,0	55,0						
UMA 2x200 BSBT	2	20	BS	43,6	32,4	74,0	195,0	2.110	1.100	1.980	900	25	42	28	16	II	35,0	57,0						
UMA 2x250 BSBT	2	25	BS	49,8	37,2	90,0	238,0	2.110	1.300	1.980	960	25	54	35	22	II	36,5	58,5						
UMA 2x300 BSBT	2	30	BS	59,0	44,4	106,0	273,0	2.110	1.300	1.980	970	25	54	35	22	II	36,0	58,0						

UMA-BSBTT

R404A-R507

range evap. T° -35/-45 °C

indoor

Model	Compressor - Compressor			Set di progetto - Design data				Dati tecnici - Technical data				Accessories						
	N°	Power kW	Type	Q	Power	T max	U _{ts}	A	B	H	Weight	Liquid receiver	S	Connections		PEI Category	Sound Power	Sound Pressure
				-15/+5 °C										D	L			
SYNHERMETIC TWO STAGE																		
UMA 150 BSBTT	1	15	BS	14,6	12,0	31,0	132,0	2.200	1.100	1.380	520	15	42	28	16	II	30,0	52,0
UMA 200 BSBTT	1	20	BS	16,8	13,0	32,0	158,0	2.200	1.100	1.380	540	25	42	28	16	II	32,0	54,0
UMA 250 BSBTT	1	25	BS	19,2	16,0	45,0	193,0	2.200	1.100	1.380	520	25	54	35	16	II	33,5	55,5
UMA 300 BSBTT	1	30	BS	22,6	19,1	53,0	226,0	2.200	1.100	1.380	580	25	54	35	16	II	33,0	55,0
SYNHERMETIC TWO STAGE																		
UMA 2x150 BSBTT	2	15	BS	29,1	24,0	62,0	163,0	2.110	1.100	1.980	900	15	42	28	16	II	33,0	55,0
UMA 2x200 BSBTT	2	20	BS	33,7	27,8	74,0	195,0	2.110	1.100	1.980	940	25	42	28	16	II	35,0	57,0
UMA 2x250 BSBTT	2	25	BS	38,5	32,0	90,0	238,0	2.110	1.300	1.980	950	25	54	35	16	II	36,5	58,5
UMA 2x300 BSBTT	2	30	BS	45,6	38,2	106,0	273,0	2.110	1.300	1.980	1.000	25	54	35	16	II	36,0	58,0

UMA-VSBT								R404A-R507				range evap. T° -25/-35 °C				indoor		
SYMMETRIC SCREW				-20/+2 °C														
UMA 600 VSBT	1	60	VS	67,2	58,5		440,0	2.110	1.100	1.980	900	50	64	35	22	III	82,5	94,5
UMA 700 VSBT	1	70	VS	77,2	62,4	124,0	485,0	2.110	1.100	1.980	920	50	70	35	22	III	83,0	95,0
UMA 750 VSBT	1	75	VS	81,0	67,5	144,0	585,0	2.110	1.100	1.980	950	50	76	42	28	III	83,5	95,5