

Table Of Content

GETTING STARTED	2
AUTHENTICATION	3
CUSTOMERS	4
PUSH ORDER	5
ORDER STATUS	7
COMMON RESPONSES	8

Getting Started

Description

Approved users of the Beecomm Content API can consume resources relevant to their registered customers.

Environment

The Beecomm API base URL is: <https://biapp.beecomm.co.il:8094>

Authentication

Description

In order to start communication with our API you'll first need to authenticate with us, you'll need to acquire an access_token using client_id and client_secret.

Get Authorized

POST**/v2/oauth/token**

Request Body

```
{
  "client_id": "client_id_provided_by_Beecom",
  "client_secret": "client_secret_provided_by_Beecom"
}
```

body format: **x-www-form-urlencoded**

Response

STATUS	BODY
/200	<pre>{ "result": true, "message": "authenticated successfully", "access_token": _token_ }</pre>

Customers

Description

Returns a list of authorized customers with their beecomm_id, you should use the customerId you obtained from this end-point for any customerId reference in this document.

Get Customers

GET**/api/v2/services/orderCenter/customers**

Headers

KEY	VALUE
access_token	_token_

Response

STATUS	BODY
/200	<pre>{ "result": bool, "customers": [{ "customerId": int, "customerName": "string", "branches": [{ "branchId": int, "branchName": "string", "pos": [{ "posId": int }] }] }] }</pre>

Push Order

Description

This end-point will handle orders and will route them to the relevant pos.

pushOrder

POST**/api/v2/services/orderCenter/pushOrder**

Headers

KEY	VALUE
Content-Type	application/json
access_token	_token_

Request Body

```
{
  "branchId": "string",
  "orderInfo": {
    "orderType": int,
    "firstName": "string",
    "lastName": "string",
    "phone": "string",
    "remarks": "string",
    "discountSum": "string",
    "outerCompId": int,
    "outerCompOrderId": "string",
    "items": [{
      "netId": int,
      "itemName": "string",
      "quantity": int,
      "price": decimal,
      "unitPrice": decimal,
      "remarks": "string",
      "belongTo": "string",
      "billRemarks": "string",
      "subItems": [],
      "toppings": []
    }],
  },
}
```

(continue on the next page)

Request Body(Cont.)

```
"payments": [{
    "paymentType": int,
    "paymentSum": decimal,
    "paymentName": "string",
    "creditCard": "string",
    "creditCardTokef": "string",
    "creditCardCvv": "string",
    "creditCardHolderID": "string",
    "paymentRemark": "string"
}],
"deliveryInfo": {
    "deliveryCost": decimal,
    "deliveryRemarks": "string",
    "city": "string",
    "street": "string",
    "homeNum": "string",
    "apartment": "string",
    "floor": "string",
    "companyName": "string"
},
"dinners": int,
"arrivalTime": "string",
"email": "string"
}
```

Response

STATUS	BODY
/200	{ "result": true, "message": "order accepted", "orderCenterId": objectId }

Order Status

Description

Returns a final confirmation together with the pos_order_id.

Order Status

POST

/api/v2/services/orderCenter/getOrderStatus

Headers

KEY	VALUE
Content-Type	application/json
access_token	_token_

Request Body

```
{
  "orderCenterId": "Id from pushOrder end-point",
}
```

Response

STATUS	BODY
/200	<pre>{ "result": bool, "posOrderId":int }</pre>

Common Responses

STATUS	BODY
/401	<pre>{ "result": false, "message": "Unauthorized" }</pre>
/401	<pre>{ "result": false, "message": "Authentication failed" }</pre>
/401	<pre>{ "result": false, "message": "token expired, please refresh your token" }</pre>
/401	<pre>{ "result": false, "message": "Invalid User or user deactivated. contact the api administrator" }</pre>
/400	<pre>{ "result": false, "message": "bad request" }</pre>
/400	<pre>{ "result": false, "message": "there is no customer with Id: customer_id" }</pre>
/400	<pre>{ "result": false, "message": "all fields are required and date format should be YYYY-MM-DD" }</pre>

STATUS	BODY
/200	<pre>{ "result": true, "message": "no results" }</pre>