

AI Email Agent Setup and Sharing Guide

Recipient installation and account connection instructions

This guide explains how to share the AI Email Agent safely, install it on another Windows computer, connect the recipient's Microsoft Outlook mailbox, and begin daily use. The recipient must approve Microsoft access to their own mailbox once; the app cannot bypass this consent.

What the recipient needs

Item	Requirement
Computer	Windows 10 or Windows 11 with internet access
Python	Python 3.11 or newer installed from python.org with Add Python to PATH selected
AI service	An API key for one supported provider such as Google Gemini, OpenAI, or Anthropic
Email account	A Microsoft Outlook or Microsoft 365 mailbox
Permission	Ability to approve mailbox access; work accounts may require an administrator

Create a safe sharing package

On the original computer, double-click `Create_Sharing_Package`. The app creates `AI-Email-Agent-Share.zip` in the project folder.

The package excludes private API keys, Microsoft authorization tokens, processed email data, the virtual environment, and runtime files. Do not copy the original project folder directly because it may contain private account material.

Install and open the app

1. **Extract the ZIP** Move the ZIP to the recipient's computer and extract it to a normal folder such as Documents. Do not run the app from inside the ZIP.

2. **Open the dashboard** Double-click Open_Dashboard. On the first run, the setup window creates the Python environment and installs required packages. Later launches open silently and go directly to the dashboard.
3. **Allow local startup** If Windows asks about an unknown downloaded file, verify that the ZIP came directly from the person sharing the project. The dashboard itself listens only on this computer at 127.0.0.1 and does not require public firewall access.
4. **Keep the agent running** Closing the browser tab does not stop the agent. Reopen it by double-clicking Open_Dashboard again. Use Stop Agent inside the dashboard when you want the background process to end.

Configure the AI provider

5. **Open Agent Settings** Select the AI and Writing tab.
6. **Choose a provider** Select Google Gemini, OpenAI, or Anthropic as the AI engine.
7. **Paste the API key** Paste the matching provider key and save Settings. The key is stored only in the local .env file and is not displayed again.

Use a separate API key for each recipient when possible. This makes usage easier to audit and lets one person's key be revoked without affecting everyone else.

Connect Microsoft Outlook

Microsoft requires a public desktop application registration. The application client ID is not a password, so the project owner may provide a suitable multi-tenant client ID to recipients. Each recipient still signs in and consents for their own mailbox.

8. **Create or reuse an app registration** In Microsoft Entra, register an application that supports personal Microsoft accounts and organizational accounts as appropriate.
9. **Enable desktop authentication** Under Authentication, add the Mobile and desktop applications platform with `http://localhost` as the redirect URI and allow public client flows.
10. **Add delegated permissions** Add Microsoft Graph delegated permissions Mail.ReadWrite and Mail.Send. Some organizations require an administrator to approve these permissions.
11. **Save the app details** In Agent Settings, select Accounts. Enter the Application client ID. Use common as the tenant unless the organization supplies a specific tenant ID, then select Save Microsoft details.
12. **Connect Microsoft** Select Connect Microsoft and complete the Microsoft sign-in and consent page. The authorization cache remains only on that computer.

Permissions and privacy

Permission	Why it is used
Read mail	Find unread messages that may need a reply and preserve conversation context
Create and modify drafts	Create proposed replies and update or remove provider drafts
Send mail	Send only after the configured approval rules allow it
Local token storage	Keep the recipient signed in without storing the mailbox password

Daily use

13. **Start** Double-click Open_Dashboard. It starts the agent if needed and opens the dashboard.
14. **Review** Open a proposed reply, check the recipient, facts, attachments, and commitments, then edit, send, discard, or delete it.
15. **Close the browser safely** Closing the tab leaves the agent running. Double-click Open_Dashboard whenever you want the page again.
16. **Stop** Select Stop Agent in the dashboard when you want monitoring and the local server to end.

Troubleshooting

Dashboard does not open. Wait for first-run package installation to finish, then double-click Open_Dashboard again.

Microsoft Connect is disabled. Save a valid Application client ID in Accounts first.

Microsoft needs admin approval. Ask the organization's Microsoft 365 administrator to approve Mail.ReadWrite and Mail.Send, or use an account whose policy permits user consent.

A connection expires. Return to Agent Settings, open Accounts, and select the provider's Connect button again.

Files that must remain private

- .env because it contains AI provider keys and Microsoft configuration
- outlook token_cache.json because it contains Microsoft authorization data
- the data folder because it may contain email content and processing history