

AI Email Agent Setup and Sharing Guide

Recipient installation and account connection instructions

This guide explains how to share the AI Email Agent safely, install it on another Windows computer, connect the recipient's own Gmail or Microsoft mailbox, and begin daily use. The recipient must approve access to their own mailbox once. Google and Microsoft require this consent and the app cannot bypass it.

What the recipient needs

Item	Requirement
Computer	Windows 10 or Windows 11 with internet access
Python	Python 3.11 or newer installed from python.org with Add Python to PATH selected
AI service	An API key for one supported provider such as Google Gemini, OpenAI, or Anthropic
Email account	A Gmail account, Microsoft Outlook account, or both
Permission	Ability to approve mailbox access; work accounts may require an administrator

Create a safe sharing package

On the original computer, double-click Create_Sharing_Package. The app creates AI-Email-Agent-Share.zip in the project folder.

The package excludes private API keys, Google and Microsoft authorization tokens, OAuth credentials, processed email data, the virtual environment, and runtime files. Do not copy the original project folder directly because it may contain private account material.

Install and open the app

1. **Extract the ZIP** Move the ZIP to the recipient's computer and extract it to a normal folder such as Documents. Do not run the app from inside the ZIP.

2. **Open the dashboard** Double-click Open_Dashboard. On the first run, the setup window creates the Python environment and installs required packages. Later launches open silently and go directly to the dashboard.
3. **Allow local startup** If Windows asks about an unknown downloaded file, verify that the ZIP came directly from the person sharing the project. The dashboard itself listens only on this computer at 127.0.0.1 and does not require public firewall access.
4. **Keep the agent running** Closing the browser tab does not stop the agent. Reopen it by double-clicking Open_Dashboard again. Use Stop Agent inside the dashboard when you want the background process to end.

Configure the AI provider

5. **Open Agent Settings** Select the AI and Writing tab.
6. **Choose a provider** Select Google Gemini, OpenAI, or Anthropic as the AI engine.
7. **Paste the API key** Paste the matching provider key and save Settings. The key is stored only in the local .env file and is not displayed again.

Use a separate API key for each recipient when possible. This makes usage easier to audit and lets one person's key be revoked without affecting everyone else.

Connect Gmail

Gmail requires a Google Cloud Desktop OAuth client plus one consent step for each mailbox owner. The app now handles the local file placement and launches sign-in from Settings.

8. **Prepare Google Cloud** Open Google Cloud Console, create or select a project, enable the Gmail API, and configure the OAuth consent screen.
9. **Add test users when needed** If the OAuth app is in Testing, add every recipient's Gmail address under Test users. For wider distribution, use Google's production and verification process.
10. **Create desktop credentials** Under APIs and Services, create an OAuth client ID with application type Desktop app, then download the JSON file.
11. **Upload the JSON** In the AI Email Agent dashboard, open Agent Settings, select Accounts, and choose Upload credentials JSON under Gmail.
12. **Connect Gmail** Select Connect Gmail. Google opens in the browser. The recipient chooses their account and approves the listed Gmail permissions. The resulting token is stored only on that computer.

If Google displays an unverified app message, confirm that the recipient was added as a test user and that the project and downloaded credentials came from the trusted project owner. Do not bypass browser security warnings.

Connect Microsoft Outlook

Microsoft requires a public desktop application registration. The application client ID is not a password, so the project owner may provide a suitable multi-tenant client ID to recipients. Each recipient still signs in and consents for their own mailbox.

13. **Create or reuse an app registration** In Microsoft Entra, register an application that supports personal Microsoft accounts and organizational accounts as appropriate.
14. **Enable desktop authentication** Under Authentication, add the Mobile and desktop applications platform with `http://localhost` as the redirect URI and allow public client flows.
15. **Add delegated permissions** Add Microsoft Graph delegated permissions Mail.ReadWrite and Mail.Send. Some organizations require an administrator to approve these permissions.
16. **Save the app details** In Agent Settings, select Accounts. Enter the Application client ID. Use common as the tenant unless the organization supplies a specific tenant ID, then select Save Microsoft details.
17. **Connect Microsoft** Select Connect Microsoft and complete the Microsoft sign-in and consent page. The authorization cache remains only on that computer.

Permissions and privacy

Permission	Why it is used
Read mail	Find unread messages that may need a reply and preserve conversation context
Create and modify drafts	Create proposed replies and update or remove provider drafts
Send mail	Send only after the configured approval rules allow it
Local token storage	Keep the recipient signed in without storing the mailbox password

Daily use

18. **Start** Double-click Open_Dashboard. It starts the agent if needed and opens the dashboard.
19. **Review** Open a proposed reply, check the recipient, facts, attachments, and commitments, then edit, send, discard, or delete it.
20. **Close the browser safely** Closing the tab leaves the agent running. Double-click Open_Dashboard whenever you want the page again.
21. **Stop** Select Stop Agent in the dashboard when you want monitoring and the local server to end.

Troubleshooting

Dashboard does not open. Wait for first-run package installation to finish, then double-click Open_Dashboard again.

Gmail Connect is disabled. Upload a valid Google Desktop OAuth credentials JSON first.

Google denies access. Confirm Gmail API is enabled and the account is listed as a test user when the app is in Testing.

Microsoft Connect is disabled. Save a valid Application client ID in Accounts first.

Microsoft needs admin approval. Ask the organization's Microsoft 365 administrator to approve Mail.ReadWrite and Mail.Send, or use an account whose policy permits user consent.

A connection expires. Return to Agent Settings, open Accounts, and select the provider's Connect button again.

Files that must remain private

- .env because it contains AI provider keys and Microsoft configuration
- gmail_credentials.json because it contains the Google OAuth client secret
- gmail_token.pickle because it grants access to the connected Gmail account
- outlook_token_cache.json because it contains Microsoft authorization data
- the data folder because it may contain email content and processing history

Always use `Create_Sharing_Package` when preparing a copy for someone else. The generated ZIP excludes these files automatically.