
# **SQUID Tuning Algorithm Output**

### Target Data


Full target name	IceCrate(014).IceBoard(6).Mezz(2).SQCB.SQUID Module(2).SQUID
HWM Name	PB2 HWM
HWM Path	/home/polarbear/hardware_maps/polarbear/PB2b/c ommissioning/202305_crate_test/crate_hwm_2023 10_shift_disable_bad_sq.yaml

## Plots


# VPhi Plots for a range of current biases IceCrate(014).IceBoard(6).Mezz(2).SQCB.SQUIDModule(2).SQUID



Current Bias Optimization (Voltage Offset Peak-to-Peak vs Current Bias Voltage) IceCrate(014).IceBoard(6).Mezz(2).SQCB.SQUIDModule(2).SQUID



# Flux Bias Optimization (For a single V-Phi curve at chosen current bias) IceCrate(014).IceBoard(6).Mezz(2).SQCB.SQUIDModule(2).SQUID Transimpedance: 756.541780 Ohms



### Additional Data

Measured Transimpedance	756.54 Ohms
Chosen Flux Bias	0.27 Volts
Chosen Current Bias	0.92 Volts
Peak to Peak at Chosen Current Bias	0.39 Volts
Reference Current Bias Used	Unavailable

#### NOTE:

The Flux Bias and Current Bias are given as Voltages at the output of the Flux Bias and Current Bias DACs