

Specifications

Print Method.	Serial impact dot matrix
Print Rate.	160 CPS
Print Direction.	Bidirectional in text mode; unidirectional in bit image mode, superscript/subscript, or when programmed
Number of Pins in Head. .	
Matrix	9x9 to 18x18 (See "Print Modes") or 11x9 user definable.

PRINTING CHARACTERISTICS

Character Set	Full 96-character ASCII with descenders; 8 international character sets; 256 programmable, downloadable characters
Bit Image Graphics	60 DPI 72 DPI (1:1 ratio) 80 DPI 90 DPI 120 DPI
Printing Modes.....	Standard, 9x9 matrix Double, 9x18 matrix (advance paper 1/216th and repeat line); Emphasized 18x9 matrix (shift right and double strike); Double Emphasized, 18x18 matrix (combination of above)
Number of Characters per line (FX-80)	Selectable via DIP switch (80 or 132) and programmable
(FX-100)	Selectable via DIP switch (136 or 233), and programmable

PRINTING SIZES	Characters Per Inch	Max. Characters Per Line
FX-80 Normal	10	80
Normal Expanded	5	40
Compressed	17.16	132
Compressed Expanded	8.58	66
Elite Enlarged	12	96
Elite Enlarged	6	48
FX-100 Normal	10	136
Normal Expanded	5	68
Compressed	17.16	233
Compressed Expanded	8.58	116
Elite Enlarged	12	163
Elite Enlarged	6	81

FORMS HANDLING

Line Feed	Programmable length 1 to 255/216ths
Form Feed	Programmable to 127 lines or 22"
Horizontal Tab	To 32 programmable positions
Skip Over Perf	Programmable length and interval
Vertical Tab	To 16 positions
Programmable Vertical Format Unit	Allows vertical tab on multiple forms
Reverse line feed	FX-80 only

INTERFACES

Standard	Centronics-style 8-bit Parallel
Optional	RS232, IEEE488
Buffer Size.	2K standard

MEDIA HANDLING

Paper Feed	FX-80, pinfeed platen 9.5" to 10"; adjustable snap-off tractor, optional FX-100, friction/tractor feed
Paper Width Range	FX-80, with optional tractor: 9.5" to 10", fanfold, 4" to 9". With standard pin/friction platen: 7.25" to 8.5" single sheet; 8.5" roll. FX-100, with tractor feed: 4" to 16" With friction feed: 7.25" to 8.5".

Number of Parts to Form	1 original plus 2 copies, 0.3mm (.013") max.
--------------------------------------	---

Paper Path	Rear
----------------------	------

SWITCHES/LIGHTS/DETECTORS

Indicators	Power Light; Printer Ready; Paper Out; On Line
Switches	Power On/Off; On Line; Form Feed; Line Feed
Detectors	Internal buzzer (bell); Paper Out Detection; Error Condition

RELIABILITY

Print Head Life Expectancy	100 x 10 ⁶ characters
MCBF (Excluding Print Head)	5 million lines

INKED RIBBON

Color	Black
Type	Cartridge
Life Expectancy.	3 million characters

ENVIRONMENTAL CONDITIONS

Operating Temperature

Range	41 °F to 95°F
-----------------	---------------

Operating Humidity	10 to 80% non-condensing
------------------------------	--------------------------

POWER REQUIREMENT

Voltage	AC 120 V ± 10%
Frequency	49.5 to 60.5 Hz
Current	1 amp
Power Consumption	70 VA maximum

SELF TEST MODE

Depressing Line Feed Switch while turning power ON
engages self-test which prints all characters in ROM.

PHYSICAL CHARACTERISTICS

	Height	Width	Depth	Weight
FX-80	100mm	420mm	347mm	7.5 kg
FX-100	150mm	615mm	354mm	10.5 kg