TEL200 - Introduction to Robotics

Group 5

Yumi Lab Project

Authors

Andreas Brustad
Johannes Standal
Håkon Bekken

Norwegian University of Life Sciences

Contents

1 Abstract **2**

2 Introduction **3**

3 Method **4**

3.1 RS BASIC 4

3.2 YuMi Application 4

3.3 YuMi Tic-Tac-Toe Challenge 6

4 Results **7**

5 Discussion **8**

6 Conclusions **9**

7 Bibliography **10**

1 Abstract

2 Introduction

3 Method

3.1 RS BASIC

3.2 YuMi Application

The control software for the dual-arm YuMi robot (IRB 14000) was developed in ABB's RAPID programming language using RobotStudio. The application implements a modular pick-and-place task that handles three distinct geometric objects — cube, cylinder, and triangular prism — triggered by external digital input signals. A central safety and recovery mechanism is provided through interrupt-driven emergency stop handling.

The program is contained in `MODULE Module1`. It defines a large number of `CONST robtarget` constants that store the taught positions for each object. These include safe approach points, gripping poses, lifting positions, transport poses, and drop-off locations. Each target is associated with the appropriate work object (`wobj`) — `Kube`, `sylinder`, `prisme` for pick-up phases, and typically `wobj0` for home and global movements. The positions were taught using the FlexPendant or RobotStudio's interface and include complete pose data (Cartesian position, orientation quaternion, robot configuration, and external axes values).

The main entry point is the `Main()` procedure, which first initializes the gripper system by calling `g_Init`. To avoid the common runtime error `ERR_ALRDYCNT` caused by connecting the same interrupt multiple times, an initialization guard is used:

```
IF NOT interrupts_setup THEN
    SkipWarn;
    CONNECT stop_emer WITH EmergencyStop;
    ISignalDI di_EmergencySituation, high, stop_emer;
    interrupts_setup := TRUE;
ENDIF
```

The program then enters an infinite loop that continuously polls three digital input signals (`di_cube`, `di_cylinder`, `di_prism`) and calls the corresponding handling procedure when a signal is high:

```
WHILE TRUE DO
    IF di_cube = 1 THEN Cube;
    ENDIF
    IF di_cylinder = 1 THEN syl;
    ENDIF
    IF di_prism = 1 THEN prism;
    ENDIF
ENDWHILE
```

Each object-specific procedure (`Cube`, `syl`, `prism`) follows a similar pick-and-place sequence:

1. Move to home position
2. Approach the pick-up area
3. Open gripper (`g_GripOut`) and wait
4. Descend to gripping pose

5. Close gripper (`g_GripIn`) and wait
6. Lift back to approach height
7. Transport to drop area
8. Descend to release pose
9. Open gripper and wait
10. Lift slightly
11. Return to home position

Most motions use `MoveJ` with speed `v500` and accuracy `fine` at critical points or `z100` during faster transfers. Wait times of 2 seconds after gripper commands ensure reliable mechanical action.

The emergency stop is implemented as a trap routine triggered on the rising edge of `di_EmergencySituation`:

```
TRAP EmergencyStop
    SkipWarn;
    StopMove;
    WaitUntil di_EmergencySituation = 0;
    StorePath;
    IF DInput(di_home) = 1 THEN
        ClearPath;
        MoveJ home, v500, fine, Servo\WObj:=wobj0;
        WaitTime 1;
        ExitCycle;
    ELSE
        RestoPath;
        StartMove;
    ENDIF
ENDTRAP
```

When the emergency input becomes active, motion stops immediately (`StopMove`). After the signal is released, the program checks `di_home`. If high, it clears the path context, moves to the safe `home` position, and executes `ExitCycle` to restart from the beginning of `Main()`. Otherwise it restores and resumes the interrupted path. This mechanism provides both immediate safety response and flexible recovery.

3.3 YuMi Tic-Tac-Toe Challenge

A tic-tac-toe demonstration was developed for the dual-arm YuMi robot to play against a human opponent. The robot exclusively draws "X" symbols, while the human manually places "O" symbols on a physical 3×3 grid. The human communicates their move to the robot using external digital inputs.



Figure 1: yumi Challenge setup

The robot uses two digital inputs to select the grid cell: - `di_x` increments the X coordinate - `di_y` increments the Y coordinate - `di_exe` triggers execution of the selected cell

A custom CAD model was designed and 3D-printed for both the pen (marker) and the pen holder to ensure reliable and repeatable tool pickup and placement.

The nine grid cells are divided between the two arms according to the following mapping (first digit = X coordinate, second digit = Y coordinate):

Table 1: Grid cell assignment to robot arms

	X=0	**X=1**	**X=2**
Y=0	Right: P00	Right: P10	Left: P20
Y=1	Right: P01	Right: P11	Left: P21
Y=2	Right: P02	Left: P12	Left: P22

Each path procedure follows a simple sequence:

- Move to home position
- Pick the pen from holder
- Move to cell-specific waypoints and draw the X
- Return pen to holder

- Return to home and resets X and

Motion commands use `MoveJ` at speed `v500`, with `fine` or small zones (`z50`–`z100`) for smooth and accurate drawing. Gripper commands are followed by `WaitTime 2` to ensure stable handling.

The same interrupt-based emergency stop system is implemented as in the pick-and-place application. For correct operation, the controller must be set to **continuous** run mode.

This project demonstrates YuMi's precision, tool handling capability, and safe interaction with humans in a fun, educational game application.

4 Results

5 Discussion

6 Conclusions

7 Bibliography